



FCC Test Report

Report No.: AGC01904140601FE02

FCC ID : 2ABYLSP4521
APPLICATION PURPOSE : Original Equipment
PRODUCT DESIGNATION : WCDMA mobile phone
BRAND NAME : WOO
MODEL NAME : SP4521
CLIENT : UWIN INNOVATION (HONGKONG) LIMITED
DATE OF ISSUE : June 19, 2014
STANDARD(S) : FCC Part 22H & 24E Rules
REPORT VERSION : V1.0

Attestation of **Global Compliance (Shenzhen) Co., Ltd.**



CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	June 19, 2014	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	6
2.1 PRODUCT DESCRIPTION	6
2.2 RELATED SUBMITTAL(S) / GRANT (S)	9
2.3 TEST METHODOLOGY	9
2.4 TEST FACILITY	9
2.5 MEASUREMENT INSTRUMENTS	9
2.6 SPECIAL ACCESSORIES	10
2.7 EQUIPMENT MODIFICATIONS	10
3. SYSTEM TEST CONFIGURATION	11
3.1 EUT CONFIGURATION	11
3.2 EUT EXERCISE	11
3.3 GENERAL TECHNICAL REQUIREMENTS	11
3.4 CONFIGURATION OF EUT SYSTEM	12
4. SUMMARY OF TEST RESULTS	13
5. DESCRIPTION OF TEST MODES	13
6. OUTPUT POWER	14
6.1 Conducted Output Power	14
6.2 RADIATED OUTPUT POWER	21
6.3. Peak-to-Average Ratio	24
7. SPURIOUS EMISSION	26
7.1 CONDUCTED SPURIOUS EMISSION	26
7.2 Radiated Spurious Emission	29
8. MAINS CONDUCTED EMISSION	33
8.1 MEASUREMENT METHOD	33
8.2 PROVISIONS APPLICABLE	33
8.3 MEASUREMENT RESULT	34
9. FREQUENCY STABILITY	36

9.1 MEASUREMENT METHOD.....	36
9.2 PROVISIONS APPLICABLE	36
9.3 MEASUREMENT RESULT (WORST)	37
10. OCCUPIED BANDWIDTH	40
10.1 MEASUREMENT METHOD	40
10.2 PROVISIONS APPLICABLE	40
10.3 MEASUREMENT RESULT	40
11. EMISSION BANDWIDTH.....	42
11.1 MEASUREMENT METHOD.....	42
11.2 PROVISIONS APPLICABLE	42
11.3 MEASUREMENT RESULT	42
12. BAND EDGE.....	44
12.1 MEASUREMENT METHOD	44
12.2 PROVISIONS APPLICABLE	44
12.3 MEASUREMENT RESULT	44
APPENDIX A.....	45
TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION.....	45
APPENDIX B.....	73
TEST PLOTS FOR OCCUPIED BANDWIDTH (99%).....	73
EMISSION BANDWIDTH (-26DBC).....	73
APPENDIX C.....	83
TEST PLOTS FOR BAND EDGES.....	83
APPENDIX D.....	90
PHOTOGRAPHS OF TEST SETUP.....	90
APPENDIX E	93
PHOTOGRAPHS OF EUT	93

1. VERIFICATION OF COMPLIANCE


Applicant	UWIN INNOVATION (HONGKONG) LIMITED
Address	Room 206, Block 30, Nantou Checking Point 2nd Road, Wisdomland Business Park, Nanshan District, Shenzhen, China
Manufacturer	Shenzhen Eternity Technology Limited
Address	Block A2, Yingzhan Industrial Park, Longtian Community, Kengzi Street, Pingshan District, Shenzhen, CHINA
Product Designation	WCDMA mobile phone
Brand Name	WOO
Test Model	SP4521
Date of test	June 09, 2014 to June 17, 2014
Deviation	None
Condition of Test Sample	Normal

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C 63.4:2003 and TIA/EIA 603. The sample tested as described in this report is in compliance with the FCC Rules Part 22H and 24E.

The test results of this report relate only to the tested sample identified in this report.

Tested By :



Bart Xie

June 19, 2014

Reviewed By :



Kidd Yang

June 19, 2014

Approved By:



Solger Zhang

June 19, 2014

2. GENERAL INFORMATION

2.1 PRODUCT DESCRIPTION

Details of technical specification refer to the description as following:

EUT 1–WCDMA mobile phone	
Hardware version:	YK828_MB_V1.0
Software version:	N/A
Frequency Bands:	<input checked="" type="checkbox"/> GSM 850 <input checked="" type="checkbox"/> PCS 1900 (U.S. Bands) <input checked="" type="checkbox"/> GSM 900 <input checked="" type="checkbox"/> DCS 1800 (Non-U.S. Bands) <input checked="" type="checkbox"/> UMTS FDD Band II <input checked="" type="checkbox"/> UMTS FDD Band V (U.S. Bands) <input type="checkbox"/> UMTS FDD Band I <input type="checkbox"/> UMTS FDD Band VIII (Non-U.S. Bands)
Antenna:	PIFA Antenna
Antenna gain:	-1.0dBi(GSM/WCDMA 850), -0.8dBi (GSM/WCDMA 1900)
Dual Card:	WCDMA / GSM Card Slot GSM Card Slot
GPRS Class	12
EUT 2–Adapter	
Brand Name	WOO
Test Model	D2-501000E
Manufacturer Name	Shenzhen Diasinger Digital Co., LTD.
Manufacturer Address	4F, Bldg, YuSheng Industrial Zone, Jiuwei Xixiang, Baoan District, shenzhen, China
Adapter Input:	AC100-240V ~ 50/60Hz
Adapter Output:	DC5V, 1000mAh

EUT 3–Li-ion Battery	
Brand Name	WOO
Test Model	SP4521
Manufacturer Name	Dongguan Guoxia Electronic Science And Technolgy Co., Ltd.
Manufacturer Address	F/3, D Building, Huashun Industrial Park, #20 Shenglian Road, Wulian Village, Fenggang, Dongguan
Power Supply:	DC 3.7V by Battery
Battery parameter:	DC3.7V/1300 mAh
Extreme Vol. Limits:	DC3.4 V to 4.2 V (Normal: DC3.7 V)
Extreme Temp. Tolerance	-10℃ to +55℃
<p>*** Note: The High Voltage DC4.2V and Low Voltage DC3.4V were declared by manufacturer, The EUT couldn't be operating normally with higher or lower voltage.</p> <p>Other functions have been performed according to verification procedure except for Bluetooth and MS function. Card 1 can't transmit with Card 2 simultaneously.</p>	

*** **Note:** The maximum power levels are GSM for MCS-4: GMSK link, EDGE for MCS-9:8PSK link, and RMC 12.2kbps mode for WCDMA band II, WCDMA band V, only these modes were used for all tests. We found out the test mode with the highest power level after we analyze all the data rates. So we chose worst case as a representative.

WCDMA Card Slot:

	Maximum ERP/EIRP (dBm)	Max. Conducted Power (dBm)	Max. Average Burst Power (dBm)
GSM 850	30.62	32.46	31.82
PCS 1900	27.67	29.58	28.89
UMTS BAND II	21.87	23.28	22.84
UMTS BAND V	21.36	23.64	23.15

GSM Card Slot:

	Maximum ERP/EIRP (dBm)	Max. Conducted Power (dBm)	Max. Average Burst Power (dBm)
GSM 850	30.24	32.18	31.45
PCS 1900	27.29	29.24	28.49

2.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2ABYLSP4521**, filing to comply with the FCC Part 22H&24E requirements.

2.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of ANSI C 63.4: 2003; TIA/EIA 603 and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

KDB 971168 D01 Power Meas License Digital Systems v02r01

2.4 TEST FACILITY

The test site used to collect the radiated data is located at:

Attestation of Global Compliance (Shenzhen) Co., Ltd.

2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China

FCC register No.: 259865

2.5 MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Calibration Date	Calibration Due.
SPECTRUM ANALYZER	AGILENT	E4440A	US41421290	July 17, 2013	July 16, 2014
TEST RECEIVER	R&S	ESCI	100694	July 17, 2013	July 16, 2014
COMMUNICATION TESTER	AGILENT	8960	122500087	Oct.21, 2013	Oct.20, 2014
COMMUNICATION TESTER	R&S	CMU200	122500166	Feb.27,2014	Feb.26,2015
SIGNAL GENERATOR	AGILENT	E4438C	MY44260051	Feb.23,2014	Feb. 22,2015
LISN	R&S	ESH3-Z5	8389791009	July 17, 2013	July 16, 2014
CLIMATE CHAMBER	ALBATROSS	--	--	July 17, 2013	July 16, 2014
Loop Antenna	A.H.	SAS-562B	SEL0097	July 17, 2013	July 16, 2014
Biological Antenna	A.H. Systems Inc.	SAS-521-4	26	June 6, 2014	June 5, 2015
Substitution Antenna	EMCO	3142C	---	June 6, 2014	June 5, 2015
Substitution Antenna	EM	EM-AH-10180	69	Apr.19, 2014	Apr.18, 2015
Horn Antenna	EM	EM-AH-10180	67	Apr.19, 2014	Apr.18, 2015
Horn Antenna	A.H. Systems Inc.	SAS-574	--	June 6, 2014	June 5, 2015

2.6 SPECIAL ACCESSORIES

The battery and the charger, earphone supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

2.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

3. SYSTEM TEST CONFIGURATION

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

3.3 GENERAL TECHNICAL REQUIREMENTS

Item Number	Item Description		FCC Rules
1	Output Power	Conducted output power	2.1046/22.913(a) (2) / 24.232 (c)
		Radiated output power	
2	Peak-to-Average Ratio	Peak-to-Average Ratio	24.232(d)
3	Spurious Emission	Conducted spurious emission	2.1051 / 22.917 / 24.238
		Radiated spurious emission	
4	Mains Conducted Emission		15.107 / 15.207
5	Frequency Stability		2.1055/22.355 /24.235
6	Occupied Bandwidth		2.1049 (h)(i)
7	Emission Bandwidth		22.917(a)/24.238(a)
8	Band Edge		22.917(a)/24.238(a)

3.4 CONFIGURATION OF EUT SYSTEM

Fig. 2-1 Configuration of EUT System




Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	ID or Specification	Note
1	WCDMA mobile phone	SP4521	FCC ID:2ABYLSP4521	EUT
2	Adapter	D2-501000E	DC5.0V / 1000mA	Accessory
3	Battery	SP4521	DC3.7V / 1300 mAh	Accessory
4	Earphone	SP4521	N/A	Accessory
5	USB Cable	SP4521	N/A	Accessory

***Note: All the accessories have been used during the test. The following “EUT” in setup diagram means EUT system.

4. SUMMARY OF TEST RESULTS

Item Number	Item Description		FCC Rules	Result
1	Output Power	Conducted Output Power	2.1046/22.913(a) (2) / 24.232 (c)	Pass
		Radiated Output Power		
2	Peak-to-Average Ratio	Peak-to-Average Ratio	24.232(d)	Pass
3	Spurious Emission	Conducted Spurious Emission	2.1051 / 22.917 / 24.238	Pass
		Radiated Spurious Emission		
4	Mains Conducted Emission		15.107 / 15.207	Pass
5	Frequency Stability		2.1055/22.355 /24.235	Pass
6	Occupied Bandwidth		2.1049 (h)(i)	Pass
7	Emission Bandwidth		22.917(a)/24.238(a)	Pass
8	Band Edge		22.917(a)/24.238(a)	Pass

5. DESCRIPTION OF TEST MODES

During the testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GSM and PCS frequency band.

*****Note:** GSM/GPRS/EGPRS 850, GSM/GPRS/EGPRS 1900, WCDMA/HSPA band II, WCDMA/HSPA band V, mode have been tested during the test.

The worst condition was recorded in the test report if no other modes test data.

6. OUTPUT POWER

6.1 Conducted Output Power

6.1.1 MEASUREMENT METHOD

The transmitter output port was connected to base station.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Measure the maximum burst average power and average power for other modulation signal.

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all modes (GSM/GPRS/EGPRS 850, GSM/GPRS/EGPRS1900, WCDMA/HSPA band II, WCDMA/HSPA band V) at 3 typical channels (the Top Channel, the Middle Channel and the Bottom Channel) for each band.

6.1.2 MEASUREMENT RESULT

Conducted Output Power Limits for GSM850/EDGE band		
Mode	Nominal Peak Power	Tolerance(dB)
GSM	33 dBm (2W)	- 2
EDGE	27 dBm(0.5W)	±2
Conducted Output Power Limits for PCS1900/EDGE band		
Mode	Nominal Peak Power	Tolerance(dB)
GSM	30 dBm (1W)	- 2
EDGE	26 dBm (0.4W)	±2
Conducted Output Power Limits for UMTS band II		
Mode	Nominal Peak Power	Tolerance(dB)
WCDMA	24 dBm (0.25W)	- 2
Conducted Output Power Limits for UMTS band V		
Mode	Nominal Peak Power	Tolerance(dB)
WCDMA	24 dBm (0.25W)	- 2

GSM 850:

Mode	Frequency (MHz)	Reference Power	Peak Power	Tolerance	Avg.Burst Power	Duty cycle Factor(dB)	Frame Power(dBm)
GSM850	824.2	33	32.46	-0.54	31.82	-9	22.82
	836.6	33	32.37	-0.63	31.75	-9	22.75
	848.8	33	32.32	-0.68	31.66	-9	22.66
GPRS850 (1 Slot)	824.2	33	32.33	-0.67	31.71	-9	22.71
	836.6	33	32.28	-0.72	31.59	-9	22.59
	848.8	33	32.26	-0.74	31.56	-9	22.56
GPRS850 (2 Slot)	824.2	30	29.56	-0.44	28.74	-6	22.74
	836.6	30	29.44	-0.56	28.65	-6	22.65
	848.8	30	29.39	-0.61	28.56	-6	22.56
GPRS850 (3 Slot)	824.2	28.23	27.52	-0.71	26.67	-4.26	22.41
	836.6	28.23	27.44	-0.79	26.61	-4.26	22.35
	848.8	28.23	27.37	-0.86	26.49	-4.26	22.23
GPRS850 (4 Slot)	824.2	27	26.36	-0.64	25.52	-3	22.52
	836.6	27	26.31	-0.69	25.47	-3	22.47
	848.8	27	26.24	-0.76	25.38	-3	22.38

Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Avg.Burst Power (dBm)
EDGE (1 Slot)	128	824.2	26.67	26.24
	189	836.6	26.61	26.15
	251	848.8	26.48	26.06
EDGE (2 Slot)	128	824.2	25.51	24.84
	189	836.6	25.42	24.74
	251	848.8	25.23	24.69
EDGE (3 Slot)	128	824.2	23.78	22.84
	189	836.6	23.64	22.75
	251	848.8	23.55	22.68
EDGE (4 Slot)	128	824.2	22.68	21.82
	189	836.6	22.55	21.68
	251	848.8	22.46	21.59

PCS 1900:

Mode	Frequency (MHz)	Reference Power	Peak Power	Tolerance	Avg.Burst Power	Duty cycle Factor(dB)	Frame Power(dBm)
GSM1900	1850.2	30	29.46	-0.54	28.82	-9	19.82
	1880	30	29.49	-0.51	28.86	-9	19.86
	1909.8	30	29.58	-0.44	28.89	-9	19.89
GPRS1900 (1 Slot)	1850.2	30	29.52	-0.48	28.73	-9	19.73
	1880	30	29.55	-0.45	28.79	-9	19.79
	1909.8	30	29.56	-0.36	28.81	-9	19.81
GPRS1900 (2 Slot)	1850.2	27	26.38	-0.62	25.61	-6	19.61
	1880	27	26.46	-0.54	25.64	-6	19.64
	1909.8	27	26.61	-0.39	25.69	-6	19.69
GPRS1900 (3 Slot)	1850.2	25.23	24.48	-0.75	24.13	-4.26	19.87
	1880	25.23	24.57	-0.66	24.17	-4.26	19.91
	1909.8	25.23	24.62	-0.61	24.22	-4.26	19.96
GPRS1900 (4 Slot)	1850.2	24	23.33	-0.67	22.52	-3	19.52
	1880	24	23.45	-0.55	22.67	-3	19.67
	1909.8	24	23.68	-0.32	22.78	-3	19.78

Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Avg.Burst Power (dBm)
EDGE (1 Slot)	512	1850.2	25.77	25.15
	661	1880	25.76	25.29
	810	1909.8	25.85	25.33
EDGE (2 Slot)	512	1850.2	24.43	23.72
	661	1880	24.52	23.77
	810	1909.8	24.54	23.84
EDGE (3 Slot)	512	1850.2	22.33	22.05
	661	1880	22.37	22.12
	810	1909.8	22.42	22.18
EDGE (4 Slot)	512	1850.2	21.28	20.62
	661	1880	21.47	20.74
	810	1909.8	21.56	20.78

UMTS BAND II

Mode	Frequency (MHz)	Reference power	Peak Power	Tolerance	Avg.Burst Power
WCDMA 1900 RMC	1852.4	24	23.14	-0.86	22.68
	1880	24	23.22	-0.78	22.75
	1907.6	24	23.28	-0.72	22.84
WCDMA 1900 AMR	1852.4	24	22.48	-1.52	22.14
	1880	24	22.56	-1.44	22.18
	1907.6	24	22.67	-1.33	22.26
HSDPA Subtest 1	1852.4	24	22.46	-1.54	22.21
	1880	24	22.53	-1.47	22.24
	1907.6	24	22.57	-1.43	22.33
HSDPA Subtest 2	1852.4	24	22.48	-1.52	22.25
	1880	24	22.52	-1.48	22.27
	1907.6	24	22.54	-1.46	22.36
HSDPA Subtest 3	1852.4	24	22.41	-1.59	22.19
	1880	24	22.55	-1.45	22.24
	1907.6	24	22.57	-1.43	22.34
HSDPA Subtest 4	1852.4	24	22.59	-1.41	22.35
	1880	24	22.67	-1.33	22.38
	1907.6	24	22.72	-1.28	22.42
HSUPA Subtest 1	1852.4	24	22.56	-1.44	22.26
	1880	24	22.63	-1.37	22.39
	1907.6	24	22.67	-1.33	22.42
HSUPA Subtest 2	1852.4	24	22.52	-1.48	22.25
	1880	24	22.56	-1.44	22.36
	1907.6	24	22.61	-1.39	22.37
HSUPA Subtest 3	1852.4	24	22.48	-1.52	22.24
	1880	24	22.54	-1.46	22.28
	1907.6	24	22.59	-1.41	22.34
HSUPA Subtest 4	1852.4	24	22.45	-1.55	22.26
	1880	24	22.53	-1.47	22.37
	1907.6	24	22.61	-1.39	22.39
HSUPA Subtest 5	1852.4	24	22.49	-1.51	22.25
	1880	24	22.55	-1.45	22.35
	1907.6	24	22.64	-1.36	22.38

UMTS BAND V

Mode	Frequency (MHz)	Reference power	Peak Power	Tolerance	Avg.Burst Power
WCDMA 850 RMC	826.4	24	23.64	-0.36	23.15
	836.6	24	23.55	-0.45	23.08
	846.6	24	23.47	-0.53	23.02
WCDMA 850 AMR	826.4	24	22.58	-1.42	22.24
	836.6	24	22.44	-1.56	22.18
	846.6	24	22.39	-1.61	22.12
HSDPA Subtest 1	826.4	24	22.63	-1.37	22.25
	836.6	24	22.57	-1.43	22.14
	846.6	24	22.46	-1.54	22.09
HSDPA Subtest 2	826.4	24	22.68	-1.32	22.27
	836.6	24	22.56	-1.44	22.23
	846.6	24	22.41	-1.59	22.18
HSDPA Subtest 3	826.4	24	22.67	-1.33	22.32
	836.6	24	22.46	-1.54	22.26
	846.6	24	22.42	-1.58	22.21
HSDPA Subtest 4	826.4	24	22.53	-1.47	22.27
	836.6	24	22.46	-1.54	22.18
	846.6	24	22.39	-1.61	22.12
HSUPA Subtest 1	826.4	24	22.48	-1.52	22.18
	836.6	24	22.37	-1.63	22.14
	846.6	24	22.34	-1.66	22.07
HSUPA Subtest 2	826.4	24	22.48	-1.52	22.15
	836.6	24	22.36	-1.64	22.09
	846.6	24	22.29	-1.71	22.05
HSUPA Subtest 3	826.4	24	22.48	-1.52	22.12
	836.6	24	22.35	-1.65	22.1
	846.6	24	22.28	-1.72	22.07
HSUPA Subtest 4	826.4	24	22.46	-1.54	22.24
	836.6	24	22.34	-1.66	22.18
	846.6	24	22.32	-1.68	22.16
HSUPA Subtest 5	826.4	24	22.58	-1.42	22.37
	836.6	24	22.46	-1.54	22.18
	846.6	24	22.34	-1.66	22.14

According to 3GPP 25.101 sub-clause 6.2.2 , the maximum output power is allowed to be reduced by following the table.

Table 6.1aA: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$\text{MAX}(CM-1,0)$
Note: $CM=1$ for $\beta_o/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensate for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

6.2 RADIATED OUTPUT POWER

6.2.1 MEASUREMENT METHOD

The measurements procedures specified in TIA-603C-2004 were applied.

- 1 In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (P_{in}) is applied to the input of the dipole, and the power received (P_r) at the chamber's probe antenna is recorded.
- 2 The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as $AR_{pl} = P_{in} + 2.15 - P_r$. The AR_{pl} is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss. The measurement results are obtained as described below: $Power = P_{Mea} + AR_{pl}$
- 3 The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
- 4 From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
- 5 The EUT is then put into continuously transmitting mode at its maximum power level.
- 6 Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.
- 7 This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (P_{in}).
- 8 ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15dBi$.

6.2.2 PROVISIONS APPLICABLE

This is the test for the maximum radiated power from the EUT. Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Mode	Nominal Peak Power
GSM 850/EDGE	≤ 38.45 dBm (7W)
PCS 1900/EDGE	≤ 33 dBm (2W)
UMTS BAND II	≤ 33 dBm (2W)
UMTS BANDV	≤ 38.45 dBm (7W)

6.2.3 MEASUREMENT RESULT

Radiated Power (ERP) for GSM 850/EDGE 8				
Mode	Frequency	Result		Conclusion
		Max. Peak ERP (dBm)	Polarization Of Max. ERP	
GSM850	824.2	30.62	Horizontal	Pass
	836.6	30.57	Horizontal	Pass
	848.8	30.46	Horizontal	Pass
	824.2	29.11	Vertical	Pass
	836.6	28.73	Vertical	Pass
	848.8	28.67	Vertical	Pass
EDGE	824.2	25.63	Horizontal	Pass
	836.6	25.55	Horizontal	Pass
	848.8	25.51	Horizontal	Pass
	824.2	25.68	Vertical	Pass
	836.6	25.56	Vertical	Pass
	848.8	25.47	Vertical	Pass

Radiated Power (E.I.R.P) for PCS 1900/EDGE 8				
Mode	Frequency	Result		Conclusion
		Max. Peak E.I.R.P.(dBm)	Polarization Of Max. E.I.R.P.	
GSM 1900	1850.2	27.48	Horizontal	Pass
	1880.0	27.51	Horizontal	Pass
	1909.8	27.67	Horizontal	Pass
	1850.2	26.55	Vertical	Pass
	1880.0	26.58	Vertical	Pass
	1909.8	26.63	Vertical	Pass
EDGE	1850.2	24.38	Horizontal	Pass
	1880.0	24.46	Horizontal	Pass
	1909.8	24.52	Horizontal	Pass
	1850.2	23.36	Vertical	Pass
	1880.0	23.47	Vertical	Pass
	1909.8	23.58	Vertical	Pass

Radiated Power (E.I.R.P) for UMTS band II				
Mode	Frequency	Result		
		Max. Peak E.I.R.P (dBm)	Polarization Of Max. E.I.R.P	
RMC 12.2kbps	1852.4	21.69	Horizontal	Pass
	1880	21.77	Horizontal	Pass
	1907.6	21.87	Horizontal	Pass
	1852.4	21.26	Vertical	Pass
	1880	21.13	Vertical	Pass
	1907.6	21.32	Vertical	Pass

Radiated Power (ERP) for UMTS band V				
Mode	Frequency	Result		Conclusion
		Max. Peak ERP (dBm)	Polarization Of Max. E.I.R.P	
RMC 12.2kbps	826.4	21.36	Horizontal	Pass
	836.6	21.27	Horizontal	Pass
	846.6	21.18	Horizontal	Pass
	826.4	21.16	Vertical	Pass
	836.6	20.84	Vertical	Pass
	846.6	21.08	Vertical	Pass

Note: Above is worst mode data.

6.3. Peak-to-Average Ratio

6.3.1 MEASUREMENT METHOD

Use one of the procedures presented in 4.1 to measure the total peak power and record as PPk. Use one of the applicable procedures presented 4.2 to measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = \text{PPk (dBm)} - \text{PAvg (dBm)}.$$

6.3.2 PROVISIONS APPLICABLE

This is the test for the Peak-to-Average Ratio from the EUT.

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

6.3.3 MEASUREMENT RESULT

Modes	GSM850(GSM)		
Channel	128	190	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.6	848.8
Peak-To-Average Ratio (dB)/GSM	0.64	0.62	0.66
Peak-To-Average Ratio (dB)/EDGE	0.43	0.46	0.42

Modes	PCS 1900 (GSM)		
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency (MHz)	1850.2	1880	1909.8
Peak-To-Average Ratio (dB)/GSM	0.64	0.63	0.67
Peak-To-Average Ratio (dB)/EDGE	0.62	0.47	0.52

Modes	UMTS BAND II		
Channel	9662	9800	9938
	(Low)	(Mid)	(High)
Frequency (MHz)	1852.4	1880	1907.6
Peak-To-Average Ratio (dB)	0.46	0.47	0.44

Modes	UMTS BAND V		
Channel	4357	4408	4458
	(Low)	(Mid)	(High)
Frequency (MHz)	826.4	836.6	846.6
Peak-To-Average Ratio (dB)	0.49	0.47	0.45

7. SPURIOUS EMISSION

7.1 CONDUCTED SPURIOUS EMISSION

7.1.1 MEASUREMENT METHOD

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1, Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM 850, data taken from 30 MHz to 9 GHz.

2, Determine EUT transmit frequencies: the following typical channels were chosen to conducted emissions testing.

Typical Channels for testing of GSM 850/EDGE 8	
Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

Typical Channels for testing of PCS 1900/EDGE 8	
Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

Typical Channels for testing of UMTS band II	
Channel	Frequency (MHz)
9662	1852.4
9800	1880
9938	1907.6

Typical Channels for testing of UMTS band V	
Channel	Frequency (MHz)
4357	826.4
4408	836.6
4458	846.6

7.1.2 PROVISIONS APPLICABLE

On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43+10\log(P)$ dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

7.1.3 MEASUREMENT RESULT

PLEASE REFER TO: APPENDIX I TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION

- Note:**
1. Below 30MHz no Spurious found and The GSM modes is the worst condition.
 2. As no emission found in standby or receive mode, no recording in this report.


7.2 Radiated Spurious Emission

7.2.1 MEASUREMENT METHOD


The measurements procedures specified in TIA-603C-2004 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GPRS/EGPRS 850, GPRS/EGPRS 1900, HSPA band II, HSPA band V) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for each band.

The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as,
$$RSE = R_x(\text{dBuV}) + CL(\text{dB}) + SA(\text{dB}) + \text{Gain}(\text{dBi}) - 107(\text{dBuV to dBm})$$
The SA is calibrated using following setup.



b) EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS 1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz), GSM850 band (824.2MHz, 836.6MHz, 848.8MHz), UMTS band II(1852.4MHz, 1880MHz, 1907.6MHz), UMTS band V(826.4MHz, 836.6MHz, 846.6MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of any band into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below: $Power = P_{Mea} + A_{Rpl}$

7.2.2 PROVISIONS APPLICABLE

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P , in Watts) by at least $43 + 10 \log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Note: only result the worst condition of each test mode:

7.2.3 MEASUREMENT RESULT

GSM 850:

The Worst Test Results for Channel 251/848.8 MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1685.23	-43.57	-5.01	-48.58	-13.00	Horizontal
2456.12	-46.46	-2.18	-48.64	-13.00	Vertical
3645.78	-48.33	3.46	-44.87	-13.00	Vertical
4536.58	-45.29	2.79	-42.50	-13.00	Horizontal

GSM 850(EDGE 8):

The Worst Test Results for Channel 251/848.8 MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1696.28	-47.52	-2.26	-49.78	-13.00	Horizontal
2162.19	-46.55	-3.12	-49.67	-13.00	Vertical
3645.78	-45.68	-1.74	-47.42	-13.00	Vertical
9257.65	-42.19	8.46	-33.73	-13.00	Horizontal

PCS 1900:

The Worst Test Results for Channel 881/1909.8MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1429.36	-46.51	-3.22	-49.73	-13.00	Vertical
2563.47	-47.32	-0.24	-47.56	-13.00	Vertical
3645.26	-47.72	3.98	-43.74	-13.00	Horizontal
4563.56	-46.45	11.56	-34.89	-13.00	Vertical
5689.25	-45.62	17.89	-27.73	-13.00	Horizontal

PCS 1900(EDGE 8):

The Worst Test Results for Channel 810/1909.8MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1430.15	-47.37	2.7	-44.67	-13.00	Vertical
9367.91	-48.44	11.6	-36.84	-13.00	Vertical
13356.68	-49.28	14.89	-34.39	-13.00	Horizontal
15249.71	-47.39	13.87	-33.52	-13.00	Vertical
17913.63	-44.64	19.76	-24.88	-13.00	Horizontal

UMTS band II:

The Worst Test Results for Channel 9888/1977.6MHz					
Frequency(MHz)	Power(dBm)	AR _{pl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
2000.00	-38.94	-2.25	-41.19	-13.00	Vertical
9548.50	-41.38	-3.03	-44.41	-13.00	Horizontal
13367.40	-44.26	-1.87	-46.13	-13.00	Horizontal
15277.80	-39.71	8.52	-31.19	-13.00	Vertical
17931.60	-55.52	18.7	-36.82	-13.00	Horizontal

UMTS band V:

The Worst Test Results for Channel 4458/846.6MHz					
Frequency(MHz)	Power(dBm)	AR _{pl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
1598.26	-39.52	-2.26	-41.78	-13.00	Vertical
2365.78	-38.64	-3.12	-41.76	-13.00	Horizontal
4967.65	-41.58	-1.74	-43.32	-13.00	Horizontal
6457.86	-38.73	8.74	-29.99	-13.00	Vertical
7896.56	-41.28	17.89	-23.39	-13.00	Horizontal

Note: AR_{pl}= Factor=Antenna Factor+ Cable loss-Amplifier gain.

The “Factor” value can be calculated automatically by software of measurement system.

Below 30MHZ no Spurious found and The GSM modes is the worst condition.

8. MAINS CONDUCTED EMISSION

8.1 MEASUREMENT METHOD

The measurement procedure specified in ANSI C63.4-2003 was used for testing. Conducted Emission was measured with travel charger.


8.2 PROVISIONS APPLICABLE

Frequency of Emission (MHz)	Conducted Limit(dBuV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50
*Decreases with the logarithm of the frequency.		
*The lower limit shall apply at the transition frequency.		

Note: The GSM850 mode is the worst condition and the test result as following:

8.3 MEASUREMENT RESULT

LINE CONDUCTED EMISSION - L




Site: Conduction
Limit: FCC Class B Conduction(QP)
EUT: WCDMA mobile phone
M/N: SP4521
Mode: Call
Note:

Phase: **L1**
Power: AC 120V/60Hz
Temperature: 26
Humidity: 60 %

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1739	36.34		16.98	10.19	46.53		27.17	64.77	54.77	-18.24	-27.60	P	
2	0.2899	33.11		15.71	10.29	43.40		26.00	60.52	50.52	-17.12	-24.52	P	
3	0.3899	33.32		24.41	10.33	43.65		34.74	58.06	48.06	-14.41	-13.32	P	
4	0.7378	28.95		18.72	10.32	39.27		29.04	56.00	46.00	-16.73	-16.96	P	
5	1.5700	30.77		14.37	10.36	41.13		24.73	56.00	46.00	-14.87	-21.27	P	
6	3.8140	26.45		3.96	10.46	36.91		14.42	56.00	46.00	-19.09	-31.58	P	

LINE CONDUCTED EMISSION - N



Site: Conduction Phase: **N** Temperature: 26
Limit: FCC Class B Conduction(QP) Power: AC 120V/60Hz Humidity: 60 %
EUT: WCDMA mobile phone
M/N: SP4521
Mode: Call
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1633	33.14		9.52	10.17	43.31		19.69	65.29	55.29	-21.98	-35.60	P	
2	0.3059	34.99		10.19	10.29	45.28		20.48	60.08	50.08	-14.80	-29.60	P	
3	0.7299	32.64		17.87	10.33	42.97		28.20	56.00	46.00	-13.03	-17.80	P	
4	2.3060	30.24		10.31	10.35	40.59		20.66	56.00	46.00	-15.41	-25.34	P	
5	7.4898	22.00		6.42	10.33	32.33		16.75	60.00	50.00	-27.67	-33.25	P	
6	22.4259	22.31		2.87	10.12	32.43		12.99	60.00	50.00	-27.57	-37.01	P	

Note: The GSM850 mode is the worst condition.

9. FREQUENCY STABILITY

9.1 MEASUREMENT METHOD

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1 , Measure the carrier frequency at room temperature.
- 2 , Subject the EUT to overnight soak at -10°C.
- 3 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 band , channel 190 for GSM 850 band, channel 9400 for UMTS band II and channel 4175 for UMTS band V measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4 , Repeat the above measurements at 10°C increments from -10°C to +55°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5 , Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6 , Subject the EUT to overnight soak at +55°C.
- 7 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8 , Repeat the above measurements at 10°C increments from +55°C to -10°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9 , At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

9.2 PROVISIONS APPLICABLE

9.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 6.3VDC and 8.5VDC, with a nominal voltage of 7.4VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

9.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment, the normal environment temperature is 20°C.

9.3 MEASUREMENT RESULT (WORST)

Frequency Error Against Voltage for GSM850/EDGE 8 band				
Voltage(V)	GSM		EDGE 8	
	Frequency error(Hz)	Frequency error(ppm)	Frequency error(Hz)	Frequency error(ppm)
3.4	15	0.018	22	0.026
3.7	17	0.020	19	0.023
4.2	19	0.023	16	0.019

Frequency Error Against Temperature for GSM850/EDGE 8 band				
temperature(°C)	GSM		EDGE 8	
	Frequency error(Hz)	Frequency error(ppm)	Frequency error(Hz)	Frequency error(ppm)
-10	21	0.025	21	0.025
0	25	0.030	23	0.028
10	24	0.029	19	0.023
20	22	0.026	22	0.026
30	21	0.025	23	0.028
40	24	0.029	26	0.031
50	22	0.026	23	0.028
55	22	0.026	24	0.029

Note: The EUT doesn't work below -10°C

Frequency Error Against Voltage for PCS1900/EDGE 8 band				
Voltage(V)	GSM		EDGE 8	
	Frequency error(Hz)	Frequency error(ppm)	Frequency error(Hz)	Frequency error(ppm)
3.4	24	0.013	24	0.013
3.7	21	0.011	26	0.014
4.2	22	0.012	22	0.012

Frequency Error Against Voltage for PCS1900/EDGE 8 band				
temperature(°C)	GSM		EDGE 8	
	Frequency error(Hz)	Frequency error(ppm)	Frequency error(Hz)	Frequency error(ppm)
-10	21	0.011	25	0.013
0	24	0.013	26	0.014
10	23	0.012	21	0.011
20	14	0.007	19	0.010
30	23	0.012	22	0.012
40	25	0.013	21	0.011
50	27	0.014	27	0.014
55	22	0.012	26	0.014

Note: The EUT doesn't work below -10°C

Frequency Error Against Voltage for UMTS band II		
Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.4	24	0.013
3.7	22	0.012
4.2	26	0.014

Frequency Error Against Temperature for UMTS band II		
temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	31	0.016
0	35	0.019
10	35	0.019
20	34	0.018
30	32	0.017
40	36	0.019
50	32	0.017
55	33	0.018

Note: The EUT doesn't work below -10°C

Frequency Error Against Voltage for UMTS band V		
Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
6.3	24	0.029
7.4	27	0.032
8.5	21	0.025

Frequency Error Against Temperature for UMTS band V		
temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	22	0.026
0	25	0.030
10	21	0.025
20	26	0.031
30	22	0.026
40	24	0.029
50	28	0.034
55	31	0.037

Note: The EUT doesn't work below -10°C

10. OCCUPIED BANDWIDTH

10.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

10.2 PROVISIONS APPLICABLE

The emission bandwidth is defined as two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power

10.3 MEASUREMENT RESULT

Occupied Bandwidth (99%) for GSM850 band			
GSM	Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
	Low Channel	824.2	244.77
	Middle Channel	836.6	244.78
	High Channel	848.8	246.36
EDGE 8	Low Channel	824.2	244.39
	Middle Channel	836.6	248.66
	High Channel	848.8	242.90

Occupied Bandwidth (99%) for PCS1900 band			
GSM	Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
	Low Channel	1850.2	244.35
	Middle Channel	1880.0	246.32
	High Channel	1909.8	244.10
EDGE 8	Low Channel	1850.2	242.71
	Middle Channel	1880.0	244.30
	High Channel	1909.8	248.86

Occupied Bandwidth (99%) for UMTS band II		
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(MHz)
Low Channel	1852.4	4.16
Middle Channel	1880	4.16
High Channel	1907.6	4.16

Occupied Bandwidth (99%) for UMTS band V		
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(MHz)
Low Channel	826.4	4.16
Middle Channel	836.6	4.17
High Channel	846.6	4.16

11. EMISSION BANDWIDTH

11.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

11.2 PROVISIONS APPLICABLE

The emission bandwidth is defined as two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power

11.3 MEASUREMENT RESULT

Emission Bandwidth (-26dBc) for GSM850 (EDGE 8) band			
GSM	Mode	Frequency(MHz)	Emission Bandwidth (-26dBc)(kHz)
	Low Channel	824.2	308.81
	Middle Channel	836.6	310.06
	High Channel	848.8	312.02
EDGE 8	Low Channel	824.2	312.89
	Middle Channel	836.6	312.54
	High Channel	848.8	314.76

Emission Bandwidth (-26dBc) for PCS1900 (EDGE 8) band			
GSM	Mode	Frequency(MHz)	Emission Bandwidth (-26dBc)(kHz)
	Low Channel	1850.2	309.29
	Middle Channel	1880.0	304.57
	High Channel	1909.8	308.47
EDGE 8	Low Channel	1850.2	317.72
	Middle Channel	1880.0	319.62
	High Channel	1909.8	322.79

Emission Bandwidth (-26dBc) for UMTS band II		
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(MHz)
Low Channel	1852.4	4.70
Middle Channel	1880	4.66
High Channel	1907.6	4.69

Emission Bandwidth (-26dBc) for UMTS band V		
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(MHz)
Low Channel	826.4	4.71
Middle Channel	836.6	4.68
High Channel	846.6	4.70

12. BAND EDGE

12.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

12.2 PROVISIONS APPLICABLE

As Specified in FCC rules of 22.917(a) and 24.238(a)

12.3 MEASUREMENT RESULT


Please refers to Appendix III for compliance test plots for band edges

APPENDIX A


TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION

CONDUCTED EMISSION IN GSM850 BAND


Conducted Emission Transmitting Mode CH 128 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 128 1GHz – 9GHz




Conducted Emission Transmitting Mode CH 190 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 190 1GHz – 9GHz



Conducted Emission Transmitting Mode CH 251 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 251 1GHz – 9GHz




CONDUCTED EMISSION IN GSM850 (EDGE 8) BAND


Conducted Emission Transmitting Mode CH 128 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 128 1GHz – 9GHz




Conducted Emission Transmitting Mode CH 190 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 190 1GHz – 9GHz




Conducted Emission Transmitting Mode CH 251 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 251 1GHz – 9GHz




CONDUCTED EMISSION IN PCS1900 BAND
Conducted Emission Transmitting Mode CH 512 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 512 1GHz – 7GHz




Conducted Emission Transmitting Mode CH 512 7GHz – 13.6GHz




Conducted Emission Transmitting Mode CH 512 13.6GHz – 20GHz




Conducted Emission Transmitting Mode CH 661 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 661 1GHz – 7GHz




Conducted Emission Transmitting Mode CH 661 7GHz – 13.6GHz




Conducted Emission Transmitting Mode CH 661 13.6GHz – 20GHz




Conducted Emission Transmitting Mode CH 810 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 810 1GHz – 7GHz




Conducted Emission Transmitting Mode CH 810 7GHz – 13.6GHz




Conducted Emission Transmitting Mode CH 810 13.6GHz – 20GHz




CONDUCTED EMISSION IN PCS1900 (EDGE 8) BAND
Conducted Emission Transmitting Mode CH 512 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 512 1GHz – 7GHz




Conducted Emission Transmitting Mode CH 512 7GHz – 13.6GHz




Conducted Emission Transmitting Mode CH 512 13.6GHz – 20GHz




Conducted Emission Transmitting Mode CH 661 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 661 1GHz – 7GHz




Conducted Emission Transmitting Mode CH 661 7GHz – 13.6GHz




Conducted Emission Transmitting Mode CH 661 13.6GHz – 20GHz




Conducted Emission Transmitting Mode CH 810 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 810 1GHz – 7GHz




Conducted Emission Transmitting Mode CH 810 7GHz – 13.6GHz




Conducted Emission Transmitting Mode CH 810 13.6GHz – 20GHz




CONDUCTED EMISSION IN UMTS band II
Conducted Emission Transmitting Mode CH 9662 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 9662 1GHz – 7GHz




Conducted Emission Transmitting Mode CH 9662 7GHz – 13.6GHz




Conducted Emission Transmitting Mode CH 9662 13.6GHz – 20GHz




Conducted Emission Transmitting Mode CH 9800 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 9800 1GHz – 7GHz




Conducted Emission Transmitting Mode CH 9800 7GHz – 13.6GHz




Conducted Emission Transmitting Mode CH 9800 13.6GHz – 20GHz




Conducted Emission Transmitting Mode CH 9938 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 9938 1GHz – 7GHz




Conducted Emission Transmitting Mode CH 9938 7GHz – 13.6GHz




Conducted Emission Transmitting Mode CH 9938 13.6GHz – 20GHz




CONDUCTED EMISSION IN UMTS band V
Conducted Emission Transmitting Mode CH 4357 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 4357 1GHz – 9GHz




Conducted Emission Transmitting Mode CH 4408 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 4408 1GHz – 9GHz



Conducted Emission Transmitting Mode CH 4458 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 4458 1GHz – 9GHz



APPENDIX B
TEST PLOTS FOR OCCUPIED BANDWIDTH (99%)
EMISSION BANDWIDTH (-26dBC)


Occupied Bandwidth (99%) GSM 850 BAND CH 128




Occupied Bandwidth (99%) GSM 850 BAND CH 190




Occupied Bandwidth (99%) GSM 850 BAND CH 251




Occupied Bandwidth (99%) GSM 850(EDGE 8) BAND CH 128




Occupied Bandwidth (99%) GSM 850 (EDGE 8) BAND CH 190



Occupied Bandwidth (99%) GSM 850 (EDGE 8) BAND CH 251




Occupied Bandwidth (99%) PCS 1900 BAND CH 512




Occupied Bandwidth (99%) PCS 1900 BAND CH 661




Occupied Bandwidth (99%) PCS 1900 BAND CH 810




Occupied Bandwidth (99%) PCS 1900 (EDGE 8) BAND CH 512




Occupied Bandwidth (99%) PCS 1900 (EDGE 8) BAND CH 661




Occupied Bandwidth (99%) PCS 1900 (EDGE 8) BAND CH 810




Occupied Bandwidth (99%) UMTS band II CH 9662




Occupied Bandwidth (99%) UMTS band II CH 9800




Occupied Bandwidth (99%) UMTS band II CH 9938




Occupied Bandwidth (99%) UMTS band V CH 4357



Occupied Bandwidth (99%) UMTS band V CH 4408




Occupied Bandwidth (99%) UMTS band V CH 4458




APPENDIX C

TEST PLOTS FOR BAND EDGES


Low Band Edge GSM 850 BAND CH 128




High Band Edge GSM 850 BAND CH 251




Low Band Edge GSM 850 (EDGE 8) BAND CH 128




High Band Edge GSM 850 (EDGE 8) BAND CH 251




Low Band Edge PCS 1900 BAND CH 512




High Band Edge PCS 1900 BAND CH 810




Low Band Edge PCS 1900 (EDGE 8) BAND CH 512




High Band Edge PCS 1900 (EDGE 8) BAND CH 810




Low Band Edge UMTS BAND II CH 9662




High Band Edge UMTS BAND II CH 9938



Low Band Edge UMTS BAND V CH 4357



High Band Edge UMTS BAND V CH 4458




APPENDIX D

PHOTOGRAPHS OF TEST SETUP

CONDUCTED EMISSION



RADIATED SPURIOUS EMISSION





APPENDIX E

PHOTOGRAPHS OF EUT


TOTAL VIEW OF EUT



TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT




OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



-----END OF REPORT-----