

4 FCC §2.1091 & §15.407(f) - RF Exposure

4.1 Applicable Standards

According to FCC §15.247(i), §15.407(f) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

4.3 MPE Results

8 dBi Antenna

5.3 GHz band:

Maximum average output power at antenna input terminal (dBm):	21.253
Maximum average output power at antenna input terminal (mW):	133.444
Prediction distance (cm):	20
Prediction frequency (MHz):	5270
Maximum Antenna Gain, typical (dBi):	8
Maximum Antenna Gain (numeric):	6.310
Power density of prediction frequency at 20.0 cm (mW/cm ²):	0.1675
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm ²):	1.0

5.6 GHz band:

<u>Maximum average output power at antenna input terminal (dBm):</u>	<u>20.36</u>
<u>Maximum average output power at antenna input terminal (mW):</u>	<u>108.643</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>5510</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>8</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>6.310</u>
<u>Power density of prediction frequency at 20.0 cm (mW/cm²):</u>	<u>0.1364</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>

25 dBi Antenna**5.3 GHz band:**

<u>Maximum average output power at antenna input terminal (dBm):</u>	<u>-13.345</u>
<u>Maximum average output power at antenna input terminal (mW):</u>	<u>0.0463</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>5260</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>25</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>316.23</u>
<u>Power density of prediction frequency at 20.0 cm (mW/cm²):</u>	<u>0.0029</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>

5.6 GHz band:

<u>Maximum average output power at antenna input terminal (dBm):</u>	<u>-9.677</u>
<u>Maximum average output power at antenna input terminal (mW):</u>	<u>0.108</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>5510</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>25</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>316.23</u>
<u>Power density of prediction frequency at 20.0 cm (mW/cm²):</u>	<u>0.0068</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>

Conclusion

The device is compliant with the requirement MPE limit for uncontrolled exposure. All transceiver modules must be installed with a separation distance of no less than **20** cm from all persons.