

TEST REPORT

Product : WIFI Module
Trade mark : GSD
Model/Type reference : WC3HM2511
Serial Number : N/A
Report Number : EED32K00324401
FCC ID : 2AC23-WC3HM2511
Date of Issue : May 21, 2019
Test Standards : 47 CFR Part 15 Subpart C
Test result : PASS

Prepared for:

Hui Zhou Gaoshengda Technology Co., LTD
No. 75 Zhongkai Development Area Huizhou, Guangdong, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested By:

Jay Zheng

Compiled by:

Wang Xin

Reviewed by:

Kevin lan

Approved by:

Kevin yang

Date:

May 21, 2019

Check No.:3096391277



2 Version

Version No.	Date	Description
00	May 21, 2019	Original

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013	PASS
Conducted Peak Output Power	47 CFR Part 15 Subpart C Section 15.247 (b)(3)	ANSI C63.10-2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15 Subpart C Section 15.247 (a)(2)	ANSI C63.10-2013	PASS
Power Spectral Density	47 CFR Part 15 Subpart C Section 15.247 (e)	ANSI C63.10-2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
Radiated Spurious Emissions	47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS

Remark:

Test according to ANSI C63.4-2014 & ANSI C63.10-2013.

The tested sample(s) and the sample information are provided by the client.


4 Content

1 COVER PAGE	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENT	4
5 TEST REQUIREMENT	5
5.1 TEST SETUP.....	5
5.1.1 For Conducted test setup.....	5
5.1.2 For Radiated Emissions test setup.....	5
5.1.3 For Conducted Emissions test setup.....	6
5.2 TEST ENVIRONMENT.....	6
5.3 TEST CONDITION.....	7
6 GENERAL INFORMATION	8
6.1 CLIENT INFORMATION.....	8
6.2 GENERAL DESCRIPTION OF EUT.....	8
6.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	8
6.4 DESCRIPTION OF SUPPORT UNITS.....	9
6.5 TEST LOCATION.....	9
6.6 DEVIATION FROM STANDARDS.....	9
6.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	9
6.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	9
6.9 MEASUREMENT UNCERTAINTY(95% CONFIDENCE LEVELS, K=2).....	10
7 EQUIPMENT LIST	11
8 RADIO TECHNICAL REQUIREMENTS SPECIFICATION	14
Appendix A): Conducted Peak Output Power.....	15
Appendix B): 6dB Occupied Bandwidth.....	28
Appendix C): Band-edge for RF Conducted Emissions.....	41
Appendix D): RF Conducted Spurious Emissions.....	50
Appendix E): Power Spectral Density.....	87
Appendix F): Antenna Requirement.....	100
Appendix G): AC Power Line Conducted Emission.....	101
Appendix H): Restricted bands around fundamental frequency (Radiated).....	104
Appendix I): Radiated Spurious Emissions.....	122
PHOTOGRAPHS OF TEST SETUP	143
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	146

5 Test Requirement

5.1 Test setup

5.1.1 For Conducted test setup



5.1.2 For Radiated Emissions test setup

Radiated Emissions setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1GHz

5.1.3 For Conducted Emissions test setup

Conducted Emissions setup



5.2 Test Environment

Operating Environment for RF test:

Temperature:	26°C
Humidity:	60% RH
Atmospheric Pressure:	1010mbar

5.3 Test Condition

Test channel:

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
802.11b/g/n(HT20)	2412MHz ~2462 MHz	Channel 1	Channel 6	Channel11
		2412MHz	2437MHz	2462MHz
802.11n(HT40)	2422MHz ~2452 MHz	Channel 1	Channel 4	Channel7
		2422MHz	2437MHz	2452MHz
TX mode:	The EUT transmitted the continuous signal at the specific channel(s).			

Test mode:
Pre-scan under all rate at lowest channel 1 for Antenna 1

Mode	802.11b				802.11g				
Data Rate	1Mbps	2Mbps	5.5Mbps	11Mbps	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps
Power(dBm)	22.74	22.98	23.00	23.08					
Mode	802.11n (HT20)								
Data Rate	6.5Mbps	13Mbps	19.5Mbps	26Mbps	39Mbps	52Mbps	58.5Mbps	65Mbps	
Power(dBm)	21.47	21.41	21.40	21.33	21.24	21.19	21.15	21.07	
Mode	802.11n (HT40)								
Data Rate	13.5Mbps	27Mbps	40.5Mbps	54Mbps	81Mbps	108Mbps	121.5Mbps	135Mbps	
Power(dBm)	20.99	20.97	20.84	20.63	20.60	20.45	20.41	20.39	

Through Pre-scan, 11Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).

6 General Information

6.1 Client Information

Applicant:	Hui Zhou Gaoshengda Technology Co., LTD
Address of Applicant:	No. 75 Zhongkai Development Area Huizhou,Guangdong, China
Manufacturer:	Hui Zhou Gaoshengda Technology Co., LTD
Address of Manufacturer:	No. 75 Zhongkai Development Area Huizhou,Guangdong, China
Factory:	Hui Zhou Gaoshengda Technology Co., LTD
Address of Factory:	No. 75 Zhongkai Development Area Huizhou,Guangdong, China

6.2 General Description of EUT

Product Name:	WIFI Module
Model No.(EUT):	WC3HM2511
Trade Mark:	GSD
EUT Supports Radios application:	2.4G WiFi: IEEE802.11b/g/n(20MHz)/n(40MHz), 2412MHz-2462MHz 5G WiFi: IEEE802.11a/ac(HT20)/ac(HT40)/ac(HT80), 5150-5250MHz, 5725-5850MHz
Power Supply:	DC 5V
Sample Received Date:	Dec. 05, 2018
Sample tested Date:	Dec. 25, 2018 to May 18, 2019

6.3 Product Specification subjective to this standard

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g:OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40): OFDM (64QAM, 16QAM, QPSK,BPSK)
Firmware version of the sample:	V1.0(manufacturer declare)
Hardware version of the sample:	V1.0(manufacturer declare)
Test Power Grade:	B:26, G:1D , N20:1B, N40:18
Test Software of EUT:	MT7662 QA (manufacturer declare)
Antenna Type:	PIFA Antenna
Antenna gain:	2dBi
Test Voltage:	DC 5V

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel(802.11n HT40)					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2422MHz	4	2437MHz	7	2452MHz
2	2427MHz	5	2442MHz		
3	2432MHz	6	2447MHz		

6.4 Description of Support Units

The EUT has been tested with associated equipment below.

Associated equipment name		Manufacture	model	serial number	Supplied by	Certification
AE1	Laptop	HP	430 G3	5CD6082JLC	CTI	CE
AE2	Mouse	L.Selectron	OP-308	G1103000147VJKJ	CTI	CE
AE3	PC	Apple	MMGF2Z P/A	ODN20170212	CTI	CE

6.5 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

6.6 Deviation from Standards

None.

6.7 Abnormalities from Standard Conditions

None.

6.8 Other Information Requested by the Customer

None.

6.9 Measurement Uncertainty(95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-18GHz)
3	Radiated Spurious emission test	4.3dB (30MHz-1GHz)
		4.5dB (1GHz-12.75GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

7 Equipment List

RF test system					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Signal Generator	Keysight	E8257D	MY53401106	03-02-2018 03-01-2019	03-01-2019 02-29-2020
Spectrum Analyzer	Keysight	N9010A	MY54510339	03-02-2018 03-01-2019	03-01-2019 02-29-2020
Signal Generator	Keysight	N5182B	MY53051549	03-02-2018 03-01-2019	03-01-2019 02-29-2020
High-pass filter	Sinoscite	FL3CX03WG18N M12-0398-002	---	01-10-2018 01-09-2019	01-09-2019 01-08-2020
High-pass filter	MICRO-TRONICS	SPA-F-63029-4	---	01-10-2018 01-09-2019	01-09-2019 01-08-2020
DC Power	Keysight	E3642A	MY54426035	03-02-2018 03-01-2019	03-01-2019 02-29-2020
PC-1	Lenovo	R4960d	---	03-02-2018 03-01-2019	03-01-2019 02-29-2020
BT&WI-FI Automatic control	R&S	OSP120	101374	03-02-2018 03-01-2019	03-01-2019 02-29-2020
RF control unit	JS Tonscend	JS0806-2	15860006	03-02-2018 03-01-2019	03-01-2019 02-29-2020
RF control unit	JS Tonscend	JS0806-1	15860004	03-02-2018 03-01-2019	03-01-2019 02-29-2020
RF control unit	JS Tonscend	JS0806-4	158060007	03-02-2018 03-01-2019	03-01-2019 02-29-2020
BT&WI-FI Automatic test software	JS Tonscend	JS1120-2	---	03-02-2018 03-01-2019	03-01-2019 02-29-2020
Temperature/ Humidity Indicator	biaozhi	HM10	1804186	10-12-2018	10-11-2019

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Receiver	R&S	ESCI	100435	05-25-2018	05-24-2019
Temperature/ Humidity Indicator	Defu	TH128	/	07-02-2018	07-01-2019
Communication test set	Agilent	E5515C	GB47050534	03-02-2018 03-01-2019	03-01-2019 02-29-2020
Communication test set	R&S	CMW500	102898	01-19-2018 01-18-2019	01-18-2019 01-17-2020
LISN	R&S	ENV216	100098	05-10-2018 05-08-2019	05-10-2019 05-06-2020
Voltage Probe	R&S	ESH2-Z3 0299.7810.56	100042	06-13-2017	06-11-2020
Current Probe	R&S	EZ-17 816.2063.03	100106	05-30-2018	05-29-2019
ISN	TESEQ	ISN T800	30297	01-17-2018 01-16-2019	01-16-2019 01-15-2020

3M Semi/full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	06-04-2016	06-03-2019
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-401	12-21-2018	12-20-2019
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-618	07-30-2018	07-29-2019
Microwave Preamplifier	Agilent	8449B	3008A02425	08-21-2018	08-20-2019
Microwave Preamplifier	Tonscend	EMC051845SE	980380	01-17-2018 01-16-2019	01-16-2019 01-15-2020
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1869	04-25-2018	04-23-2021
Horn Antenna	ETS-LINDGREN	3117	00057410	06-05-2018	06-03-2021
Double ridge horn antenna	A.H.SYSTEMS	SAS-574	374	06-05-2018	06-04-2021
Pre-amplifier	A.H.SYSTEMS	PAP-1840-60	6041.6041	08-08-2018	08-07-2019
Preamplifier	EMCI	EMC001330	980563	06-20-2018	06-19-2019
Loop Antenna	ETS	6502	00071730	06-22-2017	06-21-2019
Spectrum Analyzer	R&S	FSP40	100416	05-11-2018 04-28-2019	05-10-2019 04-26-2020
Receiver	R&S	ESCI	100435	05-25-2018	05-24-2019
Receiver	R&S	ESCI7	100938-003	11-23-2018	11-22-2019
Multi device Controller	maturo	NCD/070/10711 112	---	01-10-2018 01-09-2019	01-09-2019 01-08-2020
LISN	schwarzbeck	NNBM8125	81251547	05-11-2018 05-08-2019	05-10-2019 05-06-2020
LISN	schwarzbeck	NNBM8125	81251548	05-11-2018 05-08-2019	05-10-2019 05-06-2020
Signal Generator	Agilent	E4438C	MY45095744	03-02-2018 03-01-2019	03-01-2019 02-29-2020
Signal Generator	Keysight	E8257D	MY53401106	03-02-2018 03-01-2019	03-01-2019 02-29-2020
Temperature/ Humidity Indicator	Shanghai qixiang	HM10	1804298	10-12-2018	10-11-2019
Communication test set	Agilent	E5515C	GB47050534	03-02-2018 03-01-2019	03-01-2019 02-29-2020
Cable line	Fulai(7M)	SF106	5219/6A	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Cable line	Fulai(6M)	SF106	5220/6A	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Cable line	Fulai(3M)	SF106	5216/6A	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Cable line	Fulai(3M)	SF106	5217/6A	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Communication test set	R&S	CMW500	104466	01-10-2018 01-09-2019	01-09-2019 01-08-2020
High-pass filter	Sinoscite	FL3CX03WG18 NM12-0398-002	---	01-10-2018 01-09-2019	01-09-2019 01-08-2020
High-pass filter	MICRO-TRONICS	SPA-F-63029-4	---	01-10-2018 01-09-2019	01-09-2019 01-08-2020
band rejection filter	Sinoscite	FL5CX01CA09C L12-0395-001	---	01-10-2018 01-09-2019	01-09-2019 01-08-2020
band rejection filter	Sinoscite	FL5CX01CA08C L12-0393-001	---	01-10-2018 01-09-2019	01-09-2019 01-08-2020
band rejection filter	Sinoscite	FL5CX02CA04C L12-0396-002	---	01-10-2018 01-09-2019	01-09-2019 01-08-2020
band rejection filter	Sinoscite	FL5CX02CA03C L12-0394-001	---	01-10-2018 01-09-2019	01-09-2019 01-08-2020

3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
RSE Automatic test software	JS Tonscend	JS36-RSE	10166	06-20-2018	06-19-2019
Receiver	Keysight	N9038A	MY57290136	03-28-2018 03-27-2019	03-27-2019 03-25-2020
Spectrum Analyzer	Keysight	N9020B	MY57111112	03-28-2018 03-27-2019	03-27-2019 03-25-2020
Spectrum Analyzer	Keysight	N9030B	MY57140871	03-28-2018 03-27-2019	03-27-2019 03-25-2020
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-075	04-25-2018	04-23-2021
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04-25-2018	04-23-2021
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-25-2018	04-23-2021
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-25-2018	04-23-2021
Horn Antenna	Schwarzbeck	BBHA 9170	9170-829	04-25-2018	04-23-2021
Communication Antenna	Schwarzbeck	CLSA 0110L	1014	02-15-2018 02-14-2019	02-14-2019 02-13-2020
Biconical antenna	Schwarzbeck	VUBA 9117	9117-381	04-25-2018	04-23-2021
Horn Antenna	ETS-LINDGREN	3117	00057407	07-10-2018	07-08-2021
Preamplifier	EMCI	EMC184055SE	980596	06-20-2018	06-19-2019
Communication test set	R&S	CMW500	102898	01-19-2018 01-18-2019	01-18-2019 01-17-2020
Preamplifier	Agilent	8449B	3008A02425	08-21-2018	08-20-2019
Temperature/ Humidity Indicator	biaozhi	GM1360	EE1186631	05-02-2018 04-30-2019	05-01-2019 04-28-2020
Signal Generator	KEYSIGHT	E8257D	MY53401106	03-02-2018 03-01-2019	03-01-2019 02-29-2020
Fully Anechoic Chamber	TDK	FAC-3	---	01-17-2018	01-15-2021
Filter bank	JS Tonscend	JS0806-F	188060094	04-10-2018	04-08-2021
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Cable line	Times	EMC104-NMNM-1000	SN160710	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	01-10-2018 01-09-2019	01-09-2019 01-08-2020
Cable line	Times	HF160-KMKM-3.00M	393493-0001	01-10-2018 01-09-2019	01-09-2019 01-08-2020

8 Radio Technical Requirements Specification

Reference documents for testing:

No.	Identity	Document Title
1	FCC Part15C	Subpart C-Intentional Radiators
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Test Results List:

Test Requirement	Test method	Test item	Verdict	Note
Part15C Section 15.247 (b)(3)	ANSI C63.10	Conducted Peak Output Power	PASS	Appendix A)
Part15C Section 15.247 (a)(2)	ANSI C63.10	6dB Occupied Bandwidth	PASS	Appendix B)
Part15C Section 15.247(d)	ANSI C63.10	Band-edge for RF Conducted Emissions	PASS	Appendix C)
Part15C Section 15.247(d)	ANSI C63.10	RF Conducted Spurious Emissions	PASS	Appendix D)
Part15C Section 15.247 (e)	ANSI C63.10	Power Spectral Density	PASS	Appendix E)
Part15C Section 15.203/15.247 (c)	ANSI C63.10	Antenna Requirement	PASS	Appendix F)
Part15C Section 15.207	ANSI C63.10	AC Power Line Conducted Emission	PASS	Appendix G)
Part15C Section 15.205/15.209	ANSI C63.10	Restricted bands around fundamental frequency (Radiated Emission)	PASS	Appendix H)
Part15C Section 15.205/15.209	ANSI C63.10	Radiated Spurious Emissions	PASS	Appendix I)

Appendix A): Conducted Peak Output Power

Directional Antenna Gain

The TX chains are correlated, the antenna gain is equal among the chains.

Employs an antenna that operates simultaneously on multiple directional beams using the same frequency channels. No carrier aggregation techniques.

The directional gain is:

Antenna 1 Gain(dBi)	Antenna 2 Gain(dBi)	Correlated Chains DirectionalGain(dBi)
2	2	5

Result Table

Mode	Antenna	Channel	Conducted Peak Output Power [dBm]	Verdict
11B	Ant1	LCH	23.08	PASS
11B	Ant2	LCH	23.74	PASS
11B	Ant1	MCH	23.72	PASS
11B	Ant2	MCH	23.63	PASS
11B	Ant1	HCH	23.34	PASS
11B	Ant2	HCH	23.7	PASS
11G	Ant1	LCH	22.38	PASS
11G	Ant2	LCH	22.89	PASS
11G	Ant1	MCH	22.95	PASS
11G	Ant2	MCH	22.63	PASS
11G	Ant1	HCH	23.07	PASS
11G	Ant2	HCH	22.52	PASS
11N20SISO	Ant1	LCH	21.47	PASS
11N20SISO	Ant2	LCH	21.22	PASS
11N20SISO	Ant1	MCH	21.96	PASS
11N20SISO	Ant2	MCH	21.73	PASS
11N20SISO	Ant1	HCH	21.99	PASS
11N20SISO	Ant2	HCH	21.57	PASS
11N20MIMO	Ant1	LCH	18.48	PASS
11N20MIMO	Ant2	LCH	18.42	PASS
11N20MIMO	Ant1+2	LCH	21.46	PASS
11N20MIMO	Ant1	MCH	18.52	PASS
11N20MIMO	Ant2	MCH	18.84	PASS
11N20MIMO	Ant1+2	MCH	21.69	PASS
11N20MIMO	Ant1	HCH	18.67	PASS
11N20MIMO	Ant2	HCH	18.79	PASS
11N20MIMO	Ant1+2	HCH	21.74	PASS
11N40SISO	Ant1	LCH	20.99	PASS
11N40SISO	Ant2	LCH	20.48	PASS
11N40SISO	Ant1	MCH	20.78	PASS
11N40SISO	Ant2	MCH	20.57	PASS
11N40SISO	Ant1	HCH	20.77	PASS
11N40SISO	Ant2	HCH	20.67	PASS
11N40MIMO	Ant1	LCH	17.59	PASS
11N40MIMO	Ant2	LCH	17.74	PASS
11N40MIMO	Ant1+2	LCH	20.68	PASS
11N40MIMO	Ant1	MCH	17.82	PASS
11N40MIMO	Ant2	MCH	17.82	PASS
11N40MIMO	Ant1+2	MCH	20.83	PASS
11N40MIMO	Ant1	HCH	17.74	PASS
11N40MIMO	Ant2	HCH	17.49	PASS
11N40MIMO	Ant1+2	HCH	20.63	PASS


Test Graph


Graphs	
11B/LCH_Ant1	<p>Keystream Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.412000000 GHz</p> <p>Ref Offset 19.5 dB Ref 30.00 dBm</p> <p>10 dB/div Log</p> <p>Center 2.412 GHz #Res BW 1 MHz #VBW 3 MHz Span 40 MHz Sweep 1 ms</p> <p>Channel Power Power Spectral Density</p> <p>23.08 dBm / 20 MHz -49.93 dBm /Hz</p> <p>Frequency</p> <p>Center Freq 2.412000000 GHz</p> <p>CF Step 4.000000 MHz Auto Man</p> <p>Freq Offset 0 Hz</p>
11B/LCH_Ant2	<p>Keystream Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.412000000 GHz</p> <p>Ref Offset 19.5 dB Ref 30.00 dBm</p> <p>10 dB/div Log</p> <p>Center 2.412 GHz #Res BW 1 MHz #VBW 3 MHz Span 40 MHz Sweep 1 ms</p> <p>Channel Power Power Spectral Density</p> <p>23.74 dBm / 20 MHz -49.27 dBm /Hz</p> <p>Frequency</p> <p>Center Freq 2.412000000 GHz</p> <p>CF Step 4.000000 MHz Auto Man</p> <p>Freq Offset 0 Hz</p>
11B/MCH_Ant1	<p>Keystream Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.437000000 GHz</p> <p>Ref Offset 19.77 dB Ref 30.00 dBm</p> <p>10 dB/div Log</p> <p>Center 2.437 GHz #Res BW 1 MHz #VBW 3 MHz Span 40 MHz Sweep 1 ms</p> <p>Channel Power Power Spectral Density</p> <p>23.72 dBm / 20 MHz -49.29 dBm /Hz</p> <p>Frequency</p> <p>Center Freq 2.437000000 GHz</p> <p>CF Step 4.000000 MHz Auto Man</p> <p>Freq Offset 0 Hz</p>


























Appendix B): 6dB Occupied Bandwidth


Result Table


Mode	Antenna	Channel	6dB Bandwidth [MHz]	99% OBW [MHz]	Verdict
11B	Ant1	LCH	10.06	12.712	PASS
11B	Ant2	LCH	9.994	12.820	PASS
11B	Ant1	MCH	10.07	12.936	PASS
11B	Ant2	MCH	10.06	13.126	PASS
11B	Ant1	HCH	9.578	12.701	PASS
11B	Ant2	HCH	10.03	13.006	PASS
11G	Ant1	LCH	16.32	16.444	PASS
11G	Ant2	LCH	16.29	16.454	PASS
11G	Ant1	MCH	15.82	16.441	PASS
11G	Ant2	MCH	16.29	16.452	PASS
11G	Ant1	HCH	16.29	16.415	PASS
11G	Ant2	HCH	16.04	16.433	PASS
11N20SISO	Ant1	LCH	16.90	17.560	PASS
11N20SISO	Ant2	LCH	17.06	17.573	PASS
11N20SISO	Ant1	MCH	17.04	17.564	PASS
11N20SISO	Ant2	MCH	17.23	17.574	PASS
11N20SISO	Ant1	HCH	17.03	17.554	PASS
11N20SISO	Ant2	HCH	17.31	17.571	PASS
11N20MIMO	Ant1	LCH	16.76	17.565	PASS
11N20MIMO	Ant2	LCH	17.10	17.557	PASS
11N20MIMO	Ant1	MCH	16.68	17.565	PASS
11N20MIMO	Ant2	MCH	17.09	17.562	PASS
11N20MIMO	Ant1	HCH	17.05	17.552	PASS
11N20MIMO	Ant2	HCH	16.67	17.550	PASS
11N40SISO	Ant1	LCH	35.31	35.913	PASS
11N40SISO	Ant2	LCH	35.35	35.896	PASS
11N40SISO	Ant1	MCH	35.09	35.914	PASS
11N40SISO	Ant2	MCH	35.15	35.887	PASS
11N40SISO	Ant1	HCH	35.11	35.876	PASS
11N40SISO	Ant2	HCH	35.14	35.907	PASS
11N40MIMO	Ant1	LCH	35.16	35.889	PASS
11N40MIMO	Ant2	LCH	35.12	35.896	PASS
11N40MIMO	Ant1	MCH	35.15	35.919	PASS
11N40MIMO	Ant2	MCH	35.09	35.876	PASS
11N40MIMO	Ant1	HCH	35.34	35.895	PASS
11N40MIMO	Ant2	HCH	35.46	35.920	PASS



Test Graph


















11N20SISO/LCH_Ant1	
11N20SISO/LCH_Ant2	
11N20SISO/MCH_Ant1	









11N20MIMO/LCH_Ant1	
11N20MIMO/LCH_Ant2	
11N20MIMO/MCH_Ant1	

11N20MIMO/MCH_Ant2	
11N20MIMO/HCH_Ant1	
11N20MIMO/HCH_Ant2	

11N40SISO/LCH_Ant1	
11N40SISO/LCH_Ant2	
11N40SISO/MCH_Ant1	

11N40SISO/MCH_Ant2	
11N40SISO/HCH_Ant1	
11N40SISO/HCH_Ant2	

11N40MIMO/LCH_Ant1	
11N40MIMO/LCH_Ant2	
11N40MIMO/MCH_Ant1	

11N40MIMO/MCH_Ant2	
11N40MIMO/HCH_Ant1	
11N40MIMO/HCH_Ant2	


Appendix C): Band-edge for RF Conducted Emissions


Result Table


Mode	Antenna	Channel	Carrier Power[dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
11B	Ant1	LCH	10.824	-36.248	-19.18	PASS
11B	Ant2	LCH	11.611	-34.723	-18.39	PASS
11B	Ant1	HCH	11.247	-38.679	-18.75	PASS
11B	Ant2	HCH	11.252	-34.044	-18.75	PASS
11G	Ant1	LCH	3.736	-41.135	-26.26	PASS
11G	Ant2	LCH	4.870	-39.163	-25.13	PASS
11G	Ant1	HCH	4.854	-38.967	-25.15	PASS
11G	Ant2	HCH	3.889	-40.922	-26.11	PASS
11N20SISO	Ant1	LCH	2.864	-39.540	-27.14	PASS
11N20SISO	Ant2	LCH	3.150	-41.373	-26.85	PASS
11N20SISO	Ant1	HCH	3.412	-42.657	-26.59	PASS
11N20SISO	Ant2	HCH	2.357	-43.007	-27.64	PASS
11N20MIMO	Ant1	LCH	-0.247	-44.298	-30.25	PASS
11N20MIMO	Ant2	LCH	-0.408	-45.633	-30.41	PASS
11N20MIMO	Ant1	HCH	0.615	-46.919	-29.39	PASS
11N20MIMO	Ant2	HCH	0.560	-48.125	-29.44	PASS
11N40SISO	Ant1	LCH	-0.664	-34.204	-30.66	PASS
11N40SISO	Ant2	LCH	-0.998	-35.053	-31	PASS
11N40SISO	Ant1	HCH	-0.861	-43.027	-30.86	PASS
11N40SISO	Ant2	HCH	-1.160	-39.181	-31.16	PASS
11N40MIMO	Ant1	LCH	-3.722	-38.376	-33.72	PASS
11N40MIMO	Ant2	LCH	-3.812	-40.389	-33.81	PASS
11N40MIMO	Ant1	HCH	-3.879	-41.431	-33.88	PASS
11N40MIMO	Ant2	HCH	-4.476	-44.658	-34.48	PASS


Test Graph




















Appendix D): RF Conducted Spurious Emissions

Result Table

Mode	Antenna	Channel	Pref [dBm]	Puw[dBm]	Verdict
11B	Ant1	LCH	10.994	<Limit	PASS
11B	Ant2	LCH	11.882	<Limit	PASS
11B	Ant1	MCH	11.525	<Limit	PASS
11B	Ant2	MCH	11.551	<Limit	PASS
11B	Ant1	HCH	10.775	<Limit	PASS
11B	Ant2	HCH	11.324	<Limit	PASS
11G	Ant1	LCH	3.7	<Limit	PASS
11G	Ant2	LCH	4.851	<Limit	PASS
11G	Ant1	MCH	4.902	<Limit	PASS
11G	Ant2	MCH	4.301	<Limit	PASS
11G	Ant1	HCH	5.017	<Limit	PASS
11G	Ant2	HCH	3.676	<Limit	PASS
11N20SISO	Ant1	LCH	3.391	<Limit	PASS
11N20SISO	Ant2	LCH	3.111	<Limit	PASS
11N20SISO	Ant1	MCH	3.538	<Limit	PASS
11N20SISO	Ant2	MCH	3.646	<Limit	PASS
11N20SISO	Ant1	HCH	4.067	<Limit	PASS
11N20SISO	Ant2	HCH	3.487	<Limit	PASS
11N20MIMO	Ant1	LCH	-0.134	<Limit	PASS
11N20MIMO	Ant2	LCH	-0.384	<Limit	PASS
11N20MIMO	Ant1	MCH	0.378	<Limit	PASS
11N20MIMO	Ant2	MCH	0.383	<Limit	PASS
11N20MIMO	Ant1	HCH	0.031	<Limit	PASS
11N20MIMO	Ant2	HCH	0.791	<Limit	PASS
11N40SISO	Ant1	LCH	-0.597	<Limit	PASS
11N40SISO	Ant2	LCH	-0.971	<Limit	PASS
11N40SISO	Ant1	MCH	-0.846	<Limit	PASS
11N40SISO	Ant2	MCH	-0.811	<Limit	PASS
11N40SISO	Ant1	HCH	-0.842	<Limit	PASS
11N40SISO	Ant2	HCH	-0.976	<Limit	PASS
11N40MIMO	Ant1	LCH	-3.636	<Limit	PASS
11N40MIMO	Ant2	LCH	-3.701	<Limit	PASS
11N40MIMO	Ant1	MCH	-3.889	<Limit	PASS
11N40MIMO	Ant2	MCH	-4.037	<Limit	PASS
11N40MIMO	Ant1	HCH	-3.703	<Limit	PASS
11N40MIMO	Ant2	HCH	-3.583	<Limit	PASS

Test Graph

