

FCC REPORT

Applicant: Cellacom Incorporation

Address of Applicant: 20955 pathfinder road, suite 200 Diamond Bar, CA 91765

Equipment Under Test (EUT)

Product Name: Mobile Phone

Model No.: JM 10

Trade mark: Cellacom

FCC ID: 2AC343396993JM10

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 25 Nov., 2014

Date of Test: 25 Nov., to 09 Dec., 2014

Date of report issued: 10 Dec., 2014

Test Result: Pass *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	10 Dec., 2014	Original

Prepared by:

Yoyo Luo

Date:

10 Dec., 2014

Report Clerk

Reviewed by:

Atomb Yang

Date:

10 Dec., 2014

Project Engineer

3 Contents

Page

1	COVER PAGE.....	1
2	VERSION	2
3	CONTENTS	3
4	TEST SUMMARY.....	4
5	GENERAL INFORMATION.....	5
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF E.U.T.	5
5.3	TEST MODE.....	5
5.4	DESCRIPTION OF SUPPORT UNITS	6
5.5	LABORATORY FACILITY	6
5.6	LABORATORY LOCATION	6
5.7	TEST INSTRUMENTS LIST.....	7
6	TEST RESULTS AND MEASUREMENT DATA	8
6.1	CONDUCTED EMISSION.....	8
6.2	RADIATED EMISSION	11
7	TEST SETUP PHOTO	17
8	EUT CONSTRUCTIONAL DETAILS	18

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	Pass
Radiated Emission	Part15.109	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Cellacom Incorporation
Address of Applicant:	20955 pathfinder road, suite 200 Diamond Bar, CA 91765
Manufacturer:	Shenzhen Joinhold Communication Technology Ltd
Address of Manufacturer:	3F, Unit 3, Bldg. D2, TCL International E City, 1001 Zhongshanyuan Park Rd., Nanshan, Shenzhen, China

5.2 General Description of E.U.T.

Product Name:	Mobile Phone
Model No.:	JM 10
Power supply:	Rechargeable Li-ion Battery DC3.7V-1300mAh
AC adapter:	Input:100-240V AC,50/60Hz 0.15A Output: DC 5.0V, 750mA

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
MERCURY	Wireless router	MW150R	12922104015	FCC ID

5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

● **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China

Tel: 0755-23118282

Fax: 0755-23116366


5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	04-19-2014	04-19-2015
3	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	04-19-2014	04-19-2015
4	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
5	Amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	04-01-2014	03-31-2015
6	Amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	06-09-2014	06-08-2015
7	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	04-01-2014	03-31-2015
8	Horn Antenna	ETS-LINDGREN	3160	GTS217	03-31-2014	03-29-2015
9	Printer	HP	HP LaserJet P1007	N/A	N/A	N/A
10	Positioning Controller	UC	UC3000	CCIS0015	N/A	N/A
11	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP 30	CCIS0023	04-19-2014	04-19-2015
12	EMI Test Receiver	Rohde & Schwarz	ESRP7	CCIS0167	09-02-2014	09-01-2015
13	Loop antenna	Laplace instrument	RF300	EMC0701	04-01-2014	03-31-2015
14	Universal radio communication tester	Rhode & Schwarz	CMU200	CCIS0069	05-29-2014	05-28-2015
15	Signal Analyzer	Rohde & Schwarz	FSIQ3	CCIS0088	04-19-2014	04-19-2015

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	01-10-2014	04-09-2015
2	LISN	CHASE	MN2050D	CCIS0074	01-10-2014	04-09-2015
3	Coaxial Cable	CCIS	N/A	CCIS0086	04-01-2014	03-31-2015
4	EMI Test Software	AUDIX	E3	N/A	N/A	N/A


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part15 B Section 15.107																	
Test Method:	ANSI C63.4:2003																	
Test Frequency Range:	150kHz to 30MHz																	
Class / Severity:	Class B																	
Receiver setup:	RBW=9kHz, VBW=30kHz																	
Limit:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBμV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>0.5-30</td><td>60</td><td>50</td></tr></table>				Frequency range (MHz)	Limit (dBμV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	0.5-30	60	50
Frequency range (MHz)	Limit (dBμV)																	
	Quasi-peak	Average																
0.15-0.5	66 to 56*	56 to 46*																
0.5-5	56	46																
0.5-30	60	50																
Test setup:	<div><p style="text-align: center;">Reference Plane</p><p><i>Remark:</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p></div>																	
Test procedure	<div><div>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment.</div><div>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs).</div><div>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.</div></div>																	
Test environment:	Temp.:	23 °C	Humid.:	56%														
Measurement Record:	Press.:	1 01kPa	Uncertainty: 3.28dB															
Test Instruments:	Refer to section 5.7 for details																	
Test mode:	Refer to section 5.3 for details																	
Test results:	Passed																	

Measurement data:

Line:




Trace: 9

Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN LINE
 Job. no : 987RF
 EUT : Mobile Phone
 Model : JM 10
 Test Mode : PC mode
 Power Rating : AC120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: Carey
 Remark :

	Read	LISN	Cable	Limit	Over	
Freq	Level	Factor	Loss	Level	Line	Limit Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB
1	0.150	21.74	0.27	10.78	32.79	56.00 -23.21 Average
2	0.170	20.75	0.27	10.77	31.79	54.94 -23.15 Average
3	0.185	44.57	0.28	10.77	55.62	64.24 -8.62 QP
4	0.190	19.59	0.28	10.76	30.63	54.02 -23.39 Average
5	0.235	36.38	0.27	10.75	47.40	62.26 -14.86 QP
6	0.246	36.05	0.27	10.75	47.07	61.91 -14.84 QP
7	0.249	16.20	0.27	10.75	27.22	51.78 -24.56 Average
8	0.385	30.27	0.28	10.72	41.27	58.17 -16.90 QP
9	0.459	32.92	0.29	10.75	43.96	56.71 -12.75 QP
10	0.459	16.34	0.29	10.75	27.38	46.71 -19.33 Average
11	0.759	27.02	0.23	10.80	38.05	56.00 -17.95 QP
12	0.759	9.83	0.23	10.80	20.86	46.00 -25.14 Average

Neutral:





Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN NEUTRAL
 Job. no : 987RF
 EUT : Mobile Phone
 Model : JM 10
 Test Mode : PC mode
 Power Rating : AC120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: Carey
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.180	19.60	0.25	10.77	30.62	54.50	-23.88	Average
2	0.185	42.41	0.25	10.77	53.43	64.24	-10.81	QP
3	0.240	33.18	0.25	10.75	44.18	62.08	-17.90	QP
4	0.379	15.47	0.25	10.72	26.44	48.30	-21.86	Average
5	0.454	34.60	0.27	10.74	45.61	56.80	-11.19	QP
6	0.454	21.14	0.27	10.74	32.15	46.80	-14.65	Average
7	0.651	31.63	0.20	10.77	42.60	56.00	-13.40	QP
8	0.739	31.55	0.19	10.79	42.53	56.00	-13.47	QP
9	0.755	14.24	0.19	10.79	25.22	46.00	-20.78	Average
10	0.835	11.95	0.20	10.82	22.97	46.00	-23.03	Average
11	1.388	28.86	0.25	10.91	40.02	56.00	-15.98	QP
12	1.388	10.43	0.25	10.91	21.59	46.00	-24.41	Average

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

6.2 Radiated Emission


Test Requirement:	FCC Part15 B Section 15.109				
Test Method:	ANSI C63.4:2003				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
			74.0		Peak Value
Test setup:	Below 1GHz				
					
	Above 1GHz				
					

Test Procedure:	<div><div>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</div><div>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</div><div>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</div><div>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</div><div>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</div><div>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</div></div>					
Test environment:	Temp.:	25 °C	Humid.:	55%	Press.:	1 01kPa
Measurement Record:	Uncertainty: 4.88dB					
Test Instruments:	Refer to section 5.7 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Passed					

Measurement Data

Below 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) HORIZONTAL
 Job No. : 987RF
 EUT : Mobile Phone
 Model : JM 10
 Test mode : PC mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Carey
 REMARK :

	Freq	Read	Antenna	Cable	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	58.613	31.19	12.79	0.68	29.78	14.88	40.00	-25.12	QP
2	101.644	38.75	13.02	0.98	29.52	23.23	43.50	-20.27	QP
3	143.830	41.26	8.22	1.28	29.25	21.51	43.50	-21.99	QP
4	167.824	41.68	8.90	1.34	29.07	22.85	43.50	-20.65	QP
5	181.283	40.39	9.76	1.36	28.96	22.55	43.50	-20.95	QP
6	336.035	35.48	13.99	1.89	28.53	22.83	46.00	-23.17	QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL
 Job No. : 987RF
 EUT : Mobile Phone
 Model : JM 10
 Test mode : PC mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Carey
 REMARK :

	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	57.392	34.72	12.87	0.67	29.79	18.47	40.00	-21.53 QP
2	77.593	42.43	8.20	0.84	29.66	21.81	40.00	-18.19 QP
3	103.806	39.64	12.78	0.99	29.50	23.91	43.50	-19.59 QP
4	133.619	39.38	8.67	1.22	29.31	19.96	43.50	-23.54 QP
5	336.035	39.56	13.99	1.89	28.53	26.91	46.00	-19.09 QP
6	365.539	40.19	14.48	2.00	28.63	28.04	46.00	-17.96 QP

Above 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 Job No. : 987RF
 EUT : Mobile Phone
 Model : JM 10
 Test mode : PC mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Carey
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	3381.760	45.71	28.40	6.40	39.00	41.51	74.00	-32.49	Peak
2	3381.760	35.08	28.40	6.40	39.00	30.88	54.00	-23.12	Average
3	4223.122	46.71	30.24	8.05	40.93	44.07	74.00	-29.93	Peak
4	4223.122	36.27	30.24	8.05	40.93	33.63	54.00	-20.37	Average
5	5006.774	44.75	31.85	9.12	39.99	45.73	74.00	-28.27	Peak
6	5006.774	34.35	31.85	9.12	39.99	35.33	54.00	-18.67	Average

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 Job No. : 987RF
 EUT : Mobile Phone
 Model : JM 10
 Test mode : PC mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Carey
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	3646.072	47.22	29.21	6.45	40.39	42.49	74.00	-31.51	Peak
2	3646.072	37.81	29.21	6.45	40.39	33.08	54.00	-20.92	Average
3	4856.567	45.85	31.56	8.96	40.17	46.20	74.00	-27.80	Peak
4	4856.567	35.25	31.56	8.96	40.17	35.60	54.00	-18.40	Average
5	5505.541	47.25	32.04	9.16	40.26	48.19	74.00	-25.81	Peak
6	5505.541	37.26	32.04	9.16	40.26	38.20	54.00	-15.80	Average