Applicant/Grantee Seed Labs, Inc.				
FCC ID: 2AC30-SM41 Section 15.212 Modular Transmitters				
	Requirements	EUT Conditions	Comply (Y/N)	
	Single Modular	Approval Requirements		
1	The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	There is its own shielding on this module, please refer to the External Photo for the reference.	Y	
2	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.	This module has the buffered modulation/data input(s) function which is controlled by the component "CC2541".	Y	
3	The modular transmitter must have its own power supply regulation.	This module has its own power supply regulation which is controlled by the component "CC2541".	Y	
4	The modular transmitter must comply with the antenna and transmission system requirements of Sections 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of Section 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	The antenna type of this module is "w.FL RF connector for dipole antenna" which could comply with the FCC antenna requirement.	Y	
5	The modular transmitter must be tested in a stand-alone configuration, <i>i.e.</i> , the module must not be inside another device during testing for compliance with Part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting	This EUT is evaluated under the stand- alone configuration which the ancillary equipment (manufacturer: Seed Labs, Inc., model number: SM001), please refer to the Setup Photo for the reference.	Y	

	aguinment Any agassaries norinharals		
	equipment. Any accessories, peripherals,		
	or support equipment connected to the		
	module during testing shall be		
	unmodified and commercially available		
	(see Section 15.31(i)).		
6	The modular transmitter must be	The module complies with the	
	equipped with either a permanently	relevant labelling requirement,	Y
	affixed label or must be capable of	please refer to the Label and User	1
	electronically displaying its FCC	Manual for the reference.	
	identification number.		
	(A) If using a permanently affixed label, the		
	modular transmitter must be labeled with its own		
	FCC identification number, and, if the FCC		
	identification number is not visible when the		
	module is installed inside another device, then		
	the outside of the device into which the module is		
	installed must also display a label referring to		
	the enclosed module. This exterior label can use wording such as the following: "Contains		
	Transmitter Module		
	FCC ID: "XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX		
	"XXXXXXXXXX" Any similar wording		
	that expresses the same meaning may be used.		
	The Grantee may either provide such a label, an		
	example of which must be included in the		
	application for equipment		
	authorization, or, must provide adequate instructions along with the module which explain		
	this requirement. In the latter case, a copy of		
	these instructions must be included in the		
	application for equipment authorization.		
	(B) If the modular transmitter uses an electronic		
	display of the FCC identification number, the		
	information must be readily accessible and		
	visible on the modular transmitter or on the		
	device in which it is installed. If the module is installed inside another device, then the outside		
	of the device into which the module is installed		
	must display a label referring to the enclosed		
	module. This exterior label can use wording such		
	as the following:		
	"Contains FCC certified transmitter module(s)."		
	Any similar wording that expresses the same		
	meaning may be used. The user manual must include instructions on how to access the		
	electronic display. A copy of these instructions		
	must be included in the application for		
	equipment authorization.		
7	The modular transmitter must comply	The relevant required FCC rule has	
	with any specific rules or operating	been fulfilled and all the instructions	
	requirements that	for the maintaining compliance	Y
	ordinarily apply to a complete	have been clearly stated in the User	
	transmitter and the manufacturer must	Manual already.	
	provide adequate instructions along with	manual alleady.	
	-		
	the module to explain any such		
	requirements. A copy of these		
	instructions must be included in the		
	application for equipment authorization.		

The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.

This module meets the relevant RF exposure requirement, a SAR exemption evaluation report is submitted for this application.

Y

A **limited modular approval** may be granted for single or split modular transmitters that do not comply with all of the above requirements, *e.g.*, shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.

Sincerely,

(signture)

Szymon Slupik

President

Tel: +1 415 696 9111 Fax: +1 415 696 9111 E-mail: simon@seedlabs.io

620 Folsom St, San Francisco, CA 94107, USA