



Test Number: 450-19 Issue Date: 12/10/2019

6. Measurement Data (continued)

6.8. Public Exposure to Radio Frequency Energy Levels (15.247(i) (1.1307 (b)(1)) RSS-GEN, ISSUE 4 5.5, RSS 102)

6.8.1. 15.247(i) (1.1307 (b)(1) Requirements

Requirement: Portable devices are subject to radio frequency radiation exposure

requirements.

For a 1-g SAR, the test exclusion result must be \leq 3.0.

Test Notes: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at

test separation distances ≤ 50 mm are determined by the following

formula:

SAR Test Exclusion =
$$\frac{P_{MAX}}{d_{MIN}} \chi \sqrt{f_{(GHz)}}$$
 (1)

 P_{MAX} mW Maximum power of channel, including tune-up tolerance

d_{MIN} mm Minimum test separation distance, mm (≤ 50 mm)

 $f_{(GHz)}$ GHz $f_{(GHz)}$ is the RF channel transmit frequency in GHz (>100 MHz and <6 GHz)

(1) FCC OET 447498 - Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

Conclusion: Compliant - The device under test meets the exclusion requirement detailed in FCC OET 447498.

Input: P_{MAX}¹ (mW) 0.0004 d_{MIN} (mm) 5.0000

f_(GHz) 0.9150

Test Exclusion: 0.0001 Limit Exemption: 3.0000

6.8.2. RSS-102 Issue 5 Requirements

Requirement: SAR evaluation is required if the separation distance between the user

and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1. Portable devices are

subject to radio frequency radiation exposure requirements.

Test Notes: The limit was taken from Table 1 of RSS-102 Issue 5.

Frequency	Separation Distance	Maximum Power	RSS-102 Limit	Result
(MHz)	(mm)	(mW)	(mW)	
915.60	≤5	0.0004	16.24	Compliant

¹ Taken from column 5 of the table in Section 7.4 of this test report.