

# FCC Radio Test Report

## FCC ID: 2AC5EIW-6215BT

### Original Grant

**Report No.** : TB-FCC155827  
**Applicant** : HIGH HIT ENTERPRISE CO.,LTD.  
**Equipment Under Test (EUT)**  
**EUT Name** : WALL BLUETOOTH SPEAKER  
**Model No.** : IW-6215BT  
**Series Model No.** : Please see the page 4  
**Brand Name** : HIhits  
**Receipt Date** : 2017-06-15  
**Test Date** : 2017-06-16 to 2017-06-25  
**Issue Date** : 2017-06-26  
**Standards** : FCC Part 15: 2016, Subpart C(15.247)  
**Test Method** : ANSI C63.10: 2013  
**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,  
The EUT technically complies with the FCC requirements

**Test/Witness Engineer** :

Terry.Su

**Approved& Authorized** :

Feng Lai



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.



---

---

## Contents

<b>CONTENTS.....</b>	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT .....</b>	<b>4</b>
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test) .....	4
1.3 Block Diagram Showing the Configuration of System Tested.....	5
1.4 Description of Support Units .....	6
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting .....	7
1.7 Measurement Uncertainty .....	7
1.8 Test Facility.....	8
<b>2. TEST SUMMARY.....</b>	<b>9</b>
<b>3. TEST EQUIPMENT.....</b>	<b>10</b>
<b>4. CONDUCTED EMISSION TEST .....</b>	<b>11</b>
4.1 Test Standard and Limit.....	11
4.2 Test Setup.....	11
4.3 Test Procedure.....	11
4.4 EUT Operating Mode .....	12
4.5 Test Data.....	12
<b>5. RADIATED EMISSION TEST .....</b>	<b>17</b>
5.1 Test Standard and Limit.....	17
5.2 Test Setup.....	18
5.3 Test Procedure.....	19
5.4 EUT Operating Condition .....	19
5.5 Test Data.....	19
<b>6. RESTRICTED BANDS REQUIREMENT .....</b>	<b>40</b>
6.1 Test Standard and Limit.....	40
6.2 Test Setup.....	40
6.3 Test Procedure.....	40
6.4 EUT Operating Condition .....	41
6.5 Test Data.....	41
<b>7. NUMBER OF HOPPING CHANNEL .....</b>	<b>60</b>
7.1 Test Standard and Limit.....	60
7.2 Test Setup.....	60
7.3 Test Procedure.....	60
7.4 EUT Operating Condition .....	60
7.5 Test Data.....	60
<b>8. AVERAGE TIME OF OCCUPANCY.....</b>	<b>63</b>
8.1 Test Standard and Limit.....	63
8.2 Test Setup.....	63



---

8.3 Test Procedure.....	63
8.4 EUT Operating Condition .....	63
8.5 Test Data.....	64
<b>9. CHANNEL SEPARATION AND BANDWIDTH TEST .....</b>	<b>70</b>
9.1 Test Standard and Limit.....	70
9.2 Test Setup.....	70
9.3 Test Procedure.....	70
9.4 EUT Operating Condition .....	70
9.5 Test Data.....	71
<b>10. PEAK OUTPUT POWER TEST.....</b>	<b>83</b>
10.1 Test Standard and Limit .....	83
10.2 Test Setup.....	83
10.3 Test Procedure.....	83
10.4 EUT Operating Condition .....	83
10.5 Test Data.....	84
<b>11. ANTENNA REQUIREMENT.....</b>	<b>90</b>
11.1 Standard Requirement.....	90
11.2 Antenna Connected Construction .....	90
11.3 Result.....	90



# 1. General Information about EUT

## 1.1 Client Information

**Applicant** : HIGH HIT ENTERPRISE CO.,LTD.  
**Address** : 6F-3, NO.29-1, LANE 169, KANG-NING ST., SHI-CHIH CITY, TAIPEI  
 HSIEN, TAIWAN  
**Manufacturer** : HIGH HIT ELECTRONICS(SHENZHEN)CO.,LTD  
**Address** : BUILDING 25, AREA C, BUYONG INDUSTRIAL RD., SHAJING  
 TOWN, BAOAN ZONE, SHENZHEN, CHINA

## 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	WALL BLUETOOTH SPEAKER	
<b>Models No.</b>	:	IW-6215BT, IW-8215BT, IC-6215BT, IC8215BT, RBT-402, RBT-802, ROCK-RS4-BTL, ROCK-541-BTL, ROCK-621-BTL, ROCK-821-BTL, HP-5240AUBTO, HP-6250AUBTO, HP-4230AUBt	
<b>Model Difference</b>	:	All models are identical in the same PCB layout interior structure and electrical circuits, The only difference is model name for commercial purpose and output power.	
<b>Product Description</b>	:	Operation Frequency:	Bluetooth: 2402~2480 MHz
	:	Number of Channel:	Bluetooth: 79 Channels See Note 2
	:	Max Peak Output Power:	Bluetooth: 3.358dBm(GFSK)
	:	Antenna Gain:	0dBi PCB Antenna
	:	Modulation Type:	GFSK 1Mbps(1 Mbps) $\pi$ /4-DQPSK(2 Mbps) 8-DPSK(3 Mbps)
<b>Power Supply</b>	:	DC Voltage supplied by AC/DC Adapter	
<b>Power Rating</b>	:	AC/DC Adapter Model(ZF120-1502400) Input: AC 100V-24V 50Hz/60Hz 1.5A Output: DC 15V/2.4A	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	

### Note:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (2) Channel List:


Bluetooth Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456

01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	<b>39</b>	<b>2441</b>	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	<b>78</b>	<b>2480</b>
25	2427	52	2454		
26	2428	53	2455		


(3) The Antenna information about the equipment is provided by the applicant.

### 1.3 Block Diagram Showing the Configuration of System Tested

#### Normal Work + TX Mode



#### TX Mode





#### 1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/VOC	Manufacturer	Used “√”
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	NO	NO	5M	

#### 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Normal Work + TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX GFSK Mode
Mode 2	TX Mode(GFSK) Channel 00/39/78
Mode 3	TX Mode( $\pi/4$ -DQPSK) Channel 00/39/78
Mode 4	TX Mode(8-DPSK) Channel 00/39/78
Mode 5	Hopping Mode(GFSK)
Mode 6	Hopping Mode( $\pi/4$ -DQPSK)
Mode 7	Hopping Mode(8-DPSK)

**Note:**

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test modes above.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

TX Mode: GFSK (1 Mbps)

TX Mode:  $\pi/4$ -DQPSK (2 Mbps)

TX Mode: 8-DPSK (3Mbps)



- (2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

Test Software Version	N/A		
Frequency	2402 MHz	2441MHz	2480 MHz
GFSK	DEF	DEF	DEF
$\pi/4$ -DQPSK	DEF	DEF	DEF
8-DPSK	DEF	DEF	DEF

## 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	$\pm 3.42$ dB $\pm 3.42$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.40$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB



## 1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

### **CNAS (L5813)**

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### **FCC List No.: (811562)**

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

### **IC Registration No.: (11950A-1)**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.



## 2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 2				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203		Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.2	Conducted Emission	PASS	N/A
15.205	RSS-Gen 7.2.3	Restricted Bands	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (2)	Hopping Channel Separation	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (4)	Dwell Time	PASS	N/A
15.247(b)(1)	RSS 247 5.4 (2)	Peak Output Power	PASS	N/A
15.247(b)(1)	RSS 247 5.1 (4)	Number of Hopping Frequency	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(c)& 15.209	RSS 247 5.5	Radiated Spurious Emission	PASS	N/A
15.247(a)	RSS 247 5.1 (1)	99% Occupied Bandwidth & 20dB Bandwidth	PASS	99%OBW GFSK: 936.9131kHz $\pi$ /4-DQPSK: 1158.9kHz 8-DPSK:1161.1KHz
<b>Note:</b> N/A is an abbreviation for Not Applicable.				



### 3. Test Equipment

#### AC Main Conducted Emission

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	ROHDE& SCHWARZ	ESCI	100321	Jul. 22, 2016	Jul. 21, 2017
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 22, 2016	Jul. 21, 2017
L.I.S.N	Rohde & Schwarz	ENV216	101131	Jul. 22, 2016	Jul. 21, 2017
L.I.S.N	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 22, 2016	Jul. 21, 2017

#### Radiation Spurious Emission

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
EMI Test Receiver	Rohde & Schwarz	ESPI	10IW-6215BT0/007	Jul. 22, 2016	Jul. 21, 2017
Bilog Antenna	ETS-LINDGREN	3142E	IW-6215BT17537	Mar.25, 2017	Mar. 24, 2018
Horn Antenna	ETS-LINDGREN	3117	IW-6215BT43207	Mar.25, 2017	Mar. 24, 2018
Pre-amplifier	Sonoma	310N	185903	Mar.24, 2017	Mar. 23, 2018
Pre-amplifier	HP	8449B	3008A00849	Mar.24, 2017	Mar. 23, 2018
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.24, 2017	Mar. 23, 2018
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A

#### Antenna Conducted Emission

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
Spectrum Analyzer	Rohde & Schwarz	ESPI	100321	Jul. 22, 2016	Jul. 21, 2017



## 4. Conducted Emission Test

### 4.1 Test Standard and Limit

4.1.1 Test Standard  
FCC Part 15.207

4.1.2 Test Limit


**Conducted Emission Test Limit**

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) \*Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2 Test Setup



### 4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.



I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.


#### 4.4 EUT Operating Mode

Please refer to the description of test mode.


#### 4.5 Test Data

Test data please refer the following pages.





<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	USB Charging Mode		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1620	44.73	9.64	54.37	65.36	-10.99	QP
2		0.1620	15.71	9.64	25.35	55.36	-30.01	AVG
3		0.1860	41.27	9.65	50.92	64.21	-13.29	QP
4		0.1860	11.74	9.65	21.39	54.21	-32.82	AVG
5		0.2060	38.67	9.65	48.32	63.36	-15.04	QP
6		0.2060	10.09	9.65	19.74	53.36	-33.62	AVG
7		0.2300	35.69	9.63	45.32	62.45	-17.13	QP
8		0.2300	8.43	9.63	18.06	52.45	-34.39	AVG
9		0.6700	12.40	9.59	21.99	56.00	-34.01	QP
10		0.6700	-0.41	9.59	9.18	46.00	-36.82	AVG
11		18.9820	17.70	10.64	28.34	60.00	-31.66	QP
12		18.9820	4.62	10.64	15.26	50.00	-34.74	AVG

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 240V/60 Hz		
<b>Terminal:</b>	Line		
<b>Test Mode:</b>	USB Charging Mode		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1539	38.94	9.58	48.52	65.78	-17.26	QP
2		0.1539	7.25	9.58	16.83	55.78	-38.95	AVG
3		0.1780	35.83	9.58	45.41	64.57	-19.16	QP
4		0.1780	5.02	9.58	14.60	54.57	-39.97	AVG
5		0.2060	33.50	9.58	43.08	63.36	-20.28	QP
6		0.2060	4.00	9.58	13.58	53.36	-39.78	AVG
7		0.2540	28.79	9.59	38.38	61.62	-23.24	QP
8		0.2540	1.26	9.59	10.85	51.62	-40.77	AVG
9		2.4020	6.82	9.62	16.44	56.00	-39.56	QP
10		2.4020	-2.44	9.62	7.18	46.00	-38.82	AVG
11		22.6180	13.96	10.60	24.56	60.00	-35.44	QP
12		22.6180	0.35	10.60	10.95	50.00	-39.05	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 240V/60 Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	USB Charging Mode		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1660	38.26	9.64	47.90	65.15	-17.25	QP
2		0.1660	6.54	9.64	16.18	55.15	-38.97	AVG
3		0.1780	35.66	9.65	45.31	64.57	-19.26	QP
4		0.1780	4.99	9.65	14.64	54.57	-39.93	AVG
5		0.2100	33.03	9.64	42.67	63.20	-20.53	QP
6		0.2100	3.37	9.64	13.01	53.20	-40.19	AVG
7		0.2260	31.76	9.63	41.39	62.59	-21.20	QP
8		0.2260	3.64	9.63	13.27	52.59	-39.32	AVG
9		2.4340	8.31	9.63	17.94	56.00	-38.06	QP
10		2.4340	-2.05	9.63	7.58	46.00	-38.42	AVG
11		18.6379	17.87	10.64	28.51	60.00	-31.49	QP
12		18.6379	3.43	10.64	14.07	50.00	-35.93	AVG

Emission Level= Read Level+ Correct Factor



## 5. Radiated Emission Test

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard

FCC Part 15.209

#### 5.1.2 Test Limit

#### Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
Above 1000	74	54


**Note:**

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m)

## 5.2 Test Setup




**Below 30MHz Test Setup**



**Below 1000MHz Test Setup**





**Above 1GHz Test Setup**

### 5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

### 5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power in TX mode.

### 5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Test data please refer the following pages.


**9KHz~30MHz**

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

**30MHz~1GHz**

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		45.8553	40.91	-22.34	18.57	40.00	-21.43	QP
2	*	57.1914	55.67	-24.16	31.51	40.00	-8.49	QP
3		72.0843	37.92	-23.20	14.72	40.00	-25.28	QP
4		125.8864	40.63	-21.87	18.76	43.50	-24.74	QP
5		183.8440	41.13	-20.13	21.00	43.50	-22.50	QP
6		210.0482	51.98	-19.31	32.67	43.50	-10.83	QP

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**



<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	!	45.2166	57.75	-22.08	35.67	40.00	-4.33	QP
2	*	56.5929	60.03	-24.16	35.87	40.00	-4.13	QP
3		74.1351	50.50	-23.13	27.37	40.00	-12.63	QP
4		135.5062	46.97	-21.63	25.34	43.50	-18.16	QP
5		202.8104	53.79	-19.64	34.15	43.50	-9.35	QP
6	!	207.8501	58.37	-19.41	38.96	43.50	-4.54	QP

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**

**Above 1GHz(Only worse case is reported)**

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25℃	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4804.514	30.10	13.44	43.54	54.00	-10.46	AVG
2		4804.780	43.69	13.44	57.13	74.00	-16.87	peak

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25℃	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		4803.522	43.56	13.44	57.00	74.00	-17.00 peak
2	*	4803.772	30.35	13.44	43.79	54.00	-10.21 AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4881.792	30.34	13.90	44.24	54.00	-9.76	AVG
2		4882.106	43.78	13.90	57.68	74.00	-16.32	peak

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4881.492	30.08	13.90	43.98	54.00	-10.02	AVG
2		4882.196	43.24	13.90	57.14	74.00	-16.86	peak

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4960.394	30.64	14.36	45.00	54.00	-9.00	AVG
2		4960.506	44.34	14.36	58.70	74.00	-15.30	peak

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4959.648	44.09	14.36	58.45	74.00	-15.55	peak
2	*	4960.780	30.87	14.36	45.23	54.00	-8.77	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4804.238	30.84	13.44	44.28	54.00	-9.72	AVG
2		4805.461	42.82	13.45	56.27	74.00	-17.73	peak

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25℃	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4804.272	43.82	13.44	57.26	74.00	-16.74	peak
2	*	4805.372	31.15	13.45	44.60	54.00	-9.40	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4881.736	42.86	13.90	56.76	74.00	-17.24	peak
2	*	4883.627	31.31	13.92	45.23	54.00	-8.77	AVG

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25℃	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4881.235	31.33	13.90	45.23	54.00	-8.77	AVG
2		4882.672	42.37	13.90	56.27	74.00	-17.73	peak

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4960.752	41.77	14.36	56.13	74.00	-17.87	peak
2	*	4961.034	29.79	14.37	44.16	54.00	-9.84	AVG

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25℃	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4960.174	42.87	14.36	57.23	74.00	-16.77	peak
2	*	4960.237	30.91	14.36	45.27	54.00	-8.73	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4803.356	30.10	13.44	43.54	54.00	-10.46	AVG
2		4803.886	41.96	13.44	55.40	74.00	-18.60	peak

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25℃	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4803.438	43.23	13.44	56.67	74.00	-17.33	peak
2	*	4804.072	30.03	13.44	43.47	54.00	-10.53	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4881.368	43.26	13.90	57.16	74.00	-16.84	peak
2	*	4882.108	30.13	13.90	44.03	54.00	-9.97	AVG

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25℃	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4881.538	43.76	13.90	57.66	74.00	-16.34	peak
2	*	4881.948	30.23	13.90	44.13	54.00	-9.87	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4959.516	30.72	14.36	45.08	54.00	-8.92	AVG
2		4959.784	44.08	14.36	58.44	74.00	-15.56	peak

Emission Level= Read Level+ Correct Factor



<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4959.778	45.08	14.36	59.44	74.00	-14.56	peak
2	*	4960.870	30.66	14.36	45.02	54.00	-8.98	AVG

Emission Level= Read Level+ Correct Factor

## 6. Restricted Bands Requirement

### 6.1 Test Standard and Limit

#### 6.1.1 Test Standard

FCC Part 15.209


FCC Part 15.205

#### 6.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

**Note: All restriction bands have been tested, only the worst case is reported.**

### 6.2 Test Setup



### 6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.



- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with AVG Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

#### 6.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.


#### 6.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

All restriction bands have been tested, only the worst case is reported.

**(1) Radiation Test**

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	55.51	0.77	56.28	74.00	-17.72	peak
2		2390.000	32.35	0.77	33.12	54.00	-20.88	AVG
3	X	2401.900	91.27	0.82	92.09	Fundamental Frequency		peak
4	*	2402.100	87.09	0.82	87.91	Fundamental Frequency		AVG

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	43.84	0.77	44.61	74.00	-29.39	peak
2		2390.000	32.95	0.77	33.72	54.00	-20.28	AVG
3	*	2402.100	90.04	0.82	90.86	Fundamental Frequency		AVG
4	X	2402.200	94.32	0.82	95.14	Fundamental Frequency		peak

**Emission Level= Read Level+ Correct Factor**


<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2480 MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2479.900	85.56	1.15	86.71	Fundamental Frequency		AVG
2	X	2480.000	89.74	1.15	90.89	Fundamental Frequency		peak
3		2483.500	64.11	1.17	65.28	74.00	-8.72	peak
4		2483.500	47.43	1.17	48.60	54.00	-5.40	AVG

Emission Level= Read Level+ Correct Factor





<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	50.05	0.77	50.82	74.00	-23.18	peak
2		2390.000	30.45	0.77	31.22	54.00	-22.78	AVG
3	X	2402.100	87.96	0.82	88.78	Fundamental Frequency		peak
4	*	2402.100	82.39	0.82	83.21	Fundamental Frequency		AVG

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	50.54	0.77	51.31	74.00	-22.69	peak
2		2390.000	30.45	0.77	31.22	54.00	-22.78	AVG
3	X	2402.200	91.77	0.82	92.59	Fundamental Frequency		peak
4	*	2402.200	86.09	0.82	86.91	Fundamental Frequency		AVG

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2480MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2480.000	80.88	1.15	82.03	Fundamental Frequency		AVG
2	X	2480.200	86.42	1.15	87.57	Fundamental Frequency		peak
3		2483.500	58.42	1.17	59.59	74.00	-14.41	peak
4		2483.500	44.43	1.17	45.60	54.00	-8.40	AVG

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2480MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2480.000	84.28	1.15	85.43	Fundamental Frequency		AVG
2	X	2480.200	90.01	1.15	91.16	Fundamental Frequency		peak
3		2483.500	69.27	1.17	70.44	74.00	-3.56	peak
4		2483.500	47.39	1.17	48.56	54.00	-5.44	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	56.01	0.77	56.78	74.00	-17.22	peak
2		2390.000	33.84	0.77	34.61	54.00	-19.39	AVG
3	X	2402.000	90.93	0.82	91.75	Fundamental Frequency		peak
4	*	2402.000	85.38	0.82	86.20	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		2390.000	56.37	0.77	57.14	74.00	-16.86 peak
2		2390.000	34.20	0.77	34.97	54.00	-19.03 AVG
3	X	2402.100	93.88	0.82	94.70	Fundamental Frequency	peak
4	*	2402.100	88.18	0.82	89.00	Fundamental Frequency	AVG

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.900	89.35	1.15	90.50	Fundamental Frequency		peak
2	*	2480.100	83.49	1.15	84.64	Fundamental Frequency		AVG
3		2483.500	64.62	1.17	65.79	74.00	-8.21	peak
4		2483.500	47.57	1.17	48.74	54.00	-5.26	AVG

**Emission Level= Read Level+ Correct Factor**



<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	Only worse case is reported		





No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2479.800	88.65	1.15	89.80	Fundamental Frequency		AVG
2	X	2480.000	93.82	1.15	94.97	Fundamental Frequency		peak
3		2483.500	63.07	1.17	64.24	74.00	-9.76	peak
4		2483.500	47.56	1.17	48.73	54.00	-5.27	AVG

Emission Level= Read Level+ Correct Factor



## (2) Conducted Test

EUT:	WALL BLUETOOTH SPEAKER	Model Name :	IW-6215BT
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX GFSK Mode 2402MHz/2480 MHz		
Remark:	Only worse case is reported		







EUT:	WALL BLUETOOTH SPEAKER	Model Name :	IW-6215BT
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	GFSK Hopping Mode		
Remark:	Only worse case is reported		





EUT:	WALL BLUETOOTH SPEAKER	Model Name :	IW-6215BT
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX $\pi$ /4-DQPSK Mode 2402MHz/2480 MHz		
Remark:	Only worse case is reported		







EUT:	WALL BLUETOOTH SPEAKER	Model Name :	IW-6215BT
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	$\pi$ /4-DQPSK Hopping Mode		
Remark:	Only worse case is reported		





<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz/2480 MHz		
<b>Remark:</b>	Only worse case is reported		





EUT:	WALL BLUETOOTH SPEAKER	Model Name :	IW-6215BT
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	8-DPSK Hopping Mode		
Remark:	Only worse case is reported		



## 7. Number of Hopping Channel

### 7.1 Test Standard and Limit


#### 6.1.1 Test Standard

FCC Part 15.247 (a)(1)

#### 6.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

### 7.2 Test Setup



### 7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100 KHz, VBW=100 KHz, Sweep time= Auto.

### 7.4 EUT Operating Condition



The EUT was set to the Hopping Mode by the Customer.


### 7.5 Test Data



EUT:	WALL BLUETOOTH SPEAKER	Model Name :	IW-6215BT
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	Hopping Mode		
Frequency Range	Test Mode	Quantity of Hopping Channel	Limit
2402MHz~2480MHz	GFSK	79	>15
	$\pi$ /4-DQPSK	79	
	8-DPSK	79	

## GFSK Mode

 $\pi$  /4-DQPSK Mode






## 8. Average Time of Occupancy

### 8.1 Test Standard and Limit

- 8.1.1 Test Standard  
FCC Part 15.247 (a)(1)
- 8.1.2 Test Limit

Section	Test Item	Limit
15.247(a)(1)/ RSS 247 Issue 2	Average Time of Occupancy	0.4 sec

### 8.2 Test Setup



### 8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=1MHz.
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.

### 8.4 EUT Operating Condition

The average time of occupancy on any channel within the Period can be calculated with formulas:

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / X) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$
$$\{\text{Period}\} = 0.4s * \{\text{Number of Hopping Frequency}\}$$

Note: X=2 or 4 or 6 (1DH1=2, 1DH3=4, 1DH5=6. 2DH1=2, 2DH3=4, 2DH5=6. 3DH1=2,3DH3=4, 3DH5=6)

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

The EUT was set to the Hopping Mode by the Customer.

## 8.5 Test Data

EUT:		WALL BLUETOOTH SPEAKER		Model Name :		IW-6215BT	
Temperature:		25℃		Relative Humidity:		55%	
Test Voltage:		DC 3.7V					
Test Mode:		Hopping Mode (GFSK)					
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result	
1DH1	2441	0.40	128.00	31.60	400	PASS	
1DH3	2441	1.65	264.00	31.60	400	PASS	
1DH5	2441	2.91	310.40	31.60	400	PASS	

1DH1 Total of Dwell= Pulse Time\*(1600/2)\*31.6/79

1DH3 Total of Dwell= Pulse Time\*(1600/4)\*31.6/79

1DH5 Total of Dwell= Pulse Time\*(1600/6)\*31.6/79

GFSK Hopping Mode 1DH1

2441 MHz

Agilent

10:59:49 Jun 25, 2017

Ref 20 dBm

Atten 30 dB

Mkr1 Δ 400 μs 1.522 dB

Peak Log 10 dB/Offst 1 dB

Marker Δ 400.000000 μs 1.522 dB

W1 S2 S3 VS AA

Center 2.441 GHz

Res BW 1 MHz

#VBW 1 MHz

Span 0 Hz

Sweep 4 ms (401 pts)

Marker

Select Marker 1 2 3 4

Normal

Delta

Delta Pair (Tracking Ref) Ref Delta

Span Pair Span Center


Off

More 1 of 2




### GFSK Hopping Mode 1DH3

2441 MHz



### GFSK Hopping Mode 1DH5

2441 MHz









$\pi/4$ -DQPSK Hopping Mode 2DH3

2441 MHz



$\pi/4$ -DQPSK Hopping Mode 2DH5


2441 MHz



EUT:	WALL BLUETOOTH SPEAKER			Model Name :	IW-6215BT	
Temperature:	25°C			Relative Humidity:	55%	
Test Voltage:	DC 3.7V					
Test Mode:	Hopping Mode (8-DQPSK)					
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
3DH1	2441	0.40	128.00	31.60	400	PASS
3DH3	2441	1.65	264.00	31.60	400	PASS
3DH5	2441	2.91	310.40	31.60	400	PASS
3DH1 Total of Dwell= Pulse Time*(1600/2)*31.6/79						
3DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79						
3DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79						

### 8-DQPSK Hopping Mode 3DH1


2441 MHz






### 8-DQPSK Hopping Mode 3DH3

2441 MHz



### 8-DQPSK Hopping Mode 3DH5

2441 MHz



## 9. Channel Separation and Bandwidth Test

### 9.1 Test Standard and Limit

9.1.1 Test Standard  
FCC Part 15.247

9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	$\leq 1$ MHz (20dB bandwidth)	2400~2483.5
Channel Separation	$>25\text{KHz}$ or $>\text{two-thirds}$ of the 20 dB bandwidth Which is greater	2400~2483.5

### 9.2 Test Setup



### 9.3 Test Procedure


- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Channel Separation: RBW=100 kHz, VBW=100 kHz.  
Bandwidth: RBW=30 kHz, VBW=100 kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:30 kHz, and Video Bandwidth:100 kHz. Sweep Time set auto.

### 9.4 EUT Operating Condition

The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.




## 9.5 Test Data

<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode (GFSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	844.8752	942.101	
2441	842.2100	939.605	
2480	936.9131	934.069	
<b>GFSK TX Mode</b>			
<b>2402 MHz</b>			
 <p>Agilent 09:54:09 Jun 25, 2017</p> <p>Ch Freq 2.402 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Center 2.40200000 GHz</p> <p>Ref 10 dBm Atten 20 dB</p> <p>#Peak Log 10 dB/Offst 1 dB</p> <p>Center 2.402 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 844.8752 kHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -20.00 dB</p> <p>Transmit Freq Error -43.000 Hz</p> <p>x dB Bandwidth 942.101 kHz</p> <p>Freq/Channel</p> <p>Center Freq 2.40200000 GHz</p> <p>Start Freq 2.40050000 GHz</p> <p>Stop Freq 2.40350000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>			


GFSK TX Mode

2441 MHz




GFSK TX Mode

2480 MHz






<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode ( $\pi$ /4-DQPSK)		
<b>Channel frequency (MHz)</b>	<b>99% OBW (kHz)</b>	<b>20dB Bandwidth (kHz)</b>	<b>20dB Bandwidth *2/3 (kHz)</b>
2402	1158.9	1253	835.33
2441	1158.0	1245	830.00
2480	1152.4	1255	836.67
<b><math>\pi</math> /4-DQPSK TX Mode</b>			
<b>2402 MHz</b>			
			


$\pi$  /4-DQPSK TX Mode

2441 MHz



$\pi$  /4-DQPSK TX Mode

2480 MHz






<b>EUT:</b>	WALL BLUETOOTH SPEAKER	<b>Model Name :</b>	IW-6215BT
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode (8-DPSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	1158.5	1273	848.67
2441	1161.1	1268	845.33
2480	1152.3	1272	848.00


**8-DPSK TX Mode**

**2402 MHz**




### 8-DPSK TX Mode

2441 MHz




### 8-DPSK TX Mode


2480 MHz









**GFSK Hopping Mode**  
**2441 MHz**



**GFSK Hopping Mode**  
**2480 MHz**









$\pi$  /4-DQPSK Hopping Mode

2441 MHz




$\pi$  /4-DQPSK Hopping Mode

2480 MHz









### 8-DPSK Hopping Mode

2441 MHz



### 8-DPSK Hopping Mode

2480 MHz





## 10. Peak Output Power Test

### 10.1 Test Standard and Limit

#### 10.1.1 Test Standard

FCC Part 15.247 (b) (1)

#### 10.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

### 10.2 Test Setup




### 10.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.  
RBW=3 MHz, VBW=3 MHz for bandwidth more than 1MHz.

### 10.4 EUT Operating Condition


The EUT was set to continuously transmitting in the max power during the test.

## 10.5 Test Data







**GFSK TX Mode**  
**2441 MHz**




**GFSK TX Mode**  
**2480 MHz**








$\pi$  /4-DQPSK TX Mode  
 2441 MHz



$\pi$  /4-DQPSK TX Mode  
 2480 MHz



EUT:	WALL BLUETOOTH SPEAKER	Model Name :	IW-6215BT
Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX Mode (8-DPSK)		
Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)	
2402	2.500	21	
2441	3.123		
2480	3.305		
8-DPSK TX Mode			
2402 MHz			

Agilent10:08:53 Jun 25, 2017

Ref 20 dBmAtten 30 dB

Mkr1 2.4021250 GHz2.5 dBm

Peak Log 10 dB/Offst 1 dB

Center 2.402000000 GHz

M1 S2 S3 FC AA

Center 2.402 GHz#Res BW 3 MHz#VBW 3 MHzSweep 5 ms (401 pts)Span 5 MHz

Freq/Channel

Center Freq 2.40200000 GHz

Start Freq 2.39950000 GHz

Stop Freq 2.40450000 GHz

CF Step 500.000000 kHzAutoMan


Freq Offset 0.00000000 Hz

Signal Track OnOff


Scale Type LogLin



**8-DPSK TX Mode**  
**2441 MHz**



**8-DPSK TX Mode**  
**2480 MHz**



## 11. Antenna Requirement

### 11.1 Standard Requirement

#### 11.1.1 Standard

FCC Part 15.203

#### 11.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 11.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 0dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

### 11.3 Result

The EUT antenna is a PCB Antenna. It complies with the standard requirement.

Antenna Type	
<input checked="" type="checkbox"/>	Permanent attached antenna
<input type="checkbox"/>	Unique connector antenna
<input type="checkbox"/>	Professional installation antenna

-----END OF REPORT-----