

# **FCC ID:2AC6K-SP020**

## **RF EXPOSURE EVALUATION**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>300-1500</b>	--	--	<b>F/300</b>	<b>6</b>
<b>1500-1000000</b>	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>300-1500</b>	--	--	<b>F/1500</b>	<b>6</b>
<b>1500-1000000</b>	--	--	<b>1</b>	<b>30</b>

### **11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$**

Where

$P_d$ = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in mW

$G$ = Numeric gain of the antenna relative to isotropic antenna

$\pi$ =3.1416

$R$ = distance between observation point and center of the radiator in cm(20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

$mW = 10^{(dBm/10)}$

## 11.2 Measurement Result

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,  
802.11n HT40: 2422-2452MHz,  
Power density limited:  $1\text{mW}/\text{cm}^2$   
Antenna Type: Internal Antenna  
Antenna gain: 2.0dBi,  
R=20cm  
 $\text{mW}=10^{(\text{dBm}/10)}$   
802.11b/g/n:

Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
2412	802.11b	15.49	11.9	12±1	13	1.59	0.006291	1
2437	802.11b	18.20	12.6	12±1	13	1.59	0.006291	1
2462	802.11b	16.98	12.3	12±1	13	1.59	0.006291	1
2412	802.11g	7.59	8.8	9±1	10	1.59	0.003153	1
2437	802.11g	9.33	9.7	9±1	10	1.59	0.003153	1
2462	802.11g	9.55	9.8	9±1	10	1.59	0.003153	1
2412	802.11n H20	6.76	8.3	9±1	10	1.59	0.003153	1
2437	802.11n H20	9.55	9.8	9±1	10	1.59	0.003153	1
2462	802.11n H20	9.33	9.7	9±1	10	1.59	0.003153	1
2422	802.11n H40	8.13	9.1	9±1	10	1.59	0.003153	1
2437	802.11n H40	8.51	9.3	9±1	10	1.59	0.003153	1
2452	802.11n H40	8.71	9.4	9±1	10	1.59	0.003153	1

emission

Power density Limits (mW/cm <sup>2</sup> ) WIFI	Calculate Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
0.006291	0.006291	1

### Conclusion:

For the max result :  $0.006291 \leq 1.0$ , compliance with FCC's RF Exposure.

Jason chen

Signature:

Date: 2017-7-10

NAME AND TITLE (Please print or type): Jason Chen/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.