

RF Exposure

TUV SUD BABT TCB

Octagon House, Segensworth Road, Fareham, Hampshire, PO15 5RL

Date: Nov. 4, 2014

ATTN: Reviewing Engineer

RF exposure information for the equipment SMART LOCK (FCC ID: 2AC8KSLUSV1, IC: 12350A-SLUSV1)

Model: SMART LOCK

1. Introduction:

The device SMART LOCK (FCC ID: 2AC8KSLUSV1, IC: 12350A-SLUSV1) is designed to be used in portable exposure conditions.

This product integrates a Bluetooth Low Energy transmitter operated in the 2.4 GHz frequency band.

2. Output power considerations:

Bluetooth Low Energy transmitter: 0.59 dBm (1.15 mW) Conducted / 5.09 dBm (3.23 mW) eirp

3. Compliance criteria:

Transmitter is deeded to comply with FCC § 2.1093 requirements and IC RSS-102 Issue 4 as the output power of the device meets the conditions specified in section 4.3.1 (SAR test exclusion) considerations of the document "KDB 447498 D01 General RF Exposure Guidance v05r02" and .in section 2.5.1 (Exemption from Routine Evaluation Limits – SAR Evaluation) of RSS-104 Issue 4.

Sincerely,

Gabrielle de Lavigne

Chief Financial Officer