

# **FCC Test Report**

FCC ID : 2ACAHTVA3

Equipment : TV Adapter

Model No. : TVA3

Applicant : SBO Hearing A/S

Address : Kongebakken 9 DK-2765 Smoerum, Denmark

Standard : 47 CFR FCC Part 15.247

Received Date : Apr. 25, 2016

Tested Date : Apr. 25 ~ May 04, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

ilac MRA



Report No.: FR642501AE Report Version: Rev. 02



# **Table of Contents**

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	
1.3	Test Setup Chart	
1.4	Test Equipment List and Calibration Data	
1.5	Test Standards	
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS	11
3.1	Conducted Emissions	11
3.2	6dB and Occupied Bandwidth	14
3.3	RF Output Power	
3.4	Power Spectral Density	18
3.5	Emissions in Restricted Frequency Bands	20
3.6	Emissions in non-restricted Frequency Bands	30
4	TEST LABORATORY INFORMATION	33



# **Release Record**

Report No.	Version	Description	Issued Date
FR642501AE	Rev. 01	Initial issue	May 24, 2016
FR642501AE	Rev. 02	Modified HW version / SW version description (page 5.)	May 26, 2016

Report No.: FR642501AE Page: 3 of 33



# **Summary of Test Results**

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 0.195MHz 60.40 (Margin -3.40dB) - QP	Pass
15.247(d)	Radiated Emissions	[dBuV/m at 3m]: 47.46MHz	Pass
15.209	Radiated Effissions	32.90 (Margin -7.10dB) - PK	Fd55
15.247(b)(3)	Maximum Output Power	Power [dBm]: 5.54	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Report No.: FR642501AE Page: 4 of 33



#### **General Description** 1

#### Information 1.1

#### 1.1.1 **Specification of the Equipment under Test (EUT)**

RF General Information							
Frequency Range Bluetooth (MHz) Ch. Freq. (MHz) Channel Number Da							
2400-2483.5	V4.2 LE	2402-2480	0-39 [40]	1 Mbps			

Note 1: Bluetooth LE (Low energy) uses GFSK modulation. Note 2: HW version: B3 / SW version: 0.9.3

### 1.1.2 Antenna Details

Ant. No.	Туре	Connector	Gain (dBi)	Remarks
1	Metal plate	3.2	N/A	

# 1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type
-------------------

Report No.: FR642501AE Page: 5 of 33



## 1.1.4 Accessories

No.	Equipment	Description
1	AC adapter	Brand Name: PHIHONG Model Name: A M05A-050A-R I/P: 100-240Vac, 50-60Hz, 0.2A O/P: 5Vdc, 1A Power Line: 1.82m non-shielded without core
2	AC adapter	Brand Name: PHIHONG Model Name: PSAC05R-050T1 I/P: 100-240Vac, 300mA, 50-60Hz, 12-18VA O/P: 5Vdc, 1A Power Line: 1.81m non-shielded without core

## 1.1.5 Channel List

	Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
37	2402	9	2422	18	2442	28	2462	
0	2404	10	2424	19	2444	29	2464	
1	2406	38	2426	20	2446	30	2466	
2	2408	11	2428	21	2448	31	2468	
3	2410	12	2430	22	2450	32	2470	
4	2412	13	2432	23	2452	33	2472	
5	2414	14	2434	24	2454	34	2474	
6	2416	15	2436	25	2456	35	2476	
7	2418	16	2438	26	2458	36	2478	
8	2420	17	2440	27	2460	39	2480	

# 1.1.6 Test Tool and Duty Cycle

Test tool	NebulaDeveloper, ver. 0.9.3
Duty cycle of test signal (%)	62.96%
Duty Factor (dB)	2.01

Report No.: FR642501AE Page: 6 of 33




# 1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)			
Modulation Mode	2402	2440	2480	
GFSK/1Mbps	Default	Default	Default	

# 1.2 Local Support Equipment List

Support Equipment List							
No. Equipment Brand Model FCC ID Signal cable / Length (n					Signal cable / Length (m)		
1	DVD player	SONY	BDP-S190	3224521	Audio, 1.2m non-shielded		
2	Notebook	DELL	Latitude E6430	F2JB4X1	Fiber, 1.6m non-shielded		

# 1.3 Test Setup Chart



Note: The support notebook was disconnected from EUT and removed from test table when EUT is set to transmit continuously.

Report No.: FR642501AE Page: 7 of 33



# 1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission								
Test Site	Conduction room 1 /	Conduction room 1 / (CO01-WS)							
Instrument	Manufacturer Model No. Serial No. Calibration Date Calibration Until								
EMC Receiver	R&S	ESCS 30	100169	Oct. 21, 2015	Oct. 20, 2016				
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 13, 2015	Nov. 12, 2016				
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Nov. 26, 2015	Nov. 25, 2016				
RF Cable-CON	EMC	EMCCFD300-BM-BM-6000	50821	Dec. 21, 2015	Dec. 20, 2016				
50 ohm terminal (Support Unit)	NA	50	04	Apr. 12, 2016	Apr. 11, 2017				
Measurement Software	AUDIX	e3	6.120210k	NA	NA				
Note: Calibration Int	erval of instruments lis	ted above is one year.							

Test Item	Radiated Emission					
Test Site	966 chamber 3 / (036	CH03-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until	
Spectrum Analyzer	Agilent	N9010A	MY53400091	Sep. 14, 2015	Sep. 13, 2016	
Receiver	Agilent	N9038A	MY53290044	Oct. 14, 2015	Oct. 13, 2016	
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-562	Nov. 16, 2015	Nov. 15, 2016	
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 24, 2016	Feb. 23, 2017	
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2015	Nov. 03, 2016	
Loop Antenna	R&S	HFH2-Z2	11900	Nov. 16, 2015	Nov. 15, 2016	
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 10, 2015	Dec. 09, 2016	
Preamplifier	EMC	EMC02325	980187	Sep. 21, 2015	Sep. 20, 2016	
Preamplifier	Agilent	83017A	MY53270014	Sep. 07, 2015	Sep. 06, 2016	
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016	
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 05, 2016	Feb. 04, 2017	
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22600/4	Feb. 05, 2016	Feb. 04, 2017	
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 05, 2016	Feb. 04, 2017	
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-00 1	Feb. 05, 2016	Feb. 04, 2017	
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Feb. 05, 2016	Feb. 04, 2017	
LF cable-13M	EMC	EMC8D-NM-NM-1300 0	131104	Feb. 05, 2016	Feb. 04, 2017	
Measurement Software	AUDIX	e3	6.120210g	NA	NA	
Note: Calibration Inte	erval of instruments lis	sted above is one year.				

Report No.: FR642501AE Page: 8 of 33



Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2016	Feb. 16, 2017
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
DC POWER SOURCE	GW INSTEK	GPC-3060D	EM884797	Oct. 20, 2015	Oct. 19, 2016
AC POWER SOURCE	APC	AFC-500W	F312060012	Oct. 26, 2015	Oct. 25, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

## 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247 ANSI C63.10-2013 FCC KDB 558074 D01 DTS Meas Guidance v03r05

# 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty				
Parameters	Uncertainty			
Bandwidth	±34.134 Hz			
Conducted power	±0.808 dB			
Power density	±0.463 dB			
Conducted emission	±2.670 dB			
AC conducted emission	±2.90 dB			
Radiated emission ≤ 1GHz	±3.66 dB			
Radiated emission > 1GHz	±5.37 dB			

Report No.: FR642501AE Page: 9 of 33



# 2 Test Configuration

# 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	21°C / 60%	Howard Huang
Radiated Emissions	03CH03-WS	24°C / 62%	Allen Yu
RF Conducted	TH01-WS	22°C / 63%	Alex Huang

➤ FCC site registration No.: 207696➤ IC site registration No.: 10807C-1

## 2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions	BT LE	2440	1Mbps	
Radiated Emissions ≤ 1GHz	BT LE	2440	1Mbps	
Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	
Maximum Output Power				
6dB bandwidth	BT LE	2402, 2440, 2480	1Mbps	
Power spectral density				

### NOTE:

1. Two adapters (model A M05A-050A-R and model PSAC05R-050T1) had been covered during the pretest, and found that model **PSAC05R-050T1** was the worst case and was selected for final test.

2. S/N of test samples are as below 00J9999651454 00J9999651412 00J9999651415

3. S/N of test adapter is P160303352A1

Report No.: FR642501AE Page: 10 of 33



# 3 Transmitter Test Results

### 3.1 Conducted Emissions

### 3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit				
Frequency Emission (MHz) Quasi-Peak Average				
0.15-0.5	66 - 56 *	56 - 46 *		
0.5-5	56	46		
5-30 60 50				
Note 1: * Decreases with the logarithm of the frequency.				

#### 3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V/60Hz

### 3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR642501AE Page: 11 of 33




#### **Test Result of Conducted Emissions** 3.1.4



Report No.: FR642501AE Page: 12 of 33





Report No.: FR642501AE Page: 13 of 33



# 3.2 6dB and Occupied Bandwidth

#### 3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

#### 3.2.2 Test Procedures


#### 6dB Bandwidth

- 1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
- 2. Detector = Peak, Trace mode = max hold.
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

### **Occupied Bandwidth**

- 1. Set resolution bandwidth (RBW) = 30 kHz, Video bandwidth = 100 kHz.
- 2. Detector = Sample, Trace mode = max hold.
- 3 Sweep = auto couple, Allow the trace to stabilize.
- 4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

### 3.2.3 Test Setup




Report No.: FR642501AE Page : 14 of 33



# 3.2.4 Test Result of 6dB and Occupied Bandwidth

Mode	Freq. (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit of 6dB Bandwidth (kHz)
BT LE	2402	0.722	1.07	500
BT LE	2440	0.730	1.06	500
BT LE	2480	0.730	1.06	500



Report No.: FR642501AE Page: 15 of 33



# 3.3 RF Output Power

### 3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.

Antenna gain <= 6dBi, no any corresponding reduction is in output power limit.

Antenna gain > 6dBi

Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB

Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

#### 3.3.2 Test Procedures

Maximum Peak Conducted Output Power

#### 

- 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
- 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
- 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.

#### Nower meter

- A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Average Output Power (For reference only)

#### Nower meter

 A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

## 3.3.3 Test Setup



Report No.: FR642501AE Page: 16 of 33



# 3.3.4 Test Result of Maximum Output Power

			Peak Power		Antenna	EIRP	EIRP
Mode	Freq. (MHz)	Power (mW)	Power (dBm)	Limit (dBm)	gain (dBi)	(dBm)	Limit (dBm)
BT LE	2402	1.92	2.84	30	3.2	6.04	36
BT LE	2440	3.58	5.54	30	3.2	8.74	36
BT LE	2480	2.41	3.82	30	3.2	7.02	36

Mode	Freq. (MHz)	AV Power (mW)	AV Power (dBm)	Limit (dBm)
BT LE	2402	1.81	2.58	
BT LE	2440	3.48	5.41	
BT LE	2480	2.18	3.39	

Note: Average power is for reference only

Report No.: FR642501AE Page: 17 of 33



# 3.4 Power Spectral Density


### 3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

#### 3.4.2 Test Procedures

- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
  - Set the RBW = 3kHz, VBW = 10kHz.
  - Detector = Peak, Sweep time = auto couple.
  - 3. Trace mode = max hold, allow trace to fully stabilize.
  - 4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
  - 1. Set the RBW = 100kHz, VBW = 300 kHz.
  - 2. Detector = RMS, Sweep time = auto couple.
  - 3. Perform the measurement over a single sweep.
  - 4. Use the peak marker function to determine the maximum amplitude level.

### 3.4.3 Test Setup




Report No.: FR642501AE Page: 18 of 33



# 3.4.4 Test Result of Power Spectral Density

Mode	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BT LE	2402	-13.07	8
BT LE	2440	-10.32	8
BT LE	2480	-12.22	8



Report No.: FR642501AE Page: 19 of 33



## 3.5 Emissions in Restricted Frequency Bands

### 3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit						
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)			
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300			
0.490~1.705	24000/F(kHz)	33.8 - 23	30			
1.705~30.0	30	29	30			
30~88	100	40	3			
88~216	150	43.5	3			
216~960	200	46	3			
Above 960	500	54	3			

#### Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2**:

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

#### 3.5.2 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

#### Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR642501AE Page: 20 of 33




# 3.5.3 Test Setup



Report No.: FR642501AE Page: 21 of 33



## 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR642501AE Page: 22 of 33





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR642501AE Page: 23 of 33



## 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR642501AE Page: 24 of 33



Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	38.64	54.00	-15.36	39.74	-1.10	Average	366	13
2	2390.00	50.45	74.00	-23.55	51.55	-1.10	Peak	366	13
3	4804.00	36.83	54.00	-17.17	31.58	5.25	Average	387	81
4	4804.00	45.58	74.00	-28.42	40.33	5.25	Peak	387	81
5	12010.00	42.19	54.00	-11.81	27.12	15.07	Average	100	165
6	12010.00	54.37	74.00	-19.63	39.30	15.07	Peak	100	165

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR642501AE Page: 25 of 33



Modulation Polarization			GFSK					Test Fr	eq. (MHz)	2440		
			Horizontal									
	90	Level	(dBuV/m)									
	80										FCC CLAS	SS-B
	70											
	60									FCC	CLASS-B (A	AVG)
	50	1	4		8							1
				6 I								
	40			4	1							
	30			<u> </u>								
	-											
	20											
	10											
	0	1000	4000.	60	00. 8	000. 100	000. 1200	0. 14000.	16000. 180	000. 20000.	22000.	25000
							Frequ	ency (MHz	)			
			Freq.	Em:	issio	n Limit	Margi	n SA	Factor	Remark	ANT	Turn
					level			readin			High	Table
			MHz	dl	BuV/m	dBuV/	m dB	dBuV	dB		cm	deg
1	L		2390.6	00	38.71	54.00	-15.29	39.82	-1.10	Average	100	210
2							-23.35			Peak	100	210
3	3		2483.5	0	38.89	54.00	-15.11	39.56	-0.61	Average	100	210
4							-22.57			Peak	100	210
5							-20.61			Average		310
6							-29.63			Peak	100	310
7			7320.6	90	35.44	54.00	-18.56	25.17	7 10.27	Average	100	210

38.78

10.27

Peak

100

210

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


7320.00 49.05 74.00 -24.95

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR642501AE Page: 26 of 33



Modulation	GFSK	Test Freq. (MHz)	2440					
Polarization	Vertical							
Level (dRu)	(Inn)							



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m		SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.62	54.00	-15.38	39.72	-1.10	Average	388	314
2	2390.00	51.82	74.00	-22.18	52.92	-1.10	Peak	388	314
3	2483.50	39.01	54.00	-14.99	39.62	-0.61	Average	388	314
4	2483.50	51.42	74.00	-22.58	52.03	-0.61	Peak	388	314
5	4880.00	37.91	54.00	-16.09	32.48	5.43	Average	394	80
6	4880.00	46.64	74.00	-27.36	41.21	5.43	Peak	394	80
7	7320.00	36.48	54.00	-17.52	26.21	10.27	Average	100	136
8	7320.00	49.58	74.00	-24.42	39.31	10.27	Peak	100	136

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR642501AE Page: 27 of 33



Modulation Polarization			GF	GFSK				Test Freq. (MHz)					2480		
			Horizontal												
	90	Level	(dBuV/m)												
	80														
	70										+			FCC CLAS	S-B
	70														
	60	1	2								+		FCC CI	LASS-B (A	WG)
	50				6										
	40	.													
	40														
	30														
	20										_				
	10														
	10														
	0	1000	4000.	6000.	8000.	100	00. 120	00. 14 iency (		16000. 1	8000	. 200	000. 2	2000.	25000
			Frea.	Emissi	on L	imit			A .	Facto	r	Rema	ark	ANT	Turn
				leve					ding					High	Tabl
			MHz	dBuV/	m dl	BuV/n	ı dB	dl	BuV	dB				cm	deg
	1		2483.56	39.3	9 5	4.00	-14.61	46	0.00	-0.6	1	Aver	rage	125	267
	2		2483.50				-18.83		.78	-0.6	1	Peak	_	125	267
	3		4960.00				-17.09		.33	5.6			rage	100	302
	4		4960.00		_				.60	5.6		Peak		100	302
	5 6		7440.00						3.80 3.82	10.5 10.5		Aver Peak	_	100 100	125 125

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR642501AE Page: 28 of 33

Report Version: Rev. 02



Modulation GI	GFSK	Test Freq. (MHz)	2480		
<b>Polarization</b> Ve	/ertical				



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2/63 20	39.80	54.00	14 20	40.41	-0.61	Average	387	20
1	2403.30	39.00	34.00	-14.20	40.41	-0.01	Average	307	20
2	2483.50	60.81	74.00	-13.19	61.42	-0.61	Peak	387	20
3	4960.00	41.19	54.00	-12.81	35.57	5.62	Average	314	81
4	4960.00	48.84	74.00	-25.16	43.22	5.62	Peak	314	81
5	7440.00	37.89	54.00	-16.11	27.33	10.56	Average	100	350
6	7440.00	49.67	74.00	-24.33	39.11	10.56	Peak	100	350

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR642501AE Page: 29 of 33



# 3.6 Emissions in non-restricted Frequency Bands

## 3.6.1 Emissions in non-restricted frequency bands limit

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

### 3.6.2 Test Procedures


#### Reference Level Measurement

- 1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Set Sweep time = auto couple, Trace mode = max hold.
- 3. Allow trace to fully stabilize.
- 4. Use the peak marker function to determine the maximum amplitude level.

#### **Unwanted Emissions Level Measurement**

- 1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Trace Mode = max hold, Sweep = auto couple.
- 3. Allow the trace to stabilize.
- 4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.


### 3.6.3 Test Setup




Report No.: FR642501AE Page: 30 of 33



## 3.6.4 Test Result of Emissions in non-restricted Frequency Bands



Report No.: FR642501AE Page: 31 of 33



Report No.: FR642501AE Page: 32 of 33



# 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan,

R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C. Kwei Shan Site II

Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

<u>==END</u>==

Report No.: FR642501AE Page: 33 of 33