

FCC RADIO TEST REPORT

FCC ID: 2ACAZQD-100BT-WT

Product : Tablet PC

Trade Name :



Model Name : QD-100BT-WT

Serial Model : N/A

Prepared for

KBX GROUP

Avenida 1ra, Calle B y C manzana 58, France Field Colon Panama

Prepared by

DongGuan Precise Testing Service Co.,Ltd.

Room 203-204, 2F, Xinye Building, No.67 Shijing, Guanzhang
Road, Dongguan, China

TEST RESULT CERTIFICATION

Applicant's name KBX GROUP
Address Avenida 1ra, Calle B y C manzana 58, France Field Colon Panama
Manufacture's Name KBX GROUP
Address Avenida 1ra, Calle B y C manzana 58, France Field Colon Panama

Product description

Product name Tablet PC
Model and/or type QD-100BT-WT
reference
Serial Model : N/A

Standards FCC Part15.247

Test procedure ANSI C63.4-2003

This device described above has been tested by PTS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTS, this document may be altered or revised by PTS, personal only, and shall be noted in the revision of the document.


Date of Test

Date (s) of performance of tests Jul. 16, 2014 ~ Jul. 29, 2014

Date of Issue Jul. 29, 2014

Test Result **Pass**

Testing Engineer :



Assistant

Technical Manager :



Supervisor

Authorized Signatory :



Jacky Ou / Manager

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	10
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3 . EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
3.1.2 TEST PROCEDURE	15
3.1.3 DEVIATION FROM TEST STANDARD	15
3.1.4 TEST SETUP	15
3.1.5 EUT OPERATING CONDITIONS	15
3.1.6 TEST RESULTS	16
3.2 RADIATED EMISSION MEASUREMENT	18
3.2.1 RADIATED EMISSION LIMITS	18
3.2.2 TEST PROCEDURE	19
3.2.3 DEVIATION FROM TEST STANDARD	19
3.2.4 TEST SETUP	20
3.2.5 EUT OPERATING CONDITIONS	21
3.2.6 TEST RESULTS (BELOW 30 MHZ)	22
3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)	23
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	24
4 . NUMBER OF HOPPING CHANNEL	43
4.1 APPLIED PROCEDURES / LIMIT	43
4.1.1 TEST PROCEDURE	43
4.1.2 DEVIATION FROM STANDARD	43
4.1.3 TEST SETUP	43
4.1.4 EUT OPERATION CONDITIONS	43
4.1.5 TEST RESULTS	44
5 . AVERAGE TIME OF OCCUPANCY	45

Table of Contents

	Page
5.1 APPLIED PROCEDURES / LIMIT	45
5.1.1 TEST PROCEDURE	45
5.1.2 DEVIATION FROM STANDARD	45
5.1.3 TEST SETUP	46
5.1.4 EUT OPERATION CONDITIONS	46
5.1.5 TEST RESULTS	47
6 . HOPPING CHANNEL SEPARATION MEASUREMENT	53
6.1 APPLIED PROCEDURES / LIMIT	53
6.1.1 TEST PROCEDURE	53
6.1.2 DEVIATION FROM STANDARD	53
6.1.3 TEST SETUP	53
6.1.4 EUT OPERATION CONDITIONS	53
6.1.5 TEST RESULTS	54
7 . BANDWIDTH TEST	60
7.1 APPLIED PROCEDURES / LIMIT	60
7.1.1 TEST PROCEDURE	60
7.1.2 DEVIATION FROM STANDARD	60
7.1.3 TEST SETUP	60
7.1.4 EUT OPERATION CONDITIONS	60
7.1.5 TEST RESULTS	61
8 . PEAK OUTPUT POWER TEST	67
8.1 APPLIED PROCEDURES / LIMIT	67
8.1.1 TEST PROCEDURE	67
8.1.2 DEVIATION FROM STANDARD	67
8.1.3 TEST SETUP	67
8.1.4 EUT OPERATION CONDITIONS	67
8.1.5 TEST RESULTS	68
9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	74
9.1 APPLICABLE STANDARD	74
9.2 TEST PROCEDURE	74
9.2.1 DEVIATION FROM STANDARD	74
TEST SETUP	74
9.2.2 EUT OPERATION CONDITIONS	74

Table of Contents

	Page
9.2.3 TEST RESULTS	75
10 . ANTENNA REQUIREMENT	82
10.1 STANDARD REQUIREMENT	82
10.2 EUT ANTENNA	82
11 . EUT TEST PHOTO	83
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1


1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Tablet PC	
Trade Name		
Model Name	QD-100BT-WT	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a Tablet PC.	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	BT EDR, BT 3.0: GFSK, $\Pi/4$ -DQPSK, 8-DPSK
	Number Of Channel	79CH
	Bit Rate of Transmitter	1Mbps/2Mbps/3Mbps
	Antenna Designation:	Please see Note 3.
	Antenna Gain(Peak)	0dBi
Channel List	Please refer to the Note 2.	
Adapter	MODEL: SWI10-W0502000A INPUT: AC 100-240V , 50/60Hz, 0.4A OUTPUT: 5.0V \equiv 2.0A	
Battery	DC 3.7V, 4300mAh	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Integral Antenna	N/A	0	

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	TX Mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	TX Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The data rate was set in 3Mbps for radiated emission due to the highest RF output power.


2.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS


Test software Version	Test program: Broadcom		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1/2/3Mbps)	DEF	DEF	DEF

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

For conducted emission test:




For radiated emission test:



2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Tablet PC		QD-100BT-WT	N/A	EUT
E-2	Adapter	N/A	SWI10-W0502000A	N/A	N/A
E-3	Notebook	Sony	PCG-51111T	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.85m	
C-2	NO	NO	0.85m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2014.07.06	2015.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.06	2015.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2014.07.06	2015.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2013.12.22	2014.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2014.07.06	2015.07.05	1 year
12	Spectrum Analyzer	R&S	FSP	1165.439141	2014.05.13	2015.05.12	1 year
13	RF cable	PTS	40 CM	N/A	2014.07.01	2015.06.30	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2014.06.06	2015.06.05	1 year
2	LISN	R&S	ENV216	101313	2013.08.24	2014.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2013.08.24	2014.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2014.06.07	2015.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.07	2015.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year
7	Coaxial cable	PTS	200 CM	N/A	2014.07.01	2015.06.30	1 year

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.6 TEST RESULTS


EUT :	Tablet PC	Model Name. :	QD-100BT-WT
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V From Adapter AC 120/60Hz	Test Mode :	Mode 4

Freq MHz	Reading dBuV	Factor dB	Result dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Phase
0.52	48.68	1.30	49.98	56.00	-6.02	Peak	LINE
1.42	42.98	1.32	44.30	56.00	-11.70	Peak	LINE
2.50	46.26	1.34	47.60	56.00	-8.40	Peak	LINE
6.35	40.33	1.36	41.69	60.00	-18.31	Peak	LINE



EUT :	Tablet PC	Model Name. :	QD-100BT-WT
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V form Adapter AC 120V/60Hz	Test Mode :	Mode 4

Freq MHz	Reading dBuV	Factor dB	Result dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Phase
0.55	42.55	1.30	43.85	56.00	-12.15	Peak	NEUTRAL
0.74	37.70	1.31	39.01	56.00	-16.99	Peak	NEUTRAL
2.57	39.27	1.34	40.61	56.00	-15.39	Peak	NEUTRAL
6.73	37.00	1.36	38.36	60.00	-21.64	Peak	NEUTRAL



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


3.2.3 DEVIATION FROM TEST STANDARD

No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz

5.2 Block Diagram of Test Setup




Below 30MHz

(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BELOW 30 MHZ)

EUT :	Tablet PC	Model Name. :	QD-100BT-WT
Temperature :	20 °C	Relative Humidity:	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	Mode 4	Polarization :	---

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log (\text{specific distance/test distance})(\text{dB})$;

Limit line = specific limits(dBuv) + distance extrapolation factor.

3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)

Worst case: GFSK DH5 CHANNEL 39

EUT :	Tablet PC	Model Name. :	QD-100BT-WT
Temperature :	25 °C	Relative Humidity :	48%
Pressure :	1010hPa	Test Mode :	Mode 4
Test Voltage :	DC 5V FROM LAPTOP		

Polar (H/V)	Frequen cy	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Vertical	35.85	20.14	14.80	34.94	40.00	-5.06	QP
Vertical	47.56	24.87	10.55	35.42	40.00	-4.58	QP
Vertical	65.36	30.74	5.39	36.13	40.00	-3.87	QP
Vertical	100.56	24.67	10.51	35.18	43.50	-8.32	QP
Vertical	174.21	23.78	10.84	34.62	43.50	-8.88	QP
Vertical	600.24	13.78	23.53	37.31	46.00	-8.69	QP
Horizontal	33.78	14.13	18.04	32.17	40.00	-7.83	QP
Horizontal	61.21	21.37	5.98	27.35	40.00	-12.65	QP
Horizontal	165.45	24.35	11.76	36.11	43.50	-7.39	QP
Horizontal	199.48	25.33	8.97	34.30	43.50	-9.20	QP
Horizontal	271.20	23.41	14.59	38.00	46.00	-8.00	QP
Horizontal	577.49	13.24	23.14	36.38	46.00	-9.62	QP


3.2.8 TEST RESULTS (ABOVE 1000 MHZ)



EUT :	Tablet PC	Model Name. :	QD-100BT-WT
Temperature :	25 °C	Relative Humidity :	55%
Pressure :	1010hPa	Test Mode :	Mode 4
Test Mode :	DC 5V FROM LAPTOP		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Frequency:2402MHz							
V	4804.21	55.34	-3.64	51.70	74	-22.30	peak
V	7208.54	43.74	-0.95	42.79	74	-31.21	peak
H	4804.58	53.74	-3.64	50.10	74	-23.90	peak
H	7208.26	44.16	-0.95	43.21	74	-30.79	peak
Frequency:2441MHz							
V	4880.85	54.37	-3.67	50.70	74	-23.30	peak
V	7324.39	50.17	-0.82	49.35	74	-24.65	peak
H	4880.28	53.47	-3.68	49.79	74	-24.21	peak
H	7320.36	46.37	-0.82	45.55	74	-28.45	peak
Frequency:2480MHz							
V	4960.16	54.37	-3.59	50.78	74	-23.22	peak
V	7440.44	50.37	-0.68	49.69	74	-24.31	peak
H	4960.36	55.16	-3.59	51.57	74	-22.43	peak
H	7440.37	46.37	-0.68	45.69	74	-28.31	peak
Remark:							
Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit							



Note: Mode 3Mbps is the worst mode.


Conducted Spurious Emissions at Antenna Port: CH00 -1Mbps





CH39 -1Mbps







CH78 -1Mbps



*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -3.68 dBm
SWT 300 ms 2.480220000 GHz




*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -43.45 dBm
SWT 1.2 s 15.720000000 GHz






*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -43.45 dBm
SWT 1 s 15.72000000 GHz




CH00 -2Mbps



*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -3.69 dBm
SWT 300 ms 2.402000000 GHz




*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -44.26 dBm
SWT 1.2 s 14.208000000 GHz








*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -42.65 dBm
SWT 1 s 25.00000000 GHz





CH39 -2Mbps






CH78 -2Mbps








*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -43.65 dBm
SWT 1 s 21.80000000 GHz



CH00 -3Mbps







CH39 -3Mbps




*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -2.45 dBm
SWT 300 ms 2.441640000 GHz



*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -44.39 dBm
SWT 1.2 s 14.040000000 GHz






CH78 -3Mbps




*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -3.69 dBm
SWT 300 ms 2.480220000 GHz






*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -43.41 dBm
SWT 1.2 s 18.860000000 GHz



*RBW 100 kHz Marker 1 (T1)
*VBW 300 kHz -43.41 dBm
SWT 1 s 18.860000000 GHz



4. NUMBER OF HOPPING CHANNEL

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥ 15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW =100kHz
VB	VBW \geq RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100kHz, VBW=300kHz, Sweep time = Auto.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP




4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	Hopping Mode		

Number of Hopping Channel	79
---------------------------	----



5. AVERAGE TIME OF OCCUPANCY

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS


5.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- A Period Time = (channel number)*0.4
 DH1 Time Slot: Reading * (1600/2)*31.6/(channel number)
 DH3 Time Slot: Reading * (1600/4)*31.6/(channel number)
 DH5 Time Slot: Reading * (1600/6)*31.6/(channel number)

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP




5.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	25.5 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	CH39-DH5,2DH5,3DH5		


Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH5	2441 MHz	2.95	0.314	0.4000
2DH5	2441 MHz	2.94	0.315	0.4000
3DH5	2441 MHz	2.95	0.314	0.4000






EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	26.3 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	CH39-DH3,2DH3,3DH3		


Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH3	2441 MHz	1.71	0.278	0.4000
2DH3	2441 MHz	1.70	0.276	0.4000
3DH3	2441 MHz	1.72	0.278	0.4000






EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	26 °C	Relative Humidity :	55.5%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	CH39-DH1,2DH1,3DH1		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2441 MHz	0.6125	0.138	0.4000
2DH1	2441 MHz	0.6124	0.138	0.4000
3DH1	2441 MHz	0.5953	0.135	0.4000





6. HOPPING CHANNEL SEPARATION MEASUREMENT

6.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


6.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS


The EUT was programmed to be in continuously transmitting mode.


6.1.5 TEST RESULTS

EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	26.3 °C	Relative Humidity :	55.6%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	CH00 / CH39 /CH78 (1Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.011	Complies
2441 MHz	1.021	Complies
2480 MHz	1.000	Complies

Ch. Separation Limits: >20dB bandwidth







EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	26.2 °C	Relative Humidity :	56.5%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	CH00 / CH39 /CH78 (2Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.013	Complies
2441 MHz	1.152	Complies
2480 MHz	1.010	Complies

Ch. Separation Limits: >2/3 of 20dB bandwidth





Agilent

R T

Ref 10 dBm #Atten 10 dB Ext PG -15 dB

Peak Log 10 dB/

Mkr1 Δ -1.010 MHz
-0.779 dBm

Center 2.479 GHz
Res BW 30 kHz

#VBW 100 kHz

Span 3 MHz
Sweep 5 ms (401 pts)

Marker

Select Marker 1 2 3 4

Normal

Delta

Delta Pair (Tracking Ref)
Ref Delta

Span Pair
Span Center


Off



More 1 of 2

EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	25.9 °C	Relative Humidity :	56.5%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	CH00 / CH39 /CH78 (3Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.021	Complies
2441 MHz	1.185	Complies
2480 MHz	1.011	Complies

Ch. Separation Limits: >2/3 of 20dB bandwidth





7. BANDWIDTH TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


7.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP




7.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 TEST RESULTS

EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	25.6 °C	Relative Humidity :	55.8%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	CH00 / CH39 /C78(1Mbps)		


Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	885.805	PASS
2441 MHz	935.625	PASS
2480 MHz	946.511	PASS






EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	CH00 / CH39 /C78(2Mbps)		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.335	PASS
2441 MHz	1.336	PASS
2480 MHz	1.224	PASS





Agilent
R T

Ch Freq 2.48 GHz
Trig Free

Occupied Bandwidth

Ref 20 dBm
#Atten 20 dB
Ext PG -10 dB

#Peak
Log
10
dB/



Center 2.48 GHz
Span 3 MHz


#Res BW 100 kHz
#VBW 300 kHz
Sweep 5 ms (401 pts)


Occupied Bandwidth	Occ BW % Pwr	99.00%
1.1896 MHz	x dB	-20.00 dB
Transmit Freq Error	-882.135 Hz	
x dB Bandwidth	1.354 MHz	

 Trace/View
 Trace 1 2 3
 Clear Write
 Max Hold
 Min Hold
 View
 Blank
 More 1 of 2

EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	CH00 / CH39 /C78(3Mbps)		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.265	PASS
2441 MHz	1.216	PASS
2480 MHz	1.262	PASS





Agilent
R T

Ch Freq 2.48 GHz
Trig Free

Occupied Bandwidth

Ref 20 dBm Atten 20 dB Ext PG -10 dB
 #Peak
 Log
 10
 dB/



Center 2.48 GHz
Span 3 MHz

#Res BW 30 kHz
#VBW 100 kHz
Sweep 5 ms (401 pts)

Occupied Bandwidth Occ BW % Pwr 99.00%

1.1415 MHz

Transmit Freq Error 5.168 kHz x dB -20.00 dB

x dB Bandwidth 1.262 MHz

 Trace/View
 Trace 1 2 3
 Clear Write
 Max Hold
 Min Hold
 View
 Blank
 More 1 of 2

8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	0.125 w or 1w	2400-2483.5	PASS


8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured
 Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 VBW ≥ RBW
 Sweep = auto
 Detector function = peak
 Trace = max hold

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP




8.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


8.1.5 TEST RESULTS


EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	25.3 °C	Relative Humidity :	55.6%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP
Test Mode :	CH00/ CH39 /CH78 (1M/2M/3Mbps Mode)		


1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	0.542	30
CH39	2441	0.937	30
CH78	2480	0.912	30
2Mbps			
CH00	2402	-0.211	20.96
CH39	2441	-0.050	20.96
CH78	2480	-0.320	20.96
3Mbps			
CH00	2402	-0.403	20.96
CH39	2441	0.358	20.96
CH78	2480	0.247	20.96














9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

9.1 APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


9.2 TEST PROCEDURE

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

9.2.1 DEVIATION FROM STANDARD

No deviation.

TEST SETUP



9.2.2 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.2.3 TEST RESULTS



EUT :	Tablet PC	Model Name :	QD-100BT-WT
Temperature :	24.8 °C	Relative Humidity :	55.6%
Pressure :	1015 hPa	Test Voltage :	DC 5V FROM LAPTOP

Frequency Band	Delta Peak to band emission(Non-FHSS) (dBc)	Delta Peak to band emission(FHSS) (dBc)	> Limit (dBc)	Result
1Mbps				
Left-band	53.87	55.96	20	Pass
Right-band	50.13	49.25	20	Pass
2Mbps				
Left-band	50.88	52.38	20	Pass
Right-band	48.77	48.79	20	Pass
3Mbps				
Left-band	50.80	51.95	20	Pass
Right-band	51.53	51.22	20	Pass



Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
1Mbps(Non-FHSS)							
2390	57.38	-13.06	44.32	74	-29.68	peak	Vertical
2390	57.99	-13.06	44.93	74	-29.07	peak	Horizontal
2483.5	59.14	-12.78	46.36	74	-27.64	peak	Vertical
2483.5	57.68	-12.78	44.90	74	-29.10	peak	Horizontal
2Mbps(Non-FHSS)							
2390	58.68	-13.06	45.62	74	-28.38	peak	Vertical
2390	58.66	-13.06	45.60	74	-28.40	peak	Horizontal
2483.5	58.46	-12.78	45.68	74	-28.32	peak	Vertical
2483.5	57.68	-12.78	44.90	74	-29.10	peak	Horizontal
3Mbps(Non-FHSS)							
2390	60.23	-13.06	47.17	74	-26.83	peak	Vertical
2390	61.35	-13.06	48.29	74	-25.71	peak	Horizontal
2483.5	60.35	-12.78	47.57	74	-26.43	peak	Vertical
2483.5	59.15	-12.78	46.37	74	-27.63	peak	Horizontal

Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit, average didn't record.



1Mbps: Band Edge, Left Side





1Mbps: Band Edge, Right Side





2Mbps: Band Edge, Left Side





2Mbps: Band Edge, Right Side



3Mbps: Band Edge, Left Side



3Mbps: Band Edge, Right Side



10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA


The EUT antenna is Built-in antenna. It comply with the standard requirement.

11. EUT TEST PHOTO

Radiated Measurement Photos



CONDUCTED EMISSION Photo



END OF REPORT