

# FCC TEST REPORT

## (PART 24)

**REPORT NO.:** RF150727C28-5

**MODEL NO.:** GT7820 & GT7810 & GT7800 & GT78

**FCC ID:** 2ACC5-GT78

**RECEIVED:** Jul. 27, 2015

**TESTED:** Jul. 29, 2015 ~ Jul. 31, 2015

**ISSUED:** Aug. 13, 2015

**APPLICANT:** AMobile Intelligent Corp.

**ADDRESS:** 18F-1, No 150, Jianyi Road, Zhonghe District, New Taipei City, Taiwan R.O.C

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan ( R.O.C. )

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

## TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	3
1 CERTIFICATION .....	4
2 SUMMARY OF TEST RESULTS.....	5
2.1 MEASUREMENT UNCERTAINTY .....	5
2.2 TEST SITE AND INSTRUMENTS .....	6
3 GENERAL INFORMATION .....	7
3.1 GENERAL DESCRIPTION OF EUT.....	7
3.2 CONFIGURATION OF SYSTEM UNDER TEST .....	9
3.3 DESCRIPTION OF SUPPORT UNITS.....	10
3.4 TEST ITEM AND TEST CONFIGURATION .....	10
3.5 EUT OPERATING CONDITIONS.....	12
3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	12
4 TEST TYPES AND RESULTS.....	13
4.1 OUTPUT POWER MEASUREMENT .....	13
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT .....	13
4.1.2 TEST PROCEDURES .....	13
4.1.3 TEST SETUP .....	14
4.1.4 TEST RESULTS .....	15
4.2 FREQUENCY STABILITY MEASUREMENT .....	17
4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT .....	17
4.2.2 TEST PROCEDURE .....	17
4.2.3 TEST SETUP .....	17
4.2.4 TEST RESULTS .....	18
4.3 OCCUPIED BANDWIDTH MEASUREMENT .....	19
4.3.1 TEST PROCEDURES .....	19
4.3.2 TEST SETUP .....	19
4.3.3 TEST RESULTS .....	20
4.4 PEAK TO AVERAGE RATIO.....	21
4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT .....	21
4.4.2 TEST SETUP .....	21
4.4.3 TEST PROCEDURES .....	21
4.4.4 TEST RESULTS .....	22
4.5 BAND EDGE MEASUREMENT .....	23
4.5.1 LIMITS OF BAND EDGE MEASUREMENT .....	23
4.5.2 TEST SETUP .....	23
4.5.3 TEST PROCEDURES .....	23
4.5.4 TEST RESULTS .....	24
4.6 CONDUCTED SPURIOUS EMISSIONS .....	25
4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT.....	25
4.6.2 TEST PROCEDURE .....	25
4.6.3 TEST SETUP .....	25
4.6.4 TEST RESULTS .....	25
4.7 RADIATED EMISSION MEASUREMENT .....	26
4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	26
4.7.2 TEST PROCEDURES .....	26
4.7.3 DEVIATION FROM TEST STANDARD .....	26
4.7.4 TEST SETUP .....	27
4.7.5 TEST RESULTS .....	28
5 PHOTOGRAPHS OF THE TEST CONFIGURATION .....	36
6 INFORMATION ON THE TESTING LABORATORIES .....	37
7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	38



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF150727C28-5	Original release	Aug. 13, 2015



A D T

## 1 CERTIFICATION

**PRODUCT:** Rugged Android Tablet

**MODEL:** GT7820 & GT7810 & GT7800 & GT78

**BRAND:** Amobile

**APPLICANT:** AMobile Intelligent Corp.

**TESTED:** Jul. 29, 2015 ~ Jul. 31, 2015

**TEST SAMPLE:** Identical Prototype

**STANDARDS:** FCC Part 24, Subpart E

The above equipment (model: GT7820 & GT7810 & GT7800 & GT78) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Gina Liu , **DATE** : Aug. 13, 2015

Gina Liu / Specialist

**APPROVED BY** : Kay Wu , **DATE** : Aug. 13, 2015

Kay Wu / Supervisor

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
2.1046 24.232	Equivalent Isotropic Radiated Power	PASS	Meet the requirement of limit.
2.1055 24.235	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 24.238(b)	Occupied Bandwidth	PASS	Meet the requirement of limit.
24.232(d)	Peak to average ratio	PASS	Meet the requirement of limit.
24.238(b)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 24.238	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -13.44dB at 9400.00MHz.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



A D T

## 2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Spectrum Analyzer Agilent Technologies	N9038A	MY52260177	May 19, 2015	May 18, 2016
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 10, 2014	Dec. 09, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 04, 2015	Feb. 04, 2016
HORN Antenna SCHWARZBECK	3117	00143293	Aug. 28, 2014	Aug. 27, 2015
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Aug. 27, 2014	Aug. 26, 2015
Preamplifier EMCI	EMC 012645	980115	Dec. 12, 2014	Dec. 11, 2015
Preamplifier EMCI	EMC 184045	980116	Jan. 09, 2015	Jan. 08, 2016
Preamplifier EMCI	EMC 330H	980112	Dec. 25, 2014	Dec. 24, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2014	Oct. 17, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2014	Oct. 17, 2015
RF signal cable Worken	RG-213	NA	Nov. 07, 2014	Nov. 06, 2015
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Radio Communication Analyzer	MT8820C	6201240432	Jul. 06, 2015	Jul. 05, 2017

- NOTE:**
1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HwaYa Chamber 10.
  3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  4. The FCC Site Registration No. is 690701.
  5. The IC Site Registration No. is IC 7450F-10.

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>EUT</b>	Rugged Android Tablet	
<b>MODEL NO.</b>	GT7820 & GT7810 & GT7800 & GT78	
<b>POWER SUPPLY</b>	5.0Vdc (adapter or host equipment) 3.8Vdc (battery)	
<b>MODULATION TYPE</b>	<b>GSM/GPRS</b>	GMSK
	<b>WCDMA</b>	BPSK
<b>FREQUENCY RANGE</b>	<b>GSM/GPRS/EDGE</b>	1850.2MHz ~ 1909.8MHz
	<b>WCDMA</b>	1852.4MHz ~ 1907.6MHz
<b>MAX. EIRP POWER</b>	<b>GSM</b>	762.08mW
	<b>WCDMA</b>	146.32mW
<b>EMISSION DESIGNATOR</b>	<b>GSM</b>	245KGXW
	<b>WCDMA</b>	4M17F9W
<b>ANTENNA TYPE</b>	Fixed Internal Antenna	
<b>I/O PORTS</b>	Refer to users' manual	
<b>DATA CABLE</b>	Refer to NOTE as below	
<b>ACCESSORY DEVICES</b>	Refer to NOTE as below	

#### NOTE:

1. All models are listed as below.

BRAND	MODEL	DIFFERENCE
Amobile	GT78	EUT without barcode
	GT7800	EUT without barcode
	GT7810	EUT with 1D barcode
	GT7820	EUT with 2D barcode
GT78 and GT7800 are electrically identical, different model names are for marketing purpose.		

2. Test Configurations are listed as below.

Sample	MODEL
A	GT7800
B	GT7810
C	GT7820

3. The EUT contains following accessory devices.


ITEM	BRAND	MODEL	SPECIFICATION
Battery	JAPON	TP0750B01	3.8Vdc, 6200mAh
Earphone	HETONG	PY-1312602-09KB02	1.2m
USB Cable	miki	YXT-64-MK5P-1M	0.98m
LCD Panel	K&D	KD079D1-35NA-A1	7.8 Inch
Photo Camera	SEASONS	SPV6B9298	--
Video Camera	Wdson	WDS1NA44W552	--
WWAN Module	MTK	MT6166	--
WLAN Module	MTK	MT6627	--
CPU	MTK	MT8382	1.3GHZ
MainBoard	miki	P6128	--
EMMC	N/A	NCEFES78-08G	8GB
bar code scanner (2D)	opticon	MDI-3100	--
bar code scanner (1D)	opticon	MDC-100	--

4. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.




### 3.2 CONFIGURATION OF SYSTEM UNDER TEST

#### FOR RADIATION EMISSION TEST



#### FOR E.I.R.P. TEST





### 3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Communications Tester-Wireless	Agilent	8960 Series 10	MY53201073	NA
2	Adapter	AMIGO	AMS135-0502000FU	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.5m shielded cable w/o core

**NOTE:**

1. All power cords of the above support units are non shielded (1.8m).
2. Item 1 as a communication partner to transfer data.

### 3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found and listed as below table. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION	EIRP	RADIATED EMISSION
A	GT7820	Z-plane	X-axis
B	GT7800	Z-plane	Z-axis
C	GT7810	Z-plane	Z-axis

#### GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	512 to 810	512, 661, 810	GSM
A	FREQUENCY STABILITY	512 to 810	661	GSM
A	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GSM
A	PEAK TO AVERAGE RATIO	512 to 810	512, 661, 810	GSM
A	BAND EDGE	512 to 810	512, 810	GSM
A	CONDUCTED EMISSION	512 to 810	661	GSM
A, B, C	RADIATED EMISSION	512 to 810	661	GSM



A D T

**WCDMA MODE**

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
A	FREQUENCY STABILITY	9262 to 9538	9400	WCDMA
A	OCCUPIED BANDWIDTH	9262 to 9538	9262, 9400, 9538	WCDMA
A	PEAK TO AVERAGE RATIO	9262 to 9538	9262, 9400, 9538	WCDMA
A	BAND EDGE	9262 to 9538	9262, 9538	WCDMA
A	CONDUCTED EMISSION	9262 to 9538	9400	WCDMA
A	RADIATED EMISSION	9262 to 9538	9400	WCDMA

**TEST CONDITION:**

Test Item	Environmental Conditions	Input Power	Tested by
ERP	26deg. C, 58%RH	3.8Vdc	Carlos Chen
FREQUENCY STABILITY	26deg. C, 58%RH	3.8Vdc	Carlos Chen
OCCUPIED BANDWIDTH	26deg. C, 58%RH	3.8Vdc	Carlos Chen
PEAK TO AVERAGE RATIO	26deg. C, 58%RH	3.8Vdc	Carlos Chen
BAND EDGE	26deg. C, 58%RH	3.8Vdc	Carlos Chen
CONDUCTED EMISSION	26deg. C, 58%RH	3.8Vdc	Carlos Chen
RADIATED EMISSION	25deg. C, 65%RH	120Vac, 60Hz	Charles Hsiao

### **3.5 EUT OPERATING CONDITIONS**

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

### **3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 24**

**ANSI/TIA/EIA-603-C 2004**

**NOTE:** All test items have been performed and recorded as per the above standards.

## 4 TEST TYPES AND RESULTS

### 4.1 OUTPUT POWER MEASUREMENT

#### 4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP.

#### 4.1.2 TEST PROCEDURES

##### EIRP MEASUREMENT:


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM, GPRS & EDGE, 5MHz for CDMA & WCDMA, and 10MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G
- d.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$

##### CONDUCTED POWER MEASUREMENT:


The EUT was set up for the maximum power with GSM, GPRS, EDGE & WCDMA & LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

### 4.1.3 TEST SETUP

#### EIRP / ERP MEASUREMENT:



#### CONDUCTED POWER MEASUREMENT:



#### 4.1.4 TEST RESULTS

##### CONDUCTED OUTPUT POWER (dBm)

Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880.0	1909.8
GSM (1 Uplink)	28.94	28.82	28.72
GPRS 8 (GMSK, 1 slot)	28.92	28.80	28.70
GPRS 10 (GMSK, 2 slot)	28.21	28.09	27.99
GPRS 11 (GMSK, 3 slot)	26.43	26.31	26.21
GPRS 12 (GMSK, 4 slot)	25.30	25.18	25.08

Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
RMC 12.2K	22.29	22.25	22.30
HSDPA Subtest-1	21.31	21.27	21.32
HSDPA Subtest-2	21.32	21.28	31.33
HSDPA Subtest-3	20.89	20.85	20.90
HSDPA Subtest-4	20.87	20.83	20.88
HSUPA Subtest-1	19.37	19.33	19.38
HSUPA Subtest-2	19.36	19.32	19.37
HSUPA Subtest-3	20.36	20.32	20.37
HSUPA Subtest-4	19.88	19.84	19.89
HSUPA Subtest-5	21.29	21.25	21.30

# EIRP POWER (dBm)

GSM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	512	1850.2	-19.58	44.70	25.12	325.09	H
	661	1880.0	-18.73	44.70	25.97	395.37	H
	810	1909.8	-19.56	44.57	25.01	317.18	H
	512	1850.2	-15.92	44.27	28.35	683.91	V
	661	1880.0	-16.05	44.87	28.82	762.08	V
	810	1909.8	-15.83	44.61	28.78	755.61	V

WCDMA							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	9262	1852.4	-25.99	44.70	18.71	74.30	H
	9400	1880.0	-26.14	44.70	18.56	71.78	H
	9538	1907.6	-25.59	44.57	18.98	79.12	H
	9262	1852.4	-23.09	44.27	21.18	131.22	V
	9400	1880.0	-23.79	44.87	21.08	128.23	V
	9538	1907.6	-22.96	44.61	21.65	146.32	V



## 4.2 FREQUENCY STABILITY MEASUREMENT

### 4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

### 4.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5^{\circ}\text{C}$  during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

### 4.2.3 TEST SETUP



#### 4.2.4 TEST RESULTS

##### FREQUENCY ERROR vs. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	GSM	WCDMA	
3.8	0.000	0.001	2.5
3.6	0.001	0.000	2.5
4.35	0.001	0.001	2.5

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.35Vdc.

##### FREQUENCY ERROR vs. TEMPERATURE


TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	GSM	WCDMA	
-30	0.001	0.000	2.5
-20	0.000	0.002	2.5
-10	0.000	0.001	2.5
0	0.001	0.000	2.5
10	0.001	0.001	2.5
20	-0.002	-0.001	2.5
30	-0.001	-0.001	2.5
40	-0.001	0.000	2.5
50	-0.001	-0.001	2.5

## 4.3 OCCUPIED BANDWIDTH MEASUREMENT

### 4.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

### 4.3.2 TEST SETUP






A D T

#### 4.3.3 TEST RESULTS

CHANNEL	FREQUENCY	99% OCCUPIED BANDWIDTH (kHz)	CHANNEL	FREQUENCY	99% OCCUPIED BANDWIDTH (MHz)
		GSM			WCDMA
512	1850.2	245.08	9262	1852.4	4.17
661	1880.0	245.29	9400	1880.0	4.17
810	1909.8	242.58	9538	1907.6	4.17
CHANNEL	FREQUENCY	26dB BANDWIDTH (kHz)	CHANNEL	FREQUENCY	26dB BANDWIDTH (MHz)
		GSM			WCDMA
512	1850.2	314.70	9262	1852.4	4.70
661	1880.0	304.10	9400	1880.0	4.71
810	1909.8	319.30	9538	1907.6	4.70




## 4.4 PEAK TO AVERAGE RATIO

### 4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 4.4.2 TEST SETUP



### 4.4.3 TEST PROCEDURES


1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.



A D T

#### 4.4.4 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
		GSM			WCDMA
512	1850.2	0.09	9262	1852.4	3.07
661	1880.0	0.09	9400	1880.0	2.82
810	1909.8	0.09	9538	1907.6	2.80




## 4.5 BAND EDGE MEASUREMENT

### 4.5.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

### 4.5.2 TEST SETUP




### 4.5.3 TEST PROCEDURES

- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 3kHz and VB of the spectrum is 10kHz (GSM/GPRS/EDGE).
- The center frequency of spectrum is the band edge frequency and span is 5MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA/LTE).
- Record the max trace plot into the test report.



A D T

## 4.5.4 TEST RESULTS





## 4.6 CONDUCTED SPURIOUS EMISSIONS


### 4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit is equal to -13dBm.


### 4.6.2 TEST PROCEDURE

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30 MHz to 19.1GHz. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

### 4.6.3 TEST SETUP



### 4.6.4 TEST RESULTS



## 4.7 RADIATED EMISSION MEASUREMENT

### 4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit is equal to -13dBm.

### 4.7.2 TEST PROCEDURES


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ .
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15\text{dBi}$ .

**NOTE:** The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

### 4.7.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.7.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).



A D T

#### 4.7.5 TEST RESULTS

GSM:

MODE A




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2015-07-31



Site : 966 chamber 1  
Condition: PART 22/24 3m Horizontal  
Remark : PCS 1900\_Link\_CH661  
Tested by: Karl Lee  
Plane : X  
SIM : 1

	Freq	Level	Read	Limit	Over		
	MHz	dBm/m	Level	Line	Limit	Factor	Remark
			dBm	dBm/m	dB	dB/m	
1	38.91	-79.33	-69.74	-13.00	-66.33	-9.59	Peak
2	155.55	-77.44	-69.63	-13.00	-64.44	-7.81	Peak
3	241.68	-75.16	-69.54	-13.00	-62.16	-5.62	Peak
4	395.20	-72.50	-69.50	-13.00	-59.50	-3.00	Peak
5	618.50	-67.97	-68.19	-13.00	-54.97	0.22	Peak
6	956.60	-64.12	-69.25	-13.00	-51.12	5.13	Peak
7	3760.00	-42.63	-58.77	-13.00	-29.63	16.14	Peak
8	5640.00	-41.02	-61.49	-13.00	-28.02	20.47	Peak
9 pp	7520.00	-35.21	-57.89	-13.00	-22.21	22.68	Peak
10	9400.00	-37.62	-63.39	-13.00	-24.62	25.77	Peak



A D T




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2015-07-31



Site : 966 chamber 1  
Condition: PART 22/24 3m Vertical  
Remark : PCS 1900\_Link\_CH661  
Tested by: Karl Lee  
Plane : X  
SIM : 1

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	37.29	-79.21	-69.24	-13.00	-66.21	-9.97	Peak
2	132.60	-77.22	-69.56	-13.00	-64.22	-7.66	Peak
3	250.32	-74.92	-69.41	-13.00	-61.92	-5.51	Peak
4	400.10	-72.21	-69.45	-13.00	-59.21	-2.76	Peak
5	632.50	-68.21	-68.27	-13.00	-55.21	0.06	Peak
6	923.70	-65.57	-69.50	-13.00	-52.57	3.93	Peak
7	3760.00	-43.33	-59.47	-13.00	-30.33	16.14	Peak
8	5640.00	-39.47	-59.94	-13.00	-26.47	20.47	Peak
9	7520.00	-28.60	-51.28	-13.00	-15.60	22.68	Peak
10 pp	9400.00	-26.44	-52.21	-13.00	-13.44	25.77	Peak



A D T


## MODE B



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13



Site : 966 chamber 1  
Condition: PART 22/24 3m Horizontal  
Remark : PCS 1900\_Link\_CH661  
Tested by: Charles Hsiao  
Plane : Z  
SIM : 1

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	38.64	-79.81	-70.22	-13.00	-66.81	-9.59	Peak
2	133.14	-77.29	-69.63	-13.00	-64.29	-7.66	Peak
3	226.29	-75.67	-69.84	-13.00	-62.67	-5.83	Peak
4	400.80	-72.20	-69.44	-13.00	-59.20	-2.76	Peak
5	669.60	-68.31	-68.08	-13.00	-55.31	-0.23	Peak
6	861.40	-66.29	-68.07	-13.00	-53.29	1.78	Peak
7	3760.00	-43.22	-59.36	-13.00	-30.22	16.14	Peak
8 pp	5640.00	-29.19	-49.66	-13.00	-16.19	20.47	Peak
9	7520.00	-36.27	-58.95	-13.00	-23.27	22.68	Peak
10	9400.00	-32.11	-57.88	-13.00	-19.11	25.77	Peak



A D T




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2015-07-31



Site : 966 chamber 1  
Condition: PART 22/24 3m Vertical  
Remark : PCS 1900\_Link\_CH661  
Tested by: Charles Hsiao  
Plane : Z  
SIM : 1

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	37.02	-78.27	-67.93	-13.00	-65.27	-10.34	Peak
2	95.34	-71.50	-61.10	-13.00	-58.50	-10.40	Peak
3	204.96	-75.14	-69.02	-13.00	-62.14	-6.12	Peak
4	409.20	-72.49	-69.54	-13.00	-59.49	-2.95	Peak
5	591.90	-68.35	-68.42	-13.00	-55.35	0.07	Peak
6	814.50	-66.81	-68.66	-13.00	-53.81	1.85	Peak
7	3760.00	-42.45	-58.59	-13.00	-29.45	16.14	Peak
8 pp	5640.00	-38.43	-58.90	-13.00	-25.43	20.47	Peak
9	7520.00	-39.28	-61.96	-13.00	-26.28	22.68	Peak

# MODE C




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2015-07-31



Site : 966 chamber 1  
Condition: PART 22/24 3m Horizontal  
Remark : PCS 1900\_Link\_CH661  
Tested by: Charles Hsiao  
Plane : Z  
SIM : 1

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	37.56	-79.19	-69.22	-13.00	-66.19	-9.97	Peak
2	143.40	-76.92	-69.13	-13.00	-63.92	-7.79	Peak
3	222.78	-75.77	-69.90	-13.00	-62.77	-5.87	Peak
4	396.60	-72.74	-69.84	-13.00	-59.74	-2.90	Peak
5	652.10	-68.23	-68.09	-13.00	-55.23	-0.14	Peak
6	917.40	-65.36	-69.03	-13.00	-52.36	3.67	Peak
7	3760.00	-46.57	-62.71	-13.00	-33.57	16.14	Peak
8	5640.00	-40.47	-60.94	-13.00	-27.47	20.47	Peak
9 pp	7520.00	-27.11	-49.79	-13.00	-14.11	22.68	Peak
10	9400.00	-34.81	-60.58	-13.00	-21.81	25.77	Peak






A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14



Site : 966 chamber 1  
Condition: PART 22/24 3m Vertical  
Remark : PCS 1900\_Link\_CH661  
Tested by: Charles Hsiao  
Plane : Z  
SIM : 1

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	37.83	-78.23	-68.26	-13.00	-65.23	-9.97	Peak
2	160.95	-76.79	-69.22	-13.00	-63.79	-7.57	Peak
3	240.33	-74.37	-68.73	-13.00	-61.37	-5.64	Peak
4	401.50	-72.41	-69.63	-13.00	-59.41	-2.78	Peak
5	729.10	-68.57	-67.64	-13.00	-55.57	-0.93	Peak
6	943.30	-64.21	-69.05	-13.00	-51.21	4.84	Peak
7	3760.00	-46.87	-63.01	-13.00	-33.87	16.14	Peak
8	5640.00	-43.68	-64.15	-13.00	-30.68	20.47	Peak
9 pp	7520.00	-32.87	-55.55	-13.00	-19.87	22.68	Peak



A D T

WCDMA:  
MODE A




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2015-07-31



Site : 966 chamber 1  
Condition: PART 22/24 3m Horizontal  
Remark : Bnad II\_Link\_CH9400  
Tested by: Charles Hsiao  
Plane : X  
SIM : 1

		Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m
1 pp	3760.00	-49.47	-65.61	-13.00	-36.47	16.14 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1  
Condition: PART 22/24 3m Vertical  
Remark : Bnad II\_Link\_CH9400  
Tested by: Charles Hsiao  
Plane : X  
SIM : 1

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	pp 3760.00	-49.90	-66.04	-13.00	-36.90	16.14	Peak

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

## 6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Lab:**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.



A D T

## **7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications were made to the EUT by the lab during the test.

---END---