

# FCC SAR Test Report

**Report No.** : SA141128C02

**Applicant** : TCL Communication Ltd.

**Address** : 5F., C-Tower, No. 232, Liangjing Road, Zhangjiang High-tech Park, Pudong, Shanghai, China

**Product** : Mobile Hotspot Folio

**FCC ID** : 2ACCJB005

**Brand** : ALCATEL ONETOUCH

**Model No.** : Y860OA

**Standards** : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE 1528:2003  
IEEE 1528a-2005 / KDB 865664 D01 v01r03  
KDB 248227 D01 v01r02 / KDB 447498 D01 v05r02 / KDB 616217 D04 v01r01  
KDB 941225 D01 v02 / KDB 941225 D02 v02r02 / KDB 941225 D05 v02r03

**Sample Received Date** : Nov. 28, 2014

**Date of Testing** : Dec. 30, 2014 ~ Jan. 09, 2015

**CERTIFICATION:** The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., China Branch - Dongguan Lab**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By :

Vera Huang

Vera Huang / Specialist

Approved By :

Gordon Lin

Gordon Lin / Assistant Manager



No: 2951.01

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

|   |           |
|---|-----------|
| <b>Release Control Record .....</b>                         | <b>3</b>  |
| <b>1. Summary of Maximum SAR Value .....</b>                | <b>4</b>  |
| <b>2. Description of Equipment Under Test .....</b>         | <b>5</b>  |
| <b>3. SAR Measurement System .....</b>                      | <b>6</b>  |
| 3.1 Definition of Specific Absorption Rate (SAR) .....      | 6         |
| 3.2 SPEAG DASY System .....                                 | 6         |
| 3.2.1 Robot.....  | 7         |
| 3.2.2 Probes.....   | 8         |
| 3.2.3 Data Acquisition Electronics (DAE) .....              | 8         |
| 3.2.4 Phantoms .....  | 9         |
| 3.2.5 Device Holder.....                                    | 9         |
| 3.2.6 System Validation Dipoles.....                        | 10        |
| 3.2.7 Tissue Simulating Liquids.....                        | 10        |
| 3.3 SAR System Verification .....                           | 13        |
| 3.4 SAR Measurement Procedure .....                         | 14        |
| 3.4.1 Area & Zoom Scan Procedure .....                      | 14        |
| 3.4.2 Volume Scan Procedure.....                            | 14        |
| 3.4.3 Power Drift Monitoring.....                           | 15        |
| 3.4.4 Spatial Peak SAR Evaluation .....                     | 15        |
| 3.4.5 SAR Averaged Methods .....                            | 15        |
| <b>4. SAR Measurement Evaluation .....</b>                  | <b>16</b> |
| 4.1 EUT Configuration and Setting.....                      | 16        |
| 4.2 EUT Testing Position .....                              | 18        |
| 4.3 Tissue Verification .....                               | 22        |
| 4.4 System Validation.....                                  | 22        |
| 4.5 System Verification.....                                | 22        |
| 4.6 Maximum Output Power.....                               | 23        |
| 4.6.1 Maximum Conducted Power .....                         | 23        |
| 4.6.2 Measured Conducted Power Result.....                  | 24        |
| 4.7 SAR Testing Results .....                               | 36        |
| 4.7.1 SAR Results for Body.....                             | 36        |
| 4.7.2 SAR Measurement Variability.....                      | 41        |
| 4.7.3 Simultaneous Multi-band Transmission Evaluation ..... | 42        |
| <b>5. Calibration of Test Equipment.....</b>                | <b>45</b> |
| <b>6. Measurement Uncertainty.....</b>                      | <b>46</b> |
| <b>7. Information on the Testing Laboratories .....</b>     | <b>48</b> |

**Appendix A. SAR Plots of System Verification**  
**Appendix B. SAR Plots of SAR Measurement**  
**Appendix C. Calibration Certificate for Probe and Dipole**  
**Appendix D. Photographs of EUT and Setup**



## Release Control Record

| Report No.  | Reason for Change | Date Issued   |
|-------------|-------------------|---------------|
| SA141128C02 | Initial release   | Jan. 12, 2015 |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |

## 1. Summary of Maximum SAR Value

| Equipment Class                       | Mode      | Highest Reported Body SAR <sub>1g</sub> (W/kg) |
|---------------------------------------|-----------|--|
| PCB                                   | WCDMA II  | 1.39   |
|                                       | WCDMA V   | 0.52   |
|                                       | LTE 2     | 1.31   |
|                                       | LTE 4     | 1.28   |
|                                       | LTE 5     | 0.44   |
|                                       | LTE 7     | 0.77   |
|                                       | LTE 17    | 0.37   |
| NII                                   | 5.8G WLAN | 0.18   |
| Highest Simultaneous Transmission SAR |           | Body (W/kg)                                    |
| PCB + NII                             |           | 1.55   |

### Note:

- The SAR limit (**Head & Body: SAR<sub>1g</sub> 1.6 W/kg**) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

## 2. Description of Equipment Under Test

|  |  |
|--|--|
| <b>EUT Type</b>  | Mobile Hotspot Folio   |
| <b>FCC ID</b>  | 2ACCJB005  |
| <b>Brand Name</b>                                      | ALCATEL ONETOUCH   |
| <b>Model Name</b>                                      | Y860OA   |
| <b>Tx Frequency Bands<br/>(Unit: MHz)</b>              | WCDMA Band II : 1852.4 ~ 1907.6<br>WCDMA Band V : 826.4 ~ 846.6<br>LTE Band 2 : 1850.7 ~ 1909.3 (1.4M), 1851.5 ~ 1908.5 (3M), 1852.5 ~ 1907.5 (5M),<br>1855 ~ 1905 (10M), 1857.5 ~ 1902.5 (15M), 1860 ~ 1900 (20M)<br>LTE Band 4 : 1710.7 ~ 1754.3 (1.4M), 1711.5 ~ 1753.5 (3M), 1712.5 ~ 1752.5 (5M),<br>1715 ~ 1750 (10M), 1717.5 ~ 1747.5 (15M), 1720 ~ 1745 (20M)<br>LTE Band 5 : 824.7 ~ 848.3 (1.4M), 825.5 ~ 847.5 (3M), 826.5 ~ 846.5 (5M), 829 ~<br>844 (10M)<br>LTE Band 7 : 2502.5 ~ 2567.5 (5M), 2505 ~ 2565 (10M), 2507.5 ~ 2562.5 (15M),<br>2510 ~ 2560 (20M)<br>LTE Band 17 : 706.5 ~ 713.5 (5M), 709 ~ 711 (10M)<br>WLAN : 5745 ~ 5825 |
| <b>Uplink Modulations</b>                              | WCDMA : QPSK<br>LTE : QPSK, 16QAM<br>802.11a/n : OFDM  |
| <b>Maximum Tune-up Conducted Power<br/>(Unit: dBm)</b> | WCDMA Band II : 24.0<br>WCDMA Band V : 23.5<br>LTE Band 2 : 23.0<br>LTE Band 4 : 23.0<br>LTE Band 5 : 22.5<br>LTE Band 7 : 23.0<br>LTE Band 17 : 23.5<br>WLAN 5.8G : 15.5  |
| <b>Antenna Type</b>                                    | Fixed Internal Antenna   |
| <b>EUT Stage</b>                                       | Identical Prototype  |

**Note:**

- The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

**List of Accessory:**

|                |                     |                  |
|----------------|---------------------|------------------|
| <b>Battery</b> | <b>Brand Name</b>   | ALCATEL ONETOUCH |
|                | <b>Model Name</b>   | TLp046A2         |
|                | <b>Power Rating</b> | 3.8Vdc, 4600mAh  |
|                | <b>Type</b>         | Li-ion           |

### 3. SAR Measurement System

#### 3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

#### 3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

## FCC SAR Test Report



**Fig-3.1 DASY System Setup**

### 3.2.1 Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability  $\pm 0.035$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)





**Fig-3.2 DASY5**

## FCC SAR Test Report


### 3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

|                      |  |   |
|----------------------|--|---|
| <b>Model</b>         | EX3DV4   |  |
| <b>Construction</b>  | Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE). |   |
| <b>Frequency</b>     | 10 MHz to 6 GHz<br>Linearity: $\pm 0.2$ dB   |   |
| <b>Directivity</b>   | $\pm 0.3$ dB in HSL (rotation around probe axis)<br>$\pm 0.5$ dB in tissue material (rotation normal to probe axis)                                      |   |
| <b>Dynamic Range</b> | 10 $\mu$ W/g to 100 mW/g<br>Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)   |   |
| <b>Dimensions</b>    | Overall length: 337 mm (Tip: 20 mm)<br>Tip diameter: 2.5 mm (Body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                     |   |

|                      |   |  |
|----------------------|---|--|
| <b>Model</b>         | ES3DV3  |  |
| <b>Construction</b>  | Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE). |  |
| <b>Frequency</b>     | 10 MHz to 4 GHz<br>Linearity: $\pm 0.2$ dB  |  |
| <b>Directivity</b>   | $\pm 0.2$ dB in HSL (rotation around probe axis)<br>$\pm 0.3$ dB in tissue material (rotation normal to probe axis)   |  |
| <b>Dynamic Range</b> | 5 $\mu$ W/g to 100 mW/g<br>Linearity: $\pm 0.2$ dB  |  |
| <b>Dimensions</b>    | Overall length: 337 mm (Tip: 20 mm)<br>Tip diameter: 3.9 mm (Body: 12 mm)<br>Distance from probe tip to dipole centers: 2.0 mm  |  |


### 3.2.3 Data Acquisition Electronics (DAE)


|                             |   |   |
|-----------------------------|---|---|
| <b>Model</b>                | DAE3, DAE4  |  |
| <b>Construction</b>         | Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop. |   |
| <b>Measurement Range</b>    | -100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)  |   |
| <b>Input Offset Voltage</b> | $< 5\mu$ V (with auto zero)   |   |
| <b>Input Bias Current</b>   | $< 50$ fA   |   |
| <b>Dimensions</b>           | 60 x 60 x 68 mm   |   |




## FCC SAR Test Report

### 3.2.4 Phantoms


|                        |   |   |
|------------------------|---|---|
| <b>Model</b>           | Twin SAM  |  |
| <b>Construction</b>    | The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot. |   |
| <b>Material</b>        | Vinylester, glass fiber reinforced (VE-GF)  |   |
| <b>Shell Thickness</b> | 2 ± 0.2 mm (6 ± 0.2 mm at ear point)  |   |
| <b>Dimensions</b>      | Length: 1000 mm<br>Width: 500 mm<br>Height: adjustable feet   |   |
| <b>Filling Volume</b>  | approx. 25 liters   |   |

|                        |   |  |
|------------------------|---|--|
| <b>Model</b>           | ELI   |  |
| <b>Construction</b>    | Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles. |  |
| <b>Material</b>        | Vinylester, glass fiber reinforced (VE-GF)  |  |
| <b>Shell Thickness</b> | 2.0 ± 0.2 mm (bottom plate)   |  |
| <b>Dimensions</b>      | Major axis: 600 mm<br>Minor axis: 400 mm  |  |
| <b>Filling Volume</b>  | approx. 30 liters   |  |

### 3.2.5 Device Holder


|                     |   |   |
|---------------------|---|---|
| <b>Model</b>        | Mounting Device   |  |
| <b>Construction</b> | In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). |   |
| <b>Material</b>     | POM   |   |

## 3.2.6 System Validation Dipoles

|                         |  |   |
|-------------------------|--|---|
| <b>Model</b>            | D-Serial   |  |
| <b>Construction</b>     | Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions. |   |
| <b>Frequency</b>        | 750 MHz to 5800 MHz  |   |
| <b>Return Loss</b>      | > 20 dB  |   |
| <b>Power Capability</b> | > 100 W (f < 1GHz), > 40 W (f > 1GHz)  |   |

## 3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

**Table-3.1 Targets of Tissue Simulating Liquid**

| Frequency (MHz) | Target Permittivity | Range of $\pm 5\%$ | Target Conductivity | Range of $\pm 5\%$ |
|-----------------|---------------------|--------------------|---------------------|--------------------|
| <b>For Head</b> |                     |                    |                     |                    |
| 750             | 41.9                | 39.8 ~ 44.0        | 0.89                | 0.85 ~ 0.93        |
| 835             | 41.5                | 39.4 ~ 43.6        | 0.90                | 0.86 ~ 0.95        |
| 900             | 41.5                | 39.4 ~ 43.6        | 0.97                | 0.92 ~ 1.02        |
| 1450            | 40.5                | 38.5 ~ 42.5        | 1.20                | 1.14 ~ 1.26        |
| 1640            | 40.3                | 38.3 ~ 42.3        | 1.29                | 1.23 ~ 1.35        |
| 1750            | 40.1                | 38.1 ~ 42.1        | 1.37                | 1.30 ~ 1.44        |
| 1800            | 40.0                | 38.0 ~ 42.0        | 1.40                | 1.33 ~ 1.47        |
| 1900            | 40.0                | 38.0 ~ 42.0        | 1.40                | 1.33 ~ 1.47        |
| 2000            | 40.0                | 38.0 ~ 42.0        | 1.40                | 1.33 ~ 1.47        |
| 2300            | 39.5                | 37.5 ~ 41.5        | 1.67                | 1.59 ~ 1.75        |
| 2450            | 39.2                | 37.2 ~ 41.2        | 1.80                | 1.71 ~ 1.89        |
| 2600            | 39.0                | 37.1 ~ 41.0        | 1.96                | 1.86 ~ 2.06        |
| 3500            | 37.9                | 36.0 ~ 39.8        | 2.91                | 2.76 ~ 3.06        |
| 5200            | 36.0                | 34.2 ~ 37.8        | 4.66                | 4.43 ~ 4.89        |
| 5300            | 35.9                | 34.1 ~ 37.7        | 4.76                | 4.52 ~ 5.00        |
| 5500            | 35.6                | 33.8 ~ 37.4        | 4.96                | 4.71 ~ 5.21        |
| 5600            | 35.5                | 33.7 ~ 37.3        | 5.07                | 4.82 ~ 5.32        |
| 5800            | 35.3                | 33.5 ~ 37.1        | 5.27                | 5.01 ~ 5.53        |
| <b>For Body</b> |                     |                    |                     |                    |
| 750             | 55.5                | 52.7 ~ 58.3        | 0.96                | 0.91 ~ 1.01        |
| 835             | 55.2                | 52.4 ~ 58.0        | 0.97                | 0.92 ~ 1.02        |
| 900             | 55.0                | 52.3 ~ 57.8        | 1.05                | 1.00 ~ 1.10        |
| 1450            | 54.0                | 51.3 ~ 56.7        | 1.30                | 1.24 ~ 1.37        |
| 1640            | 53.8                | 51.1 ~ 56.5        | 1.40                | 1.33 ~ 1.47        |
| 1750            | 53.4                | 50.7 ~ 56.1        | 1.49                | 1.42 ~ 1.56        |
| 1800            | 53.3                | 50.6 ~ 56.0        | 1.52                | 1.44 ~ 1.60        |
| 1900            | 53.3                | 50.6 ~ 56.0        | 1.52                | 1.44 ~ 1.60        |
| 2000            | 53.3                | 50.6 ~ 56.0        | 1.52                | 1.44 ~ 1.60        |
| 2300            | 52.9                | 50.3 ~ 55.5        | 1.81                | 1.72 ~ 1.90        |
| 2450            | 52.7                | 50.1 ~ 55.3        | 1.95                | 1.85 ~ 2.05        |
| 2600            | 52.5                | 49.9 ~ 55.1        | 2.16                | 2.05 ~ 2.27        |
| 3500            | 51.3                | 48.7 ~ 53.9        | 3.31                | 3.14 ~ 3.48        |
| 5200            | 49.0                | 46.6 ~ 51.5        | 5.30                | 5.04 ~ 5.57        |
| 5300            | 48.9                | 46.5 ~ 51.3        | 5.42                | 5.15 ~ 5.69        |
| 5500            | 48.6                | 46.2 ~ 51.0        | 5.65                | 5.37 ~ 5.93        |
| 5600            | 48.5                | 46.1 ~ 50.9        | 5.77                | 5.48 ~ 6.06        |
| 5800            | 48.2                | 45.8 ~ 50.6        | 6.00                | 5.70 ~ 6.30        |


The following table gives the recipes for tissue simulating liquids.

**Table-3.2 Recipes of Tissue Simulating Liquid**

| Tissue Type | Bactericide | DGBE | HEC | NaCl | Sucrose | Triton X-100 | Water | Diethylene Glycol Mono-hexylether |
|-------------|-------------|------|-----|------|---------|--------------|-------|-----------------------------------|
| H750        | 0.2         | -    | 0.2 | 1.5  | 56.0    | -            | 42.1  | -                                 |
| H835        | 0.2         | -    | 0.2 | 1.5  | 57.0    | -            | 41.1  | -                                 |
| H900        | 0.2         | -    | 0.2 | 1.4  | 58.0    | -            | 40.2  | -                                 |
| H1450       | -           | 43.3 | -   | 0.6  | -       | -            | 56.1  | -                                 |
| H1640       | -           | 45.8 | -   | 0.5  | -       | -            | 53.7  | -                                 |
| H1750       | -           | 47.0 | -   | 0.4  | -       | -            | 52.6  | -                                 |
| H1800       | -           | 44.5 | -   | 0.3  | -       | -            | 55.2  | -                                 |
| H1900       | -           | 44.5 | -   | 0.2  | -       | -            | 55.3  | -                                 |
| H2000       | -           | 44.5 | -   | 0.1  | -       | -            | 55.4  | -                                 |
| H2300       | -           | 44.9 | -   | 0.1  | -       | -            | 55.0  | -                                 |
| H2450       | -           | 45.0 | -   | 0.1  | -       | -            | 54.9  | -                                 |
| H2600       | -           | 45.1 | -   | 0.1  | -       | -            | 54.8  | -                                 |
| H3500       | -           | 8.0  | -   | 0.2  | -       | 20.0         | 71.8  | -                                 |
| H5G         | -           | -    | -   | -    | -       | 17.2         | 65.5  | 17.3                              |
| B750        | 0.2         | -    | 0.2 | 0.8  | 48.8    | -            | 50.0  | -                                 |
| B835        | 0.2         | -    | 0.2 | 0.9  | 48.5    | -            | 50.2  | -                                 |
| B900        | 0.2         | -    | 0.2 | 0.9  | 48.2    | -            | 50.5  | -                                 |
| B1450       | -           | 34.0 | -   | 0.3  | -       | -            | 65.7  | -                                 |
| B1640       | -           | 32.5 | -   | 0.3  | -       | -            | 67.2  | -                                 |
| B1750       | -           | 31.0 | -   | 0.2  | -       | -            | 68.8  | -                                 |
| B1800       | -           | 29.5 | -   | 0.4  | -       | -            | 70.1  | -                                 |
| B1900       | -           | 29.5 | -   | 0.3  | -       | -            | 70.2  | -                                 |
| B2000       | -           | 30.0 | -   | 0.2  | -       | -            | 69.8  | -                                 |
| B2300       | -           | 31.0 | -   | 0.1  | -       | -            | 68.9  | -                                 |
| B2450       | -           | 31.4 | -   | 0.1  | -       | -            | 68.5  | -                                 |
| B2600       | -           | 31.8 | -   | 0.1  | -       | -            | 68.1  | -                                 |
| B3500       | -           | 28.8 | -   | 0.1  | -       | -            | 71.1  | -                                 |
| B5G         | -           | -    | -   | -    | -       | 10.7         | 78.6  | 10.7                              |

## 3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



**Fig-3.4 System Verification Setup**

The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

## FCC SAR Test Report

### 3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- Make EUT to transmit maximum output power
- Measure conducted output power through RF cable
- Place the EUT in the specific position of phantom
- Perform SAR testing steps on the DASY system
- Record the SAR value

#### 3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

| Items                                 | <= 2 GHz | 2-3 GHz  | 3-4 GHz  | 4-5 GHz  | 5-6 GHz  |
|---------------------------------------|----------|----------|----------|----------|----------|
| Area Scan<br>( $\Delta x, \Delta y$ ) | <= 15 mm | <= 12 mm | <= 12 mm | <= 10 mm | <= 10 mm |
| Zoom Scan<br>( $\Delta x, \Delta y$ ) | <= 8 mm  | <= 5 mm  | <= 5 mm  | <= 4 mm  | <= 4 mm  |
| Zoom Scan<br>( $\Delta z$ )           | <= 5 mm  | <= 5 mm  | <= 4 mm  | <= 3 mm  | <= 2 mm  |
| Zoom Scan<br>Volume                   | >= 30 mm | >= 30 mm | >= 28 mm | >= 25 mm | >= 22 mm |

#### Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of  $\Delta x / \Delta y$  (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

#### 3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

## FCC SAR Test Report

### 3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

### 3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

### 3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

## 4. SAR Measurement Evaluation

### 4.1 EUT Configuration and Setting

According to the procedures noticed in KDB 616217 D04, the proximity sensor triggering distance is 1.1 cm for EUT Front Face, 1.2 cm for EUT Rear Face, and 1.3 cm for Bottom Side. The separation distance of 1.3 cm determined by the smallest triggering distance on Bottom Side is used to assess the tilt angle influence and the sensor does not release during  $\pm 45$  degree. Therefore, the smallest separation distance for tilt angle influence is 1.3 cm. The details can be found in technical document. The conservative triggering distances based on the separation distance for the sensor triggered / not triggered as EUT with power reduction at 0 mm, and EUT without power reduction at 1.1 cm for EUT Front Face, 1.2 cm for EUT Rear Face, and 1. cm for Bottom Side is used to test SAR.

The power reduction is depends on the proximity sensor input. For a steady SAR test, the power reduction was enabled/disabled manually by engineering software during SAR testing.

The EUT is a data transmitter device that contains one WWAN transmitter (WCDMA / LTE). Confirming the LTE transmitter follows 3GPP standards, is category 3, FDD-LTE band 2/4 (BW 1.4/3/5/10/15/20 MHz), FDD-LTE band 5 (BW 1.4/3/5/10 MHz), FDD-LTE band 7 (BW 5/10/15/20 MHz), FDD-LTE band 17 (BW 5/10 MHz), supports QPSK / 16QAM modulations, and supports data transmission only. Tested per 3GPP 36.521 maximum transmit procedures for both QPSK / 16QAM.

**LTE Maximum Power Reduction in accordance with 3GPP 36.101:** Power Reduction in accordance to 3GPP is active all times during LTE operation.

| Modulation | Channel Bandwidth / RB Configurations |          |          |           |           |           | LTE MPR Setting (dB) |
|------------|---------------------------------------|----------|----------|-----------|-----------|-----------|----------------------|
|            | BW 1.4 MHz                            | BW 3 MHz | BW 5 MHz | BW 10 MHz | BW 15 MHz | BW 20 MHz |                      |
| QPSK       | > 5                                   | > 4      | > 8      | > 12      | > 16      | > 18      | 1                    |
| 16QAM      | $\leq 5$                              | $\leq 4$ | $\leq 8$ | $\leq 12$ | $\leq 16$ | $\leq 18$ | 1                    |
| 16QAM      | > 5                                   | > 4      | > 8      | > 12      | > 16      | > 18      | 2                    |

**Note:** MPR is according to the standard and implemented in the circuit (mandatory).

In addition, the device is compliant with A-MPR requirements defined in 36.101 section 6.2.4 that may be required to meet 3GPP Adjacent Channel Leakage Ratio ("ACLR") requirements. A-MPR was disabled for all FCC compliance testing.



## FCC SAR Test Report

The simultaneous transmission possibilities are listed as below.

| Simultaneous Tx Combination | RF Configuration                 |
|-----------------------------|----------------------------------|
| 1                           | WCDMA II (Data) + WLAN (Data)    |
| 2                           | WCDMA V (Data) + WLAN (Data)     |
| 3                           | LTE Band 2 (Data) + WLAN (Data)  |
| 4                           | LTE Band 4 (Data) + WLAN (Data)  |
| 5                           | LTE Band 5 (Data) + WLAN (Data)  |
| 6                           | LTE Band 7 (Data) + WLAN (Data)  |
| 7                           | LTE Band 17 (Data) + WLAN (Data) |

**Note:** This device does not support voice transmission capability.

For WWAN SAR testing, the EUT was linked and controlled by base station emulator (Agilent E5515C is used for WCDMA, and Anritsu MT8820C is used for LTE). Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

For WCDMA, head and body SAR is tested under 12.2k RMC mode with power control set all up bits. SAR for AMR is not required since its power is less than 1/4 dB higher than RMC. SAR for HSDPA/HSUPA is not required since its power is less than 1/4 dB higher than RMC without HSDPA/HSUPA and SAR for 12.2 kbps RMC is less than 75% of the SAR limit (1.2 W/kg).


For LTE, set the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB in base station simulator. When the EUT has registered and communicated to base station simulator, set the simulator to make EUT transmitting the maximum radiated power. The steps for system simulator (Anritsu MT8820C) setup are as below.

1. Press the "Std" button to select "LTE 22.20S" function
2. Choose the "Screen Select" item to "Fundamental Measurement"
3. Enter the "Common" item
4. Set the Operating Band
5. Set the Channel Bandwidth
6. Set the UL Channel & Frequency
7. Set the Modulation
8. Set the RB number and RB shift
9. Press "Start Call" button when EUT register to the system simulator
10. Set the TX-1 Max. Power to make the EUT transmit maximum output power

For WLAN SAR testing, the EUT has installed WLAN engineering testing software which can provide continuous transmitting RF signal. According to KDB 248227 D01, WLAN SAR should tested at the lowest data rate, and testing at higher data rate is not required when the maximum average output power is less than 1/4 dB higher than those measured at the lowest data rate. Since the WLAN power at lowest data rate has highest output power, WLAN SAR for this device was performed at the lowest data rate.

## 4.2 EUT Testing Position

According to KDB 616217 D04, SAR evaluation is required for back surface and edges of the devices. The back surface and edges of the tablet are tested with the tablet touching the phantom. Exposures from antennas through the front surface of the display section of a tablet are generally limited to the user's hands. Exposures to hands for typical consumer transmitters used in tablets are not expected to exceed the extremity SAR limit; therefore, SAR evaluation for the front surface of tablet display screens are generally not necessary. When voice mode is supported on a tablet and it is limited to speaker mode or headset operations only, additional SAR testing for this type of voice use is not required.



**Fig-4.1 Illustration for Tablet Setup**

# FCC SAR Test Report

A D T

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

- For the test separation distance  $\leq 50$  mm

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0$$

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

- For the test separation distance  $> 50$  mm, and the frequency at 100 MHz to 1500 MHz

$$\left[ (\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left( \frac{f_{(\text{MHz})}}{150} \right) \right]_{(\text{mW})}$$

- For the test separation distance  $> 50$  mm, and the frequency at  $> 1500$  MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(\text{mW})}$$

| Mode     | Max. Tune-up Power (dBm) | Max. Tune-up Power (mW) | Front Face           |                   |                      | Rear Face            |                   |                      | Left Side            |                   |                      |
|----------|--------------------------|-------------------------|----------------------|-------------------|----------------------|----------------------|-------------------|----------------------|----------------------|-------------------|----------------------|
|          |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
| WCDMA II | 24.0                     | 251                     | 5                    | 69.3              | Yes                  | 5                    | 69.3              | Yes                  | 114                  | 749 (mw)          | No                   |
|          |                          |                         | Right Side           |                   |                      | Top Side             |                   |                      | Bottom Side          |                   |                      |
|          |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
|          |                          |                         | 25                   | 13.9              | Yes                  | 137                  | 979 (mw)          | No                   | 5                    | 69.3              | Yes                  |
| WCDMA V  | 23.5                     | 224                     | 5                    | 41.2              | Yes                  | 5                    | 41.2              | Yes                  | 114                  | 524 (mw)          | No                   |
|          |                          |                         | Right Side           |                   |                      | Top Side             |                   |                      | Bottom Side          |                   |                      |
|          |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
|          |                          |                         | 25                   | 8.2               | Yes                  | 137                  | 654 (mw)          | No                   | 5                    | 41.2              | Yes                  |
| LTE 2    | 23.0                     | 200                     | 5                    | 55.3              | Yes                  | 5                    | 55.3              | Yes                  | 114                  | 749 (mw)          | No                   |
|          |                          |                         | Right Side           |                   |                      | Top Side             |                   |                      | Bottom Side          |                   |                      |
|          |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
|          |                          |                         | 25                   | 11.1              | Yes                  | 137                  | 979 (mw)          | No                   | 5                    | 55.3              | Yes                  |
| LTE 4    | 23.0                     | 200                     | 5                    | 53                | Yes                  | 5                    | 53                | Yes                  | 114                  | 753 (mw)          | No                   |
|          |                          |                         | Right Side           |                   |                      | Top Side             |                   |                      | Bottom Side          |                   |                      |
|          |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
|          |                          |                         | 25                   | 10.6              | Yes                  | 137                  | 983 (mw)          | No                   | 5                    | 53                | Yes                  |

# FCC SAR Test Report

A D T

| Mode   | Max. Tune-up Power (dBm) | Max. Tune-up Power (mW) | Front Face           |                   |                      | Rear Face            |                   |                      | Left Side            |                   |                      |
|--------|--------------------------|-------------------------|----------------------|-------------------|----------------------|----------------------|-------------------|----------------------|----------------------|-------------------|----------------------|
|        |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
| LTE 5  | 22.5                     | 178                     | 5                    | 32.8              | Yes                  | 5                    | 32.8              | Yes                  | 114                  | 524 (mw)          | No                   |
|        |                          |                         | Right Side           |                   |                      | Top Side             |                   |                      | Bottom Side          |                   |                      |
|        |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
|        |                          |                         | 25                   | 6.6               | Yes                  | 137                  | 654 (mw)          | No                   | 5                    | 32.8              | Yes                  |
| Mode   | Max. Tune-up Power (dBm) | Max. Tune-up Power (mW) | Front Face           |                   |                      | Rear Face            |                   |                      | Left Side            |                   |                      |
|        |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
| LTE 7  | 23.0                     | 200                     | 5                    | 62.8              | Yes                  | 5                    | 62.8              | Yes                  | 114                  | 736 (mw)          | No                   |
|        |                          |                         | Right Side           |                   |                      | Top Side             |                   |                      | Bottom Side          |                   |                      |
|        |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
|        |                          |                         | 25                   | 12.6              | Yes                  | 137                  | 966 (mw)          | No                   | 5                    | 62.8              | Yes                  |
| Mode   | Max. Tune-up Power (dBm) | Max. Tune-up Power (mW) | Front Face           |                   |                      | Rear Face            |                   |                      | Left Side            |                   |                      |
|        |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
| LTE 17 | 23.5                     | 224                     | 5                    | 37.9              | Yes                  | 5                    | 37.9              | Yes                  | 114                  | 482 (mw)          | No                   |
|        |                          |                         | Right Side           |                   |                      | Top Side             |                   |                      | Bottom Side          |                   |                      |
|        |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
|        |                          |                         | 25                   | 7.6               | Yes                  | 137                  | 592 (mw)          | No                   | 5                    | 37.9              | Yes                  |

## Note:

1. When separation distance  $\leq 50$  mm and the calculated result shown in above table is  $\leq 3.0$ , the SAR testing exclusion is applied.
2. When separation distance  $> 50$  mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.

# FCC SAR Test Report

A D T

## <Ant-0>

| Mode      | Max. Tune-up Power (dBm) | Max. Tune-up Power (mW) | Front Face           |                   |                      | Rear Face            |                   |                      | Left Side            |                   |                      |
|-----------|--------------------------|-------------------------|----------------------|-------------------|----------------------|----------------------|-------------------|----------------------|----------------------|-------------------|----------------------|
|           |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
| WLAN 5.8G | 12.0                     | 16                      | 5                    | 7.7               | Yes                  | 5                    | 7.7               | Yes                  | 5                    | 7.7               | Yes                  |
|           |                          |                         | Right Side           |                   |                      | Top Side             |                   |                      | Bottom Side          |                   |                      |
|           |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
|           |                          |                         | 207                  | 1632 (mw)         | No                   | 104                  | 602 (mw)          | No                   | 28                   | 1.4               | No                   |

## <Ant-1>

| Mode      | Max. Tune-up Power (dBm) | Max. Tune-up Power (mW) | Front Face           |                   |                      | Rear Face            |                   |                      | Left Side            |                   |                      |
|-----------|--------------------------|-------------------------|----------------------|-------------------|----------------------|----------------------|-------------------|----------------------|----------------------|-------------------|----------------------|
|           |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
| WLAN 5.8G | 12.5                     | 18                      | 5                    | 8.7               | Yes                  | 5                    | 8.7               | Yes                  | 206                  | 1622 (mw)         | No                   |
|           |                          |                         | Right Side           |                   |                      | Top Side             |                   |                      | Bottom Side          |                   |                      |
|           |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
|           |                          |                         | 5                    | 8.7               | Yes                  | 10                   | 4.3               | Yes                  | 123                  | 1.7               | No                   |

## <Ant-0+1>

| Mode      | Max. Tune-up Power (dBm) | Max. Tune-up Power (mW) | Front Face           |                   |                      | Rear Face            |                   |                      | Left Side            |                   |                      |
|-----------|--------------------------|-------------------------|----------------------|-------------------|----------------------|----------------------|-------------------|----------------------|----------------------|-------------------|----------------------|
|           |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
| WLAN 5.8G | 15.5                     | 35                      | 5                    | 16.9              | Yes                  | 5                    | 16.9              | Yes                  | 5                    | 16.9              | Yes                  |
|           |                          |                         | Right Side           |                   |                      | Top Side             |                   |                      | Bottom Side          |                   |                      |
|           |                          |                         | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? | Ant. to Surface (mm) | Calculated Result | Require SAR Testing? |
|           |                          |                         | 5                    | 16.9              | Yes                  | 10                   | 8.4               | Yes                  | 28                   | 3                 | No                   |

### Note:

1. When separation distance  $\leq 50$  mm and the calculated result shown in above table is  $\leq 3.0$ , the SAR testing exclusion is applied.
2. When separation distance  $> 50$  mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.

## 4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

| Test Date     | Tissue Type | Frequency (MHz) | Liquid Temp. (°C) | Measured Conductivity ( $\sigma$ ) | Measured Permittivity ( $\epsilon_r$ ) | Target Conductivity ( $\sigma$ ) | Target Permittivity ( $\epsilon_r$ ) | Conductivity Deviation (%) | Permittivity Deviation (%) |
|---------------|-------------|-----------------|-------------------|------------------------------------|--|----------------------------------|--------------------------------------|----------------------------|----------------------------|
| Jan. 07, 2015 | Body        | 750             | 20.7              | 0.969                              | 55.447                                 | 0.96                             | 55.5                                 | 0.94                       | -0.10                      |
| Jan. 07, 2015 | Body        | 835             | 20.8              | 0.992                              | 55.56                                  | 0.97                             | 55.2                                 | 2.27                       | 0.65                       |
| Jan. 02, 2015 | Body        | 1750            | 21.2              | 1.462                              | 54.513                                 | 1.49                             | 53.4                                 | -1.88                      | 2.08                       |
| Dec. 30, 2014 | Body        | 1900            | 20.9              | 1.552                              | 54.013                                 | 1.52                             | 53.3                                 | 2.11                       | 1.34                       |
| Jan. 08, 2015 | Body        | 2600            | 21.1              | 2.2                                | 52.401                                 | 2.16                             | 52.5                                 | 1.85                       | -0.19                      |
| Jan. 09, 2015 | Body        | 5800            | 21.5              | 6.221                              | 47.4                                   | 6                                | 48.2                                 | 3.68                       | -1.66                      |

### Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within  $\pm 5\%$  of the target values. Liquid temperature during the SAR testing must be within  $\pm 2^\circ\text{C}$ .

## 4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

| Test Date     | Probe S/N | Calibration Point |      | Measured Conductivity ( $\sigma$ ) | Measured Permittivity ( $\epsilon_r$ ) | Validation for CW |                 |                | Validation for Modulation |             |      |
|---------------|-----------|-------------------|------|------------------------------------|--|-------------------|-----------------|----------------|---------------------------|-------------|------|
|               |           |                   |      |                                    |  | Sensitivity Range | Probe Linearity | Probe Isotropy | Modulation Type           | Duty Factor | PAR  |
| Jan. 07, 2015 | 3873      | Body              | 750  | 0.969                              | 55.447                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Jan. 07, 2015 | 3873      | Body              | 835  | 0.992                              | 55.56                                  | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Jan. 02, 2015 | 3873      | Body              | 1750 | 1.462                              | 54.513                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Dec. 30, 2014 | 3873      | Body              | 1900 | 1.552                              | 54.013                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Jan. 08, 2015 | 3873      | Body              | 2600 | 2.2                                | 52.401                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Jan. 09, 2015 | 3873      | Body              | 5800 | 6.221                              | 47.4                                   | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |

## 4.5 System Verification

The measuring result for system verification is tabulated as below.

| Test Date     | Mode | Frequency (MHz) | 1W Target SAR-1g (W/kg) | Measured SAR-1g (W/kg) | Normalized to 1W SAR-1g (W/kg) | Deviation (%) | Dipole S/N | Probe S/N | DAE S/N |
|---------------|------|-----------------|-------------------------|------------------------|--------------------------------|---------------|------------|-----------|---------|
| Jan. 07, 2015 | Body | 750             | 8.83                    | 2.24                   | 8.96                           | 1.47          | 1067       | 3873      | 1341    |
| Jan. 07, 2015 | Body | 835             | 9.53                    | 2.41                   | 9.64                           | 1.15          | 4d139      | 3873      | 1341    |
| Jan. 02, 2015 | Body | 1750            | 39.00                   | 9.7                    | 38.80                          | -0.51         | 1071       | 3873      | 1341    |
| Dec. 30, 2014 | Body | 1900            | 41.10                   | 10.4                   | 41.60                          | 1.22          | 5d159      | 3873      | 1341    |
| Jan. 08, 2015 | Body | 2600            | 56.50                   | 13.7                   | 54.80                          | -3.01         | 1020       | 3873      | 1341    |
| Jan. 09, 2015 | Body | 5800            | 74.00                   | 6.83                   | 68.30                          | -7.70         | 1133       | 3873      | 1341    |

### Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

## 4.6 Maximum Output Power

### 4.6.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

| Mode      | WCDMA Band II<br>(without Power Reduction) | WCDMA Band II<br>(with Power Reduction) | Power Reduction<br>(dBm) |
|-----------|--|---|--------------------------|
| RMC 12.2K | 24.0                                       | 16.0                                    | 8.0                      |
| HSDPA     | 23.0                                       | 15.0                                    | 8.0                      |
| HSUPA     | 23.0                                       | 15.0                                    | 8.0                      |

| Mode      | WCDMA Band V<br>(without Power Reduction) | WCDMA Band V<br>(with Power Reduction) | Power Reduction<br>(dBm) |
|-----------|---|--|--------------------------|
| RMC 12.2K | 23.5                                      | 15.5                                   | 8.0                      |
| HSDPA     | 22.5                                      | 14.5                                   | 8.0                      |
| HSUPA     | 22.5                                      | 14.5                                   | 8.0                      |

| Mode         | LTE 2<br>(without Power Reduction) | LTE 2<br>(with Power Reduction) | Power Reduction<br>(dBm) |
|--------------|------------------------------------|---------------------------------|--------------------------|
| QPSK / 16QAM | 23.0                               | 15.0                            | 8.0                      |

| Mode         | LTE 4<br>(without Power Reduction) | LTE 4<br>(with Power Reduction) | Power Reduction<br>(dBm) |
|--------------|------------------------------------|---------------------------------|--------------------------|
| QPSK / 16QAM | 23.0                               | 15.0                            | 8.0                      |

| Mode         | LTE 5<br>(without Power Reduction) | LTE 5<br>(with Power Reduction) | Power Reduction<br>(dBm) |
|--------------|------------------------------------|---------------------------------|--------------------------|
| QPSK / 16QAM | 22.5                               | 15.0                            | 7.5                      |

| Mode         | LTE 7<br>(without Power Reduction) | LTE 7<br>(with Power Reduction) | Power Reduction<br>(dBm) |
|--------------|------------------------------------|---------------------------------|--------------------------|
| QPSK / 16QAM | 23.0                               | 15.0                            | 8.0                      |

| Mode         | LTE 17<br>(without Power Reduction) | LTE 17<br>(with Power Reduction) | Power Reduction<br>(dBm) |
|--------------|-------------------------------------|----------------------------------|--------------------------|
| QPSK / 16QAM | 23.5                                | 15.0                             | 8.5                      |

| Mode         | 5.8G WLAN                                   |
|--------------|---|
| 802.11a      | Ant-0: 12.0<br>Ant-1: 12.5<br>Ant-0+1: 15.5 |
| 802.11n HT20 | Ant-0: 10.0<br>Ant-1: 10.5<br>Ant-0+1: 13.0 |

# FCC SAR Test Report

A D T

## 4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

| Band   | WCDMA Band II |        |        | WCDMA Band V |       |       | 3GPP<br>MPR<br>(dB) |
|--|---------------|--------|--------|--------------|-------|-------|---------------------|
| Channel  | 9262          | 9400   | 9538   | 4132         | 4182  | 4233  |                     |
| Frequency (MHz)                                      | 1852.4        | 1880.0 | 1907.6 | 826.4        | 836.4 | 846.6 |                     |
| EUT without Power Reduction (P-Sensor NOT Triggered) |               |        |        |              |       |       |                     |
| RMC 12.2K  | 23.38         | 23.50  | 23.63  | 22.82        | 23.03 | 23.21 | -                   |
| HSDPA Subtest-1                                      | 22.31         | 22.36  | 22.45  | 21.83        | 22.07 | 22.25 | 0                   |
| HSDPA Subtest-2                                      | 22.30         | 22.37  | 22.48  | 21.84        | 22.08 | 22.27 | 0                   |
| HSDPA Subtest-3                                      | 21.85         | 21.99  | 22.07  | 21.33        | 21.63 | 21.71 | 0.5                 |
| HSDPA Subtest-4                                      | 21.95         | 21.90  | 21.98  | 21.34        | 21.53 | 21.73 | 0.5                 |
| HSUPA Subtest-1                                      | 22.21         | 22.37  | 22.47  | 21.96        | 22.10 | 22.18 | 0                   |
| HSUPA Subtest-2                                      | 20.34         | 20.42  | 20.50  | 19.90        | 19.89 | 20.19 | 2                   |
| HSUPA Subtest-3                                      | 21.26         | 21.36  | 21.48  | 20.85        | 20.97 | 21.12 | 1                   |
| HSUPA Subtest-4                                      | 20.33         | 20.41  | 20.58  | 20.01        | 20.27 | 20.31 | 2                   |
| HSUPA Subtest-5                                      | 22.29         | 22.33  | 22.49  | 21.81        | 22.04 | 22.27 | 0                   |
| EUT with Power Reduction (P-Sensor Triggered)        |               |        |        |              |       |       |                     |
| RMC 12.2K  | 15.89         | 15.59  | 15.76  | 15.09        | 15.27 | 15.08 | -                   |
| HSDPA Subtest-1                                      | 14.56         | 14.22  | 13.76  | 13.78        | 14.18 | 14.10 | -                   |
| HSDPA Subtest-2                                      | 14.55         | 14.30  | 13.75  | 13.76        | 14.15 | 14.07 | -                   |
| HSDPA Subtest-3                                      | 14.02         | 13.81  | 13.26  | 13.33        | 13.70 | 13.60 | -                   |
| HSDPA Subtest-4                                      | 14.03         | 13.82  | 13.30  | 13.35        | 13.72 | 13.64 | -                   |
| HSUPA Subtest-1                                      | 14.40         | 14.07  | 13.92  | 14.16        | 13.97 | 13.96 | -                   |
| HSUPA Subtest-2                                      | 12.47         | 12.36  | 12.06  | 12.37        | 12.26 | 12.16 | -                   |
| HSUPA Subtest-3                                      | 13.26         | 13.02  | 12.88  | 12.97        | 12.98 | 13.00 | -                   |
| HSUPA Subtest-4                                      | 12.50         | 12.18  | 12.08  | 12.18        | 12.17 | 12.11 | -                   |
| HSUPA Subtest-5                                      | 14.56         | 14.30  | 13.76  | 14.04        | 14.19 | 14.10 | -                   |

| Band /<br>BW   | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|--|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|  |            |              | Low CH<br>18607 | Mid CH<br>18900 | High CH<br>19193 |                     | Low CH<br>18607 | Mid CH<br>18900 | High CH<br>19193 |                     |
|  |            |              | 1850.7<br>MHz   | 1880.0<br>MHz   | 1909.3<br>MHz    |                     | 1850.7<br>MHz   | 1880.0<br>MHz   | 1909.3<br>MHz    |                     |
| EUT without Power Reduction (P-Sensor NOT Triggered) |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 2 / 1.4M   | 1          | 0            | 22.21           | 22.22           | 22.46            | 0                   | 21.18           | 20.86           | 21.23            | 1                   |
|  | 1          | 2            | 22.02           | 21.73           | 22.24            | 0                   | 20.99           | 21.17           | 21.24            | 1                   |
|  | 1          | 5            | 21.75           | 22.18           | 22.34            | 0                   | 20.97           | 21.02           | 21.28            | 1                   |
|  | 3          | 0            | 21.81           | 21.82           | 22.45            | 0                   | 20.67           | 20.80           | 21.32            | 1                   |
|  | 3          | 1            | 21.80           | 21.86           | 22.39            | 0                   | 20.88           | 20.95           | 21.52            | 1                   |
|  | 3          | 3            | 21.93           | 21.98           | 22.43            | 0                   | 20.94           | 20.96           | 21.55            | 1                   |
|  | 6          | 0            | 20.87           | 20.81           | 21.40            | 1                   | 19.79           | 19.86           | 20.41            | 2                   |
| EUT with Power Reduction (P-Sensor Triggered)        |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 2 / 1.4M   | 1          | 0            | 14.55           | 14.59           | 14.52            | 0                   | 14.46           | 14.58           | 14.27            | 0                   |
|  | 1          | 2            | 14.33           | 14.16           | 14.12            | 0                   | 14.57           | 14.50           | 14.32            | 0                   |
|  | 1          | 5            | 14.28           | 14.11           | 14.16            | 0                   | 14.45           | 14.31           | 13.93            | 0                   |
|  | 3          | 0            | 14.56           | 14.57           | 14.55            | 0                   | 14.34           | 13.94           | 13.91            | 0                   |
|  | 3          | 1            | 14.35           | 14.13           | 13.98            | 0                   | 14.33           | 13.88           | 13.93            | 0                   |
|  | 3          | 3            | 14.32           | 14.01           | 14.11            | 0                   | 14.31           | 13.63           | 13.74            | 0                   |
|  | 6          | 0            | 14.32           | 14.45           | 14.27            | 0                   | 14.29           | 14.25           | 14.04            | 0                   |



# FCC SAR Test Report

A D T

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 18615 | Mid CH 18900 | High CH 19185 |               | Low CH 18615 | Mid CH 18900 | High CH 19185 |               |
|  |         |           | 1851.5 MHz   | 1880.0 MHz   | 1908.5 MHz    |               | 1851.5 MHz   | 1880.0 MHz   | 1908.5 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 2 / 3M   | 1       | 0         | 22.24        | 22.25        | 22.49         | 0             | 21.21        | 20.89        | 21.26         | 1             |
|  | 1       | 7         | 22.05        | 21.76        | 22.27         | 0             | 21.02        | 21.21        | 21.20         | 1             |
|  | 1       | 14        | 21.78        | 22.21        | 22.37         | 0             | 21.00        | 21.05        | 21.27         | 1             |
|  | 8       | 0         | 20.96        | 21.01        | 21.52         | 1             | 19.70        | 19.83        | 20.35         | 2             |
|  | 8       | 3         | 20.83        | 20.89        | 21.42         | 1             | 19.91        | 19.98        | 20.55         | 2             |
|  | 8       | 7         | 20.84        | 20.85        | 21.51         | 1             | 19.97        | 19.99        | 20.58         | 2             |
| 15   | 0       | 20.90     | 20.84        | 21.43        | 1             | 19.82         | 19.89        | 20.44        | 2             |               |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 2 / 3M   | 1       | 0         | 14.58        | 14.62        | 14.55         | 0             | 14.49        | 14.61        | 14.30         | 0             |
|  | 1       | 7         | 14.36        | 14.19        | 14.15         | 0             | 14.60        | 14.53        | 14.35         | 0             |
|  | 1       | 14        | 14.31        | 14.14        | 14.19         | 0             | 14.48        | 14.34        | 13.96         | 0             |
|  | 8       | 0         | 14.59        | 14.60        | 14.58         | 0             | 14.37        | 13.97        | 13.94         | 0             |
|  | 8       | 3         | 14.38        | 14.16        | 14.01         | 0             | 14.36        | 13.91        | 13.96         | 0             |
|  | 8       | 7         | 14.35        | 14.04        | 14.14         | 0             | 14.34        | 13.66        | 13.77         | 0             |
| 15   | 0       | 14.35     | 14.48        | 14.30        | 0             | 14.32         | 14.28        | 14.07        | 0             |               |

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 18625 | Mid CH 18900 | High CH 19175 |               | Low CH 18625 | Mid CH 18900 | High CH 19175 |               |
|  |         |           | 1852.5 MHz   | 1880.0 MHz   | 1907.5 MHz    |               | 1852.5 MHz   | 1880.0 MHz   | 1907.5 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 2 / 5M   | 1       | 0         | 22.26        | 22.27        | 22.51         | 0             | 21.23        | 20.91        | 21.28         | 1             |
|  | 1       | 12        | 22.07        | 21.78        | 22.29         | 0             | 21.04        | 21.23        | 21.22         | 1             |
|  | 1       | 24        | 21.80        | 22.23        | 22.39         | 0             | 21.02        | 21.07        | 21.29         | 1             |
|  | 12      | 0         | 20.98        | 21.03        | 21.54         | 1             | 19.72        | 19.85        | 20.37         | 2             |
|  | 12      | 6         | 20.85        | 20.91        | 21.44         | 1             | 19.93        | 20.00        | 20.57         | 2             |
|  | 12      | 13        | 20.86        | 20.87        | 21.53         | 1             | 19.99        | 20.01        | 20.60         | 2             |
| 25   | 0       | 20.92     | 20.86        | 21.45        | 1             | 19.84         | 19.91        | 20.46        | 2             |               |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 2 / 5M   | 1       | 0         | 14.62        | 14.66        | 14.59         | 0             | 14.53        | 14.65        | 14.34         | 0             |
|  | 1       | 12        | 14.40        | 14.23        | 14.19         | 0             | 14.64        | 14.57        | 14.39         | 0             |
|  | 1       | 24        | 14.35        | 14.18        | 14.23         | 0             | 14.52        | 14.38        | 14.00         | 0             |
|  | 12      | 0         | 14.63        | 14.64        | 14.62         | 0             | 14.41        | 14.01        | 13.98         | 0             |
|  | 12      | 6         | 14.42        | 14.20        | 14.05         | 0             | 14.40        | 13.95        | 14.00         | 0             |
|  | 12      | 13        | 14.39        | 14.08        | 14.18         | 0             | 14.38        | 13.70        | 13.81         | 0             |
| 25   | 0       | 14.39     | 14.52        | 14.34        | 0             | 14.36         | 14.32        | 14.11        | 0             |               |

# FCC SAR Test Report

A D T

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 18650 | Mid CH 18900 | High CH 19150 |               | Low CH 18650 | Mid CH 18900 | High CH 19150 |               |
|  |         |           | 1855.0 MHz   | 1880.0 MHz   | 1905.0 MHz    |               | 1855.0 MHz   | 1880.0 MHz   | 1905.0 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 2 / 10M  | 1       | 0         | 22.29        | 22.30        | 22.54         | 0             | 21.26        | 20.94        | 21.31         | 1             |
|  | 1       | 24        | 22.10        | 21.81        | 22.32         | 0             | 21.07        | 21.26        | 21.25         | 1             |
|  | 1       | 49        | 21.83        | 22.26        | 22.42         | 0             | 21.05        | 21.10        | 21.32         | 1             |
|  | 25      | 0         | 21.01        | 21.06        | 21.57         | 1             | 19.75        | 19.88        | 20.40         | 2             |
|  | 25      | 12        | 20.88        | 20.94        | 21.47         | 1             | 19.96        | 20.03        | 20.60         | 2             |
|  | 25      | 25        | 20.89        | 20.90        | 21.56         | 1             | 20.02        | 20.04        | 20.63         | 2             |
|  | 50      | 0         | 20.95        | 20.89        | 21.48         | 1             | 19.87        | 19.94        | 20.49         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 2 / 10M  | 1       | 0         | 14.65        | 14.69        | 14.62         | 0             | 14.56        | 14.68        | 14.37         | 0             |
|  | 1       | 24        | 14.43        | 14.26        | 14.22         | 0             | 14.67        | 14.60        | 14.42         | 0             |
|  | 1       | 49        | 14.38        | 14.21        | 14.26         | 0             | 14.55        | 14.41        | 14.03         | 0             |
|  | 25      | 0         | 14.66        | 14.67        | 14.65         | 0             | 14.44        | 14.04        | 14.01         | 0             |
|  | 25      | 12        | 14.45        | 14.23        | 14.08         | 0             | 14.43        | 13.98        | 14.03         | 0             |
|  | 25      | 25        | 14.42        | 14.11        | 14.21         | 0             | 14.41        | 13.73        | 13.84         | 0             |
|  | 50      | 0         | 14.42        | 14.55        | 14.37         | 0             | 14.39        | 14.35        | 14.14         | 0             |

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 18675 | Mid CH 18900 | High CH 19125 |               | Low CH 18675 | Mid CH 18900 | High CH 19125 |               |
|  |         |           | 1857.5 MHz   | 1880.0 MHz   | 1902.5 MHz    |               | 1857.5 MHz   | 1880.0 MHz   | 1902.5 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 2 / 15M  | 1       | 0         | 22.34        | 22.35        | 22.59         | 0             | 21.31        | 20.99        | 21.36         | 1             |
|  | 1       | 37        | 22.15        | 21.86        | 22.37         | 0             | 21.12        | 21.31        | 21.30         | 1             |
|  | 1       | 74        | 21.88        | 22.31        | 22.47         | 0             | 21.10        | 21.15        | 21.37         | 1             |
|  | 36      | 0         | 21.06        | 21.11        | 21.62         | 1             | 19.80        | 19.93        | 20.45         | 2             |
|  | 36      | 19        | 20.93        | 20.99        | 21.52         | 1             | 20.01        | 20.08        | 20.65         | 2             |
|  | 36      | 39        | 20.94        | 20.95        | 21.61         | 1             | 20.07        | 20.09        | 20.68         | 2             |
|  | 75      | 0         | 21.00        | 20.94        | 21.53         | 1             | 19.92        | 19.99        | 20.54         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 2 / 15M  | 1       | 0         | 14.70        | 14.74        | 14.67         | 0             | 14.61        | 14.73        | 14.42         | 0             |
|  | 1       | 37        | 14.48        | 14.31        | 14.27         | 0             | 14.72        | 14.65        | 14.47         | 0             |
|  | 1       | 74        | 14.43        | 14.26        | 14.31         | 0             | 14.60        | 14.46        | 14.08         | 0             |
|  | 36      | 0         | 14.71        | 14.72        | 14.70         | 0             | 14.49        | 14.09        | 14.06         | 0             |
|  | 36      | 19        | 14.50        | 14.28        | 14.13         | 0             | 14.48        | 14.03        | 14.08         | 0             |
|  | 36      | 39        | 14.47        | 14.16        | 14.26         | 0             | 14.46        | 13.78        | 13.89         | 0             |
|  | 75      | 0         | 14.47        | 14.60        | 14.42         | 0             | 14.44        | 14.40        | 14.19         | 0             |

# FCC SAR Test Report

A D T

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 18700 | Mid CH 18900 | High CH 19100 |               | Low CH 18700 | Mid CH 18900 | High CH 19100 |               |
|  |         |           | 1860.0 MHz   | 1880.0 MHz   | 1900.0 MHz    |               | 1860.0 MHz   | 1880.0 MHz   | 1900.0 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 2 / 20M  | 1       | 0         | 22.38        | 22.39        | 22.63         | 0             | 21.35        | 21.03        | 21.40         | 1             |
|  | 1       | 50        | 22.19        | 21.90        | 22.41         | 0             | 21.16        | 21.35        | 21.34         | 1             |
|  | 1       | 99        | 21.92        | 22.35        | 22.51         | 0             | 21.14        | 21.19        | 21.41         | 1             |
|  | 50      | 0         | 21.10        | 21.15        | 21.66         | 1             | 19.84        | 19.97        | 20.49         | 2             |
|  | 50      | 25        | 20.97        | 21.03        | 21.56         | 1             | 20.05        | 20.12        | 20.69         | 2             |
|  | 50      | 50        | 20.98        | 20.99        | 21.65         | 1             | 20.11        | 20.13        | 20.72         | 2             |
|  | 100     | 0         | 21.04        | 20.98        | 21.57         | 1             | 19.96        | 20.03        | 20.58         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 2 / 20M  | 1       | 0         | 14.74        | 14.78        | 14.71         | 0             | 14.65        | 14.77        | 14.46         | 0             |
|  | 1       | 50        | 14.52        | 14.35        | 14.31         | 0             | 14.76        | 14.69        | 14.51         | 0             |
|  | 1       | 99        | 14.47        | 14.30        | 14.35         | 0             | 14.64        | 14.50        | 14.12         | 0             |
|  | 50      | 0         | 14.75        | 14.76        | 14.74         | 0             | 14.53        | 14.13        | 14.10         | 0             |
|  | 50      | 25        | 14.54        | 14.32        | 14.17         | 0             | 14.52        | 14.07        | 14.12         | 0             |
|  | 50      | 50        | 14.51        | 14.20        | 14.30         | 0             | 14.50        | 13.82        | 13.93         | 0             |
|  | 100     | 0         | 14.51        | 14.64        | 14.46         | 0             | 14.48        | 14.44        | 14.23         | 0             |

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 19957 | Mid CH 20175 | High CH 20393 |               | Low CH 19957 | Mid CH 20175 | High CH 20393 |               |
|  |         |           | 1710.7 MHz   | 1732.5 MHz   | 1754.3 MHz    |               | 1710.7 MHz   | 1732.5 MHz   | 1754.3 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 4 / 1.4M   | 1       | 0         | 22.29        | 22.16        | 22.18         | 0             | 21.12        | 21.12        | 21.19         | 1             |
|  | 1       | 2         | 22.01        | 21.93        | 21.62         | 0             | 21.20        | 21.04        | 20.74         | 1             |
|  | 1       | 5         | 22.05        | 21.71        | 21.61         | 0             | 21.02        | 20.79        | 20.79         | 1             |
|  | 3       | 0         | 22.28        | 21.91        | 21.74         | 0             | 21.26        | 21.01        | 20.82         | 1             |
|  | 3       | 1         | 22.05        | 21.90        | 21.63         | 0             | 21.10        | 20.94        | 20.64         | 1             |
|  | 3       | 3         | 22.04        | 21.77        | 21.52         | 0             | 21.03        | 20.81        | 20.55         | 1             |
|  | 6       | 0         | 21.32        | 21.17        | 21.14         | 1             | 20.10        | 19.94        | 19.68         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 4 / 1.4M   | 1       | 0         | 14.31        | 14.34        | 14.38         | 0             | 14.27        | 14.30        | 14.37         | 0             |
|  | 1       | 2         | 14.18        | 13.99        | 14.15         | 0             | 14.31        | 14.34        | 14.22         | 0             |
|  | 1       | 5         | 14.05        | 14.18        | 14.07         | 0             | 14.09        | 14.33        | 14.36         | 0             |
|  | 3       | 0         | 14.27        | 14.26        | 14.29         | 0             | 13.87        | 14.14        | 14.33         | 0             |
|  | 3       | 1         | 14.15        | 14.18        | 14.13         | 0             | 13.88        | 14.18        | 14.13         | 0             |
|  | 3       | 3         | 14.08        | 14.25        | 14.09         | 0             | 13.86        | 14.23        | 14.09         | 0             |
|  | 6       | 0         | 14.16        | 14.19        | 14.25         | 0             | 14.06        | 14.19        | 14.20         | 0             |

# FCC SAR Test Report

A D T

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 19965 | Mid CH 20175 | High CH 20385 |               | Low CH 19965 | Mid CH 20175 | High CH 20385 |               |
|  |         |           | 1711.5 MHz   | 1732.5 MHz   | 1753.5 MHz    |               | 1711.5 MHz   | 1732.5 MHz   | 1753.5 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 4 / 3M   | 1       | 0         | 22.32        | 22.19        | 22.21         | 0             | 21.15        | 21.15        | 21.22         | 1             |
|  | 1       | 7         | 22.04        | 21.96        | 21.65         | 0             | 21.23        | 21.07        | 20.77         | 1             |
|  | 1       | 14        | 22.08        | 21.74        | 21.64         | 0             | 21.05        | 20.82        | 20.82         | 1             |
|  | 8       | 0         | 21.34        | 21.24        | 21.17         | 1             | 20.29        | 20.04        | 19.85         | 2             |
|  | 8       | 3         | 21.08        | 20.93        | 20.66         | 1             | 20.13        | 19.97        | 19.67         | 2             |
|  | 8       | 7         | 21.07        | 20.80        | 20.55         | 1             | 20.06        | 19.84        | 19.58         | 2             |
| 15   | 0       | 21.35     | 21.20        | 21.17        | 1             | 20.13         | 19.97        | 19.71        | 2             |               |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 4 / 3M   | 1       | 0         | 14.34        | 14.37        | 14.41         | 0             | 14.30        | 14.33        | 14.40         | 0             |
|  | 1       | 7         | 14.21        | 14.02        | 14.18         | 0             | 14.34        | 14.37        | 14.25         | 0             |
|  | 1       | 14        | 14.08        | 14.21        | 14.10         | 0             | 14.12        | 14.36        | 14.39         | 0             |
|  | 8       | 0         | 14.30        | 14.29        | 14.32         | 0             | 13.90        | 14.17        | 14.36         | 0             |
|  | 8       | 3         | 14.18        | 14.21        | 14.16         | 0             | 13.91        | 14.21        | 14.16         | 0             |
|  | 8       | 7         | 14.11        | 14.28        | 14.12         | 0             | 13.89        | 14.26        | 14.12         | 0             |
| 15   | 0       | 14.19     | 14.22        | 14.28        | 0             | 14.09         | 14.22        | 14.23        | 0             |               |

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 19975 | Mid CH 20175 | High CH 20375 |               | Low CH 19975 | Mid CH 20175 | High CH 20375 |               |
|  |         |           | 1712.5 MHz   | 1732.5 MHz   | 1752.5 MHz    |               | 1712.5 MHz   | 1732.5 MHz   | 1752.5 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 4 / 5M   | 1       | 0         | 22.35        | 22.22        | 22.24         | 0             | 21.18        | 21.18        | 21.25         | 1             |
|  | 1       | 12        | 22.07        | 21.99        | 21.68         | 0             | 21.26        | 21.10        | 20.80         | 1             |
|  | 1       | 24        | 22.11        | 21.77        | 21.67         | 0             | 21.08        | 20.85        | 20.85         | 1             |
|  | 12      | 0         | 21.37        | 21.27        | 21.20         | 1             | 20.32        | 20.07        | 19.88         | 2             |
|  | 12      | 6         | 21.11        | 20.96        | 20.69         | 1             | 20.16        | 20.00        | 19.70         | 2             |
|  | 12      | 13        | 21.10        | 20.83        | 20.58         | 1             | 20.09        | 19.87        | 19.61         | 2             |
| 25   | 0       | 21.38     | 21.23        | 21.20        | 1             | 20.16         | 20.00        | 19.74        | 2             |               |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 4 / 5M   | 1       | 0         | 14.36        | 14.39        | 14.43         | 0             | 14.32        | 14.35        | 14.42         | 0             |
|  | 1       | 12        | 14.23        | 14.04        | 14.20         | 0             | 14.36        | 14.39        | 14.27         | 0             |
|  | 1       | 24        | 14.10        | 14.23        | 14.12         | 0             | 14.14        | 14.38        | 14.41         | 0             |
|  | 12      | 0         | 14.32        | 14.31        | 14.34         | 0             | 13.92        | 14.19        | 14.38         | 0             |
|  | 12      | 6         | 14.20        | 14.23        | 14.18         | 0             | 13.93        | 14.23        | 14.18         | 0             |
|  | 12      | 13        | 14.13        | 14.30        | 14.14         | 0             | 13.91        | 14.28        | 14.14         | 0             |
| 25   | 0       | 14.21     | 14.24        | 14.30        | 0             | 14.11         | 14.24        | 14.25        | 0             |               |

# FCC SAR Test Report

A D T

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 20000 | Mid CH 20175 | High CH 20350 |               | Low CH 20000 | Mid CH 20175 | High CH 20350 |               |
|  |         |           | 1715.0 MHz   | 1732.5 MHz   | 1750.0 MHz    |               | 1715.0 MHz   | 1732.5 MHz   | 1750.0 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 4 / 10M  | 1       | 0         | 22.39        | 22.26        | 22.28         | 0             | 21.22        | 21.22        | 21.29         | 1             |
|  | 1       | 24        | 22.11        | 22.03        | 21.72         | 0             | 21.30        | 21.14        | 20.84         | 1             |
|  | 1       | 49        | 22.15        | 21.81        | 21.71         | 0             | 21.12        | 20.89        | 20.89         | 1             |
|  | 25      | 0         | 21.41        | 21.31        | 21.24         | 1             | 20.36        | 20.11        | 19.92         | 2             |
|  | 25      | 12        | 21.15        | 21.00        | 20.73         | 1             | 20.20        | 20.04        | 19.74         | 2             |
|  | 25      | 25        | 21.14        | 20.87        | 20.62         | 1             | 20.13        | 19.91        | 19.65         | 2             |
|  | 50      | 0         | 21.42        | 21.27        | 21.24         | 1             | 20.20        | 20.04        | 19.78         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 4 / 10M  | 1       | 0         | 14.41        | 14.44        | 14.48         | 0             | 14.37        | 14.40        | 14.47         | 0             |
|  | 1       | 24        | 14.28        | 14.09        | 14.25         | 0             | 14.41        | 14.44        | 14.32         | 0             |
|  | 1       | 49        | 14.15        | 14.28        | 14.17         | 0             | 14.19        | 14.43        | 14.46         | 0             |
|  | 25      | 0         | 14.37        | 14.36        | 14.39         | 0             | 13.97        | 14.24        | 14.43         | 0             |
|  | 25      | 12        | 14.25        | 14.28        | 14.23         | 0             | 13.98        | 14.28        | 14.23         | 0             |
|  | 25      | 25        | 14.18        | 14.35        | 14.19         | 0             | 13.96        | 14.33        | 14.19         | 0             |
|  | 50      | 0         | 14.26        | 14.29        | 14.35         | 0             | 14.16        | 14.29        | 14.30         | 0             |

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 20025 | Mid CH 20175 | High CH 20325 |               | Low CH 20025 | Mid CH 20175 | High CH 20325 |               |
|  |         |           | 1717.5 MHz   | 1732.5 MHz   | 1747.5 MHz    |               | 1717.5 MHz   | 1732.5 MHz   | 1747.5 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 4 / 15M  | 1       | 0         | 22.43        | 22.30        | 22.32         | 0             | 21.26        | 21.26        | 21.33         | 1             |
|  | 1       | 37        | 22.15        | 22.07        | 21.76         | 0             | 21.34        | 21.18        | 20.88         | 1             |
|  | 1       | 74        | 22.19        | 21.85        | 21.75         | 0             | 21.16        | 20.93        | 20.93         | 1             |
|  | 36      | 0         | 21.45        | 21.35        | 21.28         | 1             | 20.40        | 20.15        | 19.96         | 2             |
|  | 36      | 19        | 21.19        | 21.04        | 20.77         | 1             | 20.24        | 20.08        | 19.78         | 2             |
|  | 36      | 39        | 21.18        | 20.91        | 20.66         | 1             | 20.17        | 19.95        | 19.69         | 2             |
|  | 75      | 0         | 21.46        | 21.31        | 21.28         | 1             | 20.24        | 20.08        | 19.82         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 4 / 15M  | 1       | 0         | 14.44        | 14.47        | 14.51         | 0             | 14.40        | 14.43        | 14.50         | 0             |
|  | 1       | 37        | 14.31        | 14.12        | 14.28         | 0             | 14.44        | 14.47        | 14.35         | 0             |
|  | 1       | 74        | 14.18        | 14.31        | 14.20         | 0             | 14.22        | 14.46        | 14.49         | 0             |
|  | 36      | 0         | 14.40        | 14.39        | 14.42         | 0             | 14.00        | 14.27        | 14.46         | 0             |
|  | 36      | 19        | 14.28        | 14.31        | 14.26         | 0             | 14.01        | 14.31        | 14.26         | 0             |
|  | 36      | 39        | 14.21        | 14.38        | 14.22         | 0             | 13.99        | 14.36        | 14.22         | 0             |
|  | 75      | 0         | 14.29        | 14.32        | 14.38         | 0             | 14.19        | 14.32        | 14.33         | 0             |

# FCC SAR Test Report

A D T

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 20050 | Mid CH 20175 | High CH 20300 |               | Low CH 20050 | Mid CH 20175 | High CH 20300 |               |
|  |         |           | 1720.0 MHz   | 1732.5 MHz   | 1745.0 MHz    |               | 1720.0 MHz   | 1732.5 MHz   | 1745.0 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 4 / 20M  | 1       | 0         | 22.46        | 22.33        | 22.35         | 0             | 21.29        | 21.29        | 21.36         | 1             |
|  | 1       | 50        | 22.18        | 22.10        | 21.79         | 0             | 21.37        | 21.21        | 20.91         | 1             |
|  | 1       | 99        | 22.22        | 21.88        | 21.78         | 0             | 21.19        | 20.96        | 20.96         | 1             |
|  | 50      | 0         | 21.48        | 21.38        | 21.31         | 1             | 20.43        | 20.18        | 19.99         | 2             |
|  | 50      | 25        | 21.22        | 21.07        | 20.80         | 1             | 20.27        | 20.11        | 19.81         | 2             |
|  | 50      | 50        | 21.21        | 20.94        | 20.69         | 1             | 20.20        | 19.98        | 19.72         | 2             |
|  | 100     | 0         | 21.49        | 21.34        | 21.31         | 1             | 20.27        | 20.11        | 19.85         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 4 / 20M  | 1       | 0         | 14.48        | 14.51        | 14.55         | 0             | 14.44        | 14.47        | 14.54         | 0             |
|  | 1       | 50        | 14.35        | 14.16        | 14.32         | 0             | 14.48        | 14.51        | 14.39         | 0             |
|  | 1       | 99        | 14.22        | 14.35        | 14.24         | 0             | 14.26        | 14.50        | 14.53         | 0             |
|  | 50      | 0         | 14.44        | 14.43        | 14.46         | 0             | 14.04        | 14.31        | 14.50         | 0             |
|  | 50      | 25        | 14.32        | 14.35        | 14.30         | 0             | 14.05        | 14.35        | 14.30         | 0             |
|  | 50      | 50        | 14.25        | 14.42        | 14.26         | 0             | 14.03        | 14.40        | 14.26         | 0             |
|  | 100     | 0         | 14.33        | 14.36        | 14.42         | 0             | 14.23        | 14.36        | 14.37         | 0             |

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 20407 | Mid CH 20525 | High CH 20643 |               | Low CH 20407 | Mid CH 20525 | High CH 20643 |               |
|  |         |           | 824.7 MHz    | 836.5 MHz    | 848.3 MHz     |               | 824.7 MHz    | 836.5 MHz    | 848.3 MHz     |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 5 / 1.4M   | 1       | 0         | 21.97        | 22.06        | 22.17         | 0             | 20.93        | 21.13        | 21.17         | 1             |
|  | 1       | 2         | 21.81        | 21.94        | 22.11         | 0             | 20.93        | 20.82        | 20.97         | 1             |
|  | 1       | 5         | 21.95        | 22.04        | 22.13         | 0             | 20.83        | 21.09        | 21.06         | 1             |
|  | 3       | 0         | 21.79        | 21.95        | 21.96         | 0             | 21.07        | 20.91        | 21.18         | 1             |
|  | 3       | 1         | 21.80        | 21.87        | 22.01         | 0             | 20.91        | 20.95        | 20.96         | 1             |
|  | 3       | 3         | 21.93        | 21.90        | 22.16         | 0             | 20.97        | 21.12        | 21.07         | 1             |
|  | 6       | 0         | 20.98        | 20.96        | 21.23         | 1             | 19.98        | 19.90        | 20.14         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 5 / 1.4M   | 1       | 0         | 14.52        | 14.48        | 14.53         | 0             | 14.48        | 14.31        | 14.34         | 0             |
|  | 1       | 2         | 14.20        | 14.00        | 14.11         | 0             | 14.13        | 14.33        | 14.14         | 0             |
|  | 1       | 5         | 14.48        | 14.38        | 14.26         | 0             | 14.41        | 14.52        | 14.32         | 0             |
|  | 3       | 0         | 14.21        | 14.19        | 14.11         | 0             | 14.04        | 14.06        | 14.06         | 0             |
|  | 3       | 1         | 14.03        | 13.83        | 13.93         | 0             | 13.88        | 13.92        | 14.05         | 0             |
|  | 3       | 3         | 14.38        | 14.32        | 14.44         | 0             | 14.06        | 14.04        | 14.08         | 0             |
|  | 6       | 0         | 14.29        | 14.31        | 14.45         | 0             | 14.03        | 14.11        | 14.08         | 0             |

# FCC SAR Test Report

A D T

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 20415 | Mid CH 20525 | High CH 20635 |               | Low CH 20415 | Mid CH 20525 | High CH 20635 |               |
|  |         |           | 825.5 MHz    | 836.5 MHz    | 847.5 MHz     |               | 825.5 MHz    | 836.5 MHz    | 847.5 MHz     |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 5 / 3M   | 1       | 0         | 22.01        | 22.10        | 22.21         | 0             | 20.97        | 21.17        | 21.21         | 1             |
|  | 1       | 7         | 21.85        | 21.98        | 22.15         | 0             | 20.97        | 20.86        | 21.01         | 1             |
|  | 1       | 14        | 21.99        | 22.08        | 22.17         | 0             | 20.87        | 21.13        | 21.10         | 1             |
|  | 8       | 0         | 20.83        | 20.94        | 21.00         | 1             | 20.11        | 19.95        | 20.22         | 2             |
|  | 8       | 3         | 20.84        | 20.91        | 21.05         | 1             | 19.95        | 19.99        | 20.00         | 2             |
|  | 8       | 7         | 20.97        | 20.99        | 21.23         | 1             | 20.01        | 20.16        | 20.11         | 2             |
|  | 15      | 0         | 21.02        | 21.00        | 21.27         | 1             | 20.02        | 19.94        | 20.18         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 5 / 3M   | 1       | 0         | 14.56        | 14.52        | 14.57         | 0             | 14.52        | 14.35        | 14.38         | 0             |
|  | 1       | 7         | 14.24        | 14.04        | 14.15         | 0             | 14.17        | 14.37        | 14.18         | 0             |
|  | 1       | 14        | 14.52        | 14.42        | 14.30         | 0             | 14.45        | 14.56        | 14.36         | 0             |
|  | 8       | 0         | 14.25        | 14.23        | 14.15         | 0             | 14.08        | 14.10        | 14.10         | 0             |
|  | 8       | 3         | 14.07        | 13.87        | 13.97         | 0             | 13.92        | 13.96        | 14.09         | 0             |
|  | 8       | 7         | 14.42        | 14.36        | 14.48         | 0             | 14.10        | 14.08        | 14.12         | 0             |
|  | 15      | 0         | 14.33        | 14.35        | 14.49         | 0             | 14.07        | 14.15        | 14.12         | 0             |

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 20425 | Mid CH 20525 | High CH 20625 |               | Low CH 20425 | Mid CH 20525 | High CH 20625 |               |
|  |         |           | 826.5 MHz    | 836.5 MHz    | 846.5 MHz     |               | 826.5 MHz    | 836.5 MHz    | 846.5 MHz     |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 5 / 5M   | 1       | 0         | 22.04        | 22.13        | 22.24         | 0             | 21.00        | 21.20        | 21.24         | 1             |
|  | 1       | 12        | 21.88        | 22.01        | 22.18         | 0             | 21.00        | 20.89        | 21.04         | 1             |
|  | 1       | 24        | 22.02        | 22.11        | 22.20         | 0             | 20.90        | 21.16        | 21.13         | 1             |
|  | 12      | 0         | 20.86        | 20.97        | 21.03         | 1             | 20.14        | 19.98        | 20.25         | 2             |
|  | 12      | 6         | 20.87        | 20.94        | 21.08         | 1             | 19.98        | 20.02        | 20.03         | 2             |
|  | 12      | 13        | 21.00        | 21.02        | 21.26         | 1             | 20.04        | 20.19        | 20.14         | 2             |
|  | 25      | 0         | 21.05        | 21.03        | 21.30         | 1             | 20.05        | 19.97        | 20.21         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 5 / 5M   | 1       | 0         | 14.61        | 14.57        | 14.62         | 0             | 14.57        | 14.40        | 14.43         | 0             |
|  | 1       | 12        | 14.29        | 14.09        | 14.20         | 0             | 14.22        | 14.42        | 14.23         | 0             |
|  | 1       | 24        | 14.57        | 14.47        | 14.35         | 0             | 14.50        | 14.61        | 14.41         | 0             |
|  | 12      | 0         | 14.30        | 14.28        | 14.20         | 0             | 14.13        | 14.15        | 14.15         | 0             |
|  | 12      | 6         | 14.12        | 13.92        | 14.02         | 0             | 13.97        | 14.01        | 14.14         | 0             |
|  | 12      | 13        | 14.47        | 14.41        | 14.53         | 0             | 14.15        | 14.13        | 14.17         | 0             |
|  | 25      | 0         | 14.38        | 14.40        | 14.54         | 0             | 14.12        | 14.20        | 14.17         | 0             |

# FCC SAR Test Report

A D T

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 20450 | Mid CH 20525 | High CH 20600 |               | Low CH 20450 | Mid CH 20525 | High CH 20600 |               |
|  |         |           | 829.0 MHz    | 836.5 MHz    | 844.0 MHz     |               | 829.0 MHz    | 836.5 MHz    | 844.0 MHz     |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 5 / 10M  | 1       | 0         | 22.08        | 22.17        | 22.28         | 0             | 21.04        | 21.24        | 21.28         | 1             |
|  | 1       | 24        | 21.92        | 22.05        | 22.22         | 0             | 21.04        | 20.93        | 21.08         | 1             |
|  | 1       | 49        | 22.06        | 22.15        | 22.24         | 0             | 20.94        | 21.20        | 21.17         | 1             |
|  | 25      | 0         | 20.90        | 21.01        | 21.07         | 1             | 20.18        | 20.02        | 20.29         | 2             |
|  | 25      | 12        | 20.91        | 20.98        | 21.12         | 1             | 20.02        | 20.06        | 20.07         | 2             |
|  | 25      | 25        | 21.04        | 21.06        | 21.30         | 1             | 20.08        | 20.23        | 20.18         | 2             |
|  | 50      | 0         | 21.09        | 21.07        | 21.34         | 1             | 20.09        | 20.01        | 20.25         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 5 / 10M  | 1       | 0         | 14.64        | 14.60        | 14.65         | 0             | 14.60        | 14.43        | 14.46         | 0             |
|  | 1       | 24        | 14.32        | 14.12        | 14.23         | 0             | 14.25        | 14.45        | 14.26         | 0             |
|  | 1       | 49        | 14.60        | 14.50        | 14.38         | 0             | 14.53        | 14.64        | 14.44         | 0             |
|  | 25      | 0         | 14.33        | 14.31        | 14.23         | 0             | 14.16        | 14.18        | 14.18         | 0             |
|  | 25      | 12        | 14.15        | 13.95        | 14.05         | 0             | 14.00        | 14.04        | 14.17         | 0             |
|  | 25      | 25        | 14.50        | 14.44        | 14.56         | 0             | 14.18        | 14.16        | 14.20         | 0             |
|  | 50      | 0         | 14.41        | 14.43        | 14.57         | 0             | 14.15        | 14.23        | 14.20         | 0             |

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 20775 | Mid CH 21100 | High CH 21425 |               | Low CH 20775 | Mid CH 21100 | High CH 21425 |               |
|  |         |           | 2502.5 MHz   | 2535.0 MHz   | 2567.5 MHz    |               | 2502.5 MHz   | 2535.0 MHz   | 2567.5 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 7 / 5M   | 1       | 0         | 22.51        | 22.68        | 22.49         | 0             | 21.23        | 21.76        | 21.59         | 1             |
|  | 1       | 12        | 22.23        | 22.41        | 22.48         | 0             | 21.33        | 21.71        | 21.61         | 1             |
|  | 1       | 24        | 22.22        | 22.24        | 22.48         | 0             | 21.33        | 21.75        | 21.58         | 1             |
|  | 12      | 0         | 21.20        | 21.47        | 21.55         | 1             | 20.38        | 20.42        | 20.54         | 2             |
|  | 12      | 6         | 21.50        | 21.66        | 21.64         | 1             | 20.26        | 20.65        | 20.56         | 2             |
|  | 12      | 13        | 21.26        | 21.51        | 21.57         | 1             | 20.23        | 20.60        | 20.60         | 2             |
|  | 25      | 0         | 21.15        | 21.64        | 21.48         | 1             | 20.09        | 20.63        | 20.59         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 7 / 5M   | 1       | 0         | 14.27        | 14.39        | 14.36         | 0             | 14.24        | 14.30        | 13.83         | 0             |
|  | 1       | 12        | 13.91        | 14.24        | 14.29         | 0             | 14.28        | 14.18        | 14.31         | 0             |
|  | 1       | 24        | 13.78        | 13.81        | 14.09         | 0             | 14.19        | 14.10        | 14.24         | 0             |
|  | 12      | 0         | 14.29        | 14.35        | 14.34         | 0             | 13.52        | 14.07        | 13.89         | 0             |
|  | 12      | 6         | 13.91        | 14.21        | 14.31         | 0             | 13.58        | 14.06        | 14.22         | 0             |
|  | 12      | 13        | 13.65        | 13.81        | 14.20         | 0             | 13.57        | 13.62        | 14.11         | 0             |
|  | 25      | 0         | 13.77        | 14.33        | 14.26         | 0             | 13.48        | 13.97        | 14.00         | 0             |



# FCC SAR Test Report

A D T

| Band /<br>BW   | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|--|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|  |            |              | Low CH<br>20800 | Mid CH<br>21100 | High CH<br>21400 |                     | Low CH<br>20800 | Mid CH<br>21100 | High CH<br>21400 |                     |
|  |            |              | 2505.0<br>MHz   | 2535.0<br>MHz   | 2565.0<br>MHz    |                     | 2505.0<br>MHz   | 2535.0<br>MHz   | 2565.0<br>MHz    |                     |
| EUT without Power Reduction (P-Sensor NOT Triggered) |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 7 / 10M  | 1          | 0            | 22.56           | 22.73           | 22.54            | 0                   | 21.28           | 21.81           | 21.64            | 1                   |
|  | 1          | 24           | 22.28           | 22.46           | 22.53            | 0                   | 21.38           | 21.76           | 21.66            | 1                   |
|  | 1          | 49           | 22.27           | 22.29           | 22.53            | 0                   | 21.38           | 21.80           | 21.63            | 1                   |
|  | 25         | 0            | 21.25           | 21.52           | 21.60            | 1                   | 20.43           | 20.47           | 20.59            | 2                   |
|  | 25         | 12           | 21.55           | 21.71           | 21.69            | 1                   | 20.31           | 20.70           | 20.61            | 2                   |
|  | 25         | 25           | 21.31           | 21.56           | 21.62            | 1                   | 20.28           | 20.65           | 20.65            | 2                   |
|  | 50         | 0            | 21.20           | 21.69           | 21.53            | 1                   | 20.14           | 20.68           | 20.64            | 2                   |
| EUT with Power Reduction (P-Sensor Triggered)        |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 7 / 10M  | 1          | 0            | 14.33           | 14.45           | 14.42            | 0                   | 14.30           | 14.36           | 13.89            | 0                   |
|  | 1          | 24           | 13.97           | 14.30           | 14.35            | 0                   | 14.34           | 14.24           | 14.37            | 0                   |
|  | 1          | 49           | 13.84           | 13.87           | 14.15            | 0                   | 14.25           | 14.16           | 14.30            | 0                   |
|  | 25         | 0            | 14.35           | 14.41           | 14.40            | 0                   | 13.58           | 14.13           | 13.95            | 0                   |
|  | 25         | 12           | 13.97           | 14.27           | 14.37            | 0                   | 13.64           | 14.12           | 14.28            | 0                   |
|  | 25         | 25           | 13.71           | 13.87           | 14.26            | 0                   | 13.63           | 13.68           | 14.17            | 0                   |
|  | 50         | 0            | 13.83           | 14.39           | 14.32            | 0                   | 13.54           | 14.03           | 14.06            | 0                   |

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 20825 | Mid CH 21100 | High CH 21375 |               | Low CH 20825 | Mid CH 21100 | High CH 21375 |               |
|  |         |           | 2507.5 MHz   | 2535.0 MHz   | 2562.5 MHz    |               | 2507.5 MHz   | 2535.0 MHz   | 2562.5 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 7 / 15M  | 1       | 0         | 22.60        | 22.77        | 22.58         | 0             | 21.32        | 21.85        | 21.68         | 1             |
|  | 1       | 37        | 22.32        | 22.50        | 22.57         | 0             | 21.42        | 21.80        | 21.70         | 1             |
|  | 1       | 74        | 22.31        | 22.33        | 22.57         | 0             | 21.42        | 21.84        | 21.67         | 1             |
|  | 36      | 0         | 21.29        | 21.56        | 21.64         | 1             | 20.47        | 20.51        | 20.63         | 2             |
|  | 36      | 19        | 21.59        | 21.75        | 21.73         | 1             | 20.35        | 20.74        | 20.65         | 2             |
|  | 36      | 39        | 21.35        | 21.60        | 21.66         | 1             | 20.32        | 20.69        | 20.69         | 2             |
|  | 75      | 0         | 21.24        | 21.73        | 21.57         | 1             | 20.18        | 20.72        | 20.68         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 7 / 15M  | 1       | 0         | 14.38        | 14.50        | 14.47         | 0             | 14.35        | 14.41        | 13.94         | 0             |
|  | 1       | 37        | 14.02        | 14.35        | 14.40         | 0             | 14.39        | 14.29        | 14.42         | 0             |
|  | 1       | 74        | 13.89        | 13.92        | 14.20         | 0             | 14.30        | 14.21        | 14.35         | 0             |
|  | 36      | 0         | 14.40        | 14.46        | 14.45         | 0             | 13.63        | 14.18        | 14.00         | 0             |
|  | 36      | 19        | 14.02        | 14.32        | 14.42         | 0             | 13.69        | 14.17        | 14.33         | 0             |
|  | 36      | 39        | 13.76        | 13.92        | 14.31         | 0             | 13.68        | 13.73        | 14.22         | 0             |
|  | 75      | 0         | 13.88        | 14.44        | 14.37         | 0             | 13.59        | 14.08        | 14.11         | 0             |

# FCC SAR Test Report

A D T

| Band / BW  | RB Size | RB Offset | QPSK         |              |               | 3GPP MPR (dB) | 16QAM        |              |               | 3GPP MPR (dB) |
|--|---------|-----------|--------------|--------------|---------------|---------------|--------------|--------------|---------------|---------------|
|  |         |           | Low CH 20850 | Mid CH 21100 | High CH 21350 |               | Low CH 20850 | Mid CH 21100 | High CH 21350 |               |
|  |         |           | 2510.0 MHz   | 2535.0 MHz   | 2560.0 MHz    |               | 2510.0 MHz   | 2535.0 MHz   | 2560.0 MHz    |               |
| EUT without Power Reduction (P-Sensor NOT Triggered) |         |           |              |              |               |               |              |              |               |               |
| 7 / 20M  | 1       | 0         | 22.63        | 22.80        | 22.61         | 0             | 21.35        | 21.88        | 21.71         | 1             |
|  | 1       | 50        | 22.35        | 22.53        | 22.60         | 0             | 21.45        | 21.83        | 21.73         | 1             |
|  | 1       | 99        | 22.34        | 22.36        | 22.60         | 0             | 21.45        | 21.87        | 21.70         | 1             |
|  | 50      | 0         | 21.32        | 21.59        | 21.67         | 1             | 20.50        | 20.54        | 20.66         | 2             |
|  | 50      | 25        | 21.62        | 21.78        | 21.76         | 1             | 20.38        | 20.77        | 20.68         | 2             |
|  | 50      | 50        | 21.38        | 21.63        | 21.69         | 1             | 20.35        | 20.72        | 20.72         | 2             |
|  | 100     | 0         | 21.27        | 21.76        | 21.60         | 1             | 20.21        | 20.75        | 20.71         | 2             |
| EUT with Power Reduction (P-Sensor Triggered)        |         |           |              |              |               |               |              |              |               |               |
| 7 / 20M  | 1       | 0         | 14.41        | 14.53        | 14.50         | 0             | 14.38        | 14.44        | 13.97         | 0             |
|  | 1       | 50        | 14.05        | 14.38        | 14.43         | 0             | 14.42        | 14.32        | 14.45         | 0             |
|  | 1       | 99        | 13.92        | 13.95        | 14.23         | 0             | 14.33        | 14.24        | 14.38         | 0             |
|  | 50      | 0         | 14.43        | 14.49        | 14.48         | 0             | 13.66        | 14.21        | 14.03         | 0             |
|  | 50      | 25        | 14.05        | 14.35        | 14.45         | 0             | 13.72        | 14.20        | 14.36         | 0             |
|  | 50      | 50        | 13.79        | 13.95        | 14.34         | 0             | 13.71        | 13.76        | 14.25         | 0             |
|  | 100     | 0         | 13.91        | 14.47        | 14.40         | 0             | 13.62        | 14.11        | 14.14         | 0             |

| LTE<br>Band / BW                                     | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|--|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|  |            |              | Low CH<br>23755 | Mid CH<br>23790 | High CH<br>23825 |                     | Low CH<br>23755 | Mid CH<br>23790 | High CH<br>23825 |                     |
|  |            |              | 706.5<br>MHz    | 710.0<br>MHz    | 713.5<br>MHz     |                     | 706.5<br>MHz    | 710.0<br>MHz    | 713.5<br>MHz     |                     |
| EUT without Power Reduction (P-Sensor NOT Triggered) |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 17 / 5M  | 1          | 0            | 22.79           | 22.81           | 22.82            | 0                   | 21.66           | 21.78           | 21.81            | 1                   |
|  | 1          | 12           | 22.75           | 22.74           | 22.64            | 0                   | 21.74           | 21.56           | 21.60            | 1                   |
|  | 1          | 24           | 22.55           | 22.66           | 22.74            | 0                   | 21.62           | 21.67           | 21.80            | 1                   |
|  | 12         | 0            | 21.76           | 21.69           | 21.74            | 1                   | 20.84           | 20.89           | 20.87            | 2                   |
|  | 12         | 6            | 21.79           | 21.71           | 21.72            | 1                   | 20.60           | 20.77           | 20.82            | 2                   |
|  | 12         | 13           | 21.80           | 21.75           | 21.96            | 1                   | 20.83           | 20.73           | 20.97            | 2                   |
|  | 25         | 0            | 21.73           | 21.76           | 21.79            | 1                   | 20.75           | 20.77           | 20.88            | 2                   |
| EUT with Power Reduction (P-Sensor Triggered)        |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 17 / 5M  | 1          | 0            | 14.49           | 14.38           | 14.50            | 0                   | 14.27           | 14.24           | 13.96            | 0                   |
|  | 1          | 12           | 14.19           | 14.14           | 14.14            | 0                   | 14.20           | 14.15           | 13.90            | 0                   |
|  | 1          | 24           | 14.23           | 14.15           | 14.16            | 0                   | 14.33           | 14.37           | 14.38            | 0                   |
|  | 12         | 0            | 13.77           | 13.92           | 14.25            | 0                   | 13.80           | 13.75           | 13.82            | 0                   |
|  | 12         | 6            | 13.96           | 13.98           | 14.10            | 0                   | 13.79           | 13.80           | 13.78            | 0                   |
|  | 12         | 13           | 14.35           | 14.37           | 14.39            | 0                   | 13.90           | 14.09           | 14.10            | 0                   |
|  | 25         | 0            | 14.31           | 14.24           | 14.38            | 0                   | 13.88           | 13.89           | 13.85            | 0                   |

# FCC SAR Test Report

A D T

| LTE<br>Band / BW                                     | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|--|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|  |            |              | Low CH<br>23780 | Mid CH<br>23790 | High CH<br>23800 |                     | Low CH<br>23780 | Mid CH<br>23790 | High CH<br>23800 |                     |
|  |            |              | 709.0<br>MHz    | 710.0<br>MHz    | 711.0<br>MHz     |                     | 709.0<br>MHz    | 710.0<br>MHz    | 711.0<br>MHz     |                     |
| EUT without Power Reduction (P-Sensor NOT Triggered) |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 17 / 10M   | 1          | 0            | 22.83           | 22.85           | 22.86            | 0                   | 21.70           | 21.82           | 21.85            | 1                   |
|  | 1          | 24           | 22.79           | 22.78           | 22.68            | 0                   | 21.78           | 21.60           | 21.64            | 1                   |
|  | 1          | 49           | 22.59           | 22.70           | 22.78            | 0                   | 21.66           | 21.71           | 21.84            | 1                   |
|  | 25         | 0            | 21.80           | 21.73           | 21.78            | 1                   | 20.88           | 20.93           | 20.91            | 2                   |
|  | 25         | 12           | 21.83           | 21.75           | 21.76            | 1                   | 20.64           | 20.81           | 20.86            | 2                   |
|  | 25         | 25           | 21.84           | 21.79           | 22.00            | 1                   | 20.87           | 20.77           | 21.01            | 2                   |
|  | 50         | 0            | 21.77           | 21.80           | 21.83            | 1                   | 20.79           | 20.81           | 20.92            | 2                   |
| EUT with Power Reduction (P-Sensor Triggered)        |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 17 / 10M   | 1          | 0            | 14.55           | 14.44           | 14.56            | 0                   | 14.33           | 14.30           | 14.02            | 0                   |
|  | 1          | 24           | 14.25           | 14.20           | 14.20            | 0                   | 14.26           | 14.21           | 13.96            | 0                   |
|  | 1          | 49           | 14.29           | 14.21           | 14.22            | 0                   | 14.39           | 14.43           | 14.44            | 0                   |
|  | 25         | 0            | 13.83           | 13.98           | 14.31            | 0                   | 13.86           | 13.81           | 13.88            | 0                   |
|  | 25         | 12           | 14.02           | 14.04           | 14.16            | 0                   | 13.85           | 13.86           | 13.84            | 0                   |
|  | 25         | 25           | 14.41           | 14.43           | 14.45            | 0                   | 13.96           | 14.15           | 14.16            | 0                   |
|  | 50         | 0            | 14.37           | 14.30           | 14.44            | 0                   | 13.94           | 13.95           | 13.91            | 0                   |

## <WLAN 5.8G>

| Mode                          | 802.11a        |            |            |            |            |
|-------------------------------|----------------|------------|------------|------------|------------|
| Channel / Frequency (MHz)     | 149 (5745)     | 153 (5765) | 157 (5785) | 161 (5805) | 165 (5825) |
| Average Power (Ant-0)         | 11.72          | 11.65      | 11.53      | 11.56      | 11.62      |
| Average Power (Ant-1)         | 12.34          | 11.84      | 11.43      | 11.27      | 11.07      |
| Average Power (Ant-0 + Ant-1) | <b>15.05</b>   | 14.76      | 14.49      | 14.43      | 14.36      |
| Mode                          | 802.11n (HT20) |            |            |            |            |
| Channel / Frequency (MHz)     | 149 (5745)     | 153 (5765) | 157 (5785) | 161 (5805) | 165 (5825) |
| Average Power (Ant-0)         | 9.21           | 9.28       | 9.33       | 9.41       | 9.48       |
| Average Power (Ant-1)         | 10.18          | 9.76       | 9.32       | 9.21       | 9.03       |
| Average Power (Ant-0 + Ant-1) | <b>12.73</b>   | 12.54      | 12.34      | 12.32      | 12.27      |

## 4.7 SAR Testing Results

### 4.7.1 SAR Results for Body

| Plot No. | Band     | Mode     | Test Position | Separation Distance (cm) | Ch.  | Power Reduction | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|----------|----------|---------------|--------------------------|------|-----------------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
| 01       | WCDMA II | RMC12.2K | Front Face    | 0                        | 9262 | w/              | 16.0                     | 15.89                          | 1.03           | -0.09            | 1.17                   | 1.20                 |
|          | WCDMA II | RMC12.2K | Front Face    | 1.1                      | 9538 | w/o             | 24.0                     | 23.63                          | 1.09           | 0.16             | 0.624                  | 0.68                 |
|          | WCDMA II | RMC12.2K | Rear Face     | 0                        | 9262 | w/              | 16.0                     | 15.89                          | 1.03           | 0.06             | 1.36                   | 1.39                 |
|          | WCDMA II | RMC12.2K | Rear Face     | 1.2                      | 9538 | w/o             | 24.0                     | 23.63                          | 1.09           | 0.18             | 0.826                  | 0.90                 |
|          | WCDMA II | RMC12.2K | Right Side    | 0                        | 9538 | w/o             | 24.0                     | 23.63                          | 1.09           | 0.11             | 0.093                  | 0.10                 |
|          | WCDMA II | RMC12.2K | Bottom Side   | 0                        | 9262 | w/              | 16.0                     | 15.89                          | 1.03           | 0.04             | 0.775                  | 0.79                 |
|          | WCDMA II | RMC12.2K | Bottom Side   | 1.3                      | 9538 | w/o             | 24.0                     | 23.63                          | 1.09           | 0.08             | 0.614                  | 0.67                 |
|          | WCDMA II | RMC12.2K | Front Face    | 0                        | 9400 | w/              | 16.0                     | 15.59                          | 1.10           | -0.11            | 0.975                  | 1.07                 |
|          | WCDMA II | RMC12.2K | Front Face    | 0                        | 9538 | w/              | 16.0                     | 15.76                          | 1.06           | -0.09            | 0.912                  | 0.96                 |
|          | WCDMA II | RMC12.2K | Rear Face     | 0                        | 9400 | w/              | 16.0                     | 15.59                          | 1.10           | 0.07             | 1.19                   | 1.31                 |
|          | WCDMA II | RMC12.2K | Rear Face     | 0                        | 9538 | w/              | 16.0                     | 15.76                          | 1.06           | 0.12             | 1.06                   | 1.12                 |
|          | WCDMA II | RMC12.2K | Rear Face     | 1.2                      | 9262 | w/o             | 24.0                     | 23.38                          | 1.15           | 0.01             | 0.732                  | 0.84                 |
|          | WCDMA II | RMC12.2K | Rear Face     | 1.2                      | 9400 | w/o             | 24.0                     | 23.50                          | 1.12           | -0.03            | 0.77                   | 0.86                 |
|          | WCDMA II | RMC12.2K | Rear Face     | 0                        | 9262 | w/              | 16.0                     | 15.89                          | 1.03           | 0.18             | 1.35                   | 1.38                 |
|          | WCDMA V  | RMC12.2K | Front Face    | 0                        | 4182 | w/              | 15.5                     | 15.27                          | 1.05           | 0.07             | 0.205                  | 0.22                 |
|          | WCDMA V  | RMC12.2K | Front Face    | 1.1                      | 4233 | w/o             | 23.5                     | 23.21                          | 1.07           | 0.02             | 0.491                  | 0.52                 |
| 02       | WCDMA V  | RMC12.2K | Rear Face     | 0                        | 4182 | w/              | 15.5                     | 15.27                          | 1.05           | 0.01             | 0.175                  | 0.18                 |
|          | WCDMA V  | RMC12.2K | Rear Face     | 1.2                      | 4233 | w/o             | 23.5                     | 23.21                          | 1.07           | 0.17             | 0.302                  | 0.32                 |
|          | WCDMA V  | RMC12.2K | Right Side    | 0                        | 4233 | w/o             | 23.5                     | 23.21                          | 1.07           | -0.06            | 0.34                   | 0.36                 |
|          | WCDMA V  | RMC12.2K | Bottom Side   | 0                        | 4182 | w/              | 15.5                     | 15.27                          | 1.05           | 0.16             | 0.058                  | 0.06                 |
|          | WCDMA V  | RMC12.2K | Bottom Side   | 1.3                      | 4233 | w/o             | 23.5                     | 23.21                          | 1.07           | 0.09             | 0.115                  | 0.12                 |
|          | WCDMA V  | RMC12.2K | Bottom Side   | 1.3                      | 4233 | w/o             | 23.5                     | 23.21                          | 1.07           | 0.09             | 0.115                  | 0.12                 |

#### Note:

- SAR is performed on the highest power channel. When the reported SAR value of highest power channel is  $\leq 0.8$  W/kg, SAR testing for optional channel is not required.

# FCC SAR Test Report

A D T

| Plot No. | Band  | Mode    | Test Position | Separation Distance (cm) | Ch.   | Power Reduction | RB# | RB Offset | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|-------|---------|---------------|--------------------------|-------|-----------------|-----|-----------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
| 03       | LTE 2 | QPSK20M | Front Face    | 0                        | 18900 | w/              | 1   | 0         | 15.0                     | 14.78                          | 1.05           | -0.1             | 0.967                  | 1.02                 |
|          | LTE 2 | QPSK20M | Front Face    | 1.1                      | 19100 | w/o             | 1   | 0         | 23.0                     | 22.63                          | 1.09           | -0.1             | 0.957                  | 1.04                 |
|          | LTE 2 | QPSK20M | Rear Face     | 0                        | 18900 | w/              | 1   | 0         | 15.0                     | 14.78                          | 1.05           | -0.04            | 1.25                   | 1.31                 |
|          | LTE 2 | QPSK20M | Rear Face     | 1.2                      | 19100 | w/o             | 1   | 0         | 23.0                     | 22.63                          | 1.09           | 0.09             | 0.855                  | 0.93                 |
|          | LTE 2 | QPSK20M | Right Side    | 0                        | 19100 | w/o             | 1   | 0         | 23.0                     | 22.63                          | 1.09           | 0.14             | 0.095                  | 0.10                 |
|          | LTE 2 | QPSK20M | Bottom Side   | 0                        | 18900 | w/              | 1   | 0         | 15.0                     | 14.78                          | 1.05           | -0.02            | 0.698                  | 0.73                 |
|          | LTE 2 | QPSK20M | Bottom Side   | 1.3                      | 19100 | w/o             | 1   | 0         | 23.0                     | 22.63                          | 1.09           | -0.18            | 0.673                  | 0.73                 |
|          | LTE 2 | QPSK20M | Front Face    | 0                        | 18900 | w/              | 50  | 0         | 15.0                     | 14.76                          | 1.06           | 0.13             | 0.981                  | 1.04                 |
|          | LTE 2 | QPSK20M | Front Face    | 1.1                      | 19100 | w/o             | 50  | 0         | 22.0                     | 21.66                          | 1.08           | 0.06             | 0.751                  | 0.81                 |
|          | LTE 2 | QPSK20M | Rear Face     | 0                        | 18900 | w/              | 50  | 0         | 15.0                     | 14.76                          | 1.06           | -0.01            | 1.23                   | 1.30                 |
|          | LTE 2 | QPSK20M | Rear Face     | 1.2                      | 19100 | w/o             | 50  | 0         | 22.0                     | 21.66                          | 1.08           | -0.01            | 0.635                  | 0.69                 |
|          | LTE 2 | QPSK20M | Right Side    | 0                        | 19100 | w/o             | 50  | 0         | 22.0                     | 21.66                          | 1.08           | -0.05            | 0.071                  | 0.08                 |
|          | LTE 2 | QPSK20M | Bottom Side   | 0                        | 18900 | w/              | 50  | 0         | 15.0                     | 14.76                          | 1.06           | 0.03             | 0.694                  | 0.73                 |
|          | LTE 2 | QPSK20M | Bottom Side   | 1.3                      | 19100 | w/o             | 50  | 0         | 22.0                     | 21.66                          | 1.08           | -0.02            | 0.574                  | 0.62                 |
|          | LTE 2 | QPSK20M | Front Face    | 0                        | 18700 | w/              | 1   | 0         | 15.0                     | 14.74                          | 1.06           | 0.09             | 0.911                  | 0.97                 |
|          | LTE 2 | QPSK20M | Front Face    | 0                        | 19100 | w/              | 1   | 0         | 15.0                     | 14.71                          | 1.07           | 0.02             | 0.963                  | 1.03                 |
|          | LTE 2 | QPSK20M | Front Face    | 1.1                      | 18700 | w/o             | 1   | 0         | 23.0                     | 22.38                          | 1.15           | -0.15            | 0.801                  | 0.92                 |
|          | LTE 2 | QPSK20M | Front Face    | 1.1                      | 18900 | w/o             | 1   | 0         | 23.0                     | 22.39                          | 1.15           | -0.01            | 0.92                   | 1.06                 |
|          | LTE 2 | QPSK20M | Rear Face     | 0                        | 18700 | w/              | 1   | 0         | 15.0                     | 14.74                          | 1.06           | -0.07            | 1.22                   | 1.30                 |
|          | LTE 2 | QPSK20M | Rear Face     | 0                        | 19100 | w/              | 1   | 0         | 15.0                     | 14.71                          | 1.07           | -0.11            | 1.15                   | 1.23                 |
|          | LTE 2 | QPSK20M | Rear Face     | 1.2                      | 18700 | w/o             | 1   | 0         | 23.0                     | 22.38                          | 1.15           | 0.05             | 0.716                  | 0.83                 |
|          | LTE 2 | QPSK20M | Rear Face     | 1.2                      | 18900 | w/o             | 1   | 0         | 23.0                     | 22.39                          | 1.15           | 0.14             | 0.787                  | 0.91                 |
|          | LTE 2 | QPSK20M | Front Face    | 0                        | 18700 | w/              | 50  | 0         | 15.0                     | 14.75                          | 1.06           | -0.11            | 0.965                  | 1.02                 |
|          | LTE 2 | QPSK20M | Front Face    | 0                        | 19100 | w/              | 50  | 0         | 15.0                     | 14.74                          | 1.06           | -0.19            | 1.09                   | 1.16                 |
|          | LTE 2 | QPSK20M | Front Face    | 1.1                      | 18700 | w/o             | 50  | 0         | 22.0                     | 21.10                          | 1.23           | -0.04            | 0.643                  | 0.79                 |
|          | LTE 2 | QPSK20M | Front Face    | 1.1                      | 18900 | w/o             | 50  | 0         | 22.0                     | 21.15                          | 1.22           | -0.16            | 0.718                  | 0.87                 |
|          | LTE 2 | QPSK20M | Rear Face     | 0                        | 18700 | w/              | 50  | 0         | 15.0                     | 14.75                          | 1.06           | 0.17             | 1.24                   | 1.31                 |
|          | LTE 2 | QPSK20M | Rear Face     | 0                        | 19100 | w/              | 50  | 0         | 15.0                     | 14.74                          | 1.06           | 0.05             | 1.12                   | 1.19                 |
|          | LTE 2 | QPSK20M | Front Face    | 0                        | 18900 | w/              | 100 | 0         | 15.0                     | 14.64                          | 1.09           | 0.11             | 0.954                  | 1.04                 |
|          | LTE 2 | QPSK20M | Front Face    | 1.1                      | 19100 | w/o             | 100 | 0         | 22.0                     | 21.57                          | 1.10           | 0.16             | 0.764                  | 0.84                 |
|          | LTE 2 | QPSK20M | Rear Face     | 0                        | 18900 | w/              | 100 | 0         | 15.0                     | 14.64                          | 1.09           | -0.11            | 1.19                   | 1.29                 |
|          | LTE 2 | QPSK20M | Rear Face     | 1.2                      | 19100 | w/o             | 100 | 0         | 22.0                     | 21.57                          | 1.10           | 0.13             | 0.677                  | 0.75                 |
|          | LTE 2 | QPSK20M | Rear Face     | 0                        | 18900 | w/              | 1   | 0         | 15.0                     | 14.78                          | 1.05           | -0.16            | 1.24                   | 1.30                 |

## Note:

1. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
2. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
3. According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
4. According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
5. According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.



# FCC SAR Test Report

A D T

| Plot No. | Band  | Mode    | Test Position | Separation Distance (cm) | Ch.   | Power Reduction | RB# | RB Offset | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|-------|---------|---------------|--------------------------|-------|-----------------|-----|-----------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | LTE 4 | QPSK20M | Front Face    | 0                        | 20300 | w/              | 1   | 0         | 15.0                     | 14.55                          | 1.11           | 0.11             | 0.879                  | 0.97                 |
|          | LTE 4 | QPSK20M | Front Face    | 1.1                      | 20050 | w/o             | 1   | 0         | 23.0                     | 22.46                          | 1.13           | 0.18             | 0.816                  | 0.92                 |
|          | LTE 4 | QPSK20M | Rear Face     | 0                        | 20300 | w/              | 1   | 0         | 15.0                     | 14.55                          | 1.11           | 0.03             | 1                      | 1.11                 |
|          | LTE 4 | QPSK20M | Rear Face     | 1.2                      | 20050 | w/o             | 1   | 0         | 23.0                     | 22.46                          | 1.13           | 0.18             | 0.789                  | 0.89                 |
|          | LTE 4 | QPSK20M | Right Side    | 0                        | 20050 | w/o             | 1   | 0         | 23.0                     | 22.46                          | 1.13           | 0.08             | 0.093                  | 0.11                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 0                        | 20300 | w/              | 1   | 0         | 15.0                     | 14.55                          | 1.11           | 0.03             | 0.892                  | 0.99                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 1.3                      | 20050 | w/o             | 1   | 0         | 23.0                     | 22.46                          | 1.13           | 0.03             | 0.613                  | 0.69                 |
|          | LTE 4 | QPSK20M | Front Face    | 0                        | 20300 | w/              | 50  | 0         | 15.0                     | 14.46                          | 1.13           | -0.06            | 0.884                  | 1.00                 |
|          | LTE 4 | QPSK20M | Front Face    | 1.1                      | 20050 | w/o             | 50  | 0         | 22.0                     | 21.48                          | 1.13           | -0.07            | 0.655                  | 0.74                 |
| 04       | LTE 4 | QPSK20M | Rear Face     | 0                        | 20300 | w/              | 50  | 0         | 15.0                     | 14.46                          | 1.13           | -0.11            | 1.13                   | 1.28                 |
|          | LTE 4 | QPSK20M | Rear Face     | 1.2                      | 20050 | w/o             | 50  | 0         | 22.0                     | 21.48                          | 1.13           | -0.19            | 0.635                  | 0.72                 |
|          | LTE 4 | QPSK20M | Right Side    | 0                        | 20050 | w/o             | 50  | 0         | 22.0                     | 21.48                          | 1.13           | 0.08             | 0.074                  | 0.08                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 0                        | 20300 | w/              | 50  | 0         | 15.0                     | 14.46                          | 1.13           | 0.14             | 0.866                  | 0.98                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 1.3                      | 20050 | w/o             | 50  | 0         | 22.0                     | 21.48                          | 1.13           | -0.04            | 0.489                  | 0.55                 |
|          | LTE 4 | QPSK20M | Front Face    | 0                        | 20050 | w/              | 1   | 0         | 15.0                     | 14.48                          | 1.13           | -0.04            | 0.907                  | 1.02                 |
|          | LTE 4 | QPSK20M | Front Face    | 0                        | 20175 | w/              | 1   | 0         | 15.0                     | 14.51                          | 1.12           | -0.02            | 0.873                  | 0.98                 |
|          | LTE 4 | QPSK20M | Front Face    | 1.1                      | 20175 | w/o             | 1   | 0         | 23.0                     | 22.33                          | 1.17           | 0                | 0.787                  | 0.92                 |
|          | LTE 4 | QPSK20M | Front Face    | 1.1                      | 20300 | w/o             | 1   | 0         | 23.0                     | 22.35                          | 1.16           | -0.05            | 0.796                  | 0.92                 |
|          | LTE 4 | QPSK20M | Rear Face     | 0                        | 20050 | w/              | 1   | 0         | 15.0                     | 14.48                          | 1.13           | 0.05             | 1.07                   | 1.21                 |
|          | LTE 4 | QPSK20M | Rear Face     | 0                        | 20175 | w/              | 1   | 0         | 15.0                     | 14.51                          | 1.12           | -0.16            | 1.06                   | 1.19                 |
|          | LTE 4 | QPSK20M | Rear Face     | 1.2                      | 20175 | w/o             | 1   | 0         | 23.0                     | 22.33                          | 1.17           | 0.03             | 0.77                   | 0.90                 |
|          | LTE 4 | QPSK20M | Rear Face     | 1.2                      | 20300 | w/o             | 1   | 0         | 23.0                     | 22.35                          | 1.16           | 0.12             | 0.774                  | 0.90                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 0                        | 20050 | w/              | 1   | 0         | 15.0                     | 14.48                          | 1.13           | 0.05             | 0.875                  | 0.99                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 0                        | 20175 | w/              | 1   | 0         | 15.0                     | 14.51                          | 1.12           | 0.08             | 0.853                  | 0.95                 |
|          | LTE 4 | QPSK20M | Front Face    | 0                        | 20050 | w/              | 50  | 0         | 15.0                     | 14.44                          | 1.14           | 0.1              | 0.894                  | 1.02                 |
|          | LTE 4 | QPSK20M | Front Face    | 0                        | 20175 | w/              | 50  | 0         | 15.0                     | 14.43                          | 1.14           | -0.08            | 0.83                   | 0.95                 |
|          | LTE 4 | QPSK20M | Rear Face     | 0                        | 20050 | w/              | 50  | 0         | 15.0                     | 14.44                          | 1.14           | 0.05             | 1.09                   | 1.24                 |
|          | LTE 4 | QPSK20M | Rear Face     | 0                        | 20175 | w/              | 50  | 0         | 15.0                     | 14.43                          | 1.14           | -0.14            | 1.11                   | 1.27                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 0                        | 20050 | w/              | 50  | 0         | 15.0                     | 14.44                          | 1.14           | 0.11             | 0.875                  | 1.00                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 0                        | 20175 | w/              | 50  | 0         | 15.0                     | 14.43                          | 1.14           | 0.08             | 0.827                  | 0.94                 |
|          | LTE 4 | QPSK20M | Front Face    | 0                        | 20300 | w/              | 100 | 0         | 15.0                     | 14.42                          | 1.14           | -0.16            | 0.871                  | 1.00                 |
|          | LTE 4 | QPSK20M | Front Face    | 1.1                      | 20050 | w/o             | 100 | 0         | 22.0                     | 21.49                          | 1.12           | -0.05            | 0.701                  | 0.79                 |
|          | LTE 4 | QPSK20M | Rear Face     | 0                        | 20300 | w/              | 100 | 0         | 15.0                     | 14.42                          | 1.14           | -0.16            | 1.1                    | 1.26                 |
|          | LTE 4 | QPSK20M | Rear Face     | 1.2                      | 20050 | w/o             | 100 | 0         | 22.0                     | 21.49                          | 1.12           | 0.12             | 0.622                  | 0.70                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 0                        | 20300 | w/              | 100 | 0         | 15.0                     | 14.42                          | 1.14           | 0.12             | 0.884                  | 1.01                 |
|          | LTE 4 | QPSK20M | Rear Face     | 0                        | 20300 | w/              | 50  | 0         | 15.0                     | 14.46                          | 1.13           | 0.18             | 1.1                    | 1.25                 |

## Note:

1. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
2. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
3. According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
4. According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
5. According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.

# FCC SAR Test Report

A D T

| Plot No. | Band  | Mode    | Test Position | Separation Distance (cm) | Ch.   | Power Reduction | RB# | RB Offset | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|-------|---------|---------------|--------------------------|-------|-----------------|-----|-----------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
| 05       | LTE 5 | QPSK10M | Front Face    | 0                        | 20600 | w/              | 1   | 0         | 15.0                     | 14.65                          | 1.08           | 0.07             | 0.211                  | 0.23                 |
|          | LTE 5 | QPSK10M | Front Face    | 1.1                      | 20600 | w/o             | 1   | 0         | 22.5                     | 22.28                          | 1.05           | 0                | 0.418                  | 0.44                 |
|          | LTE 5 | QPSK10M | Rear Face     | 0                        | 20600 | w/              | 1   | 0         | 15.0                     | 14.65                          | 1.08           | 0.15             | 0.182                  | 0.20                 |
|          | LTE 5 | QPSK10M | Rear Face     | 1.2                      | 20600 | w/o             | 1   | 0         | 22.5                     | 22.28                          | 1.05           | 0.04             | 0.335                  | 0.35                 |
|          | LTE 5 | QPSK10M | Right Side    | 0                        | 20600 | w/o             | 1   | 0         | 22.5                     | 22.28                          | 1.05           | 0.07             | 0.374                  | 0.39                 |
|          | LTE 5 | QPSK10M | Bottom Side   | 0                        | 20600 | w/              | 1   | 0         | 15.0                     | 14.65                          | 1.08           | 0.09             | 0.063                  | 0.07                 |
|          | LTE 5 | QPSK10M | Bottom Side   | 1.3                      | 20600 | w/o             | 1   | 0         | 22.5                     | 22.28                          | 1.05           | -0.01            | 0.093                  | 0.10                 |
|          | LTE 5 | QPSK10M | Front Face    | 0                        | 20600 | w/              | 25  | 25        | 15.0                     | 14.56                          | 1.11           | 0.11             | 0.225                  | 0.25                 |
|          | LTE 5 | QPSK10M | Front Face    | 1.1                      | 20600 | w/o             | 25  | 25        | 21.5                     | 21.30                          | 1.05           | 0.02             | 0.332                  | 0.35                 |
|          | LTE 5 | QPSK10M | Rear Face     | 0                        | 20600 | w/              | 25  | 25        | 15.0                     | 14.56                          | 1.11           | 0.03             | 0.195                  | 0.22                 |
|          | LTE 5 | QPSK10M | Rear Face     | 1.2                      | 20600 | w/o             | 25  | 25        | 21.5                     | 21.30                          | 1.05           | 0.13             | 0.311                  | 0.33                 |
|          | LTE 5 | QPSK10M | Right Side    | 0                        | 20600 | w/o             | 25  | 25        | 21.5                     | 21.30                          | 1.05           | 0.03             | 0.279                  | 0.29                 |
|          | LTE 5 | QPSK10M | Bottom Side   | 0                        | 20600 | w/              | 25  | 25        | 15.0                     | 14.56                          | 1.11           | 0.16             | 0.061                  | 0.07                 |
|          | LTE 5 | QPSK10M | Bottom Side   | 1.3                      | 20600 | w/o             | 25  | 25        | 21.5                     | 21.30                          | 1.05           | 0                | 0.075                  | 0.08                 |
|          | LTE 7 | QPSK20M | Front Face    | 0                        | 21100 | w/              | 1   | 0         | 15.0                     | 14.53                          | 1.11           | 0.07             | 0.277                  | 0.31                 |
|          | LTE 7 | QPSK20M | Front Face    | 1.1                      | 21100 | w/o             | 1   | 0         | 23.0                     | 22.80                          | 1.05           | 0.01             | 0.454                  | 0.48                 |
| 06       | LTE 7 | QPSK20M | Rear Face     | 0                        | 21100 | w/              | 1   | 0         | 15.0                     | 14.53                          | 1.11           | 0.09             | 0.669                  | 0.75                 |
|          | LTE 7 | QPSK20M | Rear Face     | 1.2                      | 21100 | w/o             | 1   | 0         | 23.0                     | 22.80                          | 1.05           | 0.08             | 0.475                  | 0.50                 |
|          | LTE 7 | QPSK20M | Right Side    | 0                        | 21100 | w/o             | 1   | 0         | 23.0                     | 22.80                          | 1.05           | -0.1             | 0.011                  | 0.01                 |
|          | LTE 7 | QPSK20M | Bottom Side   | 0                        | 21100 | w/              | 1   | 0         | 15.0                     | 14.53                          | 1.11           | 0.17             | 0.176                  | 0.20                 |
|          | LTE 7 | QPSK20M | Bottom Side   | 1.3                      | 21100 | w/o             | 1   | 0         | 23.0                     | 22.80                          | 1.05           | 0.17             | 0.294                  | 0.31                 |
|          | LTE 7 | QPSK20M | Front Face    | 0                        | 21100 | w/              | 50  | 0         | 15.0                     | 14.49                          | 1.12           | 0.05             | 0.273                  | 0.31                 |
|          | LTE 7 | QPSK20M | Front Face    | 1.1                      | 21100 | w/o             | 50  | 25        | 22.0                     | 21.78                          | 1.05           | -0.05            | 0.371                  | 0.39                 |
|          | LTE 7 | QPSK20M | Rear Face     | 0                        | 21100 | w/              | 50  | 0         | 15.0                     | 14.49                          | 1.12           | 0.08             | 0.682                  | 0.77                 |
|          | LTE 7 | QPSK20M | Rear Face     | 1.2                      | 21100 | w/o             | 50  | 25        | 22.0                     | 21.78                          | 1.05           | 0.13             | 0.388                  | 0.41                 |
|          | LTE 7 | QPSK20M | Right Side    | 0                        | 21100 | w/o             | 50  | 25        | 22.0                     | 21.78                          | 1.05           | 0.18             | 0.01                   | 0.01                 |
|          | LTE 7 | QPSK20M | Bottom Side   | 0                        | 21100 | w/              | 50  | 0         | 15.0                     | 14.49                          | 1.12           | 0.07             | 0.173                  | 0.19                 |
|          | LTE 7 | QPSK20M | Bottom Side   | 1.3                      | 21100 | w/o             | 50  | 25        | 22.0                     | 21.78                          | 1.05           | -0.15            | 0.233                  | 0.25                 |

## Note:

1. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
2. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
3. According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
4. According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
5. According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.



# FCC SAR Test Report

A D T

| Plot No. | Band   | Mode    | Test Position | Separation Distance (cm) | Ch.   | Power Reduction | RB# | RB Offset | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|--------|---------|---------------|--------------------------|-------|-----------------|-----|-----------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | LTE 17 | QPSK10M | Front Face    | 0                        | 23800 | w/              | 1   | 0         | 15.0                     | 14.56                          | 1.11           | 0.18             | 0.182                  | 0.20                 |
|          | LTE 17 | QPSK10M | Front Face    | 1.1                      | 23800 | w/o             | 1   | 0         | 23.5                     | 22.86                          | 1.16           | -0.04            | 0.254                  | 0.29                 |
|          | LTE 17 | QPSK10M | Rear Face     | 0                        | 23800 | w/              | 1   | 0         | 15.0                     | 14.56                          | 1.11           | -0.11            | 0.258                  | 0.29                 |
| 07       | LTE 17 | QPSK10M | Rear Face     | 1.2                      | 23800 | w/o             | 1   | 0         | 23.5                     | 22.86                          | 1.16           | 0.1              | 0.317                  | 0.37                 |
|          | LTE 17 | QPSK10M | Right Side    | 0                        | 23800 | w/o             | 1   | 0         | 23.5                     | 22.86                          | 1.16           | 0                | 0.111                  | 0.13                 |
|          | LTE 17 | QPSK10M | Bottom Side   | 0                        | 23800 | w/              | 1   | 0         | 15.0                     | 14.56                          | 1.11           | -0.09            | 0.048                  | 0.05                 |
|          | LTE 17 | QPSK10M | Bottom Side   | 1.3                      | 23800 | w/o             | 1   | 0         | 23.5                     | 22.86                          | 1.16           | -0.03            | 0.039                  | 0.05                 |
|          | LTE 17 | QPSK10M | Front Face    | 0                        | 23800 | w/              | 25  | 25        | 15.0                     | 14.45                          | 1.14           | -0.01            | 0.183                  | 0.21                 |
|          | LTE 17 | QPSK10M | Front Face    | 1.1                      | 23800 | w/o             | 25  | 25        | 22.5                     | 22.00                          | 1.12           | 0.04             | 0.213                  | 0.24                 |
|          | LTE 17 | QPSK10M | Rear Face     | 0                        | 23800 | w/              | 25  | 25        | 15.0                     | 14.45                          | 1.14           | 0.16             | 0.305                  | 0.35                 |
|          | LTE 17 | QPSK10M | Rear Face     | 1.2                      | 23800 | w/o             | 25  | 25        | 22.5                     | 22.00                          | 1.12           | -0.04            | 0.262                  | 0.29                 |
|          | LTE 17 | QPSK10M | Right Side    | 0                        | 23800 | w/o             | 25  | 25        | 22.5                     | 22.00                          | 1.12           | 0.05             | 0.095                  | 0.11                 |
|          | LTE 17 | QPSK10M | Bottom Side   | 0                        | 23800 | w/              | 25  | 25        | 15.0                     | 14.45                          | 1.14           | 0.08             | 0.047                  | 0.05                 |
|          | LTE 17 | QPSK10M | Bottom Side   | 1.3                      | 23800 | w/o             | 25  | 25        | 22.5                     | 22.00                          | 1.12           | 0.03             | 0.033                  | 0.04                 |

## Note:

1. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
2. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
3. According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
4. According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
5. According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.

| Plot No. | Band    | Test Position | Separation Distance (cm) | Ch. | Tx Antenna | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|---------|---------------|--------------------------|-----|------------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | 802.11a | Front Face    | 0                        | 149 | 0          | 12.0                     | 11.72                          | 1.07           | 0.08             | 0.114                  | 0.12                 |
|          | 802.11a | Rear Face     | 0                        | 149 | 0          | 12.0                     | 11.72                          | 1.07           | -0.04            | 0.141                  | 0.15                 |
| 08       | 802.11a | Left Side     | 0                        | 149 | 0          | 12.0                     | 11.72                          | 1.07           | 0.12             | 0.166                  | 0.18                 |
|          | 802.11a | Front Face    | 0                        | 149 | 1          | 12.5                     | 12.34                          | 1.04           | 0.08             | 0.049                  | 0.05                 |
|          | 802.11a | Rear Face     | 0                        | 149 | 1          | 12.5                     | 12.34                          | 1.04           | -0.06            | 0.157                  | 0.16                 |
|          | 802.11a | Right Side    | 0                        | 149 | 1          | 12.5                     | 12.34                          | 1.04           | 0.06             | 0.134                  | 0.14                 |
|          | 802.11a | Top Side      | 0                        | 149 | 1          | 12.5                     | 12.34                          | 1.04           | 0.16             | 0.00881                | 0.01                 |
|          | 802.11a | Front Face    | 0                        | 149 | 0+1        | 15.5                     | 15.05                          | 1.11           | 0.02             | 0.106                  | 0.12                 |
|          | 802.11a | Rear Face     | 0                        | 149 | 0+1        | 15.5                     | 15.05                          | 1.11           | 0.12             | 0.122                  | 0.14                 |
|          | 802.11a | Left Side     | 0                        | 149 | 0+1        | 15.5                     | 15.05                          | 1.11           | -0.06            | 0.135                  | 0.15                 |
|          | 802.11a | Right Side    | 0                        | 149 | 0+1        | 15.5                     | 15.05                          | 1.11           | 0.06             | 0.105                  | 0.12                 |
|          | 802.11a | Top Side      | 0                        | 149 | 0+1        | 15.5                     | 15.05                          | 1.11           | -0.04            | 0.00772                | 0.01                 |

## Note:

1. According to KDB 248227, when the extrapolated maximum peak SAR for the maximum output power channel is  $\leq 1.6$  W/kg and the 1g averaged SAR is  $\leq 0.8$  W/kg, WLAN SAR testing for other channels is not required.
2. SAR testing for 802.11n is not required when its maximum power is less than 1/4 dB higher than 802.11a.



## FCC SAR Test Report

### 4.7.2 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is  $< 0.80$  W/kg, repeated measurement is not required.
2. When the highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$ , or when the original or repeated measurement is  $\geq 1.45$  W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ , and the original, first or second repeated measurement is  $\geq 1.5$  W/kg, perform a third repeated measurement.

| Band     | Mode     | Test Position | Separation Distance (cm) | Ch.   | Original Measured SAR-1g (W/kg) | 1st Repeated SAR-1g (W/kg) | L/S Ratio | 2nd Repeated SAR-1g (W/kg) | L/S Ratio | 3rd Repeated SAR-1g (W/kg) | L/S Ratio |
|----------|----------|---------------|--------------------------|-------|---------------------------------|----------------------------|-----------|----------------------------|-----------|----------------------------|-----------|
| WCDMA II | RMC12.2K | Rear Face     | 0                        | 9262  | 1.36                            | 1.35                       | 1.01      | N/A                        | N/A       | N/A                        | N/A       |
| LTE 2    | QPSK20M  | Rear Face     | 0                        | 18900 | 1.25                            | 1.24                       | 1.01      | N/A                        | N/A       | N/A                        | N/A       |
| LTE 4    | QPSK20M  | Rear Face     | 0                        | 20300 | 1.13                            | 1.1                        | 1.03      | N/A                        | N/A       | N/A                        | N/A       |

## 4.7.3 Simultaneous Multi-band Transmission Evaluation

### <Estimated SAR Calculation>

According to KDB 447498 D01, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR was estimated according to following formula to result in substantially conservative SAR values of  $\leq 0.4$  W/kg to determine simultaneous transmission SAR test exclusion.

$$\text{Estimated SAR} = \frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \frac{\sqrt{f_{(\text{GHz})}}}{7.5}$$

If the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is used for estimated SAR calculation. When the test separation distance is  $> 50$  mm, the 0.4 W/kg is used for SAR-1g.

| Mode / Band | Frequency (GHz) | Max. Tune-up Power (dBm) | Test Position | Separation Distance (mm) | Estimated SAR (W/kg) |
|-------------|-----------------|--------------------------|---------------|--------------------------|----------------------|
| WCDMA II    | 1.907           | 24.0                     | Body          | 5                        | 0.4                  |
| WCDMA V     | 0.846           | 23.5                     | Body          | 5                        | 0.4                  |
| LTE 2       | 1.908           | 23.0                     | Body          | 5                        | 0.4                  |
| LTE 4       | 1.753           | 23.0                     | Body          | 5                        | 0.4                  |
| LTE 5       | 0.847           | 22.5                     | Body          | 5                        | 0.4                  |
| LTE 7       | 2.568           | 23.0                     | Body          | 5                        | 0.4                  |
| LTE 17      | 0.714           | 23.5                     | Body          | 5                        | 0.4                  |
| WLAN (NII)  | 5.825           | 16.0                     | Body          | 5                        | 0.4                  |

### Note:

1. The separation distance is determined from the outer housing of the EUT to the user.
2. When standalone SAR testing is not required, an estimated SAR can be applied to determine simultaneous transmission SAR test exclusion.

# FCC SAR Test Report

A D T

## <SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR<sub>1g</sub> of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR<sub>1g</sub> 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR<sub>1g</sub> is greater than the SAR limit (SAR<sub>1g</sub> 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

| No. | Conditions<br>(SAR1 + SAR2) | Exposure<br>Condition | Test<br>Position | Max.<br>SAR1 | Max.<br>SAR2 | SAR<br>Summation | SPLSR<br>Analysis            |
|-----|-----------------------------|-----------------------|------------------|--------------|--------------|------------------|------------------------------|
| 1   | WCDMA II<br>+<br>WLAN (NII) | Body                  | Front Face       | 1.20         | 0.12         | 1.32             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 1.39         | 0.16         | 1.55             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Side        | 0.40         | 0.18         | 0.58             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Side       | 0.10         | 0.14         | 0.24             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Top Side         | 0.40         | 0.01         | 0.41             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Bottom Side      | 0.79         | 0.40         | 1.19             | Σ SAR < 1.6,<br>Not required |
| 2   | WCDMA V<br>+<br>WLAN (NII)  | Body                  | Front Face       | 0.52         | 0.12         | 0.64             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 0.32         | 0.16         | 0.48             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Side        | 0.40         | 0.18         | 0.58             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Side       | 0.36         | 0.14         | 0.50             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Top Side         | 0.40         | 0.01         | 0.41             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Bottom Side      | 0.12         | 0.40         | 0.52             | Σ SAR < 1.6,<br>Not required |
| 3   | LTE 2<br>+<br>WLAN (NII)    | Body                  | Front Face       | 1.16         | 0.12         | 1.28             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 1.31         | 0.16         | 1.47             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Side        | 0.40         | 0.18         | 0.58             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Side       | 0.10         | 0.14         | 0.24             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Top Side         | 0.40         | 0.01         | 0.41             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Bottom Side      | 0.73         | 0.40         | 1.13             | Σ SAR < 1.6,<br>Not required |
| 4   | LTE 4<br>+<br>WLAN (NII)    | Body                  | Front Face       | 1.02         | 0.12         | 1.14             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 1.28         | 0.16         | 1.44             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Side        | 0.40         | 0.18         | 0.58             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Side       | 0.11         | 0.14         | 0.25             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Top Side         | 0.40         | 0.01         | 0.41             | Σ SAR < 1.6,<br>Not required |
|     |                             |                       | Bottom Side      | 1.01         | 0.40         | 1.41             | Σ SAR < 1.6,<br>Not required |

# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2) | Exposure<br>Condition | Test<br>Position | Max.<br>SAR1 | Max.<br>SAR2 | SAR<br>Summation | SPLSR<br>Analysis                            |
|-----|-----------------------------|-----------------------|------------------|--------------|--------------|------------------|--|
| 5   | LTE 5<br>+<br>WLAN (NII)    | Body                  | Front Face       | 0.44         | 0.12         | 0.56             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Rear Face        | 0.35         | 0.16         | 0.51             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Left Side        | 0.40         | 0.18         | 0.58             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Right Side       | 0.39         | 0.14         | 0.53             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Top Side         | 0.40         | 0.01         | 0.41             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Bottom Side      | 0.10         | 0.40         | 0.50             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
| 6   | LTE 7<br>+<br>WLAN (NII)    | Body                  | Front Face       | 0.48         | 0.12         | 0.60             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Rear Face        | 0.77         | 0.16         | 0.93             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Left Side        | 0.40         | 0.18         | 0.58             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Right Side       | 0.01         | 0.14         | 0.15             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Top Side         | 0.40         | 0.01         | 0.41             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Bottom Side      | 0.31         | 0.40         | 0.71             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
| 7   | LTE 17<br>+<br>WLAN (NII)   | Body                  | Front Face       | 0.29         | 0.12         | 0.41             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Rear Face        | 0.37         | 0.16         | 0.53             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Left Side        | 0.40         | 0.18         | 0.58             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Right Side       | 0.13         | 0.14         | 0.27             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Top Side         | 0.40         | 0.01         | 0.41             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                             |                       | Bottom Side      | 0.05         | 0.40         | 0.45             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |

Test Engineer : Yihu Xiong

## 5. Calibration of Test Equipment

| Equipment                       | Manufacturer | Model   | SN         | Cal. Date     | Cal. Interval |
|---------------------------------|--------------|---------|------------|---------------|---------------|
| System Validation Dipole        | SPEAG        | D750V3  | 1067       | Nov. 04, 2014 | 2 Years       |
| System Validation Dipole        | SPEAG        | D835V2  | 4d139      | Nov. 04, 2014 | 2 Years       |
| System Validation Dipole        | SPEAG        | D1750V2 | 1071       | Nov. 06, 2014 | 2 Years       |
| System Validation Dipole        | SPEAG        | D1900V2 | 5d159      | Nov. 05, 2014 | 2 Years       |
| System Validation Dipole        | SPEAG        | D2600V2 | 1020       | Aug. 21, 2014 | 2 Years       |
| System Validation Dipole        | SPEAG        | D5GHzV2 | 1133       | Nov. 06, 2014 | 2 Years       |
| Dosimetric E-Field Probe        | SPEAG        | EX3DV4  | 3873       | Aug. 26, 2014 | 1 Year        |
| Data Acquisition Electronics    | SPEAG        | DAE4    | 1341       | Aug. 26, 2014 | 1 Year        |
| Radio Communication Analyzer    | ANRITSU      | MT8820C | 6201300717 | Oct. 09, 2014 | 1 Year        |
| Wireless Communication Test Set | Agilent      | E5515C  | MY50260600 | Mar. 12, 2013 | 2 Years       |
| ENA Series Network Analyzer     | Agilent      | E5071C  | MY46214638 | Sep. 20, 2014 | 1 Year        |
| EXA Spectrum Analyzer           | Agilent      | E7405A  | MY45118807 | May 13, 2014  | 1 Year        |
| MXG Analog Signal Generator     | Agilent      | N5183A  | MY50140980 | Nov. 10, 2014 | 1 Year        |
| Power Meter                     | Agilent      | ML2495A | 1139001    | Feb. 21, 2014 | 1 Year        |
| Power Sensor                    | Agilent      | MA2411B | 1126068    | Feb. 21, 2014 | 1 Year        |
| Single Output DC Power Supply   | Agilent      | U8002A  | MY52140018 | Apr. 03, 2014 | 1 Year        |
| Temp. & Humi. Recorder          | HUATO        | A2000TH | HE20107684 | Jul. 21, 2014 | 1 Year        |
| Electronic Thermometer          | YONGFA       | YF-160A | 120100323  | Oct. 21, 2014 | 1 Year        |

## 6. Measurement Uncertainty

| Error Description                    | Uncertainty Value (±%) | Probability Distribution | Divisor | Ci (1g) | Standard Uncertainty (1g) | Vi |
|--------------------------------------|------------------------|--------------------------|---------|---------|---------------------------|----|
| <b>Measurement System</b>            |                        |                          |         |         |                           |    |
| Probe Calibration                    | 6.0                    | Normal                   | 1       | 1       | ± 6.0 %                   | ∞  |
| Axial Isotropy                       | 4.7                    | Rectangular              | √3      | 0.7     | ± 1.9 %                   | ∞  |
| Hemispherical Isotropy               | 9.6                    | Rectangular              | √3      | 0.7     | ± 3.9 %                   | ∞  |
| Boundary Effects                     | 1.0                    | Rectangular              | √3      | 1       | ± 0.6 %                   | ∞  |
| Linearity                            | 4.7                    | Rectangular              | √3      | 1       | ± 2.7 %                   | ∞  |
| System Detection Limits              | 1.0                    | Rectangular              | √3      | 1       | ± 0.6 %                   | ∞  |
| Readout Electronics                  | 0.6                    | Normal                   | 1       | 1       | ± 0.6 %                   | ∞  |
| Response Time                        | 0.0                    | Rectangular              | √3      | 1       | ± 0.0 %                   | ∞  |
| Integration Time                     | 1.7                    | Rectangular              | √3      | 1       | ± 1.0 %                   | ∞  |
| RF Ambient Noise                     | 3.0                    | Rectangular              | √3      | 1       | ± 1.7 %                   | ∞  |
| RF Ambient Reflections               | 3.0                    | Rectangular              | √3      | 1       | ± 1.7 %                   | ∞  |
| Probe Positioner                     | 0.5                    | Rectangular              | √3      | 1       | ± 0.3 %                   | ∞  |
| Probe Positioning                    | 2.9                    | Rectangular              | √3      | 1       | ± 1.7 %                   | ∞  |
| Max. SAR Eval.                       | 2.3                    | Rectangular              | √3      | 1       | ± 1.3 %                   | ∞  |
| <b>Test Sample Related</b>           |                        |                          |         |         |                           |    |
| Device Positioning                   | 3.9                    | Normal                   | 1       | 1       | ± 3.9 %                   | 31 |
| Device Holder                        | 2.7                    | Normal                   | 1       | 1       | ± 2.7 %                   | 19 |
| Power Drift                          | 5.0                    | Rectangular              | √3      | 1       | ± 2.9 %                   | ∞  |
| <b>Phantom and Setup</b>             |                        |                          |         |         |                           |    |
| Phantom Uncertainty                  | 4.0                    | Rectangular              | √3      | 1       | ± 2.3 %                   | ∞  |
| Liquid Conductivity (Target)         | 5.0                    | Rectangular              | √3      | 0.64    | ± 1.8 %                   | ∞  |
| Liquid Conductivity (Meas.)          | 5.0                    | Normal                   | 1       | 0.64    | ± 3.2 %                   | 29 |
| Liquid Permittivity (Target)         | 5.0                    | Rectangular              | √3      | 0.6     | ± 1.7 %                   | ∞  |
| Liquid Permittivity (Meas.)          | 5.0                    | Normal                   | 1       | 0.6     | ± 3.0 %                   | 29 |
| <b>Combined Standard Uncertainty</b> |                        |                          |         |         | ± 11.7 %                  |    |
| <b>Expanded Uncertainty (K=2)</b>    |                        |                          |         |         | ± 23.4 %                  |    |

Uncertainty budget for frequency range 300 MHz to 3 GHz

# FCC SAR Test Report

A D T

| Error Description                    | Uncertainty Value (±%) | Probability Distribution | Divisor | Ci (1g) | Standard Uncertainty (1g) | Vi |
|--------------------------------------|------------------------|--------------------------|---------|---------|---------------------------|----|
| <b>Measurement System</b>            |                        |                          |         |         |                           |    |
| Probe Calibration                    | 6.55                   | Normal                   | 1       | 1       | ± 6.55 %                  | ∞  |
| Axial Isotropy                       | 4.7                    | Rectangular              | √3      | 0.7     | ± 1.9 %                   | ∞  |
| Hemispherical Isotropy               | 9.6                    | Rectangular              | √3      | 0.7     | ± 3.9 %                   | ∞  |
| Boundary Effects                     | 2.0                    | Rectangular              | √3      | 1       | ± 1.2 %                   | ∞  |
| Linearity                            | 4.7                    | Rectangular              | √3      | 1       | ± 2.7 %                   | ∞  |
| System Detection Limits              | 1.0                    | Rectangular              | √3      | 1       | ± 0.6 %                   | ∞  |
| Readout Electronics                  | 0.3                    | Normal                   | 1       | 1       | ± 0.3 %                   | ∞  |
| Response Time                        | 0.8                    | Rectangular              | √3      | 1       | ± 0.5 %                   | ∞  |
| Integration Time                     | 2.6                    | Rectangular              | √3      | 1       | ± 1.5 %                   | ∞  |
| RF Ambient Noise                     | 3.0                    | Rectangular              | √3      | 1       | ± 1.7 %                   | ∞  |
| RF Ambient Reflections               | 3.0                    | Rectangular              | √3      | 1       | ± 1.7 %                   | ∞  |
| Probe Positioner                     | 0.8                    | Rectangular              | √3      | 1       | ± 0.5 %                   | ∞  |
| Probe Positioning                    | 9.9                    | Rectangular              | √3      | 1       | ± 5.7 %                   | ∞  |
| Max. SAR Eval.                       | 4.0                    | Rectangular              | √3      | 1       | ± 2.3 %                   | ∞  |
| <b>Test Sample Related</b>           |                        |                          |         |         |                           |    |
| Device Positioning                   | 3.9                    | Normal                   | 1       | 1       | ± 3.9 %                   | 31 |
| Device Holder                        | 2.7                    | Normal                   | 1       | 1       | ± 2.7 %                   | 19 |
| Power Drift                          | 5.0                    | Rectangular              | √3      | 1       | ± 2.9 %                   | ∞  |
| <b>Phantom and Setup</b>             |                        |                          |         |         |                           |    |
| Phantom Uncertainty                  | 4.0                    | Rectangular              | √3      | 1       | ± 2.3 %                   | ∞  |
| Liquid Conductivity (Target)         | 5.0                    | Rectangular              | √3      | 0.64    | ± 1.8 %                   | ∞  |
| Liquid Conductivity (Meas.)          | 5.0                    | Normal                   | 1       | 0.64    | ± 3.2 %                   | 30 |
| Liquid Permittivity (Target)         | 5.0                    | Rectangular              | √3      | 0.6     | ± 1.7 %                   | ∞  |
| Liquid Permittivity (Meas.)          | 5.0                    | Normal                   | 1       | 0.6     | ± 3.0 %                   | 30 |
| <b>Combined Standard Uncertainty</b> |                        |                          |         |         | ± 13.4 %                  |    |
| <b>Expanded Uncertainty (K=2)</b>    |                        |                          |         |         | ± 26.8 %                  |    |

Uncertainty budget for frequency range 3 GHz to 6 GHz

## FCC SAR Test Report

---

### 7. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., China Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**China Dongguan Lab:**

No. 34, Guantai Rd., Houjie Town, Dongguan, Guangdong 523942, China

Tel: 86-769-8593-5656

Fax: 86-769-8599-1080

**Email:** [service.dg@cn.bureauveritas.com](mailto:service.dg@cn.bureauveritas.com)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The road map of all our labs can be found in our web site also.

---END---



## **Appendix A. SAR Plots of System Verification**

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

**System Check\_B750\_150107****DUT: Dipole:750 MHz; D750V3;SN:1067**

Communication System: CW; Frequency: 750 MHz;Duty Cycle: 1:1

Medium: B750-A\_0107 Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.969$  S/m;  $\epsilon_r = 55.447$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.6 °C; Liquid Temperature : 20.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.54, 9.54, 9.54); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (71x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 2.49 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 51.43 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 2.64 W/kg

**SAR(1 g) = 2.24 W/kg; SAR(10 g) = 1.68 W/kg**

Maximum value of SAR (measured) = 2.54 W/kg




**System Check\_B835\_150107****DUT: Dipole:835 MHz; Type:D835V2; SN:4d139**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: B835-A\_0107 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.992 \text{ S/m}$ ;  $\epsilon_r = 55.56$ ;  $\rho = 1000 \text{ kg/m}^3$ Ambient Temperature :  $21.7^\circ\text{C}$ ; Liquid Temperature :  $20.8^\circ\text{C}$ 

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.5, 9.5, 9.5); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x101x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) =  $2.95 \text{ W/kg}$ **Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $54.96 \text{ V/m}$ ; Power Drift =  $0.13 \text{ dB}$ Peak SAR (extrapolated) =  $3.44 \text{ W/kg}$ **SAR(1 g) =  $2.41 \text{ W/kg}$ ; SAR(10 g) =  $1.62 \text{ W/kg}$** Maximum value of SAR (measured) =  $3.00 \text{ W/kg}$ 

**System Check\_B1750\_150102****DUT: Dipole 1750 MHz ;Type:D1750V2; SN:1071**

Communication System: CW; Frequency: 1750 MHz;Duty Cycle: 1:1

Medium: B1750-A\_0102 Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.462$  S/m;  $\epsilon_r = 54.513$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.1 °C ; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.72, 7.72, 7.72); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 13.4 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 92.35 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 16.9 W/kg

**SAR(1 g) = 9.7 W/kg; SAR(10 g) = 5.22 W/kg**

Maximum value of SAR (measured) = 13.5 W/kg



**System Check\_B1900\_141230****DUT: Dipole:1900MHz; Type:D1900V2; SN:5d159**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: B1900-A\_1230 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.552$  S/m;  $\epsilon_r = 54.013$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.8 °C; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.44, 7.44, 7.44); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 14.7 W/kg



**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 97.30 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 18.7 W/kg

**SAR(1 g) = 10.4 W/kg; SAR(10 g) = 5.39 W/kg**

Maximum value of SAR (measured) = 14.8 W/kg



**System Check\_B2600\_150108****DUT: Dipole 2600 MHz; Type: D2600V2; SN: 1020**

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: B2600-A\_0108 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.2$  S/m;  $\epsilon_r = 52.401$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22 °C ; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(6.94, 6.94, 6.94); Calibrated: 2014/8/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/8/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 21.9 W/kg


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 98.45 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 29.9 W/kg

**SAR(1 g) = 13.7 W/kg; SAR(10 g) = 6.11 W/kg**

Maximum value of SAR (measured) = 21.5 W/kg



**System Check\_B5800\_150109****DUT: Dipole D5GHzV2; Type:D5GHzV2; SN:1133**

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: B5G-A\_0109 Medium parameters used:  $f = 5800$  MHz;  $\sigma = 6.221$  S/m;  $\epsilon_r = 47.4$ ;  $\rho =$

$1000 \text{ kg/m}^3$

Ambient Temperature :  $22.3^\circ\text{C}$ ; Liquid Temperature :  $21.5^\circ\text{C}$

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3873; ConvF(4, 4, 4); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid:  $dx=1.000$  mm,  $dy=1.000$  mm

Maximum value of SAR (interpolated) =  $13.6 \text{ W/kg}$


**Pin=100mW/Zoom Scan (7x7x11)/Cube 0:** Measurement grid:  $dx=4$ mm,  $dy=4$ mm,  $dz=2$ mm

Reference Value =  $49.66 \text{ V/m}$ ; Power Drift =  $0.03 \text{ dB}$

Peak SAR (extrapolated) =  $30.2 \text{ W/kg}$

**SAR(1 g) =  $6.83 \text{ W/kg}$ ; SAR(10 g) =  $1.9 \text{ W/kg}$**

Maximum value of SAR (measured) =  $14.8 \text{ W/kg}$





### Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.



**P01 WCDMA II\_RMC12.2K\_Rear Face\_0cm\_Ch9262\_w/ Pw Reduction****DUT: 141127N057**

Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: B1900-A\_1230 Medium parameters used:  $f = 1852.4$  MHz;  $\sigma = 1.497$  S/m;  $\epsilon_r = 54.173$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.8 °C; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.44, 7.44, 7.44); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (81x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 2.22 W/kg



**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.079 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 2.81 W/kg

**SAR(1 g) = 1.36 W/kg; SAR(10 g) = 0.624 W/kg**

Maximum value of SAR (measured) = 2.17 W/kg



**P02 WCDMA V\_RMC12.2K\_Front Face\_1.1cm\_Ch4233\_w/o Pw Reduction****DUT: 141127N057**

Communication System: WCDMA; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium: B835-A\_0107 Medium parameters used:  $f = 847$  MHz;  $\sigma = 1.004$  S/m;  $\epsilon_r = 55.434$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.7 °C; Liquid Temperature : 20.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.5, 9.5, 9.5); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (81x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.613 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.674 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.732 W/kg

**SAR(1 g) = 0.491 W/kg; SAR(10 g) = 0.317 W/kg**

Maximum value of SAR (measured) = 0.611 W/kg



**P03 LTE 2\_QPSK20M\_Rear Face\_0cm\_Ch18900\_w/ Pw Reduction\_1RB\_OS0****DUT: 141127N057**

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900-A\_1230 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.529$  S/m;  $\epsilon_r = 54.066$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.8 °C ; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.44, 7.44, 7.44); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (81x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.86 W/kg



**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.933 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 2.55 W/kg

**SAR(1 g) = 1.25 W/kg; SAR(10 g) = 0.585 W/kg**

Maximum value of SAR (measured) = 1.88 W/kg



**P04 LTE 4\_QPSK20M\_Rear Face\_0cm\_Ch20300\_w/ Pw Reduction\_50RB\_OS0****DUT: 141127N057**

Communication System: LTE; Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: B1750-A\_0102 Medium parameters used:  $f = 1745$  MHz;  $\sigma = 1.455$  S/m;  $\epsilon_r = 54.523$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.1 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.72, 7.72, 7.72); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (81x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.72 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.096 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 2.29 W/kg

**SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.533 W/kg**

Maximum value of SAR (measured) = 1.71 W/kg



**P05 LTE 5\_QPSK10M\_Front Face\_1.1cm\_Ch20600\_w/o Pw Reduction\_1RB\_OS0****DUT: 141127N057**

Communication System: LTE; Frequency: 844 MHz; Duty Cycle: 1:1

Medium: B835-A\_0107 Medium parameters used:  $f = 844$  MHz;  $\sigma = 1.001$  S/m;  $\epsilon_r = 55.463$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.7 °C; Liquid Temperature : 20.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.5, 9.5, 9.5); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (81x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.523 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.921 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.615 W/kg

**SAR(1 g) = 0.418 W/kg; SAR(10 g) = 0.273 W/kg**

Maximum value of SAR (measured) = 0.527 W/kg



**P06 LTE 7\_QPSK20M\_Rear Face\_0cm\_Ch21100\_w/ Pw Reduction\_50RB\_OS0****DUT: 141127N057**

Communication System: LTE; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium: B2600-A\_0108 Medium parameters used:  $f = 2535$  MHz;  $\sigma = 2.114$  S/m;  $\epsilon_r = 52.633$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(6.94, 6.94, 6.94); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (81x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.24 W/kg


**- Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.9670 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 2.16 W/kg

**SAR(1 g) = 0.682 W/kg; SAR(10 g) = 0.269 W/kg**

Maximum value of SAR (measured) = 1.17 W/kg



**P07 LTE 17\_QPSK10M\_Rear Face\_1.2cm\_Ch23800\_w/o Pw Reduction\_1RB\_OS0****DUT: 141127N057**

Communication System: LTE; Frequency: 711 MHz; Duty Cycle: 1:1

Medium: B750-A\_0107 Medium parameters used:  $f = 711$  MHz;  $\sigma = 0.936$  S/m;  $\epsilon_r = 55.765$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.6 °C; Liquid Temperature : 20.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.54, 9.54, 9.54); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (81x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.369 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.802 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.417 W/kg

**SAR(1 g) = 0.317 W/kg; SAR(10 g) = 0.232 W/kg**

Maximum value of SAR (measured) = 0.362 W/kg



**P08 802.11a\_Left Side\_0cm\_Ch149\_Antenna 0****DUT: 141127N057**

Communication System: 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1.02

Medium: B5G-A\_0109 Medium parameters used:  $f = 5745$  MHz;  $\sigma = 6.162$  S/m;  $\epsilon_r = 47.503$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(4, 4, 4); Calibrated: 2014/08/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2014/08/26
- Phantom: ELI 5.0; Type: QD OVA 001 BB; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (61x121x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.320 W/kg

**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 1.503 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.766 W/kg

**SAR(1 g) = 0.166 W/kg; SAR(10 g) = 0.038 W/kg**

Maximum value of SAR (measured) = 0.392 W/kg

