

FCC TEST REPORT

For

LOFT

Model Number: F101P

FCC ID: 2ACCJB004

Report Number : WT148003752

Test Laboratory	:	Shenzhen Academy of Metrology and Quality Inspection National Digital Electronic Product Testing Center
Site Location	:	NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China
Tel	:	0086-755-86928965
Fax	:	0086-755-86009898-31396
Web	:	www.smq.com.cn
E-mail	:	emcrf@smq.com.cn

Test report declaration

Applicant : TCT Mobile Limited

Address : 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

Manufacturer : TCL COMMUNICATION TECHNOLOGY HOLDINGS LIMITED

Address : 70 Huifeng 4rd,ZhongKai Hi-tech Development District , Huizhou,Guangdong 516006 P.R.China
(TCL Mobile Communication Co.,LTD.Huizhou)

EUT : LOFT

Description

Model No : F101P

Trade mark : ALCATEL ONETOUCH

Marketing : ALCATEL ONETOUCH HOME F101

Name

Serial Number : --

FCC ID : **2ACCB004**

Test Standards:

FCC PART 22H AND 24E (2012)

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with FCC Rules Part 22H AND 24E.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Project
Engineer:



(Chen Silin)

Date: Dec.19 ,2014

Checked by:



(Yang Dongping)

Date: Dec.19 ,2014

Approved by:



(Peter Lin)

Date: Dec.19 ,2014

TABLE OF CONTENTS

TEST REPORT DECLARATION	2
1. TEST RESULTS SUMMARY	4
2. GENERAL INFORMATION	5
2.1. Report information	5
2.2. Laboratory Accreditation and Relationship to Customer	5
2.3. Measurement Uncertainty	6
3. PRODUCT DESCRIPTION	7
3.1. EUT Description	7
3.2. Related Submittal(s) / Grant (s)	7
3.3. Block Diagram of EUT Configuration	8
3.4. Operating Condition of EUT	8
3.5. Support Equipment List	9
3.6. Test Conditions	9
3.7. Special Accessories	9
3.8. Equipment Modifications	9
4. TEST EQUIPMENT USED	10
5. TEST RESULTS	11
5.1. RF Power Output	11
5.2. Peak to Average Ratio	13
5.3. Modulation Characteristics	14
5.4. Occupied Bandwidth/Emission Bandwidth	15
5.5. Spurious Emission at Antenna Terminal	18
5.6. Spurious Emissions Radiated	27
5.7. Frequency Stability	30

TEST Results Summary

Table 1 Test Results Summary

FCC Measurement Specification	FCC Limits Part(s)	Description	Result
2.1046	22.913 24.232	Effective Radiated Power of Transmitter	PASS
	24.232(d)	Peak to Average Ratio	PASS
2.1047	/	Modulation Characteristics	PASS
2.1049	22.917(b) 24.238(b)	Occupied Bandwidth	PASS
2.1051	22.917 24.238	Spurious Emission at Antenna Terminal	PASS
2.1053	22.917 24.238	Radiated Spurious Emissions	PASS
2.1055	22.355 24.235	Frequency Stability	PASS

Remark: "N/A" means "Not applicable."

The tests documented in this report were performed in accordance with TIA-603-C, FCC CFR 47 Part 2, FCC CFR 47 Part 22 Part 24.

1. GENERAL INFORMATION

1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 1.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

1.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at No.4 Tongfa Road, Xili Town, Nanshan District, Shenzhen, Guangdong, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number are 446246 806614 994606(semi anechoic chamber).

The Laboratory is listed in Voluntary Control Council for Interference by Information Technology Equipment (VCCI), and the registration number are R-1974(open area test site) , R-1966(semi anechoic chamber),C-2117(mains ports conducted interference measurement) and T-180(telecommunication ports conducted interference measurement).

The Laboratory is registered to perform emission tests with Industry Canada (IC), and the registration number is IC4174.

TUV Rhineland accredits the Laboratory for conformance to IEC and EN standards, the registration number is E2024086Z02.

1.3.Measurement Uncertainty

Conducted Emission

9kHz~30MHz 3.5dB

Radiated Emission

30MHz~1000MHz 4.5dB

1GHz~18GHz 4.6dB

2. PRODUCT DESCRIPTION

2.1.EUT Description

Table 2 Specification of the Equipment under Test

Product Type:	LOFT
Hardware Revision :	PIO14
Software Revision :	N/A
FCC-ID:	2ACCJB004
Frequency:	CDMA1900: 1851.25-1908.75MHz
Type(s) of Modulation:	CDMA: QPSK
Antenna Type:	PIFA Model: N/A Typical gain: 1dBi
Operating voltage:	Internal battery, 110V AC Adapter; 3.4V (Low)/3.7V (Nominal)/ 4.2V (Max)

Table 3 Identification of the Equipment Under Test (EUT)

EUT	Serial Number/IMEI	HW Version	SW Version	Notes
1	A1000043041744	PIO14	N/A	Conducted testing sample.
2	A1000043041745	PIO14	N/A	Radiated testing sample.

Table 4 Identification of Accessory equipment

AE #	Type	Manufacturer	Model	Serial Number
1	Battery	BYD Lithium Battery Co.,Ltd.	TLi008A1	N/A
2	External Antenna connector	N/A	N/A	N/A

2.2.Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2ACCJB004 filing to comply with FCC PART 22H AND 24E.

2.3. Block Diagram of EUT Configuration




Figure 1 EUT setup of test mode 1

2.4. Operating Condition of EUT

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission (X plane).

TM1: 1xRTT RC3 SO55

The maximum power levels are RC3 SO55 mode for 1xRTT, only these modes were used for all tests.

The conducted power tables are as follows:

RF Power Output for 1xRTT - 1900 Band				
Radio Configuration (RC)	Service Option(SO)	Conducted Output Power (dBm)		
		Ch. 25/1851.25 MHz	Ch. 600/1880MHz	Ch. 1175/1908.75 MHz
		Peak	Peak	Peak
RC1 (Fwd1, Rvs1)	55 (Loopback)	23.90	24.33	24.06
RC3 (Fwd3, Rvs3)	55 (Loopback)	23.93	24.45	24.12
	32 (+F-SCH)	23.91	24.36	23.87
	32 (+SCH)	23.64	24.44	23.98

2.5. Support Equipment List

Table 5 Support Equipment List

Name	Model No	S/N	Manufacturer
Adaptor for EUT	CBA3002AA0C2		TEN PAO

2.6. Test Conditions

Date of test: Sep 30,2014-Dec 15, 2014

Date of EUT Receive: Sep 30,2014

Temperature: -30~55 °C

Relative Humidity: 52~58%

2.7. Special Accessories

Not available for this EUT intended for grant.

2.8. Equipment Modifications

Not available for this EUT intended for grant.

3. TEST EQUIPMENT USED

Table 6 Test Equipment

No.	Equipment	Manufacturer	Model No.	Last Cal.	Cal. Interval
SB2603	EMI Test Receiver	Rohde & Schwarz	ESCS30	Jan.20, 2014	1 Year
SB3321	AMN	Rohde & Schwarz	ESH2-Z5	Jan.20, 2014	1 Year
SB2604	AMN	Rohde & Schwarz	ESH3-Z5	Jan.20, 2014	1 Year
SB8501/09	EMI Test Receiver	Rohde & Schwarz	ESU40	May.16, 2014	1 Year
SB8501/04	Bilog Antenna	Schwarzbeck	VULB9163	May 13, 2014	1 Year
SB5472/02	Bilog Antenna	Schwarzbeck	VULB9163	Jan.20, 2014	1 Year
SB3435	Horn Antenna	Rohde & Schwarz	HF906	Jan.20, 2014	1 Year
SB3434	Horn Antenna	Rohde & Schwarz	HF906	Jan.20, 2014	1 Year
SB3435/01	Amplifier(1-18GHz)	Rohde & Schwarz	---	Jan.20, 2014	1 Year
SB3435/02	Amplifier(18-40GHz)	Rohde & Schwarz	---	May.16, 2014	1 Year
SB5392/02	Horn Antenna	Amplifier Research	AT4560	May.16, 2014	1 Year
SB3450/01	3m Semi-anechoic chamber	Albatross Projects	9X6X6	Oct.11, 2014	2 Years
SB8501/02	Communication Test Unit	Rohde & Schwarz	CMU200	Jan.7, 2014	1 Year
SB9721/02	Signal Analyzer	Agilent	N9020A	Feb.3, 2014	1 Year
SB3611	DC Power Supply	KENWOOD	PDS36-10	May.16, 2014	1 Year
SB6691	Climatic Chamber	NANYA	DW-0150	Apr 13, 2014	1 Year
SB9721/03	Signal Generator	Agilent	E4438C	Feb 3, 2014	1 Year
---	Conducted Emissions Cable set	HUBER+SUHNER	---	Sept 3.2014	1 Year
----	Conducted Emissions Cable set	HUBER+SUHNER	---	Sept 3.2014	1 Year
----	Radiated Emissions Cable set	HUBER+SUHNER	---	Jan.20, 2014	1 Year
---	Radiated Emissions Cable set	HUBER+SUHNER	---	Jan.20, 2014	1 Year

4. TEST RESULTS

4.1. RF Power Output

4.1.1. Test Standard

FCC: CFR Part 2.1046, CFR Part 22.913, CFR Part 24.232

4.1.2. Test Limit

FCC 22.913 (a) Effective radiated power limits.

The effective radiated power (ERP) of mobile transmitters must not exceed 7 Watts.

FCC 24.232 (b)(c) Power limits.

(b) Mobile/portable stations are limited to 2 Watts effective isotropic radiated power (EIRP). (c) Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms equivalent voltage. The measurement results shall be properly adjusted for any limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement over the full bandwidth of the channel.

4.1.3. Test Procedure

Radiated Output Power Measurement procedure

Ref: TIA-603C 2004 -2.2.17.2 Effective Radiated Power (ERP) or Effective Isotropic

1. Connect the equipment as shown in the above diagram with the EUT's antenna in a vertical orientation.
2. Adjust the settings of the Universal Radio Communication Tester (CMU) to set the EUT to its maximum power at the required channel.
3. Set the spectrum analyzer to the channel frequency. Set the analyzer to measure peak hold with the required settings.
4. Rotate the EUT 360°. Record the peak level in dBm (LVL).
5. Replace the EUT with a vertically polarized half wave dipole or known gain antenna. The center of the antenna should be at the same location as the center of the EUT's antenna.
6. Connect the antenna to a signal generator with known output power and record the path loss in dB (LOSS). $LOSS = \text{Generator Output Power (dBm)} - \text{Analyzer reading (dBm)}$.
7. Determine the ERP using the following equation:
 $ERP \text{ (dBm)} = LVL \text{ (dBm)} + LOSS \text{ (dB)}$
8. Determine the EIRP using the following equation:
 $EIRP \text{ (dBm)} = ERP \text{ (dBm)} + 2.15 \text{ (dB)}$
9. Measurements are to be performed with the EUT set to the low, middle and high channel of each frequency band.

4.1.4. Test Data

Table 7 Substitution Results

Test Mode	Freq. [MHz]	SG. Level [dBm]	Cable Loss [dB]	Antenna Gain [dBi]	Substitution Level (EIRP) [dBm]	Limit [dBm]	Polarization	Result
TM1	1851.25	13.38	0.97	8.92	21.33	33	Vertical	Pass
TM1	1880	13.44	0.97	8.92	21.39	33	Vertical	Pass
TM1	1908.75	13.53	0.97	8.92	21.48	33	Vertical	Pass

Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

4.2. Peak to Average Ratio

4.2.1. Test Standard

CFR 47 (FCC) part 24 subpart E

4.2.2. Test Limit

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.2.3. Test Procedure

A peak to average ratio measurement is performed at the conducted port of the EUT. For CDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

4.2.4. Test Data

Test Band	Test Mode	Test Channel	Measured[dB]	Limit [dB]	Verdict
CDMA1900	TM1	1880	3.69	13	PASS

As the modulation used by the product is not vary with frequencies, the PAR is measured on 1880MHz only.

4.3. Modulation Characteristics

4.3.1. Test Standard

CFR 47 (FCC) part 2.1047, part 22 subpart H and par 24 subpart E

4.3.2. Test Limit

2.1047 (d) Other types of equipment. A curve or equivalent data which shows that the equipment will meet the modulation requirements of the rules under which the equipment is to be licensed.


4.3.3. Test Procedure

Connect the EUT to Universal Radio Communication Tester CMU200 via the antenna connector. The frequency band is set as US cellular; the EUT's output is matched with 50 Ω load, test method was according to 3GPP TS 51.010 and 3GPP TS 34.121. The waveform quality and constellation of the Mobile Phone was tested.

4.3.4. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

4.3.5. Test Data



4.4. Occupied Bandwidth/Emission Bandwidth

4.4.1. Test Standard

FCC: CFR Part 2.1049, CFR Part 22.917, CFR Part 24.238

4.4.2. Test Limit


The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable.

(h) Transmitters employing digital modulation techniques-when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated.

4.4.3. Test Procedure

1. Connect the equipment as shown in the above diagram.
 2. Adjust the settings of the Universal Radio Communication Tester (CMU) to set the EUT to its maximum power at the required channel.
 3. Set the spectrum analyzer to measure the 99% occupied bandwidth. Record the value.
 4. Set the spectrum analyzer to measure the -26 dB emission bandwidth. Record the value.
 5. Measurements are to be performed with the EUT set to the low, middle and high channel of each frequency band.
- Spectrum analyzer settings: Measurement bandwidth of at least 1% of the occupied bandwidth.

4.4.4. Test Setup



4.4.5. Test Data


Table 8 Occupied Bandwidth Test Data

CDMA 1900: TM1		
CHANNEL FREQUENCY (MHz)	99% OBW (MHz)	26dBc BANDWIDTH (MHz)
1851.25	1.2730	1.444
1880	1.2741	1.442
1908.75	1.2826	1.448


Test Band = CDMA1900

Test Mode = CDMA/TM1


Test Channel = LCH



Test Band = CDMA1900
 Test Mode = CDMA/TM1
 Test Channel = MCH



Test Band = CDMA1900
 Test Mode = CDMA/TM1
 Test Channel = HCH



4.5. Spurious Emission at Antenna Terminal

4.5.1. Test Standard

FCC: CFR Part 2.1051, CFR Part 22.917, CFR Part 24.238

4.5.2. Test Limit

The radio frequency voltage or power generated within the equipment and appearing on a

spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in FCC 2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. For all power levels +30dBm to 0dBm, this becomes a constant specification of -13dBm.

FCC 22.917 Emission limitations for cellular equipment.

The rules in this section govern the spectral characteristics of emissions in the Cellular

Radiotelephone Service.

(b) Measurement procedure. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz of 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

FCC 24.238 Emission limitations for Broadband PCS equipment.


The rules in this section govern the spectral characteristics of emissions in the Broadband Personal Communications Service.

(b) Measurement procedure. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz of 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

4.5.3. Test Procedure

1. Connect the equipment as shown in the above diagram.
 2. Set the spectrum analyzer to measure peak hold with the required settings.
 3. Set the signal generator to a known output power and record the path loss in dB (LOSS) for frequencies up to the tenth harmonic of the EUT's carrier frequency. \ $LOSS = \text{Generator Output Power (dBm)} - \text{Analyzer reading (dBm)}$.
 4. Replace the signal generator with the EUT.
 5. Adjust the settings of the Universal Radio Communication Tester (CMU) to set the EUT to its maximum power at the required channel.
 6. Set the spectrum analyzer to measure peak hold with the required settings. Offset the spectrum analyzer reference level by the path loss measured above.
 7. Measure and record all spurious emissions up to the tenth harmonic of the carrier frequency.
 8. Measurements are to be performed with the EUT set to the low, middle and high channel of each frequency band.
 9. If necessary steps 6 and 7 may be performed with the spectrum analyzer set to average detector.
- (Note: Step 3 above is performed prior to testing and LOSS is recorded by test software. Steps 2, 6, and 7 above are performed with test software.)

4.5.4. Test Setup





4.5.5. Test Data



Out of band measurement

Test Band = CDMA1900



Test Mode = CDMA /TM1



Test Channel = LCH









Out of band measurement
 Test Band = CDMA1900
 Test Mode = CDMA /TM1
 Test Channel = MCH







Out of band measurement
 Test Band = CDMA1900
 Test Mode = CDMA /TM1
 Test Channel = HCH





Band edge measurement
 Test Band = CDMA1900
 Test Mode = CDMA /TM1
 Test Channel = LCH/HCH



4.6. Spurious Emissions Radiated

4.6.1. Test Standard

FCC: CFR Part 2.1053, CFR Part 22.917, CFR Part 24.238

4.6.2. Test Limit

Measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission.

5.5.3 Limits:

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

For all power levels +30dBm to 0dBm, this becomes a constant specification of -13dBm.

5.5.3.1 FCC 22.917 Emission limitations for cellular equipment.

The rules in this section govern the spectral characteristics of emissions in the Cellular

Radiotelephone Service.

(b) Measurement procedure. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz of 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

5.5.3.2 FCC 24.238 Emission limitations for Broadband PCS equipment.

The rules in this section govern the spectral characteristics of emissions in the Broadband Personal Communications Service.


(b) Measurement procedure. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz of 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

4.6.3. Test Procedure

1. Connect the equipment as shown in the above diagram with the EUT's antenna in a horizontal orientation.
 2. Adjust the settings of the Universal Radio Communication Tester (CMU) to set the EUT to its maximum power at the required channel.
 3. Set the spectrum analyzer to measure peak hold with the required settings.
 4. Place the measurement antenna in a horizontal orientation. Rotate the EUT 360 .
Raise the measurement antenna up to 4 meters in 0.5 meters increments and rotate the EUT 360 at each height to maximize all emissions. Measure and record all spurious emissions (LVL) up to the tenth harmonic of the carrier frequency.
 5. Replace the EUT with a horizontally polarized half wave dipole or known gain antenna. The center of the antenna should be at the same location as the center of the EUT's antenna.
 6. Connect the antenna to a signal generator with known output power and record the path loss in dB (LOSS). $LOSS = \text{Generator Output Power (dBm)} - \text{Analyzer reading (dBm)}$.
 7. Determine the level of spurious emissions using the following equation:
 $\text{Spurious (dBm)} = \text{LVL (dBm)} + \text{LOSS (dB)}$
 8. Repeat steps 4, 5 and 6 with all antennas vertically polarized.
 9. Determine the level of spurious emissions using the following equation:
 $\text{Spurious (dBm)} = \text{LVL (dBm)} + \text{LOSS (dB)}$
 10. Measurements are to be performed with the EUT set to the low, middle and high channel of each frequency band.
- (Note: Steps 5 and 6 above are performed prior to testing and LOSS is recorded by test software. Steps 3, 4 and 7 above are performed with test software.)

Spectrum analyzer settings: RBW=VBW=1MHz

4.6.4. Test Setup



4.6.5. Test Data

Test Band = CDMA1900

Test Mode = CDMA /TM1

Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Polarization	Substitution	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB		Level (EIRP)	[dBm]
						[dBm]	
3702.5	-6.25	4.6	9.53	39	V	-40.32	-13

No other emissions were detected above system noise floor

Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = CDMA1900

Test Mode = CDMA /TM1

Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Polarization	Substitution	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB		Level (EIRP)	[dBm]
						[dBm]	
3760	-6.2	4.6	9.53	39	V	-40.27	-13
5640	-8.72	6.32	10	38.5	V	-43.54	-13

No other emissions were detected above system noise floor

Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = CDMA1900

Test Mode = CDMA /TM1

Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Polarization	Substitution	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB		Level (EIRP)	[dBm]
						[dBm]	
3817.5	-5.56	4.6	9.53	39	V	-39.63	-13
5726.25	-5.23	6.32	10	38.5	V	-40.05	-13

No other emissions were detected above system noise floor

Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

4.7. Frequency Stability

4.7.1. Test Standard

CFR 47 (FCC) part 2.1055, 22.355 and 24.235

4.7.2. Test Limit

According to part 22.355, from 821MHz to 896MHz, for mobile device, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances 2.5ppm.

4.7.3. Test Procedure

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU 200 Universal Radio Communication Tester.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30 C.
3. With the EUT, powered via nominal voltage, connected to the CMU 200 and in a simulated call on mid channel, measure the carrier frequency. These measurements should be made within 2 minutes of powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10 C increments from -30 C to +50 C. Allow at least 1 1/2 hours at each temperature, un-powered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Re-measure carrier frequency at low and high voltage. Pause at nominal voltage for 1 1/2 hours un-powered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50 C.
7. With the EUT, powered via nominal voltage, connected to the CMU 200 and in a simulated call on mid channel (384 for CDMA 800 & 600 for CDMA 1900), measure the carrier frequency. These measurements should be made within 2 minutes of powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50 C to -30 C. Allow at least 1 1/2 hours at each temperature, un-powered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5 C during the measurement procedure.

4.7.4. Test Setup

Connect the EUT to the Wireless Communication test set CMU200 via the connector. Then measure the frequency error by the Wireless Communication test set CMU200. The EUT's output is matched with a 50 Ω load.

4.7.5. Test Data

Measurement Results vs. Variation of Temperature—CDMA1900 1XRTT

Temperature	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 ℃	1880.0	22	Pass
-20 ℃	1880.0	21	Pass
-10 ℃	1880.0	3	Pass
0 ℃	1880.0	-15	Pass
+10 ℃	1880.0	25	Pass
+20 ℃	1880.0	-19	Pass
+30 ℃	1880.0	-7	Pass
+40 ℃	1880.0	1	Pass
+55 ℃	1880.0	-24	Pass

Measurement Results vs. Variation of Voltage—CDMA1900 1XRTT

Voltage	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
3.4 V	1880.0	-15	Pass
3.7 V	1880.0	10	Pass
4.2V	1880.0	-18	Pass