



# FCC RF Test Report

**APPLICANT** : TCL Communication Ltd.  
**EQUIPMENT** : HSUPA/HSDPA/UMTS Tri Band/GSM Quad  
Band/LTE 7 band mobile phone  
**BRAND NAME** : Vodafone  
**MODEL NAME** : VFD 900  
**FCC ID** : 2ACCJN007  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System

The product was received on Dec. 14, 2015 and testing was completed on Mar. 23, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

---

Prepared by: James Huang / Manager

---

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China**



## TABLE OF CONTENTS

<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1. Applicant .....	5
1.2. Manufacturer .....	5
1.3. Product Feature of Equipment Under Test .....	5
1.4. Product Specification subjective to this standard .....	6
1.5. Modification of EUT .....	6
1.6. Testing Location .....	6
1.7. Specification of Accessory .....	7
1.8. Applicable Standards .....	7
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1 Descriptions of Test Mode .....	8
2.2 Test Mode .....	9
2.3 Connection Diagram of Test System .....	10
2.4 Support Unit used in test configuration and system .....	11
2.5 EUT Operation Test Setup .....	11
2.6 Measurement Results Explanation Example .....	11
<b>3 TEST RESULT .....</b>	<b>12</b>
3.1 6dB Bandwidth Measurement .....	12
3.2 Peak Output Power Measurement .....	17
3.3 Power Spectral Density Measurement .....	19
3.4 Conducted Band Edges and Spurious Emission Measurement .....	28
3.5 Radiated Band Edges and Spurious Emission Measurement .....	45
3.6 AC Conducted Emission Measurement .....	50
3.7 Antenna Requirements .....	54
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>55</b>
<b>5 UNCERTAINTY OF EVALUATION .....</b>	<b>56</b>
<b>APPENDIX A. RADIATED TEST RESULTS</b>	
<b>APPENDIX B. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5D1401B	Rev. 01	Initial issue of report	Apr. 14, 2016

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)(1)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.11 dB at 30.000 MHz for Quasi-Peak
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 4.01 dB at 0.570 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1. Applicant

**TCL Communication Ltd.**

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

## 1.2. Manufacturer

**TCL Communication Ltd.**

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

## 1.3. Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	HSUPA/HSDPA/UMTS Tri Band/GSM Quad Band/LTE 7 band mobile phone
<b>Brand Name</b>	Vodafone
<b>Model Name</b>	VFD 900
<b>FCC ID</b>	2ACCJN007
<b>EUT supports Radios application</b>	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(16QAM uplink is not supported)/LTE/NFC/ WLAN 2.4GHz 802.11b/g/n HT20/ WLAN 5GHz 802.11a/n HT20/HT40/ WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/ Bluetooth v3.0+EDR/Bluetooth v4.0 LE/Bluetooth v4.2 LE
<b>IMEI Code</b>	Conducted: 357066070004866 Conduction: 357066070004395 Radiation: 357066070005020
<b>HW Version</b>	PIO
<b>SW Version</b>	V3HT1
<b>EUT Stage</b>	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4. Product Specification subjective to this standard

Product Specification subjective to this standard	
<b>Tx/Rx Frequency Range</b>	2402 MHz ~ 2480 MHz
<b>Number of Channels</b>	40
<b>Carrier Frequency of Each Channel</b>	40 Channel(37 hopping + 3 advertising channel)
<b>Maximum Output Power to Antenna</b>	Bluetooth 4.0 LE: 1.24 dBm (0.00133 W) Bluetooth 4.2 LE: 1.30 dBm (0.00135 W)
<b>Antenna Type/Gain</b>	LDS Antenna with gain 0.30 dBi
<b>Type of Modulation</b>	Bluetooth LE : GFSK

## 1.5. Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6. Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.			
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
<b>Test Site No.</b>	<b>Sporton Site No.</b>			<b>FCC Registration No.</b>
	TH01-KS	03CH03-KS	CO01-KS	306251

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.7. Specification of Accessory

Specification of Accessory				
AC Adapter	Brand Name	N/A	Model Name	QC10US
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5.0Vdc, 2A, / 9.0Vdc, 1.67A		
	Manufacturer	BYD	P/N	CBA0060AG1C1
Battery	Brand Name	ALCATEL ONETOUCH	Model Name	TLp030F2
	Power Rating	3.84Vdc, 3000mAh		
	Manufacturer	SCUD	P/N	CAC3000013C2
USB Cable 1	Brand Name	N/A	Model Name	CDA0000043C8
	Signal Line Type	1.01m shielded without core		
	Manufacturer	PUAN	P/N	N/A
USB Cable 2	Brand Name	N/A	Model Name	CDA0000043C2 CDA0000087C2
	Signal Line Type	1.00m shielded without core		
	Manufacturer	Shenghua	P/N	N/A
Earphone	Brand Name	N/A	Model Name	WH60
	Signal Line Type	1.24m non-shielded without core		
	Manufacturer	Lianchuang	P/N	N/A

## 1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- ANSI C63.10-2013

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Bluetooth LE RF Output Power	
		Data Rate / Modulation	
		GFSK	
		v4.0	v4.2
Ch00	2402MHz	1.23 dBm	1.27 dBm
Ch39	2441MHz	<b>1.24 dBm</b>	<b>1.30 dBm</b>
Ch78	2480MHz	0.68 dBm	0.73 dBm

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration from all possible combinations.
- b. AC power line Conducted Emission was tested under maximum output power.




## 2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth 4.0 LE/ Bluetooth 4.2 LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + USB Cable 1(Charging from Adapter)
<b>Remark:</b> For Radiated Test Cases, The tests were performed with Adapter, Earphone, and USB Cable1.	

## 2.3 Connection Diagram of Test System

### <Bluetooth LE Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritus	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	LINKSYS	WRT0N	Q87WRT600NV11	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A

## 2.5 EUT Operation Test Setup

For Bluetooth LE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

*Offset = RF cable loss.*

Following shows an offset computation example with cable loss 5.4 dB.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 5.4 \text{ (dB)} \end{aligned}$$

### **3 Test Result**

#### **3.1 6dB Bandwidth Measurement**

##### **3.1.1 Limit of 6dB Bandwidth**

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### **3.1.2 Measuring Instruments**

The section 4.0 of List of Measuring Equipment of this test report is used for test.

##### **3.1.3 Test Procedures**

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

##### **3.1.4 Test Setup**




### 3.1.5 Test Result of 6dB Bandwidth

Test Mode :	Bluetooth 4.0 LE	Temperature :	24~25°C
Test Engineer :	Issac Song	Relative Humidity :	49~51%

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
00	2402	0.671	0.5	Pass
19	2440	0.673	0.5	Pass
39	2480	0.673	0.5	Pass


**6 dB Bandwidth Plot on Channel 00**



Date: 10.MAR.2016 14:21:57




### 6 dB Bandwidth Plot on Channel 19



Date: 10.MAR.2016 14:25:17

### 6 dB Bandwidth Plot on Channel 39




Date: 10.MAR.2016 14:28:15



Test Mode :	Bluetooth 4.2 LE	Temperature :	24~25°C
Test Engineer :	Issac Song	Relative Humidity :	49~51%


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
00	2402	0.669	0.5	Pass
19	2440	0.667	0.5	Pass
39	2480	0.669	0.5	Pass

**6 dB Bandwidth Plot on Channel 00**

Date: 10.MAR.2016 14:41:23




### 6 dB Bandwidth Plot on Channel 19



Date: 10.MAR.2016 14:45:23

### 6 dB Bandwidth Plot on Channel 39



Date: 10.MAR.2016 14:49:04



## **3.2 Peak Output Power Measurement**

### **3.2.1 Limit of Peak Output Power**

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### **3.2.2 Measuring Instruments**

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### **3.2.3 Test Procedures**

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r05 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### **3.2.4 Test Setup**



**3.2.5 Test Result of Peak Output Power**

<b>Test Mode :</b>	Bluetooth 4.0 LE	<b>Temperature :</b>	24~25℃
<b>Test Engineer :</b>	Issac Song	<b>Relative Humidity :</b>	49~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	1.23	30.00	Pass
19	2440	1.24	30.00	Pass
39	2480	0.68	30.00	Pass

<b>Test Mode :</b>	Bluetooth 4.2 LE	<b>Temperature :</b>	24~25℃
<b>Test Engineer :</b>	Issac Song	<b>Relative Humidity :</b>	49~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	1.27	30.00	Pass
19	2440	1.30	30.00	Pass
39	2480	0.73	30.00	Pass

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density (100kHz)


<b>Test Mode :</b>	Bluetooth 4.0 LE	<b>Temperature :</b>	24~25°C
<b>Test Engineer :</b>	Issac Song	<b>Relative Humidity :</b>	49~51%

Channel	Frequency (MHz)	Power Density 100kHz (dBm)	Max. Limits (dBm/3kHz)	Pass/Fail
00	2402	1.31	8	Pass
19	2440	1.83	8	Pass
39	2480	0.29	8	Pass

**Note:**

1. Measured power density (dBm) has offset with cable loss.
2. The Measured power density (dBm)/ 100kHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.


**PSD 100kHz Plot on Channel 00**



Date: 10. MAR.2016 14:22:51




PSD 100kHz Plot on Channel 19



Date: 10.MAR.2016 14:26:43

PSD 100kHz Plot on Channel 39



Date: 10.MAR.2016 14:28:56


<b>Test Mode :</b>	Bluetooth 4.2 LE	<b>Temperature :</b>	24~25℃
<b>Test Engineer :</b>	Issac Song	<b>Relative Humidity :</b>	49~51%

Channel	Frequency (MHz)	Power Density 100kHz (dBm)	Max. Limits (dBm/3kHz)	Pass/Fail
00	2402	1.41	8	Pass
19	2440	1.92	8	Pass
39	2480	0.38	8	Pass

**Note:**

1. Measured power density (dBm) has offset with cable loss.
2. The Measured power density (dBm)/ 100kHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.


### PSD 100kHz Plot on Channel 00



Date: 10.MAR.2016 14:42:18




PSD 100kHz Plot on Channel 19



Date: 10.MAR.2016 14:46:40

PSD 100kHz Plot on Channel 39



Date: 10.MAR.2016 14:49:54

### 3.3.6 Test Result of Power Spectral Density (3kHz)


<b>Test Mode :</b>	Bluetooth 4.0 LE	<b>Temperature :</b>	24~25℃
<b>Test Engineer :</b>	Issac Song	<b>Relative Humidity :</b>	49~51%

Channel	Frequency (MHz)	Power Density 3kHz (dBm)	Max. Limits (dBm/3kHz)	Pass/Fail
00	2402	-13.47	8	Pass
19	2440	-12.91	8	Pass
39	2480	-14.47	8	Pass

**Note:**

1. Measured power density (dBm) has offset with cable loss.
2. The Measured power density (dBm)/ 100kHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.


#### PSD 3kHz Plot on Channel 00



Date: 10. MAR. 2016 14:22:34




### PSD 3kHz Plot on Channel 19



Date: 10.MAR.2016 14:26:22

### PSD 3kHz Plot on Channel 39



Date: 10.MAR.2016 14:28:43




<b>Test Mode :</b>	Bluetooth 4.2 LE	<b>Temperature :</b>	24~25°C
<b>Test Engineer :</b>	Issac Song	<b>Relative Humidity :</b>	49~51%

Channel	Frequency (MHz)	Power Density 3kHz (dBm)	Max. Limits (dBm/3kHz)	Pass/Fail
00	2402	-13.66	8	Pass
19	2440	-13.11	8	Pass
39	2480	-14.71	8	Pass


**Note:**

1. Measured power density (dBm) has offset with cable loss.
2. The Measured power density (dBm)/ 100kHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.

**PSD 3kHz Plot on Channel 00**


Date: 10.MAR.2016 14:42:04

### PSD 3kHz Plot on Channel 19



Date: 10.MAR.2016 14:46:21

### PSD 3kHz Plot on Channel 39



Date: 10.MAR.2016 14:49:38

### **3.4 Conducted Band Edges and Spurious Emission Measurement**

#### **3.4.1 Limit of Conducted Band Edges and Spurious Emission**

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


#### **3.4.2 Measuring Instruments**

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### **3.4.3 Test Procedure**

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### **3.4.4 Test Setup**






## 3.4.5 Test Result of Conducted Band Edges

Test Mode :	Bluetooth 4.0 LE	Temperature :	24~25℃
Test Channel :	00 and 39	Relative Humidity :	49~51%
		Test Engineer :	Issac Song


Low Band Edge Plot on Channel 00



Date: 10.MAR.2016 14:23:26




High Band Edge Plot on Channel 39



Date: 10.MAR.2016 14:29:21




Test Mode :	Bluetooth 4.2 LE	Temperature :	24~25°C
Test Channel :	00 and 39	Relative Humidity :	49~51%
		Test Engineer :	Issac Song

**Low Band Edge Plot on Channel 00**

Date: 10.MAR.2016 14:43:05



High Band Edge Plot on Channel 39



Date: 10.MAR.2016 14:50:06




### 3.4.6 Test Result of Conducted Spurious Emission

Test Mode :	Bluetooth 4.0 LE	Temperature :	24~25℃
Test Channel :	00	Relative Humidity :	49~51%
		Test Engineer :	Issac Song

#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


#### GFSK Channel 00



Date: 10.MAR.2016 14:23:36



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 00




Date: 10.MAR.2016 14:23:45



Test Mode :	Bluetooth 4.0 LE	Temperature :	24~25°C
Test Channel :	19	Relative Humidity :	49~51%
		Test Engineer :	Issac Song


**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19**



Date: 10. MAR. 2016 14:26:54




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19




Date: 10.MAR.2016 14:27:02

<b>Test Mode :</b>	Bluetooth 4.0 LE	<b>Temperature :</b>	24~25℃
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	49~51%
		<b>Test Engineer :</b>	Issac Song

### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39




Date: 10.MAR.2016 14:29:43




Test Mode :	Bluetooth 4.2 LE	Temperature :	24~25°C
Test Channel :	00	Relative Humidity :	49~51%
		Test Engineer :	Issac Song

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 00**





Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 00




Date: 10.MAR.2016 14:43:25






Test Mode :	Bluetooth 4.2 LE	Temperature :	24~25°C
Test Channel :	19	Relative Humidity :	49~51%
		Test Engineer :	Issac Song

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19**





Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19




Date: 10.MAR.2016 14:46:58




Test Mode :	Bluetooth 4.2 LE	Temperature :	24~25°C
Test Channel :	39	Relative Humidity :	49~51%
		Test Engineer :	Issac Song

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39**





Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39



Date: 10.MAR.2016 14:51:18



## **3.5 Radiated Band Edges and Spurious Emission Measurement**

### **3.5.1 Limit of Radiated Band Edges and Spurious Emission**

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

<b>Frequency (MHz)</b>	<b>Field Strength (microvolts/meter)</b>	<b>Measurement Distance (meters)</b>
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### **3.5.2 Measuring Instruments**

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.


For average measurement:

  - VBW = 10 Hz, when duty cycle is no less than 98 percent.
  - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth 4.0 LE	62.50	0.39	2.56	3kHz
Bluetooth 4.2 LE	47.22	0.30	3.33	10kHz

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.





### **3.5.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix A.

### **3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix A.

### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.6.4 Test Setup





## 3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	44~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + USB Cable 1(Charging from Adapter)		




Site : CO01-KS  
Condition : FCC PART 15C LISN-L-20151024 LINE

mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	53.02	-12.85	65.87	42.40	0.51	10.11	QP
2	0.15	44.22	-11.65	55.87	33.60	0.51	10.11	Average
3	0.56	42.79	-13.21	56.00	32.40	0.23	10.16	QP
4	0.56	35.59	-10.41	46.00	25.20	0.23	10.16	Average
5	13.56	49.51	-10.49	60.00	38.90	0.26	10.35	QP
6	13.56	42.11	-7.89	50.00	31.50	0.26	10.35	Average
7	14.59	51.54	-8.46	60.00	40.90	0.26	10.38	QP
8 *	14.59	43.24	-6.76	50.00	32.60	0.26	10.38	Average
9	15.23	51.45	-8.55	60.00	40.80	0.26	10.39	QP
10	15.23	42.15	-7.85	50.00	31.50	0.26	10.39	Average
11	24.27	48.39	-11.61	60.00	37.50	0.23	10.66	QP
12	24.27	35.39	-14.61	50.00	24.50	0.23	10.66	Average
13	25.32	50.42	-9.58	60.00	39.50	0.22	10.70	QP
14	25.32	37.32	-12.68	50.00	26.40	0.22	10.70	Average
15	26.42	52.36	-7.64	60.00	41.40	0.22	10.74	QP
16	26.42	39.36	-10.64	50.00	28.40	0.22	10.74	Average
17	27.42	50.50	-9.50	60.00	39.51	0.22	10.77	QP
18	27.42	38.40	-11.60	50.00	27.41	0.22	10.77	Average



Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	44~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + USB Cable 1(Charging from Adapter)		



Site : CO01-KS  
Condition : FCC PART 15C LISN-N-20151024 NEUTRAL

mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.54	46.29	-9.71	56.00	35.81	0.32	10.16	QP
2	0.54	40.39	-5.61	46.00	29.91	0.32	10.16	Average
3	0.57	47.09	-8.91	56.00	36.60	0.33	10.16	QP
4 *	0.57	41.99	-4.01	46.00	31.50	0.33	10.16	Average
5	0.62	41.69	-14.31	56.00	31.20	0.33	10.16	QP
6	0.62	40.09	-5.91	46.00	29.60	0.33	10.16	Average
7	14.06	43.24	-16.76	60.00	32.61	0.27	10.36	QP
8	14.06	34.44	-15.56	50.00	23.81	0.27	10.36	Average
9	14.67	43.05	-16.95	60.00	32.40	0.27	10.38	QP
10	14.67	34.25	-15.75	50.00	23.60	0.27	10.38	Average
11	20.70	43.31	-16.69	60.00	32.50	0.25	10.56	QP
12	20.70	31.71	-18.29	50.00	20.90	0.25	10.56	Average
13	23.51	47.68	-12.32	60.00	36.80	0.24	10.64	QP
14	23.51	34.58	-15.42	50.00	23.70	0.24	10.64	Average
15	25.05	51.73	-8.27	60.00	40.80	0.24	10.69	QP
16	25.05	39.53	-10.47	50.00	28.60	0.24	10.69	Average
17	26.28	54.47	-5.53	60.00	43.50	0.24	10.73	QP
18	26.28	41.87	-8.13	50.00	30.90	0.24	10.73	Average
19	28.00	50.83	-9.17	60.00	39.80	0.24	10.79	QP
20	28.00	38.63	-11.37	50.00	27.60	0.24	10.79	Average



### **3.7 Antenna Requirements**

#### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

#### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

#### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	10Hz~30GHz	May 04, 2015	Mar. 10, 2016	May 03, 2016	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 20, 2016	Mar. 10, 2016	Jan. 19, 2017	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 20, 2016	Mar. 10, 2016	Jan. 19, 2017	Conducted (TH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 04, 2015	Mar. 14, 2016	May 03, 2016	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 24, 2015	Mar. 14, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 24, 2015	Mar. 14, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000811	AC 0V~300V, 45Hz~1000Hz	Oct. 24, 2015	Mar. 14, 2016	Oct. 23, 2016	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Sep. 10, 2015	Mar. 23, 2016	Sep. 09, 2016	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Jun. 05, 2015	Mar. 23, 2016	Jun. 04, 2016	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 10, 2015	Mar. 23, 2016	Nov. 09, 2016	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	25MHz~2GHz	Mar. 12, 2016	Mar. 23, 2016	Mar. 11, 2017	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Jun. 25, 2015	Mar. 23, 2016	Jun. 24, 2016	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101070	18GHz~40GHz	Oct. 10, 2015	Mar. 23, 2016	Oct. 09, 2016	Radiation (03CH03-KS)
Amplifier	Burgeon	BPA-530	102212	0.01MHz~3000MHz	Aug. 10, 2015	Mar. 23, 2016	Aug. 09, 2016	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 24, 2015	Mar. 23, 2016	Oct. 23, 2016	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Mar. 23, 2016	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Mar. 23, 2016	NCR	Radiation (03CH03-KS)

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3 dB
--	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.5 dB
--	--------





## Appendix A. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

BLE v4.0 (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
BLE CH 00 2402MHz		2363.01	48.68	-25.32	74	53.25	26.91	5.54	37.02	100	156	P	H
		2376.51	39.99	-14.01	54	44.49	26.95	5.57	37.02	100	156	A	H
	*	2402.087	96.09	-	-	100.52	27	5.59	37.02	100	156	P	H
	*	2402.087	95.52	-	-	99.95	27	5.59	37.02	100	156	A	H
		2386.68	49.44	-24.56	74	53.87	27	5.59	37.02	312	67	P	V
		2387.67	40.02	-13.98	54	44.45	27	5.59	37.02	312	67	A	V
	*	2402.087	94.58	-	-	99.01	27	5.59	37.02	312	67	P	V
	*	2402.087	93.95	-	-	98.38	27	5.59	37.02	312	67	A	V
BLE CH 19 2440MHz	*	2440.247	96.35	-	-	100.28	27.39	5.65	36.97	100	157	P	H
	*	2439.997	95.81	-	-	99.74	27.39	5.65	36.97	100	157	A	H
	*	2440.331	94.86	-	-	98.79	27.39	5.65	36.97	282	95	P	V
	*	2440.08	94.23	-	-	98.16	27.39	5.65	36.97	282	95	A	V
BLE CH 39 2480MHz	*	2480.076	95.74	-	-	99.35	27.64	5.69	36.94	206	29	P	H
	*	2480.076	95.19	-	-	98.8	27.64	5.69	36.94	206	29	A	H
		2488.84	50.3	-23.7	74	53.75	27.77	5.71	36.93	206	29	P	H
		2491.24	40.65	-13.35	54	44.1	27.77	5.71	36.93	206	29	A	H
	*	2480.076	92.87	-	-	96.48	27.64	5.69	36.94	219	100	P	V
	*	2480.076	92.29	-	-	95.9	27.64	5.69	36.94	219	100	A	V
		2489.52	49.41	-24.59	74	52.86	27.77	5.71	36.93	219	100	P	V
		2485.6	40.67	-13.33	54	44.28	27.64	5.69	36.94	219	100	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 15C 2.4GHz 2400~2483.5MHz

## BLE v4.0 (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		4803	37.58	-36.42	74	59.12	31.48	9.1	62.12	100	360	P	H
		4803	37.3	-36.7	74	58.84	31.48	9.1	62.12	100	0	P	V
BLE CH 19 2440MHz		4881	37.01	-36.99	74	58.25	31.59	9.2	62.03	100	360	P	H
		7320	40.17	-33.83	74	53.94	34.08	11.3	59.15	100	0	P	H
		4881	39.16	-34.84	74	60.4	31.59	9.2	62.03	100	0	P	V
		7320	40.6	-33.4	74	54.37	34.08	11.3	59.15	100	360	P	V
BLE CH 39 2480MHz		4959	38.25	-35.75	74	59.13	31.72	9.32	61.92	100	360	P	H
		7440	40.76	-33.24	74	54.32	34.44	11.3	59.3	100	0	P	H
		4959	37.28	-36.72	74	58.16	31.72	9.32	61.92	100	0	P	V
		7440	40.62	-33.38	74	54.18	34.44	11.3	59.3	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 15C Emission below 1GHz

## 2.4GHz BLE v4.0 (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
2.4GHz BLE LF		30.97	30.33	-9.67	40	42.27	18.46	0.66	31.06	100	216	P	H
		76.56	19.92	-20.08	40	40.18	9.17	1.07	30.5	-	-	P	H
		159.98	22.11	-21.39	43.5	37.79	13.19	1.53	30.4	-	-	P	H
		323.91	19.49	-26.51	46	32.5	15.33	2.21	30.55	-	-	P	H
		617.82	18.48	-27.52	46	27.59	18.01	3.12	30.24	-	-	P	H
		750.71	21.39	-24.61	46	27.6	20.82	3.47	30.5	-	-	P	H
	!	30	36.75	-3.25	40	48.6	18.6	0.65	31.1	100	32	QP	V
	!	79.47	36.1	-3.9	40	56.25	9.27	1.08	30.5	-	-	P	V
		100.81	23.23	-20.27	43.5	39.3	13.11	1.22	30.4	-	-	P	V
		288.02	23.01	-22.99	46	36.97	14.5	2.04	30.5	-	-	P	V
		323.91	24.92	-21.08	46	37.93	15.33	2.21	30.55	-	-	P	V
		550.89	19.65	-26.35	46	28.45	18.57	2.93	30.3	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



## 15C 2.4GHz 2400~2483.5MHz

## BLE v4.2 (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
BLE CH 00 2402MHz		2389.02	49.08	-24.92	74	53.51	27	5.59	37.02	120	31	P	H
		2386.95	42.67	-11.33	54	47.1	27	5.59	37.02	120	31	A	H
	*	2402.171	95.98	-	-	100.41	27	5.59	37.02	120	31	P	H
	*	2402.087	95.88	-	-	100.31	27	5.59	37.02	120	31	A	H
		2344.92	50.75	-23.25	74	55.38	26.86	5.52	37.01	381	46	P	V
		2349.24	42.81	-11.19	54	47.44	26.86	5.52	37.01	381	46	A	V
	*	2402.004	97.02	-	-	101.45	27	5.59	37.02	381	46	P	V
	*	2402.087	96.76	-	-	101.19	27	5.59	37.02	381	46	A	V
BLE CH 19 2440MHz	*	2440.08	94.36	-	-	98.29	27.39	5.65	36.97	100	30	P	H
	*	2439.997	93.93	-	-	97.86	27.39	5.65	36.97	100	30	A	H
	*	2440.08	95.88	-	-	99.81	27.39	5.65	36.97	400	53	P	V
	*	2440.08	95.47	-	-	99.4	27.39	5.65	36.97	400	53	A	V
BLE CH 39 2480MHz	*	2480.076	94.4	-	-	98.01	27.64	5.69	36.94	300	299	P	H
	*	2480.076	93.86	-	-	97.47	27.64	5.69	36.94	300	299	A	H
		2489	50.23	-23.77	74	53.68	27.77	5.71	36.93	300	299	P	H
		2487.08	42.35	-11.65	54	45.96	27.64	5.69	36.94	300	299	A	H
	*	2480.076	94.83	-	-	98.44	27.64	5.69	36.94	396	57	P	V
	*	2480.076	94.39	-	-	98	27.64	5.69	36.94	396	57	A	V
		2485.04	49.73	-24.27	74	53.34	27.64	5.69	36.94	396	57	P	V
		2484.16	43.49	-10.51	54	47.1	27.64	5.69	36.94	396	57	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



## 15C 2.4GHz 2400~2483.5MHz

## BLE v4.2 (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		4803	35.61	-38.39	74	57.15	31.48	9.1	62.12	100	360	P	H
		4803	36.41	-37.59	74	57.95	31.48	9.1	62.12	100	0	P	V
BLE CH 19 2440MHz		4881	37.31	-36.69	74	58.55	31.59	9.2	62.03	100	360	P	H
		7320	40.62	-33.38	74	54.39	34.08	11.3	59.15	100	0	P	H
		4881	36.12	-37.88	74	57.36	31.59	9.2	62.03	100	0	P	V
		7320	39.8	-34.2	74	53.57	34.08	11.3	59.15	100	360	P	V
BLE CH 39 2480MHz		4959	36.77	-37.23	74	57.65	31.72	9.32	61.92	100	360	P	H
		7440	40.41	-33.59	74	53.97	34.44	11.3	59.3	100	0	P	H
		4959	36.83	-37.17	74	57.71	31.72	9.32	61.92	100	0	P	V
		7440	40.42	-33.58	74	53.98	34.44	11.3	59.3	100	360	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												


**15C Emission below 1GHz**
**2.4GHz BLE v4.2 (LF)**

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
2.4GHz BLE LF		31.94	30.39	-9.61	40	42.41	18.32	0.68	31.02	100	21	P	H
		76.56	20.85	-19.15	40	41.11	9.17	1.07	30.5	-	-	P	H
		159.98	22.65	-20.85	43.5	38.33	13.19	1.53	30.4	-	-	P	H
		323.91	18.78	-27.22	46	31.79	15.33	2.21	30.55	-	-	P	H
		665.35	20.95	-25.05	46	28.25	19.78	3.25	30.33	-	-	P	H
		835.1	23.85	-22.15	46	28.48	22.12	3.68	30.43	-	-	P	H
	!	30	36.89	-3.11	40	48.74	18.6	0.65	31.1	100	25	QP	V
	!	79.47	35.29	-4.71	40	55.44	9.27	1.08	30.5	-	-	P	V
		100.81	23.23	-20.27	43.5	39.3	13.11	1.22	30.4	-	-	P	V
		323.91	25.26	-20.74	46	38.27	15.33	2.21	30.55	-	-	P	V
		670.2	21.24	-24.76	46	28.46	19.86	3.26	30.34	-	-	P	V
		921.43	23.1	-22.9	46	26.61	23.15	3.9	30.56	-	-	P	V
Remark	3. No other spurious found. 4. All results are PASS against limit line.												

**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**