

FCC PART 15C TEST REPORT

No. I16Z40479-SRD02

for

TCL Communication Ltd.

HSUPA/HSDPA/UMTS 5 band /GSM quad band mobile phone

Model Name: 5010S

FCC ID: 2ACCJH052

with

Hardware Version: PIO

Software Version: v5E53

Issued Date: 2016-04-15



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email: cttl_terminals@catr.cn, website: www.chinattl.com



REPORT HISTORY

Report Number	Revision	Description	Issue Date
I16Z40479-SRD02	Rev.0	1st edition	2016-04-15



CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.1. TESTING ENVIRONMENT	5
1.2. PROJECT DATA	
1.3. SIGNATURE	
2.1. APPLICANT INFORMATION	
2.2. MANUFACTURER INFORMATION	6
3. EQUIPMENT UNDERTEST (EUT) AND ANCILLARY EQUIPMENT (AE)	7
3.1. ABOUT EUT	7
3.2. INTERNAL IDENTIFICATION OF EUT	7
3.3. INTERNAL IDENTIFICATION OF AE	7
3.4. Normal Accessory setting	
3.5. GENERAL DESCRIPTION	
4. REFERENCE DOCUMENTS	
4.1. DOCUMENTS SUPPLIED BY APPLICANT	
4.2. REFERENCE DOCUMENTS FOR TESTING	
5. TEST RESULTS	9
5.1. SUMMARY OF TEST RESULTS	9
5.2. Statements	9
6. TEST FACILITIES UTILIZED	10
ANNEX A: DETAILED TEST RESULTS	11
A.1. MEASUREMENT METHOD	11
A.2. PEAK OUTPUT POWER – CONDUCTED	12
A.3. FREQUENCY BAND EDGES – CONDUCTED	13
A.4. CONDUCTED EMISSION	20
A.5. RADIATED EMISSION	45
A.6. TIME OF OCCUPANCY (DWELL TIME)	64
A.7. 20dB Bandwidth	74
A.8. CARRIER FREQUENCY SEPARATION	80
A.9. Number of Hopping Channels	83
A.10. AC POWERLINE CONDUCTED EMISSION	87
ANNEY R. ACCDEDITATION CERTIFICATE	90



1. Test Laboratory

1.1. Testing Location

Location 1:CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,

P. R. China100191

Location 2:CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,

Haidian District, Beijing, P. R. China100191



1.1. Testing Environment

Normal Temperature: $15-35^{\circ}$ C Extreme Temperature: $-10/+55^{\circ}$ C Relative Humidity: 20-75%

1.2. Project data

Testing Start Date: 2016-02-29
Testing End Date: 2016-03-15

1.3. Signature

的震争

Sun Zhenyu (Prepared this test report)

黎鲜

Li Zhuofang (Reviewed this test report)

13 diay

Lv Songdong (Approvedthis test report)



2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.

Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,

Pudong Area Shanghai, P.R. China. 201203

City: Shanghai Postal Code: 201203 Country: China

Contact Person: Gong Zhizhou

 Contact Email
 zhizhou.gong@tcl.com

 Telephone:
 0086-21-31363544

 Fax:
 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.

Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,

Pudong Area Shanghai, P.R. China. 201203

City: Shanghai Postal Code: 201203 Country: China

Telephone: 0086-21-31363544 Fax: 0086-21-61460602



3. Equipment UnderTest (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description HSUPA/HSDPA/UMTS 5 band /GSM quad band mobile phone

Model Name 5010S

FCC ID 2ACCJH052

Frequency Band ISM 2400MHz~2483.5MHz Type of Modulation GFSK/π/4 DQPSK/8DPSK

Number of Channels 79

Power Supply 0 DC by Battery

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	/	PIO	v5E53
EUT2	/	PIO	v5E53

^{*}EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE1

AE ID*	Description		
AE1	Battery	/	Inbuilt

Model CAB2000041C7(711700096011)

Manufacturer Veken

Capacitance 2000 mAh

3.4. Normal Accessory setting

Fully charged battery should be used during the test.

3.5. General Description

The Equipment Under Test (EUT) is a model of HSUPA/HSDPA/UMTS 5 band /GSM quad band mobile phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfil the test.

^{*}AE ID: is used to identify the test sample in the lab internally.



4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
	FCC CFR 47, Part 15, Subpart C:	
	15.205 Restricted bands of operation;	2015
FCC Part15	2015	
	15.247 Operation within the bands 902–928MHz,	
	2400-2483.5 MHz, and 5725-5850 MHz.	
ANSI C63.10	American National Standard for Testing Unlicensed	June,2013
ANSI C03.10	Wireless Devices	June,2013



5. Test Results

5.1. Summary of Test Results

Abbreviations used in this clause:

- **P** Pass, The EUT complies with the essential requirements in the standard.
- **F** Fail, The EUT does not comply with the essential requirements in the standard
- NA Not Applicable, The test was not applicable
- NP Not Performed, The test was not performed by CTTL

SUMMARY OF MEASUREMENT RESULTS	Sub-clause	Verdict
Peak Output Power - Conducted	15.247 (b)(1)	Р
Frequency Band Edges	15.247 (d)	Р
Conducted Emission	15.247 (d)	Р
Radiated Emission	15.247, 15.205, 15.209	Р
Time of Occupancy (Dwell Time)	15.247 (a) (1)(iii)	Р
20dB Bandwidth	15.247 (a)(1)	NA
Carrier Frequency Separation	15.247 (a)(1)	Р
Number of hopping channels	15.247 (a)(b)(iii)	Р
AC Powerline Conducted Emission	15.107, 15.207	Р

Please refer to ANNEX A for detail.

The measurement is made according to ANSI C63.10.

5.2. Statements

CTTL has evaluated the test cases requested by the applicant /manufacturer as listed in section 5.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

This model is a variant product which model name is 5010G; all the test result has been derived from test report of 5010G.



6. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ26	200136	Rohde & Schwarz	1 year	2017-01-06
2	Bluetooth Tester	CBT32	100649	Rohde & Schwarz	1 year	2017-02-09
3	Shielding Room	S81	/	ETS-Lindgren	/	/
4	LISN	ENV216	101200	Rohde & Schwarz	1 year	2016-07-07
5	Test Receiver	ESCI	100344	Rohde & Schwarz	1 year	2017-03-03

Radiated emission test system

ita	Radiated emission test system					
No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESCI 7	100948	Rohde & Schwarz	1 year	2016-07-16
2	Loop antenna	HFH2-Z2	829324/00 7	Rohde & Schwarz	3 years	2017-12-16
3	BiLog Antenna	VULB9163	234	Schwarzbeck	3 years	2016-09-15
4	Dual-Ridge Waveguide Horn Antenna	3115	6914	EMCO	3 years	2017-12-15
5	Dual-Ridge Waveguide Horn Antenna	3116	2661	ETS-Lindgren	3 years	2017-06-30
6	Vector Signal Analyzer	FSV	101047	Rohde & Schwarz	1 year	2016-07-03
7	Semi-anechoic chamber	/	CT000332 -1074	Frankonia German	/	/
8	Bluetooth Tester	CBT	100153	Rohde & Schwarz	1 year	2016-09-18




ANNEX A: Detailed Test Results

A.1. Measurement Method

A.1.1. Conducted Measurements

The measurement is made according to ANSI C63.10.

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).
- 3). Set the EUT to the required channel.
- 4). Set the EUT hopping mode (hopping or hopping off).
- 5). Set the spectrum analyzer to start measurement.
- 6). Record the values. Vector Signal Analyzer



A.1.2. Radiated Emission Measurements


The measurement is made according to ANSI C63.10

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 1MHz;





A.2. Peak Output Power - Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.5

a) Use the following spectrum analyzer settings:

Span: 6MHzRBW: 3MHzVBW: 3MHz

Sweep time: 2.5msDetector function: peak

• Trace: max hold

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power.

Measurement Limit:

Standard	Limit (dBm)
FCC Part 15.247(b)(1)	< 30

Measurement Results:

For GFSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted				
Output Power	4.42	5.41	4.73	Р
(dBm)				

Forπ/4 DQPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted				
Output Power	3.93	4.56	4.27	Р
(dBm)				

For 8DPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted				
Output Power	4.39	5.05	4.79	Р
(dBm)				

Conclusion: PASS



A.3. Frequency Band Edges – Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.6

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).

- Span: 10 MHz

Resolution Bandwidth: 100 kHzVideo Bandwidth: 300 kHz

Sweep Time: 5msDetector: PeakTrace: max hold

Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.

Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	< -20

Measurement Result:

For GFSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.1	-57.64	Р
U	Hopping ON	Fig.2	-58.11	Р
70	Hopping OFF	Fig.3	-65.66	Р
78	Hopping ON	Fig.4	-66.72	Р

Forπ/4 DQPSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.5	-54.11	Р
0	Hopping ON	Fig.6	-55.66	Р
70	Hopping OFF	Fig.7	-64.26	Р
78	Hopping ON	Fig.8	-63.94	Р


For 8DPSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.9	-52.34	Р
U	Hopping ON	Fig.10	-54.33	Р




78	Hopping OFF	Fig.11	-59.97	Р
70	Hopping ON	Fig.12	-61.90	Р

Conclusion: PASS
Test graphs as below



Date: 5.MAR.2016 16:04:01


Fig.1. Frequency Band Edges: GFSK, Channel 0, Hopping Off



Date: 5.MAR.2016 16:06:21


Fig.2. Frequency Band Edges: GFSK, Channel 0, Hopping On





Date: 5.MAR.2016 16:04:19


Fig.3. Frequency Band Edges: GFSK, Channel 78, Hopping Off



Date: 5.MAR.2016 16:08:23


Fig.4. Frequency Band Edges: GFSK, Channel 78, Hopping On





Date: 5.MAR.2016 16:29:58


Fig.5. Frequency Band Edges: π/4 DQPSK, Channel 0, Hopping Off



Date: 5.MAR.2016 16:32:17


Fig.6. Frequency Band Edges: π/4 DQPSK, Channel 0, Hopping On





Date: 5.MAR.2016 16:30:15


Fig.7. Frequency Band Edges: $\pi/4$ DQPSK, Channel 78, Hopping Off



Date: 5.MAR.2016 16:34:20


Fig.8. Frequency Band Edges: $\pi/4$ DQPSK, Channel 78, Hopping On





Date: 5.MAR.2016 16:51:55


Fig.9. Frequency Band Edges: 8DPSK, Channel 0, Hopping Off



Date: 5.MAR.2016 16:54:14


Fig.10. Frequency Band Edges: 8DPSK, Channel 0, Hopping On





Date: 5.MAR.2016 16:52:12

Fig.11. Frequency Band Edges: 8DPSK, Channel 78, Hopping Off



Date: 5.MAR.2016 16:56:16

Fig.12. Frequency Band Edges: 8DPSK, Channel 78, Hopping On



A.4. Conducted Emission

Method of Measurement: See ANSI C63.10-clause 7.8.8

Measurement Procedure - Reference Level

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW = 300 kHz.
- 3. Set the span to 5-30 % greater than the EBW.
- 4. Detector = peak.
- 5. Sweep time = auto couple.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.
- 8. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

Measurement Procedure - Unwanted Emissions

- 1. Set RBW = 100 kHz.
- 2. Set VBW = 300 kHz.
- 3. Set span to encompass the spectrum to be examined.
- 4. Detector = peak.
- 5. Trace Mode = max hold.
- 6. Sweep = auto couple.
- 7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz
	bandwidth

Measurement Results:

For GFSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0	Center Frequency	Fig.13	Р



2402 MHz	30 MHz ~ 1 GHz	Fig.14	Р
	1 GHz ~ 3 GHz	Fig.15	Р
	3 GHz ~ 10 GHz	Fig.16	Р
	10 GHz ~ 26 GHz	Fig.17	Р
	Center Frequency	Fig.18	Р
Ch 20	30 MHz ~ 1 GHz	Fig.19	Р
Ch 39 2441 MHz	1 GHz ~ 3 GHz	Fig.20	Р
	3 GHz ~ 10 GHz	Fig.21	Р
	10 GHz ~ 26 GHz	Fig.22	Р
	Center Frequency	Fig.23	Р
Oh 70	30 MHz ~ 1 GHz	Fig.24	Р
Ch 78 2480 MHz	1 GHz ~ 3 GHz	Fig.25	Р
	3 GHz ~ 10 GHz	Fig.26	Р
	10 GHz ~ 26 GHz	Fig.27	Р

For π/4 DQPSK

Channel	Frequency Range	Test Results	Conclusion
	Center Frequency	Fig.28	Р
Ch O	30 MHz ~ 1 GHz	Fig.29	Р
Ch 0 2402 MHz	1 GHz ~ 3 GHz	Fig.30	Р
2.022	3 GHz ~ 10 GHz	Fig.31	Р
	10 GHz ~ 26 GHz	Fig.32	Р
	Center Frequency	Fig.33	Р
Oh 20	30 MHz ~ 1 GHz	Fig.34	Р
Ch 39 2441 MHz	1 GHz ~ 3 GHz	Fig.35	Р
	3 GHz ~ 10 GHz	Fig.36	Р
	10 GHz ~ 26 GHz	Fig.37	Р
	Center Frequency	Fig.38	Р
Ch 70	30 MHz ~ 1 GHz	Fig.39	Р
Ch 78 2480 MHz	1 GHz ~ 3 GHz	Fig.40	Р
2 100 1111 12	3 GHz ~ 10 GHz	Fig.41	Р
	10 GHz ~ 26 GHz	Fig.42	Р

For 8DPSK

Channel	Frequency Range	Test Results	Conclusion
	Center Frequency	Fig.43	Р
Ch O	30 MHz ~ 1 GHz	Fig.44	Р
Ch 0 2402 MHz	1 GHz ~ 3 GHz	Fig.45	Р
2402 IVII 12	3 GHz ~ 10 GHz	Fig.46	Р
	10 GHz ~ 26 GHz	Fig.47	Р



01.00	Center Frequency	Fig.48	Р
	30 MHz ~ 1 GHz	Fig.49	Р
Ch 39 2441 MHz	1 GHz ~ 3 GHz	Fig.50	Р
	3 GHz ~ 10 GHz	Fig.51	Р
	10 GHz ~ 26 GHz	Fig.52	Р
	Center Frequency	Fig.53	Р
Ch 70	30 MHz ~ 1 GHz	Fig.54	Р
Ch 78 2480 MHz	1 GHz ~ 3 GHz	Fig.55	Р
	3 GHz ~ 10 GHz	Fig.56	Р
	10 GHz ~ 26 GHz	Fig.57	Р

Conclusion: PASS
Test graphs as below

Date: 5.MAR.2016 16:09:03




Fig.13. Conducted spurious emission: GFSK, Channel 0,2402MHz






Fig.14. Conducted spurious emission: GFSK, Channel 0, 30MHz - 1GHz






Fig.15. Conducted spurious emission: GFSK, Channel 0, 1GHz - 3GHz





Date: 5.MAR.2016 16:10:06

Fig.16. Conducted spurious emission: GFSK, Channel 0, 3GHz - 10GHz



Date: 5.MAR.2016 16:10:22

Fig.17. Conducted spurious emission: GFSK, Channel 0,10GHz - 26GHz






Fig.18. Conducted spurious emission: GFSK, Channel 39, 2441MHz





Fig.19. Conducted spurious emission: GFSK, Channel 39, 30MHz - 1GHz


Date: 5.MAR.2016 16:10:54





Date: 5.MAR.2016 16:11:25


Fig.20. Conducted spurious emission: GFSK, Channel 39, 1GHz – 3GHz



Date: 5.MAR.2016 16:11:41

Fig.21. Conducted spurious emission: GFSK, Channel 39, 3GHz – 10GHz





Date: 5.MAR.2016 16:11:57

Date: 5.MAR.2016 16:12:14

Fig.22. Conducted spurious emission: GFSK, Channel 39, 10GHz – 26GHz






Fig.23. Conducted spurious emission: GFSK, Channel 78, 2480MHz





Date: 5.MAR.2016 16:12:30


Fig.24. Conducted spurious emission: GFSK, Channel 78, 30MHz - 1GHz



Date: 5.MAR.2016 16:13:01


Fig.25. Conducted spurious emission: GFSK, Channel 78, 1GHz - 3GHz





Date: 5.MAR.2016 16:13:17


Fig.26. Conducted spurious emission: GFSK, Channel 78, 3GHz - 10GHz



Date: 5.MAR.2016 16:13:33


Fig.27. Conducted spurious emission: GFSK, Channel 78, 10GHz - 26GHz





Date: 5.MAR.2016 16:34:39


Fig.28. Conducted spurious emission: π/4 DQPSK, Channel 0,2402MHz



Date: 5.MAR.2016 16:34:56


Fig.29. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 30MHz - 1GHz





Date: 5.MAR.2016 16:35:27


Fig.30. Conducted spurious emission: π/4 DQPSK, Channel 0, 1GHz - 3GHz



Date: 5.MAR.2016 16:35:44

Fig.31. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 3GHz - 10GHz





Date: 5.MAR.2016 16:36:00

Date: 5.MAR.2016 16:36:17

Fig.32. Conducted spurious emission: π/4 DQPSK, Channel 0,10GHz - 26GHz






Fig.33. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 2441MHz





Date: 5.MAR.2016 16:36:34


Fig.34. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 30MHz - 1GHz



Date: 5.MAR.2016 16:37:05


Fig.35. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 1GHz - 3GHz





Date: 5.MAR.2016 16:37:22


Fig.36. Conducted spurious emission: π/4 DQPSK, Channel 39, 3GHz - 10GHz



Date: 5.MAR.2016 16:37:38


Fig.37. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 10GHz - 26GHz





Date: 5.MAR.2016 16:37:55


Fig.38. Conducted spurious emission: π/4 DQPSK, Channel 78, 2480MHz



Date: 5.MAR.2016 16:38:11

Fig.39. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 30MHz - 1GHz





Date: 5.MAR.2016 16:38:43

Date: 5.MAR.2016 16:39:00

Fig.40. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 1GHz - 3GHz






Fig.41. Conducted spurious emission: π/4 DQPSK, Channel 78, 3GHz - 10GHz





Date: 5.MAR.2016 16:39:16

Fig.42. Conducted spurious emission: π/4 DQPSK, Channel 78, 10GHz - 26GHz



Date: 5.MAR.2016 16:56:36

Fig.43. Conducted spurious emission: 8DPSK, Channel 0,2402MHz






Fig.44. Conducted spurious emission: 8DPSK, Channel 0, 30MHz - 1GHz

Date: 5.MAR.2016 16:56:52






Fig.45. Conducted spurious emission: 8DPSK, Channel 0, 1GHz - 3GHz





Date: 5.MAR.2016 16:57:40


Fig.46. Conducted spurious emission: 8DPSK, Channel 0, 3GHz - 10GHz



Date: 5.MAR.2016 16:57:57

Fig.47. Conducted spurious emission: 8DPSK, Channel 0,10GHz - 26GHz





Date: 5.MAR.2016 16:58:14

Date: 5.MAR.2016 16:58:30

Fig.48. Conducted spurious emission: 8DPSK, Channel 39, 2441MHz






Fig.49. Conducted spurious emission: 8DPSK, Channel 39, 30MHz - 1GHz





Date: 5.MAR.2016 16:59:02


Fig.50. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz



Date: 5.MAR.2016 16:59:18


Fig.51. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz





Date: 5.MAR.2016 16:59:35


Fig.52. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz



Date: 5.MAR.2016 16:59:52

Fig.53. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz





Date: 5.MAR.2016 17:00:08

Fig.54. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz





Fig.55. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz





Date: 5.MAR.2016 17:00:56

Date: 5.MAR.2016 17:01:13

Fig.56. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz




Fig.57. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz



A.5. Radiated Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

The measurement is made according to ANSI C63.10

Limit in restricted band:

Frequency of emission	Field strength(uV/m)	Field strength(dBuV/m)
(MHz)		
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission	RBW/VBW	Sweep Time(s)
(MHz)		
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

Measurement Results:

Result=P_{Mea}+ARPL

For GFSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0	1 GHz ~ 3 GHz	Fig.58	Р
2402 MHz	3 GHz ~ 18 GHz	Fig.59	Р
	9 kHz ~ 30 MHz	Fig.60	Р
Ch 39	30 MHz ~ 1 GHz	Fig.61	Р
2441 MHz	1 GHz ~ 3 GHz	Fig.62	Р
	3 GHz ~ 18 GHz	Fig.63	Р
Ch 78	1 GHz ~ 3 GHz	Fig.64	Р
2480 MHz	3 GHz ~ 18 GHz	Fig.65	Р
Power	2.38GHz~2.4GHzL	Fig.66	Р



Power	2.45GHz~2.5GHzH	Fig.67	Р
For all channels	18 GHz ~ 26 GHz	Fig.68	Р

Forπ/4 DQPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0	1 GHz ~ 3 GHz	Fig.69	Р
2402 MHz	3 GHz ~ 18 GHz	Fig.70	Р
Ch 20	30 MHz ~ 1 GHz	Fig.71	Р
Ch 39 2441 MHz	1 GHz ~ 3 GHz	Fig.72	Р
2441 1011 12	3 GHz ~ 18 GHz	Fig.73	Р
Ch 78	1 GHz ~ 3 GHz	Fig.74	Р
2480 MHz	3 GHz ~ 18 GHz	Fig.75	Р
Power	2.38GHz~2.4GHzL	Fig.76	Р
Power	2.45GHz~2.5GHzH	Fig.77	Р
For all channels	18 GHz ~ 26 GHz	Fig.78	Р

For 8DPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0	1 GHz ~ 3 GHz	Fig.79	Р
2402 MHz	3 GHz ~ 18 GHz	Fig.80	Р
Ch 20	30 MHz ~ 1 GHz	Fig.81	Р
Ch 39 2441 MHz	1 GHz ~ 3 GHz	Fig.82	Р
2441 1011 12	3 GHz ~ 18 GHz	Fig.83	Р
Ch 78	1 GHz ~ 3 GHz	Fig.84	Р
2480 MHz	3 GHz ~ 18 GHz	Fig.85	Р
Power	2.38GHz~2.4GHzL	Fig.86	Р
Power	2.45GHz~2.5GHzH	Fig.87	Р
For all channels	18 GHz ~ 26 GHz	Fig.88	Р

GFSK Ch 0 - Average

	Frequency(MHz)	Result(dBuv/m)	ARPL (dB)	PMea(dBuv/m)	Polarization
	2385.605	58.1	-11.1	69.2	Н
	17906.500	62.8	27.1	35.7	Н
	17957.500	62.7	27.9	34.8	V
	17731.000	62.4	26.7	35.7	Н
	17894.500	62.4	27.1	35.3	Н
Ī	17964.000	62.4	27.9	34.5	Н

GFSK Ch 39 - Average

<u> </u>				
Frequency(MHz)	Result(dBuv/m)	ARPL (dB)	Pmea(dBuv/m)	Polarization
17921.000	62.1	27.9	34.2	Н
17892.500	62.0	27.1	34.9	Н
17943.000	61.7	27.9	33.8	V
17860.000	61.6	27.1	34.5	Н
17975.500	61.5	27.9	33.6	Н

©Copyright. All rights reserved by CTTL.



	17884.000	61.3	27.1	34.2	Н
--	-----------	------	------	------	---

GFSK Ch 78 - Average

Frequency(MHz)	Result(dBuv/m)	ARPL (dB)	Pmea(dBuv/m)	Polarization
2488.545	58.8	-11.2	70.0	Н
17716.500	62.1	26.7	35.4	Н
17933.500	62.0	27.9	34.1	V
17997.500	61.8	27.9	33.9	H
17989.500	61.7	27.9	33.8	Н
17966.000	61.6	27.9	33.7	Н

$\pi/4$ DQPSK Ch 0 - Average

Frequency(MHz)	Result(dBuv/m)	ARPL (dB)	Pmea(dBuv/m)	Polarization
2389.390	57.9	-11.1	69.0	Н
17794.000	62.3	27.1	35.2	Н
17901.500	62.0	27.1	34.9	V
17875.000	61.7	27.1	34.6	Н
17822.500	61.6	27.1	34.5	Н
17972.000	61.5	27.9	33.6	Н

$\pi/4$ DQPSK Ch 39 - Average

Frequency(MHz)	Result(dBuv/m)	ARPL (dB)	Pmea(dBuv/m)	Polarization
17931.000	62.0	27.9	34.1	Н
17974.500	62.0	27.9	34.1	Н
17935.000	61.8	27.9	33.9	V
17740.500	61.6	27.1	34.5	Н
17743.000	61.6	27.1	34.5	Н
17709.000	61.5	26.7	34.8	Н

$\pi/4$ DQPSK Ch 78 - Average

Frequency(MHz)	Result(dBuv/m)	ARPL (dB)	Pmea(dBuv/m)	Polarization
2494.880	58.6	-11.2	69.8	H
17922.500	62.7	27.9	34.8	Н
17958.000	62.3	27.9	34.4	V
17858.500	62.1	27.1	35.0	H
17856.500	61.9	27.1	34.8	Н
17901.500	61.9	27.1	34.8	Н

8DPSK Ch 0 - Average

Frequency(MHz)	Result(dBuv/m)	ARPL (dB)	Pmea(dBuv/m)	Polarization
2385.925	57.7	-11.1	68.8	Н
17833.500	62.7	27.1	35.6	Н
17970.000	61.7	27.9	33.8	V
17904.000	61.6	27.1	34.5	Н
17954.500	61.6	27.9	33.7	Н

Н

Η



8DF	PSK Ch 39 - Averag	е			
	Frequency(MHz)	Result(dBuv/m)	ARPL (dB)	Pmea(dBuv/m)	Polarization
	17940.000	62.2	27.9	34.3	Н
	17957.500	62.1	27.9	34.2	Н
	17942.000	62.0	27.9	34.1	V
	17707.500	61.8	26.7	35.1	Н

27.9

27.1

27.1

33.6

34.4

34.3

61.5

61.5

61.4

8DPSK Ch 78 - Average

17807.000

17905.000

17974.500

Frequency(MHz)	Result(dBuv/m)	ARPL (dB)	Pmea(dBuv/m)	Polarization
2489.655	58.4	-11.2	69.6	Н
17960.500	62.0	27.9	34.1	Н
17898.000	62.0	27.1	34.9	V
17978.500	61.9	27.9	34.0	Н
17858.000	61.8	27.1	34.7	Н
17935.500	61.8	27.9	33.9	Н

Conclusion: PASS
Test graphs as below:

R E_BT $_1$ G-3GHz




Fig.58. Radiated emission: GFSK, Channel 0, 1 GHz - 3 GHz








Fig.59. Radiated emission: GFSK, Channel 0, 3 GHz - 18 GHz




Fig.60. Radiated emission: GFSK, Channel 39, 9 kHz - 30 MHz






Fig.61. Radiated emission: GFSK, Channel 39, 30 MHz - 1 GHz




Fig.62. Radiated emission: GFSK, Channel 39, 1 GHz - 3 GHz








Fig.63. Radiated emission: GFSK, Channel 39, 3 GHz - 18 GHz




Fig.64. Radiated emission: GFSK, Channel 78, 1 GHz - 3 GHz









Fig.65. Radiated emission: GFSK, Channel 78, 3 GHz - 18 GHz



R E-BT-Power_2.38G-2.43GHz

Fig.66. Radiated emission (Power): GFSK, low channel

Frequency in MHz

2400

2380

2420








Fig.67. Radiated emission (Power) GFSK, high channel





Fig.68. Radiated emission: GFSK, 18 GHz - 26 GHz








Fig.69. Radiated emission: $\pi/4$ DQPSK, Channel 0, 1 GHz - 3 GHz




Fig.70. Radiated emission: $\pi/4$ DQPSK, Channel 0, 3 GHz - 18 GHz






Fig.71. Radiated emission: $\pi/4$ DQPSK, Channel 39, 30 MHz - 1 GHz




Fig.72. Radiated emission: $\pi/4$ DQPSK, Channel 39, 1 GHz - 3 GHz








Fig.73. Radiated emission: $\pi/4$ DQPSK, Channel 39, 3 GHz - 18 GHz




Fig.74. Radiated emission: $\pi/4$ DQPSK, Channel 78, 1 GHz - 3 GHz








Fig.75. Radiated emission: $\pi/4$ DQPSK, Channel 78, 3 GHz - 18 GHz





Fig.76. Radiated emission (Power): $\pi/4$ DQPSK, low channel








Fig.77. Radiated emission (Power): π/4 DQPSK, high channel





Fig.78. Radiated emission: π/4 DQPSK, 18 GHz - 26 GHz








Fig.79. Radiated emission: 8DPSK, Channel 0, 1 GHz - 3 GHz




Fig.80. Radiated emission: 8DPSK, Channel 0, 3 GHz - 18 GHz






Fig.81. Radiated emission: 8DPSK, Channel 39, 30 MHz - 1 GHz

Frequency in Hz




Fig.82. Radiated emission: 8DPSK, Channel 39, 1 GHz - 3 GHz








Fig.83. Radiated emission: 8DPSK, Channel 39, 3 GHz - 18 GHz

RE_BT_1G-3GHz



Fig.84. Radiated emission: 8DPSK, Channel 78, 1 GHz - 3 GHz

Frequency in MHz

2500

30

©Copyright. All rights reserved by CTTL.








Fig.85. Radiated emission: 8DPSK, Channel 78, 3 GHz - 18 GHz







Fig.86. Radiated emission (Power): 8DPSK, low channel








Fig.87. Radiated emission (Power): 8DPSK, high channel




Fig.88. Radiated emission: 8DPSK, 18 GHz - 26 GHz



A.6. Time of Occupancy (Dwell Time)

Method of Measurement: See ANSI C63.10-clause 7.8.4

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW ≥ RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

Measurement Result:

For GFSK

Channel	Packet	Dwell Time (ms)		Conclusion
	DH1	Fig.89	106.26	Р
		Fig.90		
39	DH3	Fig.91	163.94	Р
		Fig.92		
	DH5	Fig.93	179.68	Р
		Fig.94		

For π/4 DQPSK

Channel	Packet	Dwell Time (ms)		Conclusion
	DIA	Fig.95	110 10	Р
	DH1	Fig.96 110.42	Р	
20	DH3	Fig.97	167.22	Р
39		Fig.98		
	DH5	Fig.99	188.38	Р
		Fig.100		


For 8DPSK

Channel	Packet	Dwell Time (ms)		Conclusion
	DH1	Fig.101	103.95	В
39	DHI	Fig.102	103.95	Г
	DH3	Fig.103	186.89	P



	Fig.104		
DHE	Fig.105	206.14	D
DH5	Fig.106	200.14	Р

Conclusion: PASS
Test graphs as below:



Date: 5.MAR.2016 16:15:37

Fig.89. Time of occupancy (Dwell Time): Channel 39, Packet DH1






Fig.90. Number of Transmissions Measurement: Channel 39, Packet DH1





Date: 5.MAR.2016 16:16:53


Fig.91. Time of occupancy (Dwell Time): Channel 39, Packet DH3



Date: 5.MAR.2016 16:16:42


Fig.92. Number of Transmissions Measurement: Channel 39, Packet DH3





Date: 5.MAR.2016 16:18:07


Fig.93. Time of occupancy (Dwell Time): Channel 39, Packet DH5



Date: 5.MAR.2016 16:17:56


Fig.94. Number of Transmissions Measurement: Channel 39, Packet DH5





Date: 5.MAR.2016 16:40:39


Fig.95. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1



Date: 5.MAR.2016 16:40:27


Fig.96. Number of Transmissions Measurement: Channel 39, Packet 2-DH1





Date: 5.MAR.2016 16:41:55


Fig.97. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3



Date: 5.MAR.2016 16:41:44


Fig.98. Number of Transmissions Measurement:Channel 39,Packet 2-DH3





Date: 5.MAR.2016 16:43:10


Fig.99. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5



Date: 5.MAR.2016 16:42:58


Fig.100. Number of Transmissions Measurement: Channel 39, Packet 2-DH5





Date: 5.MAR.2016 17:20:50


Fig.101. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1



Date: 5.MAR.2016 17:20:38


Fig.102. Number of Transmissions Measurement: Channel 39, Packet 3-DH1





Date: 5.MAR.2016 17:22:08


Fig.103. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3



Date: 5.MAR.2016 17:21:57


Fig.104. Number of Transmissions Measurement: Channel 39, Packet 3-DH3





Date: 5.MAR.2016 17:23:22

Fig.105. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5



Date: 5.MAR.2016 17:23:11

Fig.106. Number of Transmissions Measurement: Channel 39, Packet 3-DH5



A.7. 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 6.9.2

Measurement Procedure - Unwanted Emissions

- 1. Set RBW = 20kHz.
- 2. Set VBW = 100 kHz.
- 3. Set span to 3MHz
- 4. Detector = peak.
- 5. Trace Mode = max hold.
- 6. Sweep = auto couple.
- 7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

Use NdB Down function of the SA to measure the 20dB Bandwidth

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for "carrier frequency separation" test case, in Annex A.8.

Measurement Results:

For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.107 870.19		NA
39	Fig.108	865.38	NA
78	Fig.109	870.19	NA

Forπ/4 DQPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.110 1254.81		NA
39	Fig.111	1269.23	NA
78	Fig.112	1254.81	NA


For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.113 1250.00		NA
39	Fig.114	1264.42	NA
78	Fig.115	1254.81	NA

Conclusion: NA


Test graphs as below:





Date: 5.MAR.2016 16:19:18


Fig.107. 20dB Bandwidth: GFSK, Channel 0



Date: 5.MAR.2016 16:19:50


Fig.108. 20dB Bandwidth: GFSK, Channel 39





Date: 5.MAR.2016 16:20:22


Fig.109. 20dB Bandwidth: GFSK, Channel 78



Date: 5.MAR.2016 16:43:43


Fig.110. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 0





Date: 5.MAR.2016 16:44:15


Fig.111. 20dB Bandwidth: π/4 DQPSK, Channel 39



Date: 5.MAR.2016 16:44:47


Fig.112. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 78





Date: 5.MAR.2016 17:05:40


Fig.113. 20dB Bandwidth: 8DPSK, Channel 0



Date: 5.MAR.2016 17:06:12

Fig.114. 20dB Bandwidth: 8DPSK, Channel 39





Date: 5.MAR.2016 17:06:44

Fig.115. 20dB Bandwidth: 8DPSK, Channel 78



A.8. Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=1MHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

* Comment: This limit should be over 25 kHz or (2/3) * 20dB bandwidth, whichever is greater.

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or (2/3) * 20dB bandwidth

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.116	1009.62	Р

For $\pi/4$ DQPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.117	1153.85	Р


For 8DPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.118	1000.00	Р

Conclusion: PASS


Test graphs as below:





Date: 5.MAR.2016 16:23:01


Fig.116. Carrier frequency separation measurement: GFSK, Channel 39



Date: 5.MAR.2016 17:16:38

Fig.117. Carrier frequency separation measurement: π/4 DQPSK, Channel 39





Date: 5.MAR.2016 17:18:43

Fig.118. Carrier frequency separation measurement: 8DPSK, Channel 39



A.9. Number of Hopping Channels

Method of Measurement: See ANSI C63.10-clause 7.8.3

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = the frequency band of operation
- RBW = 500kHz
- VBW = 500kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii)	At least 15 non-overlapping channels

Measurement Result:

For GFSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.119	70	D
40~78	Fig.120	79	P

Forπ/4 DQPSK


Channel	Number of hopping channels		Conclusion
0~39	Fig.121	70	D
40~78	Fig.122	79	P

For 8DPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.123	70	D
40~78	Fig.124	79	F


Conclusion: PASS
Test graphs as below:





Date: 5.MAR.2016 16:25:39


Fig.119. Number of hopping frequencies: GFSK, Channel 0 - 39



Date: 5.MAR.2016 16:27:42


Fig.120. Number of hopping frequencies: GFSK, Channel 40 - 78





Date: 5.MAR.2016 16:48:56


Fig.121. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 0 - 39



Date: 5.MAR.2016 16:50:58


Fig.122. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 40 - 78





Date: 5.MAR.2016 17:10:53

Fig.123. Number of hopping frequencies: 8DPSK, Channel 0 - 39



Date: 5.MAR.2016 17:12:55

Fig.124. Number of hopping frequencies: 8DPSK, Channel 40 - 78



A.10. AC Powerline Conducted Emission

Test Condition

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Conclusion
0.15 to 0.5	66 to 56	
0.5 to 5	56	Р
5 to 30	60	

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Conclusion
0.15 to 0.5	56 to 46	
0.5 to 5	46	Р
5 to 30	50	


NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

The measurement is made according to ANSI C63.10

Conclusion: PASS
Test graphs as below:



Traffic:



Final Result 1


Frequency	QuasiPeak	Meas. Time	Bandwidth	Filter	Line	Corr.	Margin	Limit
(MHz)	(dBµV)	(ms)	(kHz)			(dB)	(dB)	(dBµV)
0.154500	46.0	2000.0	9.000	On	L1	20.0	19.8	65.8
0.465000	32.7	2000.0	9.000	On	N	19.9	23.9	56.6
1.095000	34.8	2000.0	9.000	On	L1	19.7	21.2	56.0
1.801500	38.1	2000.0	9.000	On	L1	19.7	17.9	56.0
3.471000	38.8	2000.0	9.000	On	N	19.4	17.2	56.0
3.831000	38.6	2000.0	9.000	On	N	19.5	17.4	56.0

Final Result 2

Frequency	QuasiPeak	Meas. Time	Bandwidth	Filter	Line	Corr.	Margin	Limit
(MHz)	(dBµV)	(ms)	(kHz)			(dB)	(dB)	(dBµV)
0.154500	33.1	2000.0	9.000	On	L1	20.0	22.6	55.8
0.618000	25.6	2000.0	9.000	On	L1	19.8	20.4	46.0
1.032000	27.0	2000.0	9.000	On	L1	19.7	19.0	46.0
1.801500	27.0	2000.0	9.000	On	L1	19.7	19.0	46.0
3.354000	28.6	2000.0	9.000	On	L1	19.4	17.4	46.0
4.519500	28.3	2000.0	9.000	On	L1	19.6	17.7	46.0



Idle:



Final Result 1

Frequency	QuasiPeak	Meas. Time	Bandwidth	Filter	Line	Corr.	Margin	Limit
(MHz)	(dBµV)	(ms)	(kHz)			(dB)	(dB)	(dBµV)
0.154500	40.4	2000.0	9.000	On	N	20.0	25.3	65.8
0.307500	32.9	2000.0	9.000	On	N	19.8	27.2	60.0
1.045500	33.5	2000.0	9.000	On	L1	19.7	22.5	56.0
1.810500	38.2	2000.0	9.000	On	L1	19.7	17.8	56.0
3.498000	39.0	2000.0	9.000	On	N	19.5	17.0	56.0
3.988500	38.2	2000.0	9.000	On	N	19.5	17.8	56.0

Final Result 2

Frequency	QuasiPeak	Meas. Time	Bandwidth	Filter	Line	Corr.	Margin	Limit
(MHz)	(dBµV)	(ms)	(kHz)			(dB)	(dB)	(dBµV)
0.357000	26.9	2000.0	9.000	On	L1	19.8	21.8	48.8
0.618000	24.8	2000.0	9.000	On	L1	19.8	21.2	46.0
1.027500	27.0	2000.0	9.000	On	L1	19.7	19.0	46.0
1.788000	27.6	2000.0	9.000	On	L1	19.7	18.4	46.0
3.381000	29.3	2000.0	9.000	On	L1	19.4	16.7	46.0
3.790500	29.4	2000.0	9.000	On	L1	19.5	16.6	46.0



ANNEX B: Accreditation Certificate



China National Accreditation Service for Conformity Assessment

LABORATORY ACCREDITATION CERTIFICATE

(No. CNAS L0570)

Telecommunication Technology Labs,

Academy of Telecommunication Research, MIIT

No.52, Huayuan North Road, Haidian District, Beijing, China No.51, Xueyuan Road, Haidian District, Beijing, China

to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories(CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing and calibration.

The scope of accreditation is detailed in the attached schedule bearing the same accreditation number as above. The schedule forms an integral part of this certificate.

Date of Issue: 2014-10-29
Date of Expiry: 2017-06-19

Date of Initial Accreditation: 1998-07-03



Signed on behalf of China National Accreditation Service for Conformity Assessment

China National Accreditation Service for Conformity Assessment (CNAS) is authorized by Certification and Accreditation Administration of the People's Republic of China (CNCA) to operate the national accreditation schemes for conformity assessment. CNAS is the signatory to International Laboratory Accreditation Cooperation Multilateral Recognition Arrangement (ILAC MRA) and Asia Pacific Laboratory Accreditation Cooperation Multilateral Recognition Arrangement (APLAC MRA).

No.CNASAL2

0011149

END OF REPORT