



Report No.: WT168006225 Page 421 of 572

Band edge measurement LTE Band 5 Test Mode = 16QAM /TM5 Channel Bandwidth: 10 MHz




Report No.: WT168006225 Page 422 of 572




Report No.: WT168006225 Page 423 of 572

Band edge measurement LTE Band 7 Test Mode = QPSK /TM4 Channel Bandwidth: 5 MHz Test Channel = LCH/HCH




Report No.: WT168006225 Page 424 of 572




Report No.: WT168006225 Page 425 of 572

Band edge measurement LTE Band 7 Test Mode = 16QAM /TM5 Channel Bandwidth: 5 MHz




Report No.: WT168006225 Page 426 of 572




Report No.: WT168006225 Page 427 of 572

Band edge measurement LTE Band 7 Test Mode = QPSK /TM4 Channel Bandwidth: 10 MHz




Report No.: WT168006225 Page 428 of 572




Report No.: WT168006225 Page 429 of 572

Band edge measurement LTE Band 7 Test Mode = 16QAM /TM5 Channel Bandwidth: 10 MHz




Report No.: WT168006225 Page 430 of 572




Report No.: WT168006225 Page 431 of 572

Band edge measurement LTE Band 7 Test Mode = QPSK /TM4 Channel Bandwidth: 15 MHz




Report No.: WT168006225 Page 432 of 572




Report No.: WT168006225 Page 433 of 572

Band edge measurement LTE Band 7 Test Mode = 16QAM /TM5 Channel Bandwidth: 15 MHz




Report No.: WT168006225 Page 434 of 572




Report No.: WT168006225 Page 435 of 572

Band edge measurement LTE Band 7 Test Mode = QPSK /TM4 Channel Bandwidth: 20 MHz




Report No.: WT168006225 Page 436 of 572




Report No.: WT168006225 Page 437 of 572

Band edge measurement LTE Band 7 Test Mode = 16QAM /TM5 Channel Bandwidth: 20 MHz




Report No.: WT168006225 Page 438 of 572




Report No.: WT168006225 Page 439 of 572

Band edge measurement LTE Band 12 Test Mode = QPSK /TM4 Channel Bandwidth: 1.4 MHz




Report No.: WT168006225 Page 440 of 572




Report No.: WT168006225 Page 441 of 572

Band edge measurement LTE Band 12 Test Mode = 16QAM /TM5 Channel Bandwidth: 1.4 MHz




Report No.: WT168006225 Page 442 of 572




Report No.: WT168006225 Page 443 of 572

Band edge measurement LTE Band 12 Test Mode = QPSK /TM4 Channel Bandwidth: 3 MHz




Report No.: WT168006225 Page 444 of 572




Report No.: WT168006225 Page 445 of 572

Band edge measurement LTE Band 12 Test Mode = 16QAM /TM5 Channel Bandwidth: 3 MHz Test Channel = LCH/HCH




Report No.: WT168006225 Page 446 of 572




Report No.: WT168006225 Page 447 of 572

Band edge measurement LTE Band 12 Test Mode = QPSK /TM4 Channel Bandwidth: 5 MHz Test Channel = LCH/HCH




Report No.: WT168006225 Page 448 of 572




Report No.: WT168006225 Page 449 of 572

Band edge measurement LTE Band 12 Test Mode = 16QAM /TM5 Channel Bandwidth: 5 MHz Test Channel = LCH/HCH




Report No.: WT168006225 Page 450 of 572




Report No.: WT168006225 Page 451 of 572

Band edge measurement LTE Band 12 Test Mode = QPSK /TM4 Channel Bandwidth: 10 MHz




Report No.: WT168006225 Page 452 of 572




Report No.: WT168006225 Page 453 of 572

Band edge measurement LTE Band 12 Test Mode = 16QAM /TM5 Channel Bandwidth: 10 MHz




Report No.: WT168006225 Page 454 of 572




Report No.: WT168006225 Page 455 of 572

Band edge measurement LTE Band 13 Test Mode = QPSK /TM4 Channel Bandwidth: 5 MHz




Report No.: WT168006225 Page 456 of 572




Report No.: WT168006225 Page 457 of 572

Band edge measurement LTE Band 13 Test Mode = 16QAM /TM5 Channel Bandwidth: 5 MHz Test Channel = LCH/HCH




Report No.: WT168006225 Page 458 of 572




Report No.: WT168006225 Page 459 of 572

Band edge measurement LTE Band 13 Test Mode = QPSK /TM4




Report No.: WT168006225 Page 460 of 572




Report No.: WT168006225 Page 461 of 572

Band edge measurement LTE Band 13 Test Mode = 16QAM /TM5




Report No.: WT168006225 Page 462 of 572




Report No.: WT168006225 Page 463 of 572

Band edge measurement LTE Band 17 Test Mode = QPSK /TM4 Channel Bandwidth: 5 MHz Test Channel = LCH/HCH




Report No.: WT168006225 Page 464 of 572




Report No.: WT168006225 Page 465 of 572

Band edge measurement LTE Band 17 Test Mode = 16QAM /TM5 Channel Bandwidth: 5 MHz Test Channel = LCH/HCH




Report No.: WT168006225 Page 466 of 572




Report No.: WT168006225 Page 467 of 572

Band edge measurement LTE Band 17 Test Mode = QPSK /TM4 Channel Bandwidth: 10 MHz




Report No.: WT168006225 Page 468 of 572




Report No.: WT168006225 Page 469 of 572

Band edge measurement LTE Band 17 Test Mode = 16QAM /TM5 Channel Bandwidth: 10 MHz



Report No.: WT168006225 Page 470 of 572



Report No.: WT168006225 Page 471 of 572

4.5. Spurious Emissions Radiated

4.5.1.Test Standard

FCC: CFR Part 2.1053, CFR Part 22.917, CFR Part 24.238, CFR Part 27

4.5.2.Test Limit

Measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission.

5.5.3 Limits:

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

For all power levels +30dBm to 0dBm, this becomes a constant specification of -13dBm.

5.5.3.1 FCC 22.917 Emission limitations for cellular equipment.

The rules in this section govern the spectral characteristics of emissions in the Cellular

Radiotelephone Service.

(b) Measurement procedure. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz of 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

5.5.3.2 FCC 24.238 Emission limitations for Broadband PCS equipment.

The rules in this section govern the spectral characteristics of emissions in the Broadband Personal Communications Service.

(b) Measurement procedure. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz of 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

Report No.: WT168006225 Page 472 of 572

§ 27.53 (h) For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any

emission outside a licensee's frequency block shall be attenuated below the transmitter power

(P) by at least $43 + 10 \log 10(P) dB$.

The unwanted emission power shall be measured with a resolution bandwidth of at least 1% of the occupied bandwidth in the 1 MHz band immediately outside and adjacent to the channel edge of the equipment. Beyond the 1 MHz band immediately outside the channel edge of the equipment, a resolution bandwidth of 1 MHz shall be employed. A narrower resolution bandwidth is allowed to be used provided that the measured power is integrated over the full required measurement bandwidth of 1 MHz or 1% of the occupied bandwidth as applicable.

The power of any unwanted emissions measured from the channel edge of the equipment shall be attenuated below the transmitter power, P (dBW), as follows:

- a. for base station and subscriber equipment, other than mobile subscriber equipment, the attenuation shall not be less than 43 + 10 Log10 (p), dB; and
- b. for mobile subscriber equipment, the attenuation shall not be less than 43 + 10 Log10
- (p), dB at the channel edges and 55 + 10 Log10 (p) at 5.5 MHz away and beyond the channel edges where p in (a) and (b) is the transmitter power measured in watts

4.5.3.Test Procedure

- 1. Connect the equipment as shown in the above diagram with the EUT's antenna in a horizontal orientation.
- 2. Adjust the settings of the Universal Radio Communication Tester (CMU) to set the EUT to its maximum power at the required channel.
- 3. Set the spectrum analyzer to measure peak hold with the required settings.
- 4. Place the measurement antenna in a horizontal orientation. Rotate the EUT 360.

Raise the measurement antenna at 1.5 meters increments and rotate the EUT 360 at maximize all emissions. Measure and record all spurious emissions (LVL) up to the tenth harmonic of the carrier frequency.


- 5. Replace the EUT with a horizontally polarized half wave dipole or known gain antenna. The center of the antenna should be at the same location as the center of the EUT's antenna.
- 6. Connect the antenna to a signal generator with known output power and record the path loss in dB (LOSS). LOSS = Generator Output Power (dBm) Analyzer reading (dBm).
- 7. Determine the level of spurious emissions using the following equation: Spurious (dBm) = LVL (dBm) + LOSS (dB):
- 8. Repeat steps 4, 5 and 6 with all antennas vertically polarized.
- 9. Determine the level of spurious emissions using the following equation: Spurious (dBm) = LVL (dBm) + LOSS (dB):
- 10. Measurements are to be performed with the EUT set to the low, middle and high channel of each frequency band.

(Note: Steps 5 and 6 above are performed prior to testing and LOSS is recorded by test software. Steps 3, 4 and 7 above are performed with test software.)

Spectrum analyzer settings: RBW=VBW=1MHz

Report No.: WT168006225 Page 473 of 572

4.5.4.Test Setup



Report No.: WT168006225 Page 474 of 572

4.5.5.Test Data

Test Band = GSM850 Test Mode = GPRS /TM1 Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBd]	dB	Level (ERP) [dBm]		[dBm]
1648.4	4.61	0.9	6.77	40.6	-30.12	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = GSM850 Test Mode = GPRS /TM1 Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBd]	dB	Level (ERP) [dBm]		[dBm]
1673.2	2.7	0.9	6.77	40.6	-32.03	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = GSM850 Test Mode = GPRS /TM1 Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBd]	dB	Level (ERP) [dBm]		[dBm]
1697.6	3.17	0.9	6.77	40.6	-31.56	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 475 of 572

Test Band = GSM850 Test Mode = EDGE /TM2 Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBd]	dB	Level (ERP) [dBm]		[dBm]
1648.4	1.56	0.9	6.77	40.6	-33.17	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = GSM850 Test Mode = EDGE /TM2 Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBd]	dB	Level (ERP) [dBm]		[dBm]
1673.2	2.22	0.9	6.77	40.6	-32.51	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = GSM850 Test Mode = EDGE /TM2 Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBd]	dB	Level (ERP) [dBm]		[dBm]
1697.6	1.68	0.9	6.77	40.6	-33.05	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 476 of 572

Test Band = WCDMA850 Test Mode = UMTS/TM3 Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBd]	dB	Level (ERP) [dBm]		[dBm]
1652.8	2.59	0.9	6.77	40.6	-32.14	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = WCDMA850 Test Mode = UMTS/TM3 Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBd]	dB	Level (ERP) [dBm]		[dBm]
1672.8	2.9	0.9	6.77	40.6	-31.83	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = WCDMA850 Test Mode = UMTS/TM3 Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBd]	dB	Level (ERP) [dBm]		[dBm]
1693.2	2.64	0.9	6.77	40.6	-32.09	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 477 of 572

Test Band = GSM1900 Test Mode = GPRS /TM1 Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3700.4	-4.56	4.6	9.53	39	-38.63	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = GSM1900 Test Mode = GPRS /TM1 Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-3.35	4.6	9.53	39	-37.42	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = GSM1900 Test Mode = GPRS /TM1 Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3819.6	-4.22	4.6	9.53	39	-38.29	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 478 of 572

Test Band = GSM1900 Test Mode = EDGE /TM2 Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3700.4	-4.99	4.6	9.53	39	-39.06	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = GSM1900 Test Mode = EDGE /TM2 Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-5.46	4.6	9.53	39	-39.53	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = GSM1900 Test Mode = EDGE /TM2 Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3819.6	-4.86	4.6	9.53	39	-38.93	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 479 of 572

Test Band = WCDMA1900 Test Mode = UMTS /TM3 Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3705	-9.55	4.6	9.53	39	-43.62	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = WCDMA1900 Test Mode = UMTS /TM3 Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-7.52	4.6	9.53	39	-41.59	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = WCDMA1900 Test Mode = UMTS /TM3 Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3815.2	-8.3	4.6	9.53	39	-42.37	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 480 of 572

Test Band = WCDMA1700 Test Mode = UMTS /TM3 Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3424.8	-9.57	4.1	9.41	39	-43.26	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = WCDMA1700 Test Mode = UMTS /TM3 Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465.2	-8.34	4.1	9.41	39	-42.03	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = WCDMA1700 Test Mode = UMTS /TM3 Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3505.2	-7.62	4.1	9.41	39	-41.31	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 481 of 572

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=1.4MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3701.4	-10.01	4.6	9.53	39	-44.08	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=1.4MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-10.14	4.6	9.53	39	-44.21	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=1.4MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3818.6	-9.88	4.6	9.53	39	-43.95	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 482 of 572

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=1.4MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3701.4	-9.4	4.6	9.53	39	-43.47	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=1.4MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-6.89	4.6	9.53	39	-40.96	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=1.4MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3818.6	-9.98	4.6	9.53	39	-44.05	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 483 of 572

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=3MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3703	-11.2	4.6	9.53	39	-45.27	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=3MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-10.29	4.6	9.53	39	-44.36	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=3MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3817	-9.88	4.6	9.53	39	-43.95	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 484 of 572

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=3MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3703	-11.01	4.6	9.53	39	-45.08	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=3MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-10.68	4.6	9.53	39	-44.75	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=3MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3817	-9.49	4.6	9.53	39	-43.56	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 485 of 572

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3705	-10.17	4.6	9.53	39	-44.24	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-9.8	4.6	9.53	39	-43.87	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3815	-11.24	4.6	9.53	39	-45.31	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 486 of 572

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=5MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3705	-10.21	4.6	9.53	39	-44.28	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=5MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-9.51	4.6	9.53	39	-43.58	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3815	-10.72	4.6	9.53	39	-44.79	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 487 of 572

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3710	-11.19	4.6	9.53	39	-45.26	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-11.42	4.6	9.53	39	-45.49	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3810	-9.67	4.6	9.53	39	-43.74	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 488 of 572

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=10MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3710	-12.22	4.6	9.53	39	-46.29	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=10MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-10.25	4.6	9.53	39	-44.32	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=10MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3810	-11.55	4.6	9.53	39	-45.62	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 489 of 572

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=15MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3715	-9.89	4.6	9.53	39	-43.96	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=15MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-10.66	4.6	9.53	39	-44.73	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=15MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3805	-11.01	4.6	9.53	39	-45.08	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 490 of 572

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=15MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3715	-9.57	4.6	9.53	39	-43.64	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=15MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-9.77	4.6	9.53	39	-43.84	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=15MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3805	-11.6	4.6	9.53	39	-45.67	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 491 of 572

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=20MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3720	-10.32	4.6	9.53	39	-44.39	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=20MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-11.14	4.6	9.53	39	-45.21	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = QPSK /TM4
Bandwidth=20MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3800	-10.79	4.6	9.53	39	-44.86	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 492 of 572

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=20MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3720	-11.32	4.6	9.53	39	-45.39	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=20MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3760	-10.21	4.6	9.53	39	-44.28	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 2
Test Mode = 16QAM /TM5
Bandwidth=20MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3800	-9.69	4.6	9.53	39	-43.76	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 493 of 572

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=1.4MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3421.4	-10.54	4.1	9.41	39	-44.23	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=1.4MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465	-10	4.1	9.41	39	-43.69	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=1.4MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3508.6	-12.02	4.1	9.41	39	-45.71	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 494 of 572

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=1.4MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3421.4	-12.35	4.1	9.41	39	-46.04	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=1.4MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465	-12.14	4.1	9.41	39	-45.83	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = Q16QAM /TM5
Bandwidth=1.4MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3508.6	-5.87	4.1	9.41	39	-41.56	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 495 of 572

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=3MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3423	-10.87	4.1	9.41	39	-44.56	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=3MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465	-10.25	4.1	9.41	39	-43.94	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=3MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3507	-11.06	4.1	9.41	39	-44.75	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 496 of 572

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=3MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3423	-12.07	4.1	9.41	39	-45.76	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=3MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465	-10	4.1	9.41	39	-43.69	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = Q16QAM /TM5
Bandwidth=3MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3507	-11.68	4.1	9.41	39	-45.37	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 497 of 572

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3425	-10.39	4.1	9.41	39	-44.08	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465	-10.28	4.1	9.41	39	-43.97	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3505	-11.65	4.1	9.41	39	-45.34	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 498 of 572

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=5MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3425	-11.6	4.1	9.41	39	-45.29	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=5MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465	-11.02	4.1	9.41	39	-44.71	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = Q16QAM /TM5
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3505	-9.37	4.1	9.41	39	-43.06	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 499 of 572

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3430	-10.83	4.1	9.41	39	-44.52	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465	-8.94	4.1	9.41	39	-42.63	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3500	-9.15	4.1	9.41	39	-42.84	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 500 of 572

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=10MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3430	-9.96	4.1	9.41	39	-43.65	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=10MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465	-10.9	4.1	9.41	39	-44.59	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = Q16QAM /TM5
Bandwidth=10MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3500	-9.99	4.1	9.41	39	-43.68	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 501 of 572

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=15MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3435	-10.83	4.1	9.41	39	-44.52	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=15MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465	-10.16	4.1	9.41	39	-43.85	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=15MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3495	-11.07	4.1	9.41	39	-44.76	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 502 of 572

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=15MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3435	-10.14	4.1	9.41	39	-43.83	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=15MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465	-10.9	4.1	9.41	39	-44.59	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = Q16QAM /TM5
Bandwidth=15MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3495	-12.07	4.1	9.41	39	-45.76	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 503 of 572

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=20MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3440	-11.06	4.1	9.41	39	-44.75	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=20MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3465	-9.93	4.1	9.41	39	-43.62	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = QPSK /TM4
Bandwidth=20MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
3490	-10.18	4.1	9.41	39	-43.87	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 504 of 572

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=20MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (ERP) [dBm]		[dBm]
3440	-10.59	4.1	9.41	39	-44.28	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = 16QAM /TM5
Bandwidth=20MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (ERP) [dBm]		[dBm]
3465	-8.94	4.1	9.41	39	-42.63	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 4
Test Mode = Q16QAM /TM5
Bandwidth=20MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (ERP) [dBm]		[dBm]
3490	-9.47	4.1	9.41	39	-43.16	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 505 of 572

Test Band = LTE Band 5
Test Mode = QPSK /TM4
Bandwidth=1.4MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1649.4	-3.96	0.9	6.77	40.6	-38.69	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = QPSK /TM4
Bandwidth=1.4MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1673	-4.92	0.9	6.77	40.6	-39.65	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = QPSK /TM4
Bandwidth=1.4MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1696.7	-3.98	0.9	6.77	40.6	-38.71	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 506 of 572

Test Band = LTE Band 5
Test Mode = 16QAM /TM5
Bandwidth=1.4MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1649.4	-4.31	0.9	6.77	40.6	-39.04	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = 16QAM /TM5
Bandwidth=1.4MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1673	-4.94	0.9	6.77	40.6	-39.67	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = Q16QAM /TM5
Bandwidth=1.4MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1696.7	-3.7	0.9	6.77	40.6	-38.43	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 507 of 572

Test Band = LTE Band 5
Test Mode = QPSK /TM4
Bandwidth=3MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1651	-4.4	0.9	6.77	40.6	-39.13	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = QPSK /TM4
Bandwidth=3MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1673	-4.01	0.9	6.77	40.6	-38.74	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = QPSK /TM4
Bandwidth=3MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1695	-4.63	0.9	6.77	40.6	-39.36	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 508 of 572

Test Band = LTE Band 5
Test Mode = 16QAM /TM5
Bandwidth=3MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1651	-3.98	0.9	6.77	40.6	-38.71	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = 16QAM /TM5
Bandwidth=3MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1673	-4.69	0.9	6.77	40.6	-39.42	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = Q16QAM /TM5
Bandwidth=3MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1695	-3.51	0.9	6.77	40.6	-38.24	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 509 of 572

Test Band = LTE Band 5
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1653	-4.35	0.9	6.77	40.6	-39.08	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1673	-3.94	0.9	6.77	40.6	-38.67	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1693	-5.11	0.9	6.77	40.6	-39.84	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 510 of 572

Test Band = LTE Band 5
Test Mode = 16QAM /TM5
Bandwidth=5MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1653	-3.94	0.9	6.77	40.6	-38.67	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = 16QAM /TM5
Bandwidth=5MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1673	-4.97	0.9	6.77	40.6	-39.7	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = Q16QAM /TM5
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1693	-5.48	0.9	6.77	40.6	-40.21	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 511 of 572

Test Band = LTE Band 5
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1658	-4.85	0.9	6.77	40.6	-39.58	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1673	-4.06	0.9	6.77	40.6	-38.79	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5 Test Mode = QPSK /TM4 Bandwidth=10MHz Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1688	-4.64	0.9	6.77	40.6	-39.37	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 512 of 572

Test Band = LTE Band 5
Test Mode = 16QAM /TM5
Bandwidth=10MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1693	-6.09	0.9	6.77	40.6	-40.82	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = 16QAM /TM5
Bandwidth=10MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1673	-5.23	0.9	6.77	40.6	-39.96	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 5
Test Mode = Q16QAM /TM5
Bandwidth=10MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1688	-4.07	0.9	6.77	40.6	-38.8	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 513 of 572

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5005	-8.26	6.32	10	38.5	-43.08	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5070	-10.45	6.32	10	38.5	-45.27	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5135	-9.87	6.32	10	38.5	-44.69	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 514 of 572

Test Band = LTE Band 7
Test Mode = 16QAM /TM5
Bandwidth=5MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5005	-10.46	6.32	10	38.5	-45.28	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = 16QAM /TM5
Bandwidth=5MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5070	-9.55	6.32	10	38.5	-44.37	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = Q16QAM /TM5
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5135	-9.05	6.32	10	38.5	-43.87	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 515 of 572

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5010	-9.74	6.32	10	38.5	-44.56	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5070	-10.45	6.32	10	38.5	-45.27	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5130	-9.96	6.32	10	38.5	-44.78	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 516 of 572

Test Band = LTE Band 7
Test Mode = 16QAM /TM5
Bandwidth=10MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5010	-8.86	6.32	10	38.5	-43.68	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = 16QAM /TM5
Bandwidth=10MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5070	-9.9	6.32	10	38.5	-44.72	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = Q16QAM /TM5
Bandwidth=10MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5130	-8.98	6.32	10	38.5	-43.8	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 517 of 572

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=15MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5015	-9.39	6.32	10	38.5	-44.21	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=15MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5070	-10.45	6.32	10	38.5	-45.27	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=15MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5125	-9.97	6.32	10	38.5	-44.79	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 518 of 572

Test Band = LTE Band 7
Test Mode = 16QAM /TM5
Bandwidth=15MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5015	-10.99	6.32	10	38.5	-45.81	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = 16QAM /TM5
Bandwidth=15MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5070	-8.81	6.32	10	38.5	-43.63	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = Q16QAM /TM5
Bandwidth=15MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5125	-9.23	6.32	10	38.5	-44.05	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 519 of 572

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=20MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5020	-8.8	6.32	10	38.5	-43.62	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=20MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5070	-9.43	6.32	10	38.5	-44.25	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = QPSK /TM4
Bandwidth=20MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5120	-10.81	6.32	10	38.5	-45.63	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 520 of 572

Test Band = LTE Band 7
Test Mode = 16QAM /TM5
Bandwidth=20MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5020	-8.52	6.32	10	38.5	-43.34	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = 16QAM /TM5
Bandwidth=20MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5070	-9.56	6.32	10	38.5	-44.38	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 7
Test Mode = Q16QAM /TM5
Bandwidth=20MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
5120	-10.2	6.32	10	38.5	-45.02	Horizontal	-25

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 521 of 572

Test Band = LTE Band 12 Test Mode = QPSK /TM4 Bandwidth=1.4MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1399.4	-5.82	0.9	6.49	40.6	-40.83	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12 Test Mode = QPSK /TM4 Bandwidth=1.4MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1415	-4.66	0.9	6.49	40.6	-39.67	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12 Test Mode = QPSK /TM4 Bandwidth=1.4MHz Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1430.6	-4.17	0.9	6.49	40.6	-39.18	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 522 of 572

Test Band = LTE Band 12 Test Mode = 16QAM /TM5 Bandwidth=1.4MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1399.4	-5.28	0.9	6.49	40.6	-40.29	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12 Test Mode = 16QAM /TM5 Bandwidth=1.4MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1415	-5.71	0.9	6.49	40.6	-40.72	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12
Test Mode = Q16QAM /TM5
Bandwidth=1.4MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1430.6	-5.51	0.9	6.49	40.6	-40.52	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 523 of 572

Test Band = LTE Band 12 Test Mode = QPSK /TM4 Bandwidth=3MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1401	-4.66	0.9	6.49	40.6	-39.67	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12 Test Mode = QPSK /TM4 Bandwidth=3MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1415	-5.42	0.9	6.49	40.6	-40.43	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12
Test Mode = QPSK /TM4
Bandwidth=3MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1429	-4.81	0.9	6.49	40.6	-39.82	Vertical I	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 524 of 572

Test Band = LTE Band 12 Test Mode = 16QAM /TM5 Bandwidth=3MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1401	-4.36	0.9	6.49	40.6	-39.37	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12 Test Mode = 16QAM /TM5 Bandwidth=3MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1415	-5.17	0.9	6.49	40.6	-40.18	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12 Test Mode = 16QAM /TM5 Bandwidth=3MHz Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1429	-5.72	0.9	6.49	40.6	-40.73	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 525 of 572

Test Band = LTE Band 12 Test Mode = QPSK /TM4 Bandwidth=5MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1403	-4.82	0.9	6.49	40.6	-39.83	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12 Test Mode = QPSK /TM4 Bandwidth=5MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1415	-4.03	0.9	6.49	40.6	-39.04	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1427	-4.77	0.9	6.49	40.6	-39.78	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 526 of 572

Test Band = LTE Band 12 Test Mode = 16QAM /TM5 Bandwidth=5MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1403	-5.06	0.9	6.49	40.6	-40.07	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12 Test Mode = 16QAM /TM5 Bandwidth=5MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1415	-5.27	0.9	6.49	40.6	-40.28	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12
Test Mode = Q16QAM /TM5
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1427	-6.23	0.9	6.49	40.6	-41.24	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 527 of 572

Test Band = LTE Band 12 Test Mode = QPSK /TM4 Bandwidth=10MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1408	-5.9	0.9	6.49	40.6	-40.91	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12 Test Mode = QPSK /TM4 Bandwidth=10MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1415	-6.16	0.9	6.49	40.6	-41.17	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1422	-5.68	0.9	6.49	40.6	-40.69	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 528 of 572

Test Band = LTE Band 12 Test Mode = 16QAM /TM5 Bandwidth=10MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1408	-4.12	0.9	6.49	40.6	-39.13	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12 Test Mode = 16QAM /TM5 Bandwidth=10MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1415	-4.28	0.9	6.49	40.6	-39.29	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 12
Test Mode = Q16QAM /TM5
Bandwidth=10MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1422	-4.63	0.9	6.49	40.6	-39.64	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 529 of 572

Test Band = LTE Band 13 Test Mode = QPSK /TM4 Bandwidth=5MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1559	-8.78	0.9	6.49	40.6	-43.79	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 13 Test Mode = QPSK /TM4 Bandwidth=5MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1564	-9.15	0.9	6.49	40.6	-44.16	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 13
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1569	-8.6	0.9	6.49	40.6	-43.61	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 530 of 572

Test Band = LTE Band 13 Test Mode = 16QAM /TM5 Bandwidth=5MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1559	-8.94	0.9	6.49	40.6	-43.95	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 13 Test Mode = 16QAM /TM5 Bandwidth=5MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1564	-9.07	0.9	6.49	40.6	-44.08	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 13
Test Mode = Q16QAM /TM5
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1569	-9.18	0.9	6.49	40.6	-44.19	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 531 of 572

Test Band = LTE Band 13 Test Mode = QPSK /TM4 Bandwidth=10MHz

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1564	-9.26	0.9	6.49	40.6	-44.27	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 13 Test Mode = 16QAM /TM5 Bandwidth=10MHz

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1564	-9.85	0.9	6.49	40.6	-44.86	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 532 of 572

Test Band = LTE Band 17 Test Mode = QPSK /TM4 Bandwidth=5MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1413	-6.58	0.9	6.49	40.6	-41.59	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 17 Test Mode = QPSK /TM4 Bandwidth=5MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1420	-7.08	0.9	6.49	40.6	-42.09	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 17
Test Mode = QPSK /TM4
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1427	-6.86	0.9	6.49	40.6	-41.87	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 533 of 572

Test Band = LTE Band 17
Test Mode = 16QAM /TM5
Bandwidth=5MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1413	-5.95	0.9	6.49	40.6	-40.96	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 17
Test Mode = 16QAM /TM5
Bandwidth=5MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1420	-6.59	0.9	6.49	40.6	-41.6	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 17
Test Mode = Q16QAM /TM5
Bandwidth=5MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1427	-8.04	0.9	6.49	40.6	-43.05	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 534 of 572

Test Band = LTE Band 17 Test Mode = QPSK /TM4 Bandwidth=10MHz Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1418	-5.6	0.9	6.49	40.6	-40.61	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 17 Test Mode = QPSK /TM4 Bandwidth=10MHz Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1420	-6.72	0.9	6.49	40.6	-41.73	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 17
Test Mode = QPSK /TM4
Bandwidth=10MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1422	-5.95	0.9	6.49	40.6	-40.96	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 535 of 572

Test Band = LTE Band 17
Test Mode = 16QAM /TM5
Bandwidth=10MHz
Test Channel = LCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Pream p	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1418	-4.85	0.9	6.49	40.6	-39.86	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 17
Test Mode = 16QAM /TM5
Bandwidth=10MHz
Test Channel = MCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1420	-5.72	0.9	6.49	40.6	-40.73	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Test Band = LTE Band 17
Test Mode = Q16QAM /TM5
Bandwidth=10MHz
Test Channel = HCH

Freq.	SG. Level	Cable Loss	Antenna Gain	Preamp	Substitution	polarization	Limit
[MHz]	[dBm]	[dB]	[dBi]	dB	Level (EIRP) [dBm]		[dBm]
1422	-5.27	0.9	6.49	40.6	-40.28	Vertical	-13

The emissions don't show in above result tables are more than 20dB below the limits Note: both of Vertical and Horizontal polarization are evaluated, and only the worst case is recorded in this report

Report No.: WT168006225 Page 536 of 572

4.6. Frequency Stability

CFR 47 (FCC) part 2.1055, 22.355, 24.235 and 27.54

4.6.1.Test Limit

According to part 22.355, from 821MHz to 896MHz, for mobile device, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances 2.5ppm.

4.6.2.Test Procedure

GSM/WCDMA

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU 200 Universal Radio Communication Tester.

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the EUT to overnight soak at -30°C.
- 3. With the EUT, powered via nominal voltage, connected to the CMU 200 and in a simulated call on mid channel (190 for GSM 850 & 4183 for WCDMA 850 & 661 for PCS1900 & 9400 for WCDMA 1900& 1413 for WCDMA 1700), measure the carrier frequency. These measurements should be made within 2 minutes of powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10 C increments from -30 $^{\circ}$ C to +50 $^{\circ}$ C. Allow at least 1 1/2 hours at each temperature, un-powered, before making measurements.
- 5. Re-measure carrier frequency at room temperature with nominal voltage. Re-measure carrier frequency at low and high voltage. Pause at nominal voltage for 1 1/2 hours un-powered, to allow any self-heating to stabilize, before continuing.
- 6. Subject the EUT to overnight soak at +50 $^{\circ}$ C.
- 7. With the EUT, powered via nominal voltage, connected to the CMU 200 and in a simulated call on mid channel (190 for GSM 850 & 4183 for WCDMA 850 & 661 for PCS1900 & 9400 for WCDMA 1900 & 1413 for WCDMA 1700), measure the carrier frequency. These measurements should be made within 2 minutes of powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10 $^{\circ}\mathrm{C}$ increments from +50 $^{\circ}\mathrm{C}$ to -30 $^{\circ}\mathrm{C}$. Allow at least 1 1/2 hours at each temperature, un-powered, before making measurements.
- 9. At all temperature levels hold the temperature to +/- 0.5 $\,^{\circ}$ C during the measurement procedure.

I TF

- 1. The transmitter output (antenna port) was connected to the BS Simulator.
- 2. The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.
- 3. BS simulator used the frequency error function and measured the peak frequency error. Power must be removed when changingfrom one temperature to another or one voltage to another voltage. Power warm up is at least 15 min and power applied should perform before recording frequency error. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.
- 4. EUT is connected the external power supply to control the DC input power. The

Report No.: WT168006225 Page 537 of 572

various Volts from the minimum 3.5 Volts to 4.2 Volts. Each step shall be record the frequency error rate.

- 5. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value.
- 6. Extreme temperature rule is-30°C~50°C.

4.6.3.Test Setup

Connect the EUT to the Wireless Communication test set CMU200 or CMW 500 via the connector. Then measure the frequency error by the Wireless Communication test set CMU200/CMW 500. The EUT's output is matched with a 50 Ω load.

4.6.4.Test Data

Measurement Results vs. Variation of Temperature—GPRS850

Temperature	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	836.6	12.85	Pass
-20 °C	836.6	12.72	Pass
-10 °C	836.6	25.63	Pass
0 °C	836.6	20.60	Pass
+10 °C	836.6	20.60	Pass
+20 °C	836.6	20.34	Pass
+30 °C	836.6	22.92	Pass
+40 °C	836.6	12.79	Pass
+50 °C	836.6	13.11	Pass

Measurement Results vs. Variation of Voltage—GPRS850

Voltage	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
3.5 V	836.6	20.15	Pass
3.8 V	836.6	19.95	Pass
4.2 V	836.6	11.30	Pass

Report No.: WT168006225 Page 538 of 572

Measurement Results vs. Variation of Temperature—EDGE850

Temperature	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	836.6	16.05	Pass
-20 °C	836.6	14.37	Pass
-10 °C	836.6	14.66	Pass
0 °C	836.6	15.66	Pass
+10 °C	836.6	14.63	Pass
+20 °C	836.6	14.50	Pass
+30 °C	836.6	14.11	Pass
+40 °C	836.6	14.30	Pass
+50 °C	836.6	14.33	Pass

Measurement Results vs. Variation of Voltage—EDGE850

Voltage	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
3.5 V	836.6	13.50	Pass
3.8 V	836.6	15.40	Pass
4.2 V	836.6	13.95	Pass

Report No.: WT168006225 Page 539 of 572

Measurement Results vs. Variation of Temperature—WCDMA850

Temperature	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	836.6	-4.96	Pass
-20 °C	836.6	-1.02	Pass
-10 °C	836.6	-3.16	Pass
0 °C	836.6	-1.04	Pass
+10 °C	836.6	-5.48	Pass
+20 °C	836.6	-3.66	Pass
+30 °C	836.6	-4.90	Pass
+40 °C	836.6	-6.30	Pass
+50 °C	836.6	-1.28	Pass

Measurement Results vs. Variation of Voltage—WCDMA850

Voltage	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
3.5 V	836.6	-4.62	Pass
3.8 V	836.6	-0.03	Pass
4.2 V	836.6	-4.50	Pass

Report No.: WT168006225 Page 540 of 572

Measurement Results vs. Variation of Temperature—GPRS1900

Temperature	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	1880.0	-5.49	Pass
-20 °C	1880.0	-7.04	Pass
-10 °C	1880.0	-5.17	Pass
0 °C	1880.0	-5.10	Pass
+10 °C	1880.0	-5.75	Pass
+20 °C	1880.0	-8.39	Pass
+30 °C	1880.0	-2.20	Pass
+40 °C	1880.0	-5.36	Pass
+50 °C	1880.0	-5.29	Pass

Measurement Results vs. Variation of Voltage-GPRS1900

Voltage	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
3.5 V	1880.0	-6.59	Pass
3.8 V	1880.0	-4.00	Pass
4.2 V	1880.0	-5.42	Pass

Report No.: WT168006225 Page 541 of 572

Measurement Results vs. Variation of Temperature - EDGE1900

Temperature	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	1880.0	0.32	Pass
-20 °C	1880.0	-3.71	Pass
-10 °C	1880.0	-1.58	Pass
0 °C	1880.0	0.61	Pass
+10 °C	1880.0	0.32	Pass
+20 °C	1880.0	0.29	Pass
+30 °C	1880.0	-1.07	Pass
+40 °C	1880.0	0.39	Pass
+50 °C	1880.0	-3.65	Pass

Measurement Results vs. Variation of Voltage-EDGE1900

Voltage	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
3.5 V	1880.0	-1.26	Pass
3.8 V	1880.0	-3.13	Pass
4.2 V	1880.0	-0.45	Pass

Report No.: WT168006225 Page 542 of 572

Measurement Results vs. Variation of Temperature – WCDMA1900

Temperature	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	1880.0	-5.81	Pass
-20 °C	1880.0	1.66	Pass
-10 °C	1880.0	0.92	Pass
0 °C	1880.0	-0.92	Pass
+10 °C	1880.0	-1.43	Pass
+20 °C	1880.0	2.47	Pass
+30 °C	1880.0	-4.85	Pass
+40 °C	1880.0	-1.98	Pass
+50 °C	1880.0	-0.27	Pass

Measurement Results vs. Variation of Voltage—WCDMA1900

Wedsdreffield Nesdate vo. Validation of Voltage VI 921111 (1999)			
Voltage	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
3.5 V	1880.0	-4.84	Pass
3.8 V	1880.0	-2.38	Pass
4.2 V	1880.0	0.11	Pass

Report No.: WT168006225 Page 543 of 572

Measurement Results vs. Variation of Temperature – WCDMA1700

Temperature	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	1732.6	-5.31	Pass
-20 °C	1732.6	-6.85	Pass
-10 °C	1732.6	-0.70	Pass
0 °C	1732.6	-0.23	Pass
+10 °C	1732.6	-1.24	Pass
+20 °C	1732.6	-2.85	Pass
+30 °C	1732.6	-2.06	Pass
+40 °C	1732.6	-0.92	Pass
+50 °C	1732.6	2.50	Pass

Measurement Results vs. Variation of Voltage—WCDMA1700

	Wedstrement Results vs. Validition of Voltage 11 9211111111111						
Voltage	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result				
3.5 V	1732.6	-1.42	Pass				
3.8 V	1732.6	5.86	Pass				
4.2V	1732.6	-2.73	Pass				

Report No.: WT168006225 Page 544 of 572

Measurement Results vs. Variation of Voltage—LTE Band 2(1.4MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-1.26	PASS
QPSK	1880	3.7	-3.76	PASS
		4.2	-0.16	PASS
		3.5	-3.52	PASS
16QAM	1880	3.7	-3.28	PASS
		4.2	-1.07	PASS

Measurement Results vs. Variation of Temperature—LTE Band 2(1.4MHZ)

10100	dodrennent recour	to vo. variation of	Temperature ETE Ba	
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	,	-30 °C	-0.79	PASS
		-20 °C	-0.72	PASS
		-10 °C	-0.36	PASS
		0 °C	-0.04	PASS
QPSK	1880	+10 °C	-3.63	PASS
		+20 °C	-2.63	PASS
		+30 °C	-5.32	PASS
		+40 °C	-2.92	PASS
		+50 °C	-0.23	PASS
		-30 °C	0.87	PASS
		-20 °C	0.31	PASS
		-10 °C	1.53	PASS
		0 °C	-2.53	PASS
16QAM	1880	+10 °C	-2.76	PASS
		+20 °C	-2.37	PASS
		+30 °C	-2.82	PASS
		+40 °C	-2.15	PASS
		+50 °C	-2.68	PASS

Report No.: WT168006225 Page 545 of 572

Measurement Results vs. Variation of Voltage—LTE Band 2(3MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-2.25	PASS
QPSK	1880	3.7	-5.66	PASS
		4.2	1.09	PASS
		3.5	-1.04	PASS
16QAM	1880	3.7	-4.99	PASS
		4.2	0.86	PASS

Measurement Results vs. Variation of Temperature—LTE Band 2(3MHZ)

Measurement Results vs. Variation of Temperature—LTE Band 2(3MHZ)				
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
		-30 °C	-1.27	PASS
		-20 °C	-2.12	PASS
		-10 °C	-2.06	PASS
		0 °C	-1.12	PASS
QPSK	1880	+10 °C	-5.56	PASS
		+20 °C	-5.18	PASS
		+30 °C	-5.05	PASS
		+40 °C	-3.98	PASS
		+50 °C	0.03	PASS
		-30 °C	0.93	PASS
		-20 °C	0.06	PASS
		-10 °C	0.46	PASS
		0 °C	-1.13	PASS
16QAM	1880	+10 °C	-2.46	PASS
		+20 °C	-1.73	PASS
		+30 °C	-2.17	PASS
		+40 °C	-3.35	PASS
		+50 °C	-2.13	PASS

Report No.: WT168006225 Page 546 of 572

Measurement Results vs. Variation of Voltage—LTE Band 2(5MHZ)

				, ,
Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-2.29	PASS
QPSK	1880	3.7	-2.29	PASS
		4.2	-1.27	PASS
		3.5	-2.86	PASS
16QAM	1880	3.7	-4.55	PASS
		4.2	0.50	PASS

Measurement Results vs. Variation of Temperature—LTE Band 2(5MHZ)

1 V	wedstrement results vs. variation of remperature. Et E band 2(own 12)				
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict	
	, ,	-30 °C	-3.08	PASS	
		-20 °C	-0.89	PASS	
		-10 °C	-1.30	PASS	
		0 °C	-0.77	PASS	
QPSK	1880	+10 °C	-3.72	PASS	
		+20 °C	-3.05	PASS	
		+30 °C	-4.79	PASS	
		+40 °C	-5.45	PASS	
		+50 °C	0.87	PASS	
		-30 °C	0.24	PASS	
		-20 °C	-1.23	PASS	
		-10 °C	1.12	PASS	
		0 °C	-1.13	PASS	
16QAM	1880	+10 °C	-1.80	PASS	
		+20 °C	-0.79	PASS	
		+30 °C	-3.88	PASS	
		+40 °C	-4.31	PASS	
		+50 °C	-3.28	PASS	

Report No.: WT168006225 Page 547 of 572

Measurement Results vs. Variation of Voltage—LTE Band 2(10MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-2.33	PASS
QPSK	1880	3.7	-3.15	PASS
		4.2	1.37	PASS
		3.5	-4.19	PASS
16QAM	1880	3.7	-3.42	PASS
		4.2	1.02	PASS

Measurement Results vs. Variation of Temperature—LTE Band 2(10MHZ)

Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	, ,	-30 °C	-2.27	PASS
		-20 °C	-3.09	PASS
		-10 °C	-2.93	PASS
		0 °C	-2.57	PASS
QPSK	1880	+10 °C	-3.16	PASS
		+20 °C	-4.45	PASS
		+30 °C	-2.50	PASS
		+40 °C	-3.58	PASS
		+50 °C	0.50	PASS
		-30 °C	0.83	PASS
		-20 °C	0.20	PASS
		-10 °C	-1.17	PASS
		0 °C	-2.82	PASS
16QAM	1880	+10 °C	-4.39	PASS
		+20 °C	-4.02	PASS
		+30 °C	-2.00	PASS
		+40 °C	-1.82	PASS
		+50 °C	-3.05	PASS

Report No.: WT168006225 Page 548 of 572

Measurement Results vs. Variation of Voltage—LTE Band 2(15MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-2.80	PASS
QPSK	1880	3.7	-3.79	PASS
		4.2	-3.19	PASS
		3.5	-1.53	PASS
16QAM	1880	3.7	-3.02	PASS
		4.2	-5.34	PASS

Measurement Results vs. Variation of Temperature—LTE Band 2(15MHZ)

	Wedstrement Results vs. Variation of Temperature ETE Band 2(Town 12)				
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict	
	,	-30 °C	-3.32	PASS	
		-20 °C	-2.06	PASS	
		-10 °C	-4.58	PASS	
		0 °C	-2.83	PASS	
QPSK	1880	+10 °C	-1.73	PASS	
		+20 °C	-3.35	PASS	
		+30 °C	-3.35	PASS	
		+40 °C	-2.66	PASS	
		+50 °C	-3.15	PASS	
		-30 °C	-2.16	PASS	
		-20 °C	-3.71	PASS	
		-10 °C	-4.28	PASS	
		0 °C	-3.62	PASS	
16QAM	1880	+10 °C	-2.12	PASS	
		+20 °C	-2.30	PASS	
		+30 °C	-2.32	PASS	
		+40 °C	-3.89	PASS	
		+50 °C	-3.35	PASS	

Report No.: WT168006225 Page 549 of 572

Measurement Results vs. Variation of Voltage—LTE Band 2(20MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	2.32	PASS
QPSK	1880	3.7	-2.72	PASS
		4.2	-2.23	PASS
		3.5	1.90	PASS
16QAM	1880	3.7	-3.23	PASS
		4.2	-3.65	PASS

Measurement Results vs. Variation of Temperature—LTE Band 2(20MHZ)

IVI	easurement ives	suits vs. variation	or remperature	LTE Ballu 2(20MITZ)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	, ,	-30 °C	1.07	PASS
		-20 °C	0.24	PASS
		-10 °C	0.93	PASS
		0 °C	1.53	PASS
QPSK	1880	+10 °C	-4.18	PASS
		+20 °C	-3.71	PASS
		+30 °C	-3.75	PASS
		+40 °C	-1.86	PASS
		+50 °C	-2.89	PASS
		-30 °C	-2.79	PASS
		-20 °C	-2.76	PASS
		-10 °C	-2.88	PASS
		0 °C	-0.10	PASS
16QAM	1880	+10 °C	0.07	PASS
		+20 °C	0.26	PASS
		+30 °C	0.99	PASS
		+40 °C	-2.85	PASS
		+50 °C	-3.16	PASS

Report No.: WT168006225 Page 550 of 572

Measurement Results vs. Variation of Voltage—LTE Band 4(1.4MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	1.73	PASS
QPSK	1732.5	3.7	-1.57	PASS
		4.2	-4.22	PASS
		3.5	3.30	PASS
16QAM	1732.5	3.7	0.87	PASS
		4.2	-3.93	PASS

Measurement Results vs. Variation of Temperature—LTE Band 4(1.4MHZ)

inicasarcinent results vs. variation of remperature ETE band +(1.410112)				
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	, ,	-30 °C	2.39	PASS
		-20 °C	1.65	PASS
		-10 °C	0.76	PASS
		0 °C	0.86	PASS
QPSK	1732.5	+10 °C	0.92	PASS
		+20 °C	0.63	PASS
		+30 °C	-0.62	PASS
		+40 °C	-0.76	PASS
		+50 °C	-1.86	PASS
		-30 °C	-1.27	PASS
		-20 °C	-2.03	PASS
		-10 °C	-1.66	PASS
		0 °C	0.99	PASS
16QAM	1732.5	+10 °C	3.43	PASS
		+20 °C	3.22	PASS
		+30 °C	2.90	PASS
		+40 °C	1.16	PASS
		+50 °C	0.60	PASS

Report No.: WT168006225 Page 551 of 572

Measurement Results vs. Variation of Voltage—LTE Band 4(3MHZ)

Modulation	Nominal Frequency	Voltage	Measured Frequency	Verdict
	(MHz)	[Vdc]	Error(Hz)	
		3.5	0.70	PASS
QPSK	1732.5	3.7	0.53	PASS
		4.2	-0.51	PASS
		3.5	0.97	PASS
16QAM	1732.5	3.7	-0.86	PASS
		4.2	1.52	PASS

Measurement Results vs. Variation of Temperature—LTE Band 4(3MHZ)

Measurement Results vs. Variation of Temperature—LTE Band 4(3MHZ)				
Modulation	Nominal Frequency	Temperature	Measured Frequency Error(Hz)	Verdict
	(MHz)	-30 °C	, ,	DACC
			0.33	PASS
		-20 °C	-2.17	PASS
		-10 °C	-0.59	PASS
		0 °C	2.36	PASS
QPSK	1732.5	+10 °C	3.22	PASS
		+20 °C	-0.76	PASS
		+30 °C	1.09	PASS
		+40 °C	-2.52	PASS
		+50 °C	-0.92	PASS
		-30 °C	3.33	PASS
		-20 °C	-0.93	PASS
		-10 °C	1.02	PASS
		0 °C	0.86	PASS
16QAM	1732.5	+10 °C	-2.35	PASS
		+20 °C	1.29	PASS
		+30 °C	2.46	PASS
		+40 °C	2.86	PASS
		+50 °C	2.66	PASS

Report No.: WT168006225 Page 552 of 572

Measurement Results vs. Variation of Voltage—LTE Band 4(5MHZ)

	mode an emerit it to eather the familiarity of the target is a first term of the target is a fir				
Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict	
		3.5	0.87	PASS	
QPSK	1732.5	3.7	-0.66	PASS	
		4.2	1.50	PASS	
		3.5	-1.26	PASS	
16QAM	1732.5	3.7	1.03	PASS	
		4.2	1.12	PASS	

Measurement Results vs. Variation of Temperature—LTE Band 4(5MHZ)

101	icasarcinent rec	dito vo. variation	of remperature Lit	Dana +(OIVII IZ)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
		-30 °C	0.11	PASS
		-20 °C	0.96	PASS
		-10 °C	0.97	PASS
		0 °C	1.29	PASS
QPSK	1732.5	+10 °C	0.43	PASS
		+20 °C	0.49	PASS
		+30 °C	1.39	PASS
		+40 °C	0.79	PASS
		+50 °C	-0.74	PASS
		-30 °C	-0.80	PASS
		-20 °C	-0.37	PASS
		-10 °C	-1.27	PASS
		0 °C	-0.29	PASS
16QAM	1732.5	+10 °C	0.69	PASS
		+20 °C	0.13	PASS
		+30 °C	-1.93	PASS
		+40 °C	-0.72	PASS
		+50 °C	-0.11	PASS

Report No.: WT168006225 Page 553 of 572

Measurement Results vs. Variation of Voltage—LTE Band 4(10MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	0.46	PASS
QPSK	1732.5	3.7	0.70	PASS
		4.2	1.44	PASS
		3.5	-0.63	PASS
16QAM	1732.5	3.7	0.50	PASS
		4.2	0.14	PASS

Measurement Results vs. Variation of Temperature—LTE Band 4(10MHZ)

Wedderenter Reddite ver variation of remperature ETE Band ((1011/12)				
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	, ,	-30 °C	1.00	PASS
		-20 °C	0.04	PASS
		-10 °C	0.26	PASS
		0 °C	0.09	PASS
QPSK	1732.5	+10 °C	0.99	PASS
		+20 °C	0.53	PASS
		+30 °C	0.79	PASS
		+40 °C	0.40	PASS
		+50 °C	0.57	PASS
		-30 °C	0.23	PASS
		-20 °C	0.90	PASS
		-10 °C	-1.22	PASS
		0 °C	0.62	PASS
16QAM	1732.5	+10 °C	-0.04	PASS
		+20 °C	-0.66	PASS
		+30 °C	-0.41	PASS
		+40 °C	0.04	PASS
		+50 °C	-0.66	PASS

Report No.: WT168006225 Page 554 of 572

Measurement Results vs. Variation of Voltage—LTE Band 4(15MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-1.04	PASS
QPSK	1732.5	3.7	0.64	PASS
		4.2	-0.09	PASS
		3.5	0.30	PASS
16QAM	1732.5	3.7	-0.70	PASS
		4.2	-0.10	PASS

Measurement Results vs. Variation of Temperature—LTE Band 4(15MHZ)

IV	easurement ives	sults vs. variation	or remperature	LTE Band 4(15MHZ)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	(1711 12)	-30 °C	0.57	PASS
		-20 °C	-0.23	PASS
		-10 °C	-0.51	PASS
		0 °C	0.27	PASS
QPSK	1732.5	+10 °C	0.17	PASS
		+20 °C	-0.34	PASS
		+30 °C	-0.46	PASS
		+40 °C	0.76	PASS
		+50 °C	-0.04	PASS
		-30 °C	-0.06	PASS
		-20 °C	0.27	PASS
		-10 °C	-0.36	PASS
		0 °C	0.37	PASS
16QAM	1732.5	+10 °C	0.01	PASS
		+20 °C	0.26	PASS
		+30 °C	0.37	PASS
		+40 °C	0.17	PASS
		+50 °C	0.13	PASS

Report No.: WT168006225 Page 555 of 572

Measurement Results vs. Variation of Voltage—LTE Band 4(20MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	0.89	PASS
QPSK	1732.5	3.7	-0.79	PASS
		4.2	1.76	PASS
		3.5	0.89	PASS
16QAM	1732.5	3.7	-0.79	PASS
		4.2	1.76	PASS

Measurement Results vs. Variation of Temperature—LTE Band 4(20MHZ)

Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
		-30 °C	0.00	PASS
		-20 °C	0.20	PASS
		-10 °C	0.09	PASS
		0 °C	0.74	PASS
QPSK	1732.5	+10 °C	0.39	PASS
		+20 °C	-0.21	PASS
		+30 °C	1.75	PASS
		+40 °C	-0.49	PASS
		+50 °C	0.54	PASS
		-30 °C	1.43	PASS
		-20 °C	0.80	PASS
		-10 °C	1.10	PASS
		0 °C	1.30	PASS
16QAM	1732.5	+10 °C	-0.51	PASS
		+20 °C	1.44	PASS
		+30 °C	0.01	PASS
		+40 °C	-0.01	PASS
		+50 °C	-0.96	PASS

Report No.: WT168006225 Page 556 of 572

Measurement Results vs. Variation of Voltage—LTE Band 5(1.4MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-0.10	PASS
QPSK	836.5	3.7	-0.19	PASS
		4.2	1.02	PASS
		3.5	-1.27	PASS
16QAM	836.5	3.7	-0.64	PASS
		4.2	-0.87	PASS

Measurement Results vs. Variation of Temperature—LTE Band 5(1.4MHZ)

IVIC	isurement ivesur	is vs. variation or	Temperature LTE ba	110 3(1.41VII 12)
Modulation	Nominal Frequency	Temperature	Measured Frequency	Verdict
	(MHz)		Error(Hz)	
		-30 °C	-0.07	PASS
		-20 °C	-0.03	PASS
		-10 °C	-0.20	PASS
		0 °C	-1.30	PASS
QPSK	836.5	+10 °C	0.24	PASS
		+20 °C	-1.53	PASS
		+30 °C	0.57	PASS
		+40 °C	-0.23	PASS
		+50 °C	-0.29	PASS
		-30 °C	0.23	PASS
		-20 °C	-0.34	PASS
		-10 °C	0.79	PASS
		0 °C	-0.96	PASS
16QAM	836.5	+10 °C	-1.42	PASS
		+20 °C	-0.96	PASS
		+30 °C	-0.90	PASS
		+40 °C	-1.72	PASS
		+50 °C	-1.29	PASS

Report No.: WT168006225 Page 557 of 572

Measurement Results vs. Variation of Voltage—LTE Band 5(3MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-0.11	PASS
QPSK	836.5	3.7	-0.63	PASS
		4.2	-1.04	PASS
		3.5	0.97	PASS
16QAM	836.5	3.7	0.44	PASS
		4.2	-1.40	PASS

Measurement Results vs. Variation of Temperature—LTE Band 5(3MHZ)

IVIE	Measurement Results vs. Variation of Temperature—LTE Band 5(3MHZ)				
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict	
	(IVIITIZ)	-30 °C	-1.60	PASS	
		-20 °C	0.49	PASS	
		-10 °C	0.37	PASS	
		0 °C	-1.47	PASS	
QPSK	836.5	+10 °C	0.16	PASS	
		+20 °C	-0.90	PASS	
		+30 °C	-0.64	PASS	
		+40 °C	-2.33	PASS	
		+50 °C	-1.65	PASS	
		-30 °C	-0.49	PASS	
		-20 °C	-1.47	PASS	
		-10 °C	-2.06	PASS	
		0 °C	-0.87	PASS	
16QAM	836.5	+10 °C	0.57	PASS	
		+20 °C	-0.96	PASS	
		+30 °C	-0.54	PASS	
		+40 °C	-0.63	PASS	
		+50 °C	-0.37	PASS	

Report No.: WT168006225 Page 558 of 572

Measurement Results vs. Variation of Voltage—LTE Band 5(5MHZ)

	modelitement resource for remarker or remarker				
Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict	
		3.5	-1.60	PASS	
QPSK	836.5	3.7	-1.09	PASS	
		4.2	-1.09	PASS	
		3.5	-2.15	PASS	
16QAM	836.5	3.7	0.17	PASS	
		4.2	-0.41	PASS	

Measurement Results vs. Variation of Temperature—LTE Band 5(5MHZ)

	casaroment rec	dito vo. variation	of remperature Err	- Daria O(Oivii 12)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	, ,	-30 °C	-1.47	PASS
		-20 °C	-1.76	PASS
		-10 °C	-1.89	PASS
		0 °C	-1.44	PASS
QPSK	836.5	+10 °C	0.50	PASS
		+20 °C	0.16	PASS
		+30 °C	-0.83	PASS
		+40 °C	0.60	PASS
		+50 °C	0.80	PASS
		-30 °C	-0.24	PASS
		-20 °C	0.49	PASS
		-10 °C	-0.74	PASS
		0 °C	-1.86	PASS
16QAM	836.5	+10 °C	-2.22	PASS
		+20 °C	-0.49	PASS
		+30 °C	-1.44	PASS
		+40 °C	0.47	PASS
		+50 °C	-0.62	PASS

Report No.: WT168006225 Page 559 of 572

Measurement Results vs. Variation of Voltage—LTE Band 5(10MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-1.69	PASS
QPSK	836.5	3.7	-0.39	PASS
		4.2	-0.76	PASS
		3.5	-1.86	PASS
16QAM	836.5	3.7	-0.96	PASS
		4.2	0.26	PASS

Measurement Results vs. Variation of Temperature—LTE Band 5(10MHZ)

Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
		-30 °C	-0.99	PASS
		-20 °C	-0.97	PASS
		-10 °C	-0.93	PASS
		0 °C	-1.02	PASS
QPSK	836.5	+10 °C	-1.63	PASS
		+20 °C	0.09	PASS
		+30 °C	1.06	PASS
		+40 °C	-0.11	PASS
		+50 °C	-1.49	PASS
		-30 °C	0.13	PASS
		-20 °C	-1.19	PASS
		-10 °C	-0.79	PASS
		0 °C	-0.39	PASS
16QAM	836.5	+10 °C	-0.53	PASS
		+20 °C	-0.83	PASS
		+30 °C	-0.96	PASS
		+40 °C	0.10	PASS
		+50 °C	-0.63	PASS

Report No.: WT168006225 Page 560 of 572

Measurement Results vs. Variation of Voltage—LTE Band 7(5MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	2.78	PASS
QPSK	2535	3.7	-0.44	PASS
		4.2	2.62	PASS
		3.5	1.34	PASS
16QAM	2535	3.7	-0.27	PASS
		4.2	1.43	PASS

Measurement Results vs. Variation of Temperature—LTE Band 7(5MHZ)

Wedsdreffert Results vs. Variation of Temperature ETE Band ((0))(12)				
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
		-30 °C	1.44	PASS
		-20 °C	3.06	PASS
		-10 °C	1.16	PASS
		0 °C	4.01	PASS
QPSK	2535	+10 °C	-5.68	PASS
		+20 °C	-4.26	PASS
		+30 °C	-1.80	PASS
		+40 °C	-2.02	PASS
		+50 °C	1.93	PASS
		-30 °C	1.69	PASS
		-20 °C	1.06	PASS
		-10 °C	1.50	PASS
		0 °C	2.60	PASS
16QAM	2535	+10 °C	2.92	PASS
		+20 °C	2.62	PASS
		+30 °C	2.45	PASS
		+40 °C	-2.02	PASS
		+50 °C	-4.09	PASS

Report No.: WT168006225 Page 561 of 572

Measurement Results vs. Variation of Voltage—LTE Band 7(10MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-4.46	PASS
QPSK	2535	3.7	-4.29	PASS
		4.2	-3.85	PASS
		3.5	-2.20	PASS
16QAM	2535	3.7	-4.43	PASS
		4.2	-3.25	PASS

Measurement Results vs. Variation of Temperature—LTE Band 7(10MHZ)

IV	ieasurement ives	suits vs. variation	or remperature—LTE	Janu / (TOIVII IZ)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	(1711 12)	-30 °C	-2.32	PASS
		-20 °C	-1.65	PASS
		-10 °C	-1.30	PASS
		0 °C	-2.95	PASS
QPSK	2535	+10 °C	-0.59	PASS
		+20 °C	-1.99	PASS
		+30 °C	-3.59	PASS
		+40 °C	0.13	PASS
		+50 °C	-1.70	PASS
		-30 °C	-3.00	PASS
		-20 °C	-3.18	PASS
		-10 °C	-3.12	PASS
		0 °C	-4.01	PASS
16QAM	2535	+10 °C	-4.36	PASS
		+20 °C	-0.92	PASS
		+30 °C	-4.06	PASS
		+40 °C	-5.19	PASS
		+50 °C	-3.96	PASS

Report No.: WT168006225 Page 562 of 572

Measurement Results vs. Variation of Voltage—LTE Band 7(15MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	1.22	PASS
QPSK	2535	3.7	-1.97	PASS
		4.2	0.01	PASS
		3.5	0.23	PASS
16QAM	2535	3.7	-1.30	PASS
		4.2	3.93	PASS

Measurement Results vs. Variation of Temperature—LTE Band 7(15MHZ)

IV	easurement ives	suits vs. variation	or remperature	LIL Dand / (131VII 12)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
		-30 °C	0.50	PASS
		-20 °C	-1.89	PASS
		-10 °C	-0.24	PASS
		0 °C	0.00	PASS
QPSK	2535	+10 °C	-2.76	PASS
		+20 °C	-1.39	PASS
		+30 °C	-4.63	PASS
		+40 °C	-1.66	PASS
		+50 °C	1.43	PASS
		-30 °C	-0.73	PASS
		-20 °C	1.33	PASS
		-10 °C	1.26	PASS
		0 °C	-0.37	PASS
16QAM	2535	+10 °C	-1.27	PASS
		+20 °C	-1.26	PASS
		+30 °C	0.40	PASS
		+40 °C	-4.55	PASS
		+50 °C	-4.45	PASS

Report No.: WT168006225 Page 563 of 572

Measurement Results vs. Variation of Voltage—LTE Band 7(20MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	3.76	PASS
QPSK	2535	3.7	1.12	PASS
		4.2	1.59	PASS
		3.5	-0.47	PASS
16QAM	2535	3.7	-1.89	PASS
		4.2	2.06	PASS

Measurement Results vs. Variation of Temperature—LTE Band 7(20MHZ)

Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	, ,	-30 °C	1.99	PASS
		-20 °C	4.13	PASS
		-10 °C	0.34	PASS
		0 °C	0.97	PASS
QPSK	2535	+10 °C	-2.23	PASS
		+20 °C	-3.75	PASS
		+30 °C	-1.97	PASS
		+40 °C	-1.50	PASS
		+50 °C	-1.63	PASS
		-30 °C	1.17	PASS
		-20 °C	0.96	PASS
		-10 °C	-1.63	PASS
		0 °C	2.32	PASS
16QAM	2535	+10 °C	0.49	PASS
		+20 °C	-0.54	PASS
		+30 °C	4.02	PASS
		+40 °C	-1.90	PASS
		+50 °C	-1.40	PASS

Report No.: WT168006225 Page 564 of 572

Measurement Results vs. Variation of Voltage—LTE Band 12(1.4MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-0.24	PASS
QPSK	707.5	3.7	-0.30	PASS
		4.2	-0.84	PASS
		3.5	-0.57	PASS
16QAM	707.5	3.7	-1.32	PASS
		4.2	-0.33	PASS

Measurement Results vs. Variation of Temperature—LTE Band 12(1.4MHZ)

Modeuroment Reduite vo. Vanation of Temperature 212 Band 12(1: 111112)				
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	, ,	-30 °C	-0.74	PASS
		-20 °C	0.29	PASS
		-10 °C	-0.70	PASS
		0 °C	0.34	PASS
QPSK	707.5	+10 °C	-1.02	PASS
		+20 °C	-0.70	PASS
		+30 °C	-0.06	PASS
		+40 °C	-0.47	PASS
		+50 °C	0.49	PASS
		-30 °C	-0.62	PASS
		-20 °C	0.24	PASS
		-10 °C	-0.69	PASS
		0 °C	0.67	PASS
16QAM	707.5	+10 °C	-0.37	PASS
		+20 °C	1.26	PASS
		+30 °C	0.89	PASS
		+40 °C	-1.72	PASS
		+50 °C	-1.97	PASS

Report No.: WT168006225 Page 565 of 572

Measurement Results vs. Variation of Voltage—LTE Band 12(3MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-1.00	PASS
QPSK	707.5	3.7	-0.66	PASS
		4.2	-0.34	PASS
		3.5	-2.42	PASS
16QAM	707.5	3.7	-0.13	PASS
		4.2	0.47	PASS

Measurement Results vs. Variation of Temperature—LTE Band 12(3MHZ)

IVI	easurement ives	dits vs. variation	oi remperature i	LIE Ballu 12(SIVINZ)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	(1411 12)	-30 °C	-1.02	PASS
		-20 °C	-2.56	PASS
		-10 °C	-1.70	PASS
		0 °C	0.27	PASS
QPSK	707.5	+10 °C	-1.63	PASS
		+20 °C	-1.37	PASS
		+30 °C	-1.17	PASS
		+40 °C	0.41	PASS
		+50 °C	-0.34	PASS
		-30 °C	-1.00	PASS
		-20 °C	0.03	PASS
		-10 °C	-2.80	PASS
		0 °C	-3.02	PASS
16QAM	707.5	+10 °C	-0.73	PASS
		+20 °C	-0.37	PASS
		+30 °C	-0.26	PASS
		+40 °C	-1.63	PASS
		+50 °C	0.04	PASS

Report No.: WT168006225 Page 566 of 572

Measurement Results vs. Variation of Voltage—LTE Band 12(5MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	0.40	PASS
QPSK	707.5	3.7	-0.63	PASS
		4.2	-0.73	PASS
		3.5	-1.19	PASS
16QAM	707.5	3.7	0.63	PASS
		4.2	-0.63	PASS

Measurement Results vs. Variation of Temperature—LTE Band 12(5MHZ)

				ETE Bana TZ(OMTIZ)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	, ,	-30 °C	-0.82	PASS
		-20 °C	-1.43	PASS
		-10 °C	-1.39	PASS
		0 °C	-0.93	PASS
QPSK	707.5	+10 °C	-0.04	PASS
		+20 °C	-0.06	PASS
		+30 °C	-0.30	PASS
		+40 °C	-0.21	PASS
		+50 °C	-0.14	PASS
		-30 °C	-0.53	PASS
		-20 °C	0.63	PASS
		-10 °C	-1.72	PASS
		0 °C	-0.16	PASS
16QAM	707.5	+10 °C	-0.27	PASS
		+20 °C	-0.86	PASS
		+30 °C	-0.26	PASS
		+40 °C	-0.39	PASS
		+50 °C	-1.40	PASS

Report No.: WT168006225 Page 567 of 572

Measurement Results vs. Variation of Voltage—LTE Band 12(10MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-0.41	PASS
QPSK	707.5	3.7	-1.27	PASS
		4.2	-0.64	PASS
		3.5	-1.33	PASS
16QAM	707.5	3.7	-1.56	PASS
		4.2	-2.47	PASS

Measurement Results vs. Variation of Temperature—LTE Band 12(10MHZ)

IV	leasurement ives	builo vo. Varialiori	or remperature—LTE	Janu 12(10m112)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	(1411 12)	-30 °C	-1.23	PASS
		-20 °C	-1.75	PASS
		-10 °C	-0.41	PASS
		0 °C	-0.96	PASS
QPSK	707.5	+10 °C	-0.21	PASS
		+20 °C	-1.52	PASS
		+30 °C	-0.74	PASS
		+40 °C	0.09	PASS
		+50 °C	-1.79	PASS
		-30 °C	-0.59	PASS
		-20 °C	-1.26	PASS
		-10 °C	-0.74	PASS
		0 °C	-0.93	PASS
16QAM	707.5	+10 °C	-1.46	PASS
		+20 °C	-1.73	PASS
		+30 °C	0.31	PASS
		+40 °C	-0.46	PASS
		+50 °C	-1.53	PASS

Report No.: WT168006225 Page 568 of 572

Measurement Results vs. Variation of Voltage—LTE Band 13(5MHZ)

mode and more than the following the first territory				
Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-0.41	PASS
QPSK	782	3.7	-1.47	PASS
		4.2	-0.41	PASS
		3.5	-0.80	PASS
16QAM	782	3.7	-0.64	PASS
		4.2	-0.40	PASS

Measurement Results vs. Variation of Temperature—LTE Band 13(5MHZ)

IVI	easurement ives	builo vo. Varialiori	or remperature	
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	(1711 12)	-30 °C	-0.21	PASS
		-20 °C	-0.43	PASS
		-10 °C	-1.10	PASS
		0 °C	-1.06	PASS
QPSK	782	+10 °C	-0.60	PASS
		+20 °C	-0.51	PASS
		+30 °C	-0.17	PASS
		+40 °C	-1.04	PASS
		+50 °C	0.39	PASS
		-30 °C	-0.96	PASS
		-20 °C	0.41	PASS
		-10 °C	-0.50	PASS
		0 °C	-0.41	PASS
16QAM	782	+10 °C	-1.20	PASS
		+20 °C	-0.60	PASS
		+30 °C	-0.46	PASS
		+40 °C	-0.24	PASS
		+50 °C	0.10	PASS

Report No.: WT168006225 Page 569 of 572

Measurement Results vs. Variation of Voltage—LTE Band 13(10MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-0.47	PASS
QPSK	782	3.7	-0.16	PASS
		4.2	-0.63	PASS
		3.5	-0.76	PASS
16QAM	782	3.7	-1.49	PASS
		4.2	0.26	PASS

Measurement Results vs. Variation of Temperature—LTE Band 13(10MHZ)

IVI	easurement ives	dits vs. variation	or remperature	LTE Band 13(10MHZ)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	(1711 12)	-30 °C	-1.06	PASS
		-20 °C	-1.80	PASS
		-10 °C	0.11	PASS
		0 °C	-1.12	PASS
QPSK	782	+10 °C	-1.86	PASS
		+20 °C	-1.42	PASS
		+30 °C	-0.80	PASS
		+40 °C	-0.63	PASS
		+50 °C	-1.27	PASS
		-30 °C	-0.33	PASS
		-20 °C	-1.73	PASS
		-10 °C	-0.69	PASS
		0 °C	-0.40	PASS
16QAM	782	+10 °C	0.73	PASS
		+20 °C	-0.07	PASS
		+30 °C	0.59	PASS
		+40 °C	-1.29	PASS
		+50 °C	-1.00	PASS

Report No.: WT168006225 Page 570 of 572

Measurement Results vs. Variation of Voltage—LTE Band 17(5MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-1.46	PASS
QPSK	710	3.7	0.43	PASS
		4.2	-1.26	PASS
		3.5	-1.66	PASS
16QAM	710	3.7	-0.53	PASS
		4.2	-1.87	PASS

Measurement Results vs. Variation of Temperature—LTE Band 17(5MHZ)

IVI	easurement ives	sults vs. variation	or remperature i	LIE Ballu IT (SIVINZ)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	(1411 12)	-30 °C	-0.60	PASS
		-20 °C	-1.69	PASS
		-10 °C	-2.02	PASS
		0 °C	-2.96	PASS
QPSK	710	+10 °C	-0.06	PASS
		+20 °C	-0.07	PASS
		+30 °C +40 °C	-0.99	PASS
			0.40	PASS
		+50 °C	-0.46	PASS
		-30 °C	0.34	PASS
		-20 °C	0.04	PASS
		-10 °C	-0.83	PASS
		0 °C	-2.39	PASS
16QAM	710	+10 °C	-2.03	PASS
		+20 °C	-0.41	PASS
		+30 °C	-1.56	PASS
		+40 °C	0.27	PASS
		+50 °C	-0.54	PASS

Report No.: WT168006225 Page 571 of 572

Measurement Results vs. Variation of Voltage—LTE Band 17(10MHZ)

Modulation	Nominal Frequency (MHz)	Voltage [Vdc]	Measured Frequency Error(Hz)	Verdict
		3.5	-0.97	PASS
QPSK	710	3.7	-0.93	PASS
		4.2	-0.94	PASS
		3.5	-1.79	PASS
16QAM	710	3.7	0.10	PASS
		4.2	-0.33	PASS

Measurement Results vs. Variation of Temperature—LTE Band 17(10MHZ)

IVI	easurement ives	builo vo. Varialiori	or remperature—LTE	band 17 (10101112)
Modulation	Nominal Frequency (MHz)	Temperature	Measured Frequency Error(Hz)	Verdict
	(1011 12)	-30 °C	-0.31	PASS
		-20 °C	-0.11	PASS
		-10 °C	-0.97	PASS
		0 °C	-0.73	PASS
QPSK	710	+10 °C	0.14	PASS
		+20 °C	-0.07	PASS
		+30 °C	-0.67	PASS
		+40 °C -0.59	-0.59	PASS
		+50 °C	-2.45	PASS
		-30 °C	-1.13	PASS
		-20 °C	-0.79	PASS
		-10 °C	-2.07	PASS
		0 °C	-0.72	PASS
16QAM	710	+10 °C	-1.44	PASS
		+20 °C	-0.83	PASS
		+30 °C	-2.57	PASS
		+40 °C	-0.30	PASS
		+50 °C	0.16	PASS

Report No.: WT168006225 Page 572 of 572