



TEST REPORT

No. I15Z43271-EMC01

for

TCL Communication Ltd

HSUPA/HSDPA/UMTS Tri-band/GSM Quad-band mobile phone

Model Name: 4017F

FCC ID: 2ACCJH041

with

Hardware Version: PIO

Software Version: vBL43

Issued Date: 2016-01-12

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

FCC 2.948 Listed: No.525429

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: cttl_terminals@catr.cn, website: www.chinattl.com



REPORT HISTORY

| Report Number | Revision | Description | Issue Date |
|-----------------|----------|-------------|------------|
| I15Z43271-EMC01 | Rev.0 | 1st edition | 2016-01-12 |

CONTENTS

| | |
|---|-----------|
| 1. TEST LABORATORY..... | 4 |
| 1.1. TESTING LOCATION | 4 |
| 1.2. TESTING ENVIRONMENT | 4 |
| 1.3. PROJECT DATA..... | 4 |
| 1.4. SIGNATURE | 4 |
| 2. CLIENT INFORMATION..... | 5 |
| 2.1. APPLICANT INFORMATION..... | 5 |
| 2.2. MANUFACTURER INFORMATION..... | 5 |
| 3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) | 6 |
| 3.1. ABOUT EUT | 6 |
| 3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST | 6 |
| 3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST..... | 6 |
| 3.4. EUT SET-UPS | 8 |
| 4. REFERENCE DOCUMENTS | 8 |
| 4.1. REFERENCE DOCUMENTS FOR TESTING..... | 8 |
| 5. LABORATORY ENVIRONMENT | 9 |
| 6. SUMMARY OF TEST RESULTS..... | 10 |
| 7. TEST EQUIPMENTS UTILIZED..... | 11 |
| ANNEX A: MEASUREMENT RESULTS | 12 |

1. Test Laboratory

1.1. Testing Location

Location 1: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China 100191

1.2. Testing Environment

Normal Temperature: 15-35□

Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2015-12-30

Testing End Date: 2016-01-05

1.4. Signature




Zhang Ying

(Prepared this test report)



Qu Pengfei

(Reviewed this test report)



Liu Baodian

(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Postal Code: 201203
Country: China
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@tcl.com
Telephone: 0086-21-51798260
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-51798260
Fax: 0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

| | |
|---------------------|--|
| Description | HSUPA/HSDPA/UMTS Tri-band/GSM Quad-band mobile phone |
| Model Name | 4017F |
| FCC ID | 2ACCJH041 |
| Extreme vol. Limits | 3.5VDC to 4.2VDC (nominal: 3.8VDC) |

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT.

3.2. Internal Identification of EUT used during the test

| EUT ID* | SN or IMEI | HW Version | SW Version |
|---------|------------|------------|------------|
| EUT1 | / | PIO | vBL43 |

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

| AE ID* | Description | SN | Remarks |
|--------|----------------|------------------|---------------|
| AE1 | battery | BP759T9803T000H3 | 15TCT-BA-0721 |
| AE2 | battery | BP759T9803T000D2 | 15TCT-BA-0719 |
| AE3 | battery | BP759T9803T000H5 | 15TCT-BA-0722 |
| AE4 | battery | BP759T9803T000H0 | 15TCT-BA-0717 |
| AE5 | Travel Charger | / | 15TCT-CH-0170 |
| AE6 | Travel Charger | / | 15TCT-CH-1001 |
| AE7 | Travel Charger | / | 15TCT-CH-0135 |
| AE8 | Travel Charger | / | 14TCT-CH-1918 |
| AE9 | USB Cable | / | 14TCT-DC-0043 |
| AE10 | USB Cable | / | 15TCT-DC-0101 |
| AE11 | USB Cable | / | 15TCT-DC-0186 |
| AE12 | USB Cable | / | 15TCT-DC-0186 |
| AE13 | Travel Charger | / | 15TCT-CH-0167 |
| AE14 | Travel Charger | / | 15TCT-CH-1132 |
| AE16 | Travel Charger | / | 14TCT-CH-2198 |
| AE17 | USB Cable | / | 14TCT-DC-0258 |
| AE18 | USB Cable | / | 15TCT-DC-0186 |



AE1, AE2, AE3, AE4

| | |
|-----------------|-----------------------------------|
| Model | TLi013A7 |
| Manufacturer | Zhongshan Tianmao Battery Co.,Ltd |
| Capacitance | 1300mAh |
| Nominal voltage | 3.7V |

AE5, AE13

| | |
|-----------------|--------------|
| Type | CBA0066AG0C1 |
| Manufacturer | BYD |
| Length of cable | 124cm |

AE6

| | |
|-----------------|--------------|
| Type | CBA3002AG0C5 |
| Manufacturer | Puan |
| Length of cable | 118cm |

AE7, AE14

| | |
|-----------------|--------------|
| Type | CBA3068AG0C1 |
| Manufacturer | BYD |
| Length of cable | / |

AE8, AE16

| | |
|-----------------|--------------|
| Type | CBA3008AG0C2 |
| Manufacturer | Tenpao |
| Length of cable | / |

AE9, AE17

| | |
|-----------------|--------------|
| Type | CDA3122002C1 |
| Manufacturer | Juwei |
| Length of cable | 101cm |

AE10, AE18

| | |
|-----------------|--------------|
| Type | CDA3122002C8 |
| Manufacturer | PUAN |
| Length of cable | 99cm |

AE11

| | |
|-----------------|--------------|
| Type | CDA3122005C1 |
| Manufacturer | JUWEI |
| Length of cable | / |

AE12

| | |
|-----------------|--------------|
| Type | CDA3122005C8 |
| Manufacturer | PUAN |
| Length of cable | / |

*AE ID: is used to identify the test sample in the lab internally.

3.4. EUT set-ups

| EUT set-up No. | Combination of EUT and AE | Remarks |
|----------------|---------------------------|---------|
| Set.2 | EUT2 + AE4 + AE5 | Charger |
| Set.3 | EUT2 + AE4 + AE6 | Charger |
| Set.4 | EUT2 + AE4 + AE7 + AE9 | Charger |
| Set.5 | EUT2 + AE4 + AE8 + AE10 | Charger |
| Set.6 | EUT2 + AE4 + AE9 | USB |

Note:

HSUPA/HSDPA/UMTS Tri-band/GSM Quad-band mobile phone 4017F manufactured by TCL Communication Ltd is a variant model based on 4017A for conformance test. According to the declaration of changes, the results are inherited from the initial model. The report number of initial model is I15Z43226-EMC01.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

| Reference | Title | Version |
|------------------------|---|--------------------|
| FCC Part 15, Subpart B | Radio frequency devices - Unintentional Radiators | 10-1-14 Edition |
| ANSI C63.4 | Methods of Measurement of Radio-Noise Emissions from Low - Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz | 2014 |

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber SAC-1 (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

| | |
|---|---|
| Temperature | Min. = 15 °C, Max. = 35 °C |
| Relative humidity | Min. = 15 %, Max. = 75 % |
| Shielding effectiveness | 0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB. |
| Electrical insulation | > 2 MΩ |
| Ground system resistance | < 4Ω |
| Normalised site attenuation (NSA) | < ± 4 dB, 3m/10m distance, from 30 to 1000 MHz |
| Site voltage standing-wave ratio (S_{VSWR}) | Between 0 and 6 dB, from 1GHz to 18GHz |
| Uniformity of field strength | Between 0 and 6 dB, from 80 to 3000 MHz |

Shielded room did not exceed following limits along the EMC testing:

| | |
|--------------------------|---|
| Temperature | Min. = 15 °C, Max. = 35 °C |
| Relative humidity | Min. = 20 %, Max. = 75 % |
| Shielding effectiveness | 0.014MHz-1MHz, >60dB; 1MHz—1000MHz, >90dB. |
| Electrical insulation | > 2 MΩ |
| Ground system resistance | < 4 Ω |

6. SUMMARY OF TEST RESULTS

| Abbreviations used in this clause: | | |
|------------------------------------|---------|---|
| Verdict Column | P | Pass |
| | NA | Not applicable |
| | F | Fail |
| Location Column | 1/2/3/4 | The test is performed in test location 1, 2, 3 or 4 which are described in section 1.1 of this report |

| Items | Test Name | Clause in FCC rules | Section in this report | Verdict | Test Location |
|-------|--------------------|---------------------|------------------------|---------|---------------|
| 1 | Radiated Emission | 15.109(a) | B.1 | P | 1 |
| 2 | Conducted Emission | 15.107(a) | B.2 | P | 1 |

7. Test Equipments Utilized

| NO. | NAME | TYPE | SERIES NUMBER | PRODUCER | CAL. DUE DATE | CAL. INTERVAL |
|-----|---|-----------------|------------------|--------------|------------------|------------------|
| 1. | EMI Antenna | VULB9163 | 9163-301 | Schwarzbeck | 2017-12-16 | 3 Years |
| 2. | Test Receiver | ESU26 | 100235 | R&S | 2016-03-02 | 1 Year |
| 3. | EMI Antenna | 3115 | 6914 | ETS-Lindgren | 2016-12-15 | 3 Years |
| 4. | Test Receiver for Conducted Emission | ESCI 7 | 100948 | R&S | 2016-07-07 | 1 Year |
| 5. | LISN | ENV216 | 101200 | R&S | 2016-07-07 | 1 Year |
| 6. | Universal Radio Communication Tester | CMU200 | 109914 | R&S | 2016-03-26 | 1 Year |
| 7. | PC | OPTIPLEX 380 | 2X1YV2X | Dell | / | / |
| 8. | Printer | P160dn | VNC3L52122 | HP | / | / |

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission

Reference

FCC: CFR Part 15.109(a).

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (charging mode of MS) at distances of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 - 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode:

The MS is operating in the charging mode.

For the charging mode, the EUT is keeping on playing MP3 file.

A.1.3 Measurement Limit

| Frequency range (MHz) | Field strength limit (μV/m) | | |
|--------------------------|-----------------------------|---------|------|
| | Quasi-peak | Average | Peak |
| 30-88 | 100 | | |
| 88-216 | 150 | | |
| 216-960 | 200 | | |
| 960-1000 | 500 | | |
| >1000 | | 500 | 5000 |

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

A.1.4 Test Condition

| Frequency range (MHz) | RBW/VBW | Sweep Time (s) | Detector |
|-----------------------|-----------------------|----------------|-----------------|
| 30-1000 | 120kHz (IF Bandwidth) | 5 | Peak/Quasi-peak |
| Above 1000 | 1MHz/1MHz | 15 | Peak, Average |

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.
Measurement uncertainty (worst case): $U = 5.0 \text{ dB}$, $k=2$.

Measurement results for Set.2:

Charging Mode/Average detector

| Frequency(MHz) | Result(dB μ V/m) | G_{PL} (dB) | G_A (dB/m) | P_{Mea} (dB μ V) | Polarity |
|----------------|----------------------|---------------|--------------|------------------------|----------|
| 17889.500 | 51.2 | -18.5 | 45.6 | 24.100 | H |
| 17892.900 | 51.0 | -18.5 | 45.6 | 23.900 | V |
| 17940.500 | 50.8 | -17.7 | 45.6 | 22.900 | V |
| 17984.700 | 50.6 | -17.7 | 45.6 | 22.700 | H |
| 17956.650 | 50.5 | -17.7 | 45.6 | 22.600 | H |
| 17690.600 | 50.4 | -18.9 | 45.6 | 23.700 | H |

Charging Mode/Peak detector

| Frequency(MHz) | Result(dB μ V/m) | G_{PL} (dB) | G_A (dB/m) | P_{Mea} (dB μ V) | Polarity |
|----------------|----------------------|---------------|--------------|------------------------|----------|
| 17971.100 | 61.1 | -17.7 | 45.6 | 33.200 | V |
| 17906.500 | 60.9 | -18.5 | 45.6 | 33.800 | V |
| 17977.900 | 60.9 | -17.7 | 45.6 | 33.000 | H |
| 17995.750 | 60.9 | -17.7 | 45.6 | 33.000 | V |
| 17690.600 | 60.8 | -18.9 | 45.6 | 34.100 | V |
| 17781.550 | 60.5 | -18.5 | 45.6 | 33.400 | H |

Measurement results for Set.3:
Charging Mode/Average detector

| Frequency(MHz) | Result(dB μ V/m) | G _{PL} (dB) | G _A (dB/m) | P _{Mea} (dB μ V) | Polarity |
|----------------|----------------------|----------------------|-----------------------|-------------------------------|----------|
| 17948.150 | 50.6 | -17.7 | 45.6 | 22.700 | H |
| 17908.200 | 50.4 | -18.5 | 45.6 | 23.300 | V |
| 17930.300 | 50.4 | -17.7 | 45.6 | 22.500 | H |
| 17932.850 | 50.4 | -17.7 | 45.6 | 22.500 | V |
| 17859.750 | 50.3 | -18.5 | 45.6 | 23.200 | V |
| 17867.400 | 50.3 | -18.5 | 45.6 | 23.200 | H |

Charging Mode/Peak detector

| Frequency(MHz) | Result(dB μ V/m) | G _{PL} (dB) | G _A (dB/m) | P _{Mea} (dB μ V) | Polarity |
|----------------|----------------------|----------------------|-----------------------|-------------------------------|----------|
| 17994.050 | 61.0 | -17.7 | 45.6 | 33.100 | V |
| 17686.350 | 60.8 | -18.9 | 45.6 | 34.100 | H |
| 17450.050 | 60.8 | -19.2 | 41.5 | 38.500 | H |
| 17988.950 | 60.5 | -17.7 | 45.6 | 32.600 | V |
| 17829.150 | 60.3 | -18.5 | 45.6 | 33.200 | V |
| 17982.150 | 60.3 | -17.7 | 45.6 | 32.400 | V |

Measurement results for Set.4:
Charging Mode/Average detector

| Frequency(MHz) | Result(dB μ V/m) | G _{PL} (dB) | G _A (dB/m) | P _{Mea} (dB μ V) | Polarity |
|----------------|----------------------|----------------------|-----------------------|-------------------------------|----------|
| 17958.350 | 50.5 | -17.7 | 45.6 | 22.600 | V |
| 17953.250 | 50.5 | -17.7 | 45.6 | 22.600 | H |
| 17943.900 | 50.5 | -17.7 | 45.6 | 22.600 | V |
| 17993.200 | 50.4 | -17.7 | 45.6 | 22.500 | V |
| 17939.650 | 50.4 | -17.7 | 45.6 | 22.500 | H |
| 17988.950 | 50.3 | -17.7 | 45.6 | 22.400 | H |

Charging Mode/Peak detector

| Frequency(MHz) | Result(dB μ V/m) | G _{PL} (dB) | G _A (dB/m) | P _{Mea} (dB μ V) | Polarity |
|----------------|----------------------|----------------------|-----------------------|-------------------------------|----------|
| 17973.650 | 60.7 | -17.7 | 45.6 | 32.800 | H |
| 17937.100 | 60.7 | -17.7 | 45.6 | 32.800 | V |
| 17910.750 | 60.7 | -18.5 | 45.6 | 33.600 | V |
| 17888.650 | 60.7 | -18.5 | 45.6 | 33.600 | H |
| 17965.150 | 60.5 | -17.7 | 45.6 | 32.600 | V |
| 17762.000 | 60.5 | -18.5 | 45.6 | 33.400 | H |

Measurement results for Set.5:
Charging Mode/Average detector

| Frequency(MHz) | Result(dB μ V/m) | G _{PL} (dB) | G _A (dB/m) | P _{Mea} (dB μ V) | Polarity |
|----------------|----------------------|----------------------|-----------------------|-------------------------------|----------|
| 17960.050 | 51.2 | -17.7 | 45.6 | 23.300 | V |
| 17926.050 | 51.0 | -17.7 | 45.6 | 23.100 | V |
| 17905.650 | 50.9 | -18.5 | 45.6 | 23.800 | H |
| 17970.250 | 50.6 | -17.7 | 45.6 | 22.700 | V |
| 17933.700 | 50.5 | -17.7 | 45.6 | 22.600 | V |
| 17832.550 | 50.5 | -18.5 | 45.6 | 23.400 | H |

Charging Mode/Peak detector

| Frequency(MHz) | Result(dB μ V/m) | G _{PL} (dB) | G _A (dB/m) | P _{Mea} (dB μ V) | Polarity |
|----------------|----------------------|----------------------|-----------------------|-------------------------------|----------|
| 17904.800 | 62.4 | -18.5 | 45.6 | 35.300 | V |
| 17967.700 | 61.9 | -17.7 | 45.6 | 34.000 | H |
| 17958.350 | 61.8 | -17.7 | 45.6 | 33.900 | H |
| 17992.350 | 61.5 | -17.7 | 45.6 | 33.600 | V |
| 17898.850 | 61.4 | -18.5 | 45.6 | 34.300 | V |
| 17800.250 | 61.1 | -18.5 | 45.6 | 34.000 | H |

Measurement results for Set.6:
USB Mode/Average detector

| Frequency(MHz) | Result(dB μ V/m) | G _{PL} (dB) | G _A (dB/m) | P _{Mea} (dB μ V) | Polarity |
|----------------|----------------------|----------------------|-----------------------|-------------------------------|----------|
| 17949.000 | 50.7 | -17.7 | 45.6 | 22.800 | V |
| 17964.300 | 50.3 | -17.7 | 45.6 | 22.400 | H |
| 17988.100 | 50.3 | -17.7 | 45.6 | 22.400 | V |
| 17880.150 | 50.3 | -18.5 | 45.6 | 23.200 | H |
| 17903.100 | 50.3 | -18.5 | 45.6 | 23.200 | V |
| 17828.300 | 50.2 | -18.5 | 45.6 | 23.100 | V |

USB Mode/Peak detector

| Frequency(MHz) | Result(dB μ V/m) | G _{PL} (dB) | G _A (dB/m) | P _{Mea} (dB μ V) | Polarity |
|----------------|----------------------|----------------------|-----------------------|-------------------------------|----------|
| 17456.850 | 61.2 | -19.2 | 41.5 | 38.900 | H |
| 17964.300 | 60.9 | -17.7 | 45.6 | 33.000 | V |
| 17842.750 | 60.7 | -18.5 | 45.6 | 33.600 | V |
| 17784.950 | 60.7 | -18.5 | 45.6 | 33.600 | H |
| 17949.000 | 60.6 | -17.7 | 45.6 | 32.700 | V |
| 17865.700 | 60.6 | -18.5 | 45.6 | 33.500 | H |

Note: The measurement results of Set.2, Set.3, Set.4, Set.5 and Set.6 showed here are worst cases of the combinations of different batteries and USB cables.

Charging Mode, Set.2




Figure A.1 Radiated Emission from 30MHz to 1GHz




Figure A.2 Radiated Emission from 1GHz to 18GHz

Charging Mode, Set.3




Figure A.3 Radiated Emission from 30MHz to 1GHz




Figure A.4 Radiated Emission from 1GHz to 18GHz

Charging Mode, Set.4




Figure A.5 Radiated Emission from 30MHz to 1GHz




Figure A.6 Radiated Emission from 1GHz to 18GHz

Charging Mode, Set.5




Figure A.7 Radiated Emission from 30MHz to 1GHz

Final Result 1

| Frequency (MHz) | QuasiPeak (dBμV/m) | Height (cm) | Polarization | Azimuth (deg) | Corr. (dB) | Margin (dB) | Limit (dBμV/m) |
|-----------------|--------------------|-------------|--------------|---------------|------------|-------------|----------------|
| 72.063500 | 18.6 | 384.0 | V | 0.0 | -15.8 | 11.4 | 30.0 |




Figure A.8 Radiated Emission from 1GHz to 18GHz

USB Mode, Set.6

Normal RE_30M-1GHz_10m




Figure A.9 Radiated Emission from 30MHz to 1GHz

Final Result 1

| Frequency (MHz) | QuasiPeak (dBμ V/m) | Height (cm) | Polarization | Azimuth (deg) | Corr. (dB) | Margin (dB) | Limit (dBμ V/m) |
|-----------------|---------------------|-------------|--------------|---------------|------------|-------------|-----------------|
| 72.001000 | 27.7 | 125.0 | V | 210.0 | -15.8 | 2.3 | 30.0 |

Normal RE_1G-18GHz




Figure A.10 Radiated Emission from 1GHz to 18GHz

A.2 Conducted Emission

Reference

FCC: CFR Part 15.107(a).

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 - 2014, section 7.3.

A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode.

For the charging mode, the EUT is keeping on playing MP3 file.

A.2.3 Measurement Limit

| Frequency of emission (MHz) | Conducted limit (dBμV) | |
|--|------------------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |
| *Decreases with the logarithm of the frequency | | |

A.2.4 Test Condition in charging mode

| | |
|-------------|----------------|
| Voltage (V) | Frequency (Hz) |
| 120 | 60 |

| | |
|------------------|---------------|
| RBW/IF bandwidth | Sweep Time(s) |
| 9kHz | 1 |

A.2.5 Measurement Results

Measurement uncertainty: $U = 2.7 \text{ dB}$, $k=2$.

Charging Mode, Set.2




Figure A.11 Conducted Emission

Final Result 1

| Frequency (MHz) | QuasiPeak (dBμV) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|------------------|------|------------|-------------|--------------|
| 0.159000 | 53.7 | L1 | 19.9 | 11.8 | 65.5 |
| 0.258000 | 48.0 | L1 | 19.8 | 13.5 | 61.5 |
| 0.456000 | 37.5 | L1 | 19.9 | 19.2 | 56.8 |
| 2.098500 | 44.1 | L1 | 19.6 | 11.9 | 56.0 |
| 3.151500 | 44.7 | L1 | 19.3 | 11.3 | 56.0 |
| 4.101000 | 44.4 | L1 | 19.6 | 11.6 | 56.0 |

Final Result 2

| Frequency (MHz) | CAverage (dBμV) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|-----------------|------|------------|-------------|--------------|
| 0.154500 | 40.9 | L1 | 20.0 | 14.8 | 55.8 |
| 0.307500 | 32.5 | N | 19.8 | 17.5 | 50.0 |
| 1.198500 | 27.9 | L1 | 19.7 | 18.1 | 46.0 |
| 2.076000 | 31.0 | L1 | 19.7 | 15.0 | 46.0 |
| 2.400000 | 35.7 | L1 | 19.2 | 10.3 | 46.0 |
| 4.209000 | 33.9 | L1 | 19.6 | 12.1 | 46.0 |

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

Charging Mode, Set.3




Figure A.12 Conducted Emission

Final Result 1

| Frequency (MHz) | QuasiPeak (dBμV) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|------------------|------|------------|-------------|--------------|
| 0.231000 | 48.4 | L1 | 19.8 | 14.0 | 62.4 |
| 0.726000 | 43.5 | L1 | 19.8 | 12.5 | 56.0 |
| 1.167000 | 44.7 | L1 | 19.7 | 11.3 | 56.0 |
| 1.792500 | 40.4 | N | 19.7 | 15.6 | 56.0 |
| 3.228000 | 42.1 | L1 | 19.3 | 13.9 | 56.0 |
| 3.777000 | 41.5 | L1 | 19.5 | 14.5 | 56.0 |

Final Result 2

| Frequency (MHz) | CAverage (dBμV) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|-----------------|------|------------|-------------|--------------|
| 0.424500 | 36.3 | N | 19.9 | 11.1 | 47.4 |
| 0.726000 | 36.3 | L1 | 19.8 | 9.7 | 46.0 |
| 1.167000 | 36.5 | L1 | 19.7 | 9.5 | 46.0 |
| 1.707000 | 34.9 | L1 | 19.7 | 11.1 | 46.0 |
| 2.170500 | 33.9 | L1 | 19.4 | 12.1 | 46.0 |
| 4.965000 | 34.3 | L1 | 19.6 | 11.7 | 46.0 |

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

Charging Mode, Set.4




Figure A.13 Conducted Emission

Final Result 1

| Frequency (MHz) | QuasiPeak (dBμV) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|------------------|------|------------|-------------|--------------|
| 0.208500 | 52.7 | L1 | 19.8 | 10.5 | 63.3 |
| 0.276000 | 47.2 | L1 | 19.8 | 13.8 | 60.9 |
| 0.465000 | 38.1 | L1 | 19.9 | 18.5 | 56.6 |
| 2.107500 | 36.9 | L1 | 19.6 | 19.1 | 56.0 |
| 3.579000 | 40.8 | L1 | 19.5 | 15.2 | 56.0 |
| 3.894000 | 43.5 | L1 | 19.5 | 12.5 | 56.0 |

Final Result 2

| Frequency (MHz) | CAverage (dBμV) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|-----------------|------|------------|-------------|--------------|
| 0.159000 | 43.7 | L1 | 19.9 | 11.8 | 55.5 |
| 0.424500 | 33.4 | N | 19.9 | 14.0 | 47.4 |
| 0.433500 | 33.0 | N | 19.9 | 14.2 | 47.2 |
| 1.297500 | 28.4 | N | 19.7 | 17.6 | 46.0 |
| 2.652000 | 33.9 | L1 | 19.4 | 12.1 | 46.0 |
| 3.952500 | 28.2 | L1 | 19.5 | 17.8 | 46.0 |

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

Charging Mode, Set.5




Figure A.14 Conducted Emission

Final Result 1

| Frequency (MHz) | QuasiPeak (dBμV) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|------------------|------|------------|-------------|--------------|
| 0.195000 | 58.3 | L1 | 19.8 | 5.5 | 63.8 |
| 0.289500 | 43.8 | L1 | 19.8 | 16.7 | 60.5 |
| 0.537000 | 46.4 | L1 | 19.9 | 9.6 | 56.0 |
| 0.928500 | 42.2 | L1 | 19.8 | 13.8 | 56.0 |
| 2.044500 | 34.0 | L1 | 19.7 | 22.0 | 56.0 |
| 2.476500 | 39.4 | N | 19.0 | 16.6 | 56.0 |

Final Result 2

| Frequency (MHz) | CAverage (dBμV) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|-----------------|------|------------|-------------|--------------|
| 0.195000 | 47.3 | L1 | 19.8 | 6.5 | 53.8 |
| 0.339000 | 35.1 | N | 19.9 | 14.2 | 49.2 |
| 0.537000 | 41.0 | L1 | 19.9 | 5.0 | 46.0 |
| 0.928500 | 35.0 | L1 | 19.8 | 11.0 | 46.0 |
| 1.801500 | 27.9 | L1 | 19.7 | 18.1 | 46.0 |
| 2.139000 | 29.2 | L1 | 19.5 | 16.8 | 46.0 |

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

USB Mode, Set.6




Figure A.15 Conducted Emission

Final Result 1

| Frequency (MHz) | QuasiPeak (dBμV) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|------------------|------|------------|-------------|--------------|
| 0.213000 | 45.9 | N | 19.8 | 17.2 | 63.1 |
| 0.424500 | 40.8 | L1 | 19.9 | 16.6 | 57.4 |
| 0.559500 | 43.4 | L1 | 19.9 | 12.6 | 56.0 |
| 0.816000 | 37.2 | N | 19.8 | 18.8 | 56.0 |
| 1.977000 | 35.1 | L1 | 19.7 | 20.9 | 56.0 |
| 2.152500 | 33.6 | L1 | 19.5 | 22.4 | 56.0 |

Final Result 2

| Frequency (MHz) | CAverage (dBμV) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|-----------------|------|------------|-------------|--------------|
| 0.177000 | 46.5 | N | 19.8 | 8.1 | 54.6 |
| 0.276000 | 38.1 | N | 19.8 | 12.8 | 50.9 |
| 0.559500 | 35.9 | N | 19.9 | 10.1 | 46.0 |
| 2.044500 | 29.5 | L1 | 19.7 | 16.5 | 46.0 |
| 2.611500 | 29.3 | N | 19.2 | 16.7 | 46.0 |
| 4.443000 | 30.1 | N | 19.6 | 15.9 | 46.0 |

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

*****END OF REPORT*****