

# **TEST REPORT**

# No. I15Z42273-GTE03

for

**TCL Communication Ltd.** 

# HSDPA/HSUPA/UMTS quad band / GSM quad band /LTE 7 bands

mobile phone

Model Name: 5017W

FCC ID: 2ACCJH035

with

**Hardware Version: PIO** 

**Software Version: v1BD9** 

Issued Date: 2015-09-17

#### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

#### **Test Laboratory:**

FCC 2.948 Listed: No.525429

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl\_terminals@catr.cn, website: www.chinattl.com

# **REPORT HISTORY**

Report Number	Revision	Description	Issue Date
I15Z42273-GTE03	Rev.0	1st edition	2015-09-11
I15Z42273-GTE03	Rev.1	2nd edition	2015-09-17



# **CONTENTS**

1.	TEST LABORATORY	4
1.1.	TESTING LOCATION	4
1.2.	TESTING ENVIRONMENT	4
1.3.	PROJECT DATA	4
1.4.	SIGNATURE	4
2.	CLIENT INFORMATION	5
2.1.		
2.2.	MANUFACTURER INFORMATION	5
3.	EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	
3.1.		
3.2.		
3.3.		
3.4.		
	REFERENCE DOCUMENTS	
4.1.		
5.	LABORATORY ENVIRONMENT	8
6.	SUMMARY OF TEST RESULTS	9
6.1.	SUMMARY OF TEST RESULTS	9
6.2.	STATEMENTS	11
7.	TEST EQUIPMENTS UTILIZED	12
ANN	NEX A: MEASUREMENT RESULTS	13
A.	1 OUTPUT POWER	13
A.	2 EMISSION LIMIT	34
A.	3 FREQUENCY STABILITY	46
A.	4 OCCUPIED BANDWIDTH	50
A.	5 EMISSION BANDWIDTH	73
A.	6 BAND EDGE COMPLIANCE	96
A.	7 CONDUCTED SPURIOUS EMISSION	113
Δ	8 PEAK-TO-AVERAGE POWER RATIO	117



## 1. Test Laboratory

#### 1.1. Testing Location

Company Name: CTTL, Telecommunication Technology Labs, Academy of

Telecommunication Research, MIIT

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China

100191

Postal Code: 100191

Telephone: 00861062304633 Fax: 00861062304793

#### 1.2. Testing Environment

Normal Temperature:  $15-35^{\circ}$ C Relative Humidity: 20-75%

Air pressure 980 - 1040 hPa

The climatic requirements above are general exclude the special requirements for dedicated test environments listed in section 5 and some specific test cases in other parts of this report.

#### 1.3. Project data

Testing Start Date: 2015-05-10 Testing End Date: 2015-09-11

#### 1.4. Signature

Shen Yi

(Prepared this test report)

Zhong Nan

(Reviewed this test report)

Sun Xiang Qian

**Deputy Director of the laboratory** 

(Approved this test report)



# 2. Client Information

## 2.1. Applicant Information

Company Name: TCL Communication Ltd.

Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,

Pudong Area Shanghai, P.R. China. 201203

Contact Person: Gong Zhizhou

Contact Email zhizhou.gong@tcl.com
Telephone: 0086-21-51798260
Fax: 0086-21-61460602

#### 2.2. Manufacturer Information

Company Name: TCL Communication Ltd.

Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,

Pudong Area Shanghai, P.R. China. 201203

Contact Person: Gong Zhizhou

Contact Email zhizhou.gong@tcl.com
Telephone: 0086-21-51798260
Fax: 0086-21-61460602



## 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

Description HSDPA/HSUPA/UMTS quad band / GSM quad band /LTE 7 bands

mobile phone

Model Name 5017W

FCC ID 2ACCJH035 Antenna Integrated

Output power 22.65dBm maximum EIRP measured for LTE Band 2

Extreme vol. Limits 3.5VDC to 4.2VDC (nominal: 3.8VDC)

Extreme temp. Tolerance -30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

Note: The EUT is a variant model of 5017A. The conducted results of Band 2, Band 4 Band 7 are coming from the initial model.

#### 3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version
UT04a	354385070100083	PIO	v1BD9
UT03a	354385070100091	PIO	v1BD9

<sup>\*</sup>EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

AE ID\* Description
AE1 Battery
AE2 Battery

AE3 Travel charger
AE4 Travel charger

AE1

Model CAB1780006C1

Manufacturer BYD
Capacitance 1780mAh

AE2

Model CAB1780004C2

Manufacturer SCUD
Capacitance 1780mAh

AE3

Model CBA0066AG2C1

Manufacturer BYD

AE4

Model CBA0066AG2C2

Manufacturer Tenpao



\*AE ID: is used to identify the test sample in the lab internally.

#### 3.4. General Description

The Equipment Under Test (EUT) is a model of HSDPA/HSUPA/UMTS quad band / GSM quad band /LTE 7 bands mobile phone with integrated antenna. Manual and specifications of the EUT were provided to fulfil the test.

# 4. Reference Documents

## 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-14
		Edition
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-14
		Edition
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS	10-1-14
	SERVICES	Edition
ANSI/TIA-603-D	Land Mobile FM or PM Communications Equipment	2015
	Measurement and Performance Standards	
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from	2014
	Low-Voltage Electrical and Electronic Equipment in the	
	Range of 9 kHz to 40 GHz	
KDB 971168 D01	Measurement Guidance for Certification of Licensed Digital	v02r02
	Transmitters	



# 5. LABORATORY ENVIRONMENT

**Semi-anechoic chamber SAC-1** (23 meters $\times$ 17meters $\times$ 10meters) did not exceed following limits along the EMC testing:

minute diversity and minutes to the same services.	
Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB;
	1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4Ω
Normalised site attenuation (NSA)	< ± 4 dB, 3m/10m distance,
	from 30 to 1000 MHz
Site voltage standing-wave ratio (S <sub>VSWR</sub> )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

**Fully-anechoic chamber FAC-3** (9 meters × 6.5 meters × 4 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 $^{\circ}$ C, Max. = 35 $^{\circ}$ C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB;
	1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	<4 Ω
Site voltage standing-wave ratio (S <sub>VSWR</sub> )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

**Shielded room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 $^{\circ}$ C, Max. = 35 $^{\circ}$ C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB;
	1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	<4 Ω



# 6. SUMMARY OF TEST RESULTS

# 6.1. <u>Summary of test results</u>

Abbreviations used in this clause:			
	Р	Pass	
Vardiat Calumn	F	Fail	
Verdict Column	NA	Not applicable	
	NM	Not measured	
Location Column	A/B/C/D	The test is performed in test location A, B, C or D	
Location Column	A/B/C/D	which are described in section 1.1 of this report	

#### LTE Band 2

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	24.232(c)	A.1	Р
2	Emission Limit	24.238(a), 2.1051	A.2	Р
3	Frequency Stability	24.235, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	24.238(a)	A.5	Р
6	Band Edge Compliance	24.238(a)	A.6	Р
7	Conducted Spurious Emission	24.238, 2.1057	A.7	Р
8	Peak to Average Power Ratio	24.232 (d)	A.8	Р

#### LTE Band 4

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	27.50(d)(4)	A.1	Р
2	Emission Limit	27.53(h), 2.1051	A.2	Р
3	Frequency Stability	27.54, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	27.53(h)	A.5	Р
6	Band Edge Compliance	27.53(h)	A.6	Р
7	Conducted Spurious Emission	27.53(h), 2.1057	A.7	Р
8	Peak to Average Power Ratio	27.50(a)	A.8	Р



## LTE Band 5

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	§2.1046(a), 22.913(a)	A.1	Р
2	Emission Limit	22.917, 2.1051	A.2	Р
3	Frequency Stability	22.235, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	22.917(b)	A.5	Р
6	Band Edge Compliance	22.917(b)	A.6	Р
7	Conducted Spurious Emission	22.917, 2.1057	A.7	Р

#### LTE Band 7

<i>a                                    </i>				
Items	Test Name	Clause in	Section in	Verdict
Items	rest Name	FCC rules	this report	Verdict
1	Output Power	27.50(h)(2)	A.1	Р
2	Emission Limit	27.53(m), 2.1051	A.2	Р
3	Frequency Stability	27.54, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	27.53(m)	A.5	Р
6	Band Edge Compliance	27.53(m)	A.6	Р
7	Conducted Spurious Emission	27.53(m), 2.1057	A.7	Р
8	Peak to Average Power Ratio	27.50(a)	A.8	Р

#### LTE Band 17

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	27.50(c)(10)	A.1	Р
2	Emission Limit	27.53(g), 2.1051	A.2	Р
3	Frequency Stability	27.54, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	27.53(g)	A.5	Р
6	Band Edge Compliance	27.53(g)	A.6	Р
7	Conducted Spurious Emission	27.53(g), 2.1057	A.7	Р
8	Peak to Average Power Ratio	27.50(a)	A.8	Р



#### 6.2. Statements

The test cases listed in section 6.1 of this report for the EUT specified in section 3 were performed by CTTL according to the standards or reference documents in section 4.1

The EUT met all applicable requirements of the standards or reference documents in section 4.1. This report only deals with the LTE functions among the features described in section 3.



# 7. Test Equipments Utilized

NO.	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	Test Receiver	ESCI	100344	R&S	2016-03-02	1 year
2	Test Receiver	ESU26	100376	R&S	2015-10-29	1 year
3	EMI Antenna	VULB 9163	302	Schwarzbeck	2017-01-03	3 year
4	EMI Antenna	3117	00119024	ETS-Lindgren	2016-01-20	3 year
5	LISN	NV216	101200	R&S	2016-07-07	1 year
6	Universal Radio Communication Tester	CMW500	101675	R&S	2016-07-13	1 year
7	Universal Radio Communication Tester	E5515C	MY48361083	Agilent	2016-02-27	1 year
8	Spectrum Analyzer	E4440A	MY48250642	Agilent	2016-03-02	1 year
9	EMI Antenna	9117	167	Schwarzbeck	2016-04-01	3 year
10	EMI Antenna	VULB9163	9163-234	Schwarzbeck	2016-09-15	3 year
11	EMI Antenna	3117	00119024	ETS-Lindgren	2016-01-20	3 year
12	Signal Generator	N5183A	MY49060052	Agilent	2016-03-02	1 year
13	Climate chamber	SH-241	92007454	ESPEC	2015-12-14	2 year
14	Loop Antenna	HFH2-Z2	829324/007	R&S	2017-12-10	3 year



## **ANNEX A: MEASUREMENT RESULTS**

## **A.1 OUTPUT POWER**

#### Reference

FCC: 22.913(a) ,24.232(c), 27.50(c)(10),27.50(d)(4), 27.50(h)(2).

#### A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMW500) to ensure max power transmission and proper modulation. In all cases, output power is within the specified limits.

#### A.1.2 Conducted

#### A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies (bottom, middle and top of operational frequency range) for each bandwidth.

#### A.1.2.2 Measurement result

#### LTE band 2

Bandwidth	RB size/offset	Frequency (MHz)	Power(dBm)	
Danawiatii	RD Size/Oliset	i requericy (ivii iz)	QPSK	16QAM
		1850.7	22.64	21.63
	1 RB high	1880.0	23.42	22.47
		1909.3	23.17	22.05
		1850.7	22.68	21.67
	1 RB low	1880.0	23.40	22.47
1.4MHz		1909.3	23.03	22.07
1.4IVITZ		1850.7	22.64	21.65
	50% RB mid	1880.0	23.46	22.53
		1909.3	23.10	22.12
	100% RB	1850.7	21.70	20.82
		1880.0	22.49	21.63
		1909.3	22.10	21.27
		1851.5	22.60	21.95
	1 RB high	1880.0	23.27	22.76
		1908.5	23.16	22.64
3MHz		1851.5	22.78	22.27
	1 RB low	1880.0	23.27	22.81
		1908.5	23.01	22.52
	50% RB mid	1851.5	21.84	20.94



		1880.0	22.61	21.72
		1908.5	22.25	21.39
		1851.5	21.83	20.87
	100% RB	1880.0	22.51	21.57
		1908.5	22.24	21.29
		1852.5	22.70	21.65
	1 RB high	1880.0	23.23	22.28
		1907.5	23.35	22.38
		1852.5	23.11	22.13
	1 RB low	1880.0	23.28	22.34
5MHz		1907.5	23.11	22.16
SIVIFIZ		1852.5	21.95	21.02
	50% RB mid	1880.0	22.58	21.62
		1907.5	22.35	21.40
		1852.5	21.90	21.03
	100% RB	1880.0	22.44	21.58
		1907.5	22.31	21.44
	1 RB high	1855.0	22.71	22.11
		1880.0	22.91	22.47
		1905.0	23.04	22.56
		1855.0	22.87	22.30
	1 RB low	1880.0	22.97	22.51
40MU=		1905.0	23.12	22.62
10MHz		1855.0	22.17	21.23
	50% RB mid	1880.0	22.47	21.52
		1905.0	22.43	21.51
		1855.0	22.08	21.10
	100% RB	1880.0	22.35	21.39
		1905.0	22.38	21.41
		1857.5	22.78	22.19
	1 RB high	1880.0	22.74	22.26
		1902.5	22.80	22.36
		1857.5	22.72	22.19
	1 RB low	1880.0	22.79	22.34
15MHz	110 10W	1902.5	23.17	22.67
		1857.5		
	F00/ BD		22.23	21.21
	50% RB mid	1880.0	22.45	21.45
		1902.5	22.41	21.40
	100% RB	1857.5	22.13	21.11



		1880.0	22.24	21.24
		1902.5	22.31	21.30
		1860.0	22.88	22.09
	1 RB high	1880.0	22.76	22.09
		1900.0	22.86	22.18
	1 RB low	1860.0	22.80	22.09
		1880.0	22.84	22.17
20MHz		1900.0	23.20	22.50
ZUNIFIZ	50% RB mid	1860.0	22.01	21.08
		1880.0	22.33	21.40
		1900.0	22.16	21.27
		1860.0	21.99	21.08
	100% RB	1880.0	22.09	21.19
		1900.0	22.16	21.24



Pondwidth	DP size/offset	Fraguanay (MHz)	Power	(dBm)
Bandwidth	RB size/offset	Frequency (MHz)	QPSK	16QAM
		1754.3	23.23	22.22
	1 RB high	1732.5	23.28	22.25
		1710.7	23.09	22.24
		1754.3	23.22	22.19
	1 RB low	1732.5	23.27	22.26
1.4MHz		1710.7	23.22	22.23
1. <del>4</del> IVIFIZ		1754.3	23.21	22.23
	50% RB mid	1732.5	23.23	22.28
		1710.7	23.26	22.27
		1754.3	22.26	21.35
	100% RB	1732.5	22.30	21.43
		1710.7	22.23	21.36
		1753.5	23.15	22.62
	1 RB high	1732.5	23.18	22.66
		1711.5	23.16	22.65
		1753.5	23.18	22.65
	1 RB low	1732.5	23.21	22.67
2001 1-		1711.5	23.16	22.67
3MHz		1753.5	22.32	21.41
	50% RB mid	1732.5	22.37	21.42
		1711.5	22.30	21.41
		1753.5	22.27	21.31
	100% RB	1732.5	22.30	21.35
		1711.5	22.26	21.33
		1752.5	23.25	22.23
	1 RB high	1732.5	23.27	22.26
		1712.5	23.22	22.24
		1752.5	23.30	22.29
	1 RB low	1732.5	23.32	22.31
ENAL I—		1712.5	23.26	22.28
5MHz		1752.5	22.32	21.36
	50% RB mid	1732.5	22.35	21.39
		1712.5	22.29	21.35
		1752.5	22.25	21.36
	100% RB	1732.5	22.31	21.44
		1712.5	22.25	21.39
40141-	1 DD biab	1750	23.25	22.71
10MHz	1 RB high	1732.5	23.24	22.74

©Copyright. All rights reserved by CTTL.



		1715	23.23	22.70
		1750	23.26	22.80
	1 RB low	1732.5	23.25	22.70
		1715	23.23	22.71
		1750	22.32	21.34
	50% RB mid	1732.5	22.32	21.37
		1715	22.25	21.31
		1750	22.29	21.32
	100% RB	1732.5	22.32	21.35
		1715	22.25	21.29
		1747.5	23.31	22.75
	1 RB high	1732.5	23.24	22.73
		1717.5	23.29	22.73
		1747.5	23.28	22.79
	1 RB low	1732.5	23.28	22.73
458411		1717.5	23.25	22.77
15MHz	50% RB mid	1747.5	22.38	21.36
		1732.5	22.42	21.37
		1717.5	22.35	21.29
	100% RB	1747.5	22.42	21.40
		1732.5	22.41	21.38
		1717.5	22.37	21.36
		1745	23.33	22.58
	1 RB high	1732.5	23.30	22.58
		1720	23.32	22.53
		1745	23.36	22.63
	1 RB low	1732.5	23.30	22.53
201411-		1720	23.24	22.52
20MHz		1745	22.32	21.40
	50% RB mid	1732.5	22.35	21.41
		1720	22.29	21.32
		1745	22.32	21.39
	100% RB	1732.5	22.30	21.37
		1720	22.24	21.31



Dondwidth	DD size/offset	Fragueray (MIII)	Power	r(dBm)
Bandwidth	RB size/offset	Frequency (MHz)	QPSK	16QAM
		848.3	22.80	21.86
	1 RB high	836.5	22.79	21.89
		824.7	22.95	22.04
		848.3	22.79	21.85
	1 RB low	836.5	22.83	21.88
1 4 1 1 1 -		824.7	22.94	22.01
1.4MHz		848.3	22.82	21.87
	50% RB mid	836.5	22.85	21.89
		824.7	22.95	21.99
		848.3	21.81	20.98
	100% RB	836.5	21.84	21.00
		824.7	21.92	21.06
		847.5	22.80	22.30
	1 RB high	836.5	22.77	22.32
		825.5	22.85	22.44
	1 RB low	847.5	22.80	22.38
		836.5	22.81	22.33
2041.1-		825.5	22.88	22.47
3MHz		847.5	21.94	21.02
	50% RB mid	836.5	21.94	21.03
		825.5	21.99	21.12
		847.5	21.90	20.96
	100% RB	836.5	21.91	20.95
		825.5	21.99	21.01
		846.5	22.83	21.87
	1 RB high	836.5	22.84	21.89
		826.5	22.90	21.93
		846.5	22.91	21.94
	1 RB low	836.5	22.95	21.96
ENALL-		826.5	22.98	22.04
5MHz		846.5	21.90	20.96
	50% RB mid	836.5	21.96	21.02
		826.5	22.03	21.03
		846.5	21.89	20.99
	100% RB	836.5	21.92	21.04
		826.5	22.01	21.09



		844.0	22.83	22.37
	1 RB high	836.5	22.85	22.44
		829.0	22.92	22.40
		844.0	22.83	22.31
	1 RB low	836.5	22.95	22.42
10MHz		829.0	23.02	22.59
IUIVITZ	50% RB mid	844.0	21.60	20.92
		836.5	21.93	20.96
		829.0	21.94	21.00
		844.0	21.87	20.91
	100% RB	836.5	21.96	20.98
		829.0	22.00	21.01



Donadooidth	DD size/offset	Francisco (MIII-)	Power	(dBm)
Bandwidth	RB size/offset	Frequency (MHz)	QPSK	16QAM
		2502.5	22.92	21.94
	1 RB high	2535	23.19	22.27
		2567.5	23.23	22.31
		2502.5	23.05	22.13
	1 RB low	2535	23.25	22.33
5MHz		2567.5	23.15	22.22
JIVII 12		2502.5	21.98	21.20
	50% RB mid	2535	22.39	21.92
		2567.5	22.35	21.31
		2502.5	21.93	21.01
	100% RB	2535	22.68	21.98
		2567.5	22.30	21.37
		2505	22.83	22.30
	1 RB high	2535	23.01	22.63
		2565	23.18	22.79
	1 RB low	2505	23.05	22.62
		2535	23.12	22.70
10MHz		2565	23.06	22.65
TOWNIZ	50% RB mid	2505	22.07	21.07
		2535	22.23	21.25
		2565	22.29	21.30
		2505	22.06	21.02
	100% RB	2535	22.23	21.19
		2565	22.31	21.27
		2507.5	22.92	22.38
	1 RB high	2535	23.01	22.61
		2562.5	23.00	22.60
		2507.5	23.09	22.70
	1 RB low	2535	23.11	22.69
45		2562.5	23.00	22.57
15MHz		2507.5	22.26	21.20
	50% RB mid	2535	22.27	21.21
		2562.5	22.20	21.17
		2507.5	22.25	21.15
	100% RB	2535	22.27	21.21
		2562.5	22.20	21.15
		2002.0	22.20	21.10

©Copyright. All rights reserved by CTTL.



		2510	22.99	22.24
	1 RB high	2535	23.01	22.27
		2560	23.10	22.45
		2510	23.11	22.47
	1 RB low	2535	23.17	22.51
20MHz		2560	23.03	22.39
ZUIVITZ	50% RB mid	2510	22.21	21.23
		2535	22.27	21.29
		2560	22.21	21.22
		2510	22.19	21.19
	100% RB	2535	22.21	21.21
		2560	22.17	21.17

Note: Expanded measurement uncertainty is U = 0.83 dB, k = 2.



Bandwidth	RB size/offset	Frequency (MHz)	Power(dBm)		
Danuwium	RD Size/Oliset	1 requericy (IVII 12)	QPSK	16QAM	
		713.5	22.94	21.93	
	1 RB high	710.0	23.02	22.01	
		706.5	23.07	22.09	
		713.5	23.05	22.00	
	1 RB low	710.0	23.00	22.02	
5MHz		706.5	23.10	22.11	
SIVITZ		713.5	22.01	21.04	
	50% RB mid	710.0	22.02	21.09	
		706.5	22.05	21.12	
		713.5	21.95	21.10	
	100% RB	710.0	21.96	21.14	
		706.5	21.99	21.15	
		711	22.92	22.41	
	1 RB high	710	22.94	22.41	
		709	22.99	22.43	
		711	23.02	22.54	
	1 RB low	710	22.97	22.53	
101411-		709	22.98	22.49	
10MHz		711	21.97	21.06	
	50% RB mid	710	21.95	21.05	
		709	21.96	21.06	
		711	21.98	21.07	
	100% RB	710	21.98	21.05	
		709	21.98	21.05	



#### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 27.50(d) specifies "Fixed, mobile, and portable (handheld) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP".

Rule Part 27.50(h)(2) specifies "Mobile stations are limited to 2.0 watts EIRP.".


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603D-2015 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the



reference point of the chamber. An RF signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

- 4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the amplifier and the substitution antenna.
  - The cable loss  $(P_{cl})$ , the substitution antenna Gain  $(G_a)$  and the amplifier Gain  $(P_{Ag})$  should be recorded after test.
  - The measurement results are obtained as described below:
  - Power (EIRP) =  $P_{Mea} P_{Aq} P_{cl} G_a$
- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15.



#### A.1.3.3 Measurement result

LTE Band 2- EIRP 24. 232(b)

**Limits:** ≤33dBm (2W)

#### LTE Band 2\_1.4MHz\_QPSK

_								
Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1850.70	-23.06	2.92	-43.75	-4.87	22.64	33.00	10.36	Н
1880.00	-23.32	2.85	-43.75	-4.82	22.40	33.00	10.60	Н
1909.30	-25.20	2.87	-43.77	-4.76	20.46	33.00	12.54	Н

## LTE Band 2\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1851.50	-23.10	2.87	-43.75	-4.87	22.65	33.00	10.35	Н
1880.00	-24.37	2.85	-43.75	-4.82	21.35	33.00	11.65	Н
1908.50	-25.31	2.89	-43.78	-4.76	20.34	33.00	12.66	Н

#### LTE Band 2\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.50	-23.15	2.87	-43.75	-4.87	22.60	33.00	10.40	Н
1880.00	-24.36	2.85	-43.75	-4.82	21.36	33.00	11.64	Н
1907.50	-25.37	2.84	-43.77	-4.77	20.33	33.00	12.67	Н

## LTE Band 2\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1855.00	-23.29	2.88	-43.74	-4.86	22.43	33.00	10.57	Н
1880.00	-24.42	2.85	-43.75	-4.82	21.30	33.00	11.70	Н
1905.00	-25.66	2.87	-43.77	-4.77	20.01	33.00	12.99	Н

## LTE Band 2\_15MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1857.50	-23.13	2.87	-43.75	-4.86	22.61	33.00	10.39	Н
1880.00	-24.30	2.85	-43.75	-4.82	21.42	33.00	11.58	Н
1902.50	-25.24	2.86	-43.77	-4.78	20.45	33.00	12.55	Н

## LTE Band 2\_20 MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1860.00	-23.13	2.86	-43.75	-4.85	22.61	33.00	10.39	Н
1880.00	-24.42	2.85	-43.75	-4.82	21.30	33.00	11.70	Н
1900.00	-25.28	2.87	-43.77	-4.78	20.40	33.00	12.60	Н



#### LTE Band 2\_1.4MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1850.70	-24.01	2.92	-43.75	-4.87	21.69	33.00	11.31	Н
1880.00	-24.26	2.85	-43.75	-4.82	21.46	33.00	11.54	Н
1909.30	-26.20	2.87	-43.77	-4.76	19.46	33.00	13.54	Н

#### LTE Band 2\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1851.50	-24.08	2.87	-43.75	-4.87	21.67	33.00	11.33	Н
1880.00	-25.17	2.85	-43.75	-4.82	20.55	33.00	12.45	Н
1908.50	-26.29	2.89	-43.78	-4.76	19.36	33.00	13.64	Н

## LTE Band 2\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.50	-23.99	2.87	-43.75	-4.87	21.76	33.00	11.24	Н
1880.00	-25.28	2.85	-43.75	-4.82	20.44	33.00	12.56	Н
1907.50	-26.19	2.84	-43.77	-4.77	19.51	33.00	13.49	Н

#### LTE Band 2\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1855.00	-24.28	2.88	-43.74	-4.86	21.44	33.00	11.56	Н
1880.00	-25.25	2.85	-43.75	-4.82	20.47	33.00	12.53	Н
1905.00	-26.59	2.87	-43.77	-4.77	19.08	33.00	13.92	Н

## LTE Band 2\_15MHz\_16QAM

<del>-</del>								
Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1857.50	-24.11	2.87	-43.75	-4.86	21.63	33.00	11.37	Н
1880.00	-25.15	2.85	-43.75	-4.82	20.57	33.00	12.43	Н
1902.50	-26.16	2.86	-43.77	-4.78	19.53	33.00	13.47	Н

## LTE Band 2\_20 MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1860.00	-24.09	2.86	-43.75	-4.85	21.65	33.00	11.35	Н
1880.00	-25.24	2.85	-43.75	-4.82	20.48	33.00	12.52	Н
1900.00	-26.31	2.87	-43.77	-4.78	19.37	33.00	13.63	Н

 $Peak \; EIRP(dBm) = P_{Mea}(-23.10dBm) - G_a \; (-4.87dBi) - P_{Ag} \; (-43.75dB) - P_{cl} \; (2.87dB) = 22.65dBm$ 



## LTE Band 4- EIRP 27.50(d)

**Limits:** ≤30dBm (1W)

## LTE Band 4\_1.4MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1710.70	-25.72	3.17	-44.10	-5.12	20.33	30.00	9.67	Н
1732.50	-23.78	3.33	-44.14	-5.08	22.11	30.00	7.89	Н
1754.30	-26.59	3.76	-44.14	-5.04	18.83	30.00	11.17	Н

## LTE Band 4\_3MHz\_QPSK

Ī	Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
Ī	1711.50	-25.38	3.40	-44.10	-5.12	20.44	30.00	9.56	Н
Ī	1732.50	-23.77	3.33	-44.14	-5.08	22.12	30.00	7.88	Н
	1753.50	-26.43	3.80	-44.13	-5.04	18.94	30.00	11.06	Н

## LTE Band 4\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.50	-24.82	3.66	-44.10	-5.12	20.74	30.00	9.26	Н
1732.50	-23.79	3.33	-44.14	-5.08	22.10	30.00	7.90	Н
1752.50	-26.48	3.82	-44.14	-5.05	18.89	30.00	11.11	Н

#### LTE Band 4\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1715.00	-24.31	3.56	-44.10	-5.11	21.34	30.00	8.66	Н
1732.50	-23.80	3.33	-44.14	-5.08	22.09	30.00	7.91	Н
1750.50	-27.15	3.16	-44.14	-5.05	18.88	30.00	11.12	Н

#### LTE Band 4\_15MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1717.50	-23.74	3.47	-44.11	-5.11	22.01	30.00	7.99	Н
1732.50	-23.72	3.33	-44.14	-5.08	22.17	30.00	7.83	Н
1747.50	-26.72	3.34	-44.15	-5.05	19.14	30.00	10.86	Н

## LTE Band 4\_20MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1720.00	-23.30	3.37	-44.11	-5.10	22.54	30.00	7.46	Н
1732.50	-23.70	3.33	-44.14	-5.08	22.19	30.00	7.81	Н
1745.00	-25.55	3.68	-44.16	-5.06	19.99	30.00	10.01	Н



#### LTE Band 4\_1.4MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1710.70	-26.67	3.17	-44.10	-5.12	19.38	30.00	10.62	Н
1732.50	-24.75	3.33	-44.14	-5.08	21.14	30.00	8.86	Н
1754.30	-27.63	3.76	-44.14	-5.04	17.79	30.00	12.21	Н

#### LTE Band 4\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1711.50	-26.37	3.40	-44.10	-5.12	19.45	30.00	10.55	Н
1732.50	-24.63	3.33	-44.14	-5.08	21.26	30.00	8.74	Н
1753.50	-27.35	3.80	-44.13	-5.04	18.02	30.00	11.98	Н

## LTE Band 4\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.50	-25.68	3.66	-44.10	-5.12	19.88	30.00	10.12	Н
1732.50	-24.59	3.33	-44.14	-5.08	21.30	30.00	8.70	Н
1752.50	-27.43	3.82	-44.14	-5.05	17.94	30.00	12.06	Н

#### LTE Band 4\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1715.00	-25.30	3.56	-44.10	-5.11	20.35	30.00	9.65	Н
1732.50	-24.65	3.33	-44.14	-5.08	21.24	30.00	8.76	Н
1750.50	-28.08	3.16	-44.14	-5.05	17.95	30.00	12.05	Н

## LTE Band 4\_15MHz\_16QAM

<del>-</del>								
Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1717.50	-24.61	3.47	-44.11	-5.11	21.14	30.00	8.86	Н
1732.50	-24.59	3.33	-44.14	-5.08	21.30	30.00	8.70	Н
1747.50	-27.71	3.34	-44.15	-5.05	18.15	30.00	11.85	Н

## LTE Band 4\_20MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1720.00	-24.28	3.37	-44.11	-5.10	21.56	30.00	8.44	Н
1732.50	-24.56	3.33	-44.14	-5.08	21.33	30.00	8.67	Н
1745.00	-26.53	3.68	-44.16	-5.06	19.01	30.00	10.99	Н

 $Peak \; EIRP(dBm) = P_{Mea}(-23.30dBm) - G_{a} \; (-5.10dBi) - P_{Ag} \; (-44.11dB) - P_{Cl} \; (3.37dB) = 22.54dBm$ 



# LTE Band 5- ERP 22.913(a) Limits: ≤38.45dBm (7W) LTE Band 5\_1.4MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
824.70	-21.00	2.26	-45.79	-0.95	2.15	21.33	38.45	17.12	Н
836.50	-21.70	2.26	-45.66	-0.82	2.15	20.37	38.45	18.08	Н
848.30	-22.43	2.27	-45.55	-0.80	2.15	19.50	38.45	18.95	Н

## LTE Band 5\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
825.50	-21.13	2.26	-45.79	-0.94	2.15	21.19	38.45	17.26	Н
836.50	-21.90	2.26	-45.66	-0.82	2.15	20.17	38.45	18.28	Н
847.50	-22.05	2.27	-45.56	-0.81	2.15	19.90	38.45	18.55	Н

## LTE Band 5\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.50	-21.18	2.25	-45.77	-0.93	2.15	21.12	38.45	17.33	Н
836.50	-22.36	2.26	-45.66	-0.82	2.15	19.71	38.45	18.74	Н
846.50	-22.09	2.26	-45.56	-0.82	2.15	19.88	38.45	18.57	Н

#### LTE Band 5\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
829.00	-21.39	2.13	-45.74	-0.90	2.15	20.97	38.45	17.48	Н
836.50	-22.49	2.26	-45.66	-0.82	2.15	19.58	38.45	18.87	Н
844.00	-21.89	2.26	-45.59	-0.82	2.15	20.11	38.45	18.34	Н



#### LTE Band 5\_1.4MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
824.70	-21.96	2.26	-45.79	-0.95	2.15	20.37	38.45	18.08	Н
836.50	-22.52	2.26	-45.66	-0.82	2.15	19.55	38.45	18.90	Н
848.30	-23.24	2.27	-45.55	-0.80	2.15	18.69	38.45	19.76	Н

#### LTE Band 5\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
825.50	-22.05	2.26	-45.79	-0.94	2.15	20.27	38.45	18.18	Н
836.50	-22.61	2.26	-45.66	-0.82	2.15	19.46	38.45	18.99	Н
847.50	-23.01	2.27	-45.56	-0.81	2.15	18.94	38.45	19.51	Н

#### LTE Band 5\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.50	-22.03	2.25	-45.77	-0.93	2.15	20.27	38.45	18.18	Н
836.50	-23.18	2.26	-45.66	-0.82	2.15	18.89	38.45	19.56	Н
846.50	-22.85	2.26	-45.56	-0.82	2.15	19.12	38.45	19.33	Н

#### LTE Band 5\_10MHz\_16QAM

		_							
Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Aq</sub> (dB)	G <sub>a</sub> Antenna	Correction	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1 requeriey(wii iz)	i Mea(dDiii)	r cl(dD)	1 Ag(GD)	Gain(dB)	(dB)	LINI (dbiii)	Lillit(dDill)	Margin(GD)	1 Olarization
829.00	-22.44	2.13	-45.74	-0.90	2.15	19.92	38.45	18.53	Н
836.50	-23.23	2.26	-45.66	-0.82	2.15	18.84	38.45	19.61	Н
844.00	-22.76	2.26	-45.59	-0.82	2.15	19.24	38.45	19.21	Н

 $Peak \; ERP(dBm) = P_{Mea}(-21.00dBm) - G_a(-0.95dBi) - P_{Ag}(-45.79dB) - P_{cl} \; (2.26dB) - 2.15dB \; = \; 21.33dBm \; = \; 21$ 



## LTE Band 7- EIRP 27.50(h)(2)

**Limits:** ≤33 dBm (2W)

# LTE Band 7\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2502.50	-26.70	3.58	-45.68	-6.10	21.50	33.00	11.50	V
2535.00	-25.83	3.63	-44.82	-6.16	21.52	33.00	11.48	V
2567.50	-27.04	3.65	-44.92	-6.22	20.45	33.00	12.55	V

## LTE Band 7\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2505.00	-26.57	3.59	-45.64	-6.11	21.59	33.00	11.41	V
2535.00	-25.82	3.63	-44.82	-6.16	21.53	33.00	11.47	V
2565.00	-26.80	3.65	-44.97	-6.22	20.74	33.00	12.26	V

## LTE Band 7\_15MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2507.50	-26.00	3.59	-44.92	-6.11	21.44	33.00	11.56	V
2535.00	-25.93	3.63	-44.82	-6.16	21.42	33.00	11.58	V
2562.50	-27.34	3.65	-45.67	-6.21	20.89	33.00	12.11	V

#### LTE Band 7\_20MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2510.00	-26.52	3.58	-45.36	-6.12	21.38	33.00	11.62	V
2535.00	-25.96	3.63	-44.82	-6.16	21.39	33.00	11.61	V
2560.00	-27.64	3.64	-45.98	-6.21	20.91	33.00	12.09	V



## LTE Band 7\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2502.50	-27.55	3.58	-45.68	-6.10	20.65	33.00	12.35	V
2535.00	-26.76	3.63	-44.82	-6.16	20.59	33.00	12.41	V
2567.50	-27.83	3.65	-44.92	-6.22	19.66	33.00	13.34	V

## LTE Band 7\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2505.00	-27.53	3.59	-45.64	-6.11	20.63	33.00	12.37	V
2535.00	-26.64	3.63	-44.82	-6.16	20.71	33.00	12.29	V
2565.00	-27.61	3.65	-44.97	-6.22	19.93	33.00	13.07	V

# LTE Band 7\_15MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2507.50	-27.02	3.59	-44.92	-6.11	20.42	33.00	12.58	V
2535.00	-26.70	3.63	-44.82	-6.16	20.65	33.00	12.35	V
2562.50	-28.23	3.65	-45.67	-6.21	20.00	33.00	13.00	V

## LTE Band 7\_20MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2510.00	-27.48	3.58	-45.36	-6.12	20.42	33.00	12.58	V
2535.00	-26.73	3.63	-44.82	-6.16	20.62	33.00	12.38	V
2560.00	-28.61	3.64	-45.98	-6.21	19.94	33.00	13.06	V

 $Peak \; EIRP(dBm) = P_{Mea}(-26.57dBm) - G_{a} \; (-6.11dBi) - P_{Ag} \; (-45.64dB) - P_{cl} \; (3.59dB) = 21.59dBm$ 



#### LTE Band 17- EIRP 27.50(c)(10)

Limits: ≤34.77dBm (3W) LTE Band 17\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
706.50	-27.77	1.91	-45.53	-0.66	2.15	14.36	34.77	20.41	Н
710.00	-27.84	1.92	-45.68	-0.54	2.15	14.31	34.77	20.46	Н
713.50	-27.31	1.92	-45.22	-0.50	2.15	14.34	34.77	20.43	Н

#### LTE Band 17\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
709.00	-27.46	1.92	-45.64	-0.57	2.15	14.68	34.77	20.09	Н
710.00	-27.91	1.92	-45.68	-0.54	2.15	14.24	34.77	20.53	Н
711.00	-27.34	1.92	-45.19	-0.53	2.15	14.31	34.77	20.46	Н

#### LTE Band 17\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
706.50	-28.53	1.91	-45.53	-0.66	2.15	13.60	34.77	21.17	Н
710.00	-28.80	1.92	-45.68	-0.54	2.15	13.35	34.77	21.42	Н
713.50	-28.02	1.92	-45.22	-0.50	2.15	13.63	34.77	21.14	Н

#### LTE Band 17\_10MHz\_16QAM

	_	_							
Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna	Correction	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
				Gain(dB)	(dB)				
709.00	-28.61	1.92	-45.64	-0.57	2.15	13.53	34.77	21.24	Н
710.00	-28.82	1.92	-45.68	-0.54	2.15	13.33	34.77	21.44	Н
711.00	-28.33	1.92	-45.19	-0.53	2.15	13.32	34.77	21.45	Н

 $Peak \; ERP(dBm) = P_{Mea}(-27.46dBm) - G_a(-0.57dBi) - P_{Ag}(-45.64dB) - P_{cl}(1.92dB) - 2.15dB = 14.68dBm$ 

#### **ANALYZER SETTINGS:**

RBW = VBW = 8MHz for occupied bandwdiths equal to or less than 5MHz.

RBW = VBW = 20MHz for occupied bandwidths equal to or greater than 10MHz.

Note: Expanded measurement uncertainty is U = 0.96 dB, k = 2.



#### A.2 EMISSION LIMIT

#### Reference

FCC: CFR 2.1051, 22.913(a) ,24.238(a), 27.53(g), 27.53(h) , 27.53(m).


#### A.2.1 Measurement Method

The measurements procedures in TIA-603D-2015 are used. This measurement is carried out in fully-anechoic chamber FAC-3.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier. The resolution bandwidth is set 1MHz as outlined in Part 22.913(a) Part 24.238(a), Part 27.53(g), Part 27.53(h), Part 27.53(m). The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE Bands 2, 4,5, 7,17.

#### The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.





In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{\text{Mea}}$ ) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded ( $P_{\text{r}}$ ). The power of signal source ( $P_{\text{Mea}}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

- 4. The Path loss (P<sub>pl</sub>) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G<sub>a</sub>) should be recorded after test.
  - An amplifier should be connected in for the test.
  - The Path loss (Ppl) is the summation of the cable loss and the gain of the amplifier.
  - The measurement results are obtained as described below:
  - Power (EIRP)= $P_{Mea}$ +  $P_{pl}$  +  $G_a$
- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit: dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dB.

#### A.2.2 Measurement Limit

Part 22.913(a), Part 24.238(a), Part 27.53(g), Part 27.53(h), Part 27.53(m) all specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

#### A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the LTE Bands 2, 4, 5,7,17. It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the LTE Bands 2, 4, 5,7,17 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.



## LTE Band 2, 1.4MHz, QPSK, Channel 18607

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3403.10	-64.87	5.53	-7.97	-62.43	-13.00	49.43	٧
5552.46	-45.66	6.60	-10.59	-41.67	-13.00	28.67	Н
7403.29	-60.77	7.21	-12.08	-55.90	-13.00	42.90	V
9854.64	-61.07	8.44	-13.05	-56.46	-13.00	43.46	V
11516.60	-58.23	9.01	-13.10	-54.14	-13.00	41.14	٧
13494.73	-48.62	9.93	-14.19	-44.36	-13.00	31.36	Н

# LTE Band 2, 1.4MHz, QPSK, Channel 18900

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Anten na Gain	Peak EIRP(dBm	Limit (dBm)	Margin(dB	Polarizatio n
3760.18	-49.52	5.14	-8.56	-46.10	-13.00	33.10	V
5640.40	-47.17	6.85	-10.57	-43.45	-13.00	30.45	Н
7786.84	-56.24	7.26	-12.43	-51.07	-13.00	38.07	Н
9570.95	-57.67	8.19	-13.33	-52.53	-13.00	39.53	Н
11795.95	-57.93	9.07	-13.04	-53.96	-13.00	40.96	V
13609.12	-54.97	10.13	-14.27	-50.83	-13.00	37.83	V

#### LTE Band 2, 1.4MHz, QPSK, Channel 19193

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3819.04	-47.55	5.48	-8.65	-44.38	-13.00	31.38	٧
5728.38	-49.35	6.76	-10.55	-45.56	-13.00	32.56	Н
7762.02	-63.97	7.34	-12.41	-58.90	-13.00	45.90	V
10158.55	-55.67	8.57	-12.96	-51.28	-13.00	38.28	Н
12625.70	-60.52	9.53	-13.28	-56.77	-13.00	43.77	V
14481.94	-56.58	10.17	-14.40	-52.35	-13.00	39.35	V



## LTE Band 2, 1.4MHz, 16QAM, Channel 18607

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3491.53	-61.01	5.41	-8.18	-58.24	-13.00	45.24	Н
5552.59	-45.82	6.60	-10.59	-41.83	-13.00	28.83	Н
7402.88	-58.90	7.21	-12.08	-54.03	-13.00	41.03	٧
10338.31	-61.36	8.32	-13.04	-56.64	-13.00	43.64	V
12623.14	-56.32	9.54	-13.27	-52.59	-13.00	39.59	٧
14343.76	-51.15	10.09	-14.43	-46.81	-13.00	33.81	Н

## LTE Band 2, 1.4MHz, 16QAM, Channel 18900

Frequency(MHz)	P <sub>Mea</sub> (dB m)	Path Loss	Antenna Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3760.14	-51.20	5.14	-8.56	-47.78	-13.00	34.78	V
5640.24	-46.74	6.85	-10.57	-43.02	-13.00	30.02	Н
7519.78	-59.34	7.52	-12.22	-54.64	-13.00	41.64	V
10166.47	-61.04	8.60	-12.97	-56.67	-13.00	43.67	٧
12303.17	-52.81	8.90	-13.12	-48.59	-13.00	35.59	Н
14621.61	-54.33	10.56	-14.30	-50.59	-13.00	37.59	V

# LTE Band 2, 1.4MHz, 16QAM, Channel 19193

Frequency(MHz)	P <sub>Mea</sub> (dB m)	Path Loss	Antenna Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3818.85	-48.07	5.47	-8.65	-44.89	-13.00	31.89	V
5728.44	-49.37	6.76	-10.55	-45.58	-13.00	32.58	Н
7368.32	-63.36	6.98	-12.04	-58.30	-13.00	45.30	V
8499.91	-58.23	7.71	-13.00	-52.94	-13.00	39.94	Н
10805.11	-54.46	8.79	-13.16	-50.09	-13.00	37.09	Н
13635.80	-56.92	10.40	-14.28	-53.04	-13.00	40.04	V



## LTE Band 4, 1.4MHz QPSK, Channel 19957

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3570.31	-60.45	5.48	-8.30	-57.63	-13.00	44.63	I
5132.39	-45.12	6.42	-10.09	-41.45	-13.00	28.45	I
6843.04	-61.48	6.92	-11.41	-56.99	-13.00	43.99	<b>V</b>
9562.93	-64.14	8.17	-13.34	-58.97	-13.00	45.97	V
11264.18	-60.56	9.26	-13.15	-56.67	-13.00	43.67	٧
13635.12	-49.82	10.39	-14.28	-45.93	-13.00	32.93	Н

## LTE Band 4, 1.4MHz, QPSK, Channel 20175

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3283.68	-60.76	5.20	-7.68	-58.28	-13.00	45.28	Н
5197.94	-44.86	6.56	-10.18	-41.24	-13.00	28.24	Н
6926.77	-56.26	7.17	-11.51	-51.92	-13.00	38.92	Н
8709.98	-57.28	7.55	-13.04	-51.79	-13.00	38.79	Н
10360.94	-61.27	8.39	-13.04	-56.62	-13.00	43.62	V
12020.96	-60.81	8.94	-13.01	-56.74	-13.00	43.74	V

# LTE Band 4, 1.4MHz, QPSK, Channel 20393

Fragues 24/MUz)	D (dDm)	Path	Antenna	Peak	Limit	Margin(dD)	Polarization	
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	EIRP(dBm)	(dBm)	Margin(dB)	FUIAITZALIUIT	
3135.92	-58.92	5.27	-7.33	-56.86	-13.00	43.86	Н	
5263.23	-47.23	6.45	-10.27	-43.41	-13.00	30.41	Н	
7440.10	-56.38	7.12	-12.13	-51.37	-13.00	38.37	Н	
9031.84	-56.78	8.04	-13.12	-51.70	-13.00	38.70	Н	
11313.21	-54.83	9.08	-13.14	-50.77	-13.00	37.77	Н	
13412.71	-58.67	9.95	-14.08	-54.54	-13.00	41.54	V	



## LTE Band 4, 1.4MHz, 16QAM, Channel 19957

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm	Limit (dBm)	Margin(dB	Polarizatio n
3766.80	-67.34	5.09	-8.57	-63.86	-13.00	50.86	V
5132.49	-44.45	6.42	-10.09	-40.78	-13.00	27.78	Н
8112.93	-65.54	7.47	-12.69	-60.32	-13.00	47.32	٧
11527.14	-60.58	9.03	-13.09	-56.52	-13.00	43.52	V
13628.10	-49.91	10.31	-14.28	-45.94	-13.00	32.94	Н
16879.01	-51.20	11.36	-13.75	-48.81	-13.00	35.81	V

### LTE Band 4, 1.4MHz, 16QAM, Channel 20175

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm	Limit (dBm)	Margin(dB	Polarizatio n
3238.25	-59.88	5.15	-7.57	-57.46	-13.00	44.46	Н
5197.68	-45.17	6.55	-10.18	-41.54	-13.00	28.54	Н
7324.89	-64.27	7.29	-11.99	-59.57	-13.00	46.57	V
9599.96	-61.64	8.43	-13.30	-56.77	-13.00	43.77	٧
11274.32	-54.20	9.23	-13.15	-50.28	-13.00	37.28	Н
13365.89	-49.26	9.78	-14.01	-45.03	-13.00	32.03	Н

## LTE Band 4, 1.4MHz, 16QAM, Channel 20393

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3650.07	-56.43	5.46	-8.41	-53.48	-13.00	40.48	Н
5263.27	-47.40	6.45	-10.27	-43.58	-13.00	30.58	Н
7012.84	-57.08	7.36	-11.62	-52.82	-13.00	39.82	Н
8684.98	-57.94	7.67	-13.04	-52.57	-13.00	39.57	Н
10659.63	-56.15	8.54	-13.13	-51.56	-13.00	38.56	Н
13282.83	-56.35	9.92	-13.90	-52.37	-13.00	39.37	V



## LTE Band 5, 1.4MHz, QPSK, Channel 20407

Fragues (MIII)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Delerization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
3299.17	-43.30	5.38	-7.72	2.15	-43.11	-13.00	30.11	V
4259.06	-67.58	5.97	-9.16	2.15	-66.54	-13.00	53.54	V
4972.65	-60.46	6.36	-9.87	2.15	-59.10	-13.00	46.10	Н
5898.32	-65.66	6.89	-10.52	2.15	-64.18	-13.00	51.18	V
7440.64	-56.65	7.13	-12.13	2.15	-53.80	-13.00	40.80	Н
7834.70	-63.43	7.38	-12.47	2.15	-60.49	-13.00	47.49	V

### LTE Band 5, 1.4MHz, QPSK, Channel 20525

Fraguanov/MII=)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
2510.03	-49.45	4.48	-6.12	2.15	-49.96	-13.00	36.96	Н
3343.30	-59.48	5.20	-7.82	2.15	-59.01	-13.00	46.01	Н
4372.52	-65.77	6.20	-9.27	2.15	-64.85	-13.00	51.85	V
5350.22	-60.06	6.62	-10.39	2.15	-58.44	-13.00	45.44	Н
6540.10	-62.97	6.91	-11.05	2.15	-60.98	-13.00	47.98	V
8007.47	-61.91	7.69	-12.61	2.15	-59.14	-13.00	46.14	V

## LTE Band 5, 1.4MHz, QPSK, Channel 20643

Fragues av/MII=)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Delerization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
3393.57	-40.99	5.46	-7.94	2.15	-40.66	-13.00	27.66	V
3902.05	-61.14	5.92	-8.76	2.15	-60.45	-13.00	47.45	Н
4532.04	-66.01	5.99	-9.43	2.15	-64.72	-13.00	51.72	V
5397.60	-64.88	6.52	-10.46	2.15	-63.09	-13.00	50.09	V
6274.32	-65.56	6.76	-10.77	2.15	-63.70	-13.00	50.70	V
7070.87	-63.71	7.39	-11.69	2.15	-61.56	-13.00	48.56	٧



## LTE Band 5, 1.4MHz, 16QAM, Channel 20407

Fraguanov/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
3299.12	-43.24	5.38	-7.72	2.15	-43.05	-13.00	30.05	V
4503.13	-57.54	5.94	-9.40	2.15	-56.23	-13.00	43.23	Н
5598.18	-64.07	6.74	-10.58	2.15	-62.38	-13.00	49.38	V
7020.68	-60.11	7.45	-11.62	2.15	-58.09	-13.00	45.09	Н
7820.72	-55.71	7.50	-12.46	2.15	-52.90	-13.00	39.90	Н
9249.36	-63.28	8.19	-13.25	2.15	-60.37	-13.00	47.37	V

### LTE Band 5, 1.4MHz, 16QAM, Channel 20525

Fraguenov/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
3346.55	-40.56	5.22	-7.83	2.15	-40.10	-13.00	27.10	V
4285.73	-56.80	5.98	-9.19	2.15	-55.74	-13.00	42.74	Н
5597.03	-66.51	6.73	-10.58	2.15	-64.81	-13.00	51.81	V
6349.11	-56.87	6.88	-10.85	2.15	-55.05	-13.00	42.05	Н
7250.39	-64.35	7.45	-11.90	2.15	-62.05	-13.00	49.05	V
8379.83	-58.36	7.80	-12.90	2.15	-55.41	-13.00	42.41	Н

# LTE Band 5, 1.4MHz, 16QAM, Channel 20643

Fragues av/MII=)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Delerization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
3393.60	-41.58	5.46	-7.94	2.15	-41.25	-13.00	28.25	V
3904.03	-65.13	5.90	-8.77	2.15	-64.41	-13.00	51.41	V
4468.74	-58.84	5.93	-9.37	2.15	-57.55	-13.00	44.55	Н
5401.95	-58.62	6.50	-10.46	2.15	-56.81	-13.00	43.81	Н
6738.06	-57.02	7.12	-11.29	2.15	-55.00	-13.00	42.00	Н
8358.93	-57.87	7.85	-12.89	2.15	-54.98	-13.00	41.98	Н



## LTE Band 7, 5 MHz, QPSK, Channel 20775

Frequency(M Hz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
5005.56	-56.64	6.27	-9.91	-53.00	-13.00	40.00	Н
7554.32	-63.56	7.31	-12.24	-58.63	-13.00	45.63	V
9663.73	-61.74	8.37	-13.24	-56.87	-13.00	43.87	V
12513.39	-58.06	9.39	-13.21	-54.24	-13.00	41.24	V
13655.09	-49.76	10.53	-14.29	-46.00	-13.00	33.00	Н
16619.38	-50.48	11.27	-13.65	-48.10	-13.00	35.10	V

## LTE Band 7, 5 MHz, QPSK, Channel 21100

Frequency(M Hz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
4318.36	-66.04	5.93	-9.22	-62.75	-13.00	49.75	V
5760.68	-66.26	6.78	-10.55	-62.49	-13.00	49.49	٧
8610.78	-66.99	7.71	-13.02	-61.68	-13.00	48.68	V
11523.16	-52.70	9.02	-13.10	-48.62	-13.00	35.62	Н
14344.35	-53.62	10.09	-14.43	-49.28	-13.00	36.28	٧
16442.64	-49.26	11.53	-13.61	-47.18	-13.00	34.18	V

# LTE Band 7, 5 MHz, QPSK, Channel 21425

Frequency(M Hz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
5135.40	-58.55	6.40	-10.09	-54.86	-13.00	41.86	V
6844.55	-61.41	6.90	-11.41	-56.90	-13.00	43.90	V
8649.32	-67.22	7.66	-13.03	-61.85	-13.00	48.85	V
9558.62	-62.15	8.17	-13.34	-56.98	-13.00	43.98	V
13470.80	-56.72	9.94	-14.16	-52.50	-13.00	39.50	٧
14512.51	-55.55	10.31	-14.39	-51.47	-13.00	38.47	V



## LTE Band 7, 5 MHz, 16QAM, Channel 20775

Frequency( MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm	Limit (dBm)	Margin(dB	Polarization
4481.67	-65.19	5.96	-9.38	-61.77	-13.00	48.77	٧
6843.81	-56.91	6.91	-11.41	-52.41	-13.00	39.41	I
8686.49	-64.59	7.65	-13.04	-59.20	-13.00	46.20	٧
10123.36	-62.04	8.31	-12.95	-57.40	-13.00	44.40	V
11843.21	-52.37	9.09	-13.03	-48.43	-13.00	35.43	Н
13384.55	-49.91	9.82	-14.04	-45.69	-13.00	32.69	Н

## LTE Band 7, 5 MHz, 16QAM, Channel 21100

Frequency( MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
4729.16	-56.82	6.14	-9.63	-53.33	-13.00	40.33	Н
7778.50	-57.29	7.20	-12.42	-52.07	-13.00	39.07	Н
10072.20	-56.14	8.68	-12.93	-51.89	-13.00	38.89	H
12488.21	-57.15	9.24	-13.20	-53.19	-13.00	40.19	V
14157.07	-49.60	10.69	-14.47	-45.82	-13.00	32.82	Н
16284.29	-44.66	11.06	-13.64	-42.08	-13.00	29.08	Н

# LTE Band 7, 5 MHz, 16QAM, Channel 21425

Frequency( MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
4252.64	-65.52	6.01	-9.15	-62.38	-13.00	49.38	V
7112.60	-59.44	7.43	-11.74	-55.13	-13.00	42.13	Н
8073.38	-57.55	7.47	-12.66	-52.36	-13.00	39.36	Н
11180.89	-54.60	8.43	-13.16	-49.87	-13.00	36.87	Н
13532.99	-51.30	9.91	-14.22	-46.99	-13.00	33.99	Н
16929.03	-49.98	11.61	-13.77	-47.82	-13.00	34.82	V



## LTE Band 17, 5MHz, QPSK, Channel 23755

Eroguanov/MUz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Morain/dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1413.62	-57.06	3.10	-5.05	2.15	-57.26	-13.00	44.26	V
3048.81	-65.16	4.98	-7.12	2.15	-65.17	-13.00	52.17	V
4239.83	-47.64	6.07	-9.14	2.15	-46.72	-13.00	33.72	Н
5605.21	-58.75	6.77	-10.58	2.15	-57.09	-13.00	44.09	Н
6840.92	-58.34	6.95	-11.41	2.15	-56.03	-13.00	43.03	Н
8358.86	-61.46	7.86	-12.89	2.15	-58.58	-13.00	45.58	V

## LTE Band 17, 5MHz, QPSK, Channel 23790

Fraguenov/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
3125.28	-59.38	5.24	-7.30	2.15	-59.47	-13.00	46.47	Н
4261.08	-48.13	5.97	-9.16	2.15	-47.09	-13.00	34.09	Н
5029.18	-58.13	6.30	-9.94	2.15	-56.64	-13.00	43.64	Н
6088.12	-65.62	6.78	-10.59	2.15	-63.96	-13.00	50.96	V
7075.81	-62.64	7.44	-11.69	2.15	-60.54	-13.00	47.54	V
8062.55	-55.64	7.60	-12.65	2.15	-52.74	-13.00	39.74	Н

## LTE Band 17, 5MHz, QPSK, Channel 23825

Fraguenov/MHz)	P <sub>Mea</sub> (dBm)	Path	Antenna	Correction	Peak	Limit	Morgin(dD)	Polarization
Frequency(MHz)	Mea(ubiii)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1427.75	-57.53	3.09	-5.12	2.15	-57.65	-13.00	44.65	V
3481.47	-58.30	5.40	-8.16	2.15	-57.69	-13.00	44.69	Н
4281.90	-48.30	5.98	-9.18	2.15	-47.25	-13.00	34.25	Н
4923.53	-59.51	6.33	-9.82	2.15	-58.17	-13.00	45.17	Н
5606.66	-63.79	6.78	-10.58	2.15	-62.14	-13.00	49.14	V
6108.76	-62.81	6.86	-10.61	2.15	-61.21	-13.00	48.21	V



## LTE Band 17, 5MHz, 16QAM, Channel 23755

Fraguenov/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
3294.92	-59.10	5.33	-7.71	2.15	-58.87	-13.00	45.87	Н
4239.87	-48.90	6.07	-9.14	2.15	-47.98	-13.00	34.98	Н
5119.21	-62.80	6.51	-10.07	2.15	-61.39	-13.00	48.39	V
6028.88	-61.63	6.91	-10.53	2.15	-60.16	-13.00	47.16	V
7345.72	-56.96	7.09	-12.01	2.15	-54.19	-13.00	41.19	Н
8355.09	-63.83	7.88	-12.88	2.15	-60.98	-13.00	47.98	V

## LTE Band 17, 5MHz, 16QAM, Channel 23790

Fraguanov/MII=)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
3734.82	-66.02	5.22	-8.53	2.15	-64.86	-13.00	51.86	V
4261.05	-46.79	5.97	-9.16	2.15	-45.75	-13.00	32.75	Н
5439.97	-59.90	6.44	-10.52	2.15	-57.97	-13.00	44.97	Н
6783.50	-59.93	7.06	-11.34	2.15	-57.80	-13.00	44.80	V
7587.81	-64.07	7.43	-12.27	2.15	-61.38	-13.00	48.38	V
8360.85	-61.43	7.85	-12.89	2.15	-58.54	-13.00	45.54	V

## LTE Band 17, 5MHz, 16QAM, Channel 23825

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3230.89	-58.00	5.20	-7.55	2.15	-57.80	-13.00	44.80	Н
4282.40	-63.35	5.98	-9.18	2.15	-62.30	-13.00	49.30	V
4885.11	-63.17	6.32	-9.79	2.15	-61.85	-13.00	48.85	V
5757.06	-59.11	6.78	-10.55	2.15	-57.49	-13.00	44.49	Н
6324.42	-60.89	6.92	-10.82	2.15	-59.14	-13.00	46.14	V
7133.15	-55.49	7.09	-11.76	2.15	-52.97	-13.00	39.97	Н

Note: The maximum value of expanded measurement uncertainty for this test item is U = 4.2 dB, k = 2.



#### A.3 FREQUENCY STABILITY

#### Reference

FCC: CFR Part 2.1055, 22.917,24.235, 27.54.

#### A.3.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the EUT to overnight soak at -30℃.
- 3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 2/4/5/7/17, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6. Subject the EUT to overnight soak at  $+50^{\circ}$ C.
- 7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10 ℃ increments from +50℃ to -30℃. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 9. At all temperature levels hold the temperature to +/- 0.5 °C during the measurement procedure.

#### A.3.2 Measurement Limit

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d) (2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance from -5.4% to 10.8%. For the purposes of measuring frequency stability these voltage limits are to be used.



#### A.3.3 Measurement results

## LTE Band 2, 1.4MHz bandwidth (worst case of all bandwidths)

## Frequency Error vs Voltage

Voltage	Frequency error (Hz)		Frequency error (ppm)	
(V)	QPSK	16QAM	QPSK	16QAM
3.5	3.5	0	19	0.000
3.8	3.8	-29	21	0.016
4.2	4.2	-1	20	0.001

## **Frequency Error vs Temperature**

Temperature	Frequency	y error (Hz)	Frequency error (ppm)	
(℃)	QPSK	16QAM	QPSK	16QAM
50°	-1	17	0.000	0.009
40°	-2	14	0.001	0.007
30°	2	17	0.001	0.009
20°	2	18	0.001	0.009
10°	-1	20	0.000	0.011
0°	-4	16	0.002	0.009
- 10°	-2	16	0.001	0.009
- 20°	-1	16	0.001	0.009
- 30°	4	20	0.002	0.011

# LTE Band 4, 1.4MHz bandwidth (worst case of all bandwidths)

### Frequency Error vs Voltage

1 7								
Voltage	Frequency error (Hz)		Frequency	error (ppm)				
(V)	QPSK	16QAM	QPSK	16QAM				
3.5	4	20	0.002	0.012				
3.8	-26	20	0.015	0.012				
4.2	1	23	0.001	0.014				

#### Frequency Error vs Temperature

Temperature	Frequenc	y error (Hz)	Frequency error (ppm	
(℃)	QPSK	16QAM	QPSK	16QAM
50°	2	19	0.001	0.011
40°	4	20	0.002	0.011
30°	4	19	0.002	0.011
20°	0	21	0.000	0.012
10°	2	19	0.001	0.011
0°	0	18	0.000	0.010
- 10°	-1	15	0.001	0.008
- 20°	2	20	0.001	0.012
- 30°	6	21	0.003	0.012



# LTE Band 5, 1.4MHz bandwidth (worst case of all bandwidths)

## Frequency Error vs Voltage

Voltage	Frequency error (Hz)		Frequency error (ppm)	
(V)	QPSK	16QAM	QPSK	16QAM
3.5	1	20	0.001	0.024
3.8	2	19	0.002	0.023
4.2	1	20	0.002	0.024

## **Frequency Error vs Temperature**

Temperature	Frequency	y error (Hz)	Frequency error (ppm)	
(℃)	QPSK	16QAM	QPSK	16QAM
50°	1	18	0.002	0.022
40°	1	19	0.001	0.023
30°	3	20	0.004	0.024
20°	0	19	0.000	0.022
10°	-1	21	0.002	0.025
0°	1	20	0.001	0.024
- 10°	1	19	0.001	0.023
- 20°	-4	21	0.005	0.025
- 30°	1	20	0.001	0.023

## LTE Band 7, 5MHz bandwidth (worst case of all bandwidths)

## Frequency Error vs Voltage

• •	- requested = re-re-re-re-re-re-re-re-re-re-re-re-re-r									
	Voltage	Frequency error (Hz)		Frequency error (ppm)						
	(V)	QPSK	16QAM	QPSK	16QAM					
	3.5	6	-4	0.002	0.002					
	3.8	-16	-13	0.006	0.005					
	4.2	2	0	0.001	0.000					

## **Frequency Error vs Temperature**

Temperature	Frequency error (Hz)		Frequency	error (ppm)
(°C)	QPSK	16QAM	QPSK	16QAM
50°	8	4	0.003	0.002
40°	-6	-2	0.002	0.001
30°	-1	0	0.001	0.000
20°	4	0	0.002	0.000
10°	-1	3	0.001	0.001
0°	7	0	0.003	0.000
- 10°	3	7	0.001	0.003
- 20°	2	0	0.001	0.000
- 30°	-3	4	0.001	0.001



# LTE Band 17, 10MHz bandwidth (worst case of all bandwidths)

## Frequency Error vs Voltage

Voltage	Frequency error (Hz)		Frequency error (ppm)	
(V)	QPSK	16QAM	QPSK	16QAM
3.5	0	-6	0.000	0.008
3.8	2	-2	0.002	0.002
4.2	2	-5	0.003	0.006

# Frequency Error vs Temperature

Temperature	Frequency	y error (Hz)	Frequency e	rror (ppm)
(℃)	QPSK	16QAM	QPSK	16QAM
50°	3	-3	0.004	0.004
40°	-2	-1	0.003	0.002
30°	0	-3	0.001	0.004
20°	3	-3	0.004	0.004
10°	4	-3	0.005	0.004
0°	0	-4	0.001	0.005
- 10°	-1	-2	0.002	0.003
- 20°	2	-3	0.002	0.005
- 30°	0	-1	0.000	0.002

Expanded measurement uncertainty for this test item is 10 Hz, k = 2.



#### A.4 OCCUPIED BANDWIDTH

#### Reference

FCC: CFR Part 2.1049(h)(i)

#### A.4.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from KDB 971168 4.2:


- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least 10log (OBW / RBW) below the reference level.
- d) Set the detection mode to peak, and the trace mode to max hold.
- e) Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

#### LTE band 2, 1.4MHz (99%)

Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1880.0	QPSK	16QAM
	1089.74	1097.76




### LTE band 2, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 01:31:39

#### LTE band 2, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 01:31:54



### LTE band 2, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1880.0	QPSK	16QAM
1000.0	2692.31	2692.31

### LTE band 2, 3MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 01:37:22

### LTE band 2, 3MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 01:37:37



#### LTE band 2, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1880.0	QPSK	16QAM
1000.0	4495.19	4519.23

### LTE band 2, 5MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 01:43:05

### LTE band 2, 5MHz Bandwidth,16QAM (99% BW)




Date: 13.MAY.2015 01:43:21



### LTE band 2, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1880.0	QPSK	16QAM
1000.0	8990.38	8942.31

### LTE band 2, 10MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 01:48:51

# LTE band 2, 10MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 01:49:06



#### LTE band 2, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1880.0	QPSK	16QAM
1000.0	13485.58	13485.58

### LTE band 2, 15MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 01:54:40

# LTE band 2, 15MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 01:54:55



### LTE band 2, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1880.0	QPSK	16QAM
1000.0	17884.62	17884.62

## LTE band 2, 20MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 02:00:33

# LTE band 2, 20MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 02:00:48



#### LTE band 4, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1732.5	QPSK	16QAM
	1097.76	1089.74

## LTE band 4, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 02:06:21

### LTE band 4, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 02:06:36



### LTE band 4, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1732.5	QPSK	16QAM
1732.3	2692.31	2692.31

### LTE band 4, 3MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 02:12:04

### LTE band 4, 3MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 02:12:19



### LTE band 4, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1732.5	QPSK	16QAM
1732.3	4495.19	4495.19

### LTE band 4, 5MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 02:17:49

## LTE band 4, 5MHz Bandwidth,16QAM (99% BW)




Date: 13.MAY.2015 02:18:04



### LTE band 4, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1732.5	QPSK	16QAM
1732.3	8990.38	8990.38

### LTE band 4, 10MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 02:23:33

# LTE band 4, 10MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 02:23:48



### LTE band 4, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1732.5	QPSK	16QAM
1732.3	13485.58	13557.69

### LTE band 4, 15MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 02:29:21

## LTE band 4, 15MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 02:29:37



### LTE band 4, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
4722 F	QPSK	16QAM
1732.5	18076.92	17980.77

## LTE band 4, 20MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 02:35:14

# LTE band 4, 20MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 02:35:29



### LTE band 5, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
836.5	QPSK	16QAM
630.5	1097.76	1097.76

### LTE band 5, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 9.SEP.2015 15:24:57

### LTE band 5, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 9.SEP.2015 15:25:15



### LTE band 5, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
836.5	QPSK	16QAM
630.5	2692.31	2692.31

### LTE band 5, 3MHz Bandwidth, QPSK (99% BW)



Date: 9.SEP.2015 15:40:14

### LTE band 5, 3MHz Bandwidth, 16QAM (99% BW)




Date: 9.SEP.2015 15:40:29



#### LTE band 5, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
836.5	QPSK	16QAM
630.3	4495.19	4495.19

### LTE band 5, 5MHz Bandwidth, QPSK (99% BW)



Date: 9.SEP.2015 15:50:28

### LTE band 5, 5MHz Bandwidth,16QAM (99% BW)




Date: 9.SEP.2015 15:50:43



### LTE band 5, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
836.5	QPSK	16QAM
630.5	8990.38	8990.38

### LTE band 5, 10MHz Bandwidth, QPSK (99% BW)



Date: 9.SEP.2015 21:51:48

## LTE band 5, 10MHz Bandwidth, 16QAM (99% BW)




Date: 9.SEP.2015 15:56:26



#### LTE band 7, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
2525.0	QPSK	16QAM
2535.0	4519.23	4495.19

### LTE band 7, 5MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 01:08:20

### **\LTE band 7, 5MHz Bandwidth,16QAM (99% BW)**




Date: 13.MAY.2015 01:08:35



### LTE band 7, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
2535.0	QPSK	16QAM
2535.0	8990.38	8990.38

## LTE band 7, 10MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 01:14:05

## LTE band 7, 10MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 01:14:20



### LTE band 7, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
2535.0	QPSK	16QAM
2535.0	13485.58	13485.58

## LTE band 7, 15MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 01:19:54

### LTE band 7, 15MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 01:20:09



### LTE band 7, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
2535.0	QPSK	16QAM
2535.0	17980.77	17884.62

### LTE band 7, 20MHz Bandwidth, QPSK (99% BW)



Date: 13.MAY.2015 01:25:48

## LTE band 7, 20MHz Bandwidth, 16QAM (99% BW)




Date: 13.MAY.2015 01:26:03



### LTE band 17, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
710.0	QPSK	16QAM
710.0	4495.19	4519.23

### LTE band 17, 5MHz Bandwidth, QPSK (99% BW)



Date: 9.SEP.2015 16:01:56

## LTE band 17, 5MHz Bandwidth,16QAM (99% BW)




Date: 9.SEP.2015 16:02:11



## LTE band 17, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
710.0	QPSK	16QAM
710.0	8990.38	8942.31

### LTE band 17, 10MHz Bandwidth, QPSK (99% BW)



Date: 9.SEP.2015 16:36:46

### LTE band 17, 10MHz Bandwidth, 16QAM (99% BW)



Date: 9.SEP.2015 16:37:01



# A.5 EMISSION BANDWIDTH

#### Reference

FCC: CFR Part 22.917(b), 24.238(a), 27.53(h), 27.53(m)


#### A.5.1Emission Bandwidth Results

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

### LTE band 2, 1.4MHz (-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1880.0	QPSK	16QAM
1000.0	1266.03	1282.05


### LTE band 2, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 01:32:47



# LTE band 2, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 01:33:04



#### LTE band 2, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1880.0	QPSK	16QAM
1000.0	2964.74	2932.69

### LTE band 2, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 01:38:30

### LTE band 2, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 01:38:48



# LTE band 2, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1880.0	QPSK	16QAM
1000.0	4951.92	4975.96

### LTE band 2, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 01:44:16

### LTE band 2, 5MHz Bandwidth,16QAM (-26dBc BW)




Date: 13.MAY.2015 01:44:33



#### LTE band 2, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1880.0	QPSK	16QAM
1000.0	9807.69	9807.69

### LTE band 2, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 01:49:59

# LTE band 2, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 01:50:16



#### LTE band 2, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1880.0	QPSK	16QAM
1000.0	14783.65	14711.54

### LTE band 2, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 01:55:48

# LTE band 2, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 01:56:05



### LTE band 2, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1000.0	QPSK	16QAM
1880.0	19423.08	19326.92

### LTE band 2, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 02:01:41

# LTE band 2, 20MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 02:01:58



### LTE band 4, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1732.5	QPSK	16QAM
1732.3	1266.03	1274.04

### LTE band 4, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 02:07:29

# LTE band 4, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 02:07:46



# LTE band 4, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1732.5	QPSK	16QAM
1732.3	2948.72	2932.69

# LTE band 4, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 02:13:14

# LTE band 4, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 02:13:31



#### LTE band 4, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1732.5	QPSK	16QAM
1732.3	4951.92	4951.92

### LTE band 4, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 02:18:58

# LTE band 4, 5MHz Bandwidth,16QAM (-26dBc BW)




Date: 13.MAY.2015 02:19:15



### LTE band 4, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1732.5	QPSK	16QAM
1732.3	9759.62	9807.69

# LTE band 4, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 02:24:41

# LTE band 4, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 02:24:58



#### LTE band 4, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1732.5	QPSK	16QAM
1732.3	14783.65	14783.65

### LTE band 4, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 02:30:30

# LTE band 4, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 02:30:47



### LTE band 4, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
4722.5	QPSK	16QAM
1732.5	19423.08	19326.92

### LTE band 4, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 02:36:22

# LTE band 4, 20MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 02:36:39



# LTE band 5, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
836.5	QPSK	16QAM
630.3	1274.04	1274.04

### LTE band 5, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 9.SEP.2015 15:30:38

# LTE band 5, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 9.SEP.2015 15:30:55



# LTE band 5, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
836.5	QPSK	16QAM
630.5	2932.69	2932.69

# LTE band 5, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 9.SEP.2015 15:41:53

# LTE band 5, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 9.SEP.2015 15:42:10



#### LTE band 5, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
836.5	QPSK	16QAM
630.3	4927.88	4903.85

### LTE band 5, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 9.SEP.2015 15:51:36

# LTE band 5, 5MHz Bandwidth,16QAM (-26dBc BW)




Date: 9.SEP.2015 15:51:53



#### LTE band 5, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
836.5	QPSK	16QAM
630.3	9807.69	9807.69

### LTE band 5, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 9.SEP.2015 15:57:20

# LTE band 5, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 9.SEP.2015 15:57:37



# LTE band 7, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
2525.0	QPSK	16QAM
2535.0	4927.88	4951.92

### LTE band 7, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 01:09:29

### LTE band 7, 5MHz Bandwidth,16QAM (-26dBc BW)




Date: 13.MAY.2015 01:09:46



### LTE band 7, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
2525.0	QPSK	16QAM
2535.0	9807.69	9759.62

### LTE band 7, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 01:15:13

# LTE band 7, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 01:15:30



### LTE band 7, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
2525.0	QPSK	16QAM
2535.0	14855.77	14783.65

### LTE band 7, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 01:21:02

# LTE band 7, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 01:21:19



#### LTE band 7, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
2535.0	QPSK	16QAM
2535.0	19326.92	19423.08

### LTE band 7, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 13.MAY.2015 01:26:56

# LTE band 7, 20MHz Bandwidth, 16QAM (-26dBc BW)




Date: 13.MAY.2015 01:27:13



#### LTE band 17, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
710.0	QPSK	16QAM
710.0	4951.92	4927.88

### LTE band 17, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 9.SEP.2015 16:03:04

# LTE band 17, 5MHz Bandwidth,16QAM (-26dBc BW)




Date: 9.SEP.2015 16:03:21



#### LTE band 17, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
710.0	QPSK	16QAM
710.0	9711.54	9807.69

### LTE band 17, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 9.SEP.2015 16:37:55

# LTE band 17, 10MHz Bandwidth, 16QAM (-26dBc BW)



Date: 9.SEP.2015 16:38:12



# A.6 BAND EDGE COMPLIANCE

#### Reference

FCC: CFR Part 22.917(b), 24.238(a), 27.53(h), 27.53(m).

#### A.6.1 Measurement limit


Part 22.917(b), 24.238(a), 27.53(h) state that on any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log (P) dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

According to KDB 971168 6.0, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.



# A.6.2 Measurement result Only worst case result is given below LTE band 2


OBW: 1RB-low\_offset



Date: 14.MAY.2015 00:06:48




# LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 14.MAY.2015 00:07:35




# OBW: 1RB-high\_offset



Date: 13.MAY.2015 22:32:58


# **HIGH BAND EDGE BLOCK-1RB-high\_offset**



Date: 13.MAY.2015 22:33:46




### LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 13.MAY.2015 21:54:20

#### HIGH BAND EDGE BLOCK-20MHz-100%RB




Date: 13.MAY.2015 21:55:08




#### LTE band 4

### **OBW: 1RB-low\_offset**



Date: 13.MAY.2015 22:16:43


#### LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 13.MAY.2015 22:17:30




# OBW: 1RB-high\_offset



Date: 13.MAY.2015 22:37:46


# **HIGH BAND EDGE BLOCK-1RB-high\_offset**



Date: 13.MAY.2015 22:38:32




### LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 13.MAY.2015 21:56:02

#### HIGH BAND EDGE BLOCK-20MHz-100%RB




Date: 13.MAY.2015 21:56:51




#### LTE band 5

### **OBW: 1RB-low\_offset**



Date: 9.SEP.2015 17:41:06


#### LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 9.SEP.2015 17:41:52




# OBW: 1RB-high\_offset



Date: 9.SEP.2015 17:38:57


# **HIGH BAND EDGE BLOCK-1RB-high\_offset**



Date: 9.SEP.2015 17:39:43




### LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 9.SEP.2015 17:03:29

#### HIGH BAND EDGE BLOCK-10MHz-100%RB




Date: 9.SEP.2015 17:04:17




#### LTE band 7

### **OBW: 1RB-low\_offset**



Date: 13.MAY.2015 22:14:57


#### LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 13.MAY.2015 22:15:44




# OBW: 1RB-high\_offset



Date: 13.MAY.2015 22:24:04


# **HIGH BAND EDGE BLOCK-1RB-high\_offset**



Date: 13.MAY.2015 22:24:50




### LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 13.MAY.2015 21:52:41

#### **HIGH BAND EDGE BLOCK-20MHz-100%RB**




Date: 13.MAY.2015 21:53:30




#### LTE band 17

### **OBW: 1RB-low\_offset**



Date: 9.SEP.2015 17:34:04


#### LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 9.SEP.2015 17:34:50




# OBW: 1RB-high\_offset



Date: 9.SEP.2015 17:36:11


# **HIGH BAND EDGE BLOCK-1RB-high\_offset**



Date: 9.SEP.2015 17:36:57




### LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 9.SEP.2015 17:05:06

#### HIGH BAND EDGE BLOCK-10MHz-100%RB



Date: 9.SEP.2015 17:05:55



#### A.7 CONDUCTED SPURIOUS EMISSION

#### Reference

FCC: CFR Part 2.1057, 22.917, 24.238, 27.53(h), 27.53(m).

#### A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
- 2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
- 3. The number of sweep points of spectrum analyzer is set to 30001 which is greater than span/RBW.

#### A. 7.2 Measurement Limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.




#### A. 7.3 Measurement result

# Only worst case result is given below

### LTE band 2: 30MHz - 20GHz


Spurious emission limit -13dBm.



Date: 13.MAY.2015 22:05:17

#### LTE band 4: 30MHz - 20GHz

Spurious emission limit -13dBm.




Date: 13.MAY.2015 22:10:36



#### LTE band 5: 30MHz - 10GHz


Spurious emission limit -13dBm.



Date: 9.SEP.2015 17:31:35

### LTE band 7: 30MHz - 26GHz

Spurious emission limit -13dBm.




Date: 13.MAY.2015 22:02:33



### LTE band 17: 30MHz - 10GHz

Spurious emission limit -13dBm.



Date: 9.SEP.2015 17:32:44



#### A.8 PEAK-TO-AVERAGE POWER RATIO

#### Reference

FCC: CFR Part 24.232 (d), 27.50(a)

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

According to KDB 971168 v02r02 5.7.1:

- a)Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e)Record the maximum PAPR level associated with a probability of 0.1%

#### A.8.1 Measurement limit

not exceed 13 dB

#### A.8.2 Measurement results

#### LTE band 2, 20MHz

Frequency(MHz)	PAPR(dB)	
1960.0	QPSK	16QAM
1860.0	8.37	8.33

#### LTE band 4, 20MHz

Frequency(MHz)	PAPR(dB)	
1745.0	QPSK	16QAM
1745.0	6.57	7.24

#### LTE band 7, 20MHz

Frequency(MHz)	PAPR(dB)	
2510.0	QPSK	16QAM
	8.43	8.53

#### LTE band 17,10MHz

Frequency(MHz)	PAPR(dB)	
710.0	QPSK	16QAM
	5.51	6.31