

# No. I18Z61763-WMD03

for

**TCL Communication Ltd.** 

LTE/UMTS/GSM mobile phone

**Model Name: A501DL** 

FCC ID: 2ACCJH099

with

**Hardware Version: PIO** 

Software Version: vSV5

Issued Date: 2018-10-31



#### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

#### **Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: <a href="mailto:cttl">cttl</a> terminals@caict.ac.cn, website: www.caict.ac.cn

# **REPORT HISTORY**

Report Number	Revision	Description	Issue Date
I18Z61763-WMD03	Rev.0	1st edition	2018-10-31



# **CONTENTS**

1. TE	ST LABORATORY	4
1.1. T	TESTING LOCATION	4
1.2. T	TESTING ENVIRONMENT	4
	PROJECT DATA	
1.4. S	SIGNATURE	4
2. CL	IENT INFORMATION	5
	APPLICANT INFORMATION	
2.2. N	MANUFACTURER INFORMATION	5
	UIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	
	ABOUT EUT	
	NTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	
	NTERNAL IDENTIFICATION OF AE USED DURING THE TEST	
	GENERAL DESCRIPTION	
	FERENCE DOCUMENTS	
	REFERENCE DOCUMENTS FOR TESTING	
	BORATORY ENVIRONMENT	
	MMARY OF TEST RESULTS	
	SUMMARY OF TEST RESULTS	
	ST EQUIPMENTS UTILIZED	
ANNEX	A: MEASUREMENT RESULTS	14
	OUTPUT POWER	
	EMISSION LIMITFREQUENCY STABILITY	
_	OCCUPIED BANDWIDTH	_
	EMISSION BANDWIDTH	
	BAND EDGE COMPLIANCE	
	CONDUCTED SPURIOUS EMISSION	
A.8	PEAK-TO-AVERAGE POWER RATIO	140
ANNFX	B: ACCREDITATION CERTIFICATE	142



# 1. Test Laboratory

#### 1.1. Testing Location

Location 1: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,

P. R. China 100191

Location 2: CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,

Haidian District, Beijing, P. R. China 100191

## 1.2. Testing Environment

Normal Temperature:  $15-35^{\circ}$ C Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2018-09-28
Testing End Date: 2018-10-29

1.4. Signature

**Dong Yuan** 

(Prepared this test report)

11

Zhou Yu

(Reviewed this test report)

Zhao Hui Lin

**Deputy Director of the laboratory** 

(Approved this test report)



## 2. Client Information

## 2.1. Applicant Information

Company Name: TCL Communication Ltd.

7/F, Block F4, TCL Communication Technology Building, TCL

Address / Post: International E City, Zhong Shan Yuan Road, Nanshan District,

Shenzhen, Guangdong, P.R. China 518052

Contact: Gong Zhizhou

Email: zhizhou.gong@tcl.com Telephone: 0086-755-36611722

Fax: 0086-755-36612000-81722

#### 2.2. Manufacturer Information

Company Name: TCL Communication Ltd.

7/F, Block F4, TCL Communication Technology Building, TCL

Address / Post: International E City, Zhong Shan Yuan Road, Nanshan District,

Shenzhen, Guangdong, P.R. China 518052

Contact: Gong Zhizhou

Email: zhizhou.gong@tcl.com Telephone: 0086-755-36611722

Fax: 0086-755-36612000-81722



## 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

## 3.1. About EUT

Description LTE/UMTS/GSM mobile phone

Model Name A501DL FCC ID 2ACCJH099 Antenna Embedded

Output power 24.85dBm maximum EIRP measured for Band 66

Extreme vol. Limits 3.5VDC to 4.4VDC (nominal: 3.8VDC)

Extreme temp. Tolerance 0°C to +55°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

#### 3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	<b>HW Version</b>	SW Version	Date of receipt
UT21a	015293000110191	PIO	vSV5	2018-10-08
UT36A	015293000110167	PIO	vSV5	2018-10-15
UT20A	015293000110209	PIO	vSV5	2018-10-08

<sup>\*</sup>EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

# AE ID\* Description

AE1 Battery

#### AE1

Model CAB2110002C1

Manufacturer BYD Capacitance 2200mAh

#### 3.4. General Description

The Equipment Under Test (EUT) is a model of LTE/UMTS/GSM mobile phone with embedded antenna. Manual and specifications of the EUT were provided to fulfil the test.

<sup>\*</sup>AE ID: is used to identify the test sample in the lab internally.



# 4. Reference Documents

# 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-17
		Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-17
		Edition
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS	10-1-17
	SERVICES	Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment	2016
	Measurement and Performance Standards	
TIA-102.CAAA-E	DIGITAL C4FMCQPSK TRANSCEIVER MEASUREMENT	2016
	METHODS	
ANSI C63.26	American National Standard for Compliance Testing of	2015
	Transmitters Used in Licensed Radio Services	
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF	v03r01
	LICENSED DIGITAL TRANSMITTERS	



# 5. LABORATORY ENVIRONMENT

Control room / conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber 2** (8.6 meters × 6.1 meters × 3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	<1 Ω
Site voltage standing-wave ratio	Between 0 and 6 dB, from 1GHz to 18GHz
$(S_{VSWR})$	
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

**Semi-anechoic chamber 2 / Fully-anechoic chamber 3** (10 meters × 6.7 meters × 6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	<±3.5 dB, 3 m distance
Site voltage standing-wave ratio	Between 0 and 6 dB, from 1GHz to 18GHz
$(S_{VSWR})$	
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz



# 6. SUMMARY OF TEST RESULTS

# 6.1. Summary of test results

Abbreviations used in this clause:		
Р		Pass
Verdict Column	F	Fail
verdict Column	NA	Not applicable
NM		Not measured
Location Column		The test is performed in test location A, B, C or D
Location Column A/B/C/D		which are described in section 1.1 of this report

#### LTE Band 2

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	24.232(c)	A.1	Р
2	Emission Limit	24.238(a), 2.1051	A.2	Р
3	Frequency Stability	24.235, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	24.238(a)	A.5	Р
6	Band Edge Compliance	24.238(a)	A.6	Р
7	Conducted Spurious Emission	24.238, 2.1057	A.7	Р
8	Peak to Average Power Ratio	24.232 (d)	A.8	Р

#### LTE Band 5

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	§2.1046(a), 22.913(a)	A.1	Р
2	Emission Limit	22.917, 2.1051	A.2	Р
3	Frequency Stability	22.235, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	22.917(b)	A.5	Р
6	Band Edge Compliance	22.917(b)	A.6	Р
7	Conducted Spurious Emission	22.917, 2.1057	A.7	Р



#### LTE Band 12

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
			•	_
1	Output Power	27.50(c)(10)	A.1	Р
2	Emission Limit	27.53(g), 2.1051	A.2	Р
3	Frequency Stability	27.54, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	27.53(g)	A.5	Р
6	Band Edge Compliance	27.53(g)	A.6	Р
7	Conducted Spurious Emission	27.53(g), 2.1057	A.7	Р
8	Peak to Average Power Ratio	27.50(a)	A.8	Р

#### LTE Band 13

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	27.50(b)(10)	A.1	Р
2	Emission Limit	27.53(c), 2.1051	A.2	Р
3	Frequency Stability	27.54, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	27.53(c)	A.5	Р
6	Band Edge Compliance	27.53(c)	A.6	Р
7	Conducted Spurious Emission	27.53(c), 2.1057	A.7	Р
8	Peak to Average Power Ratio	27.50(a)	A.8	Р



## LTE Band 66

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	27.50(d)(4)	A.1	Р
2	Emission Limit	27.53(h), 2.1051	A.2	Р
3	Frequency Stability	27.54, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	27.53(h)	A.5	Р
6	Band Edge Compliance	27.53(h)	A.6	Р
7	Conducted Spurious Emission	27.53(h), 2.1057	A.7	Р
8	Peak to Average Power Ratio	27.50(a)	A.8	Р

#### LTE Band 71

Itomo	Test Name	Clause in	Section in	Verdict
Items	rest Name	FCC rules	this report	verdict
1	Output Power	27.50(c)(10)	A.1	Р
2	Emission Limit	27.53(g), 2.1051	A.2	Р
3	Frequency Stability	27.54, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	<b>Emission Bandwidth</b>	27.53(g)	A.5	Р
6	Band Edge Compliance	27.53(g)	A.6	Р
7	Conducted Spurious Emission	27.53(g), 2.1057	A.7	Р
8	Peak to Average Power Ratio	27.50(a)	A.8	Р



#### 6.2. Statements

The test cases listed in section 6.1 of this report for the EUT specified in section 3 were performed by CTTL according to the standards or reference documents in section 4.1

The EUT met all applicable requirements of the standards or reference documents in section 4.1. This report only deals with the LTE functions among the features described in section 3.



# 7. Test Equipments Utilized

NO.	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	Test Receiver	ESU26	100235	R&S	2019-03-31	1 year
2	Test Receiver	ESU26	100376	R&S	2018-12-27	1 year
3	EMI Antenna	3117	00058889	ETS-Lindgren	2020-05-27	3 year
4	Universal Radio Communication Tester	CMU200	108646	R&S	2019-01-05	1 year
5	Universal Radio Communication Tester	CMW500	159082	R&S	2019-01-05	1 year
6	Spectrum Analyzer	FSU26	200030	R&S	2019-06-04	1 year
7	EMI Antenna	VULB9163	9163-235	Schwarzbeck	2019-05-10	3 year
8	Signal Generator	SMF100A	101295	R&S	2018-12-23	1 year
9	Climate chamber	SH-242	93008556	ESPEC	2019-12-21	2 year
10	Loop Antenna	HFH2-Z2	829324/007	R&S	2018-12-14	3 year



## **ANNEX A: MEASUREMENT RESULTS**

#### A.1 OUTPUT POWER

#### A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMW500) to ensure max power transmission and proper modulation. In all cases, output power is within the specified limits.

#### A.1.2 Conducted

#### A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies (bottom, middle and top of operational frequency range) for each bandwidth.


#### A.1.2.2 Measurement result

#### LTE band 2

Dondwidth	RB size/offset	Fraguency (MIII)	Power(dBm)		
Bandwidth	ND SIZE/OIISEL	Frequency (MHz)	QPSK	16QAM	
		1909.3	23.56	22.30	
	1 RB high	1880.0	23.43	22.20	
		1850.7	22.77	22.34	
		1909.3	23.39	22.34	
	1 RB low	1880.0	23.15	22.21	
1.4MHz		1850.7	23.35	22.33	
1.4IVITZ		1909.3	23.53	22.59	
	50% RB mid	1880.0	23.31	22.29	
		1850.7	23.21	22.30	
	100% RB	1909.3	22.54	21.61	
		1880.0	22.30	21.35	
		1850.7	22.19	21.06	
		1908.5	23.56	22.23	
	1 RB high	1880.0	23.24	22.56	
		1851.5	23.13	22.01	
		1908.5	23.47	22.26	
3MHz	1 RB low	1880.0	23.24	22.52	
3MHZ		1851.5	23.14	22.08	
		1908.5	22.51	21.56	
	50% RB mid	1880.0	22.25	21.37	
		1851.5	22.18	21.22	
	100% RB	1908.5	22.45	21.44	



	<u> </u>			
		1880.0	22.26	21.29
		1851.5	22.10	21.08
		1907.5	23.33	22.35
	1 RB high	1880.0	23.15	22.24
		1852.5	23.08	22.44
		1907.5	23.30	22.31
	1 RB low	1880.0	23.14	22.23
5MHz		1852.5	23.03	22.44
JIVII IZ		1907.5	22.44	21.49
	50% RB mid	1880.0	22.26	21.35
		1852.5	22.15	21.31
		1907.5	22.37	21.32
	100% RB	1880.0	22.21	21.29
		1852.5	22.07	21.14
		1905.0	23.48	22.32
	1 RB high	1880.0	23.23	22.04
		1855.0	23.15	22.37
	1 RB low	1905.0	23.34	22.25
		1880.0	23.14	21.98
10MHz		1855.0	23.05	22.31
10111112	50% RB mid	1905.0	22.43	21.49
		1880.0	22.33	21.31
		1855.0	22.15	21.23
		1905.0	22.37	21.41
	100% RB	1880.0	22.20	21.22
		1855.0	22.11	21.16
		1902.5	23.29	22.55
	1 RB high	1880.0	23.14	22.00
		1857.5	23.09	22.29
		1902.5	23.24	22.52
	1 RB low	1880.0	23.08	21.92
		1857.5	23.10	22.27
15MHz		1902.5	22.49	21.42
	50% RB mid	1880.0	22.30	21.31
	30 /0 1\D 11110	1857.5	22.19	21.25
		1902.5	22.46	21.40
	100% RB	1880.0	22.30	21.27
		1857.5	22.21	21.19
20MHz	1 RB high	1900.0	23.07	22.54






		1880.0	22.93	22.36
		1860.0	22.79	22.19
		1900.0	22.92	22.48
	1 RB low	1880.0	22.80	22.23
		1860.0	22.76	22.07
	50% RB mid	1900.0	22.33	21.40
		1880.0	22.23	21.27
		1860.0	22.13	21.15
		1900.0	22.29	21.35
	100% RB	1880.0	22.19	21.20
		1860.0	22.11	21.11



Bandwidth	RB size/offset	Frequency (MHz)	Power(dBm)		
Danuwidin	RB Size/Offset	Frequency (MHZ)	QPSK	16QAM	
		848.3	23.87	22.90	
	1 RB high	836.5	23.92	23.27	
		824.7	23.84	22.82	
		848.3	23.85	22.92	
	1 RB low	836.5	23.97	23.26	
1.4MHz		824.7	23.83	22.79	
1.41/11 12		848.3	23.97	22.98	
	50% RB mid	836.5	24.06	23.22	
		824.7	23.97	23.12	
		848.3	23.06	22.07	
	100% RB	836.5	22.99	21.85	
		824.7	23.00	22.10	
		847.5	23.87	22.84	
	1 RB high	836.5	23.94	22.79	
		825.5	23.96	23.22	
	1 RB low	847.5	23.93	22.92	
		836.5	23.90	22.81	
ON41.1-		825.5	23.97	23.16	
3MHz	50% RB mid	847.5	23.02	22.01	
		836.5	22.98	22.06	
		825.5	22.97	21.99	
		847.5	22.94	21.85	
	100% RB	836.5	22.96	21.93	
		825.5	22.87	21.90	
		846.5	23.84	22.90	
	1 RB high	836.5	23.93	22.97	
		826.5	23.85	23.27	
		846.5	23.86	22.87	
	1 RB low	836.5	23.94	22.96	
5MU→		826.5	23.86	23.26	
5MHz		846.5	22.96	22.01	
	50% RB mid	836.5	22.95	22.02	
		826.5	22.91	22.05	
		846.5	22.93	21.86	
	100% RB	836.5	22.91	21.90	
		826.5	22.87	21.88	
10MHz	1 RB high	844.0	23.93	23.22	
ΙΟΙΝΙΠΖ	I KD IIIGII	836.5	23.88	22.92	

©Copyright. All rights reserved by CTTL.





		829.0	23.88	22.81
		844.0	23.95	23.20
	1 RB low	836.5	23.85	22.86
		829.0	23.90	22.70
		844.0	22.94	21.99
	50% RB mid	836.5	23.00	22.06
		829.0	22.93	21.93
	100% RB	844.0	22.97	21.99
		836.5	23.00	21.98
		829.0	22.90	21.85



Pandwidth	RB size/offset Frequency (MHz)		Power	Power(dBm)	
Bandwidth	RB size/offset	Frequency (MHZ)	QPSK	16QAM	
		715.3	23.95	22.81	
	1 RB high	707.5	24.03	22.98	
		699.7	24.10	23.26	
		715.3	23.96	22.84	
	1 RB low	707.5	24.05	22.93	
4 48411-		699.7	24.11	23.28	
1.4MHz		715.3	24.04	23.13	
	50% RB mid	707.5	24.05	23.03	
		699.7	24.15	23.18	
		715.3	23.13	22.16	
	100% RB	707.5	23.08	22.14	
		699.7	23.16	22.01	
		714.5	23.96	22.81	
	1 RB high	707.5	24.01	22.77	
		700.5	24.12	23.27	
	1 RB low	714.5	23.98	22.89	
		707.5	23.97	22.81	
0.41.1		700.5	24.12	23.24	
3MHz	50% RB mid	714.5	23.05	22.09	
		707.5	23.05	22.12	
		700.5	23.15	22.16	
		714.5	22.93	21.94	
	100% RB	707.5	22.96	22.01	
		700.5	23.03	22.05	
		713.5	23.89	22.82	
	1 RB high	707.5	23.99	22.95	
		701.5	23.93	23.35	
		713.5	23.90	22.90	
	1 RB low	707.5	23.99	22.92	
EN 41 1		701.5	23.96	23.32	
5MHz		713.5	23.01	22.08	
	50% RB mid	707.5	23.01	22.08	
		701.5	23.06	22.20	
		713.5	22.96	21.90	
	100% RB	707.5	22.97	21.99	
		701.5	22.98	22.04	
	4	711.0	24.03	22.75	
10MHz	1 RB high	707.5	24.05	23.23	

©Copyright. All rights reserved by CTTL.



		704.0	23.97	22.90
		711.0	23.94	22.77
	1 RB low	707.5	24.03	23.23
		704.0	24.03	22.89
	50% RB mid	711.0	23.04	22.03
		707.5	23.02	22.06
		704.0	23.02	22.11
		711.0	22.99	21.98
		707.5	23.01	22.03
		704.0	22.97	22.02

Bandwidth	DP size/offeet	Fraguency (MUz)	Power(dBm)	
Danuwiuin	RB size/offset	Frequency (MHz)	QPSK	16QAM
		784.5	23.58	22.51
	1 RB high	782	23.62	22.61
		779.5	23.57	22.97
		784.5	23.54	22.57
	1 RB low	782	23.64	22.56
5MHz		779.5	23.62	22.84
SIVITZ		784.5	22.69	21.73
	50% RB mid	782	22.66	21.74
		779.5	22.67	21.79
		784.5	22.66	21.62
	100% RB	782	22.63	21.62
		779.5	22.57	21.61
10MHz	1 RB high	782.0	23.71	22.41
	1 RB low	782.0	23.68	22.36
	50% RB mid	782.0	22.67	21.71
	100% RB	782.0	22.73	21.66



Pandwidth	RB size/offset Frequency (MHz)		Power(dBm)		
Bandwidth	RB SIZE/Offset	Frequency (MHZ)	QPSK	16QAM	
		1779.3	23.64	22.63	
	1 RB high	1745.0	23.77	22.78	
		1710.7	23.80	22.80	
		1779.3	23.55	22.67	
	1 RB low	1745.0	23.71	22.80	
4 4111-		1710.7	23.74	22.78	
1.4MHz		1779.3	23.73	22.77	
	50% RB mid	1745.0	23.84	23.10	
		1710.7	23.88	23.13	
		1779.3	22.77	21.85	
	100% RB	1745.0	22.85	22.00	
		1710.7	22.88	22.06	
		1778.5	23.66	22.54	
	1 RB high	1745.0	23.81	22.74	
	_	1711.5	23.92	22.69	
	1 RB low	1778.5	23.68	22.68	
		1745.0	23.71	22.83	
0.14.1		1711.5	23.82	22.74	
3MHz	50% RB mid	1778.5	22.73	21.73	
		1745.0	22.82	21.90	
		1711.5	22.88	22.02	
		1778.5	22.69	21.63	
	100% RB	1745.0	22.76	21.78	
		1711.5	22.87	21.91	
		1777.5	23.48	22.59	
	1 RB high	1745.0	23.62	22.78	
		1712.5	23.71	22.68	
		1777.5	23.52	22.59	
	1 RB low	1745.0	23.60	22.76	
55 41 1		1712.5	23.68	22.78	
5MHz		1777.5	22.68	21.76	
	50% RB mid	1745.0	22.80	21.88	
		1712.5	22.90	21.96	
		1777.5	22.67	21.62	
	100% RB	1745.0	22.72	21.79	
		1712.5	22.83	21.78	
405.00	4.55	1775.0	23.63	22.48	
10MHz	1 RB high	1745.0	23.71	22.68	

©Copyright. All rights reserved by CTTL.




		1715.0	23.80	22.75
		1775.0	23.52	22.48
	1 RB low	1745.0	23.61	22.65
		1715.0	23.75	22.79
		1775.0	22.72	21.73
	50% RB mid	1745.0	22.83	21.82
		1715.0	22.65	21.94
		1775.0	22.72	21.71
	100% RB	1745.0	22.77	21.87
		1715.0	22.97	22.02
		1772.5	23.63	22.94
	1 RB high	1745.0	23.72	23.06
		1717.5	23.78	22.72
		1772.5	23.69	22.97
	1 RB low	1745.0	23.77	23.15
451411-		1717.5	23.78	22.69
15MHz		1772.5	22.90	21.81
	50% RB mid	1745.0	22.89	21.85
		1717.5	23.01	22.00
		1772.5	22.89	21.84
	100% RB	1745.0	22.96	21.90
		1717.5	23.05	21.99
		1770.0	23.36	22.76
	1 RB high	1745.0	23.48	22.89
		1720.0	23.59	23.13
		1770.0	23.40	22.83
	1 RB low	1745.0	23.50	22.96
20MHz		1720.0	23.54	23.06
ZUIVITZ		1770.0	22.74	21.71
	50% RB mid	1745.0	22.85	21.85
		1720.0	22.94	21.92
		1770.0	22.75	21.75
	100% RB	1745.0	22.94	21.91
		1720.0	22.91	21.89



Pandwidth	DP oizo/offost	Fraguency (MIII-)	Powe	r(dBm)
Bandwidth	RB size/offset	Frequency (MHz)	QPSK	16QAM
		695.5	23.37	22.64
	1 RB high	680.5	23.31	22.24
		665.5	23.45	22.38
		695.5	23.39	22.61
	1 RB low	680.5	23.35	22.23
5MHz		665.5	23.39	22.29
JIVII IZ		695.5	22.50	21.65
	50% RB mid	680.5	22.52	21.57
		665.5	22.57	21.46
		695.5	22.46	21.48
	100% RB	680.5	22.46	21.43
		665.5	22.57	21.49
		693	23.56	22.64
	1 RB high	680.5	23.52	22.61
		668	23.56	22.69
		693	23.51	22.64
	1 RB low	680.5	23.52	22.63
10MHz		668	23.49	22.60
TOWN 12		693	22.63	21.61
	50% RB mid	680.5	22.57	21.54
		668	22.59	21.64
		693	22.67	21.59
	100% RB	680.5	22.56	21.54
		668	22.62	21.59
		690.5	23.41	22.29
	1 RB high	680.5	23.41	22.78
		670.5	23.46	22.72
		690.5	23.33	22.21
	1 RB low	680.5	23.46	22.78
		670.5	23.49	22.70
15MHz		690.5	22.61	21.58
	50% RB mid	680.5	22.62	21.59
	JU /0 KD IIIIU			
		670.5	22.67	21.63
		690.5	22.63	21.57
	100% RB	680.5	22.64	21.56
		670.5	22.69	21.63
20MHz	1 RB high	688	23.15	22.13

©Copyright. All rights reserved by CTTL.





	680.5	23.17	22.18
	673	23.16	22.14
	688	23.12	22.10
1 RB low	680.5	23.17	22.19
	673	23.15	22.13
	688	22.47	21.48
50% RB mid	680.5	22.54	21.57
	673	22.58	21.49
	688	22.49	21.52
100% RB	680.5	22.53	21.48
	673	22.49	21.51



#### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Rule Part 22.913(a) specifies "Mobile stations are limited to 2.0 watts EIRP.".

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 27.50(d) specifies "Fixed, mobile, and portable (handheld) stations operating in the

Rule Part 27.50(d) specifies "Fixed, mobile, and portable (handheld) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP".


Rule Part 27.50(h)(2) specifies "Mobile stations are limited to 2.0 watts EIRP.".

Rule Part 27.50(c) specifies "Portable stations (hand-held de-vices) are limited to 3 watts ERP.". Rule Part 27.50(a)(3) specifies "For mobile and portable stations transmitting in the 2305–2315 MHz band or the 2350–2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, except that for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth."

#### A.1.3.2 Method of Measurement


The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.





In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{\text{Mea}}$ ) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded ( $P_{\text{r}}$ ). The power of signal source ( $P_{\text{Mea}}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

- 4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the amplifier and the substitution antenna.
  - The cable loss  $(P_{cl})$ , the substitution antenna Gain  $(G_a)$  and the amplifier Gain  $(P_{Ag})$  should be recorded after test.

The measurement results are obtained as described below:

Power (EIRP) = 
$$P_{Mea} - P_{Ag} - P_{cl} - G_a$$

- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15.



#### A.1.3.3 Measurement result

LTE Band 2- EIRP 24. 232(b)

**Limits:** ≤33dBm (2W)

#### LTE Band 2\_1.4MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1850.70	-24.85	2.92	43.75	4.87	20.85	33.00	12.15	Н
1880.00	-25.12	2.85	43.75	4.82	20.60	33.00	12.40	Н
1909.30	-23.24	2.87	43.77	4.76	22.42	33.00	10.58	Н

#### LTE Band 2\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1851.50	-24.77	2.87	43.75	4.87	20.98	33.00	12.02	Н
1880.00	-25.64	2.85	43.75	4.82	20.08	33.00	12.92	Н
1908.50	-23.30	2.89	43.78	4.76	22.35	33.00	10.65	Н

#### LTE Band 2\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.50	-24.83	2.87	43.75	4.87	20.92	33.00	12.08	Н
1880.00	-25.23	2.85	43.75	4.82	20.49	33.00	12.51	Н
1907.50	-23.45	2.84	43.77	4.77	22.25	33.00	10.75	Н

## LTE Band 2\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1855.00	-25.18	2.88	43.74	4.86	20.54	33.00	12.46	Н
1880.00	-25.21	2.85	43.75	4.82	20.51	33.00	12.49	Н
1905.00	-23.09	2.87	43.77	4.77	22.58	33.00	10.42	Н

## LTE Band 2\_15MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1857.50	-25.29	2.87	43.75	4.86	20.45	33.00	12.55	Н
1880.00	-25.22	2.85	43.75	4.82	20.50	33.00	12.50	Н
1902.50	-23.26	2.86	43.77	4.78	22.43	33.00	10.57	Н

## LTE Band 2\_20 MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1860.00	-25.24	2.86	43.75	4.85	20.50	33.00	12.50	Н
1880.00	-25.13	2.85	43.75	4.82	20.59	33.00	12.41	Н
1900.00	-23.47	2.87	43.77	4.78	22.21	33.00	10.79	Н



## LTE Band 2\_1.4MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1850.70	-26.08	2.92	43.75	4.87	19.62	33.00	13.38	Н
1880.00	-26.11	2.85	43.75	4.82	19.61	33.00	13.39	Н
1909.30	-24.18	2.87	43.77	4.76	21.48	33.00	11.52	Н

#### LTE Band 2\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1851.50	-26.02	2.87	43.75	4.87	19.73	33.00	13.27	Н
1880.00	-26.21	2.85	43.75	4.82	19.51	33.00	13.49	Н
1908.50	-24.29	2.89	43.78	4.76	21.36	33.00	11.64	Н

# LTE Band 2\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.50	-26.04	2.87	43.75	4.87	19.71	33.00	13.29	Н
1880.00	-26.06	2.85	43.75	4.82	19.66	33.00	13.34	Н
1907.50	-24.35	2.84	43.77	4.77	21.35	33.00	11.65	Н

## LTE Band 2\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1855.00	-26.44	2.88	43.74	4.86	19.28	33.00	13.72	Н
1880.00	-26.14	2.85	43.75	4.82	19.58	33.00	13.42	Н
1905.00	-24.11	2.87	43.77	4.77	21.56	33.00	11.44	Н

# LTE Band 2\_15MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1857.50	-26.49	2.87	43.75	4.86	19.25	33.00	13.75	Н
1880.00	-26.08	2.85	43.75	4.82	19.64	33.00	13.36	Н
1902.50	-24.49	2.86	43.77	4.78	21.20	33.00	11.80	Н

#### LTE Band 2\_20 MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1860.00	-26.49	2.86	43.75	4.85	19.25	33.00	13.75	Н
1880.00	-25.98	2.85	43.75	4.82	19.74	33.00	13.26	Н
1900.00	-24.72	2.87	43.77	4.78	20.96	33.00	12.04	Н



# LTE Band 5- ERP 22.913(a) Limits: ≤38.45dBm (7W) LTE Band 5\_1.4MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
824.70	-19.82	2.26	45.79	0.95	2.15	22.51	38.45	15.94	Н
836.50	-20.37	2.26	45.66	0.82	2.15	21.70	38.45	16.75	Н
848.30	-20.16	2.27	45.55	0.80	2.15	21.77	38.45	16.68	Н

## LTE Band 5\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
825.50	-19.58	2.26	45.79	0.94	2.15	22.74	38.45	15.71	Н
836.50	-19.95	2.26	45.66	0.82	2.15	22.12	38.45	16.33	Н
847.50	-19.65	2.27	45.56	0.81	2.15	22.30	38.45	16.15	Н

## LTE Band 5\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.50	-19.34	2.25	45.77	0.93	2.15	22.96	38.45	15.49	Н
836.50	-20.12	2.26	45.66	0.82	2.15	21.95	38.45	16.50	Н
846.50	-19.57	2.26	45.56	0.82	2.15	22.40	38.45	16.05	Н

#### LTE Band 5\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
829.00	-19.46	2.13	45.74	0.90	2.15	22.90	38.45	15.55	Н
836.50	-20.22	2.26	45.66	0.82	2.15	21.85	38.45	16.60	Н
844.00	-19.37	2.26	45.59	0.82	2.15	22.63	38.45	15.82	Н



## LTE Band 5\_1.4MHz\_16QAM

Fraguanov/MHz)	D (dDm)	P <sub>cl</sub> (dB)	D (dD)	Ga Antenna	Correction	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (ub)	P <sub>Ag</sub> (dB)	Gain(dBi)	(dB)	ERP(UBIII)	Lilliit(UBIII)	wargin(ub)	Polarization
824.70	-21.10	2.26	45.79	0.95	2.15	21.23	38.45	17.22	Н
836.50	-20.69	2.26	45.66	0.82	2.15	21.38	38.45	17.07	Н
848.30	-21.20	2.27	45.55	0.80	2.15	20.73	38.45	17.72	Н

# LTE Band 5\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
825.50	-20.70	2.26	45.79	0.94	2.15	21.62	38.45	16.83	Н
836.50	-20.61	2.26	45.66	0.82	2.15	21.46	38.45	16.99	Н
847.50	-20.69	2.27	45.56	0.81	2.15	21.26	38.45	17.19	Н

#### LTE Band 5\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Aq</sub> (dB)	Ga Antenna	Correction	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
r requeriey(wiriz)	i Mea(dDiii)	I cl(GD)	1 Ag(GD)	Gain(dBi)	(dB)	LIVI (dbiii)	Limit(dDin)	Margin(db)	1 Olarization
826.50	-20.68	2.25	45.77	0.93	2.15	21.62	38.45	16.83	Н
836.50	-20.00	2.26	45.66	0.82	2.15	22.07	38.45	16.38	Н
846.50	-20.67	2.26	45.56	0.82	2.15	21.30	38.45	17.15	Н

# LTE Band 5\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
829.00	-20.37	2.13	45.74	0.90	2.15	21.99	38.45	16.46	Н
836.50	-20.31	2.26	45.66	0.82	2.15	21.76	38.45	16.69	Н
844.00	-20.66	2.26	45.59	0.82	2.15	21.34	38.45	17.11	Н



## LTE Band 12 - ERP 27.50(c)(10)

Limits: ≤34.77dBm (3W) LTE Band 12\_1.4MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
699.70	-27.89	1.90	44.66	0.77	2.15	13.49	34.77	21.28	V
707.50	-28.03	1.91	44.94	0.62	2.15	13.47	34.77	21.30	V
715.30	-27.80	1.92	45.26	0.50	2.15	13.89	34.77	20.88	V

## LTE Band 12\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
700.50	-28.02	1.90	44.68	0.76	2.15	13.37	34.77	21.40	V
707.50	-28.11	1.91	44.94	0.62	2.15	13.39	34.77	21.38	Н
714.50	-27.82	1.92	45.26	0.50	2.15	13.87	34.77	20.90	V

## LTE Band 12\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
701.50	-27.85	1.90	44.81	0.74	2.15	13.65	34.77	21.12	V
707.50	-28.15	1.91	44.94	0.62	2.15	13.35	34.77	21.42	V
713.50	-27.95	1.92	45.22	0.50	2.15	13.70	34.77	21.07	V

#### LTE Band 12\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
704.00	-27.90	1.91	44.93	0.70	2.15	13.67	34.77	21.10	V
707.50	-28.20	1.91	44.94	0.62	2.15	13.30	34.77	21.47	V
711.00	-28.26	1.92	45.19	0.53	2.15	13.39	34.77	21.38	V



## LTE Band 12\_1.4MHz\_16QAM

Fraguanov(MHZ)	D (dDm)	D (4D)	D (dD)	Ga Antenna	Correction	ERP(dBm)	Limit(dBm)	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Gain(dBi)	(dB)	ERP(UBIII)	LIIIII(UDIII)	Margin(dB)	Polarization
699.70	-28.87	1.90	44.66	0.77	2.15	12.51	34.77	22.26	V
707.50	-28.96	1.91	44.94	0.62	2.15	12.54	34.77	22.23	V
715.30	-28.53	1.92	45.26	0.50	2.15	13.16	34.77	21.61	V

# LTE Band 12\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
700.50	-28.78	1.90	44.68	0.76	2.15	12.61	34.77	22.16	V
707.50	-29.05	1.91	44.94	0.62	2.15	12.45	34.77	22.32	V
714.50	-28.89	1.92	45.26	0.50	2.15	12.80	34.77	21.97	V

## LTE Band 12\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
701.50	-28.83	1.90	44.81	0.74	2.15	12.67	34.77	22.10	V
707.50	-29.03	1.91	44.94	0.62	2.15	12.47	34.77	22.30	V
713.50	-28.68	1.92	45.22	0.50	2.15	12.97	34.77	21.80	V

## LTE Band 12\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
704.00	-28.77	1.91	44.93	0.70	2.15	12.80	34.77	21.97	V
707.50	-29.09	1.91	44.94	0.62	2.15	12.41	34.77	22.36	V
711.00	-29.23	1.92	45.19	0.53	2.15	12.42	34.77	22.35	V



## LTE Band 13- ERP 27.50(b)(10)

**Limits:** ≤34.77 dBm (3W)

## LTE Band 13\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
779.50	-23.41	2.01	45.64	0.04	2.15	18.11	34.77	16.66	V
782.00	-23.17	2.01	45.65	0.09	2.15	18.41	34.77	16.36	V
784.50	-22.92	2.01	45.67	0.16	2.15	18.75	34.77	16.02	V

#### LTE Band 13\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
782.00	-22.94	2.01	45.65	0.09	2.15	18.64	34.77	16.13	V

#### LTE Band 13\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
779.50	-24.28	2.01	45.64	0.04	2.15	17.24	34.77	17.53	V
782.00	-24.34	2.01	45.65	0.09	2.15	17.24	34.77	17.53	V
784.50	-23.84	2.01	45.67	0.16	2.15	17.83	34.77	16.94	V

## LTE Band 13\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
782.00	-24.26	2.01	45.65	0.09	2.15	17.32	34.77	17.45	٧



## LTE Band 66- EIRP 27.50(d)

**Limits:** ≤30dBm (1W)

## LTE Band 66\_1.4MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1710.70	-31.02	3.17	44.10	5.12	21.37	33.00	11.63	Н
1745.00	-31.27	3.68	44.16	5.06	21.63	33.00	11.37	Н
1779.30	-27.22	3.04	44.03	5.00	24.85	33.00	8.15	Н

#### LTE Band 66\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1711.50	-31.49	3.40	44.10	5.12	21.13	33.00	11.87	Н
1745.00	-31.38	3.68	44.16	5.06	21.52	33.00	11.48	Н
1778.50	-27.30	3.04	44.03	5.00	24.77	33.00	8.23	Н

#### LTE Band 66\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.50	-24.11	3.66	44.10	5.12	21.45	33.00	11.55	Н
1745.00	-23.82	3.68	44.16	5.06	21.72	33.00	11.28	Н
1777.50	-22.02	3.04	44.04	5.00	23.98	33.00	9.02	Н

#### LTE Band 66\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1715.00	-24.24	3.56	44.10	5.11	21.41	33.00	11.59	Н
1745.00	-23.78	3.68	44.16	5.06	21.76	33.00	11.24	Н
1775.00	-21.91	3.05	44.05	5.01	24.09	33.00	8.91	Н

#### LTE Band 66\_15MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1717.50	-24.32	3.47	44.11	5.11	21.43	33.00	11.57	Н
1745.00	-23.81	3.68	44.16	5.06	21.73	33.00	11.27	Н
1772.50	-22.41	3.05	44.06	5.01	23.61	33.00	9.39	Н

## LTE Band 66\_20MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1720.00	-24.25	3.37	44.11	5.10	21.59	33.00	11.41	Н
1745.00	-23.90	3.68	44.16	5.06	21.64	33.00	11.36	V
1770.00	-22.11	3.05	44.07	5.01	23.93	33.00	9.07	Н



#### LTE Band 66\_1.4MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1710.70	-31.97	3.17	44.10	5.12	20.42	33.00	12.58	Н
1745.00	-32.14	3.68	44.16	5.06	20.76	33.00	12.24	Н
1779.30	-28.13	3.04	44.03	5.00	23.94	33.00	9.06	Н

#### LTE Band 66\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1711.50	-32.37	3.40	44.10	5.12	20.25	33.00	12.75	Н
1745.00	-32.10	3.68	44.16	5.06	20.80	33.00	12.20	V
1778.50	-28.22	3.04	44.03	5.00	23.85	33.00	9.15	Н

#### LTE Band 66\_5MHz\_16QAM

Frequency	(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.	50	-24.92	3.66	44.10	5.12	20.64	33.00	12.36	Н
1745.	00	-24.56	3.68	44.16	5.06	20.98	33.00	12.02	Н
1777.	50	-22.94	3.04	44.04	5.00	23.06	33.00	9.94	Н

#### LTE Band 66\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1715.00	-24.75	3.56	44.10	5.11	20.90	33.00	12.10	Н
1745.00	-24.51	3.68	44.16	5.06	21.03	33.00	11.97	H
1775.00	-22.66	3.05	44.05	5.01	23.34	33.00	9.66	Н

#### LTE Band 66\_15MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1717.50	-25.09	3.47	44.11	5.11	20.66	33.00	12.34	Н
1745.00	-24.58	3.68	44.16	5.06	20.96	33.00	12.04	Н
1772.50	-23.49	3.05	44.06	5.01	22.53	33.00	10.47	Н

## LTE Band 66\_20MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1720.00	-25.28	3.37	44.11	5.10	20.56	33.00	12.44	Н
1745.00	-24.47	3.68	44.16	5.06	21.07	33.00	11.93	Н
1770.00	-23.25	3.05	44.07	5.01	22.79	33.00	10.21	Н



## LTE Band 71- ERP 27.50(c)(10)

**Limits:** ≤34.77 dBm (3W)

# LTE Band 71\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
665.50	-30.21	1.87	44.73	0.78	2.15	11.28	34.77	23.49	V
680.50	-28.91	1.88	44.72	0.78	2.15	12.55	34.77	22.22	V
695.50	-28.11	1.89	44.67	0.77	2.15	13.29	34.77	21.48	V

#### LTE Band 71\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
668.00	-29.84	1.87	44.75	0.78	2.15	11.68	34.77	23.09	V
680.50	-28.74	1.88	44.72	0.78	2.15	12.73	34.77	22.04	V
693.00	-27.98	1.89	44.67	0.77	2.15	13.42	34.77	21.35	V

## LTE Band 71\_15MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
670.50	-29.12	1.88	44.75	0.78	2.15	12.38	34.77	22.39	V
680.50	-29.12	1.88	44.72	0.78	2.15	12.34	34.77	22.43	V
690.50	-28.25	1.89	44.73	0.77	2.15	13.22	34.77	21.55	V

#### LTE Band 71\_20MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna	Correction	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
				Gain(dBi)	(dB)				
673.00	-29.75	1.88	44.71	0.78	2.15	11.71	34.77	23.06	V
680.50	-29.13	1.88	44.72	0.78	2.15	12.33	34.77	22.44	V
688.00	-28.66	1.89	44.72	0.77	2.15	12.80	34.77	21.97	V



#### LTE Band 71\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
665.50	-31.05	1.87	44.73	0.78	2.15	10.44	34.77	24.33	V
680.50	-29.83	1.88	44.72	0.78	2.15	11.63	34.77	23.14	V
695.50	-28.87	1.89	44.67	0.77	2.15	12.53	34.77	22.24	V

#### LTE Band 71\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
668.00	-30.77	1.87	44.75	0.78	2.15	10.75	34.77	24.02	V
680.50	-29.91	1.88	44.72	0.78	2.15	11.56	34.77	23.21	V
693.00	-28.92	1.89	44.67	0.77	2.15	12.48	34.77	22.29	V

#### LTE Band 71\_15MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
670.50	-30.46	1.88	44.75	0.78	2.15	11.04	34.77	23.73	V
680.50	-29.93	1.88	44.72	0.78	2.15	11.53	34.77	23.24	V
690.50	-29.05	1.89	44.73	0.77	2.15	12.42	34.77	22.35	V

#### LTE Band 71\_20MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
673.00	-30.73	1.88	44.71	0.78	2.15	10.73	34.77	24.04	V
680.50	-29.98	1.88	44.72	0.78	2.15	11.49	34.77	23.28	V
688.00	-29.42	1.89	44.72	0.77	2.15	12.04	34.77	22.73	V

Peak EIRP(dBm) =  $P_{Mea}$ (-27.22dBm) -  $G_a$  (-5.00dBi) -  $P_{Ag}$  (-44.03dB) -  $P_{cl}$  (3.04dB) = 24.85dBm **ANALYZER SETTINGS**:

RBW = VBW = 8MHz for occupied bandwdiths equal to or less than 5MHz.

RBW = VBW = 20MHz for occupied bandwidths equal to or greater than 10MHz.

Note: Expanded measurement uncertainty is U = 0.96 dB, k = 2.



# **A.2 EMISSION LIMIT**


#### A.2.1 Measurement Method

The measurements procedures in TIA-603E-2016 are used. This measurement is carried out in fully-anechoic chamber FAC-3.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier. The resolution bandwidth is set 1MHz. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE Bands 2 5 12 13 66 71.

#### The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power  $(P_{Mea})$  is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the



receiver reaches the previously recorded  $(P_r)$ . The power of signal source  $(P_{Mea})$  is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P<sub>pl</sub>) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G<sub>a</sub>) should be recorded after test.

An amplifier should be connected in for the test.

The Path loss (P<sub>pl</sub>) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

Power (EIRP)= $P_{Mea}$ +  $P_{pl}$  +  $G_a$ 

- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit: dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dB.

#### A.2.2 Measurement Limit

Part 22.917, Part 24.238(a), Part 27.53(g), Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(a) states for mobile and portable stations operating in the 2305–2315 MHz and 2350–2360 MHz bands: By a factor of not less than: 43 +10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB onall frequencies between 2328 and 2337MHz; By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2296 and 2300MHz, 61 + 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288 and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz; By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.

#### A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the LTE Bands 2 5 12 13 66 71. It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the LTE Bands 2 5 12 13 66 71 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this. The evaluated frequency range is from 30MHz to 26GHz.



# LTE Band 2, 1.4MHz, QPSK, Channel 18607

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3701.02	-49.52	6.42	8.48	-47.46	-13.00	34.46	Н
5554.02	-47.36	7.19	10.59	-43.96	-13.00	30.96	Н
7405.01	-37.27	8.13	12.09	-33.31	-13.00	20.31	Н
9260.01	-41.15	9.06	13.26	-36.95	-13.00	23.95	V
11113.01	-51.74	9.78	13.18	-48.34	-13.00	35.34	Н
13001.01	-48.99	10.47	13.50	-45.96	-13.00	32.96	Н

# LTE Band 2, 1.4MHz, QPSK, Channel 18900

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Anten na Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3760.02	-46.84	6.26	8.56	-44.54	-13.00	31.54	Н
5645.02	-55.18	7.27	10.57	-51.88	-13.00	38.88	V
7524.01	-35.69	8.29	12.22	-31.76	-13.00	18.76	Н
9409.01	-49.24	9.08	13.35	-44.97	-13.00	31.97	Н
11239.01	-50.80	9.63	13.15	-47.28	-13.00	34.28	Н
13161.01	-47.09	10.67	13.73	-44.03	-13.00	31.03	Н

#### LTE Band 2, 1.4MHz, QPSK, Channel 19193

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3819.02	-48.59	6.08	8.65	-46.02	-13.00	33.02	Н
5731.02	-52.67	7.29	10.55	-49.41	-13.00	36.41	Н
7641.01	-33.68	8.16	12.31	-29.53	-13.00	16.53	Η
9553.01	-40.05	9.35	13.35	-36.05	-13.00	23.05	Н
11469.01	-50.39	9.89	13.11	-47.17	-13.00	34.17	Н
13390.01	-47.31	10.57	14.05	-43.83	-13.00	30.83	Н



# LTE Band 2, 1.4MHz, 16QAM, Channel 18607

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3701.02	-49.54	6.42	8.48	-47.48	-13.00	34.48	Н
5556.02	-48.51	7.19	10.59	-45.11	-13.00	32.11	Н
7406.01	-40.11	8.13	12.09	-36.15	-13.00	23.15	Η
9259.01	-40.99	9.06	13.26	-36.79	-13.00	23.79	Η
11147.01	-51.67	9.63	13.17	-48.13	-13.00	35.13	V
12922.01	-48.24	10.50	13.45	-45.29	-13.00	32.29	V

# LTE Band 2, 1.4MHz, 16QAM, Channel 18900

Frequency(MHz)	P <sub>Mea</sub> (dB m)	Path Loss	Antenna Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3760.02	-46.00	6.26	8.56	-43.70	-13.00	30.70	Н
5644.02	-55.15	7.27	10.57	-51.85	-13.00	38.85	V
7525.01	-40.61	8.29	12.22	-36.68	-13.00	23.68	Н
9406.01	-49.17	9.07	13.34	-44.90	-13.00	31.90	Н
11245.01	-50.96	9.67	13.15	-47.48	-13.00	34.48	Н
13130.01	-47.01	10.80	13.68	-44.13	-13.00	31.13	Н

# LTE Band 2, 1.4MHz, 16QAM, Channel 19193

Frequency(MHz)	P <sub>Mea</sub> (dB m)	Path Loss	Antenna Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3819.02	-48.66	6.08	8.65	-46.09	-13.00	33.09	Н
5731.02	-53.73	7.29	10.55	-50.47	-13.00	37.47	Н
7641.01	-33.05	8.16	12.31	-28.90	-13.00	15.90	Н
9553.01	-39.48	9.35	13.35	-35.48	-13.00	22.48	Н
11500.01	-49.98	9.81	13.10	-46.69	-13.00	33.69	٧
13376.01	-47.26	10.57	14.03	-43.80	-13.00	30.80	Н



# LTE Band 5, 1.4MHz, QPSK, Channel 20407

Fraguanov/MUz)	P <sub>Mea</sub> (dBm)	P <sub>Mea</sub> (dBm)	Path	Antenna	Correction	Peak	Limit	Morain/dD)	Polarization
Frequency(MHz)	Mea(ubiii)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization	
1650.01	-58.92	3.57	5.23	2.15	-59.41	-13.00	46.41	Н	
2474.00	-48.09	4.60	6.02	2.15	-48.82	-13.00	35.82	Н	
3299.02	-44.71	5.29	7.72	2.15	-44.43	-13.00	31.43	Н	
4130.02	-35.67	6.05	9.03	2.15	-34.84	-13.00	21.84	Н	
4954.01	-47.21	6.68	9.85	2.15	-46.19	-13.00	33.19	Н	
5782.01	-53.96	7.22	10.54	2.15	-52.79	-13.00	39.79	Н	

#### LTE Band 5, 1.4MHz, QPSK, Channel 20525

Fragues 20/MHz)	) P <sub>Mea</sub> (dBm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	Mea(ubiii)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1673.01	-49.98	3.58	5.19	2.15	-50.52	-13.00	37.52	Н
2510.00	-52.27	4.63	6.12	2.15	-52.93	-13.00	39.93	Н
3346.02	-38.34	5.31	7.83	2.15	-37.97	-13.00	24.97	Н
4189.02	-36.88	6.18	9.09	2.15	-36.12	-13.00	23.12	Н
5023.01	-47.84	6.56	9.93	2.15	-46.62	-13.00	33.62	V
5861.01	-53.44	7.27	10.53	2.15	-52.33	-13.00	39.33	Н

# LTE Band 5, 1.4MHz, QPSK, Channel 20643

Fraguenov/MHz)	Frequency(MHz) P <sub>Mea</sub> (dBm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHZ)	P <sub>Mea</sub> (ubiii)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1697.01	-53.63	3.60	5.15	2.15	-54.23	-13.00	41.23	Н
2545.00	-46.44	4.66	6.18	2.15	-47.07	-13.00	34.07	Н
3394.02	-52.09	5.36	7.95	2.15	-51.65	-13.00	38.65	Н
4247.02	-43.89	6.24	9.15	2.15	-43.13	-13.00	30.13	Н
5102.01	-55.06	6.78	10.04	2.15	-53.95	-13.00	40.95	V
5932.01	-53.22	7.47	10.51	2.15	-52.33	-13.00	39.33	Н



# LTE Band 5, 1.4MHz, 16QAM, Channel 20407

Eroguanov/MUz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Marain(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	1 Olarization
1650.01	-58.19	3.57	5.23	2.15	-58.68	-13.00	45.68	Н
2474.00	-48.26	4.60	6.02	2.15	-48.99	-13.00	35.99	Н
3299.02	-45.29	5.29	7.72	2.15	-45.01	-13.00	32.01	Н
4128.02	-35.08	6.04	9.03	2.15	-34.24	-13.00	21.24	Н
4955.01	-48.22	6.68	9.86	2.15	-47.19	-13.00	34.19	Н
5765.01	-54.06	7.24	10.55	2.15	-52.90	-13.00	39.90	Н

#### LTE Band 5, 1.4MHz, 16QAM, Channel 20525

Fraguage (MIII-)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Delerization	
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization	
1673.01	-49.99	3.58	5.19	2.15	-50.53	-13.00	37.53	Н	
2509.00	-52.01	4.63	6.12	2.15	-52.67	-13.00	39.67	Н	
3346.02	-40.40	5.31	7.83	2.15	-40.03	-13.00	27.03	Н	
4186.02	-32.75	6.17	9.09	2.15	-31.98	-13.00	18.98	Н	
5022.01	-47.21	6.57	9.93	2.15	-46.00	-13.00	33.00	Н	
5852.01	-53.09	7.24	10.53	2.15	-51.95	-13.00	38.95	V	

# LTE Band 5, 1.4MHz, 16QAM, Channel 20643

Eroguepov(MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1697.01	-53.11	3.60	5.15	2.15	-53.71	-13.00	40.71	Н
2545.00	-45.77	4.66	6.18	2.15	-46.40	-13.00	33.40	Н
3394.02	-48.10	5.36	7.95	2.15	-47.66	-13.00	34.66	Н
4246.02	-39.91	6.24	9.15	2.15	-39.15	-13.00	26.15	Н
5093.01	-48.83	6.75	10.03	2.15	-47.70	-13.00	34.70	V
5924.01	-52.95	7.47	10.52	2.15	-52.05	-13.00	39.05	Н



# LTE Band 12, 1.4MHz, QPSK, Channel 23017

Eroguanov/MUz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Morgin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1400.01	-50.33	3.24	4.98	2.15	-50.74	-13.00	37.74	V
2099.00	-43.32	4.19	4.90	2.15	-44.76	-13.00	31.76	Н
2799.00	-48.81	4.91	6.64	2.15	-49.23	-13.00	36.23	V
3499.02	-51.00	5.52	8.20	2.15	-50.47	-13.00	37.47	Н
4202.02	-43.71	6.21	9.10	2.15	-42.97	-13.00	29.97	Н
4908.01	-55.11	6.73	9.81	2.15	-54.18	-13.00	41.18	Н

#### LTE Band 12, 1.4MHz, QPSK, Channel 23095

Fragues 20/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1415.01	-55.75	3.25	5.06	2.15	-56.09	-13.00	43.09	V
2123.00	-51.94	4.21	4.97	2.15	-53.33	-13.00	40.33	Н
2830.00	-46.80	4.95	6.69	2.15	-47.21	-13.00	34.21	V
3538.02	-53.84	5.70	8.25	2.15	-53.44	-13.00	40.44	Н
4249.02	-45.64	6.24	9.15	2.15	-44.88	-13.00	31.88	Н
4945.01	-54.88	6.70	9.85	2.15	-53.88	-13.00	40.88	V

# LTE Band 12, 1.4MHz, QPSK, Channel 23173

Fragues (MIII)	requency(MHz) $P_{Mea}(dBm)$	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Delerization
Frequency(MHZ)	P <sub>Mea</sub> (dBIII)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1431.01	-54.02	3.28	5.14	2.15	-54.31	-13.00	41.31	V
2146.00	-51.87	4.24	5.04	2.15	-53.22	-13.00	40.22	Н
2861.00	-40.12	4.96	6.75	2.15	-40.48	-13.00	27.48	V
3577.02	-49.53	6.10	8.31	2.15	-49.47	-13.00	36.47	Н
4293.02	-40.99	6.20	9.19	2.15	-40.15	-13.00	27.15	Н
5009.01	-52.96	6.59	9.91	2.15	-51.79	-13.00	38.79	Н



# LTE Band 12, 1.4MHz, 16QAM, Channel 23017

Fraguanov/MUz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1400.01	-51.10	3.24	4.98	2.15	-51.51	-13.00	38.51	Н
2099.00	-43.88	4.19	4.90	2.15	-45.32	-13.00	32.32	Н
2799.00	-50.15	4.91	6.64	2.15	-50.57	-13.00	37.57	Н
3499.02	-52.30	5.52	8.20	2.15	-51.77	-13.00	38.77	Н
4203.02	-43.20	6.21	9.10	2.15	-42.46	-13.00	29.46	Н
4905.01	-54.65	6.73	9.81	2.15	-53.72	-13.00	40.72	Н

#### LTE Band 12, 1.4MHz 16QAM, Channel 23095

Fraguesov/MHz)	Frequency(MHz) PMea(dBm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(Minz)	Piviea(ubiii)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1415.01	-56.84	3.25	5.06	2.15	-57.18	-13.00	44.18	V
2123.00	-53.35	4.21	4.97	2.15	-54.74	-13.00	41.74	Н
2830.00	-48.32	4.95	6.69	2.15	-48.73	-13.00	35.73	Н
3538.02	-54.71	5.70	8.25	2.15	-54.31	-13.00	41.31	Н
4247.02	-49.20	6.24	9.15	2.15	-48.44	-13.00	35.44	Н
4959.01	-55.50	6.67	9.86	2.15	-54.46	-13.00	41.46	V

# LTE Band 12, 1.4MHz, 16QAM, Channel 23173

Fragueray/MIII=)	DMag(dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Delerization
Frequency(MHz)	PMea(dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1431.01	-52.60	3.28	5.14	2.15	-52.89	-13.00	39.89	V
2146.00	-50.85	4.24	5.04	2.15	-52.20	-13.00	39.20	Н
2862.00	-41.37	4.96	6.75	2.15	-41.73	-13.00	28.73	V
3577.02	-50.42	6.10	8.31	2.15	-50.36	-13.00	37.36	Н
4295.02	-42.56	6.20	9.20	2.15	-41.71	-13.00	28.71	Н
5013.01	-55.03	6.58	9.92	2.15	-53.84	-13.00	40.84	Н



# LTE Band 13, 5MHz, QPSK, Channel 23205

Frequency(MHz) F	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHZ)	quency(MHz) P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1554.01	-60.15	3.47	5.40	2.15	-60.37	-13.00	47.37	Н
2346.00	-54.78	4.45	5.64	2.15	-55.74	-13.00	42.74	V
3118.02	-51.73	5.38	7.28	2.15	-51.98	-13.00	38.98	Н
3898.02	-48.83	6.11	8.76	2.15	-48.33	-13.00	35.33	Н
4680.02	-51.10	6.49	9.58	2.15	-50.16	-13.00	37.16	Н
5454.01	-55.21	6.89	10.54	2.15	-53.71	-13.00	40.71	V

# LTE Band 13, 5MHz, QPSK, Channel 23230

Frequency(MHz) P <sub>Mea</sub> (dBm)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
	Mea(ubiii)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	1 Glarization
1567.01	-59.82	3.48	5.38	2.15	-60.07	-13.00	47.07	Н
2356.00	-53.98	4.46	5.67	2.15	-54.92	-13.00	41.92	V
3113.02	-53.85	5.36	7.27	2.15	-54.09	-13.00	41.09	Н
3910.02	-48.63	6.12	8.77	2.15	-48.13	-13.00	35.13	Н
4695.02	-54.69	6.50	9.60	2.15	-53.74	-13.00	40.74	Н
5465.01	-55.20	6.93	10.55	2.15	-53.73	-13.00	40.73	V

# LTE Band 13, 5MHz, QPSK, Channel 23255

Fraguenov/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1571.01	-60.56	3.49	5.37	2.15	-60.83	-13.00	47.83	V
2357.00	-53.53	4.47	5.67	2.15	-54.48	-13.00	41.48	V
3136.02	-54.02	5.39	7.33	2.15	-54.23	-13.00	41.23	Н
3923.02	-47.89	6.12	8.79	2.15	-47.37	-13.00	34.37	Н
4713.02	-51.51	6.52	9.61	2.15	-50.57	-13.00	37.57	Н
5505.01	-54.87	7.08	10.60	2.15	-53.50	-13.00	40.50	Н



# LTE Band 13, 5MHz, 16QAM, Channel 23205

Fraguanov/MUz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1554.01	-60.61	3.47	5.40	2.15	-60.83	-13.00	47.83	Н
2346.00	-54.20	4.45	5.64	2.15	-55.16	-13.00	42.16	Н
3119.02	-52.04	5.38	7.29	2.15	-52.28	-13.00	39.28	Н
3899.02	-48.08	6.11	8.76	2.15	-47.58	-13.00	34.58	Н
4682.02	-54.07	6.49	9.58	2.15	-53.13	-13.00	40.13	Н
5452.01	-55.09	6.88	10.53	2.15	-53.59	-13.00	40.59	Н

#### LTE Band 13, 5 MHz, 16QAM, Channel 23230

Fragues 20/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1567.01	-60.11	3.48	5.38	2.15	-60.36	-13.00	47.36	Н
2357.00	-53.77	4.47	5.67	2.15	-54.72	-13.00	41.72	V
3122.02	-53.99	5.39	7.29	2.15	-54.24	-13.00	41.24	Н
3911.02	-49.74	6.12	8.78	2.15	-49.23	-13.00	36.23	Н
4705.02	-54.52	6.51	9.61	2.15	-53.57	-13.00	40.57	Н
5478.01	-55.37	6.98	10.57	2.15	-53.93	-13.00	40.93	Н

# LTE Band13, 5MHz, 16QAM, Channel 23255

Fragues av/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Delerization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1564.01	-60.06	3.48	5.38	2.15	-60.31	-13.00	47.31	Н
2357.00	-54.26	4.47	5.67	2.15	-55.21	-13.00	42.21	V
3130.02	-53.87	5.40	7.31	2.15	-54.11	-13.00	41.11	Н
3923.02	-47.44	6.12	8.79	2.15	-46.92	-13.00	33.92	Н
4711.02	-51.64	6.51	9.61	2.15	-50.69	-13.00	37.69	Н
5501.01	-54.91	7.06	10.60	2.15	-53.52	-13.00	40.52	V



# LTE Band 66, 1.4MHz QPSK, Channel 131979

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3422.02	-46.58	5.38	8.01	-43.95	-13.00	30.95	Н
5137.02	-50.97	6.86	10.09	-47.74	-13.00	34.74	Н
6846.01	-42.86	7.83	11.42	-39.27	-13.00	26.27	H
8557.01	-45.67	8.57	13.01	-41.23	-13.00	28.23	H
10264.01	-52.19	9.52	13.01	-48.70	-13.00	35.70	Н
11979.01	-49.04	10.15	13.00	-46.19	-13.00	33.19	V

# LTE Band 66, 1.4MHz, QPSK, Channel 132322

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3490.02	-45.93	5.50	8.18	-43.25	-13.00	30.25	Н
5237.02	-53.82	7.00	10.23	-50.59	-13.00	37.59	V
6983.01	-44.97	8.17	11.58	-41.56	-13.00	28.56	Н
8729.01	-49.73	8.45	13.05	-45.13	-13.00	32.13	Н
10472.01	-51.77	9.69	13.09	-48.37	-13.00	35.37	Н
12214.01	-49.25	10.05	13.09	-46.21	-13.00	33.21	Н

# LTE Band 66, 1.4MHz, QPSK, Channel 132665

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3559.02	-43.19	5.92	8.28	-40.83	-13.00	27.83	Н
5342.02	-51.84	6.95	10.38	-48.41	-13.00	35.41	V
7122.01	-44.51	8.16	11.75	-40.92	-13.00	27.92	Н
8900.01	-47.38	8.85	13.08	-43.15	-13.00	30.15	V
10676.01	-51.19	9.30	13.14	-47.35	-13.00	34.35	V
12456.01	-49.77	10.29	13.18	-46.88	-13.00	33.88	V



# LTE Band 66, 1.4MHz, 16QAM, Channel 131979

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3421.02	-47.62	5.38	8.01	-44.99	-13.00	31.99	Н
5137.02	-49.63	6.86	10.09	-46.40	-13.00	33.40	Н
6846.01	-42.66	7.83	11.42	-39.07	-13.00	26.07	H
8557.01	-49.47	8.57	13.01	-45.03	-13.00	32.03	H
10268.01	-52.82	9.53	13.01	-49.34	-13.00	36.34	V
11975.01	-50.29	10.17	13.00	-47.46	-13.00	34.46	Н

# LTE Band 66, 1.4MHz, 16QAM, Channel 132322

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3490.02	-45.98	5.50	8.18	-43.30	-13.00	30.30	Н
5237.02	-53.76	7.00	10.23	-50.53	-13.00	37.53	Н
6983.01	-44.95	8.17	11.58	-41.54	-13.00	28.54	Н
8729.01	-48.10	8.45	13.05	-43.50	-13.00	30.50	Н
10469.01	-51.76	9.70	13.09	-48.37	-13.00	35.37	V
12214.01	-49.39	10.05	13.09	-46.35	-13.00	33.35	Н

# LTE Band 66, 1.4MHz, 16QAM, Channel 132665

Frequency(MHz	P <sub>Mea</sub> (dB m)	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB	Polarizatio n
3559.02	-43.96	5.92	8.28	-41.60	-13.00	28.60	Н
5341.02	-52.82	6.95	10.38	-49.39	-13.00	36.39	Н
7121.01	-44.06	8.16	11.75	-40.47	-13.00	27.47	Н
8900.01	-48.04	8.85	13.08	-43.81	-13.00	30.81	V
10677.01	-51.43	9.30	13.14	-47.59	-13.00	34.59	V
12458.01	-49.33	10.29	13.18	-46.44	-13.00	33.44	Н



# LTE Band 71, 5MHz, QPSK, Channel 133147

Fraguanay/MUz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1331.01	-51.97	3.15	4.62	2.15	-52.65	-13.00	39.65	Н
1983.01	-55.25	4.00	4.63	2.15	-56.77	-13.00	43.77	V
2663.00	-51.55	4.75	6.39	2.15	-52.06	-13.00	39.06	Н
3328.02	-52.39	5.30	7.79	2.15	-52.05	-13.00	39.05	Н
3994.02	-50.35	6.07	8.89	2.15	-49.68	-13.00	36.68	Н
4688.02	-54.06	6.50	9.59	2.15	-53.12	-13.00	40.12	Н

# LTE Band 71, 5MHz, QPSK, Channel 133297

Fraguanov/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1361.01	-53.16	3.19	4.78	2.15	-53.72	-13.00	40.72	V
2042.00	-50.41	4.14	4.73	2.15	-51.97	-13.00	38.97	Н
2732.00	-51.37	4.82	6.52	2.15	-51.82	-13.00	38.82	Н
3404.02	-52.76	5.37	7.97	2.15	-52.31	-13.00	39.31	Н
4088.02	-47.05	6.04	8.99	2.15	-46.25	-13.00	33.25	Н
4769.01	-55.13	6.61	9.67	2.15	-54.22	-13.00	41.22	Н

# LTE Band 71, 5MHz, QPSK, Channel 133447

Fragues av/MII=)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Delerization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1407.01	-58.41	3.24	5.02	2.15	-58.78	-13.00	45.78	Н
2087.00	-54.72	4.18	4.86	2.15	-56.19	-13.00	43.19	Н
2755.00	-52.11	4.85	6.56	2.15	-52.55	-13.00	39.55	Н
3448.02	-55.07	5.43	8.08	2.15	-54.57	-13.00	41.57	Н
4175.02	-49.80	6.15	9.08	2.15	-49.02	-13.00	36.02	Н
4865.01	-54.95	6.72	9.77	2.15	-54.05	-13.00	41.05	Н



#### LTE Band 71, 5MHz, 16QAM, Channel 133147

Frequency(MHz)   P <sub>Mea</sub> (dBm)		Path	Antenna	Correction	Peak	Limit	Marain(dD)	Polarization
Frequency(Minz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1331.01	-53.19	3.15	4.62	2.15	-53.87	-13.00	40.87	V
1969.01	-55.02	3.96	4.66	2.15	-56.47	-13.00	43.47	V
2645.00	-51.71	4.74	6.36	2.15	-52.24	-13.00	39.24	V
3328.02	-52.85	5.30	7.79	2.15	-52.51	-13.00	39.51	Н
3994.02	-49.85	6.07	8.89	2.15	-49.18	-13.00	36.18	Н
4685.02	-52.80	6.49	9.59	2.15	-51.85	-13.00	38.85	V

#### LTE Band 71, 5MHz, 16QAM, Channel 133297

Fragues 20/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1361.01	-52.90	3.19	4.78	2.15	-53.46	-13.00	40.46	V
2042.00	-52.98	4.14	4.73	2.15	-54.54	-13.00	41.54	Н
2706.00	-51.57	4.79	6.47	2.15	-52.04	-13.00	39.04	Н
3403.02	-53.19	5.36	7.97	2.15	-52.73	-13.00	39.73	Н
4088.02	-47.50	6.04	8.99	2.15	-46.70	-13.00	33.70	Н
4734.02	-54.77	6.54	9.63	2.15	-53.83	-13.00	40.83	Н

#### LTE Band 71, 5MHz, 16QAM, Channel 133447

Fraguanov/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1391.01	-56.43	3.22	4.93	2.15	-56.87	-13.00	43.87	V
2087.00	-54.07	4.18	4.86	2.15	-55.54	-13.00	42.54	Н
2803.00	-51.87	4.92	6.65	2.15	-52.29	-13.00	39.29	Н
3459.02	-55.32	5.45	8.10	2.15	-54.82	-13.00	41.82	Н
4177.02	-50.22	6.15	9.08	2.15	-49.44	-13.00	36.44	Н
4844.01	-54.30	6.72	9.74	2.15	-53.43	-13.00	40.43	V

Note: The maximum value of expanded measurement uncertainty for this test item is U = 4.2 dB, k = 2.



# A.3 FREQUENCY STABILITY

#### A.3.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the EUT to overnight soak at -10°C.
- 3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE bands 2 5 12 13 66 71, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10°C increments from 0°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6. Subject the EUT to overnight soak at +50°C.
- 7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10 °C increments from 0 °C to +50 °C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 9. At all temperature levels hold the temperature to  $\pm 0.5^{\circ}$  during the measurement procedure.

#### A.3.2 Measurement Limit

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d) (2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.4VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance from -5.4% to 10.8%. For the purposes of measuring frequency stability these voltage limits are to be used.



#### A.3.3 Measurement results

# LTE Band 2, 1.4MHz bandwidth (worst case of all bandwidths)

# Frequency Error vs Voltage

Voltage	Frequency	error (Hz)	Frequency error (ppm)		
(V)	QPSK	16QAM	QPSK	16QAM	
3.5	8.37	-24.96	0.0045	0.0133	
3.8	-7.81	-22.00	0.0042	0.0117	
4.4	8.98	-24.39	0.0048	0.0130	

#### **Frequency Error vs Temperature**

	requests = re-re-re-re-re-re-re-re-re-re-re-re-re-r							
Temperature (°C)	Frequency	error (Hz)	Frequency error (ppm)					
	QPSK	16QAM	QPSK	16QAM				
50	10.10	-26.78	0.0054	0.0142				
40	-5.65	-26.11	0.0030	0.0139				
30	5.89	-25.02	0.0031	0.0133				
20	8.64	-23.66	0.0046	0.0126				
10	-6.64	-23.26	0.0035	0.0124				
0	11.59	-33.70	0.0062	0.0179				

# LTE Band 5, 1.4MHz bandwidth (worst case of all bandwidths)

#### Frequency Error vs Voltage

- 1							
Voltage	Frequency error (Hz)		Frequency error (ppm)				
(V)	QPSK	16QAM	QPSK	16QAM			
3.5	-17.37	-31.19	0.0208	0.0373			
3.8	-16.38	-33.47	0.0196	0.0400			
4.4	-20.18	-34.88	0.0241	0.0417			

#### **Frequency Error vs Temperature**

Temperature	Frequency	Frequency error (Hz)		rror (ppm)
(℃)	QPSK	16QAM	QPSK	16QAM
50	-17.52	-28.80	0.0209	0.0344
40	8.45	-23.19	0.0101	0.0277
30	-16.31	-31.81	0.0195	0.0380
20	-15.65	-31.13	0.0187	0.0372
10	-16.57	-30.97	0.0198	0.0370
0	-18.20	-28.10	0.0218	0.0336



# LTE Band 12, 5MHz bandwidth (worst case of all bandwidths)

# Frequency Error vs Voltage

Voltage	Frequency error (Hz)		Frequency error (ppm)		
(V)	QPSK	16QAM	QPSK	16QAM	
3.5	-16.55	-21.23	0.0234	0.0300	
3.8	-22.86	-16.78	0.0323	0.0237	
4.4	-11.84	-19.86	0.0167	0.0281	

# **Frequency Error vs Temperature**

Temperature	Frequency error (Hz)		Frequency error (ppm)	
(℃)	QPSK	16QAM	QPSK	16QAM
50	-12.19	-20.14	0.0172	0.0285
40	-13.99	-18.47	0.0198	0.0261
30	-17.18	-15.45	0.0243	0.0218
20	-18.15	-24.85	0.0257	0.0351
10	-17.11	-16.04	0.0242	0.0227
0	-13.76	-18.71	0.0194	0.0264

#### LTE Band 13, 5MHz bandwidth (worst case of all bandwidths)

# Frequency Error vs Voltage

Voltage	Frequency error (Hz)		Frequency error (ppm)		
(V)	QPSK	16QAM	QPSK	16QAM	
3.5	-13.45	-23.75	0.0172	0.0304	
3.8	-17.94	-17.82	0.0229	0.0228	
4.4	-14.93	-14.62	0.0191	0.0187	

# **Frequency Error vs Temperature**

Temperature	Frequency error (Hz)		Frequency error (ppm)	
(℃)	QPSK	16QAM	QPSK	16QAM
50	-12.76	-16.55	0.0163	0.0212
40	-9.13	-18.74	0.0117	0.0240
30	-12.10	-19.97	0.0155	0.0255
20	-11.96	-19.23	0.0153	0.0246
10	-15.62	-23.79	0.0200	0.0304
0	-8.96	-20.04	0.0115	0.0256



# LTE Band 66, 1.4MHz bandwidth (worst case of all bandwidths)

# Frequency Error vs Voltage

Voltage	Frequency	y error (Hz)	Frequency	error (ppm)
(V)	QPSK	16QAM	QPSK	16QAM
3.5	-19.60	-29.67	0.0112	0.0170
3.8	24.81	-34.02	0.0142	0.0195
4.4	-18.32	-30.80	0.0105	0.0177

# **Frequency Error vs Temperature**

Temperature	Frequency error (Hz)		Frequency error (ppm)	
(℃)	QPSK	16QAM	QPSK	16QAM
50	-19.60	-29.67	0.0112	0.0170
40	24.81	-34.02	0.0142	0.0195
30	-18.32	-30.80	0.0105	0.0177
20	-17.35	-26.66	0.0099	0.0153
10	-20.81	-32.76	0.0119	0.0188
0	-19.31	-33.62	0.0111	0.0193



# LTE Band 71, 10MHz bandwidth (worst case of all bandwidths)

# Frequency Error vs Voltage

Voltage	Frequency	y error (Hz)	Frequency	error (ppm)
(V)	QPSK	16QAM	QPSK	16QAM
3.5	-11.50	-13.13	0.0169	0.0193
3.8	-13.50	-10.33	0.0198	0.0152
4.4	-17.50	-10.04	0.0257	0.0148

# **Frequency Error vs Temperature**

Temperature	Frequency	y error (Hz)	Frequency e	rror (ppm)
(℃)	QPSK	16QAM	QPSK	16QAM
50	-10.53	-13.72	0.0155	0.0202
40	-11.50	-12.87	0.0169	0.0189
30	-6.92	-15.02	0.0102	0.0221
20	-11.10	-19.31	0.0163	0.0284
10	-13.88	-17.50	0.0204	0.0257
0	-13.32	-17.22	0.0196	0.0253

Expanded measurement uncertainty for this test item is 10 Hz, k = 2.



#### A.4 OCCUPIED BANDWIDTH

#### A.4.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from KDB 971168 4.2:


- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least 10log (OBW / RBW) below the reference level.
- d) Set the detection mode to peak, and the trace mode to max hold.
- e) Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



#### LTE band 2, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandw	idth (99%)( kHz)
1880.0	QPSK	16QAM
1000.0	1089.74	1089.74

#### LTE band 2, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 24.0CT.2018 16:58:30

# LTE band 2, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 16:59:54



# LTE band 2, 3MHz (99%)


Frequency(MHz)	Occupied Bandw	idth (99%)( kHz)
1880.0	QPSK	16QAM
1000.0	2692.31	2692.31

#### LTE band 2, 3MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:02:08

# LTE band 2, 3MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:03:32



# LTE band 2, 5MHz (99%)


Frequency(MHz)	Occupied Bandw	idth (99%)( kHz)
1880.0	QPSK	16QAM
1000.0	4519.23	4519.23

#### LTE band 2, 5MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:05:45

# LTE band 2, 5MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:07:10



# LTE band 2, 10MHz (99%)


Frequency(MHz)	Occupied Bandw	idth (99%)( kHz)
1880.0	QPSK	16QAM
1000.0	8990.38	9038.46

#### LTE band 2, 10MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:09:23

# LTE band 2, 10MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:10:48



# LTE band 2, 15MHz (99%)


Frequency(MHz)	Occupied Bandw	idth (99%)( kHz)
1880.0	QPSK	16QAM
1000.0	13557.69	13557.69

#### LTE band 2, 15MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:13:01

# LTE band 2, 15MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:14:26



#### LTE band 2, 20MHz (99%)


Frequency(MHz)	Occupied Bandw	idth (99%)( kHz)
1880.0	QPSK	16QAM
1000.0	17884.62	17884.62

#### LTE band 2, 20MHz Bandwidth, QPSK (99% BW)



Date: 24.0CT.2018 17:16:39

# LTE band 2, 20MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:18:03



#### LTE band 5, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
836.5	QPSK	16QAM
630.3	1097.76	1097.76

#### LTE band 5, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:20:18

# LTE band 5, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:21:42



#### LTE band 5, 3MHz (99%)


Frequency(MHz)	Occupied Bandw	idth (99%)( kHz)
836.5	QPSK	16QAM
630.3	2692.31	2692.31

#### LTE band 5, 3MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:23:56

# LTE band 5, 3MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:25:20



# LTE band 5, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
836.5	QPSK	16QAM
	4519.23	4495.19

#### LTE band 5, 5MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:27:33

# LTE band 5, 5MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:28:58



#### LTE band 5, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
836.5	QPSK	16QAM
	8990.38	8990.38

#### LTE band 5, 10MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:31:11

# LTE band 5, 10MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:32:36



#### LTE band 12, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
707.5	QPSK	16QAM
	1097.76	1097.76

#### LTE band 12, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:34:50

# LTE band 12, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:36:15



# LTE band 12, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
707.5	QPSK	16QAM
	2692.31	2692.31

#### LTE band 12, 3MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:38:28

# LTE band 12, 3MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:39:53



# LTE band 12, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
707.5	QPSK	16QAM
	4543.27	4519.23

#### LTE band 12, 5MHz Bandwidth, QPSK (99% BW)



Date: 24.0CT.2018 17:42:06

# LTE band 12, 5MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:43:31



# LTE band 12, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
707.5	QPSK	16QAM
	9038.46	9038.46

#### LTE band 12, 10MHz Bandwidth, QPSK (99% BW)



Date: 24.0CT.2018 17:45:45

# LTE band 12, 10MHz Bandwidth, 16QAM (99% BW)




Date: 24.OCT.2018 17:47:09



#### LTE band 13, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
782.0	QPSK	16QAM
	4495.19	4495.19

#### LTE band 13, 5MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:49:24

#### LTE band 13, 5MHz Bandwidth,16QAM (99% BW)




Date: 24.0CT.2018 17:50:48



## LTE band 13, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
782.0	QPSK	16QAM
762.0	8990.38	8990.38

# LTE band 13, 10MHz Bandwidth, QPSK (99% BW)



Date: 24.0CT.2018 17:53:02

# LTE band 13, 10MHz Bandwidth,16QAM (99% BW)




Date: 24.0CT.2018 17:54:26



## LTE band 66, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1745.0	QPSK	16QAM
1745.0	1089.74	1097.76

# LTE band 66, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 17:56:41

## LTE band 66, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 17:58:06



## LTE band 66, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1745.0	QPSK	16QAM
1745.0	2692.31	2692.31

## LTE band 66, 3MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 18:00:19

## LTE band 66, 3MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 18:01:43



## LTE band 66, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1745.0	QPSK	16QAM
1745.0	4495.19	4495.19

## LTE band 66, 5MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 18:03:57

## LTE band 66, 5MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 18:05:22



## LTE band 66, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1745.0	QPSK	16QAM
1745.0	8990.38	8990.38

## LTE band 66, 10MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 18:07:35

## LTE band 66, 10MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 18:09:00



### LTE band 66, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1745.0	QPSK	16QAM
1745.0	13485.58	13485.58

## LTE band 66, 15MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 18:11:13

# LTE band 66, 15MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 18:12:38



## LTE band 66, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
1745.0	QPSK	16QAM
1745.0	17980.77	17980.77

## LTE band 66, 20MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 18:14:51

## LTE band 66, 20MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 18:16:16



#### LTE band 71, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
680.5	QPSK	16QAM
000.5	4519.23	4495.19

## LTE band 71, 5MHz Bandwidth, QPSK (99% BW)



Date: 24.0CT.2018 18:18:38

# LTE band 71, 5MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 18:20:02



## LTE band 71, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
680.5	QPSK	16QAM
000.5	8990.38	8990.38

# LTE band 71, 10MHz Bandwidth, QPSK (99% BW)



Date: 24.0CT.2018 18:22:16

# LTE band 71, 10MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 18:23:40



### LTE band 71, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
680.5	QPSK	16QAM
060.5	13485.58	13485.58

# LTE band 71, 15MHz Bandwidth, QPSK (99% BW)



Date: 24.0CT.2018 18:25:54

# LTE band 71, 15MHz Bandwidth, 16QAM (99% BW)




Date: 24.0CT.2018 18:27:18



### LTE band 71, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
690 5	QPSK	16QAM
680.5	17980.77	17980.77

## LTE band 71, 20MHz Bandwidth, QPSK (99% BW)



Date: 24.OCT.2018 18:29:32

# LTE band 71, 20MHz Bandwidth, 16QAM (99% BW)



Date: 24.0CT.2018 18:30:56



# A.5 EMISSION BANDWIDTH

#### A.5.1Emission Bandwidth Results


The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.



### LTE band 2, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1880.0	QPSK	16QAM
1860.0	1290.06	1306.09

## LTE band 2, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 18:32:57

# LTE band 2, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.0CT.2018 18:34:22



### LTE band 2, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1880.0	QPSK	16QAM
1000.0	2868.59	2900.64

# LTE band 2, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 18:36:36

# LTE band 2, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.0CT.2018 18:38:01



## LTE band 2, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1880.0	QPSK	16QAM
1000.0	5072.12	5120.19

# LTE band 2, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 18:40:15

# LTE band 2, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 18:41:40



### LTE band 2, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1880.0	QPSK	16QAM
1000.0	10048.08	9951.92

# LTE band 2, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 18:43:54

# LTE band 2, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 18:45:18



### LTE band 2, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1880.0	QPSK	16QAM
1000.0	15000.00	15072.12

# LTE band 2, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 18:47:32

# LTE band 2, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 18:48:57



### LTE band 2, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1880.0	QPSK	16QAM
1000.0	19519.23	19423.08

## LTE band 2, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 18:51:11

# LTE band 2, 20MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 18:52:36



# LTE band 5, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
836.5	QPSK	16QAM
630.3	1282.05	1298.08

# LTE band 5, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 18:54:51

# LTE band 5, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 18:56:16



### LTE band 5, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
836.5	QPSK	16QAM
630.3	2884.62	2900.64

## LTE band 5, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 18:58:30

# LTE band 5, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 18:59:55



### LTE band 5, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
836.5	QPSK	16QAM
650.5	5144.23	5072.12

# LTE band 5, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 19:02:09

# LTE band 5, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 19:03:34



### LTE band 5, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
926 E	QPSK	16QAM
836.5	10048.08	10000.00

# LTE band 5, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 19:05:48

# LTE band 5, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 19:07:13



## LTE band 12, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
707.5	QPSK	16QAM
107.5	1314.10	1330.13

# LTE band 12, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 19:09:28

# LTE band 12, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 19:10:53



### LTE band 12, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
707.5	QPSK	16QAM
707.5	2916.67	2900.64

# LTE band 12, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 19:13:07

# LTE band 12, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 19:14:32



### LTE band 12, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
707.5	QPSK	16QAM
707.5	5144.23	5168.27

# LTE band 12, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 19:16:46

# LTE band 12, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 19:18:11



### LTE band 12, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
707.5	QPSK	16QAM
707.5	10144.23	10096.15

## LTE band 12, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 19:20:25

# LTE band 12, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 19:21:50



### LTE band 13, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
782.0	QPSK	16QAM
762.0	5096.15	5048.08

# LTE band 13, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.0CT.2018 19:24:05

# LTE band 13, 5MHz Bandwidth,16QAM (-26dBc BW)




Date: 24.OCT.2018 19:25:30



### LTE band 13, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
702.0	QPSK	16QAM
782.0	10000.00	9855.77

## LTE band 13, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 19:27:44

# LTE band 13, 10MHz Bandwidth,16QAM (-26dBc BW)




Date: 24.OCT.2018 19:29:09



### LTE band 66, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1745.0	QPSK	16QAM
1745.0	1290.06	1298.08

# LTE band 66, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 19:31:24

## LTE band 66, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.0CT.2018 19:32:49



### LTE band 66, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1745.0	QPSK	16QAM
1745.0	2900.64	2900.64

## LTE band 66, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 19:35:03

## LTE band 66, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.0CT.2018 19:36:28



### LTE band 66, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1745.0	QPSK	16QAM
1745.0	5120.19	5096.15

## LTE band 66, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 19:38:42

## LTE band 66, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.0CT.2018 19:40:07



### LTE band 66, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1745.0	QPSK	16QAM
1745.0	10096.15	9951.92

# LTE band 66, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 19:42:21

## LTE band 66, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.0CT.2018 19:43:46



### LTE band 66, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1745.0	QPSK	16QAM
1745.0	15000.00	15000.00

# LTE band 66, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 19:46:00

## LTE band 66, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.0CT.2018 19:47:26



### LTE band 66, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
1745.0	QPSK	16QAM
1745.0	19519.23	19423.08

# LTE band 66, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 19:49:40

## LTE band 66, 20MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.0CT.2018 19:51:05



### LTE band 71, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
680.5	QPSK	16QAM
000.5	5144.23	5072.12

## LTE band 71, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 19:53:28

## LTE band 71, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.OCT.2018 19:54:53



### LTE band 71, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
680.5	QPSK	16QAM
000.5	9951.92	9951.92

# LTE band 71, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 19:57:07

## LTE band 71, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.0CT.2018 19:58:32



#### LTE band 71, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
680.5	QPSK	16QAM
	15000.00	14927.88

#### LTE band 71, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 20:00:46

#### LTE band 71, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 24.0CT.2018 20:02:11



#### LTE band 71, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
680.5	QPSK	16QAM
	19615.38	19423.08

#### LTE band 71, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 24.OCT.2018 20:04:25

#### LTE band 71, 20MHz Bandwidth, 16QAM (-26dBc BW)



Date: 24.0CT.2018 20:05:50



#### A.6 BAND EDGE COMPLIANCE

#### A.6.1 Measurement limit


Part 22.917(b), 24.238(a), 27.53(h) state that on any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log (P) dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

According to KDB 971168 6.0, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

Part 27.53(m) states that for mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(c) states for operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations

Part 27.53(a) states for mobile and portable stations operating in the 2305–2315 MHz and 2350–2360 MHz bands: By a factor of not less than: 43 +10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337MHz; By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288 and 2392 MHz, and 70 + 10 log (P) dB below 2288 MHz; By a factor of not less than 43 + 10 log (P) dB below 2288 MHz; By a factor of not less than 43 + 10 log (P)






dB on all frequencies between 2360 and 2365 MHz, and not less than  $70 + 10 \log (P)$  dB above 2365 MHz.




# A.6.2 Measurement result Only worst case result is given below LTE band 2

OBW: 1RB-low\_offset



Date: 25.0CT.2018 09:18:01


#### LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 25.OCT.2018 09:18:17




#### OBW: 1RB-high\_offset



Date: 25.OCT.2018 09:23:38


# HIGH BAND EDGE BLOCK-1RB-high\_offset



Date: 25.0CT.2018 09:23:54




#### LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 25.OCT.2018 09:21:40

#### HIGH BAND EDGE BLOCK-20MHz-100%RB




Date: 25.0CT.2018 09:24:30




#### LTE band 5

#### **OBW: 1RB-low\_offset**



Date: 25.OCT.2018 09:28:22


#### LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 25.0CT.2018 09:28:38




#### OBW: 1RB-high\_offset



Date: 25.OCT.2018 09:30:33


# HIGH BAND EDGE BLOCK-1RB-high\_offset



Date: 25.0CT.2018 09:30:49




#### LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 25.OCT.2018 09:36:30

#### HIGH BAND EDGE BLOCK-10MHz-100%RB




Date: 25.0CT.2018 09:31:17




#### LTE band 12

# OBW: 1RB-low\_offset



Date: 25.OCT.2018 09:40:25


#### LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 25.0CT.2018 09:40:40




#### OBW: 1RB-high\_offset



Date: 25.OCT.2018 14:11:36


# HIGH BAND EDGE BLOCK-1RB-high\_offset



Date: 25.0CT.2018 14:17:25




#### LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 25.OCT.2018 09:41:16

#### HIGH BAND EDGE BLOCK-10MHz-100%RB




Date: 25.0CT.2018 14:22:28




#### LTE band 13

#### **OBW: 1RB-low\_offset**




Date: 26.OCT.2018 16:29:34

#### LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 26.0CT.2018 16:30:42






Date: 26.OCT.2018 16:30:56




# OBW: 1RB-high\_offset




Date: 26.OCT.2018 16:33:13

# HIGH BAND EDGE BLOCK-1RB-high\_offset



Date: 26.0CT.2018 16:34:03







Date: 26.OCT.2018 16:34:18



#### LOW BAND EDGE BLOCK-10MHz-100%RB




Date: 26.OCT.2018 16:36:10




Date: 26.0CT.2018 16:36:25



#### HIGH BAND EDGE BLOCK-10MHz-100%RB



Date: 26.OCT.2018 16:38:47




Date: 26.OCT.2018 16:39:02




#### LTE band 66

# OBW: 1RB-low\_offset



Date: 25.OCT.2018 11:10:29


#### LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 25.0CT.2018 11:10:44




#### OBW: 1RB-high\_offset



Date: 25.OCT.2018 11:12:41


# HIGH BAND EDGE BLOCK-1RB-high\_offset



Date: 25.0CT.2018 11:12:57




#### LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 25.OCT.2018 11:11:21

#### HIGH BAND EDGE BLOCK-20MHz-100%RB




Date: 25.0CT.2018 11:13:33




#### LTE band 71

# OBW: 1RB-low\_offset



Date: 26.OCT.2018 16:03:42


#### LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 26.0CT.2018 16:03:57




#### OBW: 1RB-high\_offset



Date: 26.OCT.2018 16:09:49


# HIGH BAND EDGE BLOCK-1RB-high\_offset



Date: 26.0CT.2018 16:23:10




#### LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 26.OCT.2018 16:04:33

#### HIGH BAND EDGE BLOCK-20MHz-100%RB



Date: 26.0CT.2018 16:07:24



#### A.7 CONDUCTED SPURIOUS EMISSION

#### A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- 1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
- 2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
- 3. The number of sweep points of spectrum analyzer is set to 30001 which is greater than span/RBW.


#### A. 7.2 Measurement Limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(a) states for mobile and portable stations operating in the 2305–2315 MHz and 2350–2360 MHz bands: By a factor of not less than: 43 +10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337MHz; By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288






and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz; By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.



# A. 7.2 Measurement result Only worst case result is given below

#### LTE band 2: 30MHz - 19.15GHz


Spurious emission limit -13dBm.



Date: 25.OCT.2018 14:03:23

#### LTE band 5: 30MHz - 8.49GHz

Spurious emission limit -13dBm.




Date: 25.0CT.2018 14:01:42



#### LTE band 12: 30MHz - 7.16GHz


Spurious emission limit -13dBm.



Date: 25.OCT.2018 14:00:18

#### LTE band 13: 30MHz - 7870MHz

Spurious emission limit -13dBm.




Date: 25.0CT.2018 13:57:44



#### LTE band 13: 1559MHz - 1610MHz


Spurious emission limit -13dBm.



Date: 25.OCT.2018 13:58:18

#### LTE band 66: 30MHz - 17.8GHz

Spurious emission limit -13dBm.




Date: 25.0CT.2018 13:54:30



#### LTE band 71: 30MHz - 6.98GHz

Spurious emission limit -13dBm.



Date: 25.OCT.2018 13:52:46



#### A.8 PEAK-TO-AVERAGE POWER RATIO

#### Reference

FCC: CFR Part 24.232 (d), 27.50(a)

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

#### According to KDB 971168 5.7.1:

- a)Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function:
- b) Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e)Record the maximum PAPR level associated with a probability of 0.1%

#### A.8.1 Measurement limit

not exceed 13 dB

#### A.8.2 Measurement results

#### LTE band 2, 20MHz

Frequency(MHz)	PAPR(dB)	
1860.0	QPSK	16QAM
	6.73	7.40

#### LTE band 12,10MHz

Frequency(MHz)	PAPR(dB)	
707.5	QPSK	16QAM
	5.19	5.96

#### LTE band 13,10MHz

Frequency(MHz)	PAPR(dB)	
782.0	QPSK	16QAM
	5.19	6.12

#### LTE band 66, 20MHz

Frequency(MHz)	PAPR(dB)	
1745.0	QPSK	16QAM
	6.57	7.18



# LTE band 71, 20MHz

Frequency(MHz)	PAPR(dB)	
680.5	QPSK	16QAM
	6.35	7.18



# **ANNEX B: Accreditation Certificate**

United States Department of Commerce National Institute of Standards and Technology



# Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 600118-0

#### Telecommunication Technology Labs, CAICT

Beijing China

is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:

# **Electromagnetic Compatibility & Telecommunications**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).

2018-09-28 through 2019-09-30

Effective Dates



For the National Voluntary Laboratory Accreditation Program

\*\*\*END OF REPORT\*\*\*