



# TEST REPORT

No. I17Z60633-GTE02

for

**TCL Communication Ltd.**

**CDMA/EVDO/GSM/UMTS/LTE Mobile phone**

**Model Name: 5049S**

**FCC ID: 2ACCJB083**

with

**Hardware Version: PIO**

**Software Version: v5G1H**

**Issued Date: 2017-05-22**

**Note :**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

**Test Laboratory:**

**FCC 2.948 Listed: No. 525429**

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: [cttl\\_terminals@catr.cn](mailto:cttl_terminals@catr.cn), website: [www.chinattl.com](http://www.chinattl.com)



## **REPORT HISTORY**

Report Number	Revision	Description	Issue Date
I17Z60633-GTE02	Rev.0	1 <sup>st</sup> edition	2017-05-22

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. TESTING LOCATION .....</b>	<b>4</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>4</b>
<b>1.3. PROJECT DATA .....</b>	<b>4</b>
<b>1.4. SIGNATURE .....</b>	<b>4</b>
<b>2. CLIENT INFORMATION .....</b>	<b>5</b>
<b>2.1. APPLICANT INFORMATION .....</b>	<b>5</b>
<b>2.2. MANUFACTURER INFORMATION .....</b>	<b>5</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>6</b>
<b>3.1. ABOUT EUT .....</b>	<b>6</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>6</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>6</b>
<b>3.4. GENERAL DESCRIPTION .....</b>	<b>6</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>7</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING .....</b>	<b>7</b>
<b>5. LABORATORY ENVIRONMENT .....</b>	<b>8</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>7. TEST EQUIPMENTS UTILIZED .....</b>	<b>10</b>
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>11</b>
<b>A.1 OUTPUT POWER .....</b>	<b>11</b>
<b>A.2 EMISSION LIMIT.....</b>	<b>17</b>
<b>A.3 FREQUENCY STABILITY .....</b>	<b>24</b>
<b>A.4 OCCUPIED BANDWIDTH .....</b>	<b>28</b>
<b>A.5 EMISSION BANDWIDTH .....</b>	<b>41</b>
<b>A.6 BAND EDGE COMPLIANCE .....</b>	<b>53</b>
<b>A.7 CONDUCTED SPURIOUS EMISSION .....</b>	<b>60</b>
<b>A.8 PEAK-TO-AVERAGE POWER RATIO .....</b>	<b>85</b>

## **1. Test Laboratory**

### **1.1. Testing Location**

Company Name: CTTL, Telecommunication Technology Labs, Academy of  
Telecommunication Research, MIIT  
Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China  
100191.  
No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China  
100191.  
Telephone: 00861062304633  
Fax: 00861062304793

### **1.2. Testing Environment**

Normal Temperature: 15-35℃  
Relative Humidity: 20-75%

### **1.3. Project data**

Testing Start Date: 2017-05-12  
Testing End Date: 2017-05-19

### **1.4. Signature**



---

Shen Yi


(Prepared this test report)



---

Zhong Nan

(Reviewed this test report)



---

Sun Xiang Qian

Deputy Director of the laboratory  
(Approved this test report)



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China. 201203  
Contact: Gong Zhizhou  
Email: zhizhou.gong@tcl.com  
Telephone: 0086-21-31363544

### **2.2. Manufacturer Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China. 201203  
Contact: Gong Zhizhou  
Email: zhizhou.gong@tcl.com  
Telephone: 0086-21-31363544

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	CDMA/EVDO/GSM/UMTS/LTE Mobile phone
Model Name	5049S
FCC ID	2ACCJB083
Antenna	Integrated
Output power	24.02dBm maximum EIRP measured for Band II
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.8VDC)
Extreme temp. Tolerance	-10°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

#### **3.2. Internal Identification of EUT used during the test**

EUT ID*	IMEI	HW Version	SW Version
UT45a	355471080106119	PIO	v5G1H
UT12a	355471080105657	PIO	v5G1H

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

AE ID*	Description
AE1	battery
AE2	Travel charger

AE1	
SN	CAC2900001C1
Type	TLp029C1
Capacitance	2900mAh
AE2	
Model	CBA0058AGAC2
Manufacturer	TENPAO

\*AE ID: is used to identify the test sample in the lab internally.

#### **3.4. General Description**

The Equipment Under Test (EUT) is a model of CDMA/EVDO/GSM/UMTS/LTE Mobile phone with integrated antenna. Manual and specifications of the EUT were provided to fulfil the test.

## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-16 Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-16 Edition
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES	10-1-16 Edition
ANSI/TIA-603-D	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2010
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS	v02r02

## 5. LABORATORY ENVIRONMENT

**Control room / conducted chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber 2** (8.6 meters×6.1 meters×3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 1 Ω
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

**Semi-anechoic chamber 2 / Fully-anechoic chamber 3** (10 meters×6.7 meters×6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz



## 6. SUMMARY OF TEST RESULTS

### WCDMA Band II

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	24.232(c)	P
2	Emission Limit	24.238, 2.1051	P
3	Frequency Stability	24.235, 2.1055	P
4	Occupied Bandwidth	2.1049(h)(i)	P
5	Emission Bandwidth	24.238(b)	P
6	Band Edge Compliance	24.238(b)	P
7	Conducted Spurious Emission	24.238, 2.1057	P
8	Peak-to-Average Power Ratio	24.232(d)	P

### WCDMA Band V

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	§2.1046(a), 22.913(a)	P
2	Emission Limit	22.917, 2.1051	P
3	Frequency Stability	22.235, 2.1055	P
4	Occupied Bandwidth	2.1049(h)(i)	P
5	Emission Bandwidth	22.917(b)	P
6	Band Edge Compliance	22.917(b)	P
7	Conducted Spurious Emission	22.917, 2.1057	P

### WCDMA Band IV

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50(d)(4)	P
2	Emission Limit	27.53(h), 2.1051	P
3	Frequency Stability	27.54, 2.1055	P
4	Occupied Bandwidth	2.1049(h)(i)	P
5	Emission Bandwidth	27.53(h)	P
6	Band Edge Compliance	27.53(h)	P
7	Conducted Spurious Emission	27.53(h), 2.1057	P
8	Peak-to-Average Power Ratio	27.50(a)	P

**7. Test Equipments Utilized**

NO.	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	Test Receiver	ESU26	100235	R&S	2018-03-01	1 year
2	Test Receiver	ESU26	100376	R&S	2017-10-26	1 year
3	EMI Antenna	3117	00058889	ETS-Lindgren	2017-12-15	3 year
4	Universal Radio Communication Tester	CMU200	108646	R&S	2017-10-27	1 year
5	Universal Radio Communication Tester	CMW500	149646	R&S	2017-11-02	1 year
6	Spectrum Analyzer	E4440A	MY49420053	Agilent	2018-03-01	1 year
7	EMI Antenna	9117	177	Schwarzbeck	2017-06-25	3 year
8	EMI Antenna	VULB9163	9163-235	Schwarzbeck	2017-10-29	3 year
9	Signal Generator	SMF100A	101295	R&S	2017-11-07	1 year
10	Climate chamber	SH-241	92007454	ESPEC	2017-12-14	2 year
11	Loop Antenna	HFH2-Z2	829324/007	R&S	2017-12-10	3 year

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 OUTPUT POWER**

#### **A.1.1 Summary**

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### **A.1.2 Conducted**

##### **A.1.2.1 Method of Measurements**

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II; 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V and 1712.4MHz, 1740MHz, and 1752.6MHz for WCDMA Band IV (bottom, middle and top of operational frequency range).

##### **Limit**

According to FCC §2.1046.

##### **WCDMA Band II**

###### **Measurement result-QPSK**

	CH	Frequency(MHz)	output power(dBm)
WCDMA (Band II)	9262	1852.4	22.62
	9400	1880.0	22.80
	9538	1907.6	22.91

###### **Measurement result-16QAM**

	CH	Frequency(MHz)	output power(dBm)
WCDMA (Band II)	9262	1852.4	21.32
	9400	1880.0	21.52
	9538	1907.6	21.62

##### **WCDMA Band V**

###### **Measurement result-QPSK**

	CH	Frequency(MHz)	output power(dBm)
WCDMA (Band V)	4132	826.4	23.69
	4183	836.6	23.66
	4233	846.6	23.62

###### **Measurement result-16QAM**

	CH	Frequency(MHz)	output power(dBm)
WCDMA (Band II)	4132	826.4	22.15
	4183	836.6	22.13
	4233	846.6	22.30

**WCDMA Band IV**

**Measurement result-QPSK**

WCDMA (Band IV)	CH	Frequency(MHz)	output power(dBm)
	1312	1712.4	23.76
	1450	1740.0	23.66
	1513	1752.6	23.69

**Measurement result-16QAM**

WCDMA (Band IV)	CH	Frequency(MHz)	output power(dBm)
	1312	1712.4	22.45
	1450	1740.0	22.39
	1513	1752.6	22.40

### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."


Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Rule Part 27.50(d)(2) specifies, "Fixed, mobile, and portable (handheld) stations operating in the 1710–1755MHz band are limited to a peak EIRP of 1 watt."


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603D-2015 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with RMS detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.

The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

### WCDMA Band II-EIRP

#### Limits

	Burst Peak EIRP (dBm)
WCDMA Band II	≤33dBm (2W)

#### Measurement result-QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.40	-22.08	2.84	-43.75	-4.87	23.70	33.00	9.30	H
1880.00	-22.93	2.85	-43.75	-4.82	22.79	33.00	10.21	H
1907.60	-21.64	2.88	-43.77	-4.77	24.02	33.00	8.98	H

#### Measurement result-16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.40	-23.30	2.84	-43.75	-4.87	22.48	33.00	10.52	H
1880.00	-24.26	2.85	-43.75	-4.82	21.46	33.00	11.54	H
1907.60	-22.90	2.88	-43.77	-4.77	22.76	33.00	10.24	H

**ANALYZER SETTINGS: RBW = VBW = 5MHz**

### WCDMA Band V-ERP

#### Limits

	Burst Peak ERP (dBm)
WCDMA Band V	≤38.45dBm

#### Measurement result-QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.40	-23.84	2.25	-45.76	-0.93	2.15	18.45	38.45	20.00	V
836.60	-22.69	2.26	-45.66	-0.82	2.15	19.38	38.45	19.07	V
846.60	-22.12	2.26	-45.56	-0.81	2.15	19.84	38.45	18.61	V

#### Measurement result-16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.40	-25.28	2.25	-45.76	-0.93	2.15	17.01	38.45	21.44	H
836.60	-23.77	2.26	-45.66	-0.82	2.15	18.30	38.45	20.15	V
846.60	-23.24	2.26	-45.56	-0.81	2.15	18.72	38.45	19.73	V

**ANALYZER SETTINGS: RBW = VBW = 5MHz**

# WCDMA Band IV-EIRP

## Limits

	Burst Peak EIRP (dBm)
WCDMA Band IV	30dBm (1W)

## Measurement result-QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.40	-22.83	3.66	-44.10	-5.12	22.73	30.00	7.27	H
1740.00	-22.16	4.36	-44.15	-5.07	22.70	30.00	7.30	H
1752.60	-21.77	3.85	-44.14	-5.05	23.57	30.00	6.43	H

## Measurement result-16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.40	-24.04	3.66	-44.10	-5.12	21.52	30.00	8.48	H
1740.00	-23.32	4.36	-44.15	-5.07	21.54	30.00	8.46	H
1752.60	-23.60	3.85	-44.14	-5.05	21.74	30.00	8.26	H

## ANALYZER SETTINGS: RBW = VBW = 5MHz

Frequency: 1907.60MHz

Peak EIRP(dBm)=P<sub>Mea</sub>(-21.64dBm)-P<sub>cl</sub>(2.88dB)-P<sub>Ag</sub>(-43.77dB)-G<sub>a</sub> (-4.77dB)= 24.02dBm

**Note: The EUT is tested in vertical polarization mode**



## A.2 EMISSION LIMIT


### A.2.1 Measurement Method

The measurements procedures in TIA-603D-2010 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238, Part 22.917 and Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II, WCDMA Band V and WCDMA Band IV.

**The procedure of radiated spurious emissions is as follows:**

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_{pl}$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss ( $P_{pl}$ ) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{pl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

### **A.2.2 Measurement Limit**

Part 24.238, Part 22.917 and Part 27.53 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10\log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10\log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### **A.2.3 Measurement Results**

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of WCDMA Band II (1852.4 MHz, 1880.0 MHz and 1907.6 MHz), WCDMA Band V (826.4 MHz, 836.6 MHz and 846.6 MHz) and WCDMA Band IV (1712.4 MHz, 1740 MHz and 1752.6 MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II, WCDMA Band V and WCDMA Band IV into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

#### A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
WCDMA Band V	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
WCDMA Band II	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass
WCDMA Band IV	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

#### A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
WCDMA Band V	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
WCDMA Band II	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2
WCDMA Band IV	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

**WCDMA BAND II Mode Channel 9262/1852.4MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3748.88	-60.11	5.92	-8.55	-57.48	-13.00	44.48	V
5598.82	-59.09	7.17	-10.58	-55.68	-13.00	42.68	V
7401.00	-58.18	8.26	-12.08	-54.36	-13.00	41.36	V
9237.49	-56.44	9.18	-13.24	-52.38	-13.00	39.38	V
11106.12	-53.32	10.07	-13.18	-50.21	-13.00	37.21	V
12967.86	-52.56	10.93	-13.48	-50.01	-13.00	37.01	V

**WCDMA BAND II Mode Channel 9400/1880MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3757.48	-61.13	5.88	-8.56	-58.45	-13.00	45.45	H
5580.28	-58.98	7.14	-10.58	-55.54	-13.00	42.54	H
7397.16	-58.78	8.24	-12.08	-54.94	-13.00	41.94	H
9361.43	-58.39	9.25	-13.32	-54.32	-13.00	41.32	H
11493.77	-53.17	10.23	-13.10	-50.30	-13.00	37.30	V
13281.62	-50.19	11.13	-13.89	-47.43	-13.00	34.43	H

**WCDMA BAND II Mode Channel 9538/1907.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3825.73	-60.82	5.92	-8.66	-58.08	-13.00	45.08	V
5729.79	-61.19	7.24	-10.55	-57.88	-13.00	44.88	V
7684.38	-57.16	8.37	-12.35	-53.18	-13.00	40.18	V
9554.82	-56.11	9.22	-13.35	-51.98	-13.00	38.98	H
11514.17	-53.34	10.25	-13.10	-50.49	-13.00	37.49	H
13340.68	-49.16	11.10	-13.98	-46.28	-13.00	33.28	H

**WCDMA BAND V Mode Channel 4132/826.4MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
2429.88	-54.32	4.73	-5.89	2.15	-55.31	-13.00	42.31	V
3253.74	-58.47	5.49	-7.61	2.15	-58.50	-13.00	45.50	H
4106.37	-59.73	6.17	-9.01	2.15	-59.04	-13.00	46.04	H
4873.32	-58.92	6.66	-9.77	2.15	-57.96	-13.00	44.96	V
5711.30	-58.78	7.21	-10.56	2.15	-57.58	-13.00	44.58	H
6580.10	-58.09	7.86	-11.10	2.15	-57.00	-13.00	44.00	V

**WCDMA BAND V Mode Channel 4183/836.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
2463.74	-55.01	4.75	-5.99	2.15	-55.92	-13.00	42.92	H
3300.75	-60.37	5.57	-7.72	2.15	-60.37	-13.00	47.37	H
4196.36	-59.56	6.22	-9.10	2.15	-58.83	-13.00	45.83	H
4972.08	-59.83	6.74	-9.87	2.15	-58.85	-13.00	45.85	H
5858.50	-57.32	7.34	-10.53	2.15	-56.28	-13.00	43.28	V
6609.19	-57.59	7.85	-11.13	2.15	-56.46	-13.00	43.46	H

**WCDMA BAND V Mode Channel 4233/846.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
1727.71	-60.41	3.95	-5.09	2.15	-61.42	-13.00	48.42	H
2549.98	-53.32	4.82	-6.19	2.15	-54.10	-13.00	41.10	H
3392.65	-61.24	5.63	-7.94	2.15	-61.08	-13.00	48.08	H
4232.91	-60.25	6.24	-9.13	2.15	-59.51	-13.00	46.51	V
5070.48	-58.21	6.75	-10.00	2.15	-57.11	-13.00	44.11	V
5911.34	-59.28	7.38	-10.52	2.15	-58.29	-13.00	45.29	V

**WCDMA BAND IV Mode Channel 1312/1712.4MHz**

Frequency(MHz )	P <sub>Mea</sub> (dBm )	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB )	Polarizatio n
3454.12	-60.20	5.64	-8.09	-57.75	-13.00	44.75	H
5132.46	-58.82	6.87	-10.09	-55.60	-13.00	42.60	H
6843.09	-57.21	7.83	-11.41	-53.63	-13.00	40.63	V
8583.90	-58.27	8.89	-13.02	-54.14	-13.00	41.14	V
10232.11	-56.85	9.64	-12.99	-53.50	-13.00	40.50	H
11991.18	-52.86	10.45	-13.00	-50.31	-13.00	37.31	H

**WCDMA BAND IV Mode Channel 1450/1740MHz**

Frequency(MHz )	P <sub>Mea</sub> (dBm )	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB )	Polarizatio n
3501.14	-59.87	5.70	-8.20	-57.37	-13.00	44.37	H
5220.45	-60.22	6.92	-10.21	-56.93	-13.00	43.93	H
6975.51	-57.46	8.01	-11.57	-53.90	-13.00	40.90	V
8717.25	-57.11	8.92	-13.04	-52.99	-13.00	39.99	V
10407.51	-55.03	9.73	-13.06	-51.70	-13.00	38.70	H
12204.80	-53.03	10.60	-13.08	-50.55	-13.00	37.55	H

**WCDMA BAND IV Mode Channel 1513/1752.6MHz**

Frequency(MHz )	P <sub>Mea</sub> (dBm )	Path Loss	Antenn a Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB )	Polarizatio n
3527.85	-58.25	5.74	-8.24	-55.75	-13.00	42.75	V
5229.18	-58.49	6.94	-10.22	-55.21	-13.00	42.21	V
7029.39	-57.41	8.02	-11.64	-53.79	-13.00	40.79	H
8745.60	-58.31	8.98	-13.05	-54.24	-13.00	41.24	H
10521.09	-53.64	9.74	-13.10	-50.28	-13.00	37.28	V
12295.13	-53.10	10.59	-13.12	-50.57	-13.00	37.57	V

### **A.3 FREQUENCY STABILITY**

#### **A.3.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of WCDMA Band II and WCDMA Band V, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C decrements from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

#### **A.3.2 Measurement Limit**

##### **A.3.2.1 For Hand carried battery powered equipment**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.

##### **A.3.2.2 For equipment powered by primary supply voltage**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section



2.1055(d)(1) applies.

### A.3.3 Measurement results

#### WCDMA Band II

##### Frequency Error vs Voltage-QPSK

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-6	0.003
3.8	-8	0.005
4.2	-5	0.003

##### Frequency Error vs Temperature-QPSK

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-7	0.003
0	-5	0.003
10	-6	0.003
20	-8	0.004
30	5	0.002
40	-7	0.004
50	-9	0.005

##### Frequency Error vs Voltage-16QAM

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-3	0.001
3.8	-3	0.002
4.2	-2	0.001

##### Frequency Error vs Temperature-16QAM

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-4	0.002
0	-5	0.003
10	1	0.001
20	1	0.001
30	-2	0.001
40	-5	0.003
50	-4	0.002

### WCDMA Band V

#### Frequency Error vs Voltage-QPSK

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-6	0.008
3.8	-7	0.008
4.2	-7	0.008

#### Frequency Error vs Temperature-QPSK

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-4	0.005
0	-5	0.006
10	-5	0.006
20	-6	0.007
30	-5	0.006
40	-4	0.005
50	-5	0.006

#### Frequency Error vs Voltage-16QAM

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-2	0.002
3.8	-2	0.003
4.2	-3	0.004

#### Frequency Error vs Temperature-16QAM

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-5	0.006
0	-6	0.007
10	-8	0.009
20	-8	0.010
30	-9	0.011
40	-10	0.012
50	-5	0.006

#### WCDMA Band IV

##### Frequency Error vs Voltage-QPSK

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-11	0.006
3.8	-12	0.007
4.2	-8	0.004

##### Frequency Error vs Temperature-QPSK

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-8	0.005
0	-11	0.006
10	-10	0.006
20	-10	0.006
30	-6	0.003
40	-8	0.004
50	-10	0.006

##### Frequency Error vs Voltage-16QAM

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-2	0.001
3.8	-2	0.001
4.2	-3	0.002

##### Frequency Error vs Temperature-16QAM

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-5	0.003
0	-6	0.004
10	-7	0.004
20	-5	0.003
30	-6	0.003
40	-5	0.003
50	-8	0.005

## **A.4 OCCUPIED BANDWIDTH**

### **Reference**

FCC: CFR Part 2.1049(h)(i)

#### **A.4.1 Occupied Bandwidth Results**

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from KDB 971168:


- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least  $10\log(\text{OBW} / \text{RBW})$  below the reference level.
- d) Set the detection mode to peak, and the trace mode to max hold.
- e) Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

### WCDMA Band II (99% BW)-QPSK

Frequency(MHz)	Occupied Bandwidth (99% BW)( MHz)
1852.4	4.151
1880.0	4.167
1907.6	4.167


### WCDMA Band II

#### Channel 9262-Occupied Bandwidth (99% BW)




Date: 15.MAY.2017 18:32:41

#### Channel 9400-Occupied Bandwidth (99% BW)



Date: 15.MAY.2017 18:33:16

### Channel 9538-Occupied Bandwidth (99% BW)




Date: 15.MAY.2017 18:33:50

### WCDMA Band II (99% BW)-16QAM

Frequency(MHz)	Occupied Bandwidth (99% BW)( MHz)
1852.4	4.167
1880.0	4.167
1907.6	4.183


### WCDMA Band II

#### Channel 9262-Occupied Bandwidth (99% BW)




Date: 17.MAY.2017 17:29:20

#### Channel 9400-Occupied Bandwidth (99% BW)



Date: 17.MAY.2017 17:31:18

### Channel 9538-Occupied Bandwidth (99% BW)



Date: 17.MAY.2017 17:32:27




Frequency(MHz)	Occupied Bandwidth (99% BW)( MHz)
826.4	4.167
836.6	4.151
846.6	4.151

Date: 15.MAY.2017 19:51:01

Date: 15.MAY.2017 19:51:35

### Channel 4233-Occupied Bandwidth (99% BW)




Date: 15.MAY.2017 19:52:10

### WCDMA Band V(99% BW)-16QAM

Frequency(MHz)	Occupied Bandwidth (99% BW)( MHz)
826.4	4.167
836.6	4.151
846.6	4.151


### WCDMA Band V

#### Channel 4132-Occupied Bandwidth (99% BW)




Date: 17.MAY.2017 18:05:41

#### Channel 4183-Occupied Bandwidth (99% BW)



Date: 17.MAY.2017 18:07:55

### Channel 4233-Occupied Bandwidth (99% BW)




Date: 17.MAY.2017 18:08:50

### WCDMA Band IV(99% BW)-QPSK

Frequency(MHz)	Occupied Bandwidth (99% BW)( MHz)
1712.4	4.151
1740.0	4.167
1752.6	4.199


### WCDMA Band IV

#### Channel 1312-Occupied Bandwidth (99% BW)




Date: 15.MAY.2017 19:10:09

#### Channel 1450-Occupied Bandwidth (99% BW)



Date: 15.MAY.2017 19:10:44

### Channel 1513-Occupied Bandwidth (99% BW)




Date: 15.MAY.2017 19:11:18

### WCDMA Band IV(99% BW)-16QAM

Frequency(MHz)	Occupied Bandwidth (99% BW)( MHz)
1712.4	4.183
1740.0	4.167
1752.6	4.151


### WCDMA Band IV

#### Channel 1312-Occupied Bandwidth (99% BW)




Date: 17.MAY.2017 18:26:26

### Channel 1450-Occupied Bandwidth (99% BW)



Date: 17.MAY.2017 18:28:24

### Channel 1513-Occupied Bandwidth (99% BW)



Date: 17.MAY.2017 18:29:16



## A.5 EMISSION BANDWIDTH

### Reference

FCC: CFR Part 22.917(b), 24.238(a)

### A.5.1 Emission Bandwidth Results


The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

### WCDMA Band II -QPSK

Frequency(MHz)	Emission Bandwidth ( MHz)
1852.4	4.71
1880.0	4.73
1907.6	4.71


### WCDMA Band II

### Channel 9262-Emission Bandwidth




Date: 15.MAY.2017 18:35:01

## Channel 9400-Emission Bandwidth



Date: 15.MAY.2017 18:36:11

## Channel 9538-Emission Bandwidth




Date: 15.MAY.2017 18:37:20

### WCDMA Band II -16QAM

Frequency(MHz)	Emission Bandwidth ( MHz)
1852.4	4.73
1880.0	4.71
1907.6	4.70


### WCDMA Band II

#### Channel 9262-Emission Bandwidth




Date: 17.MAY.2017 17:34:53

#### Channel 9400-Emission Bandwidth



Date: 17.MAY.2017 17:36:26

## Channel 9538-Emission Bandwidth




Date: 17.MAY.2017 17:37:56

### WCDMA Band V-QPSK

Frequency(MHz)	Emission Bandwidth ( MHz)
826.40	4.68
836.60	4.68
846.60	4.68


### WCDMA Band V

#### Channel 4132-Emission Bandwidth




Date: 15.MAY.2017 19:53:21

### Channel 4183-Emission Bandwidth



Date: 15.MAY.2017 19:54:30

### Channel 4233-Emission Bandwidth




Date: 15.MAY.2017 19:55:40

### WCDMA Band V-16QAM

Frequency(MHz)	Emission Bandwidth ( MHz)
826.40	4.66
836.60	4.65
846.60	4.66


### WCDMA Band V

#### Channel 4132-Emission Bandwidth




Date: 17.MAY.2017 18:10:55

### Channel 4183-Emission Bandwidth



Date: 17.MAY.2017 18:12:52

### Channel 4233-Emission Bandwidth



Date: 17.MAY.2017 18:14:24




### WCDMA Band IV-QPSK

Frequency(MHz)	Emission Bandwidth ( MHz)
1712.4	4.73
1740.0	4.71
1752.6	4.73


### WCDMA Band IV

#### Channel 1312-Emission Bandwidth




Date: 15.MAY.2017 19:12:29

## Channel 1450-Emission Bandwidth



Date: 15.MAY.2017 19:13:39

## Channel 1513-Emission Bandwidth




Date: 15.MAY.2017 19:14:49

### WCDMA Band IV-16QAM

Frequency(MHz)	Emission Bandwidth ( MHz)
1712.4	4.71
1740.0	4.70
1752.6	4.70


### WCDMA Band IV

#### Channel 1312-Emission Bandwidth




Date: 17.MAY.2017 18:30:52

## Channel 1450-Emission Bandwidth



Date: 17.MAY.2017 18:32:18

## Channel 1513-Emission Bandwidth



Date: 17.MAY.2017 18:33:48

## A.6 BAND EDGE COMPLIANCE


### A.6.1 Measurement limit

On any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least  $43+10\log(P)$  dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm. According to KDB 971168 v02r02 6.0, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

### A.6.2 Measurement result


#### WCDMA Band II-QPSK

#### LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262



Date: 15.MAY.2017 18:37:32

# HIGH BAND EDGE BLOCK-C (WCDMA Band II) –Channel 9538



Date: 15.MAY.2017 18:42:38


### LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262



Date: 17.MAY.2017 17:40:24


## WCDMA Band V-QPSK

### LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132



Date: 15.MAY.2017 19:55:52

### HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233




Date: 15.MAY.2017 19:57:58




## WCDMA Band V-16QAM

### LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132




Date: 19.MAY.2017 13:06:36

### HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233




Date: 17.MAY.2017 18:15:33

## WCDMA Band IV-QPSK LOW BAND EDGE BLOCK-A (WCDMA Band IV)-Channel 1312



Date: 15.MAY.2017 19:15:00


## HIGH BAND EDGE BLOCK-C (WCDMA Band IV) –Channel 1513



Date: 15.MAY.2017 19:17:06


## WCDMA Band IV-16QAM

### LOW BAND EDGE BLOCK-A (WCDMA Band IV)-Channel 1312



Date: 17.MAY.2017 17:59:11

### HIGH BAND EDGE BLOCK-C (WCDMA Band IV) –Channel 1513



Date: 17.MAY.2017 17:59:51

## **A.7 CONDUCTED SPURIOUS EMISSION**

### **Reference**

FCC: CFR Part 2.1057, 22.917, 24.238, 27.53(h).

#### **A.7.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
3. According to KDB 971168 v02r01 6.0, the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz)

#### **WCDMA Band II Transmitter**

Channel	Frequency (MHz)
9262	1852.40
9400	1880.00
9538	1907.60

#### **WCDMA Band IV Transmitter**

Channel	Frequency (MHz)
1312	1712.40
1450	1740.00
1513	1752.60

#### **WCDMA Band V Transmitter**

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60

#### **A. 7.2 Measurement Limit**

Part 24.238, Part 22.917 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A.7.3 Measurement result

#### WCDMA Band II

#### Channel 9262: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 15.MAY.2017 18:45:19

#### Channel 9262: 1GHz –2.5GHz


Spurious emission limit –13dBm.

**NOTE:** peak above the limit line is the carrier frequency.




Date: 15.MAY.2017 18:45:47

**Channel 9262: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 18:46:15

**Channel 9262: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 18:46:43

**Channel 9262: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 18:47:12


**Channel 9262: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 18:47:40

### Channel 9400: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 15.MAY.2017 18:48:11

### Channel 9400: 1GHz –2.5GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 15.MAY.2017 18:48:39




**Channel 9400: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 18:49:07

**Channel 9400: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 18:49:35

**Channel 9400: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 18:50:03


**Channel 9400: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 18:50:32

### Channel 9538: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 15.MAY.2017 18:51:03

### Channel 9538: 1GHz –2.5GHz


Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 15.MAY.2017 18:51:31

**Channel 9538: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 18:51:59

**Channel 9538: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 18:52:27

**Channel 9538: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 18:52:55

**Channel 9538: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 18:53:23

## WCDMA Band IV

### Channel 1312: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 15.MAY.2017 19:19:48

### Channel 1312: 1GHz –2.5GHz


Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 15.MAY.2017 19:20:16

**Channel 1312: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 19:20:44

**Channel 1312: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 19:21:12

**Channel 1312: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 19:21:40

**Channel 1312: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 19:22:08



### Channel 1450: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 15.MAY.2017 19:22:40

### Channel 1450: 1GHz –2.5GHz


Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 15.MAY.2017 19:23:08

**Channel 1450: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 19:23:36

**Channel 1450: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 19:24:04

**Channel 1450: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 19:24:32


**Channel 1450: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 19:25:01

### Channel 1513: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 15.MAY.2017 19:25:32

### Channel 1513: 1GHz –2.5GHz


Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 15.MAY.2017 19:26:00

**Channel 1513: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 19:26:28

**Channel 1513: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 19:26:56

**Channel 1513: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 19:27:24

**Channel 1513: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 19:27:52

## WCDMA Band V

### Channel 4132: 30MHz –1GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 15.MAY.2017 20:06:59


### Channel 4132: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 15.MAY.2017 20:07:27

**Channel 4132: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 20:07:55

**Channel 4132: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 20:08:23



### Channel 4183: 30MHz –1GHz

Spurious emission limit –13dBm.


**NOTE:** peak above the limit line is the carrier frequency.



Date: 15.MAY.2017 20:08:54


### Channel 4183: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 15.MAY.2017 20:09:22

**Channel 4183: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 20:09:50

**Channel 4183: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 15.MAY.2017 20:10:18

### Channel 4233: 30MHz –1GHz

Spurious emission limit –13dBm.


**NOTE:** peak above the limit line is the carrier frequency.



Date: 15.MAY.2017 20:10:49


### Channel 4233: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 15.MAY.2017 20:11:17

**Channel 4233: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 20:11:45

**Channel 4233: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.



Date: 15.MAY.2017 20:12:13

## **A.8 PEAK-TO-AVERAGE POWER RATIO**

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

According to KDB 971168 v02r02 5.7.1:

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e) Record the maximum PAPR level associated with a probability of 0.1%

### **A.8.1 Measurement limit**

not exceed 13 dB

### **A.8.2 Measurement results**

#### **WCDMA Band II-QPSK**

##### **Measurement result**

WCDMA (Band II)	CH	Frequency(MHz)	PAPR(dB)
	9400	1880.0	4.198

#### **WCDMA Band II-16QAM**

##### **Measurement result**

WCDMA (Band II)	CH	Frequency(MHz)	PAPR(dB)
	9400	1880.0	5.256

#### **WCDMA Band IV-QPSK**

##### **Measurement result**

WCDMA (Band IV)	CH	Frequency(MHz)	PAPR(dB)
	1450	1740.0	3.815

#### **WCDMA Band IV-16QAM**

##### **Measurement result**

WCDMA (Band IV)	CH	Frequency(MHz)	PAPR(dB)
	1450	1740.0	3.880



**China National Accreditation Service for Conformity Assessment**  
**LABORATORY ACCREDITATION CERTIFICATE**  
(Registration No. CNAS L0570 )

**Telecommunication Technology Labs,**  
**Academy of Telecommunication Research, MIIT**  
No.52, Huayuan North Road, Haidian District, Beijing, China  
No.51, Xueyuan Road, Haidian District, Beijing, China  
TCL International E City, No. 1001 Zhongshanyuan Road, Nanshan  
District, Shenzhen, Guangdong Province

*is accredited in accordance with ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories(CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence to undertake testing and calibration service as described in the schedule attached to this certificate.*

*The scope of accreditation is detailed in the attached schedule bearing the same registration number as above. The schedule form an integral part of this certificate.*

Date of Issue: 2015-11-13  
Date of Expiry: 2017-06-19  
Date of Initial Accreditation: 1998-07-03

Signed on behalf of China National Accreditation Service for Conformity Assessment 

China National Accreditation Service for Conformity Assessment(CNAS) is authorized by Certification and Accreditation Administration of the People's Republic of China (CNCA) to operate the national accreditation schemes for conformity assessment. CNAS is a signatory of the International Laboratory Accreditation Cooperation Mutual Recognition Arrangement (ILAC MRA) and the Asia Pacific Laboratory Accreditation Cooperation Mutual Recognition Arrangement (APLAC MRA). The validity of the certificate can be checked on CNAS website at <http://www.cnas.org.cn/english/findanaccreditedbody/index.shtml>

\*\*\*END OF REPORT\*\*\*