





TEST REPORT No. I19Z61862-WMD03

for

TCL Communication Ltd.

USB Connect 4G V2 (SA)

Model Name: IK41UD

FCC ID: 2ACCJB114

with

Hardware Version: V3.0

Software Version: IK41_ZZ_02.00_01

Issued Date: 2019-12-10

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: cttl terminals@caict.ac.cn, website: www.caict.ac.cn





REPORT HISTORY

Report Number	Revision	Description	Issue Date
I19Z61862-WMD03	Rev.0	1 st edition	2019-11-29
I19Z61862-WMD03	Rev.1	2 nd edition	2019-12-10
		Model number is	
		corrected to IK41UD.	
		Added the results of	
		spot check.	

Note: the latest revision of the test report supersedes all previous version.





CONTENTS

1. TEST LABORATORY	4
1.1. INTRODUCTION & ACCREDITATION	4
1.2. TESTING LOCATION	4
1.3. TESTING ENVIRONMENT	5
1.4. PROJECT DATA	5
1.5. SIGNATURE	5
2. CLIENT INFORMATION	
2.1. APPLICANT INFORMATION	6
2.2. MANUFACTURER INFORMATION	
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	
3.1. ABOUT EUT	
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	
4. REFERENCE DOCUMENTS	
4.1. REFERENCE DOCUMENTS FOR TESTING	
5. LABORATORY ENVIRONMENT	
6. SUMMARY OF TEST RESULT	
6.1. SUMMARY OF TEST RESULTS	
6.2. EXPLANATION OF RE-USE OF TEST DATA	
7. TEST EQUIPMENT UTILIZED	
ANNEX A: MEASUREMENT RESULTS	13
A.1 OUTPUT POWER	
A.2 EMISSION LIMIT	
A.3 FREQUENCY STABILITY	
A.5 EMISSION BANDWIDTH	
A.6 BAND EDGE COMPLIANCE	
A.7 CONDUCTED SPURIOUS EMISSION	
A.8 PEAK-TO-AVERAGE POWER RATIO	
ANNEY B. ACCREDITATION CERTIFICATE	122





1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0 and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Location 1: CTTL (huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,

P. R. China 100191

Location 2: CTTL (Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,

Haidian District, Beijing, P. R. China 100191





1.3. <u>Testing Environment</u>

Normal Temperature: $15-35^{\circ}$ C Relative Humidity: 20-75%

1.4. Project data

Testing Start Date: 2019-11-04
Testing End Date: 2019-12-10

1.5. Signature



Dong Yuan (Prepared this test report)



Zhou Yu (Reviewed this test report)

赵慧麟

Zhao Hui Lin
Deputy Director of the laboratory
(Approved this test report)





2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.

Address /Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science

Park, Shatin, NT, Hong Kong

Contact: Gong Zhizhou

Email: zhizhou.gong@tcl.com Telephone: 0086-755-36611722

Fax: 0086-755-36612000-81722

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.

Address /Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science

Park, Shatin, NT, Hong Kong

Contact: Gong Zhizhou

Email: zhizhou.gong@tcl.com Telephone: 0086-755-36611722

Fax: 0086-755-36612000-81722





3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description USB Connect 4G V2 (SA)

Model Name IK41UD FCC ID 2ACCJB114 Antenna Embedded

Output power 25.41dBm maximum EIRP measured for LTE Band 2

Extreme vol. Limits 4.25VDC to 5.75VDC (nominal: 5.0VDC)

Extreme temp. Tolerance -10°C to +55°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

3.2. Internal Identification of EUT used during the test

 EUT ID*
 IMEI
 HW Version
 SW Version

 UT15a
 352599110000275
 V3.0
 IK41_ZZ_02.00_01

3.3. Internal Identification of AE used during the test

AE ID* Description

AE1 Cable for supply power

AE1

Model /
Manufacturer /
Capacitance /

^{*}EUT ID: is used to identify the test sample in the lab internally.

^{*}AE ID: is used to identify the test sample in the lab internally.





4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

<u> </u>		
Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-18
		Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-18
		Edition
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS	10-1-18
	SERVICES	Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment	2016
	Measurement and Performance Standards	
ANSI/TIA-102.CAAA	DIGITAL C4FMCQPSK TRANSCEIVER MEASUREMENT	2016
-E	METHODS	
ANSI C63.26	American National Standard for Compliance Testing of	2015
	Transmitters Used in Licensed Radio Services	
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF	v03r01
	LICENSED DIGITAL TRANSMITTERS	





5. <u>LABORATORY ENVIRONMENT</u>

Fully-anechoic chamber FAC-3 (9 meters × 6.5 meters × 4 meters) did not exceed following limits along the EMC testing:

ge =e teeg.	
Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB;
	1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Site voltage standing-wave ratio (SVSWR)	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz





6. SUMMARY OF TEST RESULT

6.1. Summary of test results

LTE Band 2

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	24.232	BR
2	Emission Limit	24.238	BR
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	24.238	BR
6	Band Edge Compliance	24.238	BR
7	Conducted Spurious Emission	24.238	BR
8	Peak-to-Average Power Ratio	24.232	BR

LTE Band 4

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	BR
2	Emission Limit	27.53	BR
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	27.53	BR
6	Band Edge Compliance	27.53	BR
7	Conducted Spurious Emission	27.53	BR
8	Peak-to-Average Power Ratio	27.50	BR

LTE Band 5

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	22.913	Р
2	Emission Limit	22.917	Р
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	22.917	BR
6	Band Edge Compliance	22.917	BR
7	Conducted Spurious Emission	22.917	BR





LTE Band 7

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	Р
2	Emission Limit	27.53	Р
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	27.53	BR
6	Band Edge Compliance	27.53	BR
7	Conducted Spurious Emission	27.53	BR
8	Peak-to-Average Power Ratio	27.50	BR

LTE Band 12

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	Р
2	Emission Limit	27.53	Р
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	27.53	BR
6	Band Edge Compliance	27.53	BR
7	Conducted Spurious Emission	27.53	BR
8	Peak-to-Average Power Ratio	27.50	BR

Terms used in Verdict column

Р	Pass. The EUT complies with the essential requirements in the standard.		
NP	Not Performed. The test was not performed by CTTL.		
NA	Not Applicable. The test was not applicable.		
BR	Re-use test data from basic model report.		
F	Fail. The EUT does not comply with the essential requirements in the		
	standard.		

6.2. Explanation of re-use of test data

The Equipment Under Test (EUT) model USB Connect 4G V2 (SA) (FCC ID: 2ACCJB114) is a variant product of USB Connect 4G V2 (EMEA) (FCC ID: 2ACCJB113) and USB Connect 4G V2 (NA) (FCC ID: 2ACCJB115), according to the declaration of changes provided by the applicant and FCC KDB publication 484596 D01, spot check measurements were performed on this device. The Output Power and Emission limits of LTE band 5,7,12 were tested. The other test results of LTE Band 7 are derived from test report No.I19Z61810-WMD03. Other test results are derived from test report No.I19Z61859-WMD03. Please refer Annex A for detail spot check verification data and reference data. The spot check test results are consistent with basic model.

For detail differences between two models please refer the Declaration of Changes document.





7. Test Equipment Utilized

NO.	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	Universal Radio Communication Tester	CMW500	159082	R&S	2019-12-25	1 year
2	Spectrum Analyzer	FSU26	200030	R&S	2020-06-03	1 year
3	Climate chamber	SH-242	93008556	ESPEC	2019-12-21	2 year
4	EMI Antenna	VULB9163	9163-235	Schwarzbeck	2020-11-20	1 year
5	EMI Antenna	3117	00058889	ETS-Lindgren	2020-02-02	1 year
6	EMI Antenna	3117	00119024	ETS-Lindgren	2020-02-25	1 year
7	EMI Antenna	9117	167	Schwarzbeck	2020-05-27	1 year
8	Signal Generator	N5183A	MY49060052	R&S	2020-06-24	1 year
9	Test Receiver	E4440A	MY48250642	Agilent	2020-03-18	1 year
10	Universal Radio Communication Tester	CMW500	143008	R&S	2020-11-26	1 year





ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMW500) to ensure max power transmission and proper modulation. In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies (bottom, middle and top of operational frequency range) for each bandwidth.

A.1.2.2 Measurement result

LTE band 2

Bandwidth	RB size/offset	Fraguency (MHz)	Power	(dBm)
Danuwiutii	RD Size/Oliset	Frequency (MHz)	QPSK	16QAM
		1909.3	22.19	21.44
	1 RB high	1880.0	22.20	21.15
		1850.7	22.08	21.27
		1909.3	22.28	20.77
	1 RB low	1880.0	22.41	21.18
1.4MHz		1850.7	22.03	21.25
1.4IVITZ		1909.3	22.30	21.13
	50% RB mid	1880.0	22.43	21.30
		1850.7 22.15	22.15	21.04
		1909.3	21.12	20.11
	100% RB	3 1880.0 21.24	20.28	
	1850	1850.7	21.23	20.00
		1908.5	22.27	21.31
	1 RB high	1880.0	22.39	21.40
		1851.5	22.08	21.27
		1908.5	22.55	21.36
3MHz	1 RB low	1880.0	22.51	21.76
		1851.5	22.37	21.48
		1908.5	21.23	20.09
	50% RB mid	1880.0	21.23	20.22
		1851.5	21.20	20.43





100% RB 1908.5 21.21 20.04					
1 RB high 1880.0 22.56 20.77 1 RB high 1880.0 22.56 20.77 1 RB low 1880.0 22.50 21.28 1 RB low 1880.0 22.52 20.74 1 RB low 1880.0 21.33 20.30 1 RB low 1890.0 21.33 20.30 1 RB low 1890.0 21.38 20.19 1 RB high 1880.0 21.38 20.19 1 RB high 1880.0 22.55 21.26 20.14 1 RB low 1880.0 22.55 21.31 20.09 1 RB low 1880.0 22.55 21.31 20.09 1 RB low 1880.0 22.55 21.39 1 RB low 1880.0 22.51 21.36 1 RB low 1880.0 21.37 20.40 1 RB low 1880.0 21.37 20.40 1 RB low 1880.0 21.37 20.40 1 RB low 1880.0 22.36 21.01 1 RB low 1880.0 21.37 20.40 1 RB low 1880.0 22.36 21.01 1 RB low 1880.0 21.37 20.40 1 RB low 1880.0 22.36 21.17 20.21 1 RB low 1880.0 22.36 21.21 1 RB low 1880.0 21.37 20.40 1 RB low 1880.0 22.36 21.21 1 RB low 1880.0 22.36 21.21 2 RB low 2 RB l			1908.5	21.21	20.04
1 RB high		100% RB	1880.0	21.28	20.23
1 RB high			1851.5	21.16	20.26
1852.5 21.97 21.20 1 RB low 1880.0 22.52 20.74 1852.5 22.29 21.15 1852.5 22.29 21.15 50% RB mid 1880.0 21.33 20.30 1852.5 21.31 20.09 1907.5 21.31 20.09 1907.5 21.31 20.09 1907.5 21.31 20.09 1852.5 21.31 20.09 1852.5 21.31 20.09 1852.5 21.31 20.09 1852.5 21.31 20.09 1852.5 21.31 20.09 1852.5 21.36 20.14 1880.0 21.38 20.19 1852.5 21.26 20.14 1905.0 22.51 21.18 1 RB high 1880.0 22.55 21.39 1855.0 22.48 21.06 1880.0 22.51 21.36 1855.0 22.48 21.06 1865.0 22.36 21.01 1905.0 21.33 20.39 50% RB mid 1880.0 22.51 21.36 1855.0 22.36 21.01 1905.0 21.33 20.39 50% RB mid 1880.0 21.37 20.40 1855.0 21.21 20.22 1902.5 22.13 20.93 1 RB high 1880.0 22.09 21.20 1857.5 22.01 21.19 1 RB low 1880.0 22.15 21.28 1 RB low 1880.0 21.18 20.06 1 RB low 1880.0 21.18 20.06			1907.5	22.12	20.96
1 RB low		1 RB high	1880.0	22.56	20.77
1 RB low			1852.5	21.97	21.20
1852.5 22.29 21.15 1907.5 21.22 20.12 50% RB mid 1880.0 21.33 20.30 1852.5 21.31 20.09 1907.5 21.31 20.29 100% RB 1880.0 21.38 20.19 1852.5 21.26 20.14 1805.0 22.51 21.18 1 RB high 1880.0 22.55 21.39 1855.0 22.48 21.06 1860.0 22.51 21.38 1 RB low 1880.0 22.55 21.39 1855.0 22.48 21.06 1860.0 22.51 21.36 1855.0 22.48 21.06 1860.0 22.51 21.36 1855.0 22.36 21.01 1855.0 22.36 21.01 1805.0 21.38 20.39 50% RB mid 1880.0 21.43 20.51 1855.0 21.17 20.21 1905.0 21.37 20.40 1855.0 21.07 20.27 100% RB 1880.0 21.37 20.40 1855.0 21.21 20.22 1902.5 22.13 20.93 1 RB high 1880.0 22.09 21.20 1857.5 22.01 21.19 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1857.5 22.01 21.11 15MHz 15MHz 15MHz 150% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 1800 RB 1880.0 21.18 20.01			1907.5	22.50	21.28
5MHz 1907.5 21.22 20.12		1 RB low	1880.0	22.52	20.74
1907.5 21.22 20.12 1880.0 21.33 20.30 1852.5 21.31 20.09 1907.5 21.31 20.29 100% RB 1880.0 21.38 20.19 1852.5 21.26 20.14 1905.0 22.51 21.18 1 RB high 1880.0 22.55 21.39 1855.0 22.48 21.06 1905.0 22.60 21.40 1 RB low 1880.0 22.51 21.36 1 RB low 1880.0 22.51 21.36 1 855.0 22.36 21.01 1 855.0 22.36 21.01 1 855.0 22.36 21.01 1 855.0 21.38 20.39 1 855.0 21.38 20.39 1 855.0 21.17 20.21 1 1905.0 21.37 20.40 1 1855.0 21.17 20.21 1 1905.0 21.37 20.40 1 1855.0 21.21 20.22 1 1902.5 22.13 20.93 1 RB high 1880.0 22.09 21.20 1 1 RB high 1880.0 22.15 21.28 1 1 RB low 1880.0 22.15 21.28 1 1 RB low 1880.0 22.15 21.28 1 1 RB low 1880.0 21.18 20.06 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	5MH7		1852.5	22.29	21.15
1852.5 21.31 20.09 1907.5 21.31 20.29 100% RB 1880.0 21.38 20.19 1852.5 21.26 20.14 1905.0 22.51 21.18 1 RB high 1880.0 22.55 21.39 1855.0 22.48 21.06 1905.0 22.60 21.40 1 RB low 1880.0 22.51 21.36 1855.0 22.48 21.06 1905.0 22.60 21.40 1 RB low 1880.0 22.51 21.36 1855.0 22.36 21.01 20.39 50% RB mid 1880.0 21.38 20.39 50% RB mid 1880.0 21.43 20.51 1855.0 21.17 20.21 1905.0 21.37 20.40 1855.0 21.17 20.21 1905.0 21.37 20.40 1855.0 21.21 20.22 1902.5 22.13 20.93 1 RB high 1880.0 22.09 21.20 1857.5 22.01 21.19 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1 RB low 1880.0 22.15 21.28 1 RB low 1880.0 22.15 21.28 1 RB low 1880.0 22.15 21.21 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01	SIVII 12		1907.5	21.22	20.12
100% RB		50% RB mid	1880.0	21.33	20.30
100% RB			1852.5	21.31	20.09
1852.5 21.26 20.14 1905.0 22.51 21.18 1 RB high 1880.0 22.55 21.39 1855.0 22.48 21.06 1 1905.0 22.60 21.40 1 RB low 1880.0 22.51 21.36 1 855.0 22.36 21.01 1 1905.0 21.38 20.39 50% RB mid 1880.0 21.43 20.51 1 1905.0 21.37 20.21 1 1905.0 21.37 20.27 1 100% RB 1880.0 21.37 20.40 1 1855.0 21.21 20.22 1 1902.5 22.13 20.93 1 RB high 1880.0 22.09 21.20 1 1857.5 22.01 21.19 1 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1 1 RB low 1880.0 21.11 20.12 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			1907.5	21.31	20.29
1 RB high		100% RB	1880.0	21.38	20.19
1 RB high			1852.5	21.26	20.14
1855.0 22.48 21.06 1905.0 22.60 21.40 1880.0 22.51 21.36 1855.0 22.36 21.01 1855.0 22.36 21.01 1905.0 21.38 20.39 50% RB mid 1880.0 21.43 20.51 1855.0 21.17 20.21 100% RB 1880.0 21.07 20.27 100% RB 1880.0 21.37 20.40 1855.0 21.21 20.22 1902.5 22.13 20.93 1 RB high 1880.0 22.09 21.20 1857.5 22.01 21.19 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1 RB low 1880.0 22.15 21.28 15MHz 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 1902.5 21.17 20.16			1905.0	22.51	21.18
10MHz 1 RB low 1880.0 1885.0 22.36 21.01 1895.0 22.36 21.01 1905.0 21.38 20.39 50% RB mid 1880.0 21.43 20.51 1885.0 21.17 20.21 1905.0 21.07 20.27 100% RB 1880.0 21.37 20.40 1855.0 21.21 20.22 1902.5 22.13 20.93 1 RB high 1880.0 22.13 20.93 1 RB low 1880.0 22.09 21.20 1857.5 22.01 21.19 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1 RB low 1880.0 22.15 21.28 1 RB low 1880.0 22.15 21.21 20.22 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 1902.5 21.17 20.16		1 RB high	1880.0	22.55	21.39
10MHz 10MHz 10MHz 100Hz 10			1855.0	22.48	21.06
10MHz 1855.0 22.36 21.01 1905.0 21.38 20.39 50% RB mid 1880.0 21.43 20.51 1855.0 21.17 20.21 1905.0 21.07 20.27 1905.0 21.07 20.27 1905.0 21.37 20.40 1855.0 21.21 20.22 1902.5 22.13 20.93 1 RB high 1880.0 22.09 21.20 1857.5 22.01 21.19 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1 RB low 1880.0 22.15 21.28 1 RB low 1880.0 22.15 21.28 1 RB low 1880.0 22.15 21.11 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01			1905.0	22.60	21.40
10MHz 1905.0 21.38 20.39 50% RB mid 1880.0 21.43 20.51 1855.0 21.17 20.21 1905.0 21.07 20.27 100% RB 1880.0 21.37 20.40 1855.0 21.21 20.22 1902.5 22.13 20.93 1 RB high 1880.0 22.09 21.20 1857.5 22.01 21.19 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1857.5 22.01 21.11 1902.5 22.15 21.28 1857.5 22.01 21.11 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01		1 RB low	1880.0	22.51	21.36
1905.0 21.38 20.39 1880.0 21.43 20.51 1855.0 21.17 20.21 1905.0 21.07 20.27 100% RB 1880.0 21.37 20.40 1855.0 21.21 20.22 1902.5 22.13 20.93 1 RB high 1880.0 22.09 21.20 1857.5 22.01 21.19 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1857.5 22.01 21.11 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01	10MHz		1855.0	22.36	21.01
1855.0 21.17 20.21 1905.0 21.07 20.27 100% RB 1880.0 21.37 20.40 1855.0 21.21 20.22 1902.5 22.13 20.93 1 RB high 1880.0 22.09 21.20 1857.5 22.01 21.19 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1857.5 22.01 21.11 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01	TOWN 12		1905.0	21.38	20.39
100% RB		50% RB mid	1880.0	21.43	20.51
100% RB			1855.0	21.17	20.21
1855.0 21.21 20.22 1902.5 22.13 20.93 1 RB high 1880.0 22.09 21.20 1857.5 22.01 21.19 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1857.5 22.01 21.11 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01			1905.0	21.07	20.27
1 RB high 1880.0 22.09 21.20 1857.5 22.01 21.19 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1857.5 22.01 21.11 1902.5 22.15 21.28 1857.5 22.01 21.11 20.12 1902.5 21.14 20.12 1902.5 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01		100% RB	1880.0	21.37	20.40
1 RB high 1880.0 22.09 21.20 1857.5 22.01 21.19 1902.5 22.58 21.24 1880.0 22.15 21.28 1857.5 22.01 21.11 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01			1855.0	21.21	20.22
1857.5 22.01 21.19 1902.5 22.58 21.24 1 RB low 1880.0 22.15 21.28 1857.5 22.01 21.11 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01			1902.5	22.13	20.93
1 RB low 1880.0 22.15 21.28 1857.5 22.01 21.11 1902.5 21.14 20.12 1860.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 1880.0 21.18 20.01		1 RB high	1880.0	22.09	21.20
1 RB low 1880.0 22.15 21.28 1857.5 22.01 21.11 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01			1857.5	22.01	21.19
1 RB low 1880.0 22.15 21.28 1857.5 22.01 21.11 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01			1902.5	22.58	21.24
1857.5 22.01 21.11 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01		1 RB low	1880.0		
15MHz 1902.5 21.14 20.12 50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01					
50% RB mid 1880.0 21.18 20.06 1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01	15MHz				
1857.5 21.10 19.92 1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01		50% PP mid			
1902.5 21.17 20.16 100% RB 1880.0 21.18 20.01		JU /0 IXD IIIIU			
100% RB 1880.0 21.18 20.01					
1857.5 20.95 19.96		100% RB	1880.0	21.18	20.01
			1857.5	20.95	19.96





		1900.0	22.19	21.08
	1 RB high	1880.0	21.95	21.04
		1860.0	21.86	21.20
		1900.0	22.11	21.00
	1 RB low	1880.0	22.06	21.08
20MHz		1860.0	21.87	21.11
ZUIVITZ		1900.0	21.09	19.96
	50% RB mid	1880.0	21.27	20.07
		1860.0	21.20	20.07
		1900.0	21.14	20.01
	100% RB	1880.0	21.27	20.20
		1860.0	21.17	20.05





LTE band 4

LTE band 4	DD oine/effert	Fraguency (MIII-)	Power	(dBm)
Bandwidth	RB size/offset	Frequency (MHz)	QPSK	16QAM
		1754.3	22.26	21.18
	1 RB high	1732.5	22.38	21.10
		1710.7	22.48	21.03
		1754.3	22.15	21.18
	1 RB low	1732.5	22.28	21.29
1.4MHz		1710.7	22.32	21.19
1.4₩ΠΖ		1754.3	22.42	21.17
	50% RB mid	1732.5	22.37	21.17
		1710.7	22.45	21.26
		1754.3	21.38	20.15
	100% RB	1732.5	21.42	20.20
		1710.7	21.40	20.01
		1753.5	22.15	21.58
	1 RB high	1732.5	22.70	21.57
		1711.5	22.29	21.43
		1753.5	22.19	21.43
	1 RB low	1732.5	22.43	21.52
3MHz		1711.5	22.64	21.82
SIVITZ		1753.5	21.38	20.33
	50% RB mid	1732.5	21.37	20.13
		1711.5	21.28	20.02
		1753.5	21.35	20.13
	100% RB	1732.5	21.34	20.00
		1711.5	21.24	20.09
		1752.5	22.45	21.07
	1 RB high	1732.5	22.44	21.68
		1712.5	22.16	21.14
		1752.5	22.35	20.95
	1 RB low	1732.5	22.36	21.22
ENALI-		1712.5	22.39	21.36
5MHz		1752.5	21.37	20.09
	50% RB mid	1732.5	21.30	20.08
		1712.5	21.31	20.16
		1752.5	21.40	20.09
	100% RB	1732.5	21.28	20.23
		1712.5	21.17	20.15
40141-	4 DD biab	1750	22.32	21.07
10MHz	1 RB high	1732.5	22.69	21.37





		1715	22.22	21.36
	l	1750	22.15	21.02
	1 RB low	1732.5	22.41	21.44
		1715	22.24	21.92
		1750	21.34	20.44
	50% RB mid	1732.5	21.26	20.35
		1715	21.23	20.25
		1750	21.36	20.23
	100% RB	1732.5	21.30	20.28
		1715	21.04	19.96
		1747.5	22.36	21.01
	1 RB high	1732.5	22.60	21.57
		1717.5	22.66	21.25
		1747.5	22.48	21.27
	1 RB low	1732.5	22.50	21.35
45141		1717.5	22.56	21.42
15MHz		1747.5	21.49	20.33
	50% RB mid	1732.5	21.38	19.97
		1717.5	21.16	19.89
		1747.5	21.39	20.18
	100% RB	1732.5	21.39	20.05
		1717.5	21.26	20.05
		1745	22.38	21.38
	1 RB high	1732.5	22.11	21.22
		1720	22.00	20.91
		1745	22.80	21.14
	1 RB low	1732.5	22.11	21.16
20MHz		1720	22.12	20.90
ZUIVINZ		1745	21.40	20.15
	50% RB mid	1732.5	21.33	20.04
		1720	21.33	20.12
		1745	21.28	20.08
	100% RB	1732.5	21.36	20.03
		1720	21.21	20.07





LTE band 5

Bandwidth	RB size/offset	Frequency (MHz)	Power	(dBm)
Danuwiutii	RD SIZE/Oliset	Frequency (MHZ)	QPSK	16QAM
		848.3	22.49	21.27
	1 RB high	836.5	22.37	21.36
		824.7	22.40	21.31
		848.3	22.56	21.27
	1 RB low	836.5	22.27	21.34
1.4MHz		824.7	22.62	21.34
1.4₩ΠΖ		848.3	22.34	21.46
	50% RB mid	836.5	22.33	21.21
		824.7	21.47	20.35
		848.3	21.28	20.56
	100% RB	836.5	21.32	20.24
		824.7	22.69	21.46
		847.5	22.21	21.30
	1 RB high	836.5	22.42	21.51
		825.5	22.71	21.83
		847.5	22.42	21.31
	1 RB low	836.5	22.50	21.63
08411		825.5	22.50 21.55 21.28	20.81
3MHz		847.5	21.28	20.20
	50% RB mid	836.5	21.37	20.12
		825.5	21.36	20.34
		847.5	21.42	20.44
	100% RB	836.5	21.36	20.32
		825.5	21.86	21.32
		846.5	22.50	20.99
	1 RB high	836.5	22.70	20.92
		826.5	22.28	21.57
		846.5	22.52	21.42
	1 RB low	836.5	22.48	20.97
E		826.5	21.35	20.25
5MHz		846.5	21.53	20.30
	50% RB mid	836.5	21.38	20.40
		826.5	21.36	20.60
		846.5	21.55	20.39
	100% RB	836.5	21.43	20.59
		826.5	22.25	21.45
408411	4 DD ESE	844.0	22.34	21.46
10MHz	1 RB high	836.5	22.32	21.25





		829.0	22.23	21.36
		844.0	22.20	21.31
	1 RB low	836.5	22.17	21.32
		829.0	21.32	20.40
		844.0	21.50	20.61
	50% RB mid	836.5	21.20	20.41
		829.0	21.36	20.40
		844.0	21.35	20.30
	100% RB	836.5	21.22	20.24
		829.0	22.49	21.27





LTE band 7

Bandwidth	RB size/offset	Ereguency (MUz)	Power	(dBm)
Bandwidth	RB SIZE/OIISEL	Frequency (MHZ)	QPSK	16QAM
		2567.5	22.61	21.51
	1 RB high	2535	22.63	21.76
		2567.5 2535 2502.5 2567.5 2535 2502.5 2567.5 2535 2502.5 2567.5 2535 2502.5 2565 2535 2505 2565 2535 2505 2565 2535 2505 2565 2535 2505 2565 2535 2505 2565 2535 2505 2565 2535 2505 2565 2535 2505 2565 2535 2505 2565 2535 2505 2562.5 2535 2507.5 2562.5 2535 2507.5 2562.5 2535 2507.5 2562.5 2535 2507.5 2562.5	22.57	21.35
		2567.5	22.99	21.21
	1 RB low	2535	22.62	21.50
5MHz		2502.5	22.75	21.50
OWN 12		2567.5	21.63	20.47
	50% RB mid	2535	21.49	20.56
		2502.5	21.66	20.61
		2567.5	21.59	20.58
	100% RB	2535	21.57	20.63
		2502.5	QPSK 2567.5 22.61 2535 22.63 2502.5 22.57 2567.5 22.99 2535 22.62 2502.5 22.75 2567.5 21.63 2535 21.49 2502.5 21.66 2567.5 21.59 2535 21.57 2502.5 21.63 2565 22.50 2535 22.90 2505 22.29 2565 22.76 2535 22.14 2505 22.71 2565 22.71 2565 21.50 2535 21.64 2505 21.64 2505 21.64 2565 21.76 2535 21.69 2535 21.69 2562.5 22.69 2535 22.60 2562.5 21.74 2535 22.66 2507.5 22.82<	20.64
		2565	22.50	21.75
	1 RB high	2535	22.90	21.23
		2505	22.29	21.46
		2565	22.76	21.98
	1 RB low	2535	22.14	21.39
10MHz		2505	22.71	21.41
TOWN IZ		2565	21.50	20.60
	50% RB mid	2535	21.55	20.62
		2505	21.64	20.62
		2565	21.76	20.52
	100% RB	2535	21.65	20.51
		2505	22.75 21.63 21.49 21.66 21.59 21.57 21.63 22.50 22.90 22.29 22.76 22.14 22.71 21.50 21.55 21.64 21.76 21.65 21.69 22.69 22.69 22.69 22.60 21.74 22.66 22.82 21.70 21.48 21.65 21.69 21.69 21.69 21.69 21.69 21.70 21.48 21.65 21.69 21.50	20.63
		2562.5	22.69	21.36
	1 RB high	2535	22.56	21.16
		2507.5	22.60	21.54
		2562.5	21.74	21.40
	1 RB low	2535	22.66	21.36
,		2507.5	22.82	21.33
15MHz		2562.5	21.70	20.35
	50% RB mid	2535		20.57
				20.53
				20.50
	100% RB			20.61
				20.59





		2560	22.89	21.89
	1 RB high	2535	22.64	21.01
		2510	22.55	21.32
		2560	22.75	21.60
	1 RB low	2535	22.60	21.37
20MHz		2510	22.29	21.23
ZUIVITZ	50% RB mid	2560	21.55	20.41
		2535	21.63	20.44
		2510	21.79	20.63
		2560	21.62	20.53
	100% RB	2535	21.53	20.44
		2510	21.67	20.72





LTE band 12

LTE band 12	DD =:===	Fraguers: (MIII-)	Power	(dBm)
Bandwidth	RB size/offset	Frequency (MHZ)	QPSK	16QAM
	RB size/offset 1 RB high 1 RB low 50% RB mid 1 RB high 1 RB low 50% RB mid 100% RB 1 RB high 1 RB high 1 RB high 1 RB high 1 RB low	715.3	22.26	21.22
	1 RB high	707.5	22.33	21.40
		699.7	715.3 QPSK 707.5 22.33	21.35
		715.3	22.24	21.15
	1 RB low	707.5	22.37	21.66
1.4MHz		699.7	22.07	21.21
1.4₩ΠΖ		715.3	22.45	21.53
	50% RB mid	707.5	22.42	21.60
		699.7	22.42	21.04
		715.3	21.39	20.28
	100% RB	707.5	21.28	20.55
		699.7	21.31	19.85
		714.5	22.33	21.48
	1 RB high	707.5	22.85	21.67
		700.5	22.34	21.17
		714.5	22.70	21.15
	1 RB low	707.5	22.58	21.72
2041.1-		707.5 22.58 700.5 22.27 714.5 21.43	21.20	
3MHz	50% RB mid	714.5	21.43	19.88
		707.5	21.44	20.40
		700.5	21.25	20.04
		714.5	21.40	19.93
	100% RB	707.5	21.42	20.14
		700.5	21.24	20.10
		713.5	21.72	21.16
	1 RB high	707.5	22.22	21.23
		701.5	22.07	21.05
		713.5	22.07	21.04
	1 RB low	707.5	22.01	21.13
584LL		701.5	21.97	21.04
5MHz		713.5	21.28	19.99
	50% RB mid	707.5	21.26	19.99
		701.5	21.15	20.03
		713.5	21.33	20.06
	100% RB	707.5	21.35	20.11
		701.5	21.24	20.16
400411-	4 DD biab	711.0	22.10	21.05
10MHz	I KB NIGN	707.5	22.08	21.22





		704.0	22.07	21.19
		711.0	22.13	21.12
	1 RB low	707.5	22.17	21.00
		704.0	21.85	21.16
		711.0	21.23	20.21
	50% RB mid	707.5	21.06	20.01
		704.0	21.06	19.97
		711.0	21.27	20.13
	100% RB	707.5	21.17	19.98
		704.0	21.13	19.93





A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Rule Part 22.913(a) specifies "Mobile stations are limited to 2.0 watts EIRP.".

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power". and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 27.50(d) specifies "Fixed, mobile, and portable (handheld) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.".


Rule Part 27.50(h)(2) specifies "Mobile stations are limited to 2.0 watts EIRP.".

Rule Part 27.50(c) specifies "Portable stations (hand-held de-vices) are limited to 3 watts ERP.".


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360 and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with RMS detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.







In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

- 4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the amplifier and the substitution antenna.
 - The cable loss (P_{cl}) , the substitution antenna Gain (G_a) and the amplifier Gain (P_{Ag}) should be recorded after test.
 - The measurement results are obtained as described below:
 - Power (EIRP) = $P_{Mea} P_{Ag} P_{cl} G_a$
- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP 2.15.





A.1.3.3 Measurement result

Spot Check Measurement Results:

LTE Band 5_1.4MHz_QPSK

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Delevization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
824.70	-25.54	2.26	45.79	0.95	2.15	16.79	38.45	21.66	Н
836.50	-24.20	2.26	45.66	0.82	2.15	17.87	38.45	20.58	Н
848.30	-24.66	2.27	45.55	0.80	2.15	17.27	38.45	21.18	Н

LTE Band 5_3MHz_QPSK

Frequency	P _{Mea}	Pcl	P_{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
825.50	-25.53	2.26	45.79	0.94	2.15	16.79	38.45	21.66	Н
836.50	-24.08	2.26	45.66	0.82	2.15	17.99	38.45	20.46	Н
847.50	-24.64	2.27	45.56	0.81	2.15	17.31	38.45	21.14	Н

LTE Band 5_5MHz_QPSK

	Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Delevization
	(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1	826.50	-25.50	2.25	45.77	0.93	2.15	16.80	38.45	21.65	Н
	836.50	-24.27	2.26	45.66	0.82	2.15	17.80	38.45	20.65	Н
ĺ	846.50	-24.81	2.26	45.56	0.82	2.15	17.16	38.45	21.29	Н

LTE Band 5_10MHz_QPSK

	Frequency	P _{Mea}	Pcl	P_{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
	(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
Ī	829.00	-25.60	2.13	45.74	0.90	2.15	16.76	38.45	21.69	Н
Ī	836.50	-24.01	2.26	45.66	0.82	2.15	18.06	38.45	20.39	Н
ĺ	844.00	-24.53	2.26	45.59	0.82	2.15	17.47	38.45	20.98	Н





LTE Band 5_1.4MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
824.70	-26.40	2.26	45.79	0.95	2.15	15.93	38.45	22.52	Н
836.50	-25.04	2.26	45.66	0.82	2.15	17.03	38.45	21.42	Н
848.30	-26.02	2.27	45.55	0.80	2.15	15.91	38.45	22.54	Н

LTE Band 5_3MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
825.50	-26.40	2.26	45.79	0.94	2.15	15.92	38.45	22.53	Н
836.50	-24.99	2.26	45.66	0.82	2.15	17.08	38.45	21.37	Н
847.50	-25.99	2.27	45.56	0.81	2.15	15.96	38.45	22.49	Н

LTE Band 5_5MHz_16QAM

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
826.50	-26.37	2.25	45.77	0.93	2.15	15.93	38.45	22.52	Н
836.50	-25.11	2.26	45.66	0.82	2.15	16.96	38.45	21.49	Н
846.50	-26.08	2.26	45.56	0.82	2.15	15.89	38.45	22.56	Н

LTE Band 5_10MHz_16QAM

Ī	Frequency	P _{Mea}	Pcl	P_{Aq}	Ga	Correction	ERP	Limit	Margin	
	(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
ļ	829.00	-26.45	2.13	45.74	0.90	2.15	15.91	38.45	22.54	Н
	836.50	-24.95	2.26	45.66	0.82	2.15	17.12	38.45	21.33	Н
Î	844.00	-25.92	2.26	45.59	0.82	2.15	16.08	38.45	22.37	Н





LTE Band 7- EIRP

Limits: ≤33 dBm (2W)

LTE Band 7_5MHz_QPSK

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Polarization
2502.50	-23.79	3.58	45.68	6.10	24.41	33.00	8.59	Н
2535.00	-23.44	3.63	44.82	6.16	23.91	33.00	9.09	Н
2567.50	-25.39	3.65	44.92	6.22	22.10	33.00	10.90	Н

LTE Band 7_10MHz_QPSK

Frequency	P _{Mea}	Pcl	P_{Ag}	Ga	EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Polarization
2505.00	-23.90	3.59	45.64	6.11	24.26	33.00	8.74	Н
2535.00	-23.35	3.63	44.82	6.16	24.00	33.00	9.00	Н
2565.00	-24.83	3.65	44.97	6.22	22.71	33.00	10.29	Н

LTE Band 7_15MHz_QPSK

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	EIRP	Limit	Margin	Delevination
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Polarization
2507.50	-23.13	3.59	44.92	6.11	24.31	33.00	8.69	Н
2535.00	-23.29	3.63	44.82	6.16	24.06	33.00	8.94	Н
2562.50	-25.64	3.65	45.67	6.21	22.59	33.00	10.41	Н

LTE Band 7_20 MHz_QPSK

Frequency	P _{Mea}	Pcl	P_{Ag}	Ga	EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Folanzation
2510.00	-24.71	3.58	45.36	6.12	23.19	33.00	9.81	Н
2535.00	-23.99	3.63	44.82	6.16	23.36	33.00	9.64	Н
2560.00	-25.53	3.64	45.98	6.21	23.02	33.00	9.98	Н





LTE Band 7_5MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Polarization
2502.50	-24.51	3.58	45.68	6.10	23.69	33.00	9.31	Н
2535.00	-24.35	3.63	44.82	6.16	23.00	33.00	10.00	Н
2567.50	-25.87	3.65	44.92	6.22	21.62	33.00	11.38	Н

LTE Band 7_10MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	EIRP	Limit	Margin	Delevization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Polarization
2505.00	-24.59	3.59	45.64	6.11	23.57	33.00	9.43	Н
2535.00	-24.24	3.63	44.82	6.16	23.11	33.00	9.89	Н
2565.00	-25.49	3.65	44.97	6.22	22.05	33.00	10.95	Н

LTE Band 7_15MHz_16QAM

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Polarization
2507.50	-23.82	3.59	44.92	6.11	23.62	33.00	9.38	Н
2535.00	-24.21	3.63	44.82	6.16	23.14	33.00	9.86	Н
2562.50	-26.35	3.65	45.67	6.21	21.88	33.00	11.12	Н

LTE Band 7_20 MHz_16QAM

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
2510.00	-25.18	3.58	45.36	6.12	22.72	33.00	10.28	Н
2535.00	-24.57	3.63	44.82	6.16	22.78	33.00	10.22	Н
2560.00	-26.58	3.64	45.98	6.21	21.97	33.00	11.03	Н





LTE Band 12 - ERP

Limits: ≤34.77dBm (3W)

LTE Band 12_1.4MHz_QPSK

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
699.70	-26.90	1.90	44.66	0.77	2.15	14.48	34.77	20.29	Н
707.50	-26.76	1.91	44.94	0.62	2.15	14.74	34.77	20.03	Н
715.30	-27.11	1.92	45.26	0.50	2.15	14.58	34.77	20.19	Н

LTE Band 12_3MHz_QPSK

	Frequency	P _{Mea}	Pcl	P_{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
	(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
	700.50	-26.84	1.90	44.68	0.76	2.15	14.55	34.77	20.22	Н
	707.50	-26.78	1.91	44.94	0.62	2.15	14.72	34.77	20.05	Н
	714.50	-26.95	1.92	45.26	0.50	2.15	14.74	34.77	20.03	Н

LTE Band 12_5MHz_QPSK

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Delevization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
701.50	-26.72	1.90	44.81	0.74	2.15	14.78	34.77	19.99	Н
707.50	-26.60	1.91	44.94	0.62	2.15	14.90	34.77	19.87	Н
713.50	-27.07	1.92	45.22	0.50	2.15	14.58	34.77	20.19	Н

LTE Band 12_10MHz_QPSK

Frequency	P _{Mea}	Pcl	P_{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Folalization
704.00	-27.50	1.91	44.93	0.70	2.15	14.07	34.77	20.70	Н
707.50	-27.49	1.91	44.94	0.62	2.15	14.01	34.77	20.76	V
711.00	-27.33	1.92	45.19	0.53	2.15	14.32	34.77	20.45	V





LTE Band 12_1.4MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
699.70	-27.88	1.90	44.66	0.77	2.15	13.50	34.77	21.27	Н
707.50	-27.72	1.91	44.94	0.62	2.15	13.78	34.77	20.99	Н
715.30	-27.92	1.92	45.26	0.50	2.15	13.77	34.77	21.00	Н

LTE Band 12_3MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Delevization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
700.50	-27.83	1.90	44.68	0.76	2.15	13.56	34.77	21.21	Н
707.50	-27.79	1.91	44.94	0.62	2.15	13.71	34.77	21.06	Н
714.50	-27.87	1.92	45.26	0.50	2.15	13.82	34.77	20.95	Н

LTE Band 12_5MHz_16QAM

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
701.50	-27.66	1.90	44.81	0.74	2.15	13.84	34.77	20.93	Н
707.50	-27.71	1.91	44.94	0.62	2.15	13.79	34.77	20.98	Н
713.50	-27.92	1.92	45.22	0.50	2.15	13.73	34.77	21.04	Н

LTE Band 12_10MHz_16QAM

Frequency	P _{Mea}	Pcl	P_{Ag}	Ga	Correction	ERP	Limit	Margin	Dolovinstian
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
704.00	-28.33	1.91	44.93	0.70	2.15	13.24	34.77	21.53	Н
707.50	-28.38	1.91	44.94	0.62	2.15	13.12	34.77	21.65	V
711.00	-28.04	1.92	45.19	0.53	2.15	13.61	34.77	21.16	V





Reference Measurement Results from basic model:

LTE Band 2- EIRP

Limits: ≤33dBm (2W)

LTE Band 2_1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.70	-22.11	2.92	43.75	4.87	23.59	33.00	9.41	Н
1880.00	-20.45	2.85	43.75	4.82	25.27	33.00	7.73	Н
1909.30	-20.83	2.87	43.77	4.76	24.83	33.00	8.17	Н

LTE Band 2_3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.50	-22.49	2.87	43.75	4.87	23.26	33.00	9.74	Н
1880.00	-20.69	2.85	43.75	4.82	25.03	33.00	7.97	Н
1908.50	-21.00	2.89	43.78	4.76	24.65	33.00	8.35	Н

LTE Band 2_5MHz_QPSK

	Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
Ī	1852.50	-22.45	2.87	43.75	4.87	23.30	33.00	9.70	Н
Ī	1880.00	-20.74	2.85	43.75	4.82	24.98	33.00	8.02	Н
Ī	1907.50	-21.10	2.84	43.77	4.77	24.60	33.00	8.40	Н

LTE Band 2_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.00	-22.31	2.88	43.74	4.86	23.41	33.00	9.59	Н
1880.00	-20.76	2.85	43.75	4.82	24.96	33.00	8.04	Н
1905.00	-20.39	2.87	43.77	4.77	25.28	33.00	7.72	Н

LTE Band 2_15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.50	-22.40	2.87	43.75	4.86	23.34	33.00	9.66	Н
1880.00	-20.83	2.85	43.75	4.82	24.89	33.00	8.11	Н
1902.50	-20.58	2.86	43.77	4.78	25.11	33.00	7.89	Н

LTE Band 2_20 MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.00	-22.05	2.86	43.75	4.85	23.69	33.00	9.31	Н
1880.00	-20.92	2.85	43.75	4.82	24.80	33.00	8.20	Н
1900.00	-20.27	2.87	43.77	4.78	25.41	33.00	7.59	Н





LTE Band 2_1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.70	-22.92	2.92	43.75	4.87	22.78	33.00	10.22	Н
1880.00	-21.48	2.85	43.75	4.82	24.24	33.00	8.76	Н
1909.30	-21.71	2.87	43.77	4.76	23.95	33.00	9.05	Н

LTE Band 2_3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.50	-23.01	2.87	43.75	4.87	22.74	33.00	10.26	Н
1880.00	-21.77	2.85	43.75	4.82	23.95	33.00	9.05	Н
1908.50	-21.68	2.89	43.78	4.76	23.97	33.00	9.03	Н

LTE Band 2_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.50	-22.92	2.87	43.75	4.87	22.83	33.00	10.17	Н
1880.00	-21.94	2.85	43.75	4.82	23.78	33.00	9.22	Н
1907.50	-21.97	2.84	43.77	4.77	23.73	33.00	9.27	Н

LTE Band 2_10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.00	-23.20	2.88	43.74	4.86	22.52	33.00	10.48	Н
1880.00	-21.58	2.85	43.75	4.82	24.14	33.00	8.86	Н
1905.00	-21.60	2.87	43.77	4.77	24.07	33.00	8.93	Н

LTE Band 2_15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.50	-23.30	2.87	43.75	4.86	22.44	33.00	10.56	Н
1880.00	-22.11	2.85	43.75	4.82	23.61	33.00	9.39	Н
1902.50	-21.51	2.86	43.77	4.78	24.18	33.00	8.82	Н

LTE Band 2_20 MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.00	-23.38	2.86	43.75	4.85	22.36	33.00	10.64	Н
1880.00	-21.38	2.85	43.75	4.82	24.34	33.00	8.66	Н
1900.00	-20.95	2.87	43.77	4.78	24.73	33.00	8.27	Н





LTE Band 4- EIRP

Limits: ≤30dBm (1W)

LTE Band 4_1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.70	-25.87	3.17	44.10	5.12	20.18	30.00	9.82	Н
1732.50	-25.10	3.33	44.14	5.08	20.79	30.00	9.21	Н
1754.30	-23.16	3.76	44.14	5.04	22.26	30.00	7.74	Н

LTE Band 4_3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.50	-25.77	3.40	44.10	5.12	20.05	30.00	9.95	Н
1732.50	-25.62	3.33	44.14	5.08	20.27	30.00	9.73	Н
1753.50	-23.49	3.80	44.13	5.04	21.88	30.00	8.12	Н

LTE Band 4_5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.50	-25.56	3.66	44.10	5.12	20.00	30.00	10.00	Н
1732.50	-25.80	3.33	44.14	5.08	20.09	30.00	9.91	Н
1752.50	-23.67	3.82	44.14	5.05	21.70	30.00	8.30	Η

LTE Band 4_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.00	-25.46	3.56	44.10	5.11	20.19	30.00	9.81	Н
1732.50	-25.45	3.33	44.14	5.08	20.44	30.00	9.56	Н
1750.00	-24.15	3.00	44.15	5.05	22.05	30.00	7.95	Н

LTE Band 4_15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.50	-26.03	3.47	44.11	5.11	19.72	30.00	10.28	Н
1732.50	-25.70	3.33	44.14	5.08	20.19	30.00	9.81	Н
1747.50	-24.73	3.34	44.15	5.05	21.13	30.00	8.87	Н

LTE Band 4_20MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.00	-25.93	3.37	44.11	5.10	19.91	30.00	10.09	Н
1732.50	-25.35	3.33	44.14	5.08	20.54	30.00	9.46	Н
1745.00	-23.99	3.68	44.16	5.06	21.55	30.00	8.45	Н





LTE Band 4_1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.70	-26.68	3.17	44.10	5.12	19.37	30.00	10.63	Н
1732.50	-25.91	3.33	44.14	5.08	19.98	30.00	10.02	Н
1754.30	-24.21	3.76	44.14	5.04	21.21	30.00	8.79	Н

LTE Band 4_3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.50	-26.41	3.40	44.10	5.12	19.41	30.00	10.59	Н
1732.50	-26.50	3.33	44.14	5.08	19.39	30.00	10.61	Н
1753.50	-24.45	3.80	44.13	5.04	20.92	30.00	9.08	Н

LTE Band 4_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.50	-26.06	3.66	44.10	5.12	19.50	30.00	10.50	Н
1732.50	-26.76	3.33	44.14	5.08	19.13	30.00	10.87	Н
1752.50	-24.47	3.82	44.14	5.05	20.90	30.00	9.10	Н

LTE Band 4_10MHz_16QAM

Frequenc	y (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715	.00	-26.20	3.56	44.10	5.11	19.45	30.00	10.55	Н
1732	.50	-26.34	3.33	44.14	5.08	19.55	30.00	10.45	Н
1750	.00	-25.32	3.00	44.15	5.05	20.88	30.00	9.12	Н

LTE Band 4_15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.50	-26.58	3.47	44.11	5.11	19.17	30.00	10.83	Н
1732.50	-26.49	3.33	44.14	5.08	19.40	30.00	10.60	Н
1747.50	-25.32	3.34	44.15	5.05	20.54	30.00	9.46	Н

LTE Band 4_20MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.00	-26.98	3.37	44.11	5.10	18.86	30.00	11.14	Н
1732.50	-26.22	3.33	44.14	5.08	19.67	30.00	10.33	Н
1745.00	-24.78	3.68	44.16	5.06	20.76	30.00	9.24	Н





LTE Band 5- ERP

Limits: ≤38.45dBm (7W)

LTE Band 5_1.4MHz_QPSK

	Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
	(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Folalization
Ī	824.70	-23.81	2.26	45.79	0.95	2.15	18.52	38.45	19.93	Н
Ī	836.50	-22.44	2.26	45.66	0.82	2.15	19.63	38.45	18.82	Н
Ī	848.30	-22.10	2.27	45.55	0.80	2.15	19.83	38.45	18.62	Н

LTE Band 5_3MHz_QPSK

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Delevization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
825.50	-24.05	2.26	45.79	0.94	2.15	18.27	38.45	20.18	Н
836.50	-22.98	2.26	45.66	0.82	2.15	19.09	38.45	19.36	Н
847.50	-22.23	2.27	45.56	0.81	2.15	19.72	38.45	18.73	Н

LTE Band 5_5MHz_QPSK

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Delevization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
826.50	-24.39	2.25	45.77	0.93	2.15	17.91	38.45	20.54	Н
836.50	-22.97	2.26	45.66	0.82	2.15	19.10	38.45	19.35	Н
846.50	-22.02	2.26	45.56	0.82	2.15	19.95	38.45	18.50	Н

LTE Band 5_10MHz_QPSK

	Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
	(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Folalization
	829.00	-23.68	2.13	45.74	0.90	2.15	18.68	38.45	19.77	Н
Ī	836.50	-22.95	2.26	45.66	0.82	2.15	19.12	38.45	19.33	Н
	844.00	-22.52	2.26	45.59	0.82	2.15	19.48	38.45	18.97	Н





LTE Band 5_1.4MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
824.70	-24.67	2.26	45.79	0.95	2.15	17.66	38.45	20.79	Н
836.50	-23.66	2.26	45.66	0.82	2.15	18.41	38.45	20.04	Н
848.30	-22.74	2.27	45.55	0.80	2.15	19.19	38.45	19.26	Н

LTE Band 5_3MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Delevization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
825.50	-25.12	2.26	45.79	0.94	2.15	17.20	38.45	21.25	Н
836.50	-23.81	2.26	45.66	0.82	2.15	18.26	38.45	20.19	Н
847.50	-22.89	2.27	45.56	0.81	2.15	19.06	38.45	19.39	Н

LTE Band 5_5MHz_16QAM

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
826.50	-24.62	2.25	45.77	0.93	2.15	17.68	38.45	20.77	Н
836.50	-23.56	2.26	45.66	0.82	2.15	18.51	38.45	19.94	Н
846.50	-23.24	2.26	45.56	0.82	2.15	18.73	38.45	19.72	Н

LTE Band 5_10MHz_16QAM

Ī	_	_	_	_		0 "	555			
	Frequency	Рмеа	Pcl	P_{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
	(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Folalization
Ī	829.00	-24.86	2.13	45.74	0.90	2.15	17.50	38.45	20.95	Н
Ī	836.50	-23.69	2.26	45.66	0.82	2.15	18.38	38.45	20.07	Н
Ī	844.00	-23.04	2.26	45.59	0.82	2.15	18.96	38.45	19.49	Н





LTE Band 7- EIRP

Limits: ≤33 dBm (2W)

LTE Band 7_5MHz_QPSK

Frequency	P _{Mea}	Pcl	P_{Ag}	Ga	EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Folanzation
2502.50	-25.57	3.58	45.68	6.10	22.63	33.00	10.37	Н
2535.00	-23.14	3.63	44.82	6.16	24.21	33.00	8.79	Н
2567.50	-24.91	3.65	44.92	6.22	22.58	33.00	10.42	Н

LTE Band 7_10MHz_QPSK

Frequency	P _{Mea}	Pcl	P_{Ag}	Ga	EIRP	Limit	Margin	Dolorization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Polarization
2505.00	-25.21	3.59	45.64	6.11	22.95	33.00	10.05	Н
2535.00	-23.08	3.63	44.82	6.16	24.27	33.00	8.73	Н
2565.00	-25.14	3.65	44.97	6.22	22.40	33.00	10.60	Н

LTE Band 7_15MHz_QPSK

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	EIRP	Limit	Margin	Delevization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Polarization
2507.50	-24.86	3.59	44.92	6.11	22.58	33.00	10.42	Н
2535.00	-23.03	3.63	44.82	6.16	24.32	33.00	8.68	Н
2562.50	-25.60	3.65	45.67	6.21	22.63	33.00	10.37	Н

LTE Band 7_20 MHz_QPSK

Frequency	P _{Mea}	Pcl	P_{Ag}	Ga	EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Folanzation
2510.00	-25.00	3.58	45.36	6.12	22.90	33.00	10.10	Н
2535.00	-23.22	3.63	44.82	6.16	24.13	33.00	8.87	Н
2560.00	-25.63	3.64	45.98	6.21	22.92	33.00	10.08	Н





LTE Band 7_5MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Polarization
2502.50	-26.03	3.58	45.68	6.10	22.17	33.00	10.83	Н
2535.00	-23.93	3.63	44.82	6.16	23.42	33.00	9.58	Н
2567.50	-25.68	3.65	44.92	6.22	21.81	33.00	11.19	Н

LTE Band 7_10MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	EIRP	Limit	Margin	Delevization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Polarization
2505.00	-26.19	3.59	45.64	6.11	21.97	33.00	11.03	Н
2535.00	-23.89	3.63	44.82	6.16	23.46	33.00	9.54	Н
2565.00	-25.91	3.65	44.97	6.22	21.63	33.00	11.37	Н

LTE Band 7_15MHz_16QAM

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	Polarization
2507.50	-25.55	3.59	44.92	6.11	21.89	33.00	11.11	Н
2535.00	-23.96	3.63	44.82	6.16	23.39	33.00	9.61	Н
2562.50	-26.39	3.65	45.67	6.21	21.84	33.00	11.16	Н

LTE Band 7_20 MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	Ga (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2510.00	-26.03	3.58	45.36	6.12	21.87	33.00	11.13	Н
2535.00	-23.70	3.63	44.82	6.16	23.65	33.00	9.35	Н
2560.00	-26.35	3.64	45.98	6.21	22.20	33.00	10.80	Н





LTE Band 12 - ERP

Limits: ≤34.77dBm (3W)

LTE Band 12_1.4MHz_QPSK

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Folalization
699.70	-22.48	1.90	44.66	0.77	2.15	18.90	34.77	15.87	Н
707.50	-22.05	1.91	44.94	0.62	2.15	19.45	34.77	15.32	Н
715.30	-22.20	1.92	45.26	0.50	2.15	19.49	34.77	15.28	Н

LTE Band 12_3MHz_QPSK

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
700.50	-22.74	1.90	44.68	0.76	2.15	18.65	34.77	16.12	Н
707.50	-22.48	1.91	44.94	0.62	2.15	19.02	34.77	15.75	Н
714.50	-22.45	1.92	45.26	0.50	2.15	19.24	34.77	15.53	Н

LTE Band 12_5MHz_QPSK

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Delevization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
701.50	-22.40	1.90	44.81	0.74	2.15	19.10	34.77	15.67	Н
707.50	-22.51	1.91	44.94	0.62	2.15	18.99	34.77	15.78	Н
713.50	-22.46	1.92	45.22	0.50	2.15	19.19	34.77	15.58	Н

LTE Band 12_10MHz_QPSK

Frequency	P _{Mea}	Pcl	P_{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Folalization
704.00	-22.48	1.91	44.93	0.70	2.15	19.09	34.77	15.68	Н
707.50	-22.29	1.91	44.94	0.62	2.15	19.21	34.77	15.56	Н
711.00	-22.37	1.92	45.19	0.53	2.15	19.28	34.77	15.49	Н





LTE Band 12_1.4MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
699.70	-23.09	1.90	44.66	0.77	2.15	18.29	34.77	16.48	Н
707.50	-22.95	1.91	44.94	0.62	2.15	18.55	34.77	16.22	Н
715.30	-23.43	1.92	45.26	0.50	2.15	18.26	34.77	16.51	Н

LTE Band 12_3MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
700.50	-23.16	1.90	44.68	0.76	2.15	18.23	34.77	16.54	Н
707.50	-23.30	1.91	44.94	0.62	2.15	18.20	34.77	16.57	Н
714.50	-23.26	1.92	45.26	0.50	2.15	18.43	34.77	16.34	Н

LTE Band 12_5MHz_16QAM

Frequency	P _{Mea}	P _{cl}	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
701.50	-22.96	1.90	44.81	0.74	2.15	18.54	34.77	16.23	Н
707.50	-23.43	1.91	44.94	0.62	2.15	18.07	34.77	16.70	Н
713.50	-23.22	1.92	45.22	0.50	2.15	18.43	34.77	16.34	Н

LTE Band 12_10MHz_16QAM

Frequency	P _{Mea}	Pcl	P _{Ag}	Ga	Correction	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	(dB)	(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polatization
704.00	-23.10	1.91	44.93	0.70	2.15	18.47	34.77	16.30	Н
707.50	-23.31	1.91	44.94	0.62	2.15	18.19	34.77	16.58	Н
711.00	-23.35	1.92	45.19	0.53	2.15	18.30	34.77	16.47	Н

Frequency: 688.00MHz

 $Peak \; EIRP(dBm) = P_{Mea}(-27.55dBm) - G_a \; (-0.77dBi) - P_{Ag} \; (-44.72 \; dB) - P_{cl} \; (1.89dB) - 2.15 = 3.91dBm$

Note: Expanded measurement uncertainty is U = 2.84 dB, k = 2.





A.2 EMISSION LIMIT


A.2.1 Measurement Method

The measurements procedures in TIA-603E-2016 are used. This measurement is carried out in fully-anechoic chamber FAC-3.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier. The resolution bandwidth is set 1MHz. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE Bands 2,4,5,7,12.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5-meter-high non-conductive stand at a 3-meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360 and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere





with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

An amplifier should be connected in for the test.

The Path loss (Ppl) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

Power (EIRP)=P_{Mea}+ P_{pl} + G_a

- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit: dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dB.

A.2.2 Measurement Limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(c) states for operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 65 +





10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the LTE Bands 2,4,5,7,12. It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the LTE Bands 2,4,5,7,12 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this. The evaluated frequency range is from 30MHz to 26GHz.





Spot Check Measurement Results:

LTE Band 5, 1.4MHz, QPSK, Channel 20407

Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1649.01	-58.34	3.56	5.23	2.15	-58.82	-13.00	45.82	Н
2474.00	-37.14	4.60	6.02	2.15	-37.87	-13.00	24.87	Н
3303.02	-55.44	5.29	7.73	2.15	-55.15	-13.00	42.15	V
4125.02	-43.51	6.04	9.03	2.15	-42.67	-13.00	29.67	Н
4951.01	-55.10	6.69	9.85	2.15	-54.09	-13.00	41.09	Н
5776.01	-51.24	7.23	10.54	2.15	-50.08	-13.00	37.08	Н

LTE Band 5, 1.4MHz, QPSK, Channel 20525

	1	1		1	1		I	
Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1673.01	-58.31	3.58	5.19	2.15	-58.85	-13.00	45.85	Н
2510.00	-38.12	4.63	6.12	2.15	-38.78	-13.00	25.78	Н
3332.02	-54.63	5.30	7.80	2.15	-54.28	-13.00	41.28	Н
4184.02	-44.60	6.17	9.08	2.15	-43.84	-13.00	30.84	Н
5021.01	-55.07	6.57	9.93	2.15	-53.86	-13.00	40.86	V
5861.01	-53.44	7.27	10.53	2.15	-52.33	-13.00	39.33	V

LTE Band 5, 1.4MHz, QPSK, Channel 20643

Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1697.01	-59.43	3.60	5.15	2.15	-60.03	-13.00	47.03	Н
2545.00	-49.93	4.66	6.18	2.15	-50.56	-13.00	37.56	V
3379.02	-55.43	5.34	7.91	2.15	-55.01	-13.00	42.01	V
4249.02	-56.07	6.24	9.15	2.15	-55.31	-13.00	42.31	Н
5101.01	-55.26	6.78	10.04	2.15	-54.15	-13.00	41.15	Н
5953.01	-52.83	7.47	10.51	2.15	-51.94	-13.00	38.94	V





LTE Band 7, 5 MHz, QPSK, Channel 20775

Frequency	P _{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
4986.02	-57.15	6.63	9.89	-53.89	-25.00	28.89	Н
7510.01	-38.66	8.35	12.21	-34.80	-25.00	9.80	Н
10011.01	-48.39	9.21	12.90	-44.70	-25.00	19.70	Н
12507.01	-49.96	10.19	13.20	-46.95	-25.00	21.95	Н
15034.00	-45.68	11.26	13.98	-42.96	-25.00	17.96	V
17508.00	-43.11	12.75	14.91	-40.95	-25.00	15.95	Н

LTE Band 7, 5 MHz, QPSK, Channel 21100

Frequency	P _{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Delerization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
5071.02	-55.95	6.69	10.00	-52.64	-25.00	27.64	Н
7611.01	-41.31	8.02	12.29	-37.04	-25.00	12.04	Н
10141.01	-46.00	9.40	12.96	-42.44	-25.00	17.44	Н
12661.01	-49.29	10.36	13.30	-46.35	-25.00	21.35	Н
15207.00	-45.16	11.39	13.88	-42.67	-25.00	17.67	V
17757.00	-43.74	12.50	15.26	-40.98	-25.00	15.98	Н

LTE Band 7, 5 MHz, QPSK, Channel 21425

Frequency	P _{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
5071.02	-55.95	6.69	10.00	-52.64	-25.00	27.64	Н
7611.01	-41.31	8.02	12.29	-37.04	-25.00	12.04	Н
10141.01	-46.00	9.40	12.96	-42.44	-25.00	17.44	Н
12661.01	-49.29	10.36	13.30	-46.35	-25.00	21.35	Н
15207.00	-45.16	11.39	13.88	-42.67	-25.00	17.67	V
17757.00	-43.74	12.50	15.26	-40.98	-25.00	15.98	Н





LTE Band 12, 1.4MHz, QPSK, Channel 23017

Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1400.01	-58.29	3.24	4.98	2.15	-58.70	-13.00	45.70	Н
2100.00	-48.24	4.19	4.90	2.15	-49.68	-13.00	36.68	V
2811.00	-51.97	4.93	6.66	2.15	-52.39	-13.00	39.39	V
3508.02	-55.57	5.53	8.21	2.15	-55.04	-13.00	42.04	Н
4188.02	-55.47	6.18	9.09	2.15	-54.71	-13.00	41.71	V
4891.01	-55.02	6.73	9.79	2.15	-54.11	-13.00	41.11	Н

LTE Band 12, 1.4MHz, QPSK, Channel 23095

Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1415.01	-57.85	3.25	5.06	2.15	-58.19	-13.00	45.19	Н
2122.00	-54.66	4.21	4.97	2.15	-56.05	-13.00	43.05	V
2833.00	-50.47	4.95	6.70	2.15	-50.87	-13.00	37.87	V
3537.02	-55.69	5.69	8.25	2.15	-55.28	-13.00	42.28	Н
4244.02	-55.38	6.25	9.14	2.15	-54.64	-13.00	41.64	Н
4953.01	-55.33	6.68	9.85	2.15	-54.31	-13.00	41.31	Н

LTE Band 12, 1.4MHz, QPSK, Channel 23173

Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Delerization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1431.01	-60.37	3.28	5.14	2.15	-60.66	-13.00	47.66	Н
2132.00	-53.83	4.22	5.00	2.15	-55.20	-13.00	42.20	V
2856.00	-51.76	4.96	6.74	2.15	-52.13	-13.00	39.13	V
3571.02	-55.44	6.04	8.30	2.15	-55.33	-13.00	42.33	V
4298.02	-54.01	6.20	9.20	2.15	-53.16	-13.00	40.16	Н
5009.01	-55.22	6.59	9.91	2.15	-54.05	-13.00	41.05	Н





Reference Measurement Results from basic model:

LTE Band 2, 1.4MHz, QPSK, Channel 18607

Frequency	P _{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
3701.02	-54.90	6.42	8.48	-52.84	-13.00	39.84	V
5554.02	-50.82	7.19	10.59	-47.42	-13.00	34.42	Н
7404.01	-42.93	8.13	12.08	-38.98	-13.00	25.98	Н
9261.01	-54.52	9.06	13.26	-50.32	-13.00	37.32	V
11154.01	-51.71	9.60	13.17	-48.14	-13.00	35.14	V
12955.01	-49.84	10.48	13.47	-46.85	-13.00	33.85	Н

LTE Band 2, 1.4MHz, QPSK, Channel 18900

Frequency	P _{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Delegization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
3760.02	-54.33	6.26	8.56	-52.03	-13.00	39.03	V
5641.02	-49.34	7.27	10.57	-46.04	-13.00	33.04	V
7523.01	-41.56	8.30	12.22	-37.64	-13.00	24.64	Н
9360.01	-54.88	9.08	13.32	-50.64	-13.00	37.64	Н
11238.01	-51.45	9.63	13.15	-47.93	-13.00	34.93	Н
13197.01	-48.11	10.51	13.78	-44.84	-13.00	31.84	Н

LTE Band 2, 1.4MHz, QPSK, Channel 19193

Frequency	P_{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
3819.02	-56.21	6.08	8.65	-53.64	-13.00	40.64	Н
5731.02	-26.17	7.29	10.55	-22.91	-13.00	9.91	Н
7639.01	-41.02	8.15	12.31	-36.86	-13.00	23.86	Н
9553.01	-45.87	9.35	13.35	-41.87	-13.00	28.87	Н
11492.01	-50.83	9.83	13.10	-47.56	-13.00	34.56	V
13385.01	-48.23	10.57	14.04	-44.76	-13.00	31.76	V





LTE Band 4, 1.4MHz QPSK, Channel 19957

Frequency	P _{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
3422.02	-54.37	5.38	8.01	-51.74	-13.00	38.74	Н
5134.02	-22.88	6.86	10.09	-19.65	-13.00	6.65	Н
6844.01	-47.92	7.83	11.41	-44.34	-13.00	31.34	Н
8554.01	-44.69	8.58	13.01	-40.26	-13.00	27.26	Н
10244.01	-52.28	9.45	13.00	-48.73	-13.00	35.73	V
12001.01	-49.69	10.05	13.00	-46.74	-13.00	33.74	V

LTE Band 4, 1.4MHz, QPSK, Channel 20175

Frequency	P _{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Delegization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
3465.02	-55.60	5.46	8.12	-52.94	-13.00	39.94	Н
5201.02	-29.66	6.96	10.18	-26.44	-13.00	13.44	Н
6933.01	-44.95	7.78	11.52	-41.21	-13.00	28.21	Н
8663.01	-44.64	8.41	13.03	-40.02	-13.00	27.02	Н
10382.01	-50.86	9.77	13.05	-47.58	-13.00	34.58	V
12159.01	-49.23	10.18	13.06	-46.35	-13.00	33.35	Н

LTE Band 4, 1.4MHz, QPSK, Channel 20393

Frequency	P _{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
3509.02	-56.74	5.54	8.21	-54.07	-13.00	41.07	V
5265.02	-47.03	6.99	10.27	-43.75	-13.00	30.75	Н
7020.01	-43.92	8.27	11.62	-40.57	-13.00	27.57	Н
8772.01	-46.15	8.58	13.05	-41.68	-13.00	28.68	Н
10534.01	-51.44	9.53	13.11	-47.86	-13.00	34.86	V
12318.01	-49.84	10.08	13.13	-46.79	-13.00	33.79	Н





LTE Band 5, 1.4MHz, QPSK, Channel 20407

Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1650.01	-58.05	3.57	5.23	2.15	-58.54	-13.00	45.54	Н
2474.00	-33.97	4.60	6.02	2.15	-34.70	-13.00	21.70	Н
3301.02	-54.84	5.29	7.72	2.15	-54.56	-13.00	41.56	Н
4125.02	-40.94	6.04	9.03	2.15	-40.10	-13.00	27.10	Н
4938.01	-54.78	6.71	9.84	2.15	-53.80	-13.00	40.80	Н
5777.01	-51.15	7.22	10.54	2.15	-49.98	-13.00	36.98	Н

LTE Band 5, 1.4MHz, QPSK, Channel 20525

Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1674.01	-58.77	3.58	5.19	2.15	-59.31	-13.00	46.31	Н
2510.00	-39.08	4.63	6.12	2.15	-39.74	-13.00	26.74	Н
3358.02	-54.84	5.33	7.86	2.15	-54.46	-13.00	41.46	V
4187.02	-47.04	6.18	9.09	2.15	-46.28	-13.00	33.28	Н
5014.01	-55.07	6.58	9.92	2.15	-53.88	-13.00	40.88	Н
5859.01	-53.12	7.26	10.53	2.15	-52.00	-13.00	39.00	Н

LTE Band 5, 1.4MHz, QPSK, Channel 20643

Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1687.01	-59.18	3.59	5.16	2.15	-59.76	-13.00	46.76	V
2545.00	-43.60	4.66	6.18	2.15	-44.23	-13.00	31.23	Н
3388.02	-55.67	5.35	7.93	2.15	-55.24	-13.00	42.24	V
4254.02	-54.32	6.24	9.15	2.15	-53.56	-13.00	40.56	Н
5097.01	-55.04	6.76	10.04	2.15	-53.91	-13.00	40.91	Н
5948.01	-52.41	7.47	10.51	2.15	-51.52	-13.00	38.52	Н





LTE Band 7, 5 MHz, QPSK, Channel 20775

Frequency	P _{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
3701.02	-52.44	6.42	8.48	-50.38	-13.00	37.38	V
5552.02	-39.90	7.18	10.59	-36.49	-13.00	23.49	Н
7404.01	-52.51	8.13	12.08	-48.56	-13.00	35.56	Н
9252.01	-51.44	9.04	13.25	-47.23	-13.00	34.23	V
11098.01	-51.48	9.84	13.18	-48.14	-13.00	35.14	Н
12950.01	-50.03	10.49	13.47	-47.05	-13.00	34.05	V

LTE Band 7, 5 MHz, QPSK, Channel 21100

Frequency	P _{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
3760.02	-50.30	6.26	8.56	-48.00	-13.00	35.00	V
5641.02	-39.63	7.27	10.57	-36.33	-13.00	23.33	Н
7522.01	-50.05	8.30	12.22	-46.13	-13.00	33.13	Н
9401.01	-51.41	9.04	13.34	-47.11	-13.00	34.11	Н
11272.01	-50.80	9.83	13.15	-47.48	-13.00	34.48	Н
13146.01	-48.02	10.73	13.70	-45.05	-13.00	32.05	V

LTE Band 7, 5 MHz, QPSK, Channel 21425

Frequency	P _{Mea}	Path	Antenna	Peak EIRP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dBm)	(dBm)	(dB)	Polarization
3820.02	-57.37	6.08	8.65	-54.80	-13.00	41.80	Н
5733.02	-37.98	7.29	10.55	-34.72	-13.00	21.72	Н
7646.01	-52.36	8.18	12.32	-48.22	-13.00	35.22	Н
9553.01	-54.69	9.35	13.35	-50.69	-13.00	37.69	V
11454.01	-51.24	9.93	13.11	-48.06	-13.00	35.06	V
13377.01	-48.72	10.57	14.03	-45.26	-13.00	32.26	Н





LTE Band 12, 1.4MHz, QPSK, Channel 23017

Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1400.01	-56.97	3.24	4.98	2.15	-57.38	-13.00	44.38	Н
2099.00	-40.88	4.19	4.90	2.15	-42.32	-13.00	29.32	V
2796.00	-52.00	4.91	6.63	2.15	-52.43	-13.00	39.43	Н
3493.02	-55.79	5.51	8.18	2.15	-55.27	-13.00	42.27	Н
4190.02	-55.62	6.18	9.09	2.15	-54.86	-13.00	41.86	Н
4898.01	-55.08	6.73	9.80	2.15	-54.16	-13.00	41.16	Н

LTE Band 12, 1.4MHz, QPSK, Channel 23095

Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1412.01	-59.71	3.25	5.04	2.15	-60.07	-13.00	47.07	Н
2123.00	-40.56	4.21	4.97	2.15	-41.95	-13.00	28.95	Н
2820.00	-51.28	4.94	6.68	2.15	-51.69	-13.00	38.69	V
3525.02	-55.39	5.57	8.24	2.15	-54.87	-13.00	41.87	V
4257.02	-55.28	6.23	9.16	2.15	-54.50	-13.00	41.50	Н
4943.01	-55.35	6.70	9.84	2.15	-54.36	-13.00	41.36	Н

LTE Band 12, 1.4MHz, QPSK, Channel 23173

Frequency	P _{Mea}	Path	Antenna	Correction	Peak ERP	Limit	Margin	Polarization
(MHz)	(dBm)	Loss(dB)	Gain(dBi)	(dB)	(dBm)	(dBm)	(dB)	Polarization
1431.01	-54.59	3.28	5.14	2.15	-54.88	-13.00	41.88	Н
2146.00	-36.15	4.24	5.04	2.15	-37.50	-13.00	24.50	Н
2863.00	-52.11	4.96	6.75	2.15	-52.47	-13.00	39.47	Н
3579.02	-55.13	6.12	8.31	2.15	-55.09	-13.00	42.09	V
4305.02	-55.07	6.19	9.21	2.15	-54.20	-13.00	41.20	Н
5010.01	-55.06	6.59	9.91	2.15	-53.89	-13.00	40.89	V

Note: The maximum value of expanded measurement uncertainty for this test item is U = 5.16 dB, k = 2.





A.3 FREQUENCY STABILITY

A.3.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the EUT to overnight soak at -30℃.
- 3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE Bands 2,4,5,7,12, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6. Subject the EUT to overnight soak at +50°C.
- 7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the center channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10 °C increments from -30 °C to +50 °C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 4.25VDC and 5.75VDC, with a nominal voltage of 5.0VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.





A.3.2 Measurement results

LTE Band 2, 3.0MHz bandwidth (worst case of all bandwidths)

Frequency Error vs Voltage

Voltage	Temperature	Frequenc	y error (Hz)	Frequency error (ppm)		
(V)	(℃)	QPSK	16QAM	QPSK	16QAM	
4.25		-8.97	-30.08	0.0048	0.0160	
5.0	20	-8.96	-28.55	0.0048	0.0152	
5.75		-9.88	-29.23	0.0053	0.0155	

Frequency Error vs Temperature

Temperature	Voltage	Frequenc	y error (Hz)	Frequency	error (ppm)
(℃)	(V)	QPSK	16QAM	QPSK	16QAM
50		-9.40	-28.57	0.0050	0.0152
40		-8.34	-25.98	0.0044	0.0138
30		-10.21	-27.97	0.0054	0.0149
20		-10.76	-28.47	0.0057	0.0151
10	5.0	-8.98	-26.62	0.0048	0.0142
0		-7.93	-26.65	0.0042	0.0142
-10		-10.09	-28.01	0.0054	0.0149
-20		-10.34	-26.16	0.0055	0.0139
-30		-8.20	-28.22	0.0044	0.0150

LTE Band 4, 5.0MHz bandwidth (worst case of all bandwidths)

Frequency Error vs Voltage

. roqueno	y E1101 13 101	lage								
Voltage	Temperature	Frequency	error (Hz)	Frequency error (ppm)						
(V)	(℃)	QPSK	16QAM	QPSK	16QAM					
4.25		4.66	-25.35	0.0027	0.0146					
5.0	20	4.66	24.62	0.0027	0.0142					
5.75		8.28	-23.80	0.0048	0.0137					

Temperature	Voltage	Frequenc	cy error (Hz)	Frequency	error (ppm)
(℃)	(V)	QPSK	16QAM	QPSK	16QAM
50		6.69	26.41	0.0039	0.0152
40		6.92	25.02	0.0040	0.0144
30		7.31	-24.70	0.0042	0.0143
20		7.81	-25.91	0.0045	0.0150
10	5.0	4.02	-25.58	0.0023	0.0148
0		4.86	24.69	0.0028	0.0143
-10		8.23	25.35	0.0048	0.0146
-20		6.14	25.45	0.0035	0.0147
-30		6.47	26.52	0.0037	0.0153





LTE Band 5, 1.4MHz bandwidth (worst case of all bandwidths)

Frequency Error vs Voltage

Voltage	Temperature Frequency error (Hz) Frequency error (pp		Frequency error (Hz)		error (ppm)
(V)	(℃)	QPSK	16QAM	QPSK	16QAM
4.25		-3.50	18.57	0.0042	0.0222
5.0	20	-3.79	18.42	0.0045	0.0220
5.75		-3.12	20.90	0.0037	0.0250

Temperature	Voltage	Frequenc	y error (Hz)	Frequency	error (ppm)
(℃)	(V)	QPSK	16QAM	QPSK	16QAM
50		-2.79	18.70	0.0033	0.0224
40		-3.05	19.40	0.0036	0.0232
30		-2.86	18.44	0.0034	0.0220
20		-3.19	18.81	0.0038	0.0225
10	5.0	-3.16	19.40	0.0038	0.0232
0		-3.43	18.14	0.0041	0.0217
-10		-3.36	19.11	0.0040	0.0228
-20		-4.95	19.98	0.0059	0.0239
-30		-3.72	20.04	0.0044	0.0240





LTE Band 7, 20MHz bandwidth (worst case of all bandwidths)

Frequency Error vs Voltage

Voltage	Temperature	Frequency error (Hz)		Frequency	error (ppm)
(V)	(℃)	QPSK	16QAM	QPSK	16QAM
4.25		-9.94	-10.43	0.0039	0.0041
5.0	20	-8.78	-10.71	0.0035	0.0042
5.75		-11.77	-9.84	0.0046	0.0039

Temperature	Voltage	Frequency	Frequency error (Hz)		error (Hz)
(℃)	(V)	QPSK	16QAM	QPSK	16QAM
50		-9.40	-12.15	0.0037	0.0048
40		-9.74	-11.12	0.0038	0.0044
30		-10.06	-9.76	0.0040	0.0039
20		-11.54	-8.30	0.0046	0.0033
10	5.0	-9.10	-12.65	0.0036	0.0050
0		-9.51	-9.98	0.0038	0.0039
-10		-9.07	-12.60	0.0036	0.0050
-20		-9.63	-10.93	0.0038	0.0043
-30		-9.14	-12.72	0.0036	0.0050





LTE Band 12, 5MHz bandwidth (worst case of all bandwidths)

Frequency Error vs Voltage

Voltage	Temperature	Frequency error (Hz)		Frequency error (ppm)	
(V)	(℃)	QPSK	16QAM	QPSK	16QAM
4.25		-3.68	-11.73	0.0052	0.0166
5.0	20	3.12	-11.33	0.0044	0.0160
5.75		-2.96	-12.97	0.0042	0.0183

Temperature	Voltage	Voltage Frequency error (Hz) Frequency error		error (ppm)	
(℃)	(V)	QPSK	16QAM	QPSK	16QAM
50		-2.69	-11.09	0.0038	0.0157
40		-3.49	-12.99	0.0049	0.0184
30		-3.12	-11.06	0.0044	0.0156
20		3.71	-12.20	0.0052	0.0172
10	5.0	2.17	-11.87	0.0031	0.0168
0		-4.98	-10.96	0.0070	0.0155
-10		-3.83	-11.29	0.0054	0.0160
-20		-3.28	-12.76	0.0046	0.0180
-30		-2.88	-11.87	0.0041	0.0168





A.4 OCCUPIED BANDWIDTH

A.4.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from ANSI C63.26:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts.
- b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set ≥ 3 × RBW.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.
- d) Set the detection mode to peak, and the trace mode to max-hold.






LTE band 2, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)		
1880.0	QPSK	16QAM	
	1097.76	1089.74	

LTE band 2, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:12:07

LTE band 2, 1.4MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:13:31






LTE band 2, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)		
1990.0	QPSK	16QAM	
1880.0	2708.33	2708.33	

LTE band 2, 3MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:14:57

LTE band 2, 3MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:16:21






LTE band 2, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)		
1880.0	QPSK	16QAM	
	4519.23	4495.19	

LTE band 2, 5MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:17:47

LTE band 2, 5MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:19:11






LTE band 2, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)		
1880.0	QPSK	16QAM	
	8990.38	8990.38	

LTE band 2, 10MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:20:36

LTE band 2, 10MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:22:01






LTE band 2, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)		
1880.0	QPSK	16QAM	
	13485.58	13485.58	

LTE band 2, 15MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:23:26

LTE band 2, 15MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:24:50






LTE band 2, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)		
1880.0	QPSK	16QAM	
	17980.77	17884.62	

LTE band 2, 20MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:26:16

LTE band 2, 20MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:27:40






LTE band 4, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	1097.76	1097.76

LTE band 4, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:29:09

LTE band 4, 1.4MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:30:33






LTE band 4, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	2692.31	2692.31

LTE band 4, 3MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:31:59

LTE band 4, 3MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:33:23






LTE band 4, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	4519.23	4519.23

LTE band 4, 5MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:34:49

LTE band 4, 5MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:36:13






LTE band 4, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	8990.38	8990.38

LTE band 4, 10MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:37:38

LTE band 4, 10MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:39:02






LTE band 4, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	13485.58	13485.58

LTE band 4, 15MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:40:28

LTE band 4, 15MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:41:52






LTE band 4, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	17980.77	17980.77

LTE band 4, 20MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:43:18

LTE band 4, 20MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:44:42






LTE band 5, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
836.5	QPSK	16QAM
	1089.74	1089.74

LTE band 5, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:48:35

LTE band 5, 1.4MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:50:00






LTE band 5, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
836.5	QPSK	16QAM
	2692.31	2692.31

LTE band 5, 3MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:51:25

LTE band 5, 3MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:52:49






LTE band 5, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
836.5	QPSK	16QAM
630.3	4519.23	4519.23

LTE band 5, 5MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:54:15

LTE band 5, 5MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:55:39






LTE band 5, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
836.5	QPSK	16QAM
630.3	8942.31	8942.31

LTE band 5, 10MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 13:57:05

LTE band 5, 10MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 13:58:28






LTE band 7, 5MHz (99%)


Frequency (MHz)	Occupied Bandwidth (99%) (kHz)	
2525.0	QPSK	16QAM
2535.0	4495.19	4495.19

LTE band 7, 5MHz Bandwidth, QPSK (99% BW)



Date: 4.NOV.2019 14:50:00

LTE band 7, 5MHz Bandwidth, 16QAM (99% BW)



Date: 4.NOV.2019 14:51:24






LTE band 7, 10MHz (99%)


Frequency (MHz)	Occupied Bandwidth (99%) (kHz)	
2525.0	QPSK	16QAM
2535.0	8942.31	8942.31

LTE band 7, 10MHz Bandwidth, QPSK (99% BW)



Date: 4.NOV.2019 14:52:50

LTE band 7, 10MHz Bandwidth, 16QAM (99% BW)



Date: 4.NOV.2019 14:54:14






LTE band 7, 15MHz (99%)


Frequency (MHz)	Occupied Bandwidth (99%) (kHz)	
2525.0	QPSK	16QAM
2535.0	13485.58	13413.46

LTE band 7, 15MHz Bandwidth, QPSK (99% BW)



Date: 4.NOV.2019 14:55:40

LTE band 7, 15MHz Bandwidth, 16QAM (99% BW)



Date: 4.NOV.2019 14:57:04






LTE band 7, 20MHz (99%)


Frequency (MHz)	Occupied Bandwidth (99%) (kHz)	
2525.0	QPSK	16QAM
2535.0	17884.62	17884.62

LTE band 7, 20MHz Bandwidth, QPSK (99% BW)



Date: 4.NOV.2019 14:58:30

LTE band 7, 20MHz Bandwidth, 16QAM (99% BW)



Date: 4.NOV.2019 14:59:54






LTE band 12, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707.5	QPSK	16QAM
707.5	1081.73	1089.74

LTE band 12, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 14:01:25

LTE band 12, 1.4MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 14:02:48






LTE band 12, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707.5	QPSK	16QAM
107.5	2692.31	2692.31

LTE band 12, 3MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 14:04:13

LTE band 12, 3MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 14:05:37






LTE band 12, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707.5	QPSK	16QAM
	4495.19	4495.19

LTE band 12, 5MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 14:07:02

LTE band 12, 5MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 14:08:25






LTE band 12, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707 5	QPSK	16QAM
707.5	8942.31	8894.23

LTE band 12, 10MHz Bandwidth, QPSK (99% BW)



Date: 26.NOV.2019 14:10:53

LTE band 12, 10MHz Bandwidth, 16QAM (99% BW)



Date: 26.NOV.2019 14:12:17





A.5 EMISSION BANDWIDTH

A.5.1Emission Bandwidth Results

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.


The measurement method is from ANSI C63.26:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be wide enough to see sufficient roll off of the signal to make the measurement.
- b) The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set ≥ 3 × RBW.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.
- d) The dynamic range of the spectrum analyzer at the selected RBW shall be more than 10 dB below the target "−X dB" requirement, i.e., if the requirement calls for measuring the −26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be at least 36 dB below the reference level.
- e) Set spectrum analyzer detection mode to peak, and the trace mode to max hold.

LTE band 2, 1.4MHz (-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
1000.0	1298.08	1306.09

LTE band 2, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:27:20










LTE band 2, 1.4MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 14:28:44






LTE band 2, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
1860.0	2964.74	2980.77

LTE band 2, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:30:10

LTE band 2, 3MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 14:31:34






LTE band 2, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
1000.0	4975.96	5000.00

LTE band 2, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:33:00

LTE band 2, 5MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 14:34:24






LTE band 2, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
1860.0	9807.69	9807.69

LTE band 2, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:35:50

LTE band 2, 10MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 14:37:15






LTE band 2, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
1860.0	14783.65	14711.54

LTE band 2, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:38:41

LTE band 2, 15MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 14:40:05






LTE band 2, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
1860.0	19134.62	19230.77

LTE band 2, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:41:31

LTE band 2, 20MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 14:42:56






LTE band 4, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1732.5	QPSK	16QAM
1732.3	1322.12	1306.09

LTE band 4, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:44:25

LTE band 4, 1.4MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 14:45:49






LTE band 4, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1722 F	QPSK	16QAM
1732.5	2964.74	2980.77

LTE band 4, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:47:15

LTE band 4, 3MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 14:48:40






LTE band 4, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1732.5	QPSK	16QAM
1732.3	5000.00	5000.00

LTE band 4, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:50:06

LTE band 4, 5MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 14:51:31






LTE band 4, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1732.5	QPSK	16QAM
1732.3	9855.77	9807.69

LTE band 4, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:52:57

LTE band 4, 10MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 14:54:21






LTE band 4, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1732.5	QPSK	16QAM
	14783.65	14711.54

LTE band 4, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:55:47

LTE band 4, 15MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 14:57:12






LTE band 4, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1732.5	QPSK	16QAM
1732.3	19326.92	19230.77

LTE band 4, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 14:58:38

LTE band 4, 20MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 15:00:03






LTE band 5, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
836.5	QPSK	16QAM
630.3	1314.10	1322.12

LTE band 5, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 15:02:30

LTE band 5, 1.4MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 15:03:55






LTE band 5, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
836.5	QPSK	16QAM
630.3	2964.74	2964.74

LTE band 5, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 15:05:21

LTE band 5, 3MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 15:06:45






LTE band 5, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
836.5	QPSK	16QAM
630.3	5000.00	4951.92

LTE band 5, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 15:08:12

LTE band 5, 5MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 15:09:36






LTE band 5, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
836.5	QPSK	16QAM
	9855.77	9711.54

LTE band 5, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 15:11:02

LTE band 5, 10MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 15:12:27






LTE band 7, 5MHz (-26dBc)


Frequency (MHz)	Occupied Bandwidth (-26dBc) (kHz)	
2535.0	QPSK	16QAM
2555.0	4951.92	4903.85

LTE band 7, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 4.NOV.2019 15:04:57

LTE band 7, 5MHz Bandwidth,16QAM (-26dBc BW)



Date: 4.NOV.2019 15:06:21






LTE band 7, 10MHz (-26dBc)


Frequency (MHz)	Occupied Bandwidth (-26dBc) (kHz)	
2535.0	QPSK	16QAM
2555.0	9759.62	9759.62

LTE band 7, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 4.NOV.2019 15:07:47

LTE band 7, 10MHz Bandwidth,16QAM (-26dBc BW)



Date: 4.NOV.2019 15:09:12






LTE band 7, 15MHz (-26dBc)


Frequency (MHz)	Occupied Bandwidth (-26dBc) (kHz)	
2535.0	QPSK	16QAM
2555.0	14711.54	14711.54

LTE band 7, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 4.NOV.2019 15:10:38

LTE band 7, 15MHz Bandwidth,16QAM (-26dBc BW)



Date: 4.NOV.2019 15:12:02






LTE band 7, 20MHz (-26dBc)


Frequency (MHz)	Occupied Bandwidth (-26dBc) (kHz)	
2535.0	QPSK	16QAM
2555.0	19423.08	19230.77

LTE band 7, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 4.NOV.2019 15:13:28

LTE band 7, 20MHz Bandwidth,16QAM (-26dBc BW)



Date: 4.NOV.2019 15:14:53






LTE band 12, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
707.5	QPSK	16QAM
707.5	1314.10	1314.10

LTE band 12, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 15:15:33

LTE band 12, 1.4MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 15:16:58






LTE band 12, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
707.5	QPSK	16QAM
107.5	2980.77	2964.74

LTE band 12, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 15:18:24

LTE band 12, 3MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 15:19:49






LTE band 12, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
707.5	QPSK	16QAM
	4951.92	4951.92

LTE band 12, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 15:21:15

LTE band 12, 5MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 15:22:40






LTE band 12, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
707.5	QPSK	16QAM
107.5	9711.54	9615.38

LTE band 12, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 26.NOV.2019 15:24:06

LTE band 12, 10MHz Bandwidth, 16QAM (-26dBc BW)



Date: 26.NOV.2019 15:25:31





A.6 BAND EDGE COMPLIANCE

A.6.1 Measurement limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to KDB 971168, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.


Part 27.53(c) states for operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.






A.6.2 Measurement result Only the worst case result is given below LTE band 2

OBW: 1RB-low_offset



Date: 27.NOV.2019 16:13:07


LOW BAND EDGE BLOCK-1RB-low_offset



Date: 27.NOV.2019 16:14:46








Date: 27.NOV.2019 16:16:07

HIGH BAND EDGE BLOCK-1RB-high_offset




Date: 27.NOV.2019 16:17:46






LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 26.NOV.2019 17:45:48

HIGH BAND EDGE BLOCK-20MHz-100%RB




Date: 26.NOV.2019 17:56:13






LTE band 4

OBW: 1RB-low_offset



Date: 27.NOV.2019 16:21:50


LOW BAND EDGE BLOCK-1RB-low_offset



Date: 27.NOV.2019 16:23:29








Date: 27.NOV.2019 16:24:50

HIGH BAND EDGE BLOCK-1RB-high_offset




Date: 27.NOV.2019 16:26:28






LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 26.NOV.2019 18:01:45

HIGH BAND EDGE BLOCK-20MHz-100%RB




Date: 26.NOV.2019 18:05:01






LTE band 5

OBW: 1RB-low_offset



Date: 27.NOV.2019 16:42:03


LOW BAND EDGE BLOCK-1RB-low_offset



Date: 27.NOV.2019 16:43:41








Date: 27.NOV.2019 16:33:32

HIGH BAND EDGE BLOCK-1RB-high_offset




Date: 27.NOV.2019 16:35:10






LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 26.NOV.2019 18:10:46

HIGH BAND EDGE BLOCK-10MHz-100%RB




Date: 26.NOV.2019 18:15:27






LTE band 7

OBW: 1RB-low_offset



Date: 22.NOV.2019 14:54:03


LOW BAND EDGE BLOCK-1RB-low_offset




Date: 22.NOV.2019 14:54:23








Date: 22.NOV.2019 14:54:41



Date: 22.NOV.2019 14:54:53








Date: 22.NOV.2019 14:49:20


HIGH BAND EDGE BLOCK-1RB-high_offset




Date: 22.NOV.2019 14:49:41







Date: 22.NOV.2019 14:50:01




Date: 22.NOV.2019 14:50:12






LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 21.NOV.2019 16:24:49





Date: 21.NOV.2019 16:25:02





HIGH BAND EDGE BLOCK-20MHz-100%RB






Date: 21.NOV.2019 16:27:58






LTE band 12

OBW: 1RB-low_offset



Date: 26.NOV.2019 18:25:35


LOW BAND EDGE BLOCK-1RB-low_offset



Date: 26.NOV.2019 18:25:50








Date: 26.NOV.2019 18:28:48

HIGH BAND EDGE BLOCK-1RB-high_offset




Date: 26.NOV.2019 18:29:03






LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 26.NOV.2019 18:26:22

HIGH BAND EDGE BLOCK-10MHz-100%RB



Date: 26.NOV.2019 18:29:34





A.7 CONDUCTED SPURIOUS EMISSION

A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
- 2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
- 3. The number of sweep points of spectrum analyzer is set to 30001 which is greater than span/RBW.

A. 7.2 Measurement Limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.


Part 27.53(c) states for operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.






A. 7.2 Measurement result Only the worst case result is given below

LTE band 2: 30MHz - 19.1GHz



Date: 26.NOV.2019 19:06:36

LTE band 4: 30MHz - 17.55GHz




Date: 26.NOV.2019 19:33:27






LTE band 5: 30MHz - 8.49GHz



Date: 26.NOV.2019 19:35:43

LTE band 7: 30MHz - 25.7GHz




Date: 21.NOV.2019 16:44:27





LTE band 12: 30MHz - 7.16GHz



Date: 26.NOV.2019 19:36:11





A.8 PEAK-TO-AVERAGE POWER RATIO

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

According to KDB 971168 5.7.1:

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function:
- b) Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e) Record the maximum PAPR level associated with a probability of 0.1%

A.8.1 Measurement limit

not exceed 13 dB

A.8.2 Measurement results

LTE band 2, 20MHz

Frequency(MHz)	PAPR(dB)	
1880.0	QPSK	16QAM
	6.92	7.50

LTE band 4, 20MHz

Frequency(MHz)	PAPR(dB)	
1732.5	QPSK	16QAM
	6.67	7.37

LTE band 7, 20MHz

Frequency(MHz)	PAPR(dB)	
2535.0	QPSK	16QAM
	7.18	7.63

LTE band 12, 10MHz

Frequency(MHz)	PAPR(dB)	
707.5	QPSK	16QAM
707.5	5.13	6.06





ANNEX B: Accreditation Certificate

United States Department of Commerce National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 600118-0

Telecommunication Technology Labs, CAICT

Beijing

is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:

Electromagnetic Compatibility & Telecommunications

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).

2019-09-26 through 2020-09-30

Effective Dates

CAMENT OF COMMENT OF AMENDED

For the National Voluntary Laboratory Accreditation Program

END OF REPORT