

FCC Test Report

APPLICANT : TCL Communication Ltd.
EQUIPMENT : GSM Quad-band / UMTS Quad-band /
LTE hexa-band mobile phone
BRAND NAME : alcatel
MODEL NAME : 6055P
FCC ID : 2ACCJA019
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Mar. 31, 2016 and testing was completed on May 14, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Prepared by: James Huang / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

| | |
|--|-----------|
| REVISION HISTORY | 3 |
| SUMMARY OF TEST RESULT | 4 |
| 1. GENERAL DESCRIPTION | 5 |
| 1.1. Applicant..... | 5 |
| 1.2. Manufacturer | 5 |
| 1.3. Product Feature of Equipment Under Test | 5 |
| 1.4. Product Specification of Equipment Under Test | 6 |
| 1.5. Modification of EUT | 7 |
| 1.6. Test Location | 7 |
| 1.7. Applicable Standards | 7 |
| 1.8. Specification of Accessory | 8 |
| 2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST | 9 |
| 2.1. Test Mode | 9 |
| 2.2. Connection Diagram of Test System | 12 |
| 2.3. Support Unit used in test configuration and system..... | 14 |
| 2.4. EUT Operation Test Setup | 15 |
| 3. TEST RESULT | 16 |
| 3.1. Test of AC Conducted Emission Measurement | 16 |
| 3.2. Test of Radiated Emission Measurement | 22 |
| 4. LIST OF MEASURING EQUIPMENT | 28 |
| 5. UNCERTAINTY OF EVALUATION | 29 |
| APPENDIX A. SETUP PHOTOGRAPHS | |



REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|-------------|---------|-------------------------|--------------|
| FC611504-04 | Rev. 01 | Initial issue of report | May 26, 2016 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |



SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description | Limit | Result | Remark |
|----------------|----------|-----------------------|-----------------|--------|---|
| 3.1 | 15.107 | AC Conducted Emission | < 15.107 limits | PASS | Under limit 7.51 dB at 0.540 MHz |
| 3.2 | 15.109 | Radiated Emission | < 15.109 limits | PASS | Under limit 2.37 dB at 44.850 MHz for Quasi-Peak |

1. General Description

1.1. Applicant

TCL Communication Ltd.

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai,
P.R.China 201203

1.2. Manufacturer

TCL Communication Ltd.

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai,
P.R.China 201203

1.3. Product Feature of Equipment Under Test

| Product Feature | |
|---------------------------------|--|
| Equipment | GSM Quad-band / UMTS Quad-band / LTE hexa-band mobile phone |
| Brand Name | alcatel |
| Model Name | 6055P |
| FCC ID | 2ACCJA019 |
| EUT supports Radios application | GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(16QAM uplink is not supported)/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE Bluetooth v4.2 LE |
| IMEI Code | Conduction: 358476070060750/358476070060768 Radiation: 358476070060750/358476070060768 |
| HW Version | PIO |
| SW Version | A2E |
| EUT Stage | Identical Prototype |

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4. Product Specification of Equipment Under Test

| Standards-related Product Specification | |
|---|--|
| Tx Frequency | GSM850 : 824.2 MHz ~ 848.8 MHz GSM1900 : 1850.2 MHz ~ 1909.8MHz WCDMA Band V : 826.4 MHz ~ 846.6 MHz WCDMA Band II : 1852.4 MHz ~ 1907.6 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz 802.11b/g/n: 2412 MHz ~ 2472 MHz 802.11a/n: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5700 MHz ; Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz |
| Rx Frequency | GSM850 : 869.2 MHz ~ 893.8 MHz GSM1900 : 1930.2 MHz ~ 1989.8 MHz WCDMA Band V : 871.4 MHz ~ 891.6 MHz WCDMA Band II : 1932.4 MHz ~ 1987.6 MHz LTE Band 7: 2622.5 MHz~ 2687.5 MHz 802.11b/g/n: 2412 MHz ~ 2472 MHz 802.11a/n: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5700 MHz ; Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz Glonass: 1602 MHz + $n \times 0.5625\text{MHz}$ ($n=-7,-6,-5,...,0,...,6$) NFC : 13.56 MHz |
| Antenna Type | WWAN : IFA Antenna WLAN : IFA Antenna Bluetooth : IFA Antenna GPS/Glonass : IFA Antenna NFC : LOOP Antenna |
| Type of Modulation | GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : QPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : (16QAM uplink is not supported) DC-HSDPA : 64QAM LTE: QPSK / 16QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth v4.0 LE : GFSK Bluetooth v4.2 LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GPS/Glonass : BPSK NFC: ASK |



1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

| | | | |
|---------------------------|---|-----------|-----------------------------|
| Test Site | SPORTON INTERNATIONAL (KUNSHAN) INC. | | |
| Test Site Location | No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958 | | |
| Test Site No. | Sporton Site No. | | FCC Registration No. |
| | CO01-KS | 03CH02-KS | 418269 |

1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

1.8. Specification of Accessory

| Specification of Accessory | | | | |
|----------------------------|------------------|---|------------|--------------|
| AC Adapter 1 | Brand Name | ALCATEL onetouch | Model Name | UC13US |
| | Power Rating | I/P: 100-240Vac, 400mA, O/P: 5Vdc, 2000mA | | |
| | P/N | CBA0059AG0C2 | | |
| AC Adapter 2 | Brand Name | ALCATEL onetouch | Model Name | UC13US |
| | Power Rating | I/P: 100-240Vac, 350mA, O/P: 5Vdc, 2000mA | | |
| | P/N | CBA0059AG0C4 | | |
| AC Adapter 3 | Brand Name | N/A | Model Name | UC13US |
| | Power Rating | I/P: 100-240Vac, 500mA, O/P: 5Vdc, 2000mA | | |
| | P/N | CBA0059AG4C1 | | |
| AC Adapter 4 | Brand Name | alcatel | Model Name | UC13US |
| | Power Rating | I/P: 100-240Vac, 350mA, O/P: 5Vdc, 2000mA | | |
| | P/N | CBA0059AGAC4 | | |
| AC Adapter 5 | Brand Name | alcatel | Model Name | UC13US |
| | Power Rating | I/P: 100-240Vac, 500mA, O/P: 5Vdc, 2000mA | | |
| | P/N | CBA0059AGAC1 | | |
| Battery 1 | Brand Name | ALCATEL onetouch | Model Name | TLp026EJ |
| | Power Rating | 3.85Vdc, 2610mAh | | |
| Battery 2 | Brand Name | ALCATEL onetouch | Model Name | TLp026E2 |
| | Power Rating | 3.84Vdc, 2610mAh | | |
| Battery 3 | Brand Name | alcatel | Model Name | TLp026EJ |
| | Power Rating | 3.85Vdc, 2610mAh | | |
| Battery 4 | Brand Name | alcatel | Model Name | TLp026E2 |
| | Power Rating | 3.84Vdc, 2610mAh | | |
| USB Cable 1 | Brand Name | N/A | Model Name | CDA0000043C8 |
| | Signal Line Type | 1.0m shielded without core | | |
| USB Cable 2 | Brand Name | N/A | Model Name | CDA0000043C2 |
| | Signal Line Type | 1.0m shielded without core | | |
| Earphone 1 | Brand Name | alcatel | Model Name | J22C |
| | Signal Line Type | 1.4m non-shielded without core | | |
| | P/N | CCB0029A10CC | | |
| Earphone 2 | Brand Name | alcatel | Model Name | J22H |
| | Signal Line Type | 1.0m non-shielded without core | | |
| | P/N | CCB0047A10CC | | |

Note: The adapter 4, 5 and battery 3, 4 are just with different logo, all the designs are identical with adapter 2, 3 and battery 1, 2.

2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

| Item | EUT Configuration | Test Condition | | |
|------|--|----------------|-----------|-----------|
| | | EMI AC | EMI RE<1G | EMI RE≥1G |
| 1. | Charging Mode (EUT with adapter) | ☒ | ☒ | ☒ |
| 2. | Data application transferred mode (EUT connected with notebook) | ☒ | ☒ | ☒ |


Abbreviations:

- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz


| Test Items | EUT Configure Mode | Function Type |
|--------------------------|--------------------------|---|
| AC Conducted Emission | 1/2 | <p>Mode 1: GSM850 Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone 1 + Battery 1 + Camera (Rear) <Fig.1></p> <p>Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Charging from Adapter 2) + Earphone 2 + Battery 2 + Camera (Front) <Fig.1></p> <p>Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 2 (Charging from Adapter 3) + Earphone 2 + Battery 2 + MPEG4 <Fig.1></p> <p>Mode 4: WCDMA Band II Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Charging from Adapter 2) + Earphone 2 + Battery 2 + NFC On <Fig.1></p> <p>Mode 5: WCDMA Band II Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 2 (Charging from Adapter 2) + Earphone 2 + Battery 2 + Glonass Rx <Fig.2></p> <p>Mode 6: LTE Band 7 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 1 (Data Link with Notebook) + Earphone 2 + Battery 2 + GPS Rx <Fig.3></p> <p>Mode 7: LTE Band 7 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Data Link with Notebook) + Earphone 2 + Battery 2 + GPS Rx <Fig.3></p> |

| | | |
|---|-----|---|
| Radiated Emissions < 1GHz | 1/2 | <p>Mode 1: GSM850 Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone 1 + Battery 1 + Camera (Rear) <Fig.1></p> <p>Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Charging from Adapter 2) + Earphone 2 + Battery 2 + Camera (Front) <Fig.1></p> <p>Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Charging from Adapter 3) + Earphone 1 + Battery 1 + MPEG4 <Fig.1></p> <p>Mode 4: WCDMA Band II Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone 1 + Battery 1 + NFC On <Fig.1></p> <p>Mode 5: WCDMA Band II Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone 1 + Battery 1 + Glonass Rx <Fig.2></p> <p>Mode 6: LTE Band 7 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 1 (Data Link with Notebook) + Earphone 1 + Battery 1 + GPS Rx <Fig.3></p> <p>Mode 7: LTE Band 7 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Data Link with Notebook) + Earphone 1 + Battery 1 + GPS Rx <Fig.3></p> |
| Radiated Emissions ≥ 1GHz | 1/2 | <p>Mode 1: WCDMA Band II Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone 1 + Battery 1 + Glonass Rx <Fig.2></p> <p>Mode 2: LTE Band 7 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Data Link with Notebook) + Earphone 1 + Battery 1 + GPS Rx <Fig.3></p> |
| Remark: <ol style="list-style-type: none"> 1. The worst case of AC is mode 4, and the USB Link mode of AC is mode 6, the test data of these modes were reported. 2. The worst case of RE < 1G is mode 5, and the USB Link mode of RE is mode 7, the test data of these modes were reported. 3. Data Link with Notebook means data application transferred mode between EUT and Notebook. | | |


2.2. Connection Diagram of Test System



<Fig.1>



<Fig.2>



<Fig.3>

2.3. Support Unit used in test configuration and system

| Item | Equipment | Trade Name | Model Name | FCC ID | Data Cable | Power Cord |
|------|--------------------|------------|--------------|----------------|-------------------|--|
| 1. | System Simulator | R&S | CMU 200 | N/A | N/A | Unshielded, 1.8 m |
| 2. | LTE Base Station | Anritus | MT8820C | N/A | N/A | Unshielded, 1.8 m |
| 3. | GPS Station | ADIVIC | MP9000 | N/A | N/A | Unshielded, 1.8 m |
| 4. | Glonass Station | RACELOGIC | RLLS03-2RP | N/A | N/A | Unshielded, 1.8 m |
| 5. | WLAN AP | ASUSTek | RT-AC66U | MSQ-RTAC66U | N/A | Unshielded, 1.8 m |
| 6. | WLAN AP | LINKSYS | WRT600N | Q87-WRT600NV11 | N/A | Unshielded, 1.8 m |
| 7. | WLAN AP | D-Link | DIR-855 | KA2DIR855A2 | N/A | Unshielded, 1.8 m |
| 8. | Bluetooth Earphone | Nokia | BH-106 | QTLBH-106 | Unshielded, 0.5 m | N/A |
| 9. | Bluetooth Earphone | Lenovo | LBH301 | N/A | N/A | N/A |
| 10. | Notebook | Lenovo | G480 | N/A | N/A | AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m |
| 11. | Notebook | DELL | Latitude3440 | N/A | N/A | AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m |
| 12. | SD Card | Kingston | 4GB | N/A | N/A | N/A |
| 13. | SD Card | SanDisk | Uitra | N/A | N/A | N/A |
| 14. | iPod | Apple | A1199 | FCC DoC | Shielded, 1.2 m | N/A |



2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and was in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on GPS/Glonass function to make the EUT receive continuous signals from GPS/Glonass station.
3. Execute "Video player" to play MPEG4 files.
4. Turn on camera to capture images.
5. Turn on NFC function.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

| Frequency of emission (MHz) | Conducted limit (dBuV) | |
|--------------------------------|------------------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test Setup



3.1.5 Test Result of AC Conducted Emission

| | | | |
|-----------------|--|---------------------|--------|
| Test Mode : | Mode 4 | Temperature : | 22~24℃ |
| Test Engineer : | Amos Zhang | Relative Humidity : | 44~46% |
| Test Voltage : | 120Vac / 60Hz | Phase : | Line |
| Function Type : | WCDMA Band II Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Charging from Adapter 2) + Earphone 2 + Battery 2 + NFC On | | |




Site : CO01-KS
 Condition : FCC CLASS-B LISN-L-20151024 LINE
 Project : (FC) 611504-04
 mode : Mode 4
 : 356133070060750/356136070060768 #9

| | Freq | Level | Over | Limit | Read | LISN | Cable | |
|-----|-------|-------|--------|-------|-------|--------|-------|---------|
| | MHz | dBuV | Limit | Line | Level | Factor | Loss | Remark |
| | | | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.54 | 42.89 | -13.11 | 56.00 | 32.50 | 0.23 | 10.16 | QP |
| 2 * | 0.54 | 38.49 | -7.51 | 46.00 | 28.10 | 0.23 | 10.16 | Average |
| 3 | 0.60 | 36.99 | -19.01 | 56.00 | 26.59 | 0.24 | 10.16 | QP |
| 4 | 0.60 | 29.89 | -16.11 | 46.00 | 19.49 | 0.24 | 10.16 | Average |
| 5 | 1.11 | 37.88 | -18.12 | 56.00 | 27.50 | 0.24 | 10.14 | QP |
| 6 | 1.11 | 31.68 | -14.32 | 46.00 | 21.30 | 0.24 | 10.14 | Average |
| 7 | 1.28 | 36.66 | -19.34 | 56.00 | 26.29 | 0.23 | 10.14 | QP |
| 8 | 1.28 | 30.56 | -15.44 | 46.00 | 20.19 | 0.23 | 10.14 | Average |
| 9 | 1.48 | 35.95 | -20.05 | 56.00 | 25.60 | 0.21 | 10.14 | QP |
| 10 | 1.48 | 29.95 | -16.05 | 46.00 | 19.60 | 0.21 | 10.14 | Average |
| 11 | 18.52 | 39.56 | -20.44 | 60.00 | 28.80 | 0.27 | 10.49 | QP |
| 12 | 18.52 | 24.86 | -25.14 | 50.00 | 14.10 | 0.27 | 10.49 | Average |



| | | | |
|-----------------|--|---------------------|---------|
| Test Mode : | Mode 4 | Temperature : | 22~24°C |
| Test Engineer : | Amos Zhang | Relative Humidity : | 44~46% |
| Test Voltage : | 120Vac / 60Hz | Phase : | Neutral |
| Function Type : | WCDMA Band II Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Charging from Adapter 2) + Earphone 2 + Battery 2 + NFC On | | |




Site : CO01-KS
 Condition : FCC CLASS-B LISM-N-20151024 NEUTRAL
 Project : (FC) 611504-04
 mode : Mode 4
 : 356133070060750/356136070060768 #9

| | Freq | Level | Over Limit | Limit Line | Read Level | LISM Factor | Cable Loss | Remark |
|-----|------|-------|------------|------------|------------|-------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.15 | 48.61 | -17.30 | 65.91 | 38.20 | 0.30 | 10.11 | QP |
| 2 | 0.15 | 34.71 | -21.20 | 55.91 | 24.30 | 0.30 | 10.11 | Average |
| 3 * | 0.54 | 43.69 | -12.31 | 56.00 | 33.21 | 0.32 | 10.16 | QP |
| 4 | 0.54 | 33.09 | -12.91 | 46.00 | 22.61 | 0.32 | 10.16 | Average |
| 5 | 0.58 | 40.79 | -15.21 | 56.00 | 30.30 | 0.33 | 10.16 | QP |
| 6 | 0.58 | 29.09 | -16.91 | 46.00 | 18.60 | 0.33 | 10.16 | Average |
| 7 | 0.98 | 34.10 | -21.90 | 56.00 | 23.59 | 0.37 | 10.14 | QP |
| 8 | 0.98 | 23.10 | -22.90 | 46.00 | 12.59 | 0.37 | 10.14 | Average |
| 9 | 1.55 | 34.72 | -21.28 | 56.00 | 24.20 | 0.38 | 10.14 | QP |
| 10 | 1.55 | 21.72 | -24.28 | 46.00 | 11.20 | 0.38 | 10.14 | Average |
| 11 | 2.68 | 31.62 | -24.38 | 56.00 | 21.10 | 0.37 | 10.15 | QP |
| 12 | 2.68 | 21.82 | -24.18 | 46.00 | 11.30 | 0.37 | 10.15 | Average |



| | | | |
|-----------------|---|---------------------|--------|
| Test Mode : | Mode 6 | Temperature : | 22~24℃ |
| Test Engineer : | Amos Zhang | Relative Humidity : | 44~46% |
| Test Voltage : | 120Vac / 60Hz | Phase : | Line |
| Function Type : | LTE Band 7 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 1 (Data Link with Notebook) + Earphone 2 + Battery 2 + GPS Rx | | |




Site : CO01-KS
Condition : FCC CLASS-B LISM-L-20151024 LINE
Project : (FC) 611504-04
mode : Mode 6
: 356133070060750/356136070060768 #9

| | Freq | Level | Over | Limit | Read | LISM | Cable | |
|-----|------|-------|--------|-------|-------|--------|-------|---------|
| | MHz | dBuV | Limit | Line | Level | Factor | Loss | Remark |
| | | | dB | dBuV | dBuV | dB | dB | |
| 1 * | 0.16 | 42.20 | -23.49 | 65.69 | 31.60 | 0.49 | 10.11 | QP |
| 2 | 0.16 | 31.50 | -24.19 | 55.69 | 20.90 | 0.49 | 10.11 | Average |
| 3 | 0.17 | 37.14 | -28.07 | 65.21 | 26.60 | 0.42 | 10.12 | QP |
| 4 | 0.17 | 24.34 | -30.87 | 55.21 | 13.80 | 0.42 | 10.12 | Average |
| 5 | 0.23 | 29.56 | -32.83 | 62.39 | 19.20 | 0.22 | 10.14 | QP |
| 6 | 0.23 | 21.16 | -31.23 | 52.39 | 10.80 | 0.22 | 10.14 | Average |
| 7 | 0.40 | 27.70 | -30.16 | 57.86 | 17.30 | 0.23 | 10.17 | QP |
| 8 | 0.40 | 20.60 | -27.26 | 47.86 | 10.20 | 0.23 | 10.17 | Average |
| 9 | 0.44 | 29.60 | -27.55 | 57.15 | 19.20 | 0.23 | 10.17 | QP |
| 10 | 0.44 | 22.30 | -24.85 | 47.15 | 11.90 | 0.23 | 10.17 | Average |
| 11 | 0.79 | 26.59 | -29.41 | 56.00 | 16.20 | 0.24 | 10.15 | QP |
| 12 | 0.79 | 18.69 | -27.31 | 46.00 | 8.30 | 0.24 | 10.15 | Average |



| | | | |
|-----------------|---|---------------------|---------|
| Test Mode : | Mode 6 | Temperature : | 22~24℃ |
| Test Engineer : | Amos Zhang | Relative Humidity : | 44~46% |
| Test Voltage : | 120Vac / 60Hz | Phase : | Neutral |
| Function Type : | LTE Band 7 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 1 (Data Link with Notebook) + Earphone 2 + Battery 2 + GPS Rx | | |



| | Freq | Level | Over | Limit | Read | LISM | Cable | |
|-----|------|-------|--------|-------|-------|--------|-------|---------|
| | MHz | dBuV | Limit | Line | Level | Factor | Loss | Remark |
| | | | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.17 | 37.02 | -28.19 | 65.21 | 26.60 | 0.30 | 10.12 | QP |
| 2 | 0.17 | 23.92 | -31.29 | 55.21 | 13.50 | 0.30 | 10.12 | Average |
| 3 | 0.19 | 33.73 | -30.29 | 64.02 | 23.30 | 0.31 | 10.12 | QP |
| 4 | 0.19 | 24.33 | -29.69 | 54.02 | 13.90 | 0.31 | 10.12 | Average |
| 5 | 0.40 | 28.69 | -29.17 | 57.86 | 18.20 | 0.32 | 10.17 | QP |
| 6 | 0.40 | 20.79 | -27.07 | 47.86 | 10.30 | 0.32 | 10.17 | Average |
| 7 | 0.48 | 29.78 | -26.54 | 56.32 | 19.30 | 0.32 | 10.16 | QP |
| 8 * | 0.48 | 25.28 | -21.04 | 46.32 | 14.80 | 0.32 | 10.16 | Average |
| 9 | 0.78 | 26.80 | -29.20 | 56.00 | 16.30 | 0.35 | 10.15 | QP |
| 10 | 0.78 | 21.10 | -24.90 | 46.00 | 10.60 | 0.35 | 10.15 | Average |
| 11 | 4.60 | 28.74 | -27.26 | 56.00 | 18.20 | 0.36 | 10.18 | QP |
| 12 | 4.60 | 19.84 | -26.16 | 46.00 | 9.30 | 0.36 | 10.18 | Average |

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|----------------------------|--|--|
| 30 – 88 | 100 | 3 |
| 88 – 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| Above 960 | 500 | 3 |

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamplifier Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz






3.2.5. Test Result of Radiated Emission

| | | | |
|-----------------|---|---------------------|------------|
| Test Mode : | Mode 5 | Temperature : | 21~22°C |
| Test Engineer : | Jack Wang | Relative Humidity : | 41~42% |
| Test Distance : | 3m | Polarization : | Horizontal |
| Function Type : | WCDMA Band II Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone 1 + Battery 1 + Glonass Rx | | |





| | | | |
|-----------------|---|---------------------|----------|
| Test Mode : | Mode 5 | Temperature : | 21~22°C |
| Test Engineer : | Jack Wang | Relative Humidity : | 41~42% |
| Test Distance : | 3m | Polarization : | Vertical |
| Function Type : | WCDMA Band II Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone 1 + Battery 1 + Glonass Rx | | |




Site : 03CH02-KS
 Condition : FCC CLASS-B 3m 966-02 LF ANT VERTICAL
 Project : (FC) 611504-04
 Mode : 5
 IMEI : #9 356133070060750 356133070060768

| | Freq | Level | Over | Limit | ReadAntenna | Cable | Preamp | A/Pos | T/Pos | Remark | Pol/Phas |
|-----|---------|--------|--------|--------|-------------|-------|--------|-------|-------|--------|---------------|
| | MHz | dBuV/m | dB | dBuV/m | dBuV | dB/m | dB | dB | cm | deg | |
| 1 ! | 36.21 | 35.38 | -4.62 | 40.00 | 41.86 | 24.30 | 0.12 | 30.90 | --- | --- | Peak VERTICAL |
| 2 ! | 44.85 | 37.63 | -2.37 | 40.00 | 48.80 | 19.50 | 0.13 | 30.80 | 100 | 238 | QP VERTICAL |
| 3 | 151.77 | 32.61 | -10.89 | 43.50 | 45.17 | 17.51 | 0.33 | 30.40 | --- | --- | Peak VERTICAL |
| 4 | 198.21 | 34.04 | -9.46 | 43.50 | 48.64 | 15.39 | 0.41 | 30.40 | --- | --- | Peak VERTICAL |
| 5 | 730.50 | 26.30 | -19.70 | 46.00 | 29.05 | 26.42 | 1.29 | 30.46 | --- | --- | Peak VERTICAL |
| 6 | 960.80 | 28.18 | -25.82 | 54.00 | 28.28 | 28.66 | 1.76 | 30.52 | --- | --- | Peak VERTICAL |
| 7 | 2020.00 | 47.65 | -26.35 | 74.00 | 47.15 | 30.56 | 4.61 | 34.67 | --- | --- | Peak VERTICAL |
| 8 | 2162.00 | 48.04 | -25.96 | 74.00 | 45.72 | 31.03 | 5.65 | 34.36 | --- | --- | Peak VERTICAL |
| 9 | 2826.00 | 48.80 | -25.20 | 74.00 | 41.68 | 32.14 | 2.76 | 27.78 | --- | --- | Peak VERTICAL |
| 10 | 4155.00 | 47.73 | -26.27 | 74.00 | 38.01 | 35.08 | 6.53 | 31.89 | --- | --- | Peak VERTICAL |
| 11 | 4773.00 | 48.54 | -25.46 | 74.00 | 40.41 | 35.03 | 6.00 | 32.90 | --- | --- | Peak VERTICAL |
| 12 | 5841.00 | 48.88 | -25.12 | 74.00 | 42.51 | 35.12 | 6.47 | 35.22 | --- | --- | Peak VERTICAL |



| | | | |
|------------------------|---|----------------------------|------------|
| Test Mode : | Mode 7 | Temperature : | 21~22°C |
| Test Engineer : | Jack Wang | Relative Humidity : | 41~42% |
| Test Distance : | 3m | Polarization : | Horizontal |
| Function Type : | LTE Band 7 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Data Link with Notebook) + Earphone 1 + Battery 1 + GPS Rx | | |




Site : 03CH02-KS
Condition : FCC CLASS-B 3m 966-02 LF ANT HORIZONTAL
Project : (FC) 611504-04
Mode : 7
IMEI : #9 356133070060750 356133070060768

| | Freq | Level | Over | Limit | ReadAntenna | Cable | Preamp | A/Pos | T/Pos | Remark | Pol/Phas |
|-----|---------|--------|--------|--------|-------------|-------|--------|-------|-------|--------|-----------------|
| | MHz | dBuV/m | dB | dBuV/m | dBuV | dB/m | dB | dB | cm | deg | |
| 1 | 155.55 | 35.87 | -7.63 | 43.50 | 48.62 | 17.32 | 0.33 | 30.40 | --- | --- | Peak HORIZONTAL |
| 2 | 165.54 | 37.13 | -6.37 | 43.50 | 50.32 | 16.86 | 0.35 | 30.40 | --- | --- | Peak HORIZONTAL |
| 3 | 239.25 | 38.74 | -7.26 | 46.00 | 51.82 | 16.92 | 0.48 | 30.48 | --- | --- | Peak HORIZONTAL |
| 4 ! | 314.70 | 40.32 | -5.68 | 46.00 | 51.62 | 18.60 | 0.63 | 30.53 | --- | --- | Peak HORIZONTAL |
| 5 ! | 335.00 | 42.72 | -3.28 | 46.00 | 53.01 | 19.60 | 0.68 | 30.57 | --- | --- | Peak HORIZONTAL |
| 6 ! | 344.80 | 42.12 | -3.88 | 46.00 | 51.90 | 20.10 | 0.71 | 30.59 | 100 | 272 | QP HORIZONTAL |
| 7 | 1834.00 | 46.76 | -27.24 | 74.00 | 48.29 | 29.40 | 4.57 | 35.50 | --- | --- | Peak HORIZONTAL |
| 8 | 2190.00 | 47.76 | -26.24 | 74.00 | 45.13 | 31.14 | 5.80 | 34.31 | --- | --- | Peak HORIZONTAL |
| 9 | 2876.00 | 49.13 | -24.87 | 74.00 | 42.07 | 32.27 | 2.90 | 28.11 | --- | --- | Peak HORIZONTAL |
| 10 | 3765.00 | 47.86 | -26.14 | 74.00 | 38.39 | 34.52 | 6.44 | 31.49 | --- | --- | Peak HORIZONTAL |
| 11 | 4620.00 | 47.84 | -26.16 | 74.00 | 39.18 | 35.18 | 5.38 | 31.90 | --- | --- | Peak HORIZONTAL |
| 12 | 5781.00 | 50.30 | -23.70 | 74.00 | 44.36 | 35.22 | 6.75 | 36.03 | --- | --- | Peak HORIZONTAL |



| | | | |
|-----------------|---|---------------------|----------|
| Test Mode : | Mode 7 | Temperature : | 21~22°C |
| Test Engineer : | Jack Wang | Relative Humidity : | 41~42% |
| Test Distance : | 3m | Polarization : | Vertical |
| Function Type : | LTE Band 7 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Data Link with Notebook) + Earphone 1 + Battery 1 + GPS Rx | | |



Site : 03CH02-KS
Condition : FCC CLASS-B 3m 966-02 LF ANT VERTICAL
Project : (FC) 611504-04
Mode : 7
IMEI : #9 356133070060750 356133070060768

| | Freq | Level | Over Limit | Limit Line | ReadAntenna Level Factor | Cable Loss | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phas | |
|----|---------|--------|---------------|---------------|-----------------------------|---------------|------------------|-------|-------|--------|----------|----------|
| | MHz | dBuV/m | dB | dBuV/m | dBuV | dB/m | dB | dB | cm | deg | | |
| 1 | 155.28 | 31.18 | -12.32 | 43.50 | 43.93 | 17.32 | 0.33 | 30.40 | --- | --- | Peak | VERTICAL |
| 2 | 165.27 | 31.58 | -11.92 | 43.50 | 44.77 | 16.86 | 0.35 | 30.40 | 125 | 87 | Peak | VERTICAL |
| 3 | 196.05 | 31.42 | -12.08 | 43.50 | 45.93 | 15.48 | 0.41 | 30.40 | --- | --- | Peak | VERTICAL |
| 4 | 239.25 | 33.30 | -12.70 | 46.00 | 46.38 | 16.92 | 0.48 | 30.48 | --- | --- | Peak | VERTICAL |
| 5 | 344.80 | 32.44 | -13.56 | 46.00 | 42.22 | 20.10 | 0.71 | 30.59 | --- | --- | Peak | VERTICAL |
| 6 | 598.20 | 33.54 | -12.46 | 46.00 | 38.52 | 24.32 | 0.90 | 30.20 | --- | --- | Peak | VERTICAL |
| 7 | 1742.00 | 47.03 | -26.97 | 74.00 | 49.33 | 29.23 | 4.43 | 35.96 | --- | --- | Peak | VERTICAL |
| 8 | 2268.00 | 47.83 | -26.17 | 74.00 | 44.74 | 31.27 | 5.72 | 33.90 | --- | --- | Peak | VERTICAL |
| 9 | 2770.00 | 49.40 | -24.60 | 74.00 | 43.12 | 32.03 | 2.81 | 28.56 | --- | --- | Peak | VERTICAL |
| 10 | 3981.00 | 47.93 | -26.07 | 74.00 | 38.80 | 34.81 | 6.03 | 31.71 | --- | --- | Peak | VERTICAL |
| 11 | 4602.00 | 48.33 | -25.67 | 74.00 | 39.48 | 35.20 | 5.38 | 31.73 | --- | --- | Peak | VERTICAL |
| 12 | 5790.00 | 49.13 | -24.87 | 74.00 | 42.95 | 35.19 | 6.75 | 35.76 | --- | --- | Peak | VERTICAL |



4. List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|--------------------------------------|--------------|-------------------|------------------|----------------------------|------------------|--------------|---------------|-----------------------|
| EMI Receiver | R&S | ESCI7 | 100768 | 9kHz~7GHz; | Apr. 29, 2016 | May 12, 2016 | Apr. 28, 2017 | Conduction (CO01-KS) |
| AC LISN | MessTec | AN3016 | 060103 | 9kHz~30MHz | Oct. 24, 2015 | May 12, 2016 | Oct. 23, 2016 | Conduction (CO01-KS) |
| AC LISN (for auxiliary equipment) | MessTec | AN3016 | 060105 | 9kHz~30MHz | Oct. 24, 2015 | May 12, 2016 | Oct. 23, 2016 | Conduction (CO01-KS) |
| AC Power Source | Chroma | 61602 | ABP0000008 11 | AC 0V~300V, 45Hz~1000Hz | Oct. 24, 2015 | May 12, 2016 | Oct. 23, 2016 | Conduction (CO01-KS) |
| EMI Test Receiver | R&S | ESR7 | 101403 | 9kHz~7GHz;Ma x 30dBm | Sep. 10, 2015 | May 14, 2016 | Sep. 09, 2016 | Radiation (03CH02-KS) |
| EXA Spectrum Analyzer | Keysight | N9010A | MY55150208 | 10Hz~44G,MAX 30dB | Apr. 22, 2016 | May 14, 2016 | Apr. 21, 2017 | Radiation (03CH02-KS) |
| Bilog Antenna | TeseQ | CBL6112D | 23182 | 25MHz~2GHz | Mar. 12, 2016 | May 14, 2016 | Mar. 11, 2017 | Radiation (03CH02-KS) |
| Double Ridge Horn Antenna | ETS-Lindgren | 3117 | 75957 | 1GHz~18GHz | Nov. 07, 2015 | May 14, 2016 | Nov. 06, 2016 | Radiation (03CH02-KS) |
| SHF-EHF Horn | Schwarzbeck | BBHA 9170 | BBHA170249 | 15GHz ~40GHz | Mar. 03, 2016 | May 14, 2016 | Mar. 02, 2017 | Radiation (03CH02-KS) |
| Amplifier | com-power | PA-103A | 161069 | 1kHz~1000MHz / 32 dB | Apr. 22, 2016 | May 14, 2016 | Apr. 21, 2017 | Radiation (03CH02-KS) |
| Amplifier | Agilent | 8449B | 3008A02384 | 1~26.5GHz Gain 30dB | Oct. 24, 2015 | May 14, 2016 | Oct. 23, 2016 | Radiation (03CH02-KS) |
| Amplifier | MITEQ | TTA1840-35-H G | 1887435 | 18~40GHz | Jan. 20, 2016 | May 14, 2016 | Jan. 19, 2017 | Radiation (03CH02-KS) |
| AC Power Source | Chroma | 61601 | 61601000247 3 | N/A | NCR | May 14, 2016 | NCR | Radiation (03CH02-KS) |
| Turn Table | MF | MF7802 | N/A | 0~360 degree | NCR | May 14, 2016 | NCR | Radiation (03CH02-KS) |
| Antenna Mast | MF | MF7802 | N/A | 1 m~4 m | NCR | May 14, 2016 | NCR | Radiation (03CH02-KS) |

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

| | |
|--|-------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$) | 2.3dB |
|--|-------|

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| | |
|--|-------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$) | 5.1dB |
|--|-------|