



FCC RF Test Report

APPLICANT : TCL Communication Ltd
EQUIPMENT : GSM Quad-band / UMTS Quad-band / LTE 4 band mobile phone
BRAND NAME : ALCATEL ONETOUCH
MODEL NAME : 6045O
MARKETING NAME : ALCATEL ONETOUCH IDOL 3 (5.5)
FCC ID : 2ACCJN005
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(L), 27(H)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product completely tested on Aug. 24, 2015. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	6
1.1 Applicant.....	6
1.2 Manufacturer.....	6
1.3 Product Feature of Equipment Under Test.....	6
1.4 Product Specification subjective to this standard.....	7
1.5 Modification of EUT	8
1.6 Maximum Emission Designator, Frequency Tolerance, and ERP/EIRP Power	8
1.7 Testing Location	10
1.8 Applicable Standards.....	10
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	11
2.1 Test Mode.....	11
2.2 Connection Diagram of Test System.....	13
2.3 Support Unit used in test configuration and system	13
2.4 Measurement Results Explanation Example.....	13
3 CONDUCTED TEST ITEMS	14
3.1 Measuring Instruments	14
3.2 Test Setup	14
3.3 Test Result of Conducted Test.....	14
3.4 Conducted Output Power	15
3.5 Peak-to-Average Ratio	16
3.6 Occupied Bandwidth.....	17
3.7 Conducted Band Edge	18
3.8 Conducted Spurious Emission	20
3.9 Frequency Stability	21
4 RADIATED TEST ITEMS	22
4.1 Measuring Instruments	22
4.2 Test Setup	22
4.3 Test Result of Radiated Test	22
4.4 Effective Radiated Power and Effective Isotropic Radiated Power	23
4.5 Radiated Spurious Emission	25
5 LIST OF MEASURING EQUIPMENT	26
6 UNCERTAINTY OF EVALUATION.....	27
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	
APPENDIX D. PRODUCT EQUALITY DECLARATION	



REVISION HISTORY



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(g) §27.53(h)	Conducted Band Edge Measurement (Band 2) (Band 4) (Band 5) (Band 12)	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(g) §27.53(h)	Conducted Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12)	< 43+10log10(P[Watts])	PASS	-



Report Section	FCC Rule	Description	Limit	Result	Remark
3.9	§2.1055 §22.355 §24.235 §27.54	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22 Within Authorized Band	PASS	
4.4	§22.913(a)(2)	Effective Radiated Power (Band 5)	ERP < 7 Watt	PASS	
	§27.50(c)(10)	Effective Radiated Power (Band 12)	ERP < 3 Watt		
	§24.232(c)	Equivalent Isotropic Radiated Power (Band 2)	EIRP < 2Watt		
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4)	EIRP < 1Watt		
4.5	§2.1053 §22.917(a) §24.238(a) §27.53(g) §27.53(h)	Radiated Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12)	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 24.05 dB at 2116.000 MHz



1 General Description

1.1 Applicant

TCL Communication Ltd

FLAT/RM 1910-12A BLOCK 3 19/F CHINA HONG KONG CITY 33 CANTON ROAD TSIMSHATSUI KL

1.2 Manufacturer

TCL Communication Ltd

FLAT/RM 1910-12A BLOCK 3 19/F CHINA HONG KONG CITY 33 CANTON ROAD TSIMSHATSUI KL

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GSM Quad-band / UMTS Quad-band / LTE 4 band mobile phone
Brand Name	ALCATEL ONETOUCH
Model Name	6045O
Marketing Name	ALCATEL ONETOUCH IDOL 3 (5.5)
FCC ID	2ACCJN005
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+(Downlink Only)/LTE/NFC WLAN2.4GHz 802.11b/g/n HT20 WLAN5GHz 802.11a/n HT20/HT40 Bluetooth v3.0+EDR Bluetooth v4.1 LE
IMEI Code	Radiated: 014497000004012
HW Version	03
SW Version	5A18
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz
Rx Frequency	LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz
Bandwidth	LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 5 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 12 : 1.4MHz / 3MHz / 5MHz / 10MHz
Maximum Output Power to Antenna	LTE Band 2 : 22.67 dBm LTE Band 4 : 23.61 dBm LTE Band 5 : 23.45 dBm LTE Band 12 : 23.55 dBm
Type of Modulation	QPSK / 16QAM



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Emission Designator, Frequency Tolerance, and ERP/EIRP Power

LTE Band 2		QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	
1.4	1M10G7D	-	0.2023	1M10W7D	-	0.2213	
3	2M73G7D	-	0.2588	2M73W7D	-	0.2259	
5	4M51G7D	-	0.2415	4M50W7D	-	0.2009	
10	9M09G7D	0.0012	0.2404	9M05W7D	-	0.2138	
15	13M5G7D	-	0.2500	13M5W7D	-	0.2208	
20	18M4G7D	-	0.2529	18M5W7D	-	0.2173	

LTE Band 4		QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	
1.4	1M10G7D	-	0.3954	1M10W7D	-	0.2884	
3	2M73G7D	-	0.4295	2M73W7D	-	0.3373	
5	4M50G7D	-	0.4436	4M51W7D	-	0.3148	
10	9M07G7D	0.0058	0.4159	9M05W7D	-	0.3767	
15	13M5G7D	-	0.4027	13M5W7D	-	0.3184	
20	18M4G7D	-	0.3908	18M6W7D	-	0.3350	



LTE Band 5	QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	1M10G7D	-	0.0682	1M10W7D	-	0.0625
3	2M73G7D	-	0.0929	2M73W7D	-	0.0776
5	4M51G7D	-	0.0942	4M51W7D	-	0.0802
10	9M07G7D	0.0185	0.0920	9M05W7D	-	0.0733

LTE Band 12	QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	1M10G7D	-	0.0531	1M10W7D	-	0.0427
3	2M73G7D	-	0.0575	2M73W7D	-	0.0436
5	4M51G7D	-	0.0564	4M51W7D	-	0.0482
10	9M09G7D	0.0209	0.0522	9M03W7D	-	0.0457



1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sportun Site No.		FCC Registration No.
	TH01-KS	03CH02-KS	418269

Note: The test site complies with ANSI C63.4 2009 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L), 27(H)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.


Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v
	12	v	v	v	v	-	-	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	2						v	v	v	v			v	v	v
	4						v	v	v	v			v	v	v
	5				v	-	-	v	v	v			v	v	v
	12				v	-	-	v	v	v			v	v	v
26dB and 99% Bandwidth	2	v	v	v	v	v	v	v	v				v	v	v
	4	v	v	v	v	v	v	v	v				v	v	v
	5	v	v	v	v	-	-	v	v				v	v	v
	12	v	v	v	v	-	-	v	v				v	v	v
Conducted Band Edge	2	v	v	v	v	v	v	v	v	v	v		v	v	v
	4	v	v	v	v	v	v	v	v	v	v		v	v	v
	5	v	v	v	v	-	-	v	v	v			v	v	v
	12	v	v	v	v	-	-	v	v	v			v	v	v



Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Conducted Spurious Emission	2	v	v	v	v	v	v	v	v				v	v	v
	4	v	v	v	v	v	v	v	v				v	v	v
	5	v	v	v	v	-	-	v	v	v			v	v	v
	12	v	v	v	v	-	-	v	v	v			v	v	v
Frequency Stability	2				v			v				v		v	
	4				v			v				v		v	
	5				v	-	-	v				v		v	
	12				v	-	-	v				v		v	
E.R.P./ E.I.R.P.	2	v	v	v	v	v	v	v	v	v			v	v	v
	4	v	v	v	v	v	v	v	v	v			v	v	v
	5	v	v	v	v	-	-	v	v	v			v	v	v
	12	v	v	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	2	v	v	v	v	v	v	v	v	v				v	
	4	v	v	v	v	v	v	v	v	v				v	
	5	v	v	v	v	-	-	v		v				v	
	12	v	v	v	v	-	-	v		v				v	
Note	<ol style="list-style-type: none">The mark "v" means that this configuration is chosen for testingThe mark "-" means that this bandwidth is not supported.The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.														

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPD-2303S	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5 dB.

Example :

$$\text{Offset(dB)} = \text{RF cable loss(dB)}.$$

$$= 5 \text{ (dB)}$$


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

22.917(a) for Band 5

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a) for Band 2

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (g) for Band 12

For operations in the 698 -746 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 100 kHz bandwidth. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

27.53 (h) for Band 4

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.



3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13$ dBm.



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log(P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13$ dBm.



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25 \pm 5^\circ\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.



4.4 Effective Radiated Power and Effective Isotropic Radiated Power

4.4.1 Description of the ERP/EIRP Measurement

Effective radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-C-2004, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average ERP of 7 watts with LTE band 5 and 3 watts with LTE band 12.

Equivalent isotropic radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-C-2004, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average EIRP of 2 watts with LTE band 2 and 1 watt with LTE band 4.

4.4.2 Test Procedures

1. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
2. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



	LTE Average					
LTE BW	1.4M	3M	5M	10M	15M	20M
Span	3MHz	6MHz	10MHz	20MHz	30MHz	40MHz
RBW	30kHz	100kHz	100kHz	300kHz	300kHz	300kHz
VBW	100kHz	300kHz	300kHz	1MHz	1MHz	1MHz
Detector	RMS	RMS	RMS	RMS	RMS	RMS
Trace	Average	Average	Average	Average	Average	Average
Average Type	Power	Power	Power	Power	Power	Power
Sweep Count	100	100	100	100	100	100



4.5 Radiated Spurious Emission

4.5.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log(P)$ dB.

For LTE Band 12

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

$$\begin{aligned} \text{The limit line is derived from } & 43 + 10\log(P)\text{dB below the transmitter power P(Watts)} \\ & = P(\text{W}) - [43 + 10\log(P)] \text{ (dB)} \\ & = [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} \\ & = -13\text{dBm}. \end{aligned}$$

12. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
13. ERP (dBm) = EIRP - 2.15



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	9kHz~30GHz	May 04, 2014	Mar. 17, 2015~Mar. 23, 2015	May 03, 2015	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 25, 2014	Mar. 17, 2015~Mar. 23, 2015	Oct. 24, 2015	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max 30dBm	Sep. 29, 2014	Aug. 23, 2015~Aug. 24, 2015	Sep. 28, 2015	Radiation (03CH02-KS)
Spectrum Analyzer	R&S	FSV40	101040	10kHz~40GHz;Ma x 30dBm	Sep. 25, 2014	Aug. 23, 2015~Aug. 24, 2015	Sep. 24, 2015	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz~2GHz	Sep. 13, 2014	Aug. 23, 2015~Aug. 24, 2015	Sep. 12, 2015	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 08, 2014	Aug. 23, 2015~Aug. 24, 2015	Nov. 07, 2015	Radiation (03CH02-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 08, 2014	Aug. 23, 2015~Aug. 24, 2015	Nov. 07, 2015	Radiation (03CH02-KS)
SHF-EHF Horn	com-power	AH-840	101070	18GHz~40GHz	Sep. 04, 2014	Aug. 23, 2015~Aug. 24, 2015	Sep. 03, 2015	Radiation (03CH02-KS)
Amplifier	com-power	PA-103A	161069	1kHz~1000MHz / 32 dB	May 04, 2015	Aug. 23, 2015~Aug. 24, 2015	May 03, 2016	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1GHz~26.5GHz Gain 30dB	Oct. 28, 2014	Aug. 23, 2015~Aug. 24, 2015	Oct. 27, 2015	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Aug. 23, 2015~Aug. 24, 2015	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Aug. 23, 2015~Aug. 24, 2015	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Aug. 23, 2015~Aug. 24, 2015	NCR	Radiation (03CH02-KS)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{\text{C}}(y)$)	5.1 dB
---	--------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.10	21.78	21.68
1.4	1	2		22.31	21.93	21.78
1.4	1	5		22.20	22.08	21.78
1.4	3	0		22.16	22.17	22.07
1.4	3	1		22.46	22.28	22.08
1.4	3	2		22.29	22.16	22.02
1.4	6	0		20.41	20.43	20.42
1.4	1	0		21.18	21.20	21.80
1.4	1	2	16-QAM	20.98	21.51	21.75
1.4	1	5		20.95	21.29	21.59
1.4	3	0		21.06	21.09	20.95
1.4	3	1		21.17	21.19	21.11
1.4	3	2		21.10	21.25	21.06
1.4	6	0		19.45	19.53	19.75
3	1	0	QPSK	22.13	22.09	21.87
3	1	7		22.57	22.66	21.83
3	1	14		22.17	22.14	22.15
3	8	0		20.47	20.44	20.46
3	8	4		20.45	20.49	20.41
3	8	7		20.44	20.43	20.43
3	15	0		20.40	20.41	20.41
3	1	0		21.10	20.95	21.01
3	1	7	16-QAM	21.83	21.21	21.00
3	1	14		21.63	21.16	20.92
3	8	0		19.55	19.52	19.64
3	8	4		19.47	19.46	19.60
3	8	7		19.42	19.43	19.56
3	15	0		19.45	19.46	19.45



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.85	22.12	21.82
	1	12		22.08	21.83	21.87
	1	24		21.89	22.13	21.77
	12	0		20.48	20.48	20.48
	12	6		20.45	20.46	20.44
	12	11		20.41	20.42	20.45
	25	0		20.43	20.41	20.43
5	1	0	16-QAM	21.59	21.32	20.84
	1	12		21.31	21.77	21.08
	1	24		21.12	21.39	21.26
	12	0		19.62	19.62	19.57
	12	6		19.57	19.56	19.55
	12	11		19.45	19.57	19.53
	25	0		19.42	19.46	19.49
10	1	0	QPSK	22.50	22.24	22.27
	1	24		22.39	22.37	22.21
	1	49		22.19	22.05	21.91
	25	0		20.45	20.45	20.47
	25	12		20.44	20.44	20.44
	25	24		20.42	20.41	20.42
	50	0		20.41	20.42	20.41
10	1	0	16-QAM	20.81	21.42	21.60
	1	24		21.22	21.14	21.30
	1	49		20.60	21.62	21.13
	25	0		19.44	19.51	19.56
	25	12		19.42	19.49	19.52
	25	24		19.46	19.44	19.50
	50	0		19.52	19.42	19.46



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.36	22.16	22.07
	1	37		22.50	21.95	21.91
	1	74		21.90	21.97	21.83
	36	0		20.46	20.45	20.45
	36	18		20.43	20.42	20.42
	36	37		20.41	20.42	20.43
	75	0		20.43	20.43	20.42
15	1	0	16-QAM	21.93	21.14	21.66
	1	37		21.83	21.07	21.20
	1	74		21.39	21.28	21.48
	36	0		19.57	19.58	19.58
	36	18		19.59	19.50	19.49
	36	37		19.55	19.46	19.45
	75	0		19.42	19.46	19.62
20	1	0	QPSK	22.44	22.67	22.03
	1	49		21.98	22.39	21.78
	1	99		22.04	22.26	21.76
	50	0		20.48	20.59	20.52
	50	24		20.45	20.45	20.48
	50	49		20.46	20.42	20.44
	100	0		20.42	20.66	20.42
20	1	0	16-QAM	21.40	20.98	21.85
	1	49		21.14	20.67	21.29
	1	99		21.15	20.85	21.29
	50	0		19.54	19.52	19.64
	50	24		19.51	19.59	19.62
	50	49		19.48	19.43	19.57
	100	0		19.43	19.44	19.48



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.28	23.26	23.08
	1	2		23.32	23.46	23.05
	1	5		23.31	23.23	22.95
	3	0		23.30	23.31	23.17
	3	1		23.28	23.36	23.24
	3	2		23.29	23.39	23.19
	6	0		22.32	22.26	22.21
1.4	1	0	16-QAM	22.20	22.90	22.41
	1	2		22.17	22.00	22.26
	1	5		22.08	21.93	22.40
	3	0		22.08	21.96	22.17
	3	1		22.29	21.81	22.24
	3	2		22.12	22.04	22.38
	6	0		21.04	21.08	21.28
3	1	0	QPSK	23.24	22.99	22.94
	1	7		23.36	23.30	23.09
	1	14		23.32	23.28	23.04
	8	0		22.34	22.37	22.31
	8	4		22.43	22.34	22.20
	8	7		22.47	22.37	22.23
	15	0		22.30	22.34	22.22
3	1	0	16-QAM	21.97	22.57	22.28
	1	7		22.04	22.54	22.38
	1	14		22.90	22.55	22.28
	8	0		21.55	21.44	21.24
	8	4		21.49	21.38	21.11
	8	7		21.64	21.50	21.15
	15	0		21.23	21.53	20.85



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.22	23.17	23.15
	1	12		23.24	23.07	23.26
	1	24		23.17	23.06	22.88
	12	0		22.33	22.24	22.27
	12	6		22.46	22.36	22.25
	12	11		22.37	22.24	22.15
	25	0		22.36	22.36	22.30
5	1	0	16-QAM	22.29	22.46	22.36
	1	12		22.17	22.40	22.53
	1	24		22.20	22.35	21.73
	12	0		21.38	21.31	21.34
	12	6		21.41	21.31	21.25
	12	11		21.48	21.40	21.15
	25	0		21.35	21.42	21.42
10	1	0	QPSK	23.16	23.30	23.29
	1	24		22.90	23.32	22.98
	1	49		22.56	23.29	22.92
	25	0		22.47	22.35	22.42
	25	12		22.41	22.36	22.24
	25	24		22.39	22.34	22.17
	50	0		22.43	22.35	22.34
10	1	0	16-QAM	22.54	22.55	22.70
	1	24		22.45	22.47	22.37
	1	49		22.06	22.48	22.37
	25	0		21.44	21.46	21.52
	25	12		21.53	21.51	21.35
	25	24		21.65	21.47	21.46
	50	0		21.46	21.43	21.38



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.42	23.16	23.38
	1	37		23.30	23.13	23.19
	1	74		23.21	23.09	23.16
	36	0		22.46	22.38	22.37
	36	18		22.37	22.28	22.31
	36	37		22.23	22.23	22.23
	75	0		22.38	22.31	22.29
15	1	0	16-QAM	22.90	22.62	22.63
	1	37		22.94	22.57	22.55
	1	74		22.92	22.48	22.26
	36	0		21.56	21.44	21.42
	36	18		21.46	21.42	21.39
	36	37		21.33	21.45	21.18
	75	0		21.39	21.45	21.26
20	1	0	QPSK	23.34	23.61	23.26
	1	49		23.23	23.60	23.18
	1	99		23.01	23.34	23.20
	50	0		22.29	22.38	22.35
	50	24		22.25	22.26	22.32
	50	49		22.25	22.30	22.25
	100	0		22.27	22.35	22.32
20	1	0	16-QAM	22.82	22.40	22.12
	1	49		22.80	22.38	22.07
	1	99		22.77	22.34	22.11
	50	0		21.60	21.35	21.33
	50	24		21.39	21.34	21.27
	50	49		21.23	21.24	21.25
	100	0		21.58	21.41	21.31



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.02	23.13	23.07
	1	2		23.16	23.38	23.05
	1	5		22.95	23.15	23.10
	3	0		23.07	23.43	23.34
	3	1		23.20	23.41	23.31
	3	2		23.16	23.36	23.25
	6	0		22.21	22.37	22.28
1.4	1	0	16-QAM	22.07	22.74	22.40
	1	2		21.89	22.50	22.45
	1	5		21.89	22.46	21.90
	3	0		22.54	22.66	22.66
	3	1		22.70	22.83	22.78
	3	2		22.67	22.87	22.81
	6	0		21.04	20.98	21.26
3	1	0	QPSK	22.94	23.05	23.06
	1	7		23.34	23.12	23.33
	1	14		23.33	23.03	23.30
	8	0		22.23	22.23	22.25
	8	4		22.19	22.39	22.40
	8	7		22.27	22.30	22.24
	15	0		22.19	22.21	22.21
3	1	0	16-QAM	21.82	22.59	21.91
	1	7		21.90	22.54	22.09
	1	14		21.78	22.23	22.58
	8	0		21.22	21.36	21.08
	8	4		21.16	21.41	21.29
	8	7		21.27	21.24	21.50
	15	0		21.23	21.01	21.14



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.92	23.22	23.14
	1	12		23.15	23.36	23.22
	1	24		22.73	22.82	22.84
	12	0		22.11	22.15	22.18
	12	6		22.17	22.14	22.27
	12	11		22.20	22.15	22.19
	25	0		22.15	22.24	22.18
5	1	0	16-QAM	22.01	22.11	22.33
	1	12		22.17	22.56	22.42
	1	24		22.12	22.40	22.27
	12	0		20.97	21.12	21.13
	12	6		20.84	21.12	20.96
	12	11		20.87	21.46	20.97
	25	0		21.04	21.03	21.22
10	1	0	QPSK	23.16	23.23	23.30
	1	24		23.35	23.45	23.32
	1	49		23.19	23.14	23.30
	25	0		22.33	22.37	22.30
	25	12		22.17	22.29	22.19
	25	24		22.24	22.28	22.20
	50	0		22.22	22.30	22.21
10	1	0	16-QAM	22.38	22.94	22.39
	1	24		21.94	21.93	22.35
	1	49		22.31	22.47	22.36
	25	0		21.01	21.13	21.19
	25	12		21.28	21.06	21.05
	25	24		21.32	20.96	21.06
	50	0		21.10	21.13	21.08



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.29	23.05	23.26
	1	2		23.30	23.11	23.37
	1	5		23.12	23.21	23.27
	3	0		23.28	23.41	23.40
	3	1		23.26	23.47	23.51
	3	2		23.24	23.39	23.31
	6	0		22.20	22.31	22.25
1.4	1	0	16-QAM	22.93	22.92	22.60
	1	2		22.25	22.93	22.68
	1	5		22.26	22.84	22.61
	3	0		22.57	22.34	22.35
	3	1		22.74	22.40	22.34
	3	2		22.74	22.34	22.34
	6	0		21.02	20.86	20.90
3	1	0	QPSK	23.16	23.15	23.09
	1	7		23.26	23.37	23.42
	1	14		23.22	23.15	23.17
	8	0		22.39	22.27	22.42
	8	4		22.28	22.24	22.31
	8	7		22.35	22.31	22.42
	15	0		22.31	22.34	22.37
3	1	0	16-QAM	22.69	22.90	22.39
	1	7		22.58	22.23	22.60
	1	14		22.59	22.22	22.42
	8	0		21.51	21.51	21.53
	8	4		21.49	21.33	21.56
	8	7		21.48	21.31	21.66
	15	0		21.41	21.10	21.44



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.15	23.20	23.16
	1	12		23.32	23.40	23.28
	1	24		23.19	23.01	23.30
	12	0		22.28	22.30	22.42
	12	6		22.40	22.33	22.45
	12	11		22.38	22.36	22.46
	25	0		22.33	22.31	22.38
5	1	0	16-QAM	22.12	22.28	22.12
	1	12		22.22	22.35	22.13
	1	24		22.15	22.36	22.34
	12	0		21.06	21.32	21.40
	12	6		21.08	21.28	21.32
	12	11		21.05	21.27	21.38
	25	0		21.17	21.22	21.25
10	1	0	QPSK	23.42	23.38	23.55
	1	24		23.24	23.19	23.34
	1	49		23.18	23.17	23.33
	25	0		22.26	22.29	22.39
	25	12		22.32	22.34	22.38
	25	24		22.30	22.26	22.37
	50	0		22.32	22.35	22.37
10	1	0	16-QAM	22.54	22.56	22.92
	1	24		22.46	22.48	22.58
	1	49		22.65	22.42	22.83
	25	0		21.28	21.35	21.43
	25	12		21.34	21.50	21.52
	25	24		21.35	21.48	21.63
	50	0		21.21	21.16	21.21


**Peak-to-Average Ratio**


Mode	LTE Band 2 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.39	4.78	4.64	5.88	PASS
Middle CH	3.77	4.55	4.96	5.48	
Highest CH	3.33	4.93	4.46	5.88	


Mode	LTE Band 4 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	RB Size	Result
Lowest CH	3.94	5.04	4.41	6.03	PASS
Middle CH	4.52	5.13	5.42	6.12	
Highest CH	4.70	4.64	5.62	5.80	


Mode	LTE Band 5 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	RB Size	Result
Lowest CH	4.87	5.33	5.30	6.26	PASS
Middle CH	4.84	5.48	5.91	6.35	
Highest CH	4.90	5.39	6.09	6.38	


Mode	LTE Band 12 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	RB Size	Result
Lowest CH	3.80	4.81	4.26	5.59	PASS
Middle CH	4.14	4.81	4.99	5.68	
Highest CH	4.23	4.78	5.30	5.71	






















26dB Bandwidth

Mode	LTE Band 2 : 26dB BW(MHz)											
	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.298	1.306	3.039	3.051	5.055	5.045	10.070	9.990	14.685	14.685	20.180	20.340
Middle CH	1.295	1.290	3.045	3.045	5.055	5.025	9.990	9.970	14.745	14.685	20.340	20.140
Highest CH	1.306	1.309	3.057	3.045	5.055	5.045	10.070	9.970	14.685	14.715	20.300	20.260

Mode	LTE Band 4 : 26dB BW(MHz)											
	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.284	1.304	3.057	3.057	5.035	5.045	10.050	9.970	14.505	14.565	20.180	20.140
Middle CH	1.301	1.304	3.045	3.051	5.045	5.045	10.070	9.910	14.625	14.715	20.180	20.220
Highest CH	1.304	1.306	3.051	3.069	5.045	5.055	10.030	9.930	14.625	14.625	20.180	20.180

Mode	LTE Band 5 : 26dB BW(MHz)											
	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.295	1.292	3.051	3.057	5.045	5.035	10.010	10.030	-	-	-	-
Middle CH	1.301	1.290	3.051	3.063	5.065	5.035	10.150	9.970	-	-	-	-
Highest CH	1.298	1.290	3.051	3.051	5.025	5.005	9.990	9.970	-	-	-	-

Mode	LTE Band 12 : 26dB BW(MHz)											
	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.298	1.306	3.045	3.051	5.045	5.055	10.070	9.990	-	-	-	-
Middle CH	1.273	1.304	3.045	3.051	5.035	5.055	9.970	10.010	-	-	-	-
Highest CH	1.276	1.309	3.051	3.057	5.035	5.025	9.990	9.970	-	-	-	-

