

FCC RF Test Report

APPLICANT : TCL Communication Ltd.
EQUIPMENT : Tablet PC
BRAND NAME : ALCATEL ONETOUCH
MODEL NAME : 9006W
MARKETING NAME : ONETOUCH PIXI 2 (7)
FCC ID : 2ACCJB014
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Apr. 01, 2015 and testing was completed on May 13, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification subjective to this standard	6
1.5 Specification of Accessory.....	6
1.6 Modification of EUT	6
1.7 Testing Location	7
1.8 Applicable Standards.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	9
2.1 Descriptions of Test Mode	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	13
3 TEST RESULT	14
3.1 Number of Channel Measurement	14
3.2 Hopping Channel Separation Measurement	16
3.3 Dwell Time Measurement.....	23
3.4 20dB Bandwidth Measurement	26
3.5 Peak Output Power Measurement	33
3.6 Conducted Band Edges Measurement	35
3.7 Conducted Spurious Emission Measurement	42
3.8 Radiated Band Edges and Spurious Emission Measurement	52
3.9 AC Conducted Emission Measurement.....	58
3.10 Antenna Requirements.....	62
4 LIST OF MEASURING EQUIPMENT.....	63
5 UNCERTAINTY OF EVALUATION.....	64
APPENDIX A. RADIATED SPURIOUS EMISSION	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR540109A	Rev. 01	Initial issue of report	May 15, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 13.82 dB at 63.750 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 3.85 dB at 0.520 MHz
0	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

TCL Communication Ltd.

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

1.2 Manufacturer

TCL Communication Ltd.

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Brand Name	ALCATEL ONETOUCH
Model Name	9006W
Marketing Name	ONETOUCH PIXI 2 (7)
FCC ID	2ACCJB014
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(Downlink Only)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/ WLAN 5GHz 802.11a/n HT20/HT40/ Bluetooth v3.0 + EDR/Bluetooth v4.1 LE
IMEI Number	Conducted: 014399000021048 Radiation: 014399000021063 Conduction: 014399000021071
HW Version	V03
SW Version	B2E
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 7.11 dBm (0.00514 W) Bluetooth EDR (2Mbps) : 7.09 dBm (0.00512 W) Bluetooth EDR (3Mbps) : 7.67 dBm (0.00585 W)
Antenna Type / Gain	IFA Antenna with gain 1.5 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.5 Specification of Accessory

Specification of Accessory				
AC Adapter	Brand Name	ALCATEL onetouch	Model Name	UC13US
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5Vdc, 2000mA		
	P/N	CBA0059AG0C1		
Battery	Brand Name	ALCATEL onetouch	Model Name	TLp032B2
	Power Rating	3.7Vdc, 3240mAh		
	P/N	C3240009C2YHYKFG		
USB Cable	Brand Name	NA	Model Name	NA
	Signal Line Type	0.8m shielded without core		

1.6 Modification of EUT

No modifications are made to the EUT during all test items.



1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	
	TH01-SZ	CO01-SZ

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978	
Test Site No.	Sporton Site No.	FCC Registration No.
	03CH05-HY	TW1022

Note: The test site complies with ANSI C63.4 2009 requirement.



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. FCC permits the use of the 1.5 meter table as an alternative in C63.10-2013 through inquiry tracking number 961829.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	6.94 dBm	6.94 dBm	7.52 dBm
Ch39	2441MHz	7.11 dBm	7.09 dBm	7.67 dBm
Ch78	2480MHz	6.49 dBm	6.49 dBm	7.09 dBm

Remark:

1. All the test data for each data rate were verified, but only the worst case was reported.
 2. The data rate was set in 3Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (Z plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.


2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps π /4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
	Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :GPRS850 Idle + Bluetooth Link + WLAN Link + Earphone + Battery + USB Cable (Charging from Adapter)		
Remark:			
1. For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.			
2. For Radiated Test Cases, The tests were performance with Adapter, Earphone, and USB Cable.			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth BaseStation	R&S	CBT	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
4.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	iPod Earphone	Apple	MC690ZP/A	FCC DoC	Unshielded, 1.6 m	N/A
6.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5.0 + 10 = 15.0 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW \geq 1% of the span; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency


Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Tiny You	Relative Humidity :	50~53%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 17.APR.2015 00:49:15



Date: 17.APR.2015 00:58:00

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
 $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.


3.2.4 Test Setup



**3.2.5 Test Result of Hopping Channel Separation**

Test Mode :	1Mbps	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.6053	Pass
39	2441	1.002	0.6053	Pass
78	2480	1.002	0.6027	Pass

Channel Separation Plot on Channel 00 - 01

Date: 16.APR.2015 20:42:26




Channel Separation Plot on Channel 39 - 40



Date: 16.APR.2015 20:43:56

Channel Separation Plot on Channel 77 - 78




Date: 16.APR.2015 20:13:31



Test Mode :	2Mbps	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8440	Pass
39	2441	1.002	0.8440	Pass
78	2480	1.002	0.8440	Pass

Channel Separation Plot on Channel 00 - 01

Date: 16.APR.2015 21:10:47




Channel Separation Plot on Channel 39 - 40



Date: 16.APR.2015 20:15:26

Channel Separation Plot on Channel 77 - 78




Date: 16.APR.2015 20:16:22



Test Mode :	3Mbps	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.008	0.8240	Pass
39	2441	1.002	0.8240	Pass
78	2480	1.002	0.8240	Pass

Channel Separation Plot on Channel 00 - 01

Date: 16.APR.2015 20:17:33




Channel Separation Plot on Channel 39 - 40



Date: 16.APR.2015 20:18:27

Channel Separation Plot on Channel 77 - 78



Date: 16.APR.2015 21:54:18

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Test Mode :	3DH5	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%


Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.912	0.31	0.4	Pass
AFH	20	53.33	2.912	0.16	0.4	Pass

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.
With channel hopping rate $(1600 / 6 / 79)$ in Occupancy Time Limit (0.4×79) (s),
Hops Over Occupancy Time comes to $(1600 / 6 / 79) \times (0.4 \times 79) = 106.67$ hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate $(800 / 6 / 20)$ in Occupancy Time Limit (0.4×20) (s),
Hops Over Occupancy Time comes to $(800 / 6 / 20) \times (0.4 \times 20) = 53.33$ hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Package Transfer Time Plot



Date: 16.APR.2015 22:01:28

3.4 20dB Bandwidth Measurement

3.4.1 Limit of 20dB Bandwidth

Reporting only


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Measure and record the results in the test report.


3.4.4 Test Setup



**3.4.5 Test Result of 20dB Bandwidth**

Test Mode :	1Mbps	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.908
39	2441	0.908
78	2480	0.904

20 dB Bandwidth Plot on Channel 00

Date: 16.APR.2015 20:21:48




20 dB Bandwidth Plot on Channel 39



Date: 16.APR.2015 20:22:10

20 dB Bandwidth Plot on Channel 78




Date: 16.APR.2015 20:23:03



Test Mode :	2Mbps	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.266
39	2441	1.266
78	2480	1.266

20 dB Bandwidth Plot on Channel 00

Date: 16.APR.2015 20:24:01




20 dB Bandwidth Plot on Channel 39



Date: 16.APR.2015 20:24:17

20 dB Bandwidth Plot on Channel 78




Date: 16.APR.2015 20:25:09



Test Mode :	3Mbps	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.236
39	2441	1.236
78	2480	1.236

20 dB Bandwidth Plot on Channel 00

Date: 16.APR.2015 20:27:03




20 dB Bandwidth Plot on Channel 39



Date: 13.MAY.2015 16:10:15

20 dB Bandwidth Plot on Channel 78



Date: 16.APR.2015 20:28:39

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	6.94	20.97	Pass
39	2441	7.11	20.97	Pass
78	2480	6.49	20.97	Pass

Test Mode :	2Mbps	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	6.94	20.97	Pass
39	2441	7.09	20.97	Pass
78	2480	6.49	20.97	Pass

Test Mode :	3Mbps	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	7.52	20.97	Pass
39	2441	7.67	20.97	Pass
78	2480	7.09	20.97	Pass

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz ($\geq 1\%$ span=10MHz), VBW = 300kHz (\geq RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup




**3.6.5 Test Result of Conducted Band Edges**

Test Mode :	1Mbps	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	50~53%
		Test Engineer :	Tiny You

Low Band Edge Plot on Channel 00


Date: 16.APR.2015 20:44:46

High Band Edge Plot on Channel 78


Date: 16.APR.2015 20:48:06



Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	50~53%
		Test Engineer :	Tiny You

Low Band Edge Plot on Channel 00


Date: 16.APR.2015 21:11:07

High Band Edge Plot on Channel 78


Date: 16.APR.2015 21:04:25



Test Mode :	3Mbps	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	50~53%
		Test Engineer :	Tiny You

Low Band Edge Plot on Channel 00


Date: 16.APR.2015 21:45:52

High Band Edge Plot on Channel 78


Date: 16.APR.2015 21:49:19

**3.6.6 Test Result of Conducted Hopping Mode Band Edges**

Test Mode :	1Mbps	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%

1Mbps Hopping Mode Low Band Edge Plot


Date: 16.APR.2015 20:47:42

1Mbps Hopping Mode High Band Edge Plot


Date: 16.APR.2015 20:49:34



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Tiny You	Relative Humidity :	50~53%

2Mbps Hopping Mode Low Band Edge Plot


Date: 16.APR.2015 21:14:03

2Mbps Hopping Mode High Band Edge Plot


Date: 16.APR.2015 21:09:23



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Tiny You	Relative Humidity :	50~53%

3Mbps Hopping Mode Low Band Edge Plot

Date: 16.APR.2015 21:48:56

3Mbps Hopping Mode High Band Edge Plot

Date: 16.APR.2015 21:51:06

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows the guidelines in Spurious RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup






3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	24~26℃
Test Channel :	00	Relative Humidity :	50~53%
		Test Engineer :	Tiny You

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 16.APR.2015 20:35:00


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 16.APR.2015 20:35:52



Test Mode :	1Mbps	Temperature :	24~26℃
Test Channel :	39	Relative Humidity :	50~53%
		Test Engineer :	Tiny You

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 16.APR.2015 20:36:44

1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 16.APR.2015 20:37:36



Test Mode :	1Mbps	Temperature :	24~26℃
Test Channel :	78	Relative Humidity :	50~53%
		Test Engineer :	Tiny You

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 16.APR.2015 20:38:28

1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 16.APR.2015 20:39:19



Test Mode :	2Mbps	Temperature :	24~26℃
Test Channel :	00	Relative Humidity :	50~53%
		Test Engineer :	Tiny You

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz

Date: 16.APR.2015 21:28:28

2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz

Date: 16.APR.2015 21:29:19



Ref 20 dBm Att 20 dB SWT 300 ms 2.245620000 GHz

20 Offset 15 dB

1 PK VIEW

Marker 1 [T1] -47.27 dBm

01 -15.25 dBm

Start 30 MHz Stop 3 GHz

* RBW 100 kHz Marker 1 [T1] -36.33 dBm
 * VBW 300 kHz
 * Att 20 dB SWT 2.3 μs 13.684000000 GHz

Ref 20 dBm Offset 15 dB

1 PA
 1500

01 -15.2 dBm


2.3 GHz/

Start 2 GHz Stop 25 GHz


Page Number : 47 of 64
Report Issued Date : May 15, 2015
Report Version : Rev. 01



Test Mode :	2Mbps	Temperature :	24~26℃
Test Channel :	78	Relative Humidity :	50~53%
		Test Engineer :	Tiny You

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 16.APR.2015 21:31:55

2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 16.APR.2015 21:32:47



Test Mode :	3Mbps	Temperature :	24~26℃
Test Channel :	00	Relative Humidity :	50~53%
		Test Engineer :	Tiny You

3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz


Date: 16.APR.2015 21:40:50

3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 16.APR.2015 21:41:42



Test Mode :	3Mbps	Temperature :	24~26℃
Test Channel :	39	Relative Humidity :	50~53%
		Test Engineer :	Tiny You

3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 16.APR.2015 21:42:34

3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 16.APR.2015 21:43:26



Test Mode :	3Mbps	Temperature :	24~26℃
Test Channel :	78	Relative Humidity :	50~53%
		Test Engineer :	Tiny You

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz

Date: 16.APR.2015 21:38:27

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz

Date: 16.APR.2015 21:39:19

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures

1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
7. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20\log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


3.8.6 Duty cycle correction factor for average measurement

3DH5 on time (One Pulse) Plot on Channel 39



Date: 28.APR.2015 21:52:01

3DH5 on time (Count Pulses) Plot on Channel 39



Date: 28.APR.2015 21:53:17

Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100\text{ms}) = -24.79 \text{ dB}$$

3.8.7 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.9.4 Test Setup





3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	21~22°C
Test Engineer :	Jack Tian	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GPRS850 Idle + Bluetooth Link + WLAN Link + Earphone + Battery + USB Cable (Charging from Adapter)		




Site : C001-SZ
Condition: FCC 15C_QP LISN_L_20140304 LINE

Mode : Mode 1
IMEI : 014399000021071

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.52	40.14	-5.86	46.00	29.71	0.28	10.15	Average
2 *	0.52	51.34	-4.66	56.00	40.91	0.28	10.15	QP
3	0.55	31.92	-14.08	46.00	21.50	0.27	10.15	Average
4	0.55	41.52	-14.48	56.00	31.10	0.27	10.15	QP
5	1.11	28.81	-17.19	46.00	18.40	0.25	10.16	Average
6	1.11	42.41	-13.59	56.00	32.00	0.25	10.16	QP
7	1.34	27.31	-18.69	46.00	16.90	0.24	10.17	Average
8	1.34	41.11	-14.89	56.00	30.70	0.24	10.17	QP
9	1.45	27.51	-18.49	46.00	17.10	0.24	10.17	Average
10	1.45	41.41	-14.59	56.00	31.00	0.24	10.17	QP
11	1.52	28.51	-17.49	46.00	18.10	0.24	10.17	Average
12	1.52	42.41	-13.59	56.00	32.00	0.24	10.17	QP
13	1.72	27.81	-18.19	46.00	17.40	0.23	10.18	Average
14	1.72	41.51	-14.49	56.00	31.10	0.23	10.18	QP



Test Mode :	Mode 1	Temperature :	21~22℃
Test Engineer :	Jack Tian	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GPRS850 Idle + Bluetooth Link + WLAN Link + Earphone + Battery + USB Cable (Charging from Adapter)		



Site : C001-SZ
Condition: FCC 15C_QP LISN_N_20140304 NEUTRAL

Mode : Mode 1
IMEI : 014399000021071

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.52	42.15	-3.85	46.00	31.60	0.39	10.16	Average
2	0.52	47.25	-8.75	56.00	36.70	0.39	10.16	QP
3	0.59	35.18	-10.82	46.00	24.70	0.33	10.15	Average
4	0.59	40.28	-15.72	56.00	29.80	0.33	10.15	QP
5	1.13	32.79	-13.21	46.00	22.29	0.34	10.16	Average
6	1.13	40.09	-15.91	56.00	29.59	0.34	10.16	QP
7	1.34	34.21	-11.79	46.00	23.69	0.35	10.17	Average
8	1.34	42.11	-13.89	56.00	31.59	0.35	10.17	QP
9	1.50	34.03	-11.97	46.00	23.51	0.35	10.17	Average
10	1.50	41.43	-14.57	56.00	30.91	0.35	10.17	QP
11	1.67	34.04	-11.96	46.00	23.50	0.36	10.18	Average
12	1.67	41.04	-14.96	56.00	30.50	0.36	10.18	QP



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~40GHz	Jan. 28, 2015	Apr. 16, 2015~ May 13, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Jan. 28, 2015	Apr. 16, 2015~ May 13, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Jan. 28, 2015	Apr. 16, 2015~ May 13, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 09, 2014	Apr. 28, 2015	Jun. 08, 2015	Radiation (03CH05-HY)
Bilog Antenna	Schaffner	CBL6111C	2725	30MHz~1GHz	Sep. 27, 2014	Apr. 28, 2015	Sep. 26, 2015	Radiation (03CH05-HY)
Horn Antenna	ESCO	3117	00066584	1GHz~18GHz	Aug. 30, 2014	Apr. 28, 2015	Aug. 29, 2015	Radiation (03CH05-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	18GHz~40GHz	Oct. 02, 2014	Apr. 28, 2015	Oct. 01, 2015	Radiation (03CH05-HY)
Preamplifier	COM-POWER	PA-103A	161075	10MHz~1GHz	Apr. 09, 2015	Apr. 28, 2015	Apr. 08, 2016	Radiation (03CH05-HY)
Preamplifier	MITEQ	AMF-7D-00 101800-30- 10P	1590074	100kHz~18GHz	Jul. 07, 2014	Apr. 28, 2015	Jul. 06, 2015	Radiation (03CH05-HY)
Preamplifier	COM-POWER	PA-103	161075	9kHz~30MHz	Apr. 09, 2015	Apr. 28, 2015	Apr. 08, 2016	Radiation (03CH05-HY)
Preamplifier	Miteq	TTA0204	1872107	18GHz~40GHz	May 23, 2014	Apr. 28, 2015	May 22, 2015	Radiation (03CH05-HY)
Turn Table	HD	HD100	420/611	0 - 360 degree	N/A	Apr. 28, 2015	N/A	Radiation (03CH05-HY)
Antenna Mast	HD	HD100	240/666	1 m - 4 m	N/A	Apr. 28, 2015	N/A	Radiation (03CH05-HY)
Loop Antenna	R&S	HFH2-Z2	100315	9 kHz~30 MHz	Jul. 28, 2014	Apr. 28, 2015	Jul. 27, 2015	Radiation (03CH05-HY)
EMI Receiver	R&S	ESC17	100724	9kHz~3GHz	Jan. 28, 2015	Apr. 16, 2015	Jan. 27, 2016	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	103892	9kHz~30MHz	Feb. 02, 2015	Apr. 16, 2015	Feb. 01, 2016	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	AN3016	16850	9kHz~30MHz	Feb. 02, 2015	Apr. 16, 2015	Feb. 01, 2016	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	6160200008 91	100Vac~250Vac	Sep. 29, 2014	Apr. 16, 2015	Sep. 28, 2015	Conduction (CO01-SZ)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------



Appendix A. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2326.64	49.28	-24.72	74	43.33	33.11	6.54	33.7	312	55	P	H
		2326.64	24.49	-29.51	54	-	-	-	-	-	-	A	H
	*	2402	103.94	-	-	97.92	33.02	6.65	33.65	312	55	P	H
	*	2402	79.15	-	-	-	-	-	-	-	-	A	H
		2371.36	49.01	-24.99	74	42.98	33.04	6.65	33.66	390	258	P	V
		2371.36	24.22	-29.78	54	-	-	-	-	-	-	A	V
	*	2402	104.67	-	-	98.65	33.02	6.65	33.65	390	258	P	V
	*	2402	79.88	-	-	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		2367.38	49.21	-24.79	74	43.23	33.07	6.59	33.68	296	55	P	H
		2367.38	24.42	-29.58	54	-	-	-	-	-	-	A	H
	*	2441	103.7	-	-	97.64	32.96	6.7	33.6	296	55	P	H
	*	2441	78.91	-	-	-	-	-	-	-	-	A	H
		2488.79	48.67	-25.33	74	42.52	32.9	6.81	33.56	296	55	P	H
		2488.79	23.88	-30.12	54	-	-	-	-	-	-	A	H
		2312.85	49.49	-24.51	74	43.54	33.13	6.54	33.72	378	277	P	V
		2312.85	24.7	-29.3	54	-	-	-	-	-	-	A	V
	*	2441	103.5	-	-	97.44	32.96	6.7	33.6	378	277	P	V
	*	2441	78.71	-	-	-	-	-	-	-	-	A	V
		2493.54	48.66	-25.34	74	42.51	32.9	6.81	33.56	378	277	P	V
		2493.54	23.87	-30.13	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	101.23	-	-	95.12	32.92	6.76	33.57	374	62	P	H
	*	2480	76.44	-	-	-	-	-	-	-	-	A	H
		2483.5	59.06	-14.94	74	52.95	32.92	6.76	33.57	374	62	P	H
		2483.5	34.27	-19.73	54	-	-	-	-	-	-	A	H
	*	2480	102.97	-	-	96.86	32.92	6.76	33.57	100	239	P	V
	*	2480	78.18	-	-	-	-	-	-	-	-	A	V
		2483.5	59.14	-14.86	74	53.03	32.92	6.76	33.57	100	239	P	V
		2483.5	34.35	-19.65	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4803	39.17	-34.83	74	55.65	32.51	9.65	58.64	100	0	P	H
		4803	14.38	-39.62	54	-	-	-	-	-	-	A	H
		4803	39.35	-34.65	74	55.83	32.51	9.65	58.64	100	0	P	V
		4803	14.56	-39.44	54	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		4881	40.01	-33.99	74	56.21	32.58	9.74	58.52	100	0	P	H
		4881	15.22	-38.78	54	-	-	-	-	-	-	A	H
		7323	42.83	-31.17	74	55.1	34.07	11.85	58.19	100	0	P	H
		7323	18.04	-35.96	54	-	-	-	-	-	-	A	H
		4881	39.81	-34.19	74	56.01	32.58	9.74	58.52	100	0	P	V
		4881	15.02	-38.98	54	-	-	-	-	-	-	A	V
		7323	41.33	-32.67	74	53.6	34.07	11.85	58.19	100	0	P	V
		7323	16.54	-37.46	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4959	39.68	-34.32	74	55.54	32.67	9.83	58.36	100	0	P	H
		4959	14.89	-39.11	54	-	-	-	-	-	-	A	H
		7440	40.95	-33.05	74	53.21	34.09	12.06	58.41	100	0	P	H
		7440	16.16	-37.84	54	-	-	-	-	-	-	A	H
		4959	40.13	-33.87	74	55.99	32.67	9.83	58.36	100	0	P	V
		4959	15.34	-38.66	54	-	-	-	-	-	-	A	V
		7440	40.79	-33.21	74	53.05	34.09	12.06	58.41	100	0	P	V
		7440	16	-38	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		97.23	23.31	-20.19	43.5	42.56	9.68	1.48	30.41	-	-	P	H
		164.46	16.84	-26.66	43.5	35.69	9.8	1.71	30.36	-	-	P	H
		253.02	19.18	-26.82	46	34.43	12.85	2.14	30.24	-	-	P	H
		422.5	27.85	-18.15	46	38.37	16.76	2.68	29.96	-	-	P	H
		633.9	30.22	-15.78	46	35.99	20.46	3.33	29.56	-	-	P	H
		748.7	31.58	-14.42	46	35.27	22.2	3.54	29.43	100	0	P	H
		63.75	26.18	-13.82	40	49.42	5.98	1.22	30.44	100	0	P	V
		106.41	24.47	-19.03	43.5	42.68	10.72	1.48	30.41	-	-	P	V
		192	16.97	-26.53	43.5	36.62	8.8	1.89	30.34	-	-	P	V
		379.8	18.4	-27.6	46	30.73	15.1	2.6	30.03	-	-	P	V
		422.5	28.27	-17.73	46	38.79	16.76	2.68	29.96	-	-	P	V
		883.8	30.97	-15.03	46	33.3	23	3.84	29.17	-	-	P	V
Remark	1. No other spurious found.												
	2. All results are PASS against limit line.												

Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.