

The Photos of SAR test

No. I17Z60125-SEM01

For

TCL Communication Ltd.

GSM Quad band/UMTS 3 Band/LTE 4 Band Mobile phone

Model Name: 5046G

With

Hardware Version: PIO

Software Version: vJ5H

FCC ID: 2ACCJB075



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.


Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191 Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504


Email:cttl_terminals@catr.cn, website:www.chinattl.com




Picture 1: Constituents of the sample




Picture 2: Left Hand Touch Cheek Position



Picture 3: Left Hand Tilt 15° Position




Picture 4: Right Hand Touch Cheek Position




Picture 5: Right Hand Tilt 15° Position

Test positions for body:


The Body SAR is tested at the following 6 test positions all with the distance = 10mm or 15 mm between the EUT and the phantom bottom:



Picture 6: Front 10mm




Picture 7: Rear 10mm



Picture 8: Front 15mm



Picture 9: Rear 15mm



Picture 10: Left edge 10mm



Picture 11: Right edge 10mm



Picture 12: Bottom edge 10mm



Picture 13: Top edge 10mm