

# The Photos of SAR test

## No. I17Z61036-SEM02

For

**TCL Communication Ltd.** 

GSM Quad-band/HSPA-UMTS Six-band/LTE 19-band mobile phone

Model name: BBD100-1

With

Hardware Version: 04

**Software Version: AAN966** 

FCC ID: 2ACCJN019



#### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

#### **Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT

No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: <a href="mailto:cttl">cttl</a> terminals@caict.ac.cn, website: <a href="mailto:www.caict.ac.cn">www.caict.ac.cn</a>



Picture 1: Constituents of the sample



**Picture 2: Left Hand Touch Cheek Position** 



Picture 3: Left Hand Tilt 15° Position




**Picture 4: Right Hand Touch Cheek Position** 




Picture 5: Right Hand Tilt 15° Position

### Test positions for body:


The Body SAR is tested at the following 6 test positions all with the distance =10mm or 15mm between the EUT and the phantom bottom:




Picture 6: Front with 10mm




Picture 7: Rear with 10mm



Picture 8: Left with 10mm




Picture 9: Right with 10mm




Picture 10: Top with 10mm



Picture 11: Bottom with 10mm



Picture 12: Front with 15mm



Picture 13: Rear with 15mm



Picture 14: Front with Headset



Picture 15: Front with 0mm