



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247



TEST REPORT

For

ShangHai Ehong Technology Co.,Ltd.

Suite501,No.3 building,No.439 Jinglian road,Minhang district,Shanghai,China

FCC ID: 2ACCRM17

Report Type: Original Report	Product Type: BT Module
Test Engineer: Max Min 	
Report Number: RSHD190611013-00A	
Report Date: 2019-07-16	
Reviewed By: Oscar Ye  RF Leader	
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS.....	10
TEST EQUIPMENT LIST	11
FCC §1.1310 & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)	12
FCC §15.203 - ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	15
CORRECTED FACTOR & MARGIN CALCULATION	15
TEST RESULTS SUMMARY	15
TEST DATA	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	20
APPLICABLE STANDARD	20
EUT SETUP.....	20
EMI TEST RECEIVER SETUP.....	21
TEST PROCEDURE	21
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST RESULTS SUMMARY	21
TEST DATA	22
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	45
APPLICABLE STANDARD	45
TEST PROCEDURE	45
TEST DATA	45
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	50
APPLICABLE STANDARD	50
TEST PROCEDURE	50
TEST DATA	51

FCC §15.247(d) – BAND EDGE.....	56
APPLICABLE STANDARD	56
TEST PROCEDURE	56
TEST DATA	56
FCC §15.247(e) - POWER SPECTRAL DENSITY	59
APPLICABLE STANDARD	59
TEST PROCEDURE	59
TEST DATA	59

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	ShangHai Ehong Technology Co.,Ltd.
Tested Model	EH-MC17
Series Model	EH-MC17B
Model difference	Antenna type, EH-MC17 with ceramics antenna, EH-MC17B with dipole antenna
Product Type	BT Module
Dimension	17.7mm(L)*11.95 mm(W)*2.2 mm(H)
Power Supply	DC 1.8-3.6V

**All measurement and test data in this report was gathered from production sample serial number: 20190611013. (Assigned by BACL, Kunshan). The EUT was received on 2019-06-11.*

Objective

This report is prepared on behalf of *ShangHai Ehong Technology Co.,Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communications Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel List for BLE mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
18	2438	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

Equipment Modifications


No modification was made to the EUT tested.

EUT Exercise Software

RF test software: RTL8762C_RFTTestTool.


1Mbit/s Duty Cycle:

Middle Channel



2Mbit/s Duty Cycle:

Middle Channel



Mode	Data Rate	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
BLE	1Mbit/s	100%	/	/	0
	2Mbit/s	40.41%	0.255	3.92	3.94

Note: “x” means the Duty Cycle.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
DELL	Adapter	LA65NS0-00	DF263
/	Debug Board	/	/
/	Serial board	/	/


External I/O Cable

Cable Description	Length (m)	From Port	To
Power Cable	1.0	Adapter	AC Source


Block Diagram of Test Setup

For EH-MC17 & EH-MC17B:


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2018-11-30	2019-11-29
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2018-08-14	2019-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2018-08-15	2019-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2019-07-23	2020-07-22
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-12-12	2019-12-11
A.H.Systems, inc	Amplifier	2641-1	491	2019-02-20	2020-02-19
SELECTOR	Amplifier	EM18G40G	060726	2019-03-22	2020-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2018-08-05	2019-08-04
Narda	Attenuator	10dB	010	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2018-08-15	2019-08-14
RF Conducted Test					
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2018-11-30	2019-11-29
Narda	Attenuator	10dB	010	2018-08-15	2019-08-14
Ehong	RF Cable	/	/	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2018-11-30	2019-11-29
Rohde & Schwarz	LISN	ENV216	3560655016	2018-11-30	2019-11-29
BACL	Auto test Software	BACL-EMC	CE001	/	/
Narda	Attenuator/6dB	10690812-2	26850-6	2019-01-10	2020-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2018-08-15	2019-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Data Rate	Antenna Gain		Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
			(dBi)	(numeric)	(dBm)	(mW)			
BLE (EH-MC17)	2402-2480	1Mbit/s	0.00	1.00	6.00	3.98	20	0.0008	1.0
		2Mbit/s	0.00	1.00	6.00	3.98	20	0.0008	1.0
BLE (EH-MC17B)	2402-2480	1Mbit/s	3.00	2.00	6.00	3.98	20	0.0016	1.0
		2Mbit/s	3.00	2.00	6.00	3.98	20	0.0016	1.0

Note: The tune-up output power was declared by the manufacturer.

Conclusion: The EUT meets exemption requirement - RF exposure evaluation greater than 20cm distance specified in § 2.1091. If the device built into a host as a portable usage, the additional RF exposure evaluation may be required as specified by § 2.1093.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a ceramics antenna for EH-MC17, which the antenna gain is 0 dBi and a dipole antenna for EH-MC17B, which the antenna gain is 3 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Model	Antenna Type	Antenna Gain(dBi)
EH-MC17	Ceramics	0
EH-MC17B	Dipole	3


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Corrected Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V)} - \text{Corrected Amplitude (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, FCC Part 15.207.

Test Data

Environmental Conditions


Temperature:	20.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

The testing was performed by Max Min on 2019-06-14.

Test Result: Compliant.


Model: EH-MC17

EUT operation mode: Transmitting in low channel 1Mbit/s (worst case)

AC 120V/60 Hz, Line

Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	42.08	QP	9.000	L1	16.06	66.00	23.92	Compliant
0.150	21.05	AV	9.000	L1	16.06	56.00	34.95	Compliant
0.445	31.69	QP	9.000	L1	16.07	57.57	25.88	Compliant
0.445	18.35	AV	9.000	L1	16.07	47.57	29.22	Compliant
0.875	21.24	QP	9.000	L1	15.91	56.00	34.76	Compliant
0.875	17.24	AV	9.000	L1	15.91	46.00	28.76	Compliant
2.050	22.64	QP	9.000	L1	15.85	56.00	33.36	Compliant
2.050	16.46	AV	9.000	L1	15.85	46.00	29.54	Compliant
4.150	26.75	QP	9.000	L1	15.85	56.00	29.25	Compliant
4.150	17.61	AV	9.000	L1	15.85	46.00	28.39	Compliant
21.500	28.89	QP	9.000	L1	16.45	60.00	31.11	Compliant
21.500	23.34	AV	9.000	L1	16.45	50.00	26.66	Compliant


AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	39.37	QP	9.000	N	16.06	66.00	26.63	Compliant
0.150	20.65	AV	9.000	N	16.06	56.00	35.35	Compliant
0.425	23.54	QP	9.000	N	16.10	58.14	34.60	Compliant
0.425	21.06	AV	9.000	N	16.10	48.14	27.08	Compliant
0.830	21.38	QP	9.000	N	15.97	56.00	34.62	Compliant
0.830	17.45	AV	9.000	N	15.97	46.00	28.55	Compliant
2.000	23.17	QP	9.000	N	15.91	56.00	32.83	Compliant
2.000	18.91	AV	9.000	N	15.91	46.00	27.09	Compliant
4.100	20.01	QP	9.000	N	15.88	56.00	35.99	Compliant
4.100	14.35	AV	9.000	N	15.88	46.00	31.65	Compliant
18.900	18.19	QP	9.000	N	16.13	60.00	41.81	Compliant
18.900	13.95	AV	9.000	N	16.13	50.00	36.05	Compliant


Note:

- 1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Margin (dB) = Limit (dBμV) – Corrected Amplitude (dBμV)

Model: EH-MC17B**EUT operation mode: Transmitting in low channel 1Mbit/s (worst case)****AC 120V/60 Hz, Line**

Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.160	46.48	QP	9.000	L	16.05	65.46	18.98	Compliant
0.160	23.39	AV	9.000	L	16.05	55.46	32.07	Compliant
0.415	30.04	QP	9.000	L	16.06	57.55	27.51	Compliant
0.415	27.76	AV	9.000	L	16.06	47.55	19.79	Compliant
0.875	23.86	QP	9.000	L	15.91	56.00	32.14	Compliant
0.875	19.85	AV	9.000	L	15.91	46.00	26.15	Compliant
1.700	27.45	QP	9.000	L	15.86	56.00	28.55	Compliant
1.700	21.58	AV	9.000	L	15.86	46.00	24.42	Compliant
4.200	22.25	QP	9.000	L	15.85	56.00	33.75	Compliant
4.200	16.37	AV	9.000	L	15.85	46.00	29.63	Compliant
18.600	19.61	QP	9.000	L	16.38	60.00	40.39	Compliant
18.600	14.69	AV	9.000	L	16.37	50.00	35.31	Compliant

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	47.67	QP	9.000	N	16.06	66.00	18.33	Compliant
0.150	24.31	AV	9.000	N	16.06	56.00	31.69	Compliant
0.460	29.09	QP	9.000	N	16.10	56.69	27.60	Compliant
0.460	20.71	AV	9.000	N	16.10	46.69	25.98	Compliant
1.250	28.58	QP	9.000	N	15.93	56.00	27.42	Compliant
1.250	21.18	AV	9.000	N	15.93	46.00	24.82	Compliant
2.650	28.89	QP	9.000	N	15.90	56.00	27.11	Compliant
2.650	20.65	AV	9.000	N	15.90	46.00	25.35	Compliant
5.200	25.45	QP	9.000	N	15.88	60.00	34.55	Compliant
5.200	18.99	AV	9.000	N	15.88	50.00	31.01	Compliant
18.350	23.89	QP	9.000	N	16.11	60.00	36.11	Compliant
18.350	17.22	AV	9.000	N	16.11	50.00	32.78	Compliant



Note:

1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Margin (dB) = Limit (dBμV) – Corrected Amplitude (dBμV)

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	Peak
	1MHz	3 MHz	1MHz	AVG

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz, Peak and average detection mode above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data**Environmental Conditions**

Temperature:	24.2°C-25.6°C
Relative Humidity:	48%-51%
ATM Pressure:	100.6kPa -101.2kPa

The testing was performed by Max Min from 2019-07-03 to 2019-07-15.

Test Result: Compliant.


EUT operation mode: Transmitting

Spurious Emission Test:

Model: EH-MC17, **Data Rate:** 1Mbit/s

30MHz-1GHz

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low** channel of operation in **X-axis** of orientation was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
30.581129	18.65	200.0	H	224.0	-4.3	40.00	21.35
155.848100	23.16	200.0	H	357.0	-12.6	43.50	20.34
230.730900	18.94	100.0	H	359.0	-12.2	46.00	27.06
260.488500	17.90	100.0	H	0.0	-11.7	46.00	28.10
369.234400	32.45	100.0	H	227.0	-8.8	46.00	13.55
675.863200	17.94	100.0	V	97.0	-3.7	46.00	28.06

1GHz-18GHz:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1074.800000	---	23.09	200.0	H	125.0	-12.2	54.00	30.91
1074.800000	37.14	---	200.0	H	125.0	-12.2	74.00	36.86
1996.200000	---	30.61	100.0	V	133.0	-8.3	54.00	23.39
1999.600000	42.81	---	100.0	V	133.0	-8.2	74.00	31.19
2128.800000	---	25.16	200.0	V	137.0	-7.9	54.00	28.84
2128.800000	41.38	---	200.0	V	137.0	-7.9	74.00	32.62
3454.800000	---	33.90	100.0	V	231.0	-3.6	54.00	20.10
3454.800000	40.47	---	100.0	V	231.0	-3.6	74.00	33.53
5246.600000	---	36.02	100.0	V	46.0	0.6	54.00	17.98
5246.600000	43.02	---	100.0	V	46.0	0.6	74.00	30.98
17772.200000	---	44.09	100.0	H	125.0	13.8	54.00	9.91
17772.200000	53.95	---	100.0	H	125.0	13.8	74.00	20.05

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1074.800000	---	24.73	150.0	H	235.0	-12.2	54.00	29.27
1074.800000	37.74	---	150.0	H	235.0	-12.2	74.00	36.26
1724.200000	---	31.09	150.0	V	89.0	-9.2	54.00	22.91
1724.200000	38.91	---	150.0	V	89.0	-9.2	74.00	35.09
1999.600000	---	28.01	200.0	V	254.0	-8.2	54.00	25.99
1999.600000	40.00	---	200.0	V	254.0	-8.2	74.00	34.00
3454.800000	---	33.51	100.0	V	225.0	-3.6	54.00	20.49
3454.800000	41.58	---	100.0	V	225.0	-3.6	74.00	32.42
4880.000000	---	33.19	100.0	H	315.0	-0.4	54.00	20.81
4880.000000	42.94	---	100.0	H	315.0	-0.4	74.00	31.06
17792.600000	---	45.18	150.0	H	70.0	13.8	54.00	8.82
17792.600000	55.16	---	150.0	H	70.0	13.8	74.00	18.84

High Channel: 2480MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1044.200000	---	24.10	100.0	H	302.0	-12.4	54.00	29.90
1044.200000	38.04	---	100.0	H	302.0	-12.4	74.00	35.96
1584.800000	---	29.02	150.0	V	135.0	-9.6	54.00	24.98
1584.800000	39.09	---	150.0	V	135.0	-9.6	74.00	34.91
3454.800000	---	33.17	200.0	V	235.0	-3.6	54.00	20.83
3454.800000	41.06	---	200.0	V	235.0	-3.6	74.00	32.94
7262.800000	---	36.27	200.0	V	296.0	5.8	54.00	17.73
7262.800000	46.48	---	200.0	V	296.0	5.8	74.00	27.52
9921.600000	---	47.28	200.0	H	73.0	8.1	54.00	6.72
9921.600000	54.85	---	200.0	H	73.0	8.1	74.00	19.15
17626.000000	---	44.88	100.0	H	0.0	14.1	54.00	9.12
17626.000000	54.70	---	100.0	H	0.0	14.1	74.00	19.30

Model: EH-MC17, Data Rate: 2Mbit/s**30MHz-1GHz**

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low** channel of operation in X-axis of orientation was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
30.164806	18.76	199.0	H	195.0	-4.0	40.00	21.24
155.822450	23.45	199.0	H	333.0	-12.6	43.50	20.05
214.157600	16.62	199.0	H	347.0	-12.3	43.50	26.88
229.161400	18.34	101.0	H	24.0	-12.2	46.00	27.66
314.642550	21.58	101.0	H	336.0	-10.2	46.00	24.42
360.418250	31.66	101.0	H	237.0	-9.1	46.00	14.34

1GHz-18GHz:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V /m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1564.400000	---	32.40	100.0	V	201.0	-9.7	54.00	21.60
1564.400000	39.82	---	100.0	V	201.0	-9.7	74.00	34.18
2128.800000	---	26.16	100.0	V	123.0	-7.9	54.00	27.84
2128.800000	40.80	---	100.0	V	123.0	-7.9	74.00	33.20
3454.800000	---	33.98	100.0	V	230.0	-3.6	54.00	20.02
3454.800000	41.24	---	100.0	V	230.0	-3.6	74.00	32.76
4804.000000	---	34.15	100.0	H	242.0	-0.6	54.00	19.85
4804.000000	42.45	---	100.0	H	242.0	-0.6	74.00	31.55
7113.200000	---	38.38	200.0	H	299.0	5.5	54.00	15.62
7113.200000	48.06	---	200.0	H	299.0	5.5	74.00	25.94
17544.400000	---	45.46	200.0	H	357.0	14.2	54.00	8.54
17544.400000	56.68	---	200.0	H	357.0	14.2	74.00	17.32

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1081.600000	---	24.41	150.0	H	342.0	-12.2	54.00	29.59
1081.600000	36.75	---	150.0	H	342.0	-12.2	74.00	37.25
1649.400000	---	25.17	150.0	V	135.0	-9.4	54.00	28.83
1649.400000	38.16	---	150.0	V	135.0	-9.4	74.00	35.84
2125.400000	---	26.54	200.0	V	133.0	-7.9	54.00	27.46
2125.400000	40.82	---	200.0	V	133.0	-7.9	74.00	33.18
3454.800000	---	33.06	100.0	V	235.0	-3.6	54.00	20.94
3454.800000	41.93	---	100.0	V	235.0	-3.6	74.00	32.07
4950.800000	---	31.21	200.0	H	94.0	-0.3	54.00	22.79
4950.800000	40.77	---	200.0	H	94.0	-0.3	74.00	33.23
17632.800000	---	44.77	200.0	H	346.0	14.1	54.00	9.23
17632.800000	55.04	---	200.0	H	346.0	14.1	74.00	18.96

High Channel: 2480MHz



Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1591.600000	---	33.67	200.0	V	107.0	-9.6	54.00	20.33
1591.600000	41.16	---	200.0	V	107.0	-9.6	74.00	32.84
1999.600000	---	28.80	150.0	V	219.0	-8.2	54.00	25.20
1999.600000	44.31	---	150.0	V	219.0	-8.2	74.00	29.69
3454.800000	---	33.81	100.0	V	232.0	-3.6	54.00	20.19
3454.800000	41.20	---	100.0	V	232.0	-3.6	74.00	32.80
4960.000000	---	33.18	100.0	H	286.0	-0.3	54.00	20.82
4960.000000	41.03	---	100.0	H	286.0	-0.3	74.00	32.97
7072.400000	---	38.22	200.0	H	359.0	5.5	54.00	15.78
7072.400000	48.01	---	200.0	H	359.0	5.5	74.00	25.99
17581.800000	---	44.95	200.0	H	296.0	14.1	54.00	9.05
17581.800000	54.65	---	200.0	H	296.0	14.1	74.00	19.35

Model: EH-MC17, Data Rate: 2Mbit/s (worst case)**18GHz-25GHz:**

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low** channel of operation in X-axis of orientation was recorded)

Horizontal**Vertical**

Restricted Bands Emissions Test:

(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded.)

Note:

1. The test is performed with a 10dB Attenuator.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Model: EH-MC17, Data Rate: 1Mbit/s


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2389.300000	46.31	---	150.0	H	205.0	2.8	74.00	27.69
2389.300000	---	35.83	150.0	H	205.0	2.8	54.00	18.17
2389.300000	45.22	---	200.0	V	344.0	2.8	74.00	28.78
2389.300000	---	35.12	200.0	V	344.0	2.8	54.00	18.88
High Channel: 2480MHz								
2483.872000	---	35.97	200.0	H	5.0	3.0	54.00	18.03
2483.872000	46.80	---	200.0	H	5.0	3.0	74.00	27.20
2483.872000	---	35.66	150.0	V	296.0	3.0	54.00	18.34
2483.872000	46.47	---	150.0	V	296.0	3.0	74.00	27.53

Model: EH-MC17, Data Rate: 2Mbit/s

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2389.300000	46.83	---	150.0	H	20.0	2.8	74.00	27.17
2389.300000	---	35.81	150.0	H	20.0	2.8	54.00	18.19
2389.300000	46.67	---	200.0	V	354.0	2.8	74.00	27.33
2389.300000	---	36.13	200.0	V	354.0	2.8	54.00	17.87
High Channel: 2480MHz								
2483.872000	---	37.66	150.0	H	26.0	3.0	54.00	16.34
2483.872000	51.47	---	150.0	H	26.0	3.0	74.00	22.53
2483.872000	---	36.33	100.0	V	212.0	3.0	54.00	17.67
2483.872000	50.26	---	100.0	V	212.0	3.0	74.00	23.74

Spurious Emission Test:**Model: EH-MC17B, Data Rate: 1Mbit/s****30MHz-1GHz**

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low** channel of operation in X-axis of orientation was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
30.764705	18.28	200.0	V	299.0	-4.4	40.00	21.72
74.078900	16.17	100.0	V	0.0	-17.5	40.00	23.83
214.281700	21.47	200.0	V	309.0	-12.3	43.50	22.03
309.549800	24.66	200.0	H	123.0	-10.3	46.00	21.34
392.732450	27.08	100.0	V	203.0	-8.3	46.00	18.92
956.890300	22.12	200.0	H	181.0	1.4	46.00	23.88

1GHz-18GHz:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1088.400000	---	23.59	150.0	H	249.0	-12.2	54.00	30.41
1088.400000	38.52	---	150.0	H	249.0	-12.2	74.00	35.48
1591.600000	---	28.70	200.0	V	140.0	-9.6	54.00	25.30
1591.600000	39.78	---	200.0	V	140.0	-9.6	74.00	34.22
3454.800000	---	34.05	200.0	V	229.0	-3.6	54.00	19.95
3454.800000	40.85	---	200.0	V	229.0	-3.6	74.00	33.15
4804.000000	---	42.23	150.0	V	147.0	-0.6	54.00	11.77
4804.000000	50.31	---	150.0	V	147.0	-0.6	74.00	23.69
7058.800000	---	38.04	200.0	H	326.0	5.4	54.00	15.96
7058.800000	47.65	---	200.0	H	326.0	5.4	74.00	26.35
17932.000000	---	44.79	200.0	H	74.0	13.6	54.00	9.21
17932.000000	54.63	---	200.0	H	74.0	13.6	74.00	19.37

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1088.400000	---	22.55	150.0	H	260.0	-12.2	54.00	31.45
1088.400000	37.25	---	150.0	H	260.0	-12.2	74.00	36.75
1598.400000	---	28.91	200.0	V	199.0	-9.6	54.00	25.09
1598.400000	40.65	---	200.0	V	199.0	-9.6	74.00	33.35
2985.600000	---	30.75	200.0	V	111.0	-4.5	54.00	23.25
2985.600000	40.14	---	200.0	V	111.0	-4.5	74.00	33.86
3454.800000	---	33.80	100.0	V	235.0	-3.6	54.00	20.20
3454.800000	42.45	---	100.0	V	235.0	-3.6	74.00	31.55
4880.000000	---	42.01	150.0	V	145.0	-0.4	54.00	11.99
4880.000000	48.38	---	150.0	V	145.0	-0.4	74.00	25.62
17864.000000	---	45.59	200.0	H	11.0	13.7	54.00	8.41
17864.000000	53.61	---	200.0	H	11.0	13.7	74.00	20.39

High Channel: 2480MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1078.200000	---	23.89	100.0	H	296.0	-12.2	54.00	30.11
1078.200000	38.21	---	100.0	H	296.0	-12.2	74.00	35.79
1550.800000	---	27.41	200.0	V	157.0	-9.8	54.00	26.59
1550.800000	39.09	---	200.0	V	157.0	-9.8	74.00	34.91
1999.600000	---	28.18	150.0	V	166.0	-8.2	54.00	25.82
1999.600000	40.71	---	150.0	V	166.0	-8.2	74.00	33.29
3454.800000	---	33.61	200.0	V	225.0	-3.6	54.00	20.39
3454.800000	41.80	---	200.0	V	225.0	-3.6	74.00	32.20
4960.000000	---	39.63	200.0	V	109.0	-0.3	54.00	14.37
4960.000000	49.84	---	200.0	V	109.0	-0.3	74.00	24.16
17816.400000	---	44.52	200.0	H	84.0	13.8	54.00	9.48
17816.400000	53.93	---	200.0	H	84.0	13.8	74.00	20.07

Model: EH-MC17B, Data Rate: 2Mbit/s**30MHz-1GHz**

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low** channel of operation in X-axis of orientation was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
30.867525	18.33	100.0	V	276.0	-4.5	40.00	21.67
72.970400	16.50	100.0	V	6.0	-17.4	40.00	23.50
154.586150	20.72	100.0	H	77.0	-12.5	43.50	22.78
302.662300	25.49	100.0	V	308.0	-10.4	46.00	20.51
361.489650	25.57	200.0	V	325.0	-9.0	46.00	20.43
946.670650	22.10	100.0	V	256.0	1.2	46.00	23.90

1GHz-18GHz:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1074.800000	---	24.12	150.0	H	132.0	-12.2	54.00	29.88
1074.800000	37.44	---	150.0	H	132.0	-12.2	74.00	36.56
1527.000000	---	28.11	100.0	V	151.0	-9.8	54.00	25.89
1527.000000	36.61	---	100.0	V	151.0	-9.8	74.00	37.39
1727.600000	---	30.97	200.0	V	74.0	-9.2	54.00	23.03
1727.600000	38.45	---	200.0	V	74.0	-9.2	74.00	35.55
2128.800000	---	26.04	150.0	V	115.0	-7.9	54.00	27.96
2128.800000	41.02	---	150.0	V	115.0	-7.9	74.00	32.98
3454.800000	---	34.06	150.0	V	223.0	-3.6	54.00	19.94
3454.800000	42.00	---	150.0	V	223.0	-3.6	74.00	32.00
4804.000000	---	39.55	100.0	V	170.0	-0.6	54.00	14.45
4804.000000	50.82	---	100.0	V	170.0	-0.6	74.00	23.18

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1078.200000	---	24.76	150.0	H	240.0	-12.2	54.00	29.24
1078.200000	38.32	---	150.0	H	240.0	-12.2	74.00	35.68
1588.200000	---	27.94	200.0	V	199.0	-9.6	54.00	26.06
1588.200000	41.63	---	200.0	V	199.0	-9.6	74.00	32.37
1999.600000	---	29.94	150.0	V	252.0	-8.2	54.00	24.06
1999.600000	44.84	---	150.0	V	252.0	-8.2	74.00	29.16
3454.800000	---	33.89	200.0	V	160.0	-3.6	54.00	20.11
3454.800000	41.96	---	200.0	V	160.0	-3.6	74.00	32.04
4880.000000	---	40.53	150.0	V	105.0	-0.4	54.00	13.47
4880.000000	49.51	---	150.0	V	105.0	-0.4	74.00	24.49
17643.000000	---	44.62	150.0	H	34.0	14.1	54.00	9.38
17643.000000	54.20	---	150.0	H	34.0	14.1	74.00	19.80

High Channel: 2480MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1595.000000	---	26.76	150.0	V	173.0	-9.6	54.00	27.24
1595.000000	42.03	---	150.0	V	173.0	-9.6	74.00	31.97
1999.600000	---	29.30	150.0	V	222.0	-8.2	54.00	24.70
1999.600000	43.56	---	150.0	V	222.0	-8.2	74.00	30.44
3454.800000	---	33.19	200.0	V	225.0	-3.6	54.00	20.81
3454.800000	40.34	---	200.0	V	225.0	-3.6	74.00	33.66
4960.000000	---	37.78	150.0	V	183.0	-0.3	54.00	16.22
4960.000000	47.32	---	150.0	V	183.0	-0.3	74.00	26.68
7035.000000	---	38.01	150.0	H	189.0	5.4	54.00	15.99
7035.000000	47.48	---	150.0	H	189.0	5.4	74.00	26.52
17925.200000	---	45.29	200.0	H	358.0	13.6	54.00	8.71
17925.200000	54.33	---	200.0	H	358.0	13.6	74.00	19.67

Model: EH-MC17B, Data Rate: 2Mbit/s (worst case)


18GHz-25GHz

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low** channel of operation in X-axis of orientation was recorded)

Horizontal



Vertical



Restricted Bands Emissions Test:

(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded.)

Note:



1. The test is performed with a 10dB Attenuator.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Model: EH-MC17B, Data Rate: 1Mbit/s


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2389.300000	46.77	---	150.0	H	25.0	2.8	74.00	27.23
2389.300000	---	36.56	150.0	H	25.0	2.8	54.00	17.44
2389.300000	46.02	---	200.0	V	182.0	2.8	74.00	27.98
2389.300000	---	36.33	200.0	V	182.0	2.8	54.00	17.67
High Channel: 2480MHz								
2483.872000	---	36.41	100.0	H	114.0	3.0	54.00	17.59
2483.872000	46.37	---	100.0	H	114.0	3.0	74.00	27.63
2483.872000	---	37.62	150.0	V	229.0	3.0	54.00	16.38
2483.872000	47.47	---	150.0	V	229.0	3.0	74.00	26.53

Model: EH-MC17B, Data Rate: 2Mbit/s

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2389.300000	46.26	---	100.0	H	327.0	2.8	74.00	27.74
2389.300000	---	36.39	100.0	H	327.0	2.8	54.00	17.61
2389.300000	46.51	---	150.0	V	51.0	2.8	74.00	27.49
2389.300000	---	36.84	150.0	V	51.0	2.8	54.00	17.16
High Channel: 2480MHz								
2483.872000	---	36.61	150.0	H	280.0	3.0	54.00	17.39
2483.872000	48.47	---	150.0	H	280.0	3.0	74.00	25.53
2483.872000	---	36.77	200.0	V	271.0	3.0	54.00	17.23
2483.872000	49.66	---	200.0	V	271.0	3.0	74.00	24.34


Conducted Spurious Emissions at Antenna Port**Data Rate: 1Mbit/s****Low Channel****Middle Channel**

High Channel




Data Rate: 2Mbit/s


Low Channel



Middle Channel



High Channel




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH**Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**Test Data****Environmental Conditions**

Temperature:	24.2°C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Max Min on 2019-07-03.


Test Result: Compliant.

EUT operation mode: Transmitting


Data Rate: 1Mbit/s

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Low	2402	0.697	≥ 0.5
Middle	2440	0.697	≥ 0.5
High	2480	0.703	≥ 0.5


Low Channel



Middle Channel




High Channel




Data Rate: 2Mbit/s


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Low	2402	0.998	≥ 0.5
Middle	2440	1.154	≥ 0.5
High	2480	1.154	≥ 0.5

Low Channel

Middle Channel



High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW \geq DTS bandwidth.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 3 \times$ RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data**Environmental Conditions**

Temperature:	24.2°C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Max Min on 2019-07-03.


Test Result: Compliant.

EUT operation mode: Transmitting


Data Rate: 1Mbit/s

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	5.15	30	Pass
Middle	2440	5.02	30	Pass
High	2480	4.86	30	Pass


Low Channel



Middle Channel




High Channel




Data Rate: 2Mbit/s

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	5.15	30	Pass
Middle	2440	5.02	30	Pass
High	2480	4.89	30	Pass


Low Channel



Middle Channel



High Channel



FCC §15.247(d) – BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	24.2°C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa


The testing was performed by Max Min on 2019-07-03.

Test Result: Compliant.


EUT operation mode: Transmitting

Data Rate: 1Mbit/s

Left Side




Right Side




Data Rate: 2Mbit/s

Left Side



Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 \times \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	24.2°C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Max Min on 2019-07-03.


Test Result: Compliant.

EUT operation mode: Transmitting


Data Rate: 1Mbit/s

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-6.15	≤ 8
Middle	2440	-6.36	≤ 8
High	2480	-6.51	≤ 8


Low Channel



Middle Channel




High Channel




Data Rate: 2Mbit/s

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-12.04	≤ 8
Middle	2440	-12.49	≤ 8
High	2480	-12.39	≤ 8


Low Channel



Middle Channel



High Channel



***** END OF REPORT *****