



# FCC RADIO TEST REPORT

FCC ID : 2ACDX-MRR-30  
Equipment : Vehicle Radar  
Brand Name : Mando  
Model Name : MRR-30  
Applicant : MANDO corp.  
21, Pangyo-ro 255beon-gil, Bundang-gu, Seongnam-si,  
Gyeonggi-do, 463-400, Republic of Korea  
Manufacturer : MANDO corp.  
21, Pangyo-ro 255beon-gil, Bundang-gu, Seongnam-si,  
Gyeonggi-do, 463-400, Republic of Korea  
Standard : 47 CFR FCC Part 95M

The product was received on Oct. 15, 2019, and testing was started from Oct. 26, 2019 and completed on Nov. 05, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Sam Chen

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report.....</b>	<b>3</b>
<b>Summary of Test Result.....</b>	<b>4</b>
<b>1 General Description .....</b>	<b>5</b>
1.1 Information.....	5
1.2 Applicable Standards .....	6
1.3 Testing Location Information .....	6
1.4 Measurement Uncertainty .....	6
<b>2 Test Configuration of EUT.....</b>	<b>7</b>
2.1 Test Channel Frequencies Configuration.....	7
2.2 Conformance Tests and Related Test Frequencies.....	7
2.3 The Worst Case Measurement Configuration.....	8
2.4 EUT Operation during Test .....	8
2.5 Accessories .....	9
2.6 Support Equipment.....	9
2.7 Far Field Boundary Calculations .....	9
2.8 Test Setup Diagram .....	10
<b>3 Transmitter Test Result .....</b>	<b>11</b>
3.1 Occupied Bandwidth .....	11
3.2 Radiated E.I.R.P Power .....	13
3.3 Transmitter Radiated Unwanted Emissions .....	15
3.4 Frequency Stability .....	24
<b>4 Test Equipment and Calibration Data .....</b>	<b>26</b>

### Appendix A. Test Photos

#### Photographs of EUT v01



TEL : 886-3-656-9065  
FAX : 886-3-656-9085  
Report Template No.: CB-A17\_2 Ver1.0



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
-	15.107	AC Power-line Conducted Emissions	N/A	Note
3.1	95.303	Occupied Bandwidth	PASS	-
3.2	95.3367	Radiated E.I.R.P Power	PASS	-
3.3	95.3379	Transmitter Radiated Unwanted Emissions	PASS	-
3.4	95.3379	Frequency Stability	PASS	-
Note: It was supplied power by DC-Powered for EUT; it's not necessary to apply to AC Power-line Conducted Emissions test.				

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Sam Chen**

**Report Producer: Cindy Peng**



# 1 General Description

## 1.1 Information

### 1.1.1 RF General Information

RF General Information					
Frequency Range (GHz)	Operating Frequency (GHz)	Modulation	EIRP Power - Peak (dBm)	Power Density ( $\mu\text{W}/\text{cm}^2$ ) at 3m	99% Occupied Bandwidth (MHz)
76-81	76.1-76.87	FMCW	42.47	0.2901	726.48

### 1.1.2 Antenna Information

Ant.	Port	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
						TX	RX
1	1	Mando	MRR-30	Patch Antenna	Micro Strip Line	18.51	14.73
	2	Mando	MRR-30	Patch Antenna	Micro Strip Line	14.73	14.73
	3	Mando	MRR-30	Patch Antenna	Micro Strip Line	18.51	14.73
	4	Mando	MRR-30	Patch Antenna	Micro Strip Line	-	14.73

Note1: The above information was declared by manufacturer.

Note2: The antenna has four ports (3TX, 4RX).

Port 1, Port 2 and Port 3 could transmit simultaneously.

Port 1, Port 2, Port 3 and Port 4 could receive simultaneously.

### 1.1.3 EUT Operational Condition

EUT Power Type	From DC power supply			
Supply Voltage	<input type="checkbox"/>	AC	State AC voltage	-
Supply Voltage	<input checked="" type="checkbox"/>	DC	State DC voltage	12 V

### 1.1.4 Test Signal Duty Cycle

Test Signal Duty Cycle	
<input checked="" type="checkbox"/>	Continuous transmission - 40.83%
<input type="checkbox"/>	Transmissions occur regularly in time - ...%



## 1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 95M
- ♦ ANSI C63.10 - Testing Unlicensed Wireless Devices
- ♦ KDB653005 D01 76-81 GHz Radars v01r01
- ♦ FCC KDB 414788 D01 v01r01

## 1.3 Testing Location Information

Testing Location				
<input type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)		
		TEL : 886-3-327-3456	FAX : 886-3-327-0973	
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.		
		TEL : 886-3-656-9065	FAX : 886-3-656-9085	

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH03-CB	Lucas Huang	24.2~25.5°C / 58~64%	Oct. 26, 2019~Nov. 05, 2019
Radiated	03CH05-CB	Cola Fan	24.5~25.5°C / 56~61%	Oct. 26, 2019~Nov. 05, 2019

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086D with Industry Canada.

## 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Radiated Emission (30MHz ~ 1,000MHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	5.1 dB	Confidence levels of 95%
Radiated Emission (40GHz ~ 60GHz)	4.6 dB	Confidence levels of 95%
Radiated Emission (60GHz ~ 90GHz)	5.1 dB	Confidence levels of 95%
Radiated Emission (90GHz ~ 200GHz)	5.6 dB	Confidence levels of 95%
Radiated Emission (200GHz ~ 280GHz)	6.7 dB	Confidence levels of 95%
Temperature	1°C	Confidence levels of 95%

## 2 Test Configuration of EUT

### 2.1 Test Channel Frequencies Configuration

Test Channel Frequencies Configuration
Test Channel Frequencies (GHz)
76.485

### 2.2 Conformance Tests and Related Test Frequencies

Test Item	Test Frequencies (GHz)
Occupied Bandwidth	76.485
Radiated E.I.R.P Power	76.485
Transmitter Spurious Emissions (below 1 GHz)	76.485
Transmitter Spurious Emissions (1 GHz-40 GHz)	76.485
Transmitter Spurious Emissions (above 40 GHz)	76.485
Frequency Stability	76.485

## 2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	Occupied Bandwidth Radiated E.I.R.P Power Frequency Stability
<b>Test Condition</b>	Radiated measurement
<b>Operating Mode</b>	CTX

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	Transmitter Radiated Unwanted Emissions
<b>Test Condition</b>	Radiated measurement
<b>Operating Mode &lt; 1GHz</b>	CTX
The EUT was performed at X axis and Y axis position for Transmitter Radiated Unwanted Emissions test. "EUT in Y axis" generated the worst test result for Transmitter Radiated Unwanted Emissions above 1GHz test, thus the measurement for Transmitter Radiated Unwanted Emissions below 1GHz test will follow this same test configuration.	
1	EUT in Y axis
<b>Operating Mode &gt; 1GHz</b>	CTX
1	EUT in X axis
2	EUT in Y axis
Mode 2 has been evaluated to be the worst case after evaluating. Consequently, measurement will follow this same test mode.	

## 2.4 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.





## 2.5 Accessories

N/A

## 2.6 Support Equipment

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Automotive battery	YOASA	GTX7A-BS GTX7A-12B	N/A

## 2.7 Far Field Boundary Calculations

The far-field boundary is given as:

$$\text{far field} = (2 * L^2) / \lambda$$


where:

L = Largest Antenna Dimension, including the reflector, in meters

$\lambda$  = wavelength in meters

Far Field (m)				
Frequency (GHz)	L (m)	Lambda (m)	d(Far Field) (m)	d(Far Field) (cm)
76.485	0.042	0.0039223	0.899	89.95

## 2.8 Test Setup Diagram



### 3 Transmitter Test Result

#### 3.1 Occupied Bandwidth

##### 3.1.1 Occupied Bandwidth (OBW) Limit

Occupied Bandwidth (EBW) Limit
Information only


##### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

##### 3.1.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> For the Occupied bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 7.8.7 for EBW measurement.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.2 for occupied bandwidth testing.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 9 for radiated measurement.
<input checked="" type="checkbox"/> Radiated test was conducted at far-field distance. the distance from the radiating element of the EUT to the edge of the far field may be calculated from $[r \geq 2D^2/\lambda]$ r is the distance from the radiating element of the EUT to the edge of the far field, in m D is the largest dimension of both the radiating element and the test antenna (horn), in m λ is the wavelength of the emission under investigation $[300/f \text{ (MHz)}]$ , in m


##### 3.1.4 Test Setup





### 3.1.5 Test Result of Occupied Bandwidth

Test Results		
Test Freq. (GHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)
76.485	726.48	N/A



## 3.2 Radiated E.I.R.P Power

### 3.2.1 Radiated E.I.R.P Power Limit

Radiated E.I.R.P Power Limit	
<input checked="" type="checkbox"/>	76-81 GHz Band:
<input checked="" type="checkbox"/>	Peak: EIRP 55 dBm [279uW/cm <sup>2</sup> at 3m] Average: EIRP 50 dBm [88uW/cm <sup>2</sup> at 3m]


### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.2.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	For the Occupied bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 9 for radiated measurement.
<input checked="" type="checkbox"/>	<p>Radiated test was conducted at far-field distance. the distance from the radiating element of the EUT to the edge of the far field may be calculated from <math>[r \geq 2D^2/\lambda]</math>  <math>r</math> is the distance from the radiating element of the EUT to the edge of the far field, in m  <math>D</math> is the largest dimension of both the radiating element and the test antenna (horn), in m  <math>\lambda</math> is the wavelength of the emission under investigation <math>[300/f \text{ (MHz)}]</math>, in m</p>
<input checked="" type="checkbox"/>	<p>The measured power level is converted to EIRP using the Friis equation:  <math>E \text{ Meas} = 126.8 - 20\log(\lambda) + P - G</math></p> <p>where  <math>E</math> is the field strength of the emission at the measurement distance, in dBμV/m  <math>P</math> is the power measured at the output of the test antenna, in dBm  <math>\lambda</math> is the wavelength of the emission under investigation <math>[300/f\text{MHz}]</math>, in m  <math>G</math> is the gain of the test antenna, in dBi</p> <hr/> <p><math>EIRP = E \text{ Meas} + 20 \log(d \text{ Meas}) - 104.7</math></p> <p>where  <math>EIRP</math> : is the equivalent isotropically radiated power, in dBm.  <math>E \text{ Meas}</math> : is the field strength of the emission at the measurement distance, in dBμV/m.  <math>d \text{ Meas}</math> : is the measurement distance, in m.</p>

### 3.2.4 Test Setup



### 3.2.5 Test Result of Radiated E.I.R.P Power

Freq. (GHz)	Rx Gain (dBi)	P-Peak (dBm)	P-Average (dBm)	E-Meas- Peak (dBuV/m)	E-Meas- Average (dBuV/m)	Distance (m)	EIRP- Peak (dBm)	EIRP- Average (dBm)
76.485	23.6	-4.06	-15.16	147.27	136.17	1.00	42.47	35.26
<b>EIRP Limit</b>							<b>55</b>	<b>50</b>



### 3.3 Transmitter Radiated Unwanted Emissions

#### 3.3.1 Transmitter Radiated Unwanted Emissions Limit

Transmitter Radiated Unwanted Emissions Limit (Below 40 GHz)			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960 - 40000	500	54	3

Frequency Range (GHz)	EIRP (dBm)	Power Density (pW/cm <sup>2</sup> @ 3m)
40 - 200	-1.7	600
200 - 231	0.5	1000

#### 3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


#### 3.3.3 Test Procedures


Test Method – General Information	
<input checked="" type="checkbox"/> For the transmitter unwanted emissions shall be measured using following options below:	
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.3 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/>	For unwanted emissions below 40GHz bands.
<input checked="" type="checkbox"/>	Radiated emissions below 40 GHz shall not exceed the general limits in LP0002 Section 2.8
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 4.1.4.2.3 (Video Averaging) average measurements using spectrum reduced video bandwidth (VBW≥10Hz) - [duty cycle ≥ 98 or external power trigger].
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.1.4.2.4 average value of pulsed emissions.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak limit.

Test Method	
<input checked="" type="checkbox"/>	For radiated measurement below 40GHz.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.3 through 6.6 for radiated emissions from below 40 GHz.
<input checked="" type="checkbox"/>	For radiated measurement above 40GHz. Refer as ANSI C63.10, clause 9.12 for radiated measurement.
<input checked="" type="checkbox"/>	<p>Radiated test was conducted at far-field distance. the distance from the radiating element of the EUT to the edge of the far field may be calculated from <math>[r \geq 2D^2/\lambda]</math></p> <p>r is the distance from the radiating element of the EUT to the edge of the far field, in m  D is the largest dimension of both the radiating element and the test antenna (horn), in m  <math>\lambda</math> is the wavelength of the emission under investigation <math>[300/f \text{ (MHz)}]</math>, in m</p>
<input checked="" type="checkbox"/>	<p>The measured power level is converted to EIRP using the Friis equation:  <math>E \text{ Meas} = 126.8 - 20\log(\lambda) + P - G</math></p> <p>where  E is the field strength of the emission at the measurement distance, in dB<math>\mu</math>V/m  P is the power measured at the output of the test antenna, in dBm  <math>\lambda</math> is the wavelength of the emission under investigation <math>[300/f \text{ MHz}]</math>, in m  G is the gain of the test antenna, in dBi</p> <hr/> <p><math>EIRP = E \text{ Meas} + 20 \log(d \text{ Meas}) - 104.7</math></p> <p>where  EIRP : is the equivalent isotropically radiated power, in dBm.  E Meas : is the field strength of the emission at the measurement distance, in dB<math>\mu</math>V/m.  d Meas : is the measurement distance, in m.</p> <hr/> <p>Equations to calculate power density  Calculate the power density at the distance specified by the limit from the EIRP in watts using Equation:</p> $PD = \frac{EIRP_{Linear}}{4\pi d^2}$ <p>where  PD is the power density at the distance specified by the limit, in W/m<sup>2</sup>  EIRPLinear is the equivalent isotropically radiated power, in watts  d is the distance at which the power density limit is specified, in m.</p>



### 3.3.4 Test Setup





### 3.3.5 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

### 3.3.6 Test Result of Transmitter Radiated Unwanted Emissions (Below 30MHz)

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to KDB414788 Radiated Test Site, and the result came out very similar.

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10 harmonic or 40 GHz, whichever is appropriate.




### 3.3.7 Test Result of Transmitter Radiated Unwanted Emissions (30MHz ~ 1GHz)

Test Range	30 MHz – 1000 MHz	Test Freq. (GHz)	76.485
Test Distance	3 m		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	37.76	29.61	40.00	-10.39	39.25	0.80	21.06	31.50	100	358 Peak	HORIZONTAL
2	159.01	29.27	43.50	-14.23	42.98	1.60	16.52	31.83	200	323 Peak	HORIZONTAL
3	315.18	29.70	46.00	-16.30	39.26	2.29	20.25	32.10	100	240 Peak	HORIZONTAL
4	354.95	31.71	46.00	-14.29	40.05	2.47	21.34	32.15	150	307 Peak	HORIZONTAL
5	496.57	32.64	46.00	-13.36	38.44	2.92	23.75	32.47	150	179 Peak	HORIZONTAL
6	503.36	33.58	46.00	-12.42	39.25	2.94	23.86	32.47	200	350 Peak	HORIZONTAL

**Vertical**

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	39.70	30.32	40.00	-9.68	41.04	0.83	19.96	31.51	200	107	Peak
2	145.43	34.24	43.50	-9.26	47.42	1.54	17.31	32.03	200	114	Peak
3	209.45	36.38	43.50	-7.12	50.16	1.79	16.39	31.96	200	123	Peak
4	223.03	37.05	46.00	-8.95	50.53	1.88	16.62	31.98	200	170	Peak
5	241.46	38.25	46.00	-7.75	50.05	1.99	18.23	32.02	200	180	Peak
6	353.98	36.13	46.00	-9.87	44.50	2.47	21.30	32.14	200	150	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

**3.3.8 Test Result of Transmitter Radiated Unwanted Emissions (1GHz – 40GHz)**

<b>Test Range</b>	1GHz – 18GHz	<b>Test Freq. (GHz)</b>	76.485
<b>Test Distance</b>	1 m		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	16708.56	59.23	74.00	-14.77	43.48	10.36	39.60	34.21	148	178 Peak	HORIZONTAL
2	16710.32	45.46	54.00	-8.54	29.71	10.36	39.60	34.21	148	178 Average	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	16704.52	58.78	74.00	-15.22	43.03	10.36	39.60	34.21	174	33 Peak	VERTICAL
2	16709.76	46.69	54.00	-7.31	30.94	10.36	39.60	34.21	174	33 Average	VERTICAL



<b>Test Range</b>	18GHz – 40GHz	<b>Test Freq. (GHz)</b>	76.485
<b>Test Distance</b>	1 m		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	18070.24	45.03	63.54	-18.51	43.77	13.63	37.57	49.94	150	325	Average	HORIZONTAL
2	18072.17	59.18	83.54	-24.36	57.92	13.63	37.57	49.94	150	325	Peak	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	18071.58	45.71	63.54	-17.83	44.45	13.63	37.57	49.94	150	272	Average	VERTICAL
2	18072.38	60.44	83.54	-23.10	59.18	13.63	37.57	49.94	150	272	Peak	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

**3.3.9 Test Result of Transmitter Radiated Unwanted Emissions (40GHz – 200GHz)**

Test Freq. (GHz)	Rx Gain (dBi)	Distance (m)	Read Worse Frequency (GHz)	Read Level (dBm)	EIRP (dBm)	Specification Distance (m)	Power Density (pW/cm <sup>2</sup> )	Test Result
76.485	23.6	1.00	66.98	-84.73	-39.37	3	0.1022	PASS
Limit							600	-

Note :

EIRP = Read Level - Rx Gain +20\*LOG(4\*3.14159\* Distance / (300/(Test Freq.\*1000))).

Power Density = ((10<sup>^(EIRP/10)</sup>/1000)/(4\*3.14159\*(Specification Distance \*100)<sup>2</sup>))\*1000000000000.**3.3.10 Test Result of Transmitter Radiated Unwanted Emissions (200GHz – 231GHz)**

Test Freq. (GHz)	Rx Gain (dBi)	Distance (m)	Read Worse Frequency (GHz)	Read Level (dBm)	EIRP (dBm)	Specification Distance (m)	Power Density (pW/cm <sup>2</sup> )	Test Result
76.485	23.6	1.00	219.49	-90.51	-34.84	3	0.2901	PASS
Limit							1000	-

Note :

EIRP = Read Level - Rx Gain +20\*LOG(4\*3.14159\* Distance / (300/(Test Freq.\*1000))).

Power Density = ((10<sup>^(EIRP/10)</sup>/1000)/(4\*3.14159\*(Specification Distance \*100)<sup>2</sup>))\*1000000000000.

### 3.4 Frequency Stability

#### 3.4.1 Frequency Stability Limit

Frequency Stability Limit	
Fundamental emissions must be contained within the frequency bands specified in this 76-81GHz band during all conditions of operation. Equipment is presumed to operate over the temperature range -20 to +50 degrees Celsius with an input voltage variation of 85% to 115% of rated input voltage.	


#### 3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.4.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	For the frequency stability shall be measured using one of the options below:
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 9.14 for frequency stability measurement.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 9 for radiated measurement.
<input checked="" type="checkbox"/>	Radiated test was conducted at far-field distance. the distance from the radiating element of the EUT to the edge of the far field may be calculated from $[r \geq 2D^2/\lambda]$ r is the distance from the radiating element of the EUT to the edge of the far field, in m D is the largest dimension of both the radiating element and the test antenna (horn), in m $\lambda$ is the wavelength of the emission under investigation $[300/f \text{ (MHz)}]$ , in m
<input checked="" type="checkbox"/>	The mixer may be placed outside the chamber in front of the temperature chamber door, and the chamber door opened for each reading.

#### 3.4.4 Test Setup





**3.4.5 Test Result of Frequency Stability****Test Freq. (GHz): 76.485**

<b>Test Temperature: (°C)</b>	<b>Measured Frequency (MHz)</b>	<b>Delta Frequency (kHz)</b>	<b>Limit (±kHz)</b>
<b>-20</b>	76503.5421	-267.90	<b>within band</b>
<b>-10</b>	76503.2422	-567.80	<b>within band</b>
<b>0</b>	76503.1446	-665.40	<b>within band</b>
<b>10</b>	76503.5454	-264.60	<b>within band</b>
<b>20</b>	76503.8100	Reference	<b>within band</b>
<b>30</b>	76503.8423	32.30	<b>within band</b>
<b>40</b>	76503.4727	-337.30	<b>within band</b>
<b>50</b>	76503.5798	-230.20	<b>within band</b>
<b>60</b>	76503.6689	-141.10	<b>within band</b>
<b>Test Voltage: (Vdc)</b>	<b>Measured Frequency (MHz)</b>	<b>Delta Frequency (kHz)</b>	<b>Limit (±kHz)</b>
<b>10.2</b>	76503.8102	0.20	<b>within band</b>
<b>12</b>	76503.8100	Reference	<b>within band</b>
<b>13.8</b>	76503.8104	0.40	<b>within band</b>



## 4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 29, 2019	Mar. 28, 2020	Radiation (03CH05-CB)
Bilog Antenna with 6dB Attenuator	TESE & EMC	CBL 6112D & N-6-06	35236 & AT-N0610	30MHz ~ 2GHz	Mar. 28, 2019	Mar. 27, 2020	Radiation (03CH05-CB)
Horn Antenna	SCHWARZBECK	BBHA9120D	BBHA 9120D-1291	1GHz~18GHz	Oct. 05, 2019	Oct. 04, 2020	Radiation (03CH05-CB)
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170507	15GHz ~ 40GHz	Jun. 12, 2019	Jun. 11, 2020	Radiation (03CH05-CB)
Pre-Amplifier	EMCI	EMC330N	980331	20MHz ~ 3GHz	May 01, 2019	Apr. 30, 2020	Radiation (03CH05-CB)
Pre-Amplifier	EMCI	EMC12630SE	980287	1GHz ~ 26.5GHz	Apr. 16, 2019	Apr. 15, 2020	Radiation (03CH05-CB)
Pre-Amplifier	MITEQ	TTA1840-35-HG	1864479	18GHz ~ 40GHz	Jul. 03, 2019	Jul. 02, 2020	Radiation (03CH05-CB)
Spectrum Analyzer	R&S	FSP40	100304	9kHz ~ 40GHz	Aug. 15, 2019	Aug. 14, 2020	Radiation (03CH05-CB)
EMI Test Receiver	R&S	ESCS	826547/017	9kHz ~ 2.75GHz	May 15, 2019	May 14, 2020	Radiation (03CH05-CB)
RF Cable-low	Woken	RG402	LOW Cable-04+23	30MHz~1GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH05-CB)
RF Cable-high	Woken	RG402	High Cable-04	1GHz~18GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH05-CB)
RF Cable-high	Woken	RG402	High Cable-04+23	30MHz~18GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH05-CB)
RF Cable-high	Woken	RG402	High Cable-40G#1	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH05-CB)
RF Cable-high	Woken	RG402	High Cable-40G#2	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH05-CB)
Mixer	OML	M19HWA	U91113-1	40 ~ 60 GHz	Apr. 04 2019	Apr. 03, 2020	Radiation (03CH05-CB)
Mixer	OML	M15HWA	V91113-1	50 ~ 75 GHz	Apr. 04 2019	Apr. 03, 2020	Radiation (03CH05-CB)
Mixer	OML	M12HWA	E91113-1	60 ~ 90 GHz	Apr. 04 2019	Apr. 03, 2020	Radiation (03CH05-CB)
Mixer	OML	M08HWA	F91113-1	90 ~ 140 GHz	Apr. 04 2019	Apr. 03, 2020	Radiation (03CH05-CB)
Mixer	OML	M05HW/A	G91113-1	140 ~ 220 GHz	Apr. 04 2019	Apr. 03, 2020	Radiation (03CH05-CB)
Mixer	OML	M03HWD	120320-1	220 ~ 325 GHz	Apr. 04 2019	Apr. 03, 2020	Radiation (03CH05-CB)
Standard Horn Antenna	Custom Microwave	M19RH	U91113-A	40 ~ 60 GHz	N.C.R	N.C.R	Radiation (03CH05-CB)
Standard Horn Antenna	Custom Microwave	M15RH	V91113-A	50 ~ 75 GHz	N.C.R	N.C.R	Radiation (03CH05-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
Standard Horn Antenna	Custom Microwave	M12RH	E91113-A	60 ~ 90 GHz	N.C.R	N.C.R	Radiation (03CH05-CB)
Standard Horn Antenna	Custom Microwave	M08RH	F91113-A	90 ~ 140 GHz	N.C.R	N.C.R	Radiation (03CH05-CB)
Standard Horn Antenna	Custom Microwave	M05RH	G91113-A	140 ~ 220 GHz	N.C.R	N.C.R	Radiation (03CH05-CB)
Standard Horn Antenna	Custom Microwave	M03RH	120320-A	220 ~ 325 GHz	N.C.R	N.C.R	Radiation (03CH05-CB)
Temp. and Humidity Chamber	Gaint Force	GTH-408-40-C P-AR	MAA1410-011	-40~100 degree	Sep. 12, 2019	Sep. 11, 2020	Conducted (TH03-CB)

Note: Calibration Interval of instruments listed above is one year.

N.C.R. means Non-Calibration required.