

Company: Hangzhou Gubei Electronics Technology Co., Ltd

Add: Rooml06, No.1 Building, No.611 Jianghong Road Binjiang, Hangzhou, Zhejiang, China

Tel: 0571-86691817 Fax: 0571-86691817

Applican	\ <b>+</b>	Hangghau Cu	hai Flaats	vanias Tashnalasy Co. I td					
Applicant		Hangzhou Gubei Electronics Technology Co., Ltd  2ACDZ-WT1HBS05							
FCC ID:									
Section 15.212 Modular Transmitters									
Request for Modular A		• •	⊠ R	Request for Limited Modular Appro		\//NI\			
	ке	quirements	ا ما الم	EUT Conditions	Comply(	Y/IN)			
				Approval Requirements	Υ				
1	modular			'	Y				
		transmitter own shieldir							
		rystal and	•	cover.					
		may be l	_						
	•	•							
	external to the shielded radio elements.		ı radio						
2		ar transmitte	r must	All inputs to the modules are	Υ				
-		red modulati		buffered through logic or					
	inputs (if			microprocessor inputs.					
	•	to ensure th							
		comply with							
	requirement	s under condi	tions of						
	excessive	data rate	s or						
	over-modula	ation.							
3	The modul	ar transmitte	r must	Internal 3.3V power regulator.	Υ				
	have its	own power	supply	Refer to schematics.					
	regulation.								
4	The modul	ar transmitte	r must	The antenna is integral to the	Υ				
	comply wit	h the antenr	na and	device.					
	transmission	า	system						
	requirement		15.203,						
	15.204(b)	and 15.204(c	•						
	antenna	must eithe							
		attached or							
	•	intenna couple	•						
	connections	between the	module						

	and the antenna, including the cable). The "professional installation" provision of §15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.		
5	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in §15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see §15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see §15.31(i)).	The modular transmitter is tesed in a stand-alone configuration.  Please reference test setup photo for the stand-alone test configuration	Y
6	If using a permanently affixed label, the modular transmitter must be labeled with its own FCC identification number, and, if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into	Refer to the lable	Y

	which the module is installed						
	must also display a label referring						
	to the enclosed module. This						
	exterior label can use wording						
	such as the following: "Contains						
	Transmitter Module FCC ID:						
	XYZMODEL1" or "Contains FCC						
	ID: XYZMODEL1." Any similar						
	wording that expresses the same						
	meaning may be used. The						
	Grantee may either provide such						
	a label, an example of which must						
	be included in the application for						
	equipment authorization, or, must						
	provide adequate instructions						
	along with the module which						
	explain this requirement. In the						
	latter case, a copy of these						
	instructions must be included in						
	the application for equipment						
	authorization.						
7	The modular transmitter must	Refer to manual	Υ				
	comply with any specific rules or						
	operating requirements that						
	ordinarily apply to a complete						
	transmitter and the manufacturer						
	must provide adequate						
	instructions along with the module						
	to explain any such requirements.						
	A copy of these instructions must						
	be included in the application for						
	equipment authorization.						
8	The modular transmitter must	Refer to the test report	Υ				
	comply with any applicable RF						
	exposure requirements in its final						
	configuration						
Sincerely Yours,							
naney show							
C:	•						
Signatur	e: $\mathcal J$						

Title:Manager