

# FCC PART 15.247



## TEST REPORT


For

**Hangzhou Gubei Electronics Technology Co., Ltd**

Room106, No.1 Bui lding, No.611 Jianghong Road Binjiang, Hangzhou,Zhejiang,China

**FCC ID: 2ACDZ-WT1HBS05**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Embedded Wi-Fi Module
<b>Test Engineer:</b> Matt Yao	
<b>Report Number:</b> RKS150410001-00A	
<b>Report Date:</b> 2015-04-08	
<b>Reviewed By:</b> EMC Manager	Jesse Huang
<b>Prepared By:</b>	
Bay Area Compliance Laboratories Corp. (Kunshan) Chenghu Road,Kunshan Development Zone No.248,Kunshan, Jiangsu, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	



**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EQUIPMENT MODIFICATIONS .....	6
EUT EXERCISE SOFTWARE .....	6
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS .....</b>	<b>8</b>
<b>FCC§15.247 (i), §1.1310&amp; §2.1091 –MAXIMUM PERMISSIBLE.....</b>	<b>9</b>
<b>EXPOSURE (MPE).....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
ANTENNA CONNECTOR CONSTRUCTION .....	10
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
MEASUREMENT UNCERTAINTY.....	11
EUT SETUP .....	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE .....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
CORRECTED FACTOR & MARGIN CALCULATION .....	12
TEST RESULTS SUMMARY .....	13
TEST DATA .....	13
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>16</b>
APPLICABLE STANDARD .....	16
MEASUREMENT UNCERTAINTY.....	16
EUT SETUP .....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	17
TEST PROCEDURE .....	17
TEST EQUIPMENT LIST AND DETAILS.....	18
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	18
TEST RESULTS SUMMARY .....	18
TEST DATA .....	19
<b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....</b>	<b>32</b>
APPLICABLE STANDARD .....	32
TEST PROCEDURE .....	32
TEST EQUIPMENT LIST AND DETAILS.....	32

TEST DATA .....	32
<b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....</b>	<b>40</b>
APPLICABLE STANDARD .....	40
TEST PROCEDURE .....	40
TEST EQUIPMENT LIST AND DETAILS.....	40
TEST DATA .....	40
<b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>42</b>
APPLICABLE STANDARD .....	42
TEST PROCEDURE .....	42
TEST EQUIPMENT LIST AND DETAILS.....	42
TEST DATA .....	42
<b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>	<b>47</b>
APPLICABLE STANDARD .....	47
TEST PROCEDURE .....	47
TEST EQUIPMENT LIST AND DETAILS.....	47
TEST DATA .....	47

---

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The Hangzhou Gubei Electronics Technology Co., Ltd's product,model number: WT1HBS05 (FCC ID: 2ACDZ-WT1HBS05) or the "EUT" in this report was a Embedded Wi-Fi Module, which was measured approximately: 49.6mm x 31mm x 4mm, rated with input voltage: DC4. 5-5. 5 V from mainboard.

*\*The product ' s series model number : WT1, WT1PBS, WT1DBS, WT1FBS, WT1HBS, WT1H.They have the same or similar appearance, structure, PCB, Material and function to the testing products, and only are different for little parameters..*

*\*All measurement and test data in this report was gathered from production sample serial number:150309 (Assigned by the Hangzhou Gubei Electronics Technology Co., Ltd. The EUT supplied by the applicant was received on 2015-03-09)*

### Objective

This report is prepared on behalf of Hangzhou Gubei Electronics Technology Co., Ltd in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

N/A

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with RF radiated emission is 5.91 dB for 30MHz-1GHz.and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

## **Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Lake Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

For 802.11n-HT40 mode, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	8	2447
4	2427	9	2452
5	2432	/	/
6	2437	/	/
7	2442	/	/

EUT was tested with Channel 3, 6 and 9.

### Equipment Modifications

No modification was made to the EUT tested.

### EUT Exercise Software

RF test tool built-in the EUT.

The worst case was performed under:

802.11b: Data rate: 1 Mbps, Power level: 16

802.11g: Data rate: 6 Mbps, Power level: 9

802.11n-HT20: Data rate: MCS0, Power level: 9


802.11n-HT40: Data rate: MCS0, Power level: 17

**External I/O Cable**

Cable Description	Length (m)	From Port	To
N/A	/	/	/

**Block Diagram of Test Setup**

For conducted emission



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.247 (i), §1.1307 (b) (1)& §2.1091	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance



## FCC§15.247 (i), §1.1310& §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

### Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

### Calculated Data:

Mode	Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412	2	1.585	16.11	40.83	20	0.0129	1.0
802.11g	2412	2	1.585	14.01	25.18	20	0.0079	1.0
802.11n HT20	2412	2	1.585	13.40	21.88	20	0.0069	1.0
802.11n HT40	2452	2	1.585	13.38	21.78	20	0.0069	1.0

**Result:** The device meet FCC MPE at 20 cm distance

---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **Antenna Connector Construction**

The EUT has one integral antenna arrangement for wifi, which was permanently attached and the antenna gain is 2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207


### Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements may be receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Kunshan) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report.

Port	Expanded Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

### EUT Setup



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The adapter was connected to a 120 VAC/60 Hz power source.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

## Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	831294/005	2014-09-16	2015-09-16
Rohde & Schwarz	LISN	ESH3-Z5	12005	2014-09-16	2015-09-16
Rohde & Schwarz	LISN	ESH3-Z5	12008	2014-09-16	2015-09-16
Rohde & Schwarz	CE Test software	EMC 32	V 09.10.0	--	--

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, the worst margin reading as below:

**19.5 dB at 0.319 MHz in the line conducted mode**

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.


## Test Data

### Environmental Conditions

Temperature:	23 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


*The testing was performed by Matt Yao on 2015-03-21.*

*EUT operation mode: Transmitting*

**AC 120V/60 Hz, Line**

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.314718	38.3	9.000	L1	0.7	21.5	59.8	Compliance
0.319773	40.2	9.000	L1	0.7	19.5	59.7	Compliance
0.756101	34.5	9.000	L1	0.8	21.5	56.0	Compliance
0.805868	35.8	9.000	L1	0.7	20.2	56.0	Compliance
1.341955	33.5	9.000	L1	0.8	22.5	56.0	Compliance
1.385415	34.6	9.000	L1	0.8	21.4	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.319773	21.2	9.000	L1	0.7	28.5	49.7	Compliance
0.426011	18.7	9.000	L1	0.6	28.7	47.3	Compliance
0.715082	-0.2	9.000	L1	0.8	46.2	46.0	Compliance
0.812315	21.7	9.000	L1	0.7	24.3	46.0	Compliance
0.865782	19.8	9.000	L1	0.8	26.2	46.0	Compliance
1.453260	18.8	9.000	L1	0.8	27.2	46.0	Compliance

**AC 120V/60 Hz, Neutral**

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.162441	43.2	9.000	N	0.6	22.2	65.3	Compliance
0.207957	40.3	9.000	N	0.6	22.9	63.3	Compliance
0.259937	36.3	9.000	N	0.7	25.1	61.4	Compliance
0.324910	37.9	9.000	N	0.7	21.7	59.6	Compliance
1.352690	35.5	9.000	N	0.8	20.5	56.0	Compliance
0.162441	43.2	9.000	N	0.6	22.2	65.3	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.157346	27.7	9.000	N	0.6	27.9	55.6	Compliance
0.206306	23.6	9.000	N	0.6	29.7	53.4	Compliance
0.322331	22.0	9.000	N	0.7	27.6	49.6	Compliance
0.922769	19.8	9.000	N	0.9	26.2	46.0	Compliance
1.500325	22.5	9.000	N	0.8	23.5	46.0	Compliance
1.599078	13.7	9.000	N	0.8	32.4	46.0	Compliance

**Note:**

- 1) Corr.=LISN VDF (Voltage Division Factor) + Cable Loss
- 2) Corrected Amplitude = Reading + Corr.
- 3) Margin = Limit –Corrected Amplitude

## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Kunshan) is 5.91 dB for 30MHz-1GHz and 4.92 dB for above 1GHz, 1.95dB for conducted measurement at antenna port. And the uncertainty will not be taken into consideration for the test data recorded in the report

### EUT Setup

Below 1 GHz:





**Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The adapter was connected to a 120 VAC/60 Hz power source.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

**Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrument	Amplifier	330	171377	2014-09-16	2015-09-16
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2014-09-16	2015-09-16
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2014-09-12	2015-09-12
ETS	Horn Antenna	3115	6229	2014-09-12	2015-09-12
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-09-16	2015-09-16
Mini	Pre-amplifier	ZVA-183-S+	857001418	2014-09-16	2015-09-16
champrotek	Chamber	Chamber A	1#	2014-09-17	2015-09-17
R&S	Auto test Software	EMC32	V 09.10.0	-	-

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

**3.19 at 7234.88 MHz in the vertical polarization**  
for 802.11b mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

**Test Data****Environmental Conditions**


<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Matt Yao on 2015-03-24.

EUT operation mode: Transmitting

**30 MHz-1 GHz:**

The worst case was performed under 802.11b mode



Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
39.093750	43.68	QP	0.0	100.0	V	-10.3	33.38	40.00	6.62
44.913750	44.84	QP	0.0	200.0	V	-13.3	31.54	40.00	8.46
71.952500	50.7	QP	162.0	200.0	V	-17.1	33.60	40.00	6.40
95.960000	51.9	QP	114.0	200.0	H	-17.0	34.90	43.50	8.60
143.975000	50.56	QP	79.0	200.0	H	-11.9	38.66	43.50	4.84
200.113750	40.54	QP	90.0	100.0	H	-12.3	28.24	43.50	15.26

**1GHz-25GHz****802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Low Channel (2412 MHz)									
2412.00	89.12	PK	164	100	H	6.13	95.25	/	/
2412.00	84.55	Ave.	164	100	H	6.13	90.68	/	/
2412.00	89.75	PK	138	100	V	6.13	95.88	/	/
2412.00	85.02	Ave.	138	100	V	6.13	91.15	/	/
2367.72	40.96	PK	127	180	V	5.48	46.44	74	27.56
2367.72	24.96	Ave.	127	180	V	5.48	30.44	54	23.56
2496.89	34.91	PK	134	200	V	7.21	42.12	74	31.88
2496.89	21.43	Ave.	134	200	V	7.21	28.64	54	25.36
2611.41	32.01	PK	142	250	V	7.40	39.41	74	34.59
2611.41	18.80	Ave.	142	250	V	7.40	26.20	54	27.80
4824.00	42.86	PK	139	148	H	11.6	54.46	74	19.54
4824.00	37.53	Ave	139	148	H	11.6	49.13	54	4.87
7236.00	41.86	PK	175	100	V	17.3	59.16	74	14.84
7236.00	33.41	Ave	175	100	V	17.3	50.71	54	3.29

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2437 MHz)									
2437.00	87.97	PK	262	160	H	6.13	94.10	/	/
2437.00	83.05	Ave.	262	160	H	6.13	89.18	/	/
2437.00	89.48	PK	196	190	V	6.13	95.61	/	/
2437.00	84.89	Ave.	196	190	V	6.13	91.02	/	/
2388.56	40.99	PK	111	200	V	5.48	46.47	74	27.53
2388.56	25.52	Ave.	111	200	V	5.48	31.00	54	23.00
2492.86	37.96	PK	40	100	V	7.21	45.17	74	28.83
2492.86	23.02	Ave.	40	100	V	7.21	30.23	54	23.77
2520.53	34.03	PK	348	160	V	7.21	41.24	74	32.76
2520.53	21.00	Ave.	348	160	V	7.21	28.21	54	25.79
4874.00	35.00	PK	143.0	148	H	11.7	46.70	74	27.3
4874.00	22.43	Ave	143.0	148	H	11.7	34.13	54	19.87
7311.00	37.34	PK	168.0	100	V	17.4	54.74	74	19.26
7311.00	26.30	Ave	168.0	100	V	17.4	43.70	54	10.3

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2462 MHz)									
2462.00	87.33	PK	43	120	H	7.21	94.54	/	/
2462.00	82.58	Ave.	43	120	H	7.21	89.79	/	/
2472.00	87.10	PK	89	100	V	7.21	94.31	/	/
2472.00	82.55	Ave.	89	100	V	7.21	89.76	/	/
2384.39	36.29	PK	3	200	V	5.48	41.77	74	32.23
2384.39	22.26	Ave.	3	200	V	5.48	27.74	54	26.26
2483.53	41.31	PK	69	180	V	7.21	48.52	74	25.48
2483.53	30.98	Ave.	69	180	V	7.21	38.19	54	15.81
2527.70	38.31	PK	242	100	V	7.21	45.52	74	28.48
2527.70	28.06	Ave.	242	100	V	7.21	35.27	54	18.73
4924.00	40.26	PK	33.0	130	V	11.8	52.06	74	21.94
4924.00	32.81	Ave	33.0	130	V	11.8	44.61	54	9.39
7386.00	32.12	PK	2.0	100	V	17.6	49.72	74	24.28
7386.00	18.5	Ave	2.0	100	V	17.6	36.10	54	17.9

**802.11g Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
2412.00	89.97	PK	211	110	H	6.13	96.10	/	/
2412.00	79.29	Ave.	211	110	H	6.13	85.42	/	/
2412.00	90.53	PK	314	200	V	6.13	96.66	/	/
2412.00	79.85	Ave.	314	200	V	6.13	85.98	/	/
2389.36	45.01	PK	66	160	V	5.48	50.49	74	23.51
2389.36	29.39	Ave.	66	160	V	5.48	34.87	54	19.13
2491.63	35.89	PK	95	160	V	7.21	43.10	74	30.90
2491.63	22.26	Ave.	95	160	V	7.21	29.47	54	24.53
2570.45	32.97	PK	199	200	V	7.59	40.56	74	33.44
2570.45	18.28	Ave.	199	200	V	7.59	25.87	54	28.13
4824.00	35.64	PK	155.0	129	V	11.6	47.24	74	26.76
4824.00	20.74	Ave	155.0	129	V	11.6	32.34	54	21.66
7236.00	32.77	PK	2.0	100	V	17.3	50.07	74	23.93
7236.00	17.95	Ave	2.0	100	V	17.3	35.25	54	18.75

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2437 MHz)									
2437.00	88.61	PK	156	180	H	6.13	94.74	/	/
2437.00	77.73	Ave.	156	180	H	6.13	83.86	/	/
2437.00	89.15	PK	225	200	V	6.13	95.28	/	/
2437.00	78.43	Ave.	225	200	V	6.13	84.56	/	/
2380.38	39.57	PK	318	170	V	5.48	45.05	74	28.95
2380.38	26.04	Ave.	318	170	V	5.48	31.52	54	22.48
2483.67	36.76	PK	132	120	V	7.21	43.97	74	30.03
2483.67	23.02	Ave.	132	120	V	7.21	30.23	54	23.77
2619.41	33.48	PK	267	200	V	7.40	40.88	74	33.12
2619.41	19.46	Ave.	267	200	V	7.40	26.86	54	27.14
4874.00	34.22	PK	50.0	148	H	11.6	45.82	74	28.18
4874.00	20.89	Ave	50.0	148	H	11.6	32.49	54	21.51
7311.00	35.73	PK	200.0	100	V	17.5	53.23	74	20.77
7311.00	17.91	Ave	200.0	100	V	17.5	35.41	54	18.59

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15.247/205/209	
	Reading (dBµV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
High Channel (2462 MHz)									
2462.00	88.21	PK	54	180	H	7.21	95.42	/	/
2462.00	76.95	Ave.	54	180	H	7.21	84.16	/	/
2462.00	88.73	PK	146	210	V	7.21	95.94	/	/
2462.00	78.05	Ave.	146	210	V	7.21	85.26	/	/
2389.20	38.50	PK	124	220	V	5.48	43.98	74	30.02
2389.20	26.04	Ave.	124	220	V	5.48	31.52	54	22.48
2484.72	53.84	PK	301	200	V	7.21	61.05	74	12.95
2484.72	32.56	Ave.	301	200	V	7.21	39.77	54	14.23
2552.69	50.86	PK	286	140	V	7.59	58.45	74	15.55
2552.69	28.89	Ave.	286	140	V	7.59	36.48	54	17.52
4924.00	21.65	Ave	138.0	100	H	11.9	33.55	54	20.45
4924.00	37.41	PK	138.0	100	H	11.9	49.31	74	24.69
7386.00	20.82	Ave	221.0	200	H	17.6	38.42	54	15.58
7386.00	33.74	PK	221.0	100	H	17.6	51.34	74	22.66

**802.11n-HT20 Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
2412.00	88.73	PK	29	140	H	6.13	94.86	/	/
2412.00	78.46	Ave.	29	140	H	6.13	84.59	/	/
2412.00	91.09	PK	338	140	V	6.13	97.22	/	/
2412.00	79.97	Ave.	338	140	V	6.13	86.10	/	/
2390.00	49.92	PK	249	180	V	5.48	55.40	74	18.60
2390.00	33.69	Ave.	249	180	V	5.48	39.17	54	14.83
2485.19	37.94	PK	270	190	V	7.21	45.15	74	28.85
2485.19	23.71	Ave.	270	190	V	7.21	30.92	54	23.08
2645.32	34.71	PK	189	200	V	7.40	42.11	74	31.89
2645.32	21.02	Ave.	189	200	V	7.40	28.42	54	25.58
4824.00	35.12	PK	159.0	100	V	11.6	46.72	74	27.28
4824.00	20.75	Ave	159.0	100	V	11.6	32.35	54	21.65
7236.00	35.48	PK	144.0	100	V	17.3	52.78	74	21.22
7236.00	18.53	Ave	144.0	100	V	17.3	35.83	54	18.17

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2437 MHz)									
2437.00	88.65	PK	237	140	H	6.13	94.78	/	/
2437.00	78.22	Ave.	237	140	H	6.13	84.35	/	/
2437.00	90.21	PK	231	150	V	6.13	96.34	/	/
2437.00	79.16	Ave.	231	150	V	6.13	85.29	/	/
2389.36	42.92	PK	248	120	V	5.48	48.40	74	25.60
2389.36	27.88	Ave.	248	120	V	5.48	33.36	54	20.64
2486.01	39.89	PK	201	100	V	7.21	47.10	74	26.90
2486.01	24.96	Ave.	201	100	V	7.21	32.17	54	21.83
2511.54	36.16	PK	329	200	V	7.21	43.37	74	30.63
2511.54	21.40	Ave.	329	200	V	7.21	28.61	54	25.39
4874.00	37.27	PK	57.0	138	H	11.6	48.87	74	25.13
4874.00	21.88	Ave	57.0	138	H	11.6	33.48	54	20.52
7311.00	37.39	PK	189.0	100	V	17.5	54.89	74	19.11
7311.00	16.41	Ave	189.0	100	V	17.5	33.91	54	20.09

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2462 MHz)									
2462.00	88.46	PK	241	120	H	7.21	95.67	/	/
2462.00	77.71	Ave.	241	120	H	7.21	84.92	/	/
2462.00	88.37	PK	265	200	V	7.21	95.58	/	/
2462.00	77.38	Ave.	265	200	V	7.21	84.59	/	/
2387.60	40.24	PK	136	180	V	5.48	45.72	74	28.28
2387.60	27.46	Ave.	136	180	V	5.48	32.94	54	21.06
2483.67	55.61	PK	323	200	V	7.21	62.82	74	11.18
2483.67	35.41	Ave.	323	200	V	7.21	42.62	54	11.38
2525.49	53.36	PK	335	145	V	7.21	60.57	74	13.43
2525.49	32.08	Ave.	335	145	V	7.21	39.29	54	14.71
4924.00	21.76	Ave	141.0	100	H	11.8	33.56	54	20.44
4924.00	37.07	PK	141.0	100	H	11.8	48.87	74	25.13
7386.00	20.82	Ave	195.0	151	V	17.6	38.42	54	15.58
7386.00	34.28	PK	195.0	151	V	17.6	51.88	74	22.12



**802.11n-HT40 Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2422 MHz)									
2422.00	86.70	PK	330	200	H	6.13	92.83	/	/
2422.00	74.62	Ave.	330	200	H	6.13	80.75	/	/
2422.00	86.38	PK	179	170	V	6.13	92.51	/	/
2422.00	74.83	Ave.	179	170	V	6.13	80.96	/	/
2388.56	52.11	PK	79	100	V	5.48	57.59	74	16.41
2388.56	35.24	Ave.	79	100	V	5.48	40.72	54	13.28
2498.97	36.23	PK	173	160	V	7.21	43.44	74	30.56
2498.97	21.43	Ave.	173	160	V	7.21	28.64	54	25.36
2650.73	32.40	PK	191	170	V	7.40	39.80	74	34.20
2650.73	18.55	Ave.	191	170	V	7.40	25.95	54	28.05
4844.00	21.97	Ave	134.0	100	H	11.6	33.57	54	20.43
4844.00	37.44	PK	134.0	100	H	11.6	49.04	74	24.96
7236.00	35.14	PK	140.0	100.0	V	17.5	52.64	74	21.36
7236.00	14.36	Ave	140.0	100.0	V	17.5	31.86	54	22.14




Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2437 MHz)									
2437.00	85.72	PK	184	200	H	6.13	91.85	/	/
2437.00	73.83	Ave.	184	200	H	6.13	79.96	/	/
2437.00	85.59	PK	343	150	V	6.13	91.72	/	/
2437.00	73.71	Ave.	343	150	V	6.13	79.84	/	/
2390.00	45.28	PK	28	150	V	5.48	50.76	74	23.24
2390.00	29.39	Ave.	28	150	V	5.48	34.87	54	19.13
2484.92	38.24	PK	112	130	V	7.21	45.45	74	28.55
2484.92	23.02	Ave.	112	130	V	7.21	30.23	54	23.77
2647.74	31.14	PK	191	170	V	7.40	35.54	74	35.46
2647.74	15.47	Ave.	191	170	V	7.40	22.87	54	31.13
4874.00	20.75	Ave	147.0	100	V	11.6	32.35	54	21.65
4874.00	35.00	PK	147.0	100	V	11.6	46.60	74	27.4
7311.00	34.74	PK	147	100.0	V	17.5	52.24	74	21.76
7311.00	13.64	Ave	147	100.0	V	17.5	31.14	54	22.86


Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2452 MHz)									
2452.00	85.05	PK	95	100	H	6.13	91.18	/	/
2452.00	72.27	Ave.	95	100	H	6.13	78.40	/	/
2452.00	86.41	PK	287	100	V	6.13	92.54	/	/
2452.00	74.90	Ave.	287	100	V	6.13	81.03	/	/
2390.00	40.81	PK	268	120	V	5.48	46.29	74	27.71
2390.00	26.04	Ave.	268	120	V	5.48	31.52	54	22.48
2483.50	51.21	PK	155	138	V	7.21	58.42	74	15.58
2483.50	31.80	Ave.	155	138	V	7.21	39.01	54	14.99
2644.10	48.64	PK	103	180	V	7.40	56.04	74	17.96
2644.10	29.64	Ave.	103	180	V	7.40	37.04	54	16.96
4904.00	35.25	PK	159.0	129	V	11.8	47.05	74	26.95
4904.00	20.56	Ave	159.0	129	V	11.8	32.36	54	21.64
7356.00	36.46	PK	136.0	100	V	17.6	54.06	74	19.94
7356.00	17.92	Ave	136.0	100	V	17.6	35.52	54	18.48

**Conducted Spurious Emissions at Antenna Port****802.11b Low Channel****802.11b Middle Channel**

### 802.11b High Channel




### 802.11g Low Channel







### 802.11n-HT20 Low Channel




### 802.11n-HT20 Middle Channel



### 802.11n-HT20 High Channel



### 802.11n-HT40 Low Channel



0.5 dB Offset

Marker 1 [T1] 0.32 dBm 2.43192385 GHz

Ref Lvl 30.5 dBm RBW 100 kHz RF Att 60 dB

VBW 300 kHz SWT 6.4 s Unit dBm

1MAX

1 [T1] 0.32 dBm 2.43192385 GHz

2 [T1] -23.52 dBm 6.63529658 GHz

D1 -19.68 dBm

Start 30 MHz 2.497 GHz/ Stop 25 GHz

Date: 20.MAR.2015 15:14:21

Ref Lvl 30.5 dBm Marker 1 [T1] 3.99 dBm RBW 100 kHz RF Att 60 dB

2.45200000 GHz VBW 300 kHz SWT 6.4 s Unit dBm

0.5 dB Offset

1MAX

D1 -16.01 dBm

Start 30 MHz Stop 25 GHz


Date: 20.MAR.2015 15:16:40

**FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH****Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

**Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-09-16	2015-09-16

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

Temperature:	27 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

*The testing was performed by Matt Yao on 2015-03-20.*

**Test Result:** Pass.


Please refer to the following tables and plots.

*EUT operation mode: Transmitting*




Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode			
Low	2412	10.04	$\geq 500$
Middle	2437	10.04	$\geq 500$
High	2462	10.04	$\geq 500$
802.11g mode			
Low	2412	16.53	$\geq 500$
Middle	2437	16.53	$\geq 500$
High	2462	16.41	$\geq 500$
802.11n-HT20 mode			
Low	2412	17.43	$\geq 500$
Middle	2437	17.43	$\geq 500$
High	2462	17.56	$\geq 500$
802.11n-HT40 mode			
Low	2422	36.07	$\geq 500$
Middle	2437	36.01	$\geq 500$
High	2452	36.28	$\geq 500$

## 802.11b Low Channel



## 802.11b Middle Channel



Delta 2 [T1] -0.46 dB RBW 100 kHz RF Att 60 dB

Ref Lvl 30.5 dBm 10.04008016 MHz SWT 7.5 ms Unit dBm

0.5 dB Offset

D1 4.54 dBm

1MAX

1 10.54 dBm

2 2.46299198 GHz

2 2.45697996 GHz

2 2.46299198 GHz

Center 2.462 GHz 3 MHz/ Span 30 MHz

Date: 20.MAR.2015 12:58:55

Ref Lvl -2.26 dB VBW 300 kHz RF Att 60 dB

30.5 dBm 16.53306613 MHz SWT 7.5 ms Unit dBm

0.5 dB Offset

2 [T1] -6.52 dBm 2.40379359 GHz

2 [T1] -8.26 dBm 2.40379359 GHz

1 [T1] 4.75 dBm 2.41948497 GHz


1 [T1] 4.75 dBm 2.41948497 GHz

D1 -1.25 dBm 1max


Center 2.412 GHz 3 MHz/ Span 30 MHz

Date: 20.MAR.2015 13:05:34


### 802.11g Middle Channel




### 802.11g High Channel




## 802.11n-HT20 Low Channel




## 802.11n-HT20 Middle Channel




## 802.11n-HT20 High Channel




## 802.11n-HT40 Low Channel



## 802.11n-HT40 Middle Channel



## 802.11n-HT40 High Channel




## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210120	2014-11-03	2015-11-03
Agilent	Wideband Power Sensor	N1921A	MY54210115	2014-11-03	2015-11-03
Agilent	P-Series Power Meter	N1921A	MY5000465	2014-11-03	2015-11-03

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	27 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

*The testing was performed by Matt Yao on 2015-03-20*



*EUT operation mode: Transmitting*

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b				
Low	2412	16.11	14.02	30
Middle	2437	15.59	13.27	30
High	2462	14.83	12.78	30
802.11g				
Low	2412	14.01	11.74	30
Middle	2437	13.90	11.51	30
High	2462	13.57	11.09	30
802.11n-HT20				
Low	2412	13.40	11.62	30
Middle	2437	13.37	11.25	30
High	2462	12.55	10.79	30
802.11n-HT40				
Low	2422	13.30	11.99	30
Middle	2437	13.37	11.57	30
High	2452	13.38	11.29	30

**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE****Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-09-16	2015-09-16

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**


Temperature:	27 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

*The testing was performed by Matt Yao on 2015-03-20.*


**Test Result: Compliance**

Please refer to the following table and plots.


### 802.11b: Band Edge, Left Side




### 802.11b: Band Edge, Right Side




### 802.11g: Band Edge, Left Side




### 802.11g: Band Edge, Right Side




### 802.11n-HT20: Band Edge, Left Side




### 802.11n-HT20: Band Edge, Right Side



### 802.11n-HT40: Band Edge, Left Side



### 802.11n-HT40: Band Edge, Right Side



**FCC §15.247(e) - POWER SPECTRAL DENSITY****Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

**Test Procedure**

According to KDB558074 D01 DTS Meas Guidance v03r02 sub-clause 10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-09-16	2015-09-16

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

Temperature:	27 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

*The testing was performed by Matt Yao on 2015-03-20.*


*EUT operation mode: Transmitting*

**Test Result:** Pass


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-3.51	$\leq 8$
Middle	2437	-3.07	$\leq 8$
High	2462	-5.80	$\leq 8$
802.11g mode			
Low	2412	-12.59	$\leq 8$
Middle	2437	-14.06	$\leq 8$
High	2462	-11.45	$\leq 8$
802.11n-HT20 mode			
Low	2412	-11.93	$\leq 8$
Middle	2437	-11.66	$\leq 8$
High	2462	-12.91	$\leq 8$
802.11n-HT40 mode			
Low	2422	-14.32	$\leq 8$
Middle	2437	-13.80	$\leq 8$
High	2452	-12.94	$\leq 8$




### Power Spectral Density, 802.11b Low Channel




### Power Spectral Density, 802.11b Middle Channel




### Power Spectral Density, 802.11b High Channel




### Power Spectral Density, 802.11g Low Channel




### Power Spectral Density, 802.11g Middle Channel




### Power Spectral Density, 802.11g High Channel




### Power Spectral Density, 802.11n-HT20 Low Channel




### Power Spectral Density, 802.11n-HT20 Middle Channel




### Power Spectral Density, 802.11n-HT20 High Channel




### Power Spectral Density, 802.11n-HT40 Low Channel



### Power Spectral Density, 802.11n-HT40 Middle Channel



### Power Spectral Density, 802.11n-HT40 High Channel



\*\*\*\*\* END OF REPORT \*\*\*\*\*