



Shenzhen CTL Testing Technology Co., Ltd.  
Tel: +86-755-89486194 Fax: +86-755-26636041

## FCC PART 15 SUBPART C TEST REPORT

### Part 15.247

Report Reference No.....: **CTL1504200904-WF**

Compiled by

( position+printed name+signature) .: File administrators Happy Guo

Happy Guo

Name of the organization performing the tests

Test Engineer Nice Nong

Nice Nong

( position+printed name+signature) .:

Approved by

( position+printed name+signature) .: Manager Tracy Qi

Tracy Qi

Date of issue.....: Apr. 27, 2015

Test Laboratory Name .....: **Shenzhen CTL Testing Technology Co., Ltd.**

Address .....: Floor 1-A, Baisha Technology Park, No.3011, Shahe Xi Road, Nanshan District, Shenzhen, China 518055

Applicant's name.....: **SHENZHEN VIEWPAKER TECHNOLOGY., LTD**

Address .....: West of 2F, 3F, 4F, No.24 Building, Ma An Shan 2nd Industrial Zone, Shajing Street, Bao An District, Shenzhen, China

#### Test specification:

Standard .....: FCC Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

TRF Originator.....: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF.....: Dated 2011-01

#### Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description .....: ALL IN ONE PC MONITOR

FCC ID.....: 2ACEJ-E270DMG

Trade Mark .....: N/A

Model/Type reference .....: E270DMG, E270\*\*\*\*\*, E280\*\*\*\*\*, E320\*\*\*\*\*(\* can be '0-9' or 'A-Z' or '-' or space, \* is made up of 1-7 digit)

Modulation .....: 802.11b DSSS, 802.11g/n: OFDM

Work Frequency Range .....: 802.11b/g/n(20MHz): 2412~2462MHz  
802.11n(40MHz): 2422~2452

Antenna Type .....: internal

Antenna Gain.....: 2dBi

Result .....: **Positive**

**TEST REPORT**

<b>Test Report No. :</b> CTL1504200904-WF	Apr. 27, 2015 Date of issue
---	--------------------------------

Equipment under Test : ALL IN ONE PC MONITOR

Model /Type : E270DMG

Listed Models : E270\*\*\*\*\*, E280\*\*\*\*\*, E320\*\*\*\*\*(\* can be '0-9' or 'A-Z' or '-' or space, \* is made up of 1-7 digit)

Difference Description : Only the color and model's name is different.

**Applicant** : SHENZHEN VIEWPAKER TECHNOLOGY., LTD

Address : West of 2F, 3F, 4F, No.24 Building, Ma An Shan 2nd Industrial Zone, Shajing Street, Bao An District, Shenzhen, China

**Manufacturer** : SHENZHEN VIEWPAKER TECHNOLOGY., LTD

Address : West of 2F, 3F, 4F, No.24 Building, Ma An Shan 2nd Industrial Zone, Shajing Street, Bao An District, Shenzhen, China

**Test Result** according to the standards on page 4:

**Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

<b>1.</b>	<b><u>TEST STANDARDS .....</u></b>	<b><u>4</u></b>
<b>2.</b>	<b><u>SUMMARY .....</u></b>	<b><u>5</u></b>
2.1.	General Remarks	5
2.2.	Equipment Under Test	5
2.3.	Short description of the Equipment under Test (EUT)	5
2.4.	EUT operation mode	6
2.5.	EUT configuration	6
2.6.	NOTE	6
2.7.	Related Submittal(s) / Grant (s)	7
2.8.	Modifications	7
<b>3.</b>	<b><u>TEST ENVIRONMENT .....</u></b>	<b><u>8</u></b>
3.1.	Address of the test laboratory	8
3.2.	Test Facility	8
3.3.	Environmental conditions	8
3.4.	Configuration of Tested System	8
3.5.	Duty Cycle	9
3.6.	Statement of the measurement uncertainty	9
3.7.	Equipments Used during the Test	10
3.8.	Summary of Test Result	11
<b>4.</b>	<b><u>TEST CONDITIONS AND RESULTS.....</u></b>	<b><u>12</u></b>
4.1.	Conducted Emissions Test	12
4.2.	Radiated Emission and Bandedge Test	15
4.3.	6dB Bandwidth Measurement	23
4.4.	Maximum Peak Output Power	31
4.5.	Power Spectral Density Measurement	33
4.6.	Spurious RF Conducted Emission and bandedge	41
4.8.	Antenna Requirement	54
<b>5.</b>	<b><u>TEST SETUP PHOTOS OF THE EUT .....</u></b>	<b><u>55</u></b>
<b>6.</b>	<b><u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</u></b>	<b><u>57</u></b>

## **1. TEST STANDARDS**

The tests were performed according to following standards:

**FCC Part 15.247:** Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

**ANSI C63.10-2013:** American National Standard for Testing Unlicensed Wireless Devices.

**KDB Publication No. 558074 D01 v03r02 Guidance on Measurements for Digital Transmission Systems**



## 2. SUMMARY

### 2.1. General Remarks

Date of receipt of test sample	:	Apr. 20, 2015
Testing commenced on	:	Apr. 20, 2015
Testing concluded on	:	Apr. 27, 2015

### 2.2. Equipment Under Test

#### Power supply system utilised

Power supply voltage	:	<input checked="" type="radio"/> 120V / 60 Hz	<input type="radio"/> 115V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input type="radio"/> Other (specified in blank below)	

#### Description of the test mode

IEEE 802.11b/g/n(HT20): Thirteen channels are provided to the EUT, but only eleven channels used for USA.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

IEEE 802.11n (HT40): Nine channels are provided to the EUT, but only seven channels used for USA.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
3	2422	8	2447
4	2427	9	2452
5	2432		
6	2437		
7	2442		

### 2.3. Short description of the Equipment under Test (EUT)

**ALL IN ONE PC MONITOR**, support 802.11b/g/n.

For more details, refer to the user's manual of the EUT.

Serial number: Prototype



## 2.4. EUT operation mode

Test Mode:

1. The EUT has been tested under normal operating condition.
2. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed. Channel low (2412MHz), mid (2437MHz) and high (2462MHz) for 802.11b/g/n(HT20) and Channel low (2422MHz), mid (2437MHz) and high (2452MHz) for 802.11 n HT40 with highest data rate are chosen for full testing.
3. Test Mode:

Test Mode(TM)	Description	Remark
1	Transmitting	802.11 b 2412MHz, 2437MHz, 2462MHz
2	Transmitting	802.11 g 2412MHz, 2437MHz, 2462MHz
3	Transmitting	802.11 n HT20 2412MHz, 2437MHz, 2462MHz
4	Transmitting	802.11 n HT40 2422MHz, 2437MHz, 2452MHz

**Note:**The field strength of radiation emission was measured in the following position: EUT stand-up position (Y axis), lie-down position (X, Z axis).

The following data show only with the worst case setup.

The worst case of Y axis was reported.

Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report.

## 2.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

○ - supplied by the manufacturer

● - supplied by the lab

● Mouse

Manufacturer: DELL

Model: MS111-P

● Keyboard

Manufacturer: DELL

Model: KB2521

## 2.6. NOTE

1. The EUT is a ALL IN ONE PC MONITOR ,The functions of the EUT listed as below:

	Test Standards	Reference Report
WLAN 802.11b/g, 802.11n	FCC Part 15 Subpart C (Section15.247) FCC Per 47 CFR 2.1091(b)	CTL1504200904-WF CTL1504200904-WM

2. The frequency bands used in this EUT are listed as follows:

Frequency Band(MHz)	2400-2483.5	5150-5350	5470-5725	5725-5850
802.11b	✓	—	—	—
802.11g	✓	—	—	—
802.11n(20MHz)	✓	—	—	—
802.11n(40MHz)	✓	—	—	—

3. The EUT incorporates a SISO function, Physically, the EUT provides two completed transmitter and two completed receivers.

Modulation Mode	TX Function
802.11b	1TX
802.11g	1TX
802.11n (20MHz)	1TX
802.11n (40MHz)	1TX

## 2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCCID: 2ACEJ-E270DMG filing to comply with of the FCC part15.247 Rules.

## 2.8. Modifications

No modifications were implemented to meet testing criteria.



3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.  
Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2009) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.


3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Configuration of Tested System

Fig. 2-1 Configuration of Tested System





### 3.5. Duty Cycle

Operated Mode for Worst Duty Cycle		
<input type="checkbox"/> Operated normally mode for worst duty cycle		
<input checked="" type="checkbox"/> Operated test mode for worst duty cycle		
Mode	Duty Cycle (%)	Duty Factor (dB)
11b	100	0
11g	100	0
11n HT20	100	0
11n HT40	100	0

### 3.6. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	1~12.75GHz	4.32dB	(1)
Radiated Emission	12.75GHz-25 GHz	4.68dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3.7. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2014/07/12	2015/07/11
EMI Test Receiver	R&S	ESCI	103710	2014/07/10	2015/07/09
Spectrum Analyzer	Agilent	E4407B	MY45108355	2014/07/06	2015/07/05
Controller	EM Electronics	Controller EM 1000	N/A	2014/07/06	2015/07/05
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2014/07/12	2015/07/11
Horn Antenna	SCHWARZBECK	BBHA9170	1562	2014/07/12	2015/07/11
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2014/07/12	2015/07/11
LISN	R&S	ENV216	101316	2014/07/10	2015/07/09
LISN	SCHWARZBECK	NSLK8127	8127687	2014/07/10	2015/07/09
Microwave Preamplifier	HP	8349B	3155A00882	2014/07/10	2015/07/09
Amplifier	HP	8447D	3113A07663	2014/07/10	2015/07/09
Power Sensor	Rohde&Schwarz	OSP-120 (including B157)	115683	2014/07/02	2015/07/01
Transient Limiter	Com-Power	LIT-153	532226	2014/07/10	2015/07/09
Radio Communication Tester	R&S	CMU200	3655A03522	2014/07/06	2015/07/05
Temperature/Humidity Meter	zhicheng	ZC1-2	22522	2014/07/10	2015/07/09
SIGNAL GENERATOR	HP	8647A	3200A00852	2014/07/10	2015/07/09
Wideband Peak Power Meter	Anritsu	ML2495A	220.23.35	2014/07/06	2015/07/05
Power Sensor	Anritsu	MA2411B	0738552	2014/07/06	2015/07/05
Climate Chamber	ESPEC	EL-10KA	A20120523	2014/07/06	2015/07/05
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	/	2014/07/06	2015/07/05
High-Pass Filter	K&L	41H10-1375/U12750-O/O	/	2014/07/06	2015/07/05
RF Cable	HUBER+SUHNER	RG214	/	2014/07/09	2015/07/08

### 3.8. Summary of Test Result

FCC PART 15		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(2)	6dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Peak Output Power	PASS
FCC Part 15.247(e)	Power Spectral Density	PASS
FCC Part 15.109/ 15.205/ 15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge Compliance of RF Emission	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS

Remark: The measurement uncertainty is not included in the test result.

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.


Test Items	Mode	Data Rate	Channel
AC Power Conducted Emission	Normal Link	11 Mbps	1
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission	11b/DSSS	11 Mbps	1/6/11
	11g/OFDM	54 Mbps	1/6/11
	11n(20MHz)/OFDM	65Mbps	1/6/11
	11n(40MHz)/OFDM	150Mbps	3/6/9
Radiated Emission 30MHz~1GHz	11b/DSSS	11 Mbps	1/6/11
	11g/OFDM	54 Mbps	1/6/11
	11n(20MHz)/OFDM	65Mbps	1/6/11
	11n(40MHz)/OFDM	150Mbps	3/6/9
Radiated Emission 1GHz~10th Harmonic	11b/DSSS	11 Mbps	1/6/11
	11g/OFDM	54 Mbps	1/6/11
	11n(20MHz)/OFDM	65Mbps	1/6/11
	11n(40MHz)/OFDM	150Mbps	3/6/9
Band Edge Compliance of RF Emission	11b/DSSS	11 Mbps	1/11
	11g/OFDM	54 Mbps	1/11
	11n(20MHz)/OFDM	65Mbps	1/11
	11n(40MHz)/OFDM	150Mbps	3/9

Note1: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

## 4. TEST CONDITIONS AND RESULTS

### 4.1. Conducted Emissions Test

#### TEST CONFIGURATION



#### TEST PROCEDURE

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following:

Frequency (MHz)	Maximum RF Line Voltage (dBμV)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

\* Decreasing linearly with the logarithm of the frequency


For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

1. Please follow the guidelines in ANSI C63.10-2013.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

**The RBW/VBW for 150KHz to 30MHz: 9KHz**

**TEST RESULTS****SCAN TABLE: "Voltage (9K-30M)FIN"**

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "CTL150423137\_fin"**

4/23/2015 9:07AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.199500	40.30	10.2	64	23.3	QP	N	GND
14.095500	39.00	10.6	60	21.0	QP	N	GND
14.163000	40.20	10.6	60	19.8	QP	N	GND
14.230500	40.20	10.6	60	19.8	QP	N	GND
14.298000	40.30	10.7	60	19.7	QP	N	GND
14.365500	39.70	10.7	60	20.3	QP	N	GND

**MEASUREMENT RESULT: "CTL150423137\_fin2"**


4/23/2015 9:07AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
14.028000	36.20	10.6	50	13.8	AV	N	GND
14.095500	37.30	10.6	50	12.7	AV	N	GND
14.163000	38.70	10.6	50	11.3	AV	N	GND
14.230500	38.70	10.6	50	11.3	AV	N	GND
14.298000	38.70	10.7	50	11.3	AV	N	GND
14.365500	37.80	10.7	50	12.2	AV	N	GND



**SCAN TABLE: "Voltage (9K-30M)FIN"**

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "CTL150423138\_fin"**

4/23/2015 9:10AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.199500	41.80	10.2	64	21.8	QP	L1	GND
14.095500	38.70	10.6	60	21.3	QP	L1	GND
14.163000	39.90	10.6	60	20.1	QP	L1	GND
14.230500	39.90	10.6	60	20.1	QP	L1	GND
14.298000	40.00	10.7	60	20.0	QP	L1	GND
14.365500	39.40	10.7	60	20.6	QP	L1	GND

**MEASUREMENT RESULT: "CTL150423138\_fin2"**


4/23/2015 9:10AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
14.095500	37.00	10.6	50	13.0	AV	L1	GND
14.163000	38.40	10.6	50	11.6	AV	L1	GND
14.230500	38.30	10.6	50	11.7	AV	L1	GND
14.298000	38.50	10.7	50	11.5	AV	L1	GND
14.365500	37.50	10.7	50	12.5	AV	L1	GND
15.697500	35.80	10.7	50	14.2	AV	L1	GND


## 4.2. Radiated Emission and Bandedge Test

### TEST CONFIGURATION


#### (A) Radiated Emission Test Set-Up, Frequency Below 30MHz



#### (B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



#### (C) Radiated Emission Test Set-Up, Frequency above 1000MHz



**FIELD STRENGTH CALCULATION**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

**TEST PROCEDURE**

1. The testing follows FCC KDB Publication No. 558074 D01 v03r02 (Measurement Guidelines of DTS).
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for  $f > 1$  GHz, 100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Repeat above procedures until all frequency measurements have been completed.

**Note:**

When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the “cone of radiation” of EUT. The 3dB beamwidth is 60 degrees for H-plane and 90 degrees for E-plane.

**LIMIT**

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

**TEST RESULTS****9KHz-30MHz:**

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note: The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor= 40 log (specific distance/ test distance) (dB);


Limit line= specific limits (dBuV) + distance extrapolation factor.

**Below 1GHz:**

The radiated measurement are performed the each test mode (b/g/n) and channel (low/mid/high), the datum recorded below (802.11b mode, the middle channel) is the worst case for all the test mode and channel.

***SWEEP TABLE: "test (30M-1G)"***

Short Description:		Field Strength			
Start	Stop	Detector	Meas.	IF	Transducer
Frequency	Frequency		Time	Bandw.	
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	JB1


**MEASUREMENT RESULT: "CTL150422621\_red"**

4/22/2015 8:19PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
249.220000	43.10	14.1	46.0	2.9	---	0.0	0.00	HORIZONTAL
375.320000	44.70	17.7	46.0	1.3	---	0.0	0.00	HORIZONTAL
445.160000	34.40	19.2	46.0	11.6	---	0.0	0.00	HORIZONTAL
499.480000	36.30	20.4	46.0	9.7	---	0.0	0.00	HORIZONTAL
515.000000	35.90	20.5	46.0	10.1	---	0.0	0.00	HORIZONTAL
741.980000	35.70	24.1	46.0	10.3	---	0.0	0.00	HORIZONTAL

**SWEEP TABLE: "test (30M-1G)"**

Short Description:		Field Strength			
Start	Stop	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency				
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	JB1

**MEASUREMENT RESULT: "CTL150422622\_red"**

4/22/2015 8:20PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
109.540000	33.00	13.7	43.5	10.5	---	0.0	0.00	VERTICAL
179.380000	34.00	13.3	43.5	9.5	---	0.0	0.00	VERTICAL
249.220000	40.90	14.1	46.0	5.1	---	0.0	0.00	VERTICAL
371.440000	44.00	17.7	46.0	2.0	---	0.0	0.00	VERTICAL
445.160000	37.50	19.2	46.0	8.5	---	0.0	0.00	VERTICAL
499.480000	39.70	20.4	46.0	6.3	---	0.0	0.00	VERTICAL





## Above 1GHz:

802.11b

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	V	2411.9	83.0	30.8	113.8	Fundamental	/	PK
	V	3200	16.2	31.1	47.3	54(note3)	6.7	PK
	V	2390	36.7	32.2	68.9	74	5.1	PK
	V	2390	18.0	32.2	50.2	54	3.8	AV
	V	2400	37.6	32.1	69.7	74	4.3	PK
	V	2400	19.2	32.1	51.3	54	2.7	AV
	V	4824	7.7	42.6	50.3	54(note3)	3.7	PK
	V	7236	22.1	46.5	68.6	74	5.4	PK
	V	7236	3.4	46.5	49.9	54	4.1	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK
6	V	2437	81.9	31.2	113.1	Fundamental	/	PK
	V	3200	18.0	31.1	49.1	54(note3)	4.9	PK
	V	4876	16.1	32.8	48.9	54(note3)	5.1	PK
	V	7311	21.4	46.8	68.2	74	5.8	PK
	V	7311	4.2	46.1	50.3	54	3.7	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK
	V	2462.3	81.9	30.9	112.8	Fundamental	/	PK
11	V	3200	14.8	31.1	45.9	54(note3)	8.1	PK
	V	2483.5	38.9	30.2	69.1	74	4.9	PK
	V	2483.5	19.0	30.2	49.2	54	4.8	AV
	V	4927	16.2	32.5	48.7	54(note3)	5.3	PK
	V	7386	21.2	46.3	67.5	74	6.5	PK
	V	7386	1.5	46.3	47.8	54	6.2	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK

Note: 1. Measure Level = Reading Level + Factor.

2. The test results which are attenuated more than 20 dB below the permissible value limit (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Remark: RBW 1MHz VBW 3MHz peak detector for PK value, RMS detector for AV value

802.11g

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	V	2411.9	82.1	30.8	112.9	Fundamental	/	PK
	V	3200	17.1	31.1	48.2	54(note3)	5.8	PK
	V	2390	36.1	32.2	68.3	74	5.7	PK
	V	2390	18.2	32.2	50.4	54	3.6	AV
	V	2400	37.4	32.1	69.5	74	4.5	PK
	V	2400	19.6	32.1	51.7	54	2.3	AV
	V	4824	7.5	42.6	50.1	54(note3)	3.9	PK
	V	7236	22.2	46.5	68.7	74	5.3	PK
	V	7236	2.8	46.5	49.3	54	4.7	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK
6	V	2437	81.3	31.2	112.5	Fundamental	/	PK
	V	3200	16.2	31.1	47.3	54(note3)	6.7	PK
	V	4876	15.4	32.8	48.2	54(note3)	5.8	PK
	V	7311	22.0	46.8	68.8	74	5.2	PK
	V	7311	3.6	46.1	49.7	54	4.3	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK
11	V	2462.3	81.4	30.9	112.3	Fundamental	/	PK
	V	3200	15.6	31.1	46.7	54(note3)	7.3	PK
	V	2483.5	37.0	30.2	67.2	74	6.8	PK
	V	2483.5	18.9	30.2	49.1	54	4.9	AV
	V	4927	16.1	32.5	48.6	54(note3)	5.4	PK
	V	7386	22.6	46.3	68.9	74	5.1	PK
	V	7386	2.1	46.3	48.4	54	5.6	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK

Note: 1. Measure Level = Reading Level + Factor.

2. The test results which are attenuated more than 20 dB below the permissible value limit (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Remark: RBW 1MHz VBW 3MHz peak detector for PK value, RMS detector for AV value

802.11n(20MHz)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	V	2411.9	80.8	30.8	111.6	Fundamental	/	PK
	V	3200	16.2	31.1	47.3	54(note3)	6.7	PK
	V	2390	36.5	32.2	68.7	74	5.3	PK
	V	2390	18.0	32.2	50.2	54	3.8	AV
	V	2400	37.3	32.1	69.4	74	4.6	PK
	V	2400	19.0	32.1	51.1	54	2.9	AV
	V	4824	6.8	42.6	49.4	54(note3)	4.6	PK
	V	7236	22.1	46.5	68.6	74	5.4	PK
	V	7236	2.6	46.5	49.1	54	4.9	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK
6	V	2437	80.0	31.2	111.2	Fundamental	/	PK
	V	3200	17.4	31.1	48.5	54(note3)	5.5	PK
	V	4876	13.5	32.8	46.3	54(note3)	7.7	PK
	V	7311	22.3	46.8	69.1	74	4.9	PK
	V	7311	3.3	46.1	49.4	54	4.6	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK
11	V	2462.3	81.0	30.9	111.9	Fundamental	/	PK
	V	3200	16.1	31.1	47.2	54(note3)	6.8	PK
	V	2483.5	38.3	30.2	68.5	74	5.5	PK
	V	2483.5	18.2	30.2	48.4	54	5.6	AV
	V	4927	13.6	32.5	46.1	54(note3)	7.9	PK
	V	7386	22.5	46.3	68.8	74	5.2	PK
	V	7386	1.8	46.3	48.1	54	5.9	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK

Note: 1. Measure Level = Reading Level + Factor.

2. The test results which are attenuated more than 20 dB below the permissible value limit (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Remark: RBW 1MHz VBW 3MHz peak detector for PK value, RMS detector for AV value

802.11n(40MHz)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	V	2422	79.7	30.8	110.5	Fundamental	/	PK
	V	3200	17.1	31.1	48.2	54(note3)	5.8	PK
	V	2390	36.9	32.2	69.1	74	4.9	PK
	V	2390	17.0	32.2	49.2	54	4.8	AV
	V	2400	36.0	32.1	68.1	74	5.9	PK
	V	2400	15.1	32.1	47.2	54	6.8	AV
	V	4844	5.7	42.9	48.6	54(note3)	5.4	PK
	V	7266	22.1	46.8	68.9	74	5.1	PK
	V	7266	1.6	46.8	48.4	54	5.6	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK
6	V	2437	78.5	31.2	109.7	Fundamental	/	PK
	V	3200	16.5	31.1	47.6	54(note3)	6.4	PK
	V	4876	13.3	32.8	46.1	54(note3)	7.9	PK
	V	7311	21.5	46.8	68.3	74	5.7	PK
	V	7311	3.5	46.1	49.6	54	4.4	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK
11	V	2452	79.3	30.9	110.2	Fundamental	/	PK
	V	3200	17.5	31.1	48.6	54(note3)	5.4	PK
	V	2483.5	38.1	30.2	68.3	74	5.7	PK
	V	2483.5	18.9	30.2	49.1	54	4.9	AV
	V	4967	15.1	32.5	47.6	54(note3)	6.4	PK
	V	7356	23.6	46.1	69.7	74	4.3	PK
	V	7356	2.1	46.1	48.2	54	5.8	AV
	H	24000	11.7	38.9	50.6	54	3.4	PK

Note: 1. Measure Level = Reading Level + Factor.


2. The test results which are attenuated more than 20 dB below the permissible value limit (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Remark: RBW 1MHz VBW 3MHz peak detector for PK value, RMS detector for AV value

### 4.3. 6dB Bandwidth Measurement

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The testing follows FCC KDB Publication No. 558074 D01 v03r02 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.
4. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

#### LIMIT


For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

#### TEST RESULTS

Product	:	ALL IN ONE PC MONITOR
Test Item	:	6dB Occupied Bandwidth
Test Mode	:	Mode 1: Transmit by 802.11b


Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)	Limit (kHz)	Result
01	2412	11869	500	Pass
06	2437	12470	500	Pass
11	2462	11726	500	Pass

Channel 01 (2412MHz)






Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	ALL IN ONE PC MONITOR
Test Item	:	6dB Occupied Bandwidth
Test Mode	:	Mode 2: Transmit by 802.11g

Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)	Limit (kHz)	Result
01	2412	16556	500	Pass
06	2437	16530	500	Pass
11	2462	16550	500	Pass


### Channel 01 (2412MHz)



### Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	ALL IN ONE PC MONITOR
Test Item	:	6dB Occupied Bandwidth
Test Mode	:	Mode 3: Transmit by 802.11n (20MHz)

Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)	Limit (kHz)	Result
01	2412	17772	500	Pass
06	2437	17744	500	Pass
11	2462	17705	500	Pass


## Channel 01 (2412MHz)



## Channel 06 (2437MHz)



Channel 11 (2462MHz)







Product	:	ALL IN ONE PC MONITOR
Test Item	:	6dB Occupied Bandwidth
Test Mode	:	Mode 4: Transmit by 802.11n (40MHz)

Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)	Limit (kHz)	Result
03	2422	36502	500	Pass
06	2437	36506	500	Pass
09	2452	36536	500	Pass


## Channel 03 (2422MHz)



## Channel 06 (2437MHz)




Channel 09 (2452MHz)



#### 4.4. Maximum Peak Output Power

##### TEST CONFIGURATION



##### TEST PROCEDURE

According to C63.10 -2013 and KDB558074 D01 v03r02, The EUT was directly connected to the power meter / spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

Use the wideband power meter to test peak power and record the result.

##### LIMIT

The Peak Output Power Measurement limits are 30dBm.

##### TEST RESULTS

Product	:	ALL IN ONE PC MONITOR
Test Item	:	Power Output
Test Mode	:	Mode 1: Transmit by 802.11b

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
1	2412	18.63	30.00	Pass
6	2437	18.57	30.00	Pass
11	2462	18.52	30.00	Pass

Product	:	ALL IN ONE PC MONITOR
Test Item	:	Power Output
Test Mode	:	Mode 2: Transmit by 802.11g

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
1	2412	17.48	30.00	Pass
6	2437	17.19	30.00	Pass
11	2462	17.36	30.00	Pass

Product	:	ALL IN ONE PC MONITOR
Test Item	:	Power Output
Test Mode	:	Mode 3: Transmit by 802.11n(20MHz)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
1	2412	17.17	30.00	Pass
6	2437	17.06	30.00	Pass
11	2462	17.14	30.00	Pass


Product	:	ALL IN ONE PC MONITOR
Test Item	:	Power Output
Test Mode	:	Mode 4: Transmit by 802.11n(40MHz)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
3	2422	16.96	30.00	Pass
6	2437	16.64	30.00	Pass
9	2452	16.73	30.00	Pass

**Note: The test results including the cable lose.**

## 4.5. Power Spectral Density Measurement

### TEST CONFIGURATION



### TEST PROCEDURE

The EUT was tested according to KDB558074 D01 v03r02 for compliance to FCC 47CFR 15.247 and requirements.

Set RBW= 3 kHz, VBW $\geq$ 10KHz, SPAN to 1.5 times greater than the EBW,.

### LIMIT


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST RESULTS

Product	:	ALL IN ONE PC MONITOR
Test Item	:	Power Spectral Density
Test Mode	:	Mode 1: Transmit by 802.11b


Channel No.	Frequency (MHz)	Measurement PPSD (dBm/3KHz)	Limit (dBm/3KHz)	Result
01	2412	-6.058	8	Pass
06	2437	-7.147	8	Pass
11	2462	-8.215	8	Pass

Channel 01 (2412MHz)






Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	ALL IN ONE PC MONITOR
Test Item	:	Power Spectral Density
Test Mode	:	Mode 2: Transmit by 802.11g

Channel No.	Frequency (MHz)	Measurement PPSD (dBm/3KHz)	Limit (dBm/3KHz)	Result
01	2412	-9.328	8	Pass
06	2437	-8.611	8	Pass
11	2462	-9.952	8	Pass


### Channel 01 (2412MHz)



**Channel 06 (2437MHz)**




Channel 11 (2462MHz)




Product	:	ALL IN ONE PC MONITOR
Test Item	:	Power Spectral Density
Test Mode	:	Mode 3: Transmit by 802.11n (20MHz)

Channel No.	Frequency (MHz)	Measurement PPSD (dBm/3KHz)	Limit (dBm/3KHz)	Result
01	2412	-9.376	8	Pass
06	2437	-10.85	8	Pass
11	2462	-11.36	8	Pass


### Channel 01 (2412MHz)



**Channel 06 (2437MHz)**




Channel 11 (2462MHz)




Product	:	ALL IN ONE PC MONITOR
Test Item	:	Power Spectral Density
Test Mode	:	Mode 4: Transmit by 802.11n (40MHz)

Channel No.	Frequency (MHz)	Measurement PPSD (dBm/3KHz)	Limit (dBm/3KHz)	Result
03	2422	-14.94	8	Pass
06	2437	-14.58	8	Pass
09	2452	-14.22	8	Pass

### Channel 03 (2422MHz)




### Channel 06 (2437MHz)






Channel 09 (2452MHz)



## 4.6. Spurious RF Conducted Emission and bandedge

### TEST CONFIGURATION



### TEST PROCEDURE

The EUT was tested according to KDB558074 D01 v03r02 for compliance to FCC 47CFR 15.247 requirements.

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBM= 300KHz to measure the peak field strength, and measure frequency range from 30MHz to 26.5GHz.


### LIMIT



In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### TEST RESULTS



Product	:	ALL IN ONE PC MONITOR
Test Item	:	RF Antenna Conducted Spurious
Test Mode	:	Mode 1: Transmit by 802.11b

#### Channel 01 (2412MHz)








Channel 06 (2437MHz)






Channel 11 (2462MHz)





Product	:	ALL IN ONE PC MONITOR
Test Item	:	RF Antenna Conducted Spurious
Test Mode	:	Mode 2: Transmit by 802.11g

Channel 01 (2412MHz)








Channel 06 (2437MHz)






Channel 11 (2462MHz)





Product	:	ALL IN ONE PC MONITOR
Test Item	:	RF Antenna Conducted Spurious
Test Mode	:	Mode 3: Transmit by 802.11n (20MHz)




Channel 01 (2412MHz)



Channel 06 (2437MHz)






Channel 11 (2462MHz)





Product	:	ALL IN ONE PC MONITOR
Test Item	:	RF Antenna Conducted Spurious
Test Mode	:	Mode 4: Transmit by 802.11n (40MHz)

Channel 03 (2422MHz)








Channel 06 (2437MHz)



Channel 09 (2452MHz)



## 4.8. Antenna Requirement

### **STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

**Refer to statement below for compliance.**

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### **ANTENNA CONNECTED CONSTRUCTION**

The directional gains of antenna used for transmitting is 2 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Please see EUT photo for details.



## 5. Test Setup Photos of the EUT







## **6. External and Internal Photos of the EUT**


### **External Photos of EUT**














Internal Photos of EUT

























.....End of Report.....