

# **FCC RF Exposure Report**

FCC ID : 2ACF3BUZZILIGHT

Equipment : Buzzi Light Model No. : Buzzi Light

Brand Name : Blackloud Inc.

Applicant : Blackloud Inc.

Address : 42 Corporate Park #250 Irvine, CA 92606 USA

Standard : 47 CFR FCC Part 2.1091

Received Date : Aug. 29, 2015

Tested Date : Sep. 02 ~ Sep. 21, 2015

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

ilac-MRA

Taf Testing Laboratory 2732

Page: 1 of 5

Report No.: FA582901



## **Table of Contents**

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	4
1.2	MPE EVALUATION FORMULA	4
1.3	MPE EVALUATION RESULTS	4
2	TEST LABORATORY INFORMATION	F

Report No.: FA582901

Page : 2 of 5



## **Release Record**

Report No.	Version	Description	Issued Date	
FA582901	Rev. 01	Initial issue	Oct. 15, 2015	

Report No.: FA582901 Page: 3 of 5



#### 1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

#### 1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)		
300~1500	F/1500	30		
1500~100000	1.0	30		

#### 1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4*Pi*R^2}$$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pt= EIRP in mW Pi= 3.1416

R= Measurement distance

#### 1.3 MPE EVALUATION RESULTS

Modulation Type	Frequency Range (MHz)	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
BT LE	2402~2480	9.64	1	20	0.002	1
WLAN	2412~2462	17.11	1.2	20	0.013	1

Report No.: FA582901 Page: 4 of 5



### 2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan,

R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C. Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END===

Report No.: FA582901 Page: 5 of 5