

# FCC Radio Test Report

## FCC ID: 2ACG3TRX-1011

### Original Grant

**Report No.** : TB-FCC140407  
**Applicant** : HANGZHOU YANGCHANG I&E Co., LTD  
**Equipment Under Test (EUT)**  
**EUT Name** : Bluetooth speaker  
**Model No.** : TRX-1011  
**Series Model No.** : N/A  
**Brand Name** : N/A  
**Receipt Date** : 2014-05-23  
**Test Date** : 2014-05-26 to 2014-06-03  
**Issue Date** : 2014-06-04  
**Standards** : FCC Part 15, Subpart C(15.247)  
**Test Method** : ANSI C63.4:2003  
**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,  
The EUT technically complies with the FCC requirements

**Test/Witness Engineer** :

**Approved& Authorized** :



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

## Contents

<b>CONTENTS.....</b>	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT .....</b>	<b>4</b>
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test) .....	4
1.3 Block Diagram Showing the Configuration of System Tested.....	6
1.4 Description of Support Units .....	6
1.5 Description of Test Mode.....	7
1.6 Description of Test Software Setting .....	7
1.7 Test Facility.....	8
<b>2. TEST SUMMARY.....</b>	<b>9</b>
<b>3. CONDUCTED EMISSION TEST .....</b>	<b>10</b>
3.1 Test Standard and Limit.....	10
3.2 Test Setup.....	10
3.3 Test Procedure.....	10
3.4 Test Equipment Used.....	11
3.5 EUT Operating Mode .....	11
3.6 Test Data.....	11
<b>4. RADIATED EMISSION TEST .....</b>	<b>14</b>
4.1 Test Standard and Limit.....	14
4.2 Test Setup.....	15
4.3 Test Procedure.....	16
4.4 EUT Operating Condition .....	16
4.5 Test Equipment .....	16
<b>5. RESTRICTED BANDS REQUIREMENT .....</b>	<b>32</b>
5.1 Test Standard and Limit.....	32
5.2 Test Setup.....	32
5.3 Test Procedure.....	32
5.4 EUT Operating Condition .....	33
5.5 Test Equipment .....	33
<b>6. NUMBER OF HOPPING CHANNEL .....</b>	<b>44</b>
6.1 Test Standard and Limit.....	44
6.2 Test Setup.....	44
6.3 Test Procedure.....	44
6.4 EUT Operating Condition .....	44
6.5 Test Equipment .....	44
6.6 Test Data.....	44
<b>7. AVERAGE TIME OF OCCUPANCY .....</b>	<b>46</b>
7.1 Test Standard and Limit.....	46
7.2 Test Setup.....	46
7.3 Test Procedure.....	46

7.4 EUT Operating Condition .....	46
7.5 Test Equipment .....	46
7.6 Test Data .....	47
<b>8. CHANNEL SEPARATION AND BANDWIDTH TEST .....</b>	<b>59</b>
8.1 Test Standard and Limit .....	59
8.2 Test Setup .....	59
8.3 Test Procedure .....	59
8.4 EUT Operating Condition .....	59
8.5 Test Equipment .....	60
8.6 Test Data .....	60
<b>9. PEAK OUTPUT POWER TEST .....</b>	<b>68</b>
9.1 Test Standard and Limit .....	68
9.2 Test Setup .....	68
9.3 Test Procedure .....	68
9.4 EUT Operating Condition .....	68
9.5 Test Equipment .....	68
9.6 Test Data .....	68
<b>10. ANTENNA CONDUCTED SPURIOUS EMISSION .....</b>	<b>73</b>
10.1 Test Standard and Limit .....	73
10.2 Test Setup .....	73
10.3 Test Procedure .....	73
10.4 EUT Operating Condition .....	74
10.5 Test Equipment .....	74
10.6 Test Data .....	74
<b>11. ANTENNA REQUIREMENT .....</b>	<b>81</b>
11.1 Standard Requirement .....	81
11.2 Antenna Connected Construction .....	81
11.2 Result .....	81

# 1. General Information about EUT

## 1.1 Client Information

**Applicant** : HANGZHOU YANGCHANG I&E Co., LTD  
**Address** : A12A05 Room, NO.39, Blue Ocean International Times Building 1, Yile Road, Hangzhou City, Zhejiang Province, China  
**Manufacturer** : East West Life Technology CO., LTD  
**Address** : 6/F, Fuyuan Industry and commerce Building Chentian, hangcheng Industrial Area, Xixiang Town Bao'an District, Shenzhen, Guangdong, China

## 1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Bluetooth Speaker	
Models No.	:	TRX-1011	
Model Difference	:	N/A	
Product Description	:	Operation Frequency: Bluetooth:2402~2480MHz	
		Number of Channel:	Bluetooth:79 Channels <b>see note (2)</b>
		Max Peak Output Power:	8-DPSK: 0.439 dBm (Conducted Power)
		Antenna Gain:	0 dBi PCB Antenna
		Modulation Type:	GFSK 1Mbps(1 Mbps) $\pi$ /4-DQPSK(2 Mbps) 8-DPSK(3 Mbps)
Power Supply	:	DC Voltage supplied from Host System by USB cable DC power by Li-ion Battery	
Power Rating	:	DC 5.0V by USB cable DC 3.7V Li-ion Battery 850 mAh	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

### Note:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (2) This Test Report is FCC Part 15.247 for Bluetooth, and test procedure in accordance with Public Notice: DA 00-705.
- (3) Channel List:


Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456

01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		


(4) The Antenna information about the equipment is provided by the applicant.

### 1.3 Block Diagram Showing the Configuration of System Tested

#### USB Charging and Keeping TX Mode



#### TX Mode



### 1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/DOC	Manufacturer	Used “√”
PC	OPTIPLEX380	DOC	DELL	√
LCD Monitor	E170Sc	DOC	DELL	√
Keyboard	L100	DOC	DELL	√
Mouse	M-UARDEL7	DOC	DELL	√
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	YES	YES(2)	1.8M	
Cable 3	YES	NO	1.5M	

Cable 4	YES	NO	1.5M	
Cable 4	NO	NO	0.5M	Accessories

## 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	USB Charging and Keeping TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	USB Charging and Keeping TX Mode
Mode 2	TX Mode(GFSK) Channel 00/39/78
Mode 3	TX Mode( $\pi/4$ -DQPSK) Channel 00/39/78
Mode 4	TX Mode(8-DPSK) Channel 00/39/78
Mode 5	Hopping Mode(GFSK)
Mode 6	Hopping Mode( $\pi/4$ -DQPSK)
Mode 7	Hopping Mode(8-DPSK)

### Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test mode above.  
According to ANSI C63.4 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:  
TX Mode: GFSK (1 Mbps)  
TX Mode: 8-DPSK (3 Mbps)
- (2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power

selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

Test Software Version	Test Program: Bluetooth Authentication Test Tool v1.3.3-CE/FCC.exe		
Frequency	2402 MHz	2441MHz	2480 MHz
1 Mbps	0x0B0B	0x0B0B	0x0B0B
3 Mbps	0x0B0B	0x0B0B	0x0B0B

## 1.7 Test Facility

The testing was performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at:

1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China.

At the time of testing, the following bodies accredited the Laboratory:

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.



## 2. Test Summary

FCC Part 15 Subpart C(15.247)			
Standard Section	Test Item	Judgment	Remark
15.203	Antenna Requirement	PASS	N/A
15.207	Conducted Emission	PASS	N/A
15.205	Restricted Bands	PASS	N/A
15.247(a)(1)	Hopping Channel Separation	PASS	N/A
15.247(a)(1)	Dwell Time	PASS	N/A
15.247(b)(1)	Peak Output Power	PASS	N/A
15.247(b)(1)	Number of Hopping Frequency	PASS	N/A
15.247(c)	Radiated Spurious Emission	PASS	N/A
15.247(c)	Antenna Conducted Spurious Emission	PASS	N/A
15.247(a)	20dB Bandwidth	PASS	N/A
<b>Note:</b> N/A is an abbreviation for Not Applicable.			

## 3. Conducted Emission Test

### 3.1 Test Standard and Limit

#### 3.1.1 Test Standard

FCC Part 15.207

#### 3.1.2 Test Limit

**Conducted Emission Test Limit**

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) \*Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 3.2 Test Setup



### 3.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

### 3.4 Test Equipment Used

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	ROHDE& SCHWARZ	ESCI	100321	2013-08-10	2014-08-09
50ΩCoaxial Switch	Anritsu	MP59B	X10321	2013-08-10	2014-08-09
L.I.S.N	Rohde & Schwarz	ENV216	101131	2013-08-10	2014-08-09
L.I.S.N	SCHWARZBECK	NNBL 8226-2	8226-2/164	2013-08-10	2014-08-09


### 3.5 EUT Operating Mode

Please refer to the description of test mode.

### 3.6 Test Data


Please see the next page.

<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Terminal:</b>	Line		
<b>Test Mode:</b>	USB Charging with TX GFSK Mode 2402 MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2100	37.39	10.02	47.41	63.20	-15.79	QP	
2	*	0.2100	34.05	10.02	44.07	53.20	-9.13	AVG	
3		0.8300	28.54	10.09	38.63	56.00	-17.37	QP	
4		0.8300	22.01	10.09	32.10	46.00	-13.90	AVG	
5		2.7620	24.91	10.03	34.94	56.00	-21.06	QP	
6		2.7620	20.96	10.03	30.99	46.00	-15.01	AVG	
7		8.5060	22.72	10.11	32.83	60.00	-27.17	QP	
8		8.5060	16.68	10.11	26.79	50.00	-23.21	AVG	
9		13.7380	23.12	10.23	33.35	60.00	-26.65	QP	
10		13.7380	16.06	10.23	26.29	50.00	-23.71	AVG	
11		24.1860	22.17	10.16	32.33	60.00	-27.67	QP	
12		24.1860	10.03	10.16	20.19	50.00	-29.81	AVG	

**Emission Level= Read Level+ Correct Factor**



## 4. Radiated Emission Test

### 4.1 Test Standard and Limit

#### 4.1.1 Test Standard

FCC Part 15.209

#### 4.1.2 Test Limit

#### Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### Radiated Emission Limit (Above 1000MHz)


Frequency (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
Above 1000	74	54

**Note:**


(1) The tighter limit applies at the band edges.

(2) Emission Level (dBuV/m)=20log Emission Level (uV/m)


## 4.2 Test Setup



Bellow 30MHz Test Setup



Bellow 1000MHz Test Setup



Above 1GHz Test Setup

### 4.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) For the actual test configuration, please see the test setup photo.

### 4.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power in TX mode.

### 4.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015
Spectrum	Rohde & Schwarz	FSP30	DE25181	Aug. 10, 2013	Aug.09, 2014




Analyzer					
EMI Test Receiver	Rohde & Schwarz	ESCI	101165	Aug. 10, 2013	Aug.09, 2014
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 07, 2014	Mar.06, 2015
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	11909A	185903	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	8447B	3008A00849	Mar. 07, 2014	Mar.06, 2015
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 07, 2014	Mar.06, 2015
Signal Generator	Rohde & Schwarz	SML03	IKW682-054	Feb. 11, 2014	Feb.10, 2015
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A

## 4.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Test data please refer the following pages.


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		44.9006	42.05	-22.23	19.82	40.00	-20.18	peak
2		63.0916	49.57	-24.25	25.32	40.00	-14.68	peak
3		119.8556	49.83	-22.50	27.33	43.50	-16.17	peak
4	*	239.9874	57.14	-18.59	38.55	46.00	-7.45	peak
5		377.2591	52.67	-14.31	38.36	46.00	-7.64	peak
6		658.8362	42.93	-8.32	34.61	46.00	-11.39	peak

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		50.9420	52.79	-24.41	28.38	40.00	-11.62 peak
2		107.8877	51.43	-21.86	29.57	43.50	-13.93 peak
3		187.7530	50.59	-20.84	29.75	43.50	-13.75 peak
4		243.3772	52.42	-18.43	33.99	46.00	-12.01 peak
5	*	377.2591	55.13	-14.31	40.82	46.00	-5.18 peak
6		530.1014	43.68	-10.14	33.54	46.00	-12.46 peak

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4803.950	44.96	13.44	58.40	74.00	-15.60	peak
2	*	4803.950	29.49	13.44	42.93	54.00	-11.07	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4803.960	46.52	13.44	59.96	74.00	-14.04	peak
2	*	4803.960	29.98	13.44	43.42	54.00	-10.58	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4881.972	42.57	13.90	56.47	74.00	-17.53	peak
2	*	4881.972	30.03	13.90	43.93	54.00	-10.07	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4881.960	44.97	13.90	58.87	74.00	-15.13	peak
2	*	4881.960	29.88	13.90	43.78	54.00	-10.22	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4989.968	44.16	14.54	58.70	74.00	-15.30	peak
2	*	4989.968	30.67	14.54	45.21	54.00	-8.79	AVG

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4959.970	44.87	14.36	59.23	74.00	-14.77	peak
2	*	4959.970	30.76	14.36	45.12	54.00	-8.88	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		4803.978	42.56	13.44	56.00	74.00	-18.00 peak
2	*	4803.978	30.50	13.44	43.94	54.00	-10.06 AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4803.970	45.24	13.44	58.68	74.00	-15.32	peak
2	*	4803.970	30.09	13.44	43.53	54.00	-10.47	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4881.985	44.85	13.90	58.75	74.00	-15.25	peak
2	*	4881.985	31.20	13.90	45.10	54.00	-8.90	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4881.895	44.21	13.90	58.11	74.00	-15.89	peak
2	*	4881.895	30.87	13.90	44.77	54.00	-9.23	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4959.898	43.89	14.36	58.25	74.00	-15.75	peak
2	*	4959.898	30.47	14.36	44.83	54.00	-9.17	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4959.957	45.01	14.36	59.37	74.00	-14.63	peak
2	*	4959.957	31.40	14.36	45.76	54.00	-8.24	AVG

Emission Level= Read Level+ Correct Factor

## 5. Restricted Bands Requirement

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard


FCC Part 15.209

FCC Part 15.205

#### 5.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54
<b>Note: All restriction bands have been tested, only the worst case is reported.</b>		

### 5.2 Test Setup



### 5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked



and then Quasi Peak detector mode re-measured.

- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) For the actual test configuration, please see the test setup photo.

## 5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

## 5.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015
Spectrum Analyzer	Rohde & Schwarz	FSP30	DE25181	Aug. 10, 2013	Aug.09, 2014
EMI Test Receiver	Rohde & Schwarz	ESCI	101165	Aug. 10, 2013	Aug.09, 2014
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 07, 2014	Mar.06, 2015
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	11909A	185903	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	8447B	3008A00849	Mar. 07, 2014	Mar.06, 2015
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 07, 2014	Mar.06, 2015
Signal Generator	Rohde & Schwarz	SML03	IKW682-054	Feb. 11, 2014	Feb.10, 2015
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A


## 5.6 Test Data

All restriction bands have been tested, only the worst case is reported.

For above 1GHz , RBW 1MHz , VBW 3MHz PK detector for PK value , RBW 1MHz , VBW 10Hz PK detector for AV value

## (1) Radiation Test


EUT:	Bluetooth Speaker	Model Name :	TRX-1011
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2350.000	52.90	0.61	53.51	74.00	-20.49	peak
2	*	2350.000	40.36	0.61	40.97	54.00	-13.03	AVG
3		2390.000	50.88	0.77	51.65	74.00	-22.35	peak
4		2390.000	39.29	0.77	40.06	54.00	-13.94	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Bluetooth Speaker	Model Name :	TRX-1011
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	51.54	0.77	52.31	74.00	-21.69	peak
2	*	2390.000	39.24	0.77	40.01	54.00	-13.99	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2480 MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2483.500	53.89	1.17	55.06	74.00	-18.94	peak
2	*	2483.500	51.50	1.17	52.67	54.00	-1.33	AVG
3		2500.000	51.31	1.23	52.54	74.00	-21.46	peak
4		2500.000	39.05	1.23	40.28	54.00	-13.72	AVG

**Emission Level= Read Level+ Correct Factor**


EUT:	Bluetooth Speaker	Model Name :	TRX-1011
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2480 MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV		dBuV/m	dBuV/m	dB Detector
1		2483.500	54.75	1.17	55.92	74.00	-18.08 peak
2	*	2483.500	48.98	1.17	50.15	54.00	-3.85 AVG
3		2500.000	51.12	1.23	52.35	74.00	-21.65 peak
4		2500.000	39.08	1.23	40.31	54.00	-13.69 AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		2390.000	50.93	0.77	51.70	74.00	-22.30 peak
2	*	2390.000	39.08	0.77	39.85	54.00	-14.15 AVG

**Emission Level= Read Level+ Correct Factor**


<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	51.29	0.77	52.06	74.00	-21.94	peak
2	*	2390.000	39.06	0.77	39.83	54.00	-14.17	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Speaker	Model Name :	TRX-1011
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX 8-DPSK Mode 2480MHz		
Remark:	N/A		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2483.500	54.48	1.17	55.65	74.00	-18.35	peak
2	*	2483.500	50.04	1.17	51.21	54.00	-2.79	AVG
3		2500.000	51.31	1.23	52.54	74.00	-21.46	peak
4		2500.000	38.92	1.23	40.15	54.00	-13.85	AVG

Emission Level= Read Level+ Correct Factor



<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	N/A		





No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2483.500	54.12	1.17	55.29	74.00	-18.71	peak
2	*	2483.500	48.56	1.17	49.73	54.00	-4.27	AVG
3		2500.000	50.45	1.23	51.68	74.00	-22.32	peak
4		2500.000	38.96	1.23	40.19	54.00	-13.81	AVG



**Emission Level= Read Level+ Correct Factor**

## (2) Conducted Test

<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz / 2480 MHz		
<b>Remark:</b>	Hopping on mode and hopping off mode all have been tested, only list the worst case hopping off mode in report		



<b>EUT:</b>	Bluetooth Speaker	<b>Model Name :</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz / 2480 MHz		
<b>Remark:</b>	Hopping on mode and hopping off mode all have been tested, only list the worst case hopping off mode in report		



## 6. Number of Hopping Channel

### 6.1 Test Standard and Limit


#### 6.1.1 Test Standard

FCC Part 15.247 (a)(1)

#### 6.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

### 6.2 Test Setup



### 6.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:RBW=100 KHz, VBW=100 KHz, Sweep time= Auto.

### 6.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.


### 6.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015


### 6.6 Test Data

<b>EUT:</b>	Bluetooth speaker	<b>Model:</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	Hopping Mode (GFSK/ 8-DPSK)		
Frequency Range	Quantity of Hopping Channel	Limit	
2402MHz~2480MHz	79	>15	
	79		

### GFSK Mode



### 8-DPSK



## 7. Average Time of Occupancy

### 7.1 Test Standard and Limit


#### 5.1.1 Test Standard

FCC Part 15.247 (a)(1)

#### 5.1.2 Test Limit

Section	Test Item	Limit
15.247(a)(1)/ RSS-210 Annex 8(A8.1d)	Average Time of Occupancy	0.4 sec

### 7.2 Test Setup



### 7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=1MHz.
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.

### 7.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.


### 7.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015




### GFSK Hopping Mode DH1

2441 MHz



### GFSK Hopping Mode DH1

2480 MHz






EUT:		Bluetooth speaker		Model:		TRX-1011	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.7V					
Test Mode:		Hopping Mode (GFSK DH3)					
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result		
2402	1.675	268.00	31.60	400	PASS		
2441	1.700	272.00					
2480	1.713	274.08					


## GFSK Hopping Mode DH3

**2402 MHz**




### GFSK Hopping Mode DH3

2441 MHz



### GFSK Hopping Mode DH3


2480 MHz



EUT:	Bluetooth speaker	Model:	TRX-1011		
Temperature:	25 °C	Relative Humidity:	55%		
Test Voltage:	DC 3.7V				
Test Mode:	Hopping Mode (GFSK DH5)				
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	2.975	317.33	31.60	400	PASS
2441	3.000	320.00			
2480	2.975	317.33			


GFSK Hopping Mode DH5

2402 MHz




### GFSK Hopping Mode DH5

2441 MHz



### GFSK Hopping Mode DH5

2480 MHz



EUT:		Bluetooth speaker	Model:		TRX-1011
Temperature:		25 °C	Relative Humidity:		55%
Test Voltage:		DC 3.7V			
Test Mode:		Hopping Mode (8-DPSK DH1)			
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	0.413	132.16	31.60	400	PASS
2441	0.425	136.00			
2480	0.438	140.16			

8-DPSK Hopping Mode DH1

2402 MHz

Agilent15:11:27 Jun 3, 2014

Ref 10 dBm

Atten 20 dB

Mkr1 Δ 412.5 μs1.015 dB

Peak

Log

10

dB/

Offst

2

dB

Marker Δ

412.500000 μs

1.015 dB

W1 S2

S3 FS

AA

Center 2.402 GHz

Res BW 1 MHz


#VBW 1 MHz

Span 0 Hz

Sweep 5 ms (401 pts)


**8-DPSK Hopping Mode DH1**

**2441 MHz**



**8-DPSK Hopping Mode DH1**


**2480 MHz**



EUT:		Bluetooth speaker		Model:		TRX-1011	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.7V					
Test Mode:		Hopping Mode (8-DPSK DH3)					
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result		
2402	1.675	268.00	31.60	400	PASS		
2441	1.713	274.08					
2480	1.700	272.00					


**8-DPSK Hopping Mode DH3**

**2402 MHz**




**8-DPSK Hopping Mode DH3**

**2441 MHz**



**8-DPSK Hopping Mode DH3**

**2480 MHz**





EUT:		Bluetooth speaker		Model:		TRX-1011	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.7V					
Test Mode:		Hopping Mode (8-DPSK DH5)					
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result		
2402	2.982	318.08	31.60	400	PASS		
2441	3.000	320.00					
2480	2.950	314.67					

8-DPSK Hopping Mode DH5

2402 MHz

Agilent14:19:35 Jun 5, 2014

Ref 10 dBm

#Atten 20 dB

Mkr1 Δ 2.982 ms  
-2.237 dB

Peak Log 10 dB/Offst 2 dB

Marker Δ 2.982450000 ms  
-2.237 dB

W1 S2 S3 FS AA

Center 2.402 GHz

Res BW 1 MHz


#VBW 1 MHz

Sweep 10.11 ms (401 pts)

Span 0 Hz


### 8-DPSK Hopping Mode DH5

2441 MHz



### 8-DPSK Hopping Mode DH5

2480 MHz



## 8. Channel Separation and Bandwidth Test

### 8.1 Test Standard and Limit


#### 8.1.1 Test Standard

FCC Part 15.247

#### 8.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	$\leq 1$ MHz (20dB bandwidth)	2400~2483.5
Channel Separation	$>25$ KHz or $>$ two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

### 8.2 Test Setup



### 8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Channel Separation: RBW=30 kHz, VBW=100 kHz.  
Bandwidth: RBW=30 kHz, VBW=100 kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:30 kHz, and Video Bandwidth:100 kHz. Sweep Time set auto.

### 8.4 EUT Operating Condition

The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.

## 8.5 Test Equipment


Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015

## 8.6 Test Data

EUT:	Bluetooth speaker	Model:	TRX-1011
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX Mode (GFSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	842.62	878.34	585.56
2441	838.45	862.12	574.75
2480	833.02	880.39	586.93


## GFSK TX Mode

**2402 MHz**




**GFSK TX Mode**


**2441 MHz**



**GFSK TX Mode**


**2480 MHz**



<b>EUT:</b>	Bluetooth speaker	<b>Model:</b>	TRX-1011
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode (8-DPSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	1150.40	1274.00	849.33
2441	1149.70	1269.00	846.00
2480	1150.60	1269.00	846.00
<b>8-DPSK TX Mode</b>			
<b>2402 MHz</b>			
			


**8-DPSK TX Mode**

**2441 MHz**



**8-DPSK TX Mode**


**2480 MHz**



EUT:	Bluetooth speaker	Model:	TRX-1011
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	Hopping Mode (GFSK)		
Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit (kHz)	
2402	1057.5	585.56	
2441	952.5	574.75	
2480	945.0	586.93	

### GFSK Hopping Mode


2402 MHz






**GFSK Hopping Mode**


**2441 MHz**



**GFSK Hopping Mode**


**2480 MHz**






### 8-DPSK Hopping Mode

2441 MHz



### 8-DPSK Hopping Mode

2480 MHz



## 9. Peak Output Power Test

### 9.1 Test Standard and Limit


#### 9.1.1 Test Standard

FCC Part 15.247 (b) (1)

#### 9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

### 9.2 Test Setup



### 9.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.  
RBW=3 MHz, VBW=3 MHz for bandwidth more than 1MHz.


### 9.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

### 9.5 Test Equipment


Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015

### 8.6 Test Data




**GFSK TX Mode**


**2441 MHz**



**GFSK TX Mode**


**2480 MHz**






**8-DPSK TX Mode**

**2441 MHz**



**8-DPSK TX Mode**

**2480 MHz**





## 10. Antenna Conducted Spurious Emission

### 10.1 Test Standard and Limit

#### 10.1.1 Test Standard


FCC Part 15.247 (d)

#### 10.1.2 Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above~960	500	3

### 10.2 Test Setup



### 10.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
 RBW=100 KHz, VBW=300 KHz.  
 Frequency range: from 30MHz to 25 GHz

## 10.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.


## 10.5 Test Equipment

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015


## 10.6 Test Data

TX CH 00 2402MHz (1 Mbps)

Above 1 GHz




Bellow 1 GHz




TX CH 39 2441MHz (1 Mbps)

Above 1 GHz




Bellow 1 GHz




TX CH 78 2480MHz (1 Mbps)

Above 1 GHz




Bellow 1 GHz




TX CH 00 2402MHz (3 Mbps)

Above 1 GHz




Bellow 1 GHz




TX CH 39 2441MHz (3 Mbps)

Above 1 GHz




Bellow 1 GHz




TX CH 78 2480MHz (3 Mbps)

Above 1 GHz



Bellow 1 GHz





## **11. Antenna Requirement**

### **11.1 Standard Requirement**

#### **11.1.1 Standard**

FCC Part 15.203

#### **11.1.2 Requirement**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **11.2 Antenna Connected Construction**

The directional gains of the antenna used for transmitting is 0 dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

### **11.2 Result**

The EUT antenna is a PCB Antenna. It complies with the standard requirement.