

APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
IMC INTERNATIONAL INC.

7 inch 3G TABLET
Model No.: ROAD XT-71BG

FCC ID: 2ACI7-ROADXT-71BG

Prepared for : IMC INTERNATIONAL INC.
Address : 28E Jingang, xixiang, Bao an District, Shenzhen,
Guangdong Province, China
Prepared by : ACCURATE TECHNOLOGY CO., LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report No. : ATE20140926
Date of Test : Jun 04, 2014- Jun 28, 2014
Date of Report : Jun 28, 2014

TABLE OF CONTENTS

| Description | Page |
|--|-----------|
| Test Report Certification | |
| 1. GENERAL INFORMATION | 5 |
| 1.1. Description of Device (EUT)..... | 5 |
| 1.2. Carrier Frequency of Channels..... | 6 |
| 1.3. Accessory and Auxiliary Equipment | 6 |
| 1.4. Description of Test Facility | 6 |
| 1.5. Measurement Uncertainty..... | 7 |
| 2. MEASURING DEVICE AND TEST EQUIPMENT | 8 |
| 3. OPERATION OF EUT DURING TESTING | 9 |
| 3.1. Operating Mode..... | 9 |
| 3.2. Configuration and peripherals | 9 |
| 4. TEST PROCEDURES AND RESULTS | 10 |
| 5. POWER LINE CONDUCTED MEASUREMENT | 11 |
| 5.1. Block Diagram of Test Setup..... | 11 |
| 5.2. Power Line Conducted Emission Measurement Limits..... | 11 |
| 5.3. Configuration of EUT on Measurement | 11 |
| 5.4. Operating Condition of EUT | 11 |
| 5.5. Test Procedure | 12 |
| 5.6. Power Line Conducted Emission Measurement Results | 13 |
| 6. 6DB BANDWIDTH MEASUREMENT | 16 |
| 6.1. Block Diagram of Test Setup..... | 16 |
| 6.2. The Requirement For Section 15.247(a)(2)..... | 16 |
| 6.3. EUT Configuration on Measurement | 16 |
| 6.4. Operating Condition of EUT | 16 |
| 6.5. Test Procedure | 16 |
| 6.6. Test Result | 17 |
| 7. MAXIMUM CONDUCTED (AVERAGE) OUTPUT POWER | 24 |
| 7.1. Block Diagram of Test Setup..... | 24 |
| 7.2. The Requirement For Section 15.247(b)(3)..... | 24 |
| 7.3. EUT Configuration on Measurement | 24 |
| 7.4. Operating Condition of EUT | 24 |
| 7.5. Test Procedure | 24 |
| 7.6. Test Result | 25 |
| 8. POWER SPECTRAL DENSITY MEASUREMENT..... | 32 |
| 8.1. Block Diagram of Test Setup..... | 32 |
| 8.2. The Requirement For Section 15.247(e)..... | 32 |
| 8.3. EUT Configuration on Measurement | 32 |
| 8.4. Operating Condition of EUT | 32 |
| 8.5. Test Procedure | 32 |
| 8.6. Test Result | 33 |
| 9. BAND EDGE COMPLIANCE TEST | 40 |
| 9.1. Block Diagram of Test Setup..... | 40 |
| 9.2. The Requirement For Section 15.247(d) | 40 |

| | | |
|------------|--|------------|
| 9.3. | EUT Configuration on Measurement | 40 |
| 9.4. | Operating Condition of EUT | 40 |
| 9.5. | Test Procedure | 40 |
| 9.6. | Test Result | 41 |
| 10. | RADIATED SPURIOUS EMISSION TEST | 62 |
| 10.1. | Block Diagram of Test Setup..... | 62 |
| 10.2. | The Limit For Section 15.247(d) | 62 |
| 10.3. | Restricted bands of operation | 63 |
| 10.4. | Configuration of EUT on Measurement | 63 |
| 10.5. | Operating Condition of EUT | 64 |
| 10.6. | Test Procedure | 64 |
| 10.7. | The Field Strength of Radiation Emission Measurement Results | 65 |
| 11. | CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST | 96 |
| 11.1. | Block Diagram of Test Setup..... | 96 |
| 11.2. | The Requirement For Section 15.247(d) | 96 |
| 11.3. | EUT Configuration on Measurement | 96 |
| 11.4. | Operating Condition of EUT | 96 |
| 11.5. | Test Procedure | 97 |
| 11.6. | Test Result | 97 |
| 12. | ANTENNA REQUIREMENT..... | 104 |
| 12.1. | The Requirement | 104 |
| 12.2. | Antenna Construction | 104 |

Test Report Certification

Applicant : IMC INTERNATIONAL INC.
Manufacturer : IMC INTERNATIONAL INC.
EUT Description : 7 inch 3G TABLET
(A) MODEL NO.: ROAD XT-71BG
(B) Trade Name.: LOGIC
(C) POWER SUPPLY: DC 3.7V (Powered by battery) or AC 120V/60Hz
(Powered by adapter)

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.4: 2009


The EUT was tested according to DTS test procedure of Jun 05, 2014 KDB558074 D01 DTS Meas Guidance v03r02 for compliance to FCC 47CFR 15.247 requirements

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : Jun 04, 2014-Jun 25, 2014

Prepared by :



(Tim.zhang, Engineer)

Approved & Authorized Signer :



(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

| | | |
|-------------------------|---|---|
| EUT | : | 7 inch 3G TABLET |
| Model Number | : | ROAD XT-71BG |
| Frequency Range | : | 802.11b/g/n(20MHz): 2412-2462MHz 802.11n(40MHz): 2422-2452MHz |
| Number of Channels | : | 802.11b/g/n (20MHz):11 802.11n (40MHz): 7 |
| Antenna Gain | : | 1.5dBi |
| Type of Antenna | : | Integral Antenna |
| Power Supply | : | DC 3.7V (Powered by Battery) AC 120V/60Hz (Powered by Adapter) |
| Data Rate | : | 802.11b: 11, 5.5, 2, 1 Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11n: up to 150Mbps |
| Adapter | : | Model:DY-050150 Input: AC 100-240V 50/60Hz Output: 5.0V 1.5A |
| Modulation Type | : | CCK, OFDM |
| Applicant | : | IMC INTERNATIONAL INC. |
| Address | : | 28E Jingang, xixiang,Bao an District, Shenzhen, Guangdong Province, China |
| Manufacturer | : | IMC INTERNATIONAL INC. |
| Address | : | 28E Jingang, xixiang,Bao an District, Shenzhen, Guangdong Province, China |
| Date of sample received | : | Jun 04, 2014 |
| Date of Test | : | Jun 04, 2014-Jun 28, 2014 |

1.2.Carrier Frequency of Channels

802.11b, 802.11g, 802.11n (20MHz)

| Channel | Frequency(MHz) | Channel | Frequency(MHz) |
|---------|----------------|---------|----------------|
| 01 | 2412 | 07 | 2442 |
| 02 | 2417 | 08 | 2447 |
| 03 | 2422 | 09 | 2452 |
| 04 | 2427 | 10 | 2457 |
| 05 | 2432 | 11 | 2462 |
| 06 | 2437 | --- | --- |

802.11n (40MHz)

| Channel | Frequency(MHz) | Channel | Frequency(MHz) |
|---------|----------------|---------|----------------|
| --- | --- | 07 | 2442 |
| --- | --- | 08 | 2447 |
| 03 | 2422 | 09 | 2452 |
| 04 | 2427 | --- | --- |
| 05 | 2432 | --- | --- |
| 06 | 2437 | --- | --- |

1.3.Accessory and Auxiliary Equipment

N/A

1.4.Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC
The Registration Number is 752051

Listed by Industry Canada
The Registration Number is 5077A-2

Accredited by China National Accreditation Committee
for Laboratories
The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO. LTD

Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

1.5.Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty
(9kHz-30MHz) = 3.08dB, k=2

Radiated emission expanded uncertainty
(30MHz-1000MHz) = 4.42dB, k=2

Radiated emission expanded uncertainty
(Above 1GHz) = 4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

| Kind of equipment | Manufacturer | Type | S/N | Calibrated dates | Calibrated until |
|--------------------|---------------------------|---|------------|------------------|------------------|
| EMI Test Receiver | Rohde&Schwarz | ESCS30 | 100307 | Jan. 11, 2014 | Jan. 10, 2015 |
| EMI Test Receiver | Rohde&Schwarz | ESPI3 | 101526/003 | Jan. 11, 2014 | Jan. 10, 2015 |
| Spectrum Analyzer | Agilent | E7405A | MY45115511 | Jan. 11, 2014 | Jan. 10, 2015 |
| Pre-Amplifier | Rohde&Schwarz | CBLU118354 0-01 | 3791 | Jan. 11, 2014 | Jan. 10, 2015 |
| Loop Antenna | Schwarzbeck | FMZB1516 | 1516131 | Jan. 15, 2014 | Jan. 14, 2015 |
| Bilog Antenna | Schwarzbeck | VULB9163 | 9163-323 | Jan. 15, 2014 | Jan. 14, 2015 |
| Horn Antenna | Schwarzbeck | BBHA9120D | 9120D-655 | Jan. 15, 2014 | Jan. 14, 2015 |
| Horn Antenna | Schwarzbeck | BBHA9170 | 9170-359 | Jan. 15, 2014 | Jan. 14, 2015 |
| LISN | Rohde&Schwarz | ESH3-Z5 | 100305 | Jan. 11, 2014 | Jan. 10, 2015 |
| LISN | Schwarzbeck | NSLK8126 | 8126431 | Jan. 11, 2014 | Jan. 10, 2015 |
| Highpass Filter | Wainwright Instruments | WHKX3.6/18 G-10SS | N/A | Jan. 11, 2014 | Jan. 10, 2015 |
| Band Reject Filter | Wainwright Instruments | WRCG2400/2 485-2375/2510 -60/11SS | N/A | Jan. 11, 2014 | Jan. 10, 2015 |

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: **1.802.11b Transmitting mode**

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

2.802.11g Transmitting mode

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

3.802.11n (20MHz) Transmitting mode

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

4.802.11n (40MHz) Transmitting mode

Low Channel: 2422MHz

Middle Channel: 2437MHz

High Channel: 2452MHz

3.2.Configuration and peripherals





Figure 1 Setup: Transmitting mode

4. TEST PROCEDURES AND RESULTS

| FCC Rules | Description of Test | Result |
|-------------------------------------|----------------------------------|-----------|
| Section 15.207 | Power Line Conducted Emission | Compliant |
| Section 15.247(a)(2) | 6dB Bandwidth Test | Compliant |
| Section 15.247(e) | Power Spectral Density Test | Compliant |
| Section 15.247(b)(3) | Maximum Peak Output Power Test | Compliant |
| Section 15.247(d) | Band Edge Compliance Test | Compliant |
| Section 15.247(d) Section 15.209 | Radiated Spurious Emission Test | Compliant |
| Section 15.247(d) | Conducted Spurious Emission Test | Compliant |
| Section 15.203 | Antenna Requirement | Compliant |

5. POWER LINE CONDUCTED MEASUREMENT

5.1. Block Diagram of Test Setup



(EUT: 7 inch 3G TABLET)

5.2. Power Line Conducted Emission Measurement Limits

| Frequency (MHz) | Limit dB(μV) | |
|--|------------------|---------------|
| | Quasi-peak Level | Average Level |
| 0.15 - 0.50 | 66.0 – 56.0 * | 56.0 – 46.0 * |
| 0.50 - 5.00 | 56.0 | 46.0 |
| 5.00 - 30.00 | 60.0 | 50.0 |
| NOTE1: The lower limit shall apply at the transition frequencies. | | |
| NOTE2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz. | | |

5.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in test mode and measure it.

5.5. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2009 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

5.6. Power Line Conducted Emission Measurement Results

PASS.

The frequency range from 150kHz to 30MHz is checked.

| Test mode : Charging&WIFI communicating | | | | | | | | |
|---|---------------|--------------|---------------|--------------|----------|------|-----|--|
| MEASUREMENT RESULT: "IMC-B03_fin" | | | | | | | | |
| 6/7/2014 9:16AM | | | | | | | | |
| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE | |
| 0.517062 | 36.10 | 10.7 | 56 | 19.9 | QP | L1 | GND | |
| 0.933537 | 38.30 | 10.8 | 56 | 17.7 | QP | L1 | GND | |
| 26.803049 | 32.60 | 11.5 | 60 | 27.4 | QP | L1 | GND | |
| MEASUREMENT RESULT: "IMC-B03_fin2" | | | | | | | | |
| 6/7/2014 9:16AM | | | | | | | | |
| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE | |
| 0.535976 | 27.70 | 10.7 | 46 | 18.3 | AV | L1 | GND | |
| 0.933537 | 27.60 | 10.8 | 46 | 18.4 | AV | L1 | GND | |
| 26.064429 | 24.40 | 11.5 | 50 | 25.6 | AV | L1 | GND | |
| MEASUREMENT RESULT: "IMC-B04_fin" | | | | | | | | |
| 6/7/2014 9:18AM | | | | | | | | |
| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE | |
| 0.517062 | 36.40 | 10.7 | 56 | 19.6 | QP | N | GND | |
| 0.933537 | 38.30 | 10.8 | 56 | 17.7 | QP | N | GND | |
| 13.543138 | 34.90 | 11.3 | 60 | 25.1 | QP | N | GND | |
| MEASUREMENT RESULT: "IMC-B04_fin2" | | | | | | | | |
| 6/7/2014 9:18AM | | | | | | | | |
| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE | |
| 0.191358 | 37.00 | 10.5 | 54 | 17.0 | AV | N | GND | |
| 0.956168 | 26.60 | 10.8 | 46 | 19.4 | AV | N | GND | |
| 26.483968 | 24.60 | 11.5 | 50 | 25.4 | AV | N | GND | |

Emissions attenuated more than 20 dB below the permissible value are not reported.

The spectral diagrams are attached as below.


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: 7" 3G TABLET M/N:ROAD XT-71BG
 Manufacturer: IMC
 Operating Condition: BT/Charging
 Test Site: 1#Shielding Room
 Operator: Alen
 Test Specification: N 120V/60Hz
 Comment: Report No:ATE20140926
 Start of Test: 6/7/2014 / 9:16:43AM

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "IMC-B04_fin"

6/7/2014 9:18AM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.517062 | 36.40 | 10.7 | 56 | 19.6 | QP | N | GND |
| 0.933537 | 38.30 | 10.8 | 56 | 17.7 | QP | N | GND |
| 13.543138 | 34.90 | 11.3 | 60 | 25.1 | QP | N | GND |

MEASUREMENT RESULT: "IMC-B04_fin2"

6/7/2014 9:18AM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.191358 | 37.00 | 10.5 | 54 | 17.0 | AV | N | GND |
| 0.956168 | 26.60 | 10.8 | 46 | 19.4 | AV | N | GND |
| 26.483968 | 24.60 | 11.5 | 50 | 25.4 | AV | N | GND |


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: 7" 3G TABLET M/N:ROAD XT-71BG
 Manufacturer: IMC
 Operating Condition: BT/Charging
 Test Site: 1#Shielding Room
 Operator: Alen
 Test Specification: L 120V/60Hz
 Comment: Report No:ATE20140926
 Start of Test: 6/7/2014 / 9:14:16AM

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "IMC-B03_fin"

6/7/2014 9:16AM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.517062 | 36.10 | 10.7 | 56 | 19.9 | QP | L1 | GND |
| 0.933537 | 38.30 | 10.8 | 56 | 17.7 | QP | L1 | GND |
| 26.803049 | 32.60 | 11.5 | 60 | 27.4 | QP | L1 | GND |


MEASUREMENT RESULT: "IMC-B03_fin2"

6/7/2014 9:16AM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.535976 | 27.70 | 10.7 | 46 | 18.3 | AV | L1 | GND |
| 0.933537 | 27.60 | 10.8 | 46 | 18.4 | AV | L1 | GND |
| 26.064429 | 24.40 | 11.5 | 50 | 25.6 | AV | L1 | GND |

6. 6DB BANDWIDTH MEASUREMENT

6.1. Block Diagram of Test Setup



6.2. The Requirement For Section 15.247(a)(2)

Section 15.247(a)(2): Systems using digital modulation techniques may operate in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

6.5. Test Procedure

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.6.Test Result

| The test was performed with 802.11b | | | |
|-------------------------------------|-----------------|---------------------|-------------|
| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Limit (MHz) |
| Low | 2412 | 10.32 | > 0.5MHz |
| Middle | 2437 | 10.32 | > 0.5MHz |
| High | 2462 | 10.32 | > 0.5MHz |


| The test was performed with 802.11g | | | |
|-------------------------------------|-----------------|---------------------|-------------|
| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Limit (MHz) |
| Low | 2412 | 16.60 | > 0.5MHz |
| Middle | 2437 | 16.60 | > 0.5MHz |
| High | 2462 | 16.60 | > 0.5MHz |

| The test was performed with 802.11n (Bandwidth: 20 MHz) | | | |
|---|-----------------|---------------------|-------------|
| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Limit (MHz) |
| Low | 2412 | 17.76 | > 0.5MHz |
| Middle | 2437 | 17.76 | > 0.5MHz |
| High | 2462 | 17.76 | > 0.5MHz |

| The test was performed with 802.11n (Bandwidth: 40 MHz) | | | |
|---|-----------------|---------------------|-------------|
| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Limit (MHz) |
| Low | 2422 | 36.56 | > 0.5MHz |
| Middle | 2437 | 36.56 | > 0.5MHz |
| High | 2452 | 36.56 | > 0.5MHz |


The spectrum analyzer plots are attached as below.

802.11b Channel Low 2412MHz




Date: 27.JUN.2014 18:33:03

802.11b Channel Middle 2437MHz




Date: 27.JUN.2014 18:34:17

802.11b Channel High 2462MHz




Date: 27.JUN.2014 18:30:28

802.11g Channel Low 2412MHz




Date: 27.JUN.2014 18:13:28

802.11g Channel Middle 2437MHz




Date: 27.JUN.2014 18:12:29

802.11g Channel High 2462MHz




Date: 27.JUN.2014 18:11:14

802.11n Channel Low 2412MHz (20MHz)




Date: 27.JUN.2014 18:15:05

802.11n Channel Middle 2437MHz(20MHz)




Date: 27.JUN.2014 18:16:57

802.11n Channel High 2462MHz(20MHz)




Date: 27.JUN.2014 18:18:43

802.11n Channel Low 2422MHz (40MHz)




Date: 27.JUN.2014 18:20:21

802.11n Channel Middle 2437MHz(40MHz)



Date: 27.JUN.2014 18:21:28


802.11n Channel High 2452MHz(40MHz)



Date: 27.JUN.2014 18:22:36

7. MAXIMUM CONDUCTED (AVERAGE) OUTPUT POWER

7.1. Block Diagram of Test Setup



7.2. The Requirement For Section 15.247(b)(3)

Section 15.247(b)(3): For systems using digital modulation in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands: 1 Watt.

7.3. EUT Configuration on Measurement

The equipment is installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

7.5. Test Procedure

7.5.1. The EUT was tested according to DTS test procedure of Jun 05, 2014 KDB558074 D01 DTS Meas Guidance v03r02 for compliance to FCC 47CFR 15.247 requirements.

7.5.2. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.3. Set RBW = 1-5% of the OBW, not to exceed 1 MHz, VBW \geq 3 x RBW, Sweep time = auto, Set span to at least 1.5 times the OBW, Detector = RMS.

7.5.4. Measurement the Maximum conducted (average) output power.

7.6. Test Result

| The test was performed with 802.11b | | | | |
|-------------------------------------|-----------------|------------------------|-----------------------|----------------|
| Channel | Frequency (MHz) | Ave output power (dBm) | Ave output power (mW) | Limits dBm / W |
| Low | 2412 | 9.50 | 8.91 | 30 dBm / 1 W |
| Middle | 2437 | 9.27 | 8.45 | 30 dBm / 1 W |
| High | 2462 | 9.01 | 7.96 | 30 dBm / 1 W |


| The test was performed with 802.11g | | | | |
|-------------------------------------|-----------------|------------------------|-----------------------|----------------|
| Channel | Frequency (MHz) | Ave output power (dBm) | Ave output power (mW) | Limits dBm / W |
| Low | 2412 | 7.82 | 6.05 | 30 dBm / 1 W |
| Middle | 2437 | 7.61 | 5.77 | 30 dBm / 1 W |
| High | 2462 | 6.76 | 4.74 | 30 dBm / 1 W |

| The test was performed with 802.11n (20MHz) | | | | |
|---|-----------------|------------------------|-----------------------|----------------|
| Channel | Frequency (MHz) | Ave output power (dBm) | Ave output power (mW) | Limits dBm / W |
| Low | 2412 | 7.12 | 5.15 | 30 dBm / 1 W |
| Middle | 2437 | 6.89 | 4.89 | 30 dBm / 1 W |
| High | 2462 | 6.65 | 4.62 | 30 dBm / 1 W |

| The test was performed with 802.11n (40MHz) | | | | |
|---|-----------------|------------------------|-----------------------|----------------|
| Channel | Frequency (MHz) | Ave output power (dBm) | Ave output power (mW) | Limits dBm / W |
| Low | 2422 | 4.07 | 2.55 | 30 dBm / 1 W |
| Middle | 2437 | 4.95 | 3.13 | 30 dBm / 1 W |
| High | 2452 | 5.03 | 3.18 | 30 dBm / 1 W |


The spectrum analyzer plots are attached as below.

802.11b Channel Low 2412MHz




Date: 27.JUN.2014 18:36:27

802.11b Channel Middle 2437MHz




Date: 27.JUN.2014 18:35:51

802.11b Channel High 2462MHz




Date: 27.JUN.2014 18:37:15

802.11g Channel Low 2412MHz




Date: 27.JUN.2014 18:40:34

802.11g Channel Middle 2437MHz




Date: 27.JUN.2014 18:39:59

802.11g Channel High 2462MHz




Date: 27.JUN.2014 18:38:39

802.11n Channel Low 2412MHz (20MHz)




Date: 27.JUN.2014 18:41:27

802.11n Channel Middle 2437MHz (20MHz)




Date: 27.JUN.2014 18:41:55

802.11n Channel High 2462MHz (20MHz)




Date: 27.JUN.2014 18:42:38

802.11n Channel Low 2422MHz (40MHz)




Date: 27.JUN.2014 18:44:10

802.11n Channel Middle 2437MHz (40MHz)



Date: 27.JUN.2014 18:45:25


802.11n Channel High 2452MHz (40MHz)



Date: 27.JUN.2014 18:46:20

8. POWER SPECTRAL DENSITY MEASUREMENT

8.1. Block Diagram of Test Setup



8.2. The Requirement For Section 15.247(e)

Section 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Measurement Procedure PKPSD:

This procedure must be used if maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit, and is optional if the maximum (average) conducted output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.

3. Set the RBW $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

8.5.3.Measurement the maximum power spectral density.

8.6.Test Result

| The test was performed with 802.11b | | | |
|-------------------------------------|-----------------|------------------------------|--------------|
| Channel | Frequency (MHz) | Power Spectral Density (dBm) | Limits (dBm) |
| Low | 2412 | -18.77 | 8 dBm |
| Middle | 2437 | -19.25 | 8 dBm |
| High | 2462 | -18.04 | 8 dBm |


| The test was performed with 802.11g | | | |
|-------------------------------------|-----------------|------------------------------|--------------|
| Channel | Frequency (MHz) | Power Spectral Density (dBm) | Limits (dBm) |
| Low | 2412 | -22.83 | 8 dBm |
| Middle | 2437 | -23.37 | 8 dBm |
| High | 2462 | -23.86 | 8 dBm |

| The test was performed with 802.11n (20MHz) | | | |
|---|-----------------|------------------------------|--------------|
| Channel | Frequency (MHz) | Power Spectral Density (dBm) | Limits (dBm) |
| Low | 2412 | -24.60 | 8 dBm |
| Middle | 2437 | -25.36 | 8 dBm |
| High | 2462 | -25.25 | 8 dBm |

| The test was performed with 802.11n (40MHz) | | | |
|---|-----------------|------------------------------|--------------|
| Channel | Frequency (MHz) | Power Spectral Density (dBm) | Limits (dBm) |
| Low | 2422 | -28.28 | 8 dBm |
| Middle | 2437 | -29.62 | 8 dBm |
| High | 2452 | -28.90 | 8 dBm |


The spectrum analyzer plots are attached as below.

802.11b Channel Low 2412MHz




Date: 27.JUN.2014 18:53:39

802.11b Channel Middle 2437MHz




Date: 27.JUN.2014 18:54:17

802.11b Channel High 2462MHz




Date: 27.JUN.2014 18:54:47

802.11g Channel Low 2412MHz




Date: 27.JUN.2014 18:52:57

802.11g Channel Middle 2437MHz




Date: 27.JUN.2014 18:52:26

802.11g Channel High 2462MHz




Date: 27.JUN.2014 18:51:48

802.11n Channel Low 2412MHz (20MHz)




Date: 27.JUN.2014 18:49:38

802.11n Channel Middle 2437MHz (20MHz)




Date: 27.JUN.2014 18:50:19

802.11n Channel High 2462MHz(20MHz)




Date: 27.JUN.2014 18:51:12

802.11n Channel Low 2422MHz (40MHz)




Date: 27.JUN.2014 18:48:48

802.11n Channel Middle 2437MHz(40MHz)



Date: 27.JUN.2014 18:48:11


802.11n Channel High 2452MHz(40MHz)



Date: 27.JUN.2014 18:47:23

9. BAND EDGE COMPLIANCE TEST

9.1. Block Diagram of Test Setup



9.2. The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

9.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz MHz. We select 2412MHz, 2462MHz and 2422MHz, 2452MHz TX frequency to transmit.

9.5. Test Procedure

Conducted Band Edge:

9.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

9.5.2. Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz.

Radiate Band Edge:

9.5.3. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.

9.5.4. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

9.5.5. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

9.5.6. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

9.5.7. RBW=1MHz, VBW=1MHz

9.5.8. The band edges were measured and recorded.

9.6. Test Result


| The test was performed with 802.11b | | |
|-------------------------------------|---------------------------|--------------------------|
| Frequency (MHz) | Result of Band Edge (dBc) | Limit of Band Edge (dBc) |
| 2412 | 44.61 | > 20dBc |
| 2462 | 52.87 | > 20dBc |

| The test was performed with 802.11g | | |
|-------------------------------------|---------------------------|--------------------------|
| Frequency (MHz) | Result of Band Edge (dBc) | Limit of Band Edge (dBc) |
| 2412 | 34.95 | > 20dBc |
| 2462 | 40.66 | > 20dBc |


| The test was performed with 802.11n (20MHz) | | |
|---|---------------------------|--------------------------|
| Frequency (MHz) | Result of Band Edge (dBc) | Limit of Band Edge (dBc) |
| 2412 | 36.25 | > 20dBc |
| 2462 | 41.87 | > 20dBc |

| The test was performed with 802.11n (40MHz) | | |
|---|---------------------------|--------------------------|
| Frequency (MHz) | Result of Band Edge (dBc) | Limit of Band Edge (dBc) |
| 2422 | 31.15 | > 20dBc |
| 2452 | 37.70 | > 20dBc |


802.11b Channel Low 2412MHz




802.11b Channel High 2462MHz




802.11g Channel Low 2412MHz




802.11g Channel High 2462MHz




802.11n Channel Low 2412MHz (20MHz)




802.11n Channel High 2462MHz (20MHz)



802.11n Channel Low 2422MHz (40MHz)



802.11n Channel High 2452MHz (40MHz)



Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

3. Display the measurement of peak values.



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2924

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 7" 3G Tablet

Mode: TX 2412MHz(802.11b)

Model: BOAD XT-71BG

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 14/06/16/

Time: 13/59/39

Engineer Signature:

Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2398.920 | 59.81 | -6.76 | 53.05 | 74.00 | -20.95 | peak | | | |
| 2 | 2398.920 | 53.78 | -6.76 | 47.02 | 54.00 | -6.98 | AVG | | | |
| 3 | 2399.960 | 62.04 | -6.76 | 55.28 | 74.00 | -18.72 | peak | | | |
| 4 | 2399.960 | 56.01 | -6.76 | 49.25 | 54.00 | -4.75 | AVG | | | |

Job No.: alen #2923
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2412MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/58/59
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2398.920 | 59.78 | -6.76 | 53.02 | 74.00 | -20.98 | peak | | | |
| 2 | 2398.920 | 53.69 | -6.76 | 46.93 | 54.00 | -7.07 | AVG | | | |
| 3 | 2399.960 | 61.09 | -6.76 | 54.33 | 74.00 | -19.67 | peak | | | |
| 4 | 2399.960 | 54.87 | -6.76 | 48.11 | 54.00 | -5.89 | AVG | | | |

Job No.: alen #2925
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/01/18
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2483.500 | 51.20 | -6.54 | 44.66 | 74.00 | -29.34 | peak | | | |
| 2 | 2483.500 | 45.12 | -6.54 | 38.58 | 54.00 | -15.42 | AVG | | | |
| 3 | 2486.860 | 51.78 | -6.53 | 45.25 | 74.00 | -28.75 | peak | | | |
| 4 | 2486.860 | 45.57 | -6.53 | 39.04 | 54.00 | -14.96 | AVG | | | |

Job No.: alen #2926
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/01/55
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2483.560 | 52.17 | -6.54 | 45.63 | 74.00 | -28.37 | peak | | | |
| 2 | 2483.560 | 46.01 | -6.54 | 39.47 | 54.00 | -14.53 | AVG | | | |
| 3 | 2485.780 | 52.55 | -6.54 | 46.01 | 74.00 | -27.99 | peak | | | |
| 4 | 2485.780 | 46.47 | -6.54 | 39.93 | 54.00 | -14.07 | AVG | | | |

Job No.: alen #2929
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2412MHz(802.11g)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/05/36
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2398.920 | 61.25 | -6.76 | 54.49 | 74.00 | -19.51 | peak | | | |
| 2 | 2398.920 | 55.32 | -6.76 | 48.56 | 54.00 | -5.44 | AVG | | | |
| 3 | 2399.960 | 64.24 | -6.76 | 57.48 | 74.00 | -16.52 | peak | | | |
| 4 | 2399.960 | 58.01 | -6.76 | 51.25 | 54.00 | -2.75 | AVG | | | |

Job No.: alen #2930
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2412MHz(802.11g)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/06/16
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2398.790 | 61.05 | -6.76 | 54.29 | 74.00 | -19.71 | peak | | | |
| 2 | 2398.790 | 55.07 | -6.76 | 48.31 | 54.00 | -5.69 | AVG | | | |
| 3 | 2399.960 | 64.88 | -6.76 | 58.12 | 74.00 | -15.88 | peak | | | |
| 4 | 2399.960 | 58.36 | -6.76 | 51.60 | 54.00 | -2.40 | AVG | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2928
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11g)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/04/03
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2483.800 | 53.77 | -6.54 | 47.23 | 74.00 | -26.77 | peak | | | |
| 2 | 2483.800 | 47.68 | -6.54 | 41.14 | 54.00 | -12.86 | AVG | | | |
| 3 | 2485.000 | 52.81 | -6.54 | 46.27 | 74.00 | -27.73 | peak | | | |
| 4 | 2485.000 | 46.74 | -6.54 | 40.20 | 54.00 | -13.80 | AVG | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2927
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11g)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/03/26
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2483.740 | 50.38 | -6.54 | 43.84 | 74.00 | -30.16 | peak | | | |
| 2 | 2483.740 | 43.74 | -6.54 | 37.20 | 54.00 | -16.80 | AVG | | | |
| 3 | 2484.700 | 50.77 | -6.54 | 44.23 | 74.00 | -29.77 | peak | | | |
| 4 | 2484.700 | 44.28 | -6.54 | 37.74 | 54.00 | -16.26 | AVG | | | |

Job No.: alen #2932
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2412MHz(802.11n20)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/08/26
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2398.400 | 57.64 | -6.75 | 50.89 | 74.00 | -23.11 | peak | | | |
| 2 | 2398.400 | 51.57 | -6.75 | 44.82 | 54.00 | -9.18 | AVG | | | |
| 3 | 2399.700 | 61.77 | -6.76 | 55.01 | 74.00 | -18.99 | peak | | | |
| 4 | 2399.700 | 55.81 | -6.76 | 49.05 | 54.00 | -4.95 | AVG | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2931

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 7" 3G Tablet

Mode: TX 2412MHz(802.11n20)

Model: BOAD XT-71BG

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/16/

Time: 14/07/47

Engineer Signature:

Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2399.050 | 59.73 | -6.76 | 52.97 | 74.00 | -21.03 | peak | | | |
| 2 | 2399.050 | 56.38 | -6.76 | 49.62 | 54.00 | -4.38 | AVG | | | |
| 3 | 2399.700 | 64.11 | -6.76 | 57.35 | 74.00 | -16.65 | peak | | | |
| 4 | 2399.700 | 58.04 | -6.76 | 51.28 | 54.00 | -2.72 | AVG | | | |

Job No.: alen #2933
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11n20)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/10/04
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2483.440 | 55.08 | -6.54 | 48.54 | 74.00 | -25.46 | peak | | | |
| 2 | 2483.440 | 49.02 | -6.54 | 42.48 | 54.00 | -11.52 | AVG | | | |
| 3 | 2485.060 | 54.15 | -6.54 | 47.61 | 74.00 | -26.39 | peak | | | |
| 4 | 2485.060 | 48.13 | -6.54 | 41.59 | 54.00 | -12.41 | AVG | | | |



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: alen #2934
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11n20)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/10/44
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2483.500 | 54.54 | -6.54 | 48.00 | 74.00 | -26.00 | peak | | | |
| 2 | 2483.500 | 48.57 | -6.54 | 42.03 | 54.00 | -11.97 | AVG | | | |
| 3 | 2484.640 | 53.48 | -6.54 | 46.94 | 74.00 | -27.06 | peak | | | |
| 4 | 2484.640 | 46.42 | -6.54 | 39.88 | 54.00 | -14.12 | AVG | | | |

Job No.: alen #2937
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2422MHz(802.11n40)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/14/30
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2398.140 | 59.13 | -6.75 | 52.38 | 74.00 | -21.62 | peak | | | |
| 2 | 2398.140 | 56.01 | -6.75 | 49.26 | 54.00 | -4.74 | AVG | | | |
| 3 | 2400.220 | 59.35 | -6.76 | 52.59 | 74.00 | -21.41 | peak | | | |
| 4 | 2400.220 | 56.14 | -6.76 | 49.38 | 54.00 | -4.62 | AVG | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2938

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 7" 3G Tablet

Mode: TX 2422MHz(802.11n40)

Model: BOAD XT-71BG

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/16/

Time: 14/15/10

Engineer Signature:

Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2398.790 | 59.16 | -6.76 | 52.40 | 74.00 | -21.60 | peak | | | |
| 2 | 2398.790 | 52.17 | -6.76 | 45.41 | 54.00 | -8.59 | AVG | | | |
| 3 | 2400.610 | 61.10 | -6.76 | 54.34 | 74.00 | -19.66 | peak | | | |
| 4 | 2400.610 | 55.04 | -6.76 | 48.28 | 54.00 | -5.72 | AVG | | | |

Job No.: alen #2936
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2452MHz(802.11n40)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/12/46
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2483.500 | 52.96 | -6.54 | 46.42 | 74.00 | -27.58 | peak | | | |
| 2 | 2483.500 | 46.65 | -6.54 | 40.11 | 54.00 | -13.89 | AVG | | | |
| 3 | 2485.600 | 53.47 | -6.54 | 46.93 | 74.00 | -27.07 | peak | | | |
| 4 | 2485.600 | 47.58 | -6.54 | 41.04 | 54.00 | -12.96 | AVG | | | |

Job No.: alen #2935
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2452MHz(802.11n40)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 14/12/18
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2483.440 | 52.68 | -6.54 | 46.14 | 74.00 | -27.86 | peak | | | |
| 2 | 2483.440 | 46.57 | -6.54 | 40.03 | 54.00 | -13.97 | AVG | | | |
| 3 | 2484.220 | 53.34 | -6.54 | 46.80 | 74.00 | -27.20 | peak | | | |
| 4 | 2484.220 | 47.35 | -6.54 | 40.81 | 54.00 | -13.19 | AVG | | | |


10. RADIATED SPURIOUS EMISSION TEST

10.1. Block Diagram of Test Setup

10.1.1. Block diagram of connection between the EUT and peripherals



10.1.2. Semi-Anechoic Chamber Test Setup Diagram



10.2. The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the

transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.Restricted bands of operation

10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|--------------------------|---------------------|---------------|------------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| ¹ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (²) |
| 13.36-13.41 | | | |

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

10.4.Configuration of EUT on Measurement

The equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.5. Operating Condition of EUT

10.5.1. Setup the EUT and simulator as shown as Section 10.1.

10.5.2. Turn on the power of all equipment.

10.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

10.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2009 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The worst-case data rate for this channel to be 1Mbps for 802.11b mode and 6Mbps for 802.11g mode and 150Mbps for 802.11n mode, based on previous with 802.11 WLAN product design architectures.

The final measurement in band 9-90 kHz, 110-490 kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector. When average radiated emissions measurements are specified there is also a limit on the peak emissions level which is 20 dB above the applicable maximum permitted average emission limit

A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth for average detection(AV) at below at frequency above 1GHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

| Frequency Band (MHz) | Function | Resolution Bandwidth | Video Bandwidth |
|----------------------|----------|----------------------|-----------------|
| 30 to 1000 | Peak | 100 kHz | 100 kHz |
| Above 1000 | Peak | 1 MHz | 1 MHz |
| | Average | 1 MHz | 10 Hz |

10.7.The Field Strength of Radiation Emission Measurement Results

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. *: Denotes restricted band of operation.

3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.

4. The EUT is tested radiation emission at each test mode(802.11 b/g/n) in three axes. The worst emissions are reported in all test mode and channels.

5. The radiation emissions from 18-25GHz are not reported, because the test values lower than the limits of 20dB.

Below 1G



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: alen #4404
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2412MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/14/
Time: 13/50/01
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 116.9495 | 55.54 | -22.42 | 33.12 | 43.50 | -10.38 | QP | | | |
| 2 | 146.3735 | 56.54 | -23.73 | 32.81 | 43.50 | -10.69 | QP | | | |
| 3 | 379.9141 | 50.32 | -15.78 | 34.54 | 46.00 | -11.46 | QP | | | |

Job No.: alen #4405
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2412MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/14/
Time: 13/50/57
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 86.5029 | 53.65 | -21.59 | 32.06 | 40.00 | -7.94 | QP | | | |
| 2 | 116.5401 | 56.57 | -22.40 | 34.17 | 43.50 | -9.33 | QP | | | |
| 3 | 145.8611 | 62.21 | -23.72 | 38.49 | 43.50 | -5.01 | QP | | | |

Job No.: alen #4407
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2437MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/14/
Time: 13/52/48
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 116.1320 | 55.23 | -22.39 | 32.84 | 43.50 | -10.66 | QP | | | |
| 2 | 145.8610 | 57.50 | -23.72 | 33.78 | 43.50 | -9.72 | QP | | | |
| 3 | 379.9141 | 51.38 | -15.78 | 35.60 | 46.00 | -10.40 | QP | | | |

Job No.: alen #4406
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2437MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/14/
Time: 13/51/38
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 85.5977 | 55.21 | -21.56 | 33.65 | 40.00 | -6.35 | QP | | | |
| 2 | 109.0285 | 57.01 | -22.31 | 34.70 | 43.50 | -8.80 | QP | | | |
| 3 | 145.3505 | 62.89 | -23.70 | 39.19 | 43.50 | -4.31 | QP | | | |

Job No.: alen #4408
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/14/
Time: 13/53/48
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926





ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: alen #4409
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/14/
Time: 13/54/44
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



Above 1G



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: alen #2900
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Table
Mode: TX 2412MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 9/59/42
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 11533.485 | 43.72 | 6.07 | 49.79 | 54.00 | -4.21 | peak | | | |
| 2 | 14408.425 | 37.93 | 12.53 | 50.46 | 54.00 | -3.54 | peak | | | |
| 3 | 16696.884 | 36.97 | 12.81 | 49.78 | 54.00 | -4.22 | peak | | | |



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: alen #2899
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2412MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 9/59/01
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 11600.350 | 43.21 | 6.14 | 49.35 | 54.00 | -4.65 | peak | | | |
| 2 | 13404.009 | 41.03 | 8.82 | 49.85 | 54.00 | -4.15 | peak | | | |
| 3 | 15850.410 | 38.42 | 11.48 | 49.90 | 54.00 | -4.10 | peak | | | |

Job No.: alen #2903
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2437MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 10/03/29
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 9152.479 | 45.47 | 3.88 | 49.35 | 54.00 | -4.65 | peak | | | |
| 2 | 11533.485 | 42.94 | 6.07 | 49.01 | 54.00 | -4.99 | peak | | | |
| 3 | 13365.322 | 41.06 | 8.74 | 49.80 | 54.00 | -4.20 | peak | | | |



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: alen #2901
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2437MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 10/01/25
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 11533.485 | 43.52 | 6.07 | 49.59 | 54.00 | -4.41 | peak | | | |
| 2 | 13877.076 | 40.14 | 10.08 | 50.22 | 54.00 | -3.78 | peak | | | |
| 3 | 16174.372 | 37.91 | 11.79 | 49.70 | 54.00 | -4.30 | peak | | | |

Job No.: alen #2904
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 10/04/12
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 9753.371 | 44.19 | 5.06 | 49.25 | 54.00 | -4.75 | peak | | | |
| 2 | 12469.611 | 42.54 | 7.12 | 49.66 | 54.00 | -4.34 | peak | | | |
| 3 | 15850.410 | 38.11 | 11.48 | 49.59 | 54.00 | -4.41 | peak | | | |

Job No.: alen #2903
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11b)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 10/03/29
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 9152.479 | 45.47 | 3.88 | 49.35 | 54.00 | -4.65 | peak | | | |
| 2 | 11533.485 | 42.94 | 6.07 | 49.01 | 54.00 | -4.99 | peak | | | |
| 3 | 13365.322 | 41.06 | 8.74 | 49.80 | 54.00 | -4.20 | peak | | | |

Job No.: alen #2905
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11g)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 10/05/59
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 11140.310 | 43.84 | 5.65 | 49.49 | 54.00 | -4.51 | peak | | | |
| 2 | 13288.284 | 41.56 | 8.56 | 50.12 | 54.00 | -3.88 | peak | | | |
| 3 | 14119.835 | 38.90 | 11.02 | 49.92 | 54.00 | -4.08 | peak | | | |

Job No.: alen #2906
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11g)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 10/06/33
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 11140.310 | 43.60 | 5.65 | 49.25 | 54.00 | -4.75 | peak | | | |
| 2 | 14450.131 | 37.54 | 12.74 | 50.28 | 54.00 | -3.72 | peak | | | |
| 3 | 15988.449 | 38.43 | 11.57 | 50.00 | 54.00 | -4.00 | peak | | | |

Job No.: alen #2908
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2437MHz(802.11g)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/44/37
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 10606.147 | 43.64 | 5.26 | 48.90 | 54.00 | -5.10 | peak | | | |
| 2 | 13059.822 | 41.06 | 8.02 | 49.08 | 54.00 | -4.92 | peak | | | |
| 3 | 14450.131 | 36.83 | 12.73 | 49.56 | 54.00 | -4.44 | peak | | | |

Job No.: alen #2907
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2437MHz(802.11g)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/43/49
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|----------------|---------------------|----------------|--------------------|-------------------|----------------|----------|----------------|------------------|--------|
| 1 | 10333.803 | 43.88 | 5.26 | 49.14 | 54.00 | -4.86 | peak | | | |
| 2 | 11940.536 | 43.01 | 6.43 | 49.44 | 54.00 | -4.56 | peak | | | |
| 3 | 14960.120 | 37.77 | 11.98 | 49.75 | 54.00 | -4.25 | peak | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2909
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2412MHz(802.11g)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/45/26
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 12255.224 | 42.46 | 6.84 | 49.30 | 54.00 | -4.70 | peak | | | |
| 2 | 13559.879 | 40.43 | 9.22 | 49.65 | 54.00 | -4.35 | peak | | | |
| 3 | 17136.924 | 35.33 | 14.42 | 49.75 | 54.00 | -4.25 | peak | | | |

Job No.: alen #2910
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2412MHz(802.11g)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/46/09
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 11140.310 | 43.23 | 5.65 | 48.88 | 54.00 | -5.12 | peak | | | |
| 2 | 12397.735 | 42.07 | 7.02 | 49.09 | 54.00 | -4.91 | peak | | | |
| 3 | 15090.405 | 37.33 | 11.76 | 49.09 | 54.00 | -4.91 | peak | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2912
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2412MHz(802.11n20)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/46/45
Engineer Signature:
Distance: 3m


Note: Report No:ATE20140926



Job No.: alen #2911
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2412MHz(802.11n20)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/46/45
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 12219.853 | 42.69 | 6.79 | 49.48 | 54.00 | -4.52 | peak | | | |
| 2 | 14160.705 | 38.11 | 11.24 | 49.35 | 54.00 | -4.65 | peak | | | |
| 3 | 17336.202 | 33.37 | 15.33 | 48.70 | 54.00 | -5.30 | peak | | | |

Job No.: alen #2913
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2437MHz(802.11n20)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/48/06
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 11837.445 | 42.83 | 6.34 | 49.17 | 54.00 | -4.83 | peak | | | |
| 2 | 13404.009 | 40.71 | 8.82 | 49.53 | 54.00 | -4.47 | peak | | | |
| 3 | 16174.372 | 37.35 | 11.79 | 49.14 | 54.00 | -4.86 | peak | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2914
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2437MHz(802.11n20)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/49/07
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926





ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2916
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11n20)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/50/22
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 10606.147 | 43.78 | 5.26 | 49.04 | 54.00 | -4.96 | peak | | | |
| 2 | 13365.322 | 40.37 | 8.74 | 49.11 | 54.00 | -4.89 | peak | | | |
| 3 | 15354.388 | 37.45 | 11.43 | 48.88 | 54.00 | -5.12 | peak | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2915
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2462MHz(802.11n20)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/49/41
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 11044.129 | 43.94 | 5.55 | 49.49 | 54.00 | -4.51 | peak | | | |
| 2 | 13481.719 | 40.48 | 9.01 | 49.49 | 54.00 | -4.51 | peak | | | |
| 3 | 14788.154 | 37.03 | 12.36 | 49.39 | 54.00 | -4.61 | peak | | | |

Job No.: alen #2921
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2422MHz(802.11n40)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/54/04
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 12114.352 | 42.42 | 6.65 | 49.07 | 54.00 | -4.93 | peak | | | |
| 2 | 14408.425 | 36.79 | 12.53 | 49.32 | 54.00 | -4.68 | peak | | | |
| 3 | 16409.819 | 37.34 | 12.06 | 49.40 | 54.00 | -4.60 | peak | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2922
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2422MHz(802.11n40)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/54/46
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 10097.596 | 43.17 | 5.35 | 48.52 | 54.00 | -5.48 | peak | | | |
| 2 | 11433.909 | 43.12 | 5.97 | 49.09 | 54.00 | -4.91 | peak | | | |
| 3 | 13135.536 | 40.85 | 8.19 | 49.04 | 54.00 | -4.96 | peak | | | |



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: alen #2920
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2437MHz(802.11n40)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/53/16
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 11633.928 | 43.44 | 6.16 | 49.60 | 54.00 | -4.40 | peak | | | |
| 2 | 12505.705 | 42.24 | 7.16 | 49.40 | 54.00 | -4.60 | peak | | | |
| 3 | 15090.405 | 37.47 | 11.76 | 49.23 | 54.00 | -4.77 | peak | | | |

Job No.: alen #2919
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2437MHz(802.11n40)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/52/39
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926




| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 9725.221 | 43.53 | 5.03 | 48.56 | 54.00 | -5.44 | peak | | | |
| 2 | 12433.621 | 41.42 | 7.06 | 48.48 | 54.00 | -5.52 | peak | | | |
| 3 | 14450.131 | 36.39 | 12.74 | 49.13 | 54.00 | -4.87 | peak | | | |

Job No.: alen #2917
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2452MHz(802.11n40)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/51/15
Engineer Signature:
Distance: 3m

Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 11108.157 | 42.96 | 5.62 | 48.58 | 54.00 | -5.42 | peak | | | |
| 2 | 14038.447 | 38.17 | 10.61 | 48.78 | 54.00 | -5.22 | peak | | | |
| 3 | 17087.464 | 35.29 | 14.19 | 49.48 | 54.00 | -4.52 | peak | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #2918
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 7" 3G Tablet
Mode: TX 2452MHz(802.11n40)
Model: BOAD XT-71BG
Manufacturer: IMC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 14/06/16/
Time: 13/52/00
Engineer Signature:
Distance: 3m


Note: Report No:ATE20140926



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 10854.250 | 43.47 | 5.41 | 48.88 | 54.00 | -5.12 | peak | | | |
| 2 | 13249.931 | 40.73 | 8.46 | 49.19 | 54.00 | -4.81 | peak | | | |
| 3 | 15090.405 | 37.93 | 11.76 | 49.69 | 54.00 | -4.31 | peak | | | |

11.CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST

11.1.Block Diagram of Test Setup



11.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

11.3.EUT Configuration on Measurement

The equipment is installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.4.Operating Condition of EUT

11.4.1.Setup the EUT and simulator as shown as Section 11.1.

11.4.2.Turn on the power of all equipment.

11.4.3.Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

11.5. Test Procedure

11.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

11.5.2. Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz (below 1GHz).

11.5.3. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz (above 1GHz).


11.5.4. The Conducted Spurious Emission was measured and recorded.

11.6. Test Result


Pass.

The spectrum analyzer plots are attached as below.


TX 802.11b Channel Low 2412MHz




TX 802.11b Channel Middle 2437MHz




TX 802.11b Channel High 2462MHz




TX 802.11g Channel Low 2412MHz




TX 802.11g Channel Middle 2437MHz




TX 802.11g Channel High 2462MHz




TX 802.11n Channel Low 2412MHz (20MHz)




TX 802.11n Channel Middle 2437MHz (20MHz)




TX 802.11n Channel High 2462MHz (20MHz)




TX 802.11n Channel Low 2422MHz (40MHz)



TX 802.11n Channel Middle 2437MHz (40MHz)



TX 802.11n Channel High 2452MHz (40MHz)




12.ANTENNA REQUIREMENT

12.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

12.2.Antenna Construction

Device is equipped with Ceramic antenna, which isn't displaced by other antenna. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna