







### ISO/IEC17025Accredited Lab.

Report No: FCC 1507069-01 File reference No: 2015-07-13

Applicant: SHENZHEN HARMONY TECHNOLOGY CO., LTD

Product: TABLET PC

Model No: PLT9650G

Trademark: N/A

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10,FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: July 21, 2015

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

# SHENZHEN TIMEWAY TESTING LABORATORIES

Room 512-519, 5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen, Guangdong, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timewaytech.com

Report No: FCC1507069-01 Page 2 of 100

Date: 2015-07-13



# **Special Statement:**

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

### **CNAL-LAB Code: L2292**


The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

### FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

### IC- Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-02.



Date: 2015-07-13



# **Test Report Conclusion**

### Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details.	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	6
3.0	Technical Details	8
3.1	Summary of Test Results	8
3.2	Test Standards	8
4.0	EUT Modification.	8
5.0	Power Line Conducted Emission Test.	9
5.1	Schematics of the Test.	9
5.2	Test Method and Test Procedure.	9
5.3	Configuration of the EUT	9
5.4	EUT Operating Condition.	10
5.5	Conducted Emission Limit.	10
5.6	Test Result.	10
6.0	Radiated Emission test.	13
6.1	Test Method and Test Procedure.	13
6.2	Configuration of the EUT	13
6.3	EUT Operation Condition.	13
6.4	Radiated Emission Limit.	14
7.0	6dB Bandwidth Measurement	38
8.0	Maximum Peak Output Power	58
9.0	Power Spectral Density Measurement.	61
10.0	Out of Band Measurement.	79
11.0	Antenna Requirement.	88
12.0	FCC ID Label	89
13.0	Photo of Test Setup and EUT View	90

Date: 2015-07-13



### 1.0 General Details

### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Room 512-519,5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen,

Guangdong China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

### 1.2 Applicant Details

Applicant: SHENZHEN HARMONY TECHNOLOGY CO., LTD

Address: Block 2, Jiayuan Industrial Zone, Heping Community high-tech Park, No 2 Fuyuan Road,

Fuyong, Bao'an, Shenzhen, China

Telephone: -Fax: --

### 1.3 Description of EUT

Product: TABLET PC

Manufacturer: SHENZHEN HARMONY TECHNOLOGY CO., LTD

Address: Block 2, Jiayuan Industrial Zone, Heping Community high-tech Park, No 2

Fuyuan Road, Fuyong, Bao'an, Shenzhen, China

Brand Name: N/A
Additional Brand Name: N/A

Model Number: PLT9650G

Additional Model Number: N/A

Type of Modulation IEEE 802.11b : DSSS (CCK, QPSK, DBPSK)

IEEE 802.11g/n HT20/HT40: OFDM(64QAM, 16QAM, QPSK, BPSK)

Frequency range IEEE 802.11b/g/n HT20: 2412-2462MHz; IEEE 802.11n HT40: 2422-2452MHz;

Channel Spacing IEEE 802.11b/g/n HT20/HT40: 5MHz

Antenna: Integral antenna used.
Antenna Gain: Maximum 2.0dBi

Air Data Rate IEEE 802.11b : 11, 5.5, 2, 1 Mbps

IEEE 802.11g: 54, 48,36, 24, 18, 12, 9, 6 Mbps

IEEE  $802.11n\ HT20/40$ : up to 72Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: FCC1507069-01 Page 5 of 100

Date: 2015-07-13

By software Frequency Selection

Power Supply: HJ-050200U Input: 100-240V, 50/60Hz, 0.6A; Output: 5V, 2A

Channel Number IEEE 802.11b/g/n HT20: 11 Channels; IEEE 802.11n HT40: 7 Channels;

Submitted Sample: 2 Samples

1.5 **Test Duration** 

2015-07-10 to 2015-07-13

Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

Page 6 of 100

Report No: FCC1507069-01

Date: 2015-07-13



2.0		Test Equip	ments		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2014-08-22	2015-08-21
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2014-08-22	2015-08-21
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2014-08-22	2015-08-21
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2014-08-22	2015-08-21
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2014-08-22	2015-08-21
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2014-08-22	2015-08-21
System Controller	CT	SC100	-		
Loop Antenna	EMCO	6502	00042960	2014-08-22	2015-08-21
Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2014-08-22	2015-08-21
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2014-08-23	2015-08-21
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2014-08-23	2015-08-21
Power meter	Anritsu	ML2487A	6K00003613	2014-08-22	2015-08-21
Power sensor	Anritsu	MA2491A	32263	2014-08-22	2015-08-21
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2014-08-23	2015-08-21
LISN	AFJ	LS16C	10010947251	2014-08-22	2015-08-21
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2014-08-22	2015-08-21
9*6*6 Anechoic			N/A	2014-08-22	2015-08-21
EMI Test Receiver	RS	ESCS30	100139	2014-08-22	2015-08-21

### Auxiliary Equipment 2.1

Name	Model No.	Serial No.	Manufacturer	Cable	FCC ID/DOC
Passive Earphone					

Report No: FCC1507069-01 Page 7 of 100

Date: 2015-07-13



### 3. DESCRIPTION OF TEST MODES

### IEEE 802.11b, 802.11g, 802.11n (HT20) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 11Mbps data rate (worst case) was chosen for full testing. IEEE 802.11g mode: 6Mbps data rate (worst case) was chosen for full testing. IEEE 802.11n (HT20) mode: 72Mbps data rate (worst case) were chosen for full testing

### IEEE 802.11n (HT40) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2422
Middle	2437
High	2452

IEEE 802.11n (HT40) mode: 27Mbps data rate (worst case) were chosen for full testing

Note: EUT Test With 100% Duty cycle.

Date: 2015-07-13



### 3.0 **Technical Details**

### 3.1 **Summary of test results**

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107 & 15.207	<b>Conducted Emission Test</b>	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit: Table 15.209	PASS	Complies

### 3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247, ANSI C 63.10:2013 ANSI C 63.4:2014

### 4.0 **EUT Modification**


No modification by Shenzhen Timeway Technology Consulting Co., Ltd

Date: 2015-07-13



### 5. Power Line Conducted Emission Test

### 5.1 Schematics of the test




**EUT: Equipment Under Test** 

### 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10-2013

Test Voltage: 120V~, 60Hz Block diagram of Test setup



### 5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

### A. EUT

Device	Manufacturer	Model	FCC ID	
TABLET PC	SHENZHEN HARMONY	PLT9650G	2ACJAPLT9650G	
IABLET PC	TECHNOLOGY CO., LTD	PL19030G	ZACJAPL19030G	

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: FCC1507069-01 Page 10 of 100

Date: 2015-07-13



### B. Internal Device

Device	Manufacturer	Model	Rating

### C. Peripherals

Device	Manufacturer	Model	Rating

### 5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

### 5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107 and RSS-210

Frequency	Class A Lim	Class A Limits (dB µ V)		nits (dB µ V)				
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level				
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*				
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0				
5.00 ~ 30.00	73.0	60.0	60.0	50.0				

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

### 5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Date: 2015-07-13



### Conducted Emission on Live Terminal (150kHz to 30MHz) A:

**EUT Operating Environment** 


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

**EUT set Condition: Keeping WIFI Transmitting** 

**Equipment Level: Class B** 

**Results: PASS** 

Please refer to following diagram for individual



No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1508	35.90	11.00	46.90	65.96	-19.06	QP	
2	0.1508	4.00	11.00	15.00	55.96	-40.96	AVG	
3	0.1676	38.20	11.02	49.22	65.08	-15.86	QP	
4	0.1676	7.00	11.02	18.02	55.08	-37.06	AVG	
5 *	0.2041	42.20	11.06	53.26	63.44	-10.18	QP	
6	0.2041	6.80	11.06	17.86	53.44	-35.58	AVG	
7	0.2706	33.90	11.13	45.03	61.10	-16.07	QP	
8	0.2706	-0.20	11.13	10.93	51.10	-40.17	AVG	
9	2.4928	26.90	12.50	39.40	56.00	-16.60	QP	
10	2.4928	6.80	12.50	19.30	46.00	-26.70	AVG	

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Date: 2015-07-13



### B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

**EUT Operating Environment** 


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

**EUT set Condition: Keeping WIFI Transmitting** 

**Equipment Level: Class B** 

**Results: Pass** 

Please refer to following diagram for individual



No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1508	37.30	11.00	48.30	65.96	-17.66	QP	
2	0.1508	5.20	11.00	16.20	55.96	-39.76	AVG	
3	0.1706	38.60	11.02	49.62	64.93	-15.31	QP	
4	0.1706	2.90	11.02	13.92	54.93	-41.01	AVG	
5 *	0.2031	43.40	11.06	54.46	63.48	-9.02	QP	
6	0.2031	31.10	11.06	42.16	53.48	-11.32	AVG	
7	0.2701	35.30	11.13	46.43	61.11	-14.68	QP	
8	0.2701	9.20	11.13	20.33	51.11	-30.78	AVG	

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Report No: FCC1507069-01 Page 13 of 100

Date: 2015-07-13



### 6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10–2013. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization : Vertical polarization and Horizontal polarization.

# Block diagram of Test setup Distance = 3m Computer Pre -Amplifier Furn-table Receiver

- 6.2 Configuration of The EUT
  Same as section 5.3 of this report
- 6.3 EUT Operating Condition
  Same as section 5.4 of this report.

The report refers only to the sample tested and does not apply to the bulk.

Report No: FCC1507069-01 Page 14 of 100

Date: 2015-07-13



### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109

		<u> </u>
Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Page 15 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### Test result

### General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

**EUT set Condition: Keeping WIFI Transmitting** 

**Results: Pass** 

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
132.000	38.51	Н	43.50
900.000	43.04	Н	46.00
165.000	39.74	Н	43.50
110.600	31.54	V	43.50
561.000	39.03	V	46.00
132.000	33.93	V	43.50


Page 16 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### Test Figure:



10.JUL.2015 17:07:14 Date:


Page 17 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### Test Figure:



10.JUL.2015 17:03:46 Date:

Report No: FCC1507069-01 Page 18 of 100

Date: 2015-07-13



# Operation Mode: Keeping WIFI Transmitting under CH01 for 11g at 6Mbps

	1 0		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
4824.00	50.28 (PK)	Н	74(Peak)/ 54(AV)
4824.00	50.32 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16884		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 6Mbps

Date: 2015-07-13



### Operation Mode: Keeping WIFI Transmitting under CH06 for 11g at 6Mbps

	1 0	0	
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \) V/m)
4874.00	51.15 (PK)	Н	74(Peak)/ 54(AV)
4874.00	52.20 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 6 Mbps

### Operation Mode: Keeping WIFI Transmitting under CH11 for 11g at 6Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \) V/m)
4924	52.08 (PK)	Н	74(Peak)/ 54(AV)
4924	51.64 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 6 Mbps

Date: 2015-07-13




Please refer to the following test plots for details:

### CH01 for 11g at 6Mbps: Horizontal



### CH01 for 11g at 6Mbps: Vertical




Page 21 of 100

Report No: FCC1507069-01


Date: 2015-07-13



# CH06 for 11g at 6Mbps: Vertical



### CH06 for 11g at 6Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Date: 2015-07-13



### CH11 for 11g at 6Mbps: Vertical



### CH11 for 11g at 6Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Date: 2015-07-13



### Operation Mode: Keeping WIFI Transmitting under CH01 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03bc V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4824.00	50.82 (PK)	Н	74(Peak)/ 54(AV)
4824.00	50.59 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

# Operation Mode: Keeping WIFI Transmitting under CH06 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4874.00	52.51 (PK)	Н	74(Peak)/ 54(AV)
4874.00	50.08 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

Report No: FCC1507069-01 Page 24 of 100

Date: 2015-07-13



### Operation Mode: Keeping WIFI Transmitting under CH11 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4924	49.29 (PK)	Н	74(Peak)/ 54(AV)
4924	52.63 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode at 11Mbps

Date: 2015-07-13




Please refer to the following test plots for details:

# CH01 for 11b at 11Mbps: Horizontal



# CH01 for 11b at 11Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 26 of 100

Report No: FCC1507069-01


Date: 2015-07-13



### CH06 for 11b at 11Mbps: Vertical



### CH06 for 11b at 11Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Date: 2015-07-13



### CH11 for 11b at 11Mbps: Vertical



# CH11 for 11b at 11Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Date: 2015-07-13



### Operation Mode: Keeping WIFI Transmitting under CH01 for 11n HT20 at 72Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4824.00	49.35 (PK)	Н	74(Peak)/ 54(AV)
4824.00	51.59 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 72Mbps

# Operation Mode: Keeping WIFI Transmitting under CH06 for 11n HT20 at 72Mbps

Frequency (MHz)	Level@3m (dB \u03ba V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4874.00	50.54 (PK)	Н	74(Peak)/ 54(AV)
4874.00	51.19 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 72Mbps

Report No: FCC1507069-01 Page 29 of 100

Date: 2015-07-13



### Operation Mode: Keeping WIFI Transmitting under CH11 for 11n HT20 at 72Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4924	50.19 (PK)	Н	74(Peak)/ 54(AV)
4924	50.64 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 72Mbps

Date: 2015-07-13




Please refer to the following test plots for details:

### CH01 for 11n HT20 at 72Mbps: Horizontal



### CH01 for 11n HT20 at 72Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Date: 2015-07-13



### CH06 for 11n HT20 at 72Mbps: Vertical



# CH06 for 11n HT20 at 72Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Date: 2015-07-13



### CH11 for 11n HT20 at 72Mbps: Vertical



# CH11 for 11n HT20 at 72Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Date: 2015-07-13



### Operation Mode: Transmitting under CH01 for 11n HT40 at 27Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4844.00	50.51 (PK)	Н	74(Peak)/ 54(AV)
4844.00	52.27 (PK)	V	74(Peak)/ 54(AV)
7266.00		H/V	74(Peak)/ 54(AV)
9688.00		H/V	74(Peak)/ 54(AV)
12110		H/V	74(Peak)/ 54(AV)
14532		H/V	74(Peak)/ 54(AV)
16954		H/V	74(Peak)/ 54(AV)
19376	-	H/V	74(Peak)/ 54(AV)
21798		H/V	74(Peak)/ 54(AV)
24220		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 27Mbps

### Operation Mode: Transmitting under CH04 for 11n HT40 at 27Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4874.00	50.66 (PK)	Н	74(Peak)/ 54(AV)
4874.00	51.03 (PK)	V	74(Peak)/ 54(AV)
7311.00	-	H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622	-	H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 27Mbps

Report No: FCC1507069-01 Page 34 of 100

Date: 2015-07-13



### Operation Mode: Transmitting under CH07 for 11n HT40 at 27Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4904	49.82 (PK)	Н	74(Peak)/ 54(AV)
4904	51.08 (PK)	V	74(Peak)/ 54(AV)
7356		H/V	74(Peak)/ 54(AV)
9808		H/V	74(Peak)/ 54(AV)
12260		H/V	74(Peak)/ 54(AV)
14712		H/V	74(Peak)/ 54(AV)
17164		H/V	74(Peak)/ 54(AV)
19616		H/V	74(Peak)/ 54(AV)
22068		H/V	74(Peak)/ 54(AV)
24520		H/V	74(Peak)/ 54(AV)


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 27Mbps

Date: 2015-07-13




Please refer to the following test plots for details:

### CH01 for 11n HT40 at 27Mbps: Horizontal



### CH01 for 11n HT40 at 27Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Date: 2015-07-13



### CH04 for 11n HT40 at 27Mbps: Vertical



# CH04 for 11n HT40 at 27Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Report No: FCC1507069-01


Date: 2015-07-13



## CH07 for 11n HT40 at 27Mbps: Vertical



### CH07 for 11n HT40 at 27Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Page 38 of 100


Report No: FCC1507069-01

Date: 2015-07-13



#### 7.0 6dB Bandwidth Measurement

### 7.1 Test Setup



#### 7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

#### 7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW)  $\geq$  3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 7.4 Test Result

Report No: FCC1507069-01 Page 39 of 100

Date: 2015-07-13



# 6dB Occupied Bandwidth

EUT		TABLET PO	Model		PLT9650G			
Mode		802.11b		Input Voltage			DC3.7	V
Temperat	ure	24 deg. C,		Hum	idity	56% RH		
Channel	Channel Frequency (MHz)		Tra R	ata nsfer ate bps)	6 dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass/ Fail
1	2412			1	10.04		0.5	Pass
6		2437		1	10.04	ļ	0.5	Pass
11		2462		1	10.04	ļ	0.5	Pass
1	2412			11	9.32		0.5	Pass
6	2437			11	9.32		0.5	Pass
11	2462			11	9.32		0.5	Pass


Page 40 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 1. 802.11b at 1Mbps of CH01



7.JUL.2015 10:37:01 Date:


Page 41 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 2. 802.11b at 1Mbps of CH06



7.JUL.2015 10:53:27 Date:


Page 42 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 3. 802.11b at 1Mbps of CH11



7.JUL.2015 10:57:43 Date:


Page 43 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 4. 802.11b at 11Mbps of CH01




Page 44 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 5. 802.11b at 11Mbps of CH06



7.JUL.2015 10:51:00 Date:


Page 45 of 100

Report No: FCC1507069-01

Date: 2015-07-13



# 6. 802.11b at 11Mbps of CH11



7.JUL.2015 11:02:05 Date:

Report No: FCC1507069-01 Page 46 of 100

Date: 2015-07-13



# 6dB Occupied Bandwidth

EUT	UT TABLET PC Model		el	PLT9650G				
Mode		802.11g		Input Voltage		DC3.7V		7
Temperat	ure	24 deg. C,		Hum	idity		56% RI	I
Channel	Chai	nnel Frequency (MHz)	Tra R	oata nsfer ate (bps)	6 dB Band (MHz		Minimum Limit (MHz)	Pass/ Fail
1		2412		6	16.41		0.5	Pass
6		2437		6 16.41			0.5	Pass
11		2462		6	16.41	l	0.5	Pass

Page 47 of 100


Report No: FCC1507069-01

Date: 2015-07-13



#### **Test Plots:**

#### 1. 802.11g at 6Mbps of CH01




Page 48 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 2. 802.11g at 6Mbps of CH06



7.JUL.2015 10:48:40 Date:


Page 49 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 3. 802.11g at 6Mbps of CH11



7.JUL.2015 10:59:57 Date:

Report No: FCC1507069-01 Page 50 of 100

Date: 2015-07-13



### 6dB Occupied Bandwidth

EUT	UT TABLET P		С	C Model		PLT9650G			
Mode		802.11n HT	20	Input Voltage		DC3.7V			
Temperati	ure	24 deg. C,		Hu	midity		56% R	CH .	
Channel	Channel Frequency (MHz)		Dat Trans Rat (Mbp	sfer e	6 dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass/ Fail	
1		2412		72 17.50		6	0.5	Pass	
6	2437		72	2 17.50		5	0.5	Pass	
11		2462			17.50	6	0.5	Pass	

Page 51 of 100


Report No: FCC1507069-01

Date: 2015-07-13



#### **Test Plots:**

#### 1. 802.11n at HT20 of CH01



7.JUL.2015 11:38:44 Date:


Page 52 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 2. 802.11n at HT20 of CH06



7.JUL.2015 Date: 11:41:36


Page 53 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 3. 802.11n at HT20 of CH11



7.JUL.2015 Date: 11:44:19 Report No: FCC1507069-01 Page 54 of 100

Date: 2015-07-13



### 6dB Occupied Bandwidth

EUT	EUT TABLET P		С	Model		PLT9650G			
Mode		802.11n HT	40	Input Voltage		DC3.7V			
Temperati	ure	24 deg. C,		Hu	midity		56% R	LH .	
Channel	Channel Frequency (MHz)		Dat Trans Rat (Mbp	sfer e	6 dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass/ Fail	
1		2422		27 35.39		)	0.5	Pass	
4	2437		27	27 35.39		)	0.5	Pass	
7	2452		27	35.39		)	0.5	Pass	

Page 55 of 100


Report No: FCC1507069-01

Date: 2015-07-13



#### **Test Plots:**

#### 1. 802.11n at HT40 of CH01



7.JUL.2015 11:48:18 Date:


Page 56 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 2. 802.11n at HT40 of CH04



7.JUL.2015 14:48:35 Date:


Page 57 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 3. 802.11n at HT40 of CH7



7.JUL.2015 14:50:42 Date:

Report No: FCC1507069-01


Date: 2015-07-13



Page 58 of 100

## 8. Maximum Peak Output Power

### 8.1 Test Setup



### 8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

#### **8.3 Test Procedure**

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the peak power was measured

Report No: FCC1507069-01

Date: 2015-07-13



# **8.4Test Results**

EUT	TABLET PC	Model	PLT9650G		
Mode	802.11b	Input Voltage	DC3.7V		
Temperature	24 deg. C,	Humidity	56% RH		
Chamal	Channel Frequency	Max. Power 0	Output	Power Limit	Pass/ Fail
Channel	(MHz)	(dBm)		(dBm)	
1	2412	7.95		30	Pass
6	2437	8.37		30	Pass
11	2462	8.39		30	Pass

Note: 1. At finial test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT	TABLET PC	Model		PLT9650G		
Mode	802.11g	Input Voltage	DC3.7V			
Temperature	24 deg. C,	Humidity	56% RH			
Channal	Channel Frequency	Max. Powe	r Output	Power Limit	Pass/ Fail	
Channel	(MHz)	(dBn	n)	(dBm)		
1	2412	4.66	6	30	Pass	
6	2437	5.12	2	30	Pass	
11	2462	5.09	)	30	Pass	

Note: 1. At finial test to get the worst-case emission at 6Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

Page 60 of 100

Report No: FCC1507069-01

Date: 2015-07-13



EUT	TABLET PC	Model		PLT9650G			
Mode	802.11n (HT20)	Input Voltage	DC3.7V				
Temperature	24 deg. C,	Humidity	56% RH				
Channel	Channel Frequency	Max. Power	Output	Power Limit	Pass/ Fail		
Chamiei	(MHz)	(dBm	1)	(dBm)			
1	2412	4.97		30	Pass		
6	2437	5.43		30	Pass		
11	2462	5.26		30	Pass		

Note: 1. At finial test to get the worst-case emission at 72Mbps 11n HT20 for CH01, CH06 and CH11

- 2. The result basic equation calculation as follow: Peak Power Output = Peak Power Reading + Cable loss + Attenuator
- 3. The worse case was recorded

EUT	TA	BLET PC	Model		PLT9650G		
Mode		302.11n (HT40)	Input Voltage	e	DC3.7V		
Temperature	24	4 deg. C,	Humidity		56% RH		
Channel		el Frequency (MHz)		Max. Power Output (dBm)		mit	Pass/ Fail
1		2422	5	5.14			Pass
4		2437	5	5.20			Pass
7		2452	5	5.24			Pass

Note: 1. At finial test to get the worst-case emission at 27Mbps of 11n HT40 for CH01, CH04 and CH7

- 2. The result basic equation calculation as follow:
  - Max. Power Output = Power Reading + Cable loss + Attenuator
- 3. The worse case was recorded


Report No: FCC1507069-01 Page 61 of 100

Date: 2015-07-13



# 9. Power Spectral Density Measurement

### 9.1 Test Setup



## 9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

#### 9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW > 30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be  $\leq 8$  dBm.

Page 62 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 9.4Test Result

EUT	TABLET PC		Model	PLT9650G		
Mode	Mode 802.11b 11Mbps		Input Voltage	DC3.7V		
Temperatur	e	24 deg. C,	Humidity	56% RH		
Channel	Channel Frequency (MHz)		Final RF Power Level (dBm)	Maximum Limit (dBm)	Pass/ Fail	
			11Mbps			
1		2412	-16.00	8	Pass	
6		2437	-15.70	8	Pass	
11		2462	-15.93	8	Pass	

EUT	EUT TABLET PC		Model		PLT9650G	
Mode	Mode 802.11b 1Mbps		Input Voltage		DC3.7V	
Temperatur	e	24 deg. C,	Humidity		56% RH	
Channel	Channel Frequency		Final RF Power		Maximum Limit	Pass/ Fail
Channel		(MHz)	Level (dBm)		(dBm)	
			1Mbps	}		
1		2412	-16.79		8	Pass
6		2437	-16.28		8	Pass
11		2462	-16.19		8	Pass

Page 63 of 100

Report No: FCC1507069-01

Date: 2015-07-13



EUT	UT TABLET PC		Model		PLT9650G	
Mode	Mode 802.11g 6Mbps		Input Voltage		DC3.7V	
Temperatur	e	24 deg. C,	Humidity		56% RH	
C11	Cł	nannel Frequency	Final RF Power		Maximum Limit	Pass/ Fail
Channel		(MHz)	Level (dBm)		(dBm)	
			6Mbps			
1		2412	-24.29		8	Pass
6		2437	-24.09		8	Pass
11		2462	-24.54		8	Pass

EUT		TABLET PC	Model	PLT9650G	
Mode	Mode 802.11n HT20 72Mbps		Input Voltage	DC3.7V	
Temperatur	е	24 deg. C,	Humidity	56% RH	
Channel	Channel Frequency (MHz)		Final RF Power Level (dBm)	Maximum Limit (dBm)	Pass/ Fail
			72Mbps		
1		2412	-23.02	8	Pass
6		2437	-24.08	8	Pass
11		2462	-23.35	8	Pass

EUT		TABLET PC	Model	PLT9650G	
Mode		802.11n (HT40) 27Mbps	Input Voltage	DC3.7V	
Temperature		24 deg. C,	Humidity	56% RH	
Channel	Channel Frequency (MHz)		Final RF Power Level (dBm)	Maximum Limit (dBm)	Pass/ Fail
27Mbps					
1		2422	-26.34	8	Pass
4		2437	-26.17	8	Pass
7	2452		-25.85	8	Pass

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

adopt any other remedies which may be appropriate.

Page 64 of 100


Report No: FCC1507069-01

Date: 2015-07-13



## 9.5 Photo of Power Spectral Density Measurement

1.802.11b at 11Mbps of CH01



7.JUL.2015 15:57:13 Date:


Page 65 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 2. 802.11b at 11Mbps at CH06



7.JUL.2015 15:57:59 Date:


Page 66 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 3. 802.11b at 11Mbps of CH11



7.JUL.2015 15:58:46 Date:


Page 67 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 4. 802.11b at 1Mbps of CH1



7.JUL.2015 15:51:02 Date:


Page 68 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 5. 802.11b at 1Mbps of CH6



7.JUL.2015 15:51:45 Date:


Page 69 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 6. 802.11b at 1Mbps of CH11



7.JUL.2015 15:52:11 Date:


Page 70 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 7. 802.11g at 6Mbps of CH1



7.JUL.2015 15:56:19 Date:


Page 71 of 100

Report No: FCC1507069-01

Date: 2015-07-13



### 8. 802.11g at 6 Mbps of CH6



7.JUL.2015 15:54:43 Date:


Page 72 of 100

Report No: FCC1507069-01

Date: 2015-07-13



# 9. 802.11g at 6 Mbps of CH11



7.JUL.2015 15:52:51 Date:


Page 73 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 10. 802.11n at HT20 of CH01



7.JUL.2015 16:03:28 Date:


Page 74 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 11. 802.11n at HT20 of CH06



7.JUL.2015 16:02:30 Date:


Page 75 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 12. 802.11n at HT20 of CH11



7.JUL.2015 16:00:25 Date:


Page 76 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 13. 802.11n at HT40 of CH01



7.JUL.2015 16:04:58 Date:


Page 77 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 14. 802.11n at HT40 of CH04



7.JUL.2015 16:06:16 Date:


Page 78 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 15. 802.11n at HT40 of CH07



7.JUL.2015 16:09:04 Date:


Report No: FCC1507069-01 Page 79 of 100

Date: 2015-07-13



### 10 Out of Band Measurement

# 10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

#### 10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

#### **10.3 Test Procedure**

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of Radiated emission test. (Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector)

For bandage test, the spectrum set as follows: RBW=100 kHz, VBW=300 kHz. A conducted measurement used

### 10.4 Test Result

Please see next pages

Note: 1. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

2. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Report No: FCC1507069-01

Date: 2015-07-13




#### For 802.11b mode

# CH01 at 11Mbps

Band-edge and Restricted band Measurement 10.4

EUT	TABLET PC	Model		PLT9650G		
Mode	Keeping Transmitting	g Input Voltage	DC3.7V			
Temperature	24 deg. C,	Humidity	56% RH			
Test Result:	Pass	Detector	PK			
2400	PK (dBμV/m)	58.2	Limit	$74(dB\mu V/m)$		
	AV (dBμV/m)	39.6	Limit	$54(dB\mu V/m)$		
2390	PK (dBµV/m)	43.9	Limit	$74(dB\mu V/m)$		
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$		

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 81 of 100

Report No: FCC1507069-01

Date: 2015-07-13




#### CH11 at 11Mbps

**10.4** Band-edge and Restricted band Measurement

EUT	TABLET PC	Model		PLT9650G
Mode	Keeping Transmitting	g Input Voltage		DC3.7V
Temperature	24 deg. C,	Humidity	56% RH	
Test Result:	Pass	Detector	PK	
2483.5	PK (dBµV/m)	43.7	T ::4	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	54(dBμV/m)

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Report No: FCC1507069-01

Date: 2015-07-13




#### For 802.11g mode

CH01 at 6Mbps

Band-edge and Restricted band Measurement 10.4

EUT	TABLET PC	Model		PLT9650G
Mode	Keeping Transmitting	Input Voltage		DC3.7V
Temperature	24 deg. C,	Humidity		56% RH
Test Result:	Pass	Detector	PK	
2400	PK (dBμV/m)	59.5	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)	41.6	Limit	$54(dB\mu V/m)$
2390	PK (dBμV/m)	44.6	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)			$54(dB\mu V/m)$

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 83 of 100

Report No: FCC1507069-01

Date: 2015-07-13




#### CH11 at 6Mbps

10.4 Band-edge and Restricted band Measurement

EUT	TABLET PC	Model		PLT9650G
Mode	Keeping Transmittin	g Input Voltage		DC3.7V
Temperature	24 deg. C,	Humidity		56% RH
Test Result:	Pass	Detector	PK	
2483.5	PK (dBμV/m)	45.2	T ::4	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	54(dBμV/m)

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Report No: FCC1507069-01

Date: 2015-07-13




#### For 802.11n (HT20) mode

CH01 at 72Mbps

Band-edge and Restricted band Measurement 10.4

	1011 Sund 1081 and 1100011010 cand 1110000110110					
EUT	TABLET PC	Model	PLT9650G			
Mode	Keeping Transmitting	Input Voltage	DC3.7V			
Temperature	24 deg. C,	Humidity	56% RH			
Test Result:	Pass	Detector	PK			
2400	PK (dBμV/m)	61.6	Timit	$74(dB\mu V/m)$		
	AV (dBμV/m)	42.8	Limit	$54(dB\mu V/m)$		
2390	PK (dBμV/m)	45.6	Limit	$74(dB\mu V/m)$		
	AV (dBμV/m)		Liffill	$54(dB\mu V/m)$		

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 85 of 100

Report No: FCC1507069-01

Date: 2015-07-13




#### CH11 at 72Mbps

## 10.4 Band-edge and Restricted band Measurement

EUT	TABLET PC	Model	PLT9650G	
Mode	Keeping Transmitting	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Test Result:	Pass	Detector	PK	
2483.5	PK (dBμV/m)	46.3	T: '/	74(dBμV/m)
	AV (dBμV/m)		Limit	54(dBµV/m)

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Report No: FCC1507069-01

Date: 2015-07-13




#### For 802.11n (HT40) mode

CH01 at 27Mbps

Band-edge and Restricted band Measurement 10.4

	<b>1011</b> — 1					
EUT	TABLET PC	Model		PLT9650G		
Mode	Keeping Transmitting	Input Voltage	DC3.7V			
Temperature	24 deg. C,	Humidity	56% RH			
Test Result:	Pass	Detector	PK			
2400	PK (dBμV/m)	63.1	T ::4	$74(dB\mu V/m)$		
	AV (dBμV/m)	45.8	Limit	$54(dB\mu V/m)$		
2390	PK (dBμV/m)	49.2	Limit	74(dBμV/m)		
	AV (dBμV/m)			$54(dB\mu V/m)$		

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 87 of 100

Report No: FCC1507069-01

Date: 2015-07-13




#### CH7 at 27Mbps

10.4 Band-edge and Restricted band Measurement

EUT	TABLET PC	Model	PLT9650G	
Mode	Keeping Transmitting	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Test Result:	Pass	Detector	PK	
2483.5	PK (dBµV/m)	56.2	T,	74(dBμV/m)
	AV (dBμV/m)	38.2	Limit	54(dBµV/m)

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Report No: FCC1507069-01

Date: 2015-07-13



Page 88 of 100

# 11.0 Antenna Requirement

## 11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 11.2 Antenna Connected construction

Integral antennas used. The maximum Gain of each antenna is 2.0 dBi.

Report No: FCC1507069-01 Page 89 of 100

Date: 2015-07-13




#### 12.0 FCC Label

#### FCC ID: 2ACJAPLT9650G

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

#### **Mark Location:**



Page 90 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### 13.0 Photo of testing

Conducted Emission Test Setup:



Page 91 of 100

Report No: FCC1507069-01

Date: 2015-07-13



# Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 92 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 93 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 94 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 95 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 96 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 97 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 98 of 100

Report No: FCC1507069-01

Date: 2015-07-13



#### **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 99 of 100

Report No: FCC1507069-01

Date: 2015-07-13



# **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 100 of 100


Report No: FCC1507069-01

Date: 2015-07-13



# **Photos of EUT**





End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.