

TEST REPORT

Reference No. : WTS14S0614741E
FCC ID..... : 2ACMNB15AP2
Applicant..... : HealthCare Information,LLC
Address : 113 Commerce Blvd,Loveland OH 45140 USA
Manufacturer : Goldtec (China) Ltd.
Address : 3/F Block C11,Fuyuan Industrial Park,NO.111 Zhoushi Road, Xixiang Town, Shenzhen,Guangdong, China.
Product Name : 15.6" Android Bedmate V2
Model No. : BM15AP2
Standards..... : FCC CFR47 Part 15 C Section 15.247:2012
Date of Receipt sample..... : Jun.12, 2014
Date of Test..... : Jun.13~19, 2014
Date of Issue : Jun.25, 2014
Test Result : Pass *

***Remarks:**

The results shown in this test report refer only to the sample(s) tested; this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Testing location: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Zero Zhou / Project Engineer

Approved by:

Philo Zhong / Manager

2 Test Summary

Test Items	Test Requirement	Result
Radiated Emissions	15.247 15.205(a) 15.209(a)	PASS
Conducted Emissions	15.207(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3),(4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

3 Contents

	Page
1 COVER PAGE.....	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	5
4.1 GENERAL DESCRIPTION OF E.U.T.	5
4.2 DETAILS OF E.U.T.	5
4.3 CHANNEL LIST	5
4.4 TEST MODE	6
4.5 TEST FACILITY.....	6
5 EQUIPMENT USED DURING TEST	7
5.1 EQUIPMENTS LIST	7
5.2 DESCRIPTION OF SUPPORT UNITS	8
5.3 MEASUREMENT UNCERTAINTY	8
5.4 TEST EQUIPMENT CALIBRATION	8
6 CONDUCTED EMISSION	9
6.1 E.U.T. OPERATION	9
6.2 EUT SETUP.....	9
6.3 MEASUREMENT DESCRIPTION	9
6.4 CONDUCTED EMISSION TEST RESULT	10
7 RADIATED EMISSIONS.....	12
7.1 EUT OPERATION.....	12
7.2 TEST SETUP	13
7.3 SPECTRUM ANALYZER SETUP	14
7.4 TEST PROCEDURE	15
7.5 SUMMARY OF TEST RESULTS	16
8 BAND EDGE MEASUREMENT	28
8.1 TEST PRODUCE.....	28
8.2 TEST RESULT	29
9 6 DB BANDWIDTH MEASUREMENT	33
9.1 TEST PROCEDURE:	33
9.2 TEST RESULT:	33
10 MAXIMUM PEAK OUTPUT POWER	40
10.1 TEST PROCEDURE:.....	40
10.2 TEST RESULT:	40
11 POWER SPECTRAL DENSITY	47
11.1 TEST PROCEDURE:.....	47
11.2 TEST RESULT:	47
12 ANTENNA REQUIREMENT	54
13 RF EXPOSURE.....	55
13.1 REQUIREMENTS.....	55
13.2 THE PROCEDURES / LIMIT	55
13.3 MPE CALCULATION METHOD	56
14 PHOTOGRAPHS – MODEL BM15AP2 TEST SETUP	57
14.1 CONDUCTED EMISSION	57
14.2 RADIATED EMISSION	57
15 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS	59

15.1 MODEL BM15AP2 –EXTERNAL VIEW59

15.2 MODEL BM15AP2 – INTERNAL VIEW.....63

4 General Information

4.1 General Description of E.U.T.

Product Name	: 15.6" Android Bedmate V2
Model No.	: BM15AP2
Model Difference	: N/A
Operation Frequency	: 2412MHz ~ 2462MHz, 2422MHz~2452MHz
The Lowest Oscillator	: 12MHz
Antenna Gain	: 2dBi
Type of modulation	: IEEE 802.11b (CCK/QPSK/BPSK,11Mbps max.) IEEE 802.11g (BPSK/QPSK/16QAM/64QAM,54Mbps max.) IEEE 802.11n (BPSK/QPSK/16QAM/64QAM,HT20:72Mbps max., HT40:150Mbps max.)

4.2 Details of E.U.T.

Technical Data	: DC 24V, 1.6A by adapter
----------------	---------------------------

4.3 Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

4.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Power Spectral Density	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Frequency Range	802.11b	11 Mbps	1/11	TX
	802.11g	54 Mbps	1/11	TX
	802.11n HT20	108 Mbps	1/11	TX
	802.11n HT40	150 Mbps	3/9	TX
Transmitter Spurious Emissions	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/7/9	TX

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

Table 2 Tests Carried Out Under FCC part 15.207 & FCC part 15.209

Test Item	Test Mode
Conduction Emission, 0.15MHz to 30MHz	Communication

4.5 Test Facility

The test facility has a test site registered with the following organizations:

- **IC – Registration No.: 7760A-1**

Waltek Services (Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A-1, July 12, 2012.

- **FCC – Registration No.: 880581**

Waltek Service s(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

5 Equipment Used during Test

5.1 Equipments List

Conducted Emissions at Mains Terminals Disturbance Voltage						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	Sep.18,2013	Sep.17,2014
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	Sep.18,2013	Sep.17,2014
3.	Limiter	York	MTS-IMP-136	261115-001-0024	Sep.18,2013	Sep.17,2014
4.	Cable	LARGE	RF300	-	Sep.18,2013	Sep.17,2014
3m Semi-anechoic Chamber for Radiation						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	EMC Analyzer	Agilent	E7405A	MY45114943	Sep.18,2013	Sep.17,2014
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	Sep.18,2013	Sep.17,2014
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	Apr.19,2014	Apr.18,2015
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	Sep.18,2013	Sep.17,2014
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Apr.19,2014	Apr.18,2015
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	Apr.19,2014	Apr.18,2015
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Mar.17,2014	Mar.16,2015
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	Apr.10,2014	Apr.09,2015
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer	R&S	ESCI	101155	Sep.18,2013	Sep.17,2014
2.	Humidity Chamber	GF	GTH-225-40-1P	IAA061213	May 16,2014	May 15,2015
3.	DC Power Supply	EVERFINE	WY305	1004002	Apr.11,2014	Apr.10,2015

5.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
Adapter	SONY	AC-S2416	-
Remark: Adapter Input: AC 100-240V, 50/60Hz, 1.2A Max. output:DC24V,1.6A			

5.3 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (30M~1000MHz)
	± 5.47 dB (1000M~25000MHz)
Conducted Spurious Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)

5.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

6 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.4:2003
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth)

6.1 E.U.T. Operation

Operating Environment :


Temperature:	22.5 °C
Humidity:	51.9 % RH
Atmospheric Pressure:	101.2kPa

EUT Operation :

The test was performed in communication mode, the test data were shown in the report.

6.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.4:2003.




6.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


6.4 Conducted Emission Test Result

An initial pre-scan was performed on the live and neutral lines.

Live line:



Neutral line:



7 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.4:2003

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

7.1 EUT Operation

Operating Environment :

Temperature: 22.0 °C

Humidity: 51.8 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4: 2003.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Below 30MHz

- Sweep Speed Auto
- IF Bandwidth.....10kHz
- Video Bandwidth.....10kHz
- Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

- Sweep Speed Auto
- DetectorPK
- Resolution Bandwidth.....100kHz
- Video Bandwidth.....300kHz

Above 1GHz

- Sweep Speed Auto
- DetectorPK
- Resolution Bandwidth.....1MHz
- Video Bandwidth.....3MHz
- DetectorAve.
- Resolution Bandwidth.....1MHz
- Video Bandwidth.....10Hz

7.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in X axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used druing radiated emissions above 1GHz measurement.

7.5 Summary of Test Results

Test Frequency: 12MHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11b: Low Channel 2412MHz									
198.56	22.01	PK	169	1.6	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	162	1.5	V	11.26	30.83	40.00	-9.17
4824.00	51.79	PK	168	1.6	V	-1.06	50.73	74.00	-23.27
4824.00	49.21	Ave	168	1.6	V	-1.06	48.15	54.00	-5.85
7236.00	41.67	PK	198	1.8	H	1.33	43.00	74.00	-31.00
7236.00	38.83	Ave	198	1.8	H	1.33	40.16	54.00	-13.84
2327.79	46.02	PK	129	1.6	V	-13.19	32.83	74.00	-41.17
2327.79	37.79	Ave	129	1.6	V	-13.19	24.60	54.00	-29.40
2387.63	42.74	PK	150	1.7	H	-13.14	29.60	74.00	-44.40
2387.63	36.87	Ave	150	1.7	H	-13.14	23.73	54.00	-30.27
2495.53	42.21	PK	328	1.7	V	-13.08	29.13	74.00	-44.87
2495.53	36.52	Ave	328	1.7	V	-13.08	23.44	54.00	-30.56

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11b: Middle Channel 2437MHz									
198.56	22.01	PK	306	1.7	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	15	1.1	V	11.26	30.83	40.00	-9.17
4874.00	52.40	PK	153	1.4	V	-0.62	51.78	74.00	-22.22
4874.00	49.11	Ave	153	1.4	V	-0.62	48.49	54.00	-5.51
7311.00	46.49	PK	247	1.3	H	2.21	48.70	74.00	-25.30
7311.00	39.73	Ave	247	1.3	H	2.21	41.94	54.00	-12.06
2346.71	46.58	PK	308	1.6	V	-13.19	33.39	74.00	-40.61
2346.71	39.84	Ave	308	1.6	V	-13.19	26.65	54.00	-27.35
2361.88	44.39	PK	127	1.1	H	-13.14	31.25	74.00	-42.75
2361.88	37.50	Ave	127	1.1	H	-13.14	24.36	54.00	-29.64
2494.36	42.61	PK	64	1.4	V	-13.08	29.53	74.00	-44.47
2494.36	37.36	Ave	64	1.4	V	-13.08	24.28	54.00	-29.72

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11b: High Channel 2462MHz									
198.56	22.01	PK	202	1.2	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	211	1.3	V	11.26	30.83	40.00	-9.17
4924.00	52.09	PK	2	1.7	V	-0.24	51.85	74.00	-22.15
4924.00	49.32	Ave	2	1.7	V	-0.24	49.08	54.00	-4.92
7386.00	48.60	PK	140	1.1	H	2.84	51.44	74.00	-22.56
7386.00	40.37	Ave	140	1.1	H	2.84	43.21	54.00	-10.79
2327.58	45.79	PK	228	1.9	V	-13.19	32.60	74.00	-41.40
2327.58	39.33	Ave	228	1.9	V	-13.19	26.14	54.00	-27.86
2367.85	42.50	PK	36	1.9	H	-13.14	29.36	74.00	-44.64
2367.85	36.68	Ave	36	1.9	H	-13.14	23.54	54.00	-30.46
2499.89	42.62	PK	74	1.8	V	-13.08	29.54	74.00	-44.46
2499.89	38.72	Ave	74	1.8	V	-13.08	25.64	54.00	-28.36

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11g: Low Channel 2412MHz									
198.56	22.01	PK	215	1.2	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	274	1.9	V	11.26	30.83	40.00	-9.17
4824.00	51.20	PK	284	1.5	V	-1.06	50.14	74.00	-23.86
4824.00	49.19	Ave	284	1.5	V	-1.06	48.13	54.00	-5.87
7236.00	42.36	PK	283	1.8	H	1.33	43.69	74.00	-30.31
7236.00	38.97	Ave	283	1.8	H	1.33	40.30	54.00	-13.70
2347.50	45.28	PK	7	1.2	V	-13.19	32.09	74.00	-41.91
2347.50	37.95	Ave	7	1.2	V	-13.19	24.76	54.00	-29.24
2361.68	44.89	PK	208	1.0	H	-13.14	31.75	74.00	-42.25
2361.68	38.29	Ave	208	1.0	H	-13.14	25.15	54.00	-28.85
2491.53	42.89	PK	221	1.7	V	-13.08	29.81	74.00	-44.19
2491.53	38.66	Ave	221	1.7	V	-13.08	25.58	54.00	-28.42

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11g: Middle Channel 2437MHz									
198.56	22.01	PK	122	1.3	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	68	2.0	V	11.26	30.83	40.00	-9.17
4874.00	50.83	PK	297	1.5	V	-0.62	50.21	74.00	-23.79
4874.00	49.58	Ave	297	1.5	V	-0.62	48.96	54.00	-5.04
7311.00	46.08	PK	231	1.2	H	2.21	48.29	74.00	-25.71
7311.00	38.80	Ave	231	1.2	H	2.21	41.01	54.00	-12.99
2324.56	46.63	PK	1	1.1	V	-13.19	33.44	74.00	-40.56
2324.56	37.42	Ave	1	1.1	V	-13.19	24.23	54.00	-29.77
2388.95	44.29	PK	192	1.9	H	-13.14	31.15	74.00	-42.85
2388.95	38.07	Ave	192	1.9	H	-13.14	24.93	54.00	-29.07
2491.15	42.93	PK	145	1.2	V	-13.08	29.85	74.00	-44.15
2491.15	38.14	Ave	145	1.2	V	-13.08	25.06	54.00	-28.94

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11g: High Channel 2462MHz									
198.56	22.01	PK	4	1.6	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	320	1.6	V	11.26	30.83	40.00	-9.17
4924.00	51.43	PK	320	1.4	V	-0.24	51.19	74.00	-22.81
4924.00	49.15	Ave	320	1.4	V	-0.24	48.91	54.00	-5.09
7386.00	48.25	PK	201	1.3	H	2.84	51.09	74.00	-22.91
7386.00	39.15	Ave	201	1.3	H	2.84	41.99	54.00	-12.01
2331.40	45.82	PK	302	1.4	V	-13.19	32.63	74.00	-41.37
2331.40	37.67	Ave	302	1.4	V	-13.19	24.48	54.00	-29.52
2364.91	42.33	PK	107	1.1	H	-13.14	29.19	74.00	-44.81
2364.91	37.67	Ave	107	1.1	H	-13.14	24.53	54.00	-29.47
2490.00	44.88	PK	351	1.1	V	-13.08	31.80	74.00	-42.20
2490.00	38.26	Ave	351	1.1	V	-13.08	25.18	54.00	-28.82

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) low channel 2412MHz									
198.56	22.01	PK	195	1.2	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	153	2.0	V	11.26	30.83	40.00	-9.17
4824.00	50.92	PK	261	1.0	V	-1.06	49.86	74.00	-24.14
4824.00	49.49	Ave	261	1.0	V	-1.06	48.43	54.00	-5.57
7236.00	42.98	PK	56	1.5	H	1.33	44.31	74.00	-29.69
7236.00	39.18	Ave	56	1.5	H	1.33	40.51	54.00	-13.49
2321.07	45.20	PK	210	1.3	V	-13.19	32.01	74.00	-41.99
2321.07	38.61	Ave	210	1.3	V	-13.19	25.42	54.00	-28.58
2374.65	44.69	PK	44	1.2	H	-13.14	31.55	74.00	-42.45
2374.65	38.77	Ave	44	1.2	H	-13.14	25.63	54.00	-28.37
2489.35	42.77	PK	288	1.5	V	-13.08	29.69	74.00	-44.31
2489.35	37.20	Ave	288	1.5	V	-13.08	24.12	54.00	-29.88

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) middle channel 2437MHz									
198.56	22.01	PK	323	1.7	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	52	1.9	V	11.26	30.83	40.00	-9.17
4874.00	50.70	PK	209	1.8	V	-0.62	50.08	74.00	-23.92
4874.00	48.56	Ave	209	1.8	V	-0.62	47.94	54.00	-6.06
7311.00	46.76	PK	282	1.3	H	2.21	48.97	74.00	-25.03
7311.00	38.80	Ave	282	1.3	H	2.21	41.01	54.00	-12.99
2324.42	46.07	PK	314	1.7	V	-13.19	32.88	74.00	-41.12
2324.42	39.65	Ave	314	1.7	V	-13.19	26.46	54.00	-27.54
2364.96	44.94	PK	290	1.4	H	-13.14	31.80	74.00	-42.20
2364.96	38.59	Ave	290	1.4	H	-13.14	25.45	54.00	-28.55
2488.78	42.35	PK	344	1.1	V	-13.08	29.27	74.00	-44.73
2488.78	38.51	Ave	344	1.1	V	-13.08	25.43	54.00	-28.57

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) high channel 2462MHz									
198.56	22.01	PK	203	1.9	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	279	1.7	V	11.26	30.83	40.00	-9.17
4924.00	49.96	PK	333	1.3	V	-0.24	49.72	74.00	-24.28
4924.00	48.28	Ave	333	1.3	V	-0.24	48.04	54.00	-5.96
7386.00	48.82	PK	35	1.0	H	2.84	51.66	74.00	-22.34
7386.00	38.70	Ave	35	1.0	H	2.84	41.54	54.00	-12.46
2339.94	46.81	PK	132	1.1	V	-13.19	33.62	74.00	-40.38
2339.94	37.03	Ave	132	1.1	V	-13.19	23.84	54.00	-30.16
2367.89	44.40	PK	60	1.2	H	-13.14	31.26	74.00	-42.74
2367.89	38.05	Ave	60	1.2	H	-13.14	24.91	54.00	-29.09
2496.70	44.85	PK	341	1.7	V	-13.08	31.77	74.00	-42.23
2496.70	36.90	Ave	341	1.7	V	-13.08	23.82	54.00	-30.18

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT40) low channel 2422MHz									
198.56	22.01	PK	55	1.3	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	279	1.9	V	11.26	30.83	40.00	-9.17
4844.00	48.35	PK	187	1.2	V	-1.06	47.29	74.00	-26.71
4844.00	46.72	Ave	187	1.2	V	-1.06	45.66	54.00	-8.34
7266.00	42.33	PK	266	1.9	H	1.33	43.66	74.00	-30.34
7266.00	39.48	Ave	266	1.9	H	1.33	40.81	54.00	-13.19
2314.49	45.42	PK	31	1.4	V	-13.19	32.23	74.00	-41.77
2314.49	39.96	Ave	31	1.4	V	-13.19	26.77	54.00	-27.23
2379.88	42.68	PK	36	1.6	H	-13.14	29.54	74.00	-44.46
2379.88	38.07	Ave	36	1.6	H	-13.14	24.93	54.00	-29.07
2487.96	44.67	PK	118	1.7	V	-13.08	31.59	74.00	-42.41
2487.96	36.65	Ave	118	1.7	V	-13.08	23.57	54.00	-30.43

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT40) middle channel 2437MHz									
198.56	22.01	PK	29	1.2	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	251	1.3	V	11.26	30.83	40.00	-9.17
4874.00	47.61	PK	250	1.5	V	-0.62	46.99	74.00	-27.01
4874.00	46.53	Ave	250	1.5	V	-0.62	45.91	54.00	-8.09
7311.00	45.98	PK	158	1.4	H	2.21	48.19	74.00	-25.81
7311.00	39.23	Ave	158	1.4	H	2.21	41.44	54.00	-12.56
2330.25	46.74	PK	170	1.8	V	-13.19	33.55	74.00	-40.45
2330.25	37.42	Ave	170	1.8	V	-13.19	24.23	54.00	-29.77
2350.66	44.78	PK	83	1.0	H	-13.14	31.64	74.00	-42.36
2350.66	37.65	Ave	83	1.0	H	-13.14	24.51	54.00	-29.49
2490.63	44.15	PK	46	1.8	V	-13.08	31.07	74.00	-42.93
2490.63	37.28	Ave	46	1.8	V	-13.08	24.20	54.00	-29.80

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT40) high channel 2452MHz									
198.56	22.01	PK	10	1.6	H	11.26	33.27	40.00	-6.73
198.56	19.57	PK	354	1.7	V	11.26	30.83	40.00	-9.17
4904.00	46.77	PK	224	1.1	V	-0.24	46.53	74.00	-27.47
4904.00	47.00	Ave	224	1.1	V	-0.24	46.76	54.00	-7.24
7356.00	48.31	PK	223	1.0	H	2.84	51.15	74.00	-22.85
7356.00	39.50	Ave	223	1.0	H	2.84	42.34	54.00	-11.66
2333.54	46.47	PK	278	1.4	V	-13.19	33.28	74.00	-40.72
2333.54	37.42	Ave	278	1.4	V	-13.19	24.23	54.00	-29.77
2373.24	43.82	PK	131	1.5	H	-13.14	30.68	74.00	-43.32
2373.24	37.16	Ave	131	1.5	H	-13.14	24.02	54.00	-29.98
2488.34	43.43	PK	157	1.8	V	-13.08	30.35	74.00	-43.65
2488.34	36.43	Ave	157	1.8	V	-13.08	23.35	54.00	-30.65

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

8 Band Edge Measurement



Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	558074 D01 DTS Meas Guidance v03r02 06/05/2014
Test Mode:	Transmitting



8.1 Test Produce



1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



8.2 Test Result

Test result plots shown as follows:









9 6 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: 558074 D01 DTS Meas Guidance v03r02 06/05/2014


9.1 Test Procedure:



- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
- 2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz



9.2 Test Result:



Operation mode	Bandwidth (MHz)		
TX 11b	Channel 1	Channel 6	Channel 11
	11.03	11.03	11.03
TX 11g	Channel 1	Channel 6	Channel 11
	16.57	16.57	16.57
TX 11n HT20	Channel 1	Channel 6	Channel 11
	17.78	17.78	17.78
TX 11n HT40	Channel 3	Channel 6	Channel 9
	36.56	36.56	36.56



Test result plot as follows:


















10 Maximum Peak Output Power

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

558074 D01 DTS Meas Guidance v03r02 06/05/2014

10.1 Test Procedure:

558074 D01 DTS Meas Guidance v03r02 06/05/2014 section 9.1.2

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak, Set the span to fully encompass the DTS bandwidth.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.



10.2 Test Result:



Test mode :TX 11b		
10 Maximum Peak Output Power (dBm)		
2412MHz	2437MHz	2462MHz
9.36	9.74	9.66
Limit: 1W/30dBm		
1W/30dBm		



Test mode :TX 11g		
10 Maximum Peak Output Power (dBm)		
2412MHz	2437MHz	2462MHz
9.42	9.49	9.51
Limit		
1W/30dBm		



Test mode :TX 11n HT20		
10 Maximum Peak Output Power (dBm)		
2412MHz	2437MHz	2462MHz
9.43	9.50	9.54
Limit		
1W/30dBm		



Test mode : TX 11n HT40		
10 Maximum Peak Output Power (dBm)		
2422MHz	2437MHz	2452MHz
9.08	9.24	9.25
Limit		
1W/30dBm		















11 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: 558074 D01 DTS Meas Guidance v03r02 06/05/2014

11.1 Test Procedure:

558074 D01 DTS Meas Guidance v03r02 06/05/2014 section 10.2

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.



11.2 Test Result:



Test mode :TX 11b		
Power Spectral (dBm per 3kHz)		
2412MHz	2437MHz	2462MHz
-16.46	-16.39	-16.39
Limit: 1W/30dBm		
8dBm per 3kHz		



Test mode :TX 11g		
Power Spectral (dBm per 3kHz)		
2412MHz	2437MHz	2462MHz
-20.75	-20.35	-20.20
Limit		
8dBm per 3kHz		



Test mode :TX 11n HT20		
Power Spectral (dBm per 3kHz)		
2412MHz	2437MHz	2462MHz
-20.78	-20.41	-20.18
Limit		
8dBm per 3kHz		



Test mode : TX 11n HT40		
Power Spectral (dBm per 3kHz)		
2422MHz	2437MHz	2452MHz
-20.91	-20.82	-20.65
Limit		
8dBm per 3kHz		















12 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfil the requirement of this section.

13 RF Exposure

Test Requirement: FCC Part 1.1307

Evaluation Method: FCC Part 2.1091

13.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

13.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

13.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the gain of the used antenna, the RF power density can be obtained

Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	9.74	9.419	0.00187	1

14 Photographs – Model BM15AP2 Test Setup

14.1 Conducted Emission




14.2 Radiated Emission


Test frequency: 12MHz~ 30MHz



Test frequency from 30MHz to 1GHz



Test frequency: 1GHz~25GHz



15 Photographs - Constructional Details

15.1 Model BM15AP2 –External View

















15.2 Model BM15AP2 – Internal View


















=====End of Report=====