

RF exposure report

For

Colmei Technology International Limited

2nd Floor, 8th Block,Dongfangming Industry park,33rd Baoan District,Shenzhen

FCC ID: 2ACNGQA910

(M/N):

QA910,

Neo 9,QA911,QA912,QA913,QA914,QA915,QA916

June 26, 2014

This Report Concerns:	Equipment Type:
Original Report	TABLET PC
Test Engineer:	Lisa Chen <i>Lisa Chen</i>
Report No.:	BSL13071012d
Receive EUT Date/Test Date:	June 12, 2014 / June 12- June 26, 2014
Reviewed By:	Sky Zhang <i>Sky Zhang</i>
Prepared By:	BSL Testing Co.,LTD. NO. 24, ZH Park, Nantou, Shenzhen, 518000 China Tel: 86- 755-26508703 Fax: 86- 755-26508703

FCC §15.247 (i) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v05

Result

According to FCC KDB 447498 D01 General RF Exposure Guidance v05 generic portable criteria

The distance between antenna and test point is 5 mm
The max output power:9.45 dBm(8.81 mW)

According to the Appendix A of KDB 447498, the exclusion thresholds for 2450 MHz is 10 mW.

Conclusion:

The time-averaged output power is 8.81 mW <the exclusion thresholds 10 mW, so stand-alone SAR evaluation is not required.