



June 24, 2019

TUV SUD BABT  
Octagon House, Concorde Way  
Segensworth Rd N, Fareham  
PO15 5RL

Attention: Director of Certification

**RE: Analysis of RF Exposure for Portable and Mobile use per KDB 447498 D01 Mobile Portable RF Exposure v06 and RSS-102 Issue 5 March 2015.**

FCC ID: 2ACR3-T100

IC: 12047A-T100

**1. Limits:**

Limits for General Population/Uncontrolled Exposure (Title 47 Subpart J §2.1091 and KDB 447498 D01 referring to limits under §1.1310)

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Electric Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f/1500	30
1500 - 100,000	-	-	1.0	30

*f = frequency in MHz*

*\*Plane-wave equivalent power density*

Limits for Devices Used by the General Public (Uncontrolled Environment (RSS-102 Issue 5 March 2015))

Frequency Range (MHz)	Electric Field Strength (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003 - 10 <sup>21</sup>	83	90	-	Instantaneous
0.1 - 10	-	0.73/f	-	6**
1.1 - 10	87/f <sup>0.5</sup>	-	-	6**
10 - 20	27.46	0.0728	2	6
20 - 48	-58.07/f <sup>0.25</sup>	0.1540/f <sup>0.25</sup>	8.944/f <sup>0.5</sup>	6
48 - 300	22.06	0.05852	1.291	6



300 - 6000	$3.142 f^{0.3417}$	$0.008335 f^{0.3417}$	$0.02619 f^{0.6834}$	6
6000 - 15000	61.4	0.163	10	6
15000 - 150000	61.4	0.163	10	$616000/f^{1.2}$
150000 - 300000	$0.158f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	$6.67 \times 10^{-5} f$	$616000/f^{1.2}$

$f$  is frequency in MHz

\*Based on nerve stimulation (NS)

\*\* Based on specific absorption rate (SAR)

## 2. Mobile MPE Calculation Summary using a 20cm separation distance (worst case channel):

Model	Field Strength (dBμV/m)	Radiated Output Power (mW)	Power Density (mW/cm <sup>2</sup> )
T100 @ 24GHz	112.84 @ 3 meters	0.0007432	0.00000015

## 3. Mobile MPE Calculation using a 20cm separation distance:

Using Power Density formula:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to isotropic

R = distance to the center of radiation of the antenna

Measured Field Strength --Radiated:	112.84	(dBuV/m)
Maximum peak output power --Radiated:	57.692	(mW)
Antenna gain(typical):	0.00	(dBi)
Maximum antenna gain:	1	(numeric)
Prediction distance:	20.00	(cm)
Prediction frequency:	24134.28	(MHz)
Applied Limit:	1	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	0.01147761	(mW/cm <sup>2</sup> )
Margin of Compliance:	-19.40	(dB)



Sincerely,

A handwritten signature in black ink that reads "Sandipan Basu".

Sandipan Basu

---

Name

Authorized Signatory

Title: EMC/Wireless Test Engineer