

## FCC PART 15.247



## TEST REPORT

For

### Yuneec Technology Co., Limited

Unit 2301, 23/F, 9 Chong Yip Street, Kwun Tong, Kowloon, Hong Kong, China

**FCC ID: 2ACS5-YUNMGA**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Mantis G
<b>Test Engineer:</b> Max Min	
<b>Report Number:</b> RSHA181204001-00A	
<b>Report Date:</b> 2019-01-02	
<b>Reviewed By:</b> Oscar Ye RF Leader	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
OBJECTIVE .....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY .....	3
MEASUREMENT UNCERTAINTY .....	4
TEST FACILITY .....	4
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
DESCRIPTION OF TEST CONFIGURATION .....	5
EQUIPMENT MODIFICATIONS .....	5
EUT EXERCISE SOFTWARE .....	5
SUPPORT EQUIPMENT LIST AND DETAILS .....	10
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP .....	10
<b>SUMMARY OF TEST RESULTS .....</b>	<b>12</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>13</b>
<b>FCC §1.1310 &amp; §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....</b>	<b>14</b>
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>16</b>
APPLICABLE STANDARD .....	16
ANTENNA CONNECTOR CONSTRUCTION .....	16
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>17</b>
APPLICABLE STANDARD .....	17
EUT SETUP .....	17
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE .....	18
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	18
TEST RESULTS SUMMARY .....	18
TEST DATA .....	19
<b>FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH .....</b>	<b>43</b>
APPLICABLE STANDARD .....	43
TEST PROCEDURE .....	43
TEST DATA .....	43
<b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....</b>	<b>55</b>
APPLICABLE STANDARD .....	55
TEST PROCEDURE .....	55
TEST DATA .....	55
<b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>57</b>
APPLICABLE STANDARD .....	57
TEST PROCEDURE .....	57
TEST DATA .....	57
<b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>	<b>64</b>
APPLICABLE STANDARD .....	64
TEST PROCEDURE .....	64
TEST DATA .....	64

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Applicant	Yunee Technology Co., Limited
Test Model	YUNMGA
Product Type	Mantis G
Dimension	168mm(L)* 96 mm(W)* 58 mm(H)
Power Supply	DC 11.4V from battery

*\*All measurement and test data in this report was gathered from production sample serial number: 20181204001. (Assigned by the BACL. The EUT supplied by the applicant was received on 2018-12-04.*

### Objective

This report is prepared on behalf of Yunee Technology Co., Limited in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15.407 NII submissions with FCC ID: 2ACS5-YUNMGA.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC 558074 D01 15.247 Meas Guidance v05.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

**Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

Test channel list is as below:

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11;

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

### Equipment Modifications

No modification was made to the EUT tested.

### EUT Exercise Software


RF test tool: MPTool

Pre-scan with all the data rates, and the worst case was performed as below:


Mode	Data Rate	Power Level	
		Chain 0	Chain 1
802.11b	1 Mbps	35	38
802.11g	6 Mbps	45	48
802.11n-HT20	MCS0	45	48

**Duty Cycle(Chain 0):**


**802.11b Mode Middle Channel**



**802.11g Mode Middle Channel**



### 802.11n-HT20 Mode Middle Channel




Mode	Duty Cycle (%)	T(us)	1/T(kHz)	10log(1/x)
802.11b	100	/	/	0
802.11g	100	/	/	0
802.11n-HT20	100	/	/	0


**Note:** “x” means the Duty Cycle.

**Duty Cycle(Chain 1):**

**802.11b Mode Middle Channel**




**802.11g Mode Middle Channel**





### 802.11n-HT20 Mode Middle Channel



Mode	Duty Cycle (%)	T(us)	1/T(kHz)	10log(1/x)
802.11b	100	/	/	0
802.11g	100	/	/	0
802.11n-HT20	100	/	/	0

**Note:** “x” means the Duty Cycle.

**Support Equipment List and Details**


Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
DELL	Adapter	LA65NS0-00	DF263

**External I/O Cable**


Cable Description	Length (m)	From Port	To
Data Cable	0.5	EUT	Notebook

**Block Diagram of Test Setup**

For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable (See Note 1)
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Note 1: The EUT is powered by battery.

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test (Chamber 1#)</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2018-11-12	2019-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2018-08-15	2019-08-14
<b>Radiated Emission Test (Chamber 2#)</b>					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2018-08-27	2019-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
A.H.Systems, inc	Amplifier	2641-1	466	2018-09-11	2019-09-10
EM Electronics Corporation	Amplifier	EM18G40G	060726	2018-03-22	2019-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2018-08-05	2019-08-04
Narda	Attenuator	10dB	010	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2018-08-15	2019-08-14
<b>RF Conducted Test</b>					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2018-11-12	2019-11-11
Agilent	Power Meter	N1912A	MY5000492	2018-11-18	2019-11-17
Agilent	Power Sensor	N1921A	MY54210024	2018-11-18	2019-11-17
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
Yuneec	RF Cable	YuneecC01	C01	Each Time	/

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## **FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

### **Applicable Standard**

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

**Calculated Data:****For worst case:**

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412~2462	3.00	2.00	18.00	63.10	20	0.0250	1.00
802.11g		3.00	2.00	22.00	158.49	20	0.0629	1.00
802.11n-HT20		3.00	2.00	24.00	251.19	20	0.0997	1.00

Mode	Frequency (MHz)	Antenna Gain		Tune-up Conducted output power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
802.11a	5150-5250	3.00	2.00	25.00	316.23	20	0.1258	1.0
802.11n-HT20		3.00	2.00	28.00	630.96	20	0.2510	1.0
802.11a	5725-5850	3.00	2.00	26.00	398.11	20	0.1580	1.0
802.11n-HT20		3.00	2.00	28.00	630.96	20	0.2504	1.0

Note:

- (1) The Tune-up output power was declared by the Manufacturer.
- (2) 2.4GWi-Fi and 5GWi-Fi cannot transmit simultaneously.

**Conclusion:** The device meets FCC MPE at 20 cm distance.

## **FCC §15.203 - ANTENNA REQUIREMENT**

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
  - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **Antenna Connector Construction**

The EUT has two PCB antennas for Wi-Fi which was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.

ANT	Antenna Type	Max. Antenna Gain
0	PCB	3.0 dBi
1	PCB	3.0 dBi

**Result:** Compliant.




## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

### EUT Setup

**Below 1 GHz:**



**Above 1GHz:**



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

### EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

### Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30MHz - 1GHz, peak and Average detection mode for frequencies above 1 GHz.

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V /m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V /m)}$$

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

**Test Data****Environmental Conditions**


<b>Temperature:</b>	23.5 °C
<b>Relative Humidity:</b>	50 %
<b>ATM Pressure:</b>	101.2 kPa

The testing was performed by Max Min from 2018-12-10 to 2018-12-28.

EUT operation mode: Transmitting

**Spurious Emission Test:****30MHz-1GHz:**

Pre-scan with 802.11b, 802.11g and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case **middle channel of 802.11n-HT20 mode in Z-axis of orientation** was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
44.101450	31.87	101.0	V	19.0	-13.5	40.00	8.13
54.202100	32.38	101.0	V	19.0	-17.7	40.00	7.62
111.582200	39.45	199.0	H	331.0	-12.7	43.50	4.05
234.142250	39.85	199.0	H	331.0	-12.2	46.00	6.15
355.422950	38.44	101.0	H	267.0	-9.2	46.00	7.56
364.428800	39.11	101.0	H	267.0	-9.0	46.00	6.89

**1GHz-18GHz:****802.11b Mode(Worst case: Chain 0):**


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4 - 2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)  
 Corrected Amplitude (dB $\mu$ V /m) = Corrected Factor (dB/m) + Reading (dB $\mu$ V)  
 Margin (dB) = Limit (dB $\mu$ V/m) – Corrected Amplitude (dB $\mu$ V /m)

**Low Channel: 2412MHz**


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	MaxPeak (dB $\mu$ V /m)	Average (dB $\mu$ V /m)	Height (cm)	Polar (H/V)				
1197.200000	---	29.66	100.0	H	349.0	-9.3	54.00	24.34
1197.200000	39.59	---	100.0	H	349.0	-9.3	74.00	34.41
3070.600000	---	30.86	100.0	V	183.0	-1.5	54.00	23.14
3070.600000	40.38	---	100.0	V	183.0	-1.5	74.00	33.62
4824.000000	---	35.40	100.0	V	4.0	1.9	54.00	18.60
4824.000000	45.31	---	100.0	V	4.0	1.9	74.00	28.69
7236.000000	---	38.59	100.0	V	86.0	9.0	54.00	15.41
7236.000000	46.83	---	100.0	V	86.0	9.0	74.00	27.17
11016.400000	---	41.27	200.0	V	78.0	13.5	54.00	12.73
11016.400000	52.79	---	200.0	V	78.0	13.5	74.00	21.21
17704.200000	---	45.80	200.0	H	359.0	17.4	54.00	8.20
17704.200000	56.62	---	200.0	H	359.0	17.4	74.00	17.38

**Middle Channel: 2437MHz**


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	MaxPeak (dB $\mu$ V /m)	Average (dB $\mu$ V /m)	Height (cm)	Polar (H/V)				
1197.200000	---	29.39	150.0	H	354.0	-9.3	54.00	24.61
1197.200000	39.48	---	150.0	H	354.0	-9.3	74.00	34.52
3070.600000	---	31.57	200.0	V	191.0	-1.5	54.00	22.43
3070.600000	40.06	---	200.0	V	191.0	-1.5	74.00	33.94
4874.000000	---	33.93	150.0	V	217.0	1.9	54.00	20.07
4874.000000	42.82	---	150.0	V	217.0	1.9	74.00	31.18
7311.000000	---	38.19	100.0	V	7.0	9.2	54.00	15.81
7311.000000	47.06	---	100.0	V	7.0	9.2	74.00	26.94
11223.800000	---	42.30	150.0	H	95.0	13.2	54.00	11.70
11223.800000	52.43	---	150.0	H	95.0	13.2	74.00	21.57
17571.600000	---	46.44	100.0	H	154.0	17.3	54.00	7.56
17571.600000	56.80	---	100.0	H	154.0	17.3	74.00	17.20

**High Channel: 2462MHz**

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	MaxPeak (dB $\mu$ V /m)	Average (dB $\mu$ V /m)	Height (cm)	Polar (H/V)				
1197.200000	---	28.54	200.0	V	244.0	-9.3	54.00	25.46
1197.200000	37.84	---	200.0	V	244.0	-9.3	74.00	36.16
3070.600000	---	31.14	200.0	V	169.0	-1.5	54.00	22.86
3070.600000	40.48	---	200.0	V	169.0	-1.5	74.00	33.52
4924.000000	---	33.37	200.0	V	84.0	2.0	54.00	20.63
4924.000000	41.41	---	200.0	V	84.0	2.0	74.00	32.59
7386.000000	---	38.63	150.0	V	260.0	9.4	54.00	15.37
7386.000000	47.38	---	150.0	V	260.0	9.4	74.00	26.62
11873.200000	---	42.09	150.0	V	217.0	13.2	54.00	11.91
11873.200000	52.49	---	150.0	V	217.0	13.2	74.00	21.51
17513.800000	---	46.08	200.0	H	100.0	17.2	54.00	7.92
17513.800000	56.98	---	200.0	H	100.0	17.2	74.00	17.02

**802.11g Mode(Worst case: Chain 1):**


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4 - 2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)  
 Corrected Amplitude (dB $\mu$ V /m) = Corrected Factor (dB/m) + Reading (dB $\mu$ V)  
 Margin (dB) = Limit (dB $\mu$ V/m) – Corrected Amplitude (dB $\mu$ V /m)

**Low Channel: 2412MHz**


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	MaxPeak (dB $\mu$ V /m)	Average (dB $\mu$ V /m)	Height (cm)	Polar (H/V)				
1200.600000	36.79	---	150.0	H	224.0	-9.3	74.00	37.21
1200.600000	---	27.32	150.0	H	224.0	-9.3	54.00	26.68
3070.600000	39.54	---	150.0	V	135.0	-1.5	74.00	34.46
3070.600000	---	30.91	150.0	V	135.0	-1.5	54.00	23.09
4824.000000	---	33.61	150.0	V	135.0	1.9	54.00	20.39
4824.000000	41.28	---	150.0	V	135.0	1.9	74.00	32.72
7236.000000	46.14	---	150.0	V	1.0	9.0	74.00	27.86
7236.000000	---	37.14	150.0	V	1.0	9.0	54.00	16.86
11251.000000	52.44	---	150.0	V	135.0	13.2	74.00	21.56
11251.000000	---	42.34	150.0	V	135.0	13.2	54.00	11.66
17731.400000	---	44.47	150.0	V	300.0	17.4	54.00	9.53
17731.400000	56.04	---	150.0	V	300.0	17.4	74.00	17.96

**Middle Channel: 2437MHz**

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	MaxPeak (dB $\mu$ V /m)	Average (dB $\mu$ V /m)	Height (cm)	Polar (H/V)				
1200.600000	36.70	---	150.0	H	230.0	-9.3	74.00	37.30
1200.600000	---	27.69	150.0	H	230.0	-9.3	54.00	26.31
3070.600000	39.48	---	150.0	V	132.0	-1.5	74.00	34.52
3070.600000	---	30.83	150.0	V	132.0	-1.5	54.00	23.17
4874.000000	42.07	---	150.0	H	43.0	1.9	74.00	31.93
4874.000000	---	31.74	150.0	H	43.0	1.9	54.00	22.26
7311.000000	46.94	---	150.0	H	18.0	9.2	74.00	27.06
7311.000000	---	37.96	150.0	H	18.0	9.2	54.00	16.04
10312.600000	51.59	---	150.0	H	32.0	12.7	74.00	22.41
10312.600000	---	41.00	150.0	H	32.0	12.7	54.00	13.00
17561.400000	---	46.42	150.0	V	218.0	17.3	54.00	7.58
17561.400000	57.80	---	150.0	V	218.0	17.3	74.00	16.20



**High Channel: 2462MHz**

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	MaxPeak (dB $\mu$ V /m)	Average (dB $\mu$ V /m)	Height (cm)	Polar (H/V)				
1204.000000	38.26	---	150.0	H	219.0	-9.3	74.00	35.74
1204.000000	---	28.00	150.0	H	219.0	-9.3	54.00	26.00
3070.600000	38.99	---	150.0	V	313.0	-1.5	74.00	35.01
3070.600000	---	29.71	150.0	V	313.0	-1.5	54.00	24.29
4924.000000	41.37	---	150.0	V	249.0	2.0	74.00	32.63
4924.000000	---	32.01	150.0	V	249.0	2.0	54.00	21.99
7386.000000	47.82	---	150.0	V	112.0	9.4	74.00	26.18
7386.000000	---	37.68	150.0	V	112.0	9.4	54.00	16.32
10724.000000	51.85	---	150.0	V	206.0	13.1	74.00	22.15
10724.000000	---	41.24	150.0	V	206.0	13.1	54.00	12.76
17592.000000	54.46	---	150.0	H	283.0	17.3	74.00	19.54
17592.000000	---	47.57	150.0	H	283.0	17.3	54.00	6.43

**802.11n-HT20 Mode(Chain0+Chain1):**


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4 - 2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)  
 Corrected Amplitude (dBμV /m) = Corrected Factor (dB/m) + Reading (dBμV)  
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV /m)

**Low Channel: 2412MHz**


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1197.200000	---	27.10	150.0	H	239.0	-9.3	54.00	26.90
1197.200000	36.95	---	150.0	H	239.0	-9.3	74.00	37.05
3250.800000	---	30.52	150.0	V	164.0	-1.2	54.00	23.48
3250.800000	40.67	---	150.0	V	164.0	-1.2	74.00	33.33
4824.000000	---	32.91	150.0	V	218.0	1.9	54.00	21.09
4824.000000	39.82	---	150.0	V	218.0	1.9	74.00	34.18
7236.000000	---	37.57	150.0	H	250.0	9.0	54.00	16.43
7236.000000	46.80	---	150.0	H	250.0	9.0	74.00	27.20
10666.200000	---	40.88	150.0	H	202.0	13.0	54.00	13.12
10666.200000	53.18	---	150.0	H	202.0	13.0	74.00	20.82
17649.800000	---	46.54	150.0	V	359.0	17.3	54.00	7.46
17649.800000	56.69	---	150.0	V	359.0	17.3	74.00	17.31

**Middle Channel: 2437MHz**


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	MaxPeak (dB $\mu$ V /m)	Average (dB $\mu$ V /m)	Height (cm)	Polar (H/V)				
1591.600000	39.63	---	150.0	V	153.0	-7.2	74.00	34.37
1591.600000	---	28.77	150.0	V	153.0	-7.2	54.00	25.23
3043.400000	---	28.75	150.0	H	74.0	-1.6	54.00	25.25
3043.400000	39.50	---	150.0	H	74.0	-1.6	74.00	34.50
4874.000000	---	32.52	150.0	V	243.0	1.9	54.00	21.48
4874.000000	42.28	---	150.0	V	243.0	1.9	74.00	31.72
7311.000000	---	37.88	150.0	V	106.0	9.2	54.00	16.12
7311.000000	47.77	---	150.0	V	106.0	9.2	74.00	26.23
11009.600000	---	40.86	150.0	H	106.0	13.5	54.00	13.14
11009.600000	51.38	---	150.0	H	106.0	13.5	74.00	22.62
17612.400000	---	46.93	150.0	V	0.0	17.3	54.00	7.07
17612.400000	57.29	---	150.0	V	0.0	17.3	74.00	16.71

**High Channel: 2462MHz**


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1200.600000	---	28.19	150.0	H	228.0	-9.3	54.00	25.81
1200.600000	37.05	---	150.0	H	228.0	-9.3	74.00	36.95
3070.600000	---	30.73	150.0	V	128.0	-1.5	54.00	23.27
3070.600000	39.53	---	150.0	V	128.0	-1.5	74.00	34.47
4924.000000	---	32.96	150.0	V	224.0	2.0	54.00	21.04
4924.000000	41.99	---	150.0	V	224.0	2.0	74.00	32.01
7386.000000	---	37.63	150.0	V	25.0	9.4	54.00	16.37
7386.000000	46.88	---	150.0	V	25.0	9.4	74.00	27.12
10707.000000	---	42.20	150.0	V	359.0	13.0	54.00	11.80
10707.000000	51.46	---	150.0	V	359.0	13.0	74.00	22.54
17510.400000	---	46.22	150.0	H	0.0	17.2	54.00	7.78
17510.400000	56.87	---	150.0	H	0.0	17.2	74.00	17.13

**18GHz-25GHz:**

Pre-scan with 802.11b, 802.11g and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case **middle channel of 802.11n-HT20 mode in Z-axis of orientation** was recorded

**Horizontal**

Date: 28.DEC.2018 12:59:40

**Vertical**

Date: 28.DEC.2018 14:24:18

**Fundamental Test & Restricted Bands Emissions Test:**

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dB $\mu$ V /m) = Corrected Factor (dB/m) + Reading (dB $\mu$ V)Margin (dB) = Limit (dB $\mu$ V/m) – Corrected Amplitude (dB $\mu$ V /m)**802.11b Mode (Chain 0 worst case):** (Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2412.000000	105.28	---	100.0	H	343.0	6.1	/	/
2412.000000	---	102.24	100.0	H	343.0	6.1	/	/
2412.000000	102.97	---	150.0	V	240.0	6.1	/	/
2412.000000	---	100.01	150.0	V	240.0	6.1	/	/
2390.000000	---	41.14	200.0	H	327.0	6.0	54.00	12.86
2390.000000	50.61	---	200.0	H	327.0	6.0	74.00	23.39
Middle Channel: 2437MHz								
2437.000000	105.03	---	100.0	H	25.0	6.1	/	/
2437.000000	---	102.18	100.0	H	25.0	6.1	/	/
2437.000000	102.73	---	150.0	V	181.0	6.1	/	/
2437.000000	---	99.91	150.0	V	181.0	6.1	/	/
High Channel: 2462MHz								
2462.000000	105.25	---	200.0	H	84.0	6.2	/	/
2462.000000	---	102.04	200.0	H	84.0	6.2	/	/
2462.000000	102.75	---	100.0	V	312.0	6.2	/	/
2462.000000	---	99.60	100.0	V	312.0	6.2	/	/
2483.500000	49.18	---	100.0	H	174.0	6.3	74.00	24.82
2483.500000	---	40.84	100.0	H	174.0	6.3	54.00	13.16

**802.11g Mode (Chain 1 worst case):** (Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2412.000000	103.59	---	200.0	H	356.0	6.1	/	/
2412.000000	---	100.30	200.0	H	356.0	6.1	/	/
2412.000000	101.25	---	150.0	V	23.0	6.1	/	/
2412.000000	---	98.06	150.0	V	23.0	6.1	/	/
2390.000000	---	44.70	250.0	H	87.0	6.0	54.00	9.30
2390.000000	55.95	---	250.0	H	87.0	6.0	74.00	18.05
Middle Channel: 2437MHz								
2437.000000	103.66	---	100.0	H	268.0	6.1	/	/
2437.000000	---	100.38	100.0	H	268.0	6.1	/	/
2437.000000	101.24	---	250.0	V	257.0	6.1	/	/
2437.000000	---	98.28	250.0	V	257.0	6.1	/	/
High Channel: 2462MHz								
2462.000000	103.64	---	100.0	H	202.0	6.2	/	/
2462.000000	---	100.83	100.0	H	202.0	6.2	/	/
2462.000000	101.57	---	150.0	V	243.0	6.2	/	/
2462.000000	---	98.47	150.0	V	243.0	6.2	/	/
2483.500000	52.40	---	100.0	H	29.0	6.3	74.00	21.60
2483.500000	---	42.48	100.0	H	29.0	6.3	54.00	11.52


**802.11n-HT20 Mode (Chain0+Chain1):** (Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2412.000000	102.60	---	150.0	H	219.0	6.1	/	/
2412.000000	---	99.34	150.0	H	219.0	6.1	/	/
2412.000000	100.35	---	100.0	V	23.0	6.1	/	/
2412.000000	---	97.13	100.0	V	23.0	6.1	/	/
2390.000000	---	49.24	150.0	H	211.0	6.0	54.00	4.76
2390.000000	61.21	---	150.0	H	211.0	6.0	74.00	12.79
Middle Channel: 2437MHz								
2437.000000	103.48	---	100.0	H	59.0	6.1	/	/
2437.000000	---	100.36	100.0	H	59.0	6.1	/	/
2437.000000	101.01	---	150.0	V	44.0	6.1	/	/
2437.000000	---	98.29	150.0	V	44.0	6.1	/	/
High Channel: 2462MHz								
2462.000000	103.68	---	200.0	H	352.0	6.2	/	/
2462.000000	---	100.87	200.0	H	352.0	6.2	/	/
2462.000000	101.25	---	150.0	V	121.0	6.2	/	/
2462.000000	---	98.81	150.0	V	121.0	6.2	/	/
2483.500000	52.49	---	100.0	H	42.0	6.3	74.00	21.51
2483.500000	---	41.50	100.0	H	42.0	6.3	54.00	12.50




# Conducted Spurious Emissions at Antenna Port


## Chain0: 802.11b Mode Low Channel




## Chain0: 802.11b Mode Middle Channel





### Chain0: 802.11b Mode High Channel




### Chain0: 802.11g Mode Low Channel




**Chain0: 802.11g Mode Middle Channel****Chain0: 802.11g Mode High Channel**


### Chain0: 802.11n-HT20 Mode Low Channel



### Chain0: 802.11n-HT20 Mode Middle Channel




Chain0: 802.11n-HT20 Mode High Channel




# Conducted Spurious Emissions at Antenna Port


## Chain1: 802.11b Mode Low Channel




## Chain1: 802.11b Mode Middle Channel




### Chain1: 802.11b Mode High Channel




### Chain1: 802.11g Mode Low Channel



### Chain1: 802.11g Mode Middle Channel




### Chain1: 802.11g Mode High Channel







### Chain1: 802.11n-HT20 Mode Low Channel



### Chain1: 802.11n-HT20 Mode Middle Channel



Chain1: 802.11n-HT20 Mode High Channel




**FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH****Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

**Test Procedure**

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3 * \text{RBW}$ .
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**Test Data****Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa


*The testing was performed by Max Min on 2018-12-10.*

*EUT operation mode: Transmitting*


**Test Result:** Pass

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)		Limit (MHz)
		Chain 0	Chain 1	
802.11b Mode				
Low	2412	9.98	10.16	≥ 0.5
Middle	2437	9.98	10.16	≥ 0.5
High	2462	9.98	10.16	≥ 0.5
802.11g Mode				
Low	2412	16.59	16.59	≥ 0.5
Middle	2437	16.59	16.59	≥ 0.5
High	2462	16.59	16.59	≥ 0.5
802.11n-HT20 Mode				
Low	2412	17.80	17.86	≥ 0.5
Middle	2437	17.80	17.80	≥ 0.5
High	2462	17.80	17.80	≥ 0.5


### Chain0: 802.11b Mode Low Channel




### Chain0: 802.11b Mode Middle Channel




### Chain0: 802.11b Mode High Channel




### Chain0: 802.11g Mode Low Channel




### Chain0: 802.11g Mode Middle Channel




### Chain0: 802.11g Mode High Channel



### Chain0: 802.11n-HT20 Mode Low Channel




### Chain0: 802.11n-HT20 Mode Middle Channel







Chain0: 802.11n-HT20 Mode High Channel



### Chain1: 802.11b Mode Low Channel



### Chain1: 802.11b Mode Middle Channel



Delta 1 [T1] -0.42 dB  
 Ref Lvl 16.5 dBm  
 RBW 100 kHz  
 VBW 300 kHz  
 RF Att 30 dB  
 Unit dBm  
 SWT 7.5 ms

6.5 dB Offset  
 D1 2.84 dBm  
 D2 -3.16 dBm  
 1MAX  
 10.16032064 MHz  
 2.45697996 GHz  
 -2.68 dBm  
 -0.42 dB  
 10.16032064 MHz  
 1MAX

Center 2.462 GHz  
 3 MHz/  
 Span 30 MHz

Date: 10.DEC.2018 20:02:01

Delta 1 [T1]

Ref Lvl 16.5 dBm

RBW 100 kHz

RF Att 30 dB

16.59318637 MHz

SWT 7.5 ms

Unit dBm

6.5 dB Offset

▼1 [T1] -7.49 dBm

▲1 [T1] 0.40 dB

D1 -1.55 dBm

D2 -7.55 dBm

16.59318637 MHz

1MAX


Center 2.412 GHz

3 MHz/


Span 30 MHz

Date: 10.DEC.2018 19:43:49


### Chain1: 802.11g Mode Middle Channel




### Chain1: 802.11g Mode High Channel




### Chain1: 802.11n-HT20 Mode Low Channel



### Chain1: 802.11n-HT20 Mode Middle Channel



### Chain1: 802.11n-HT20 Mode High Channel



## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

According to ANSI C63.10-2013 sub-clause 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



### Test Data

#### Environmental Conditions

Temperature:	23.8°C
Relative Humidity:	54 %
ATM Pressure:	101.2 kPa

*The testing was performed by Max Min from 2018-12-10 to 2018-12-11.*

*EUT operation mode: Transmitting*

Test mode	Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)			Limit (dBm)	Result
			Chain0	Chain1	Total		
802.11b	Low	2412	17.64	17.32	/	30	Pass
	Middle	2437	17.14	17.51	/	30	Pass
	High	2462	16.66	17.16	/	30	Pass
802.11g	Low	2412	20.25	21.18	/	30	Pass
	Middle	2437	20.27	21.26	/	30	Pass
	High	2462	19.88	20.76	/	30	Pass
802.11n-HT20	Low	2412	20.29	21.21	23.78	30	Pass
	Middle	2437	20.30	21.46	23.93	30	Pass
	High	2462	19.88	21.05	23.51	30	Pass

Note: The total output power =  $10 \log_{10} (10^{\text{Chain 0/10}} + 10^{\text{Chain 1/10}})$

The maximum antenna gain is 3dBi, the device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for  $N_{\text{ANT}} \leq 4$ ;

So:

Directional gain =  $G_{\text{ANT}} + \text{Array Gain} = 3\text{dBi} < 6\text{dBi}$



**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE****Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**Test Procedure**

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**


<b>Temperature:</b>	24.3 °C
<b>Relative Humidity:</b>	50 %
<b>ATM Pressure:</b>	101.3 kPa

*The testing was performed by Max Min on 2018-12-10.*

*EUT operation mode: Transmitting*

**Test Result:** Compliance


### Chain0: 802.11b Mode Left Side




### Chain0: 802.11b Mode Right Side




### Chain0: 802.11g Mode Left Side




### Chain0: 802.11g Mode Right Side




### Chain0: 802.11n-HT20 Mode Left Side




### Chain0: 802.11n-HT20 Mode Right Side




### Chain1: 802.11b Mode Left Side




### Chain1: 802.11b Mode Right Side




### Chain1: 802.11g Mode Left Side




### Chain1: 802.11g Mode Right Side



### Chain1: 802.11n-HT20 Mode Left Side



### Chain1: 802.11n-HT20 Mode Right Side



## **FCC §15.247(e) - POWER SPECTRAL DENSITY**

### **Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### **Test Procedure**

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
2. Set the VBW  $\geq 3 \times \text{RBW}$ .
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	24.1 °C-24.5°C
<b>Relative Humidity:</b>	50%-52%
<b>ATM Pressure:</b>	101.1 kPa-101.3 kPa

*The testing was performed by Max Min from 2018-12-10 to 2018-12-11.*

*EUT operation mode: Transmitting*

**Test Result:** Pass



Channel	Frequency (MHz)	PSD (dBm/3kHz)			Limit (dBm/3kHz)
		Chain0	Chain1	Total	
802.11b mode					
Low	2412	-17.95	-16.29	/	≤8
Middle	2437	-17.88	-16.02	/	≤8
High	2462	-18.05	-16.46	/	≤8
802.11g mode					
Low	2412	-17.71	-16.02	/	≤8
Middle	2437	-17.71	-15.73	/	≤8
High	2462	-17.84	-15.71	/	≤8
802.11n-HT20 mode					
Low	2412	-17.02	-14.99	-12.88	≤8
Middle	2437	-16.71	-15.69	-13.16	≤8
High	2462	-16.61	-15.36	-12.93	≤8

Note:

The total PSD =  $10 \log_{10} (10^{\text{Chain 0/10}} + 10^{\text{Chain 1/10}})$


The maximum antenna gain is 3dBi. The device employed Cyclic Delay Diversity (CDD) for 802.11MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:

Array Gain =  $10 \log(N_{\text{ANT}}/N_{\text{SS}})$  dB.


So:

Directional gain = GANT + Array Gain =  $3 + 10 \log(2/1) = 6$  dBi


### Chain0: 802.11b Mode Low Channel




### Chain0: 802.11b Mode Middle Channel




### Chain0: 802.11b Mode High Channel




### Chain0: 802.11g Mode Low Channel




### Chain0: 802.11g Mode Middle Channel




### Chain0: 802.11g Mode High Channel




### Chain0: 802.11n-HT20 Mode Low Channel




### Chain0: 802.11n-HT20 Mode Middle Channel




Chain0: 802.11n-HT20 Mode High Channel




### Chain1: 802.11b Mode Low Channel




### Chain1: 802.11b Mode Middle Channel



### Chain1: 802.11b Mode High Channel




### Chain1: 802.11g Mode Low Channel







### Chain1: 802.11g Mode Middle Channel




### Chain1: 802.11g Mode High Channel




### Chain1: 802.11n-HT20 Mode Low Channel



### Chain1: 802.11n-HT20 Mode Middle Channel



**Chain1: 802.11n-HT20 Mode High Channel**



\*\*\*\*\* END OF REPORT \*\*\*\*\*