FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Report No.: RSHA181204001-00A

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure								
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)				
0.3-1.34	614	1.63	*(100)	30				
1.34-30	824/f	2.19/f	*(180/f ²)	30				
30-300	27.5	0.073	0.2	30				
300-1500	/	/	f/1500	30				
1500-100,000	/	/	1.0	30				

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2 = power density (in appropriate units, e.g. mW/cm^2);$

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

FCC Part 15.247 Page 14 of 75

Calculated Data:

For worst case:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance	Power Density	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm ²)	, (, , , , , , , , , , , , , , , , , ,
802.11b	2412~2462	3.00	2.00	18.00	63.10	20	0.0250	1.00
802.11g		3.00	2.00	22.00	158.49	20	0.0629	1.00
802.11 n-HT20		3.00	2.00	24.00	251.19	20	0.0997	1.00

Report No.: RSHA181204001-00A

Mode	Frequency (MHz)	Antenna Gain		Tune-up Conducted output power		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm ²)	(mW/cm ²)
802.11a	5150-5250	3.00	2.00	25.00	316.23	20	0.1258	1.0
802.11n-HT20		3.00	2.00	28.00	630.96	20	0.2510	1.0
802.11a	5725-5850	3.00	2.00	26.00	398.11	20	0.1580	1.0
802.11n-HT20		3.00	2.00	28.00	630.96	20	0.2504	1.0

Note:

(1) The Tune-up output power was declared by the Manufacturer.

(2) 2.4GWi-Fi and 5GWi-Fi cannot transmit simultaneously.

Conclusion: The device meets FCC MPE at 20 cm distance.

FCC Part 15.247 Page 15 of 75