

MRT Technology (Suzhou) Co., Ltd

Phone: +86-512-66308358 Fax: +86-512-66308368 www.mrt-cert.com

Report No.: 1407RSU04402 Report Version: V01 Issue Date: 08-05-2014

RF Exposure Evaluation Declaration

FCC ID: 2ACVW-W908I

APPLICANT: Shenzhen Haidian Technology Co., Ltd

Certification **Application Type:**

Product: WI-FI Home Automation Products

Model No.: W908I, W908II, W908F, W809I, W809II, W809III,

W608I, W608II, W608III

FCC Classification: Digital Transmission System (DTS)

July 23 ~ August 05, 2014 **Test Date:**

Reviewed By : Robin Wu)

Approved By : Marlinchen

(Marlin Chen)

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou)

Co., Ltd.

FCC ID: 2ACVW-W908I Page Number: 1 of 5





Revision History

Report No.	Version	Description	Issue Date
1407RSU04402	Rev. 01	Initial report	08-05-2014

FCC ID: 2ACVW-W908I Page Number: 2 of 5



1. RF Exposure Evaluation

1.1. Limits

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in Note 1 must be applied to determine SAR test exclusion.

150 39 77 116 155 194 300 27 55 82 110 137 450 22 45 67 89 112 835 16 33 49 66 82 900 16 32 47 63 79 1500 12 24 37 49 61	SAR Test Exclusion Threshold (mW)					
450 22 45 67 89 112 835 16 33 49 66 82 900 16 32 47 63 79 1500 12 24 37 49 61	Threshold					
835 16 33 49 66 82 900 16 32 47 63 79 1500 12 24 37 49 61						
900 16 32 47 63 79 1500 12 24 37 49 61	(mW)					
1500 12 24 37 49 61						
1900 11 22 33 44 54						
2450 10 19 29 38 48						
3600 8 16 24 32 40						
5200 7 13 20 26 33						
5400 6 13 19 26 32						
5800 6 12 19 25 31						
MHz 30 35 40 45 50	mm					
150 232 271 310 349 387	SAR Test					
300 164 192 219 246 274	Exclusion					
450 134 157 179 201 224	Threshold					
835 98 115 131 148 164	(mW)					
900 95 111 126 142 158						
1500 73 86 98 110 122						
1900 65 76 87 98 109						
2450 57 67 77 86 96						
3600 47 55 63 71 79						
5200 39 46 53 59 66						
5400 39 45 52 58 65						
5800 37 44 50 56 62						

Note 1:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

FCC ID: 2ACVW-W908I Page Number: 3 of 5



[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * $[\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

FCC ID: 2ACVW-W908I Page Number: 4 of 5



1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	WI-FI Home Automation Products	
Test Item	RF Exposure Evaluation	

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.5dBi for 2.4GHz in logarithm scale.

Output Power into Antenna:

Test Mode	Frequency Band (MHz)	Maximum output power to antenna (mW)	SAR Test Exclusion Threshold (mW)
802.11b/g/n	2412~2462	8.77	10

Per FCC KDB 447498 D01v05r02, the SAR exclusion threshold for distances<50mm is defined by the following equation:

$$\frac{Max\ Power\ of\ Channel\ (mW)}{Test\ Separation\ Dist\ (mm)}*\sqrt{Frequency(GHz)} \leq 3.0$$

Based on the maximum conducted power of Wi-Fi and the antenna to use separation distance, Wi-Fi SAR was not required;

$$[(8.77 \text{mW/5})^* \sqrt{2.437}] = 2.74 < 3.0.$$

Note: When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

FCC ID: 2ACVW-W908I Page Number: 5 of 5