RF EXPOSURE TEST FCC ID: 2ACVX-DVRQ7

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and \leq 50 mm Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz 5 10 15 20 25 mm 150 39 77 116 155 194	
	SAR Test Exclusion Threshold (mW)
300 27 55 82 110 137	
450 22 45 67 89 112	
835 16 33 49 66 82	
900 16 32 47 63 79 SAR Test	
1300 17 74 37 49 101	
1000 11 20 22 1 44 54	
2450 10 19 29 38 48	
3600 8 16 24 32 40	
5200 7 13 20 26 33	
5400 6 13 19 26 32	
5800 6 12 19 25 31	
MHz 30 35 40 45 50 mm	
150 232 271 310 349 387	
300 164 192 219 246 274	
450 134 157 179 201 224	
835 98 115 131 148 164	
835 98 115 131 148 164 900 95 111 126 142 158	
835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 SAR Test	
835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1000 65 76 87 08 100 SAR Test Exclusion	V)
835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 SAR Test Exclusion	V)
835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 Threshold (m)	V)
835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 2450 57 67 77 86 96 SAR Test Exclusion Threshold (m)	V)
835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 2450 57 67 77 86 96 3600 47 55 63 71 79	V)

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [$\sqrt{f_{(GHz)}}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,16 where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation17

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

WiFi

Channel	Frequency (MHz)	PK Output Power (dBm)	PK Output Power (mW)	Limit (dBm)
IEEE 802.11 b	2462	9.5	8.91	30
IEEE 802.11 g	2462	8.5	7.08	30
IEEE 802.11 n/HT20	2462	8.0	6.31	30
IEEE 802.11 n/HT40	2452	7.5	5.62	30

The WiFi max.output power E.I.R.P is 9.5dBm=8.91mW, Frequency is 2.462GHz So $(8.91/5)^*$ $\sqrt{2.462}=2.80 \le 3.0$

Note: $\sqrt{2.462} = 1.569$

Conclusion: No SAR is required.