FCC 47 CFR MPE REPORT

Shenyang Tongfang Multimedia Technology Co., Limited

LED TV

Model Number: SE55FGT

Additional Model: SE55XXXXXXXXX

FCC ID: 2ACWISE55FGT

Prepared for : Shenyang Tongfang Multimedia Technology Co., Limited

No. 10 Nanping East Road HunNan New District Shenyang,

LiaoNing Province P.R. China

Prepared By :EST Technology Co., Ltd.

Santun(guantai Road), Houjie Town, DongGuan City,GuangDong, China.

Tel: 86-769-83081888-808

Report Number: ESTE-R1509075

Date of Test : September 14~ September 23, 2015

Date of Report : September 24, 2015

Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm2)	Averaging Times｜E｜2 , ｜H｜2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm2)	Averaging Times｜E｜2 , ｜H｜2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.o	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

E (V/m) = $(30*P*G)^{0.5}/d$ 　　　　Power Density: Pd (W/m2) = $E^2/377$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$Pd = (30*P*G) / (377*d^2)$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、**Calculated Result and Limit**

Mode	Frequency (MHz)	output power (dBm)	output power (mW)	Target power（dBm）	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
					(dBi)	(Linear)			
IEEE 802.11b	2412	13.89	24.49	14±1	2	1.59	0.00997	1	Compiles
	2442	14.11	25.76	14±1	2	1.59	0.00997	1	Compiles
	2472	14.54	28.44	14±1	2	1.59	0.00997	1	Compiles
IEEE 802.11g	2412	9.46	8.83	10±1	2	1.59	0.00397	1	Compiles
	2442	10.26	10.62	10±1	2	1.59	0.00397	1	Compiles
	2472	10.71	11.78	10±1	2	1.59	0.00397	1	Compiles
IEEE 802.11n HT20	2412	7.42	5.52	8±1	2	1.59	0.00250	1	Compiles
	2442	7.44	5.55	8±1	2	1.59	0.00250	1	Compiles
	2472	8.46	7.01	8±1	2	1.59	0.00250	1	Compiles
IEEE 802.11n HT40	2422	7.59	5.74	8±1	2	1.59	0.00250	1	Compiles
	2442	7.55	5.69	8±1	2	1.59	0.00250	1	Compiles
	2462	7.75	5.96	8±1	2	1.59	0.00250	1	Compiles