FCC RF EXPOSURE REPORT

Shenyang Tongfang Multimedia Technology Co., Limited

LED TV

Model Number: ELST5016S

Additional Model: SE50FS, SE50FYT，ELST50XXXXXXXXX, SE50XXXXXXXXX

FCC ID: 2ACWIELST5016S

Prepared for : Shenyang Tongfang Multimedia Technology Co., Limited
No. 10 Nanping East Road HunNan New District Shenyang,
LiaoNing Province P.R. China

Prepared By :EST Technology Co., Ltd.
Santun(guantai Road), Houjie Town, DongGuan City,GuangDong,
China.

Tel: 86-769-83081888-808

Report Number: ESTE-R1603043
Date of Test　　: Feb 27~ Mar 15, 2016
Date of Report : Mar 17, 2016

Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm2)	Averaging Times｜E｜2，｜H｜2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm2)	Averaging Times｜E｜2，｜H｜2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.o	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

E (V/m) = (30*P*G) 0.5/d   Power Density: Pd (W/m2) = E2/377

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

Pd = (30*P*G) / (377*d2)

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、**Calculated Result and Limit**

Mode	Frequency (MHz)	output power (dBm)	output power (mW)	Target power（dBm）	Antenna gain (dBi)	Antenna gain (Linear)	Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
IEEE 802.11b	2412	13.19	20.85	13±1	2	1.59	0.00792	1	Compiles
	2442	13.18	20.80	13±1	2	1.59	0.00792	1	Compiles
	2472	13.08	20.32	13±1	2	1.59	0.00792	1	Compiles
IEEE 802.11g	2412	11.39	13.77	11±1	2	1.59	0.00500	1	Compiles
	2442	11.24	13.31	11±1	2	1.59	0.00500	1	Compiles
	2472	11.00	12.59	11±1	2	1.59	0.00500	1	Compiles
IEEE 802.11n HT20	2412	9.17	8.26	9±1	2	1.59	0.00315	1	Compiles
	2442	9.42	8.75	9±1	2	1.59	0.00315	1	Compiles
	2472	8.66	7.35	9±1	2	1.59	0.00315	1	Compiles
IEEE 802.11n HT40	2422	6.99	5.00	7±1	2	1.59	0.00199	1	Compiles
	2442	7.73	5.93	7±1	2	1.59	0.00199	1	Compiles
	2462	6.57	4.54	7±1	2	1.59	0.00199	1	Compiles