



FCC RADIO TEST REPORT

FCC ID: 2ACXW-K001

Product : Wi-Fi Hi-Fi Speaker

Trade Name : GJK

Model Name : K001

Serial Model : N/A

Report No. : NTEK-2014NT0725144F

Prepared for

Huong Hai Science and Technology Inc.

221 Bayshore Blvd. San Francisco, CA 94124

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599

Website: www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name Huong Hai Science and Technology Inc.
Address 221 Bayshore Blvd. San Francisco, CA 94124
Manufacture's Name... Huong Hai Science and Technology Inc.
Address 221 Bayshore Blvd. San Francisco, CA 94124

Product description

Product name Wi-Fi Hi-Fi Speaker
Model and/or type K001
reference
Serial Model N/A

Standards FCC Part15.247 01 Oct. 2013

Test procedure ANSI C63.4-2003 and 558074 D01 DTS Meas Guidance v03r02

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.


This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests 25 Jul. 2014 ~01 Aug. 2014

Date of Issue 01 Aug. 2014

Test Result **Pass**

Testing Engineer : 
Denny Huang

Technical Manager : 
(Brown Lu)

Authorized Signatory : 
(Bill Yao)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3 . EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
3.1.2 TEST PROCEDURE	15
3.1.3 DEVIATION FROM TEST STANDARD	15
3.1.4 TEST SETUP	15
3.1.5 EUT OPERATING CONDITIONS	15
3.1.6 TEST RESULTS	16
3.2 RADIATED EMISSION MEASUREMENT	18
3.2.1 RADIATED EMISSION LIMITS	18
3.2.2 TEST PROCEDURE	19
3.2.3 DEVIATION FROM TEST STANDARD	19
3.2.4 TEST SETUP	20
3.2.5 EUT OPERATING CONDITIONS	21
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	22
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	23
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	24
4 . POWER SPECTRAL DENSITY TEST	25
4.1 APPLIED PROCEDURES / LIMIT	25
4.1.1 TEST PROCEDURE	25
4.1.2 DEVIATION FROM STANDARD	25
4.1.3 TEST SETUP	25
4.1.4 EUT OPERATION CONDITIONS	25
4.1.5 TEST RESULTS	26
5 . BANDWIDTH TEST	34
5.1 APPLIED PROCEDURES / LIMIT	34
5.1.1 TEST PROCEDURE	34

Table of Contents

	Page
TEST SETUP	34
5.1.2 EUT OPERATION CONDITIONS	34
5.1.3 TEST RESULTS	35
6 . PEAK OUTPUT POWER TEST	43
6.1 APPLIED PROCEDURES / LIMIT	43
6.1.1 TEST PROCEDURE	43
6.1.2 DEVIATION FROM STANDARD	43
6.1.3 TEST SETUP	43
6.1.4 EUT OPERATION CONDITIONS	43
6.1.5 TEST RESULTS	44
7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	45
7.1 DEVIATION FROM STANDARD	45
7.2 TEST SETUP	45
7.3 EUT OPERATION CONDITIONS	45
7.4 TEST RESULTS	46
8 . ANTENNA REQUIREMENT	52
8.1 STANDARD REQUIREMENT	52
8.2 EUT ANTENNA	52
9 . EUT TEST PHOTO	53
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.:1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Wi-Fi Hi-Fi Speaker	
Trade Name	GJK	
Model Name	K001	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a Wi-Fi Hi-Fi Speaker	
	Operation Frequency:	802.11b/g/n(20MHz): 2412~2462MHz 802.11n(40MHz):2422~2452MHz
	Modulation Type:	CCK/OFDM/DBPSK/DAPSK
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20MHz/40MHz):150/144.44/130/117/115.56/104/86.67/78/52/6.5Mbps
	Number Of Channel	802.11b/g/n20MHz:11CH 802.11n40MHz:7CH
	Antenna Designation:	Please see Note 3.
	Output Power(Conducted):	802.11b: 12.48 dBm (Max.) 802.11g: 12.47 dBm (Max.) 802.11n(20M): 12.29 dBm (Max.) 802.11n(40M): 10.90 dBm (Max.)
	Antenna Gain (dBi)	ANT A:0 dBi ANT B:0 dBi
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Ratings	DC 18V	
Adapter	Input: 100-240V~50/60 Hz Output: 18V $\overline{\text{---}}$, 2A	
Battery	N/A	

Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.


Channel List for 802.11b/g/n(20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	06	2437	09	2452		
04	2427	07	2442				
05	2432	08	2447				

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	FPCB Antenna	N/A	0	Wifi Antenna
B	N/A	N/A	FPCB Antenna	N/A	0	Wifi Antenna



The Control software(tool_WIFI.exe) can control antenna A B ,
 For 2.4GHz mode, antenna A B are transmitting,two antennas simultaneously transmit.
 And the data is recorded for radiated emission and band edge.
 For MIMO mode , Directional gain= $G_{ANT} + 10\log(N)\text{dbi} = 3.01\text{dbi}$ in 2.4GHz
 802.11 b/g/n 2.4GHz has MIMO mode.

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n/20MHz CH1/ CH6/ CH11
Mode 4	802.11n/40MHz CH3/ CH6/ CH9
Mode 5	Link Mode


For Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n/20MHz CH1/ CH6/ CH11
Mode 4	802.11n/40MHz CH3/ CH6/ CH9

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Wi-Fi Hi-Fi Speaker	GJK	K001	N/A	EUT
E-2	Adapter	N/A	N/A	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.2m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2014.07.06	2015.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.06	2015.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2014.07.06	2015.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2013.12.22	2014.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2014.07.06	2015.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2014.06.06	2015.06.05	1 year
2	LISN	R&S	ENV216	101313	2013.08.24	2014.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2013.08.24	2014.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2014.06.07	2015.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.07	2015.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2014.06.08	2015.06.07	1 year
---	-------------	-----	----------	--------	------------	------------	--------

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN .

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

EUT :	Wi-Fi Hi-Fi Speaker	Model Name. :	K001
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 18V form Adapter AC 120V/60Hz	Test Mode :	Mode 5

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	43.67	9.60	53.27	65.56	-12.29	QP
0.1580	23.74	9.60	33.34	55.56	-22.22	AVG
0.1940	37.71	9.51	47.22	63.86	-16.64	QP
0.1940	20.02	9.51	29.53	53.86	-24.33	AVG
0.2580	37.10	9.49	46.59	61.49	-14.90	QP
0.2580	19.88	9.49	29.37	51.49	-22.12	AVG
0.7700	18.45	9.53	27.98	56.00	-28.02	QP
0.7700	15.16	9.53	24.69	46.00	-21.31	AVG
6.3339	5.23	9.65	14.88	50.00	-35.12	AVG
6.3339	15.50	9.65	25.15	60.00	-34.85	QP
17.1459	26.30	10.04	36.34	60.00	-23.66	QP
17.1459	18.29	10.04	28.33	50.00	-21.67	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Wi-Fi Hi-Fi Speaker	Model Name. :	K001
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 18V form Adapter AC 120V/60Hz	Test Mode :	Mode 5

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1499	47.33	9.63	56.96	66.00	-9.04	QP
0.1499	27.89	9.63	37.52	56.00	-18.48	AVG
0.1980	37.60	9.50	47.10	63.69	-16.59	QP
0.1980	21.22	9.50	30.72	53.69	-22.97	AVG
0.2660	34.88	9.49	44.37	61.24	-16.87	QP
0.2660	20.16	9.49	29.65	51.24	-21.59	AVG
0.7660	18.60	9.53	28.13	56.00	-27.87	QP
0.7660	14.55	9.53	24.08	46.00	-21.92	AVG
5.8259	20.04	9.64	29.68	60.00	-30.32	QP
5.8259	8.31	9.64	17.95	50.00	-32.05	AVG
17.1659	14.42	10.04	24.46	50.00	-25.54	AVG
17.1659	22.58	10.04	32.62	60.00	-27.38	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz

**3.2.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	Wi-Fi Hi-Fi Speaker	Model Name. :	K001
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})(\text{dB})$;

Limit line = specific limits(dBuv) + distance extrapolation factor.

3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Below 1G							
36.5091	16.86	15.74	32.60	40.00	-7.40	QP	Vertical
51.8430	25.31	10.16	35.47	40.00	-4.53	QP	Vertical
57.9992	28.90	8.40	37.30	40.00	-2.70	QP	Vertical
124.1329	23.10	12.02	35.12	40.00	-4.88	QP	Vertical
295.1469	28.24	14.10	42.34	47.00	-4.66	QP	Vertical
485.6093	18.22	20.00	38.22	47.00	-8.78	QP	Vertical
45.0583	16.23	11.91	28.14	40.00	-11.86	QP	Horizontal
124.1329	18.76	12.02	30.78	40.00	-9.22	QP	Horizontal
196.5098	25.42	10.75	36.17	40.00	-3.83	QP	Horizontal
295.1469	29.55	14.10	43.65	47.00	-3.35	QP	Horizontal
304.6099	28.26	14.34	42.60	47.00	-4.40	QP	Horizontal
350.4768	23.82	16.26	40.08	47.00	-6.92	QP	Horizontal

3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2412 MHz)-Above 1G							
4824.215	50.89	10.44	61.33	74.00	-12.67	Pk	Vertical
4824.215	32.21	10.44	42.65	54.00	-11.35	Av	Vertical
7236.133	44.18	12.39	56.57	74.00	-17.43	Pk	Vertical
7236.133	28.45	12.39	40.84	54.00	-13.16	Av	Vertical
4824.109	52.31	10.44	62.75	74.00	-11.25	Pk	Horizontal
4824.109	33.39	10.44	43.83	54.00	-10.17	Av	Horizontal
7236.218	44.85	12.39	57.24	74.00	-16.76	Pk	Horizontal
7236.218	30.02	12.39	42.41	54.00	-11.59	Av	Horizontal
Mid Channel (2437 MHz)-Above 1G							
4874.219	46.51	10.40	56.91	74.00	-17.09	Pk	Vertical
4874.219	27.42	10.40	37.82	54.00	-16.18	AV	Vertical
7311.152	40.14	12.75	52.89	74.00	-21.11	Pk	Vertical
7311.152	23.1	12.75	35.85	54.00	-18.15	AV	Vertical
4874.247	47.28	10.40	57.68	74.00	-16.32	Pk	Horizontal
4874.247	28.5	10.40	38.90	54.00	-15.10	AV	Horizontal
7311.155	39.39	12.75	52.14	74.00	-21.86	Pk	Horizontal
7311.155	24.08	12.75	36.83	54.00	-17.17	AV	Horizontal
High Channel (2462 MHz)- Above 1G							
4924.094	49.38	10.39	59.77	74.00	-14.23	Pk	Vertical
4924.094	31.01	10.39	41.40	54.00	-12.60	Av	Vertical
7386.137	42.78	12.68	55.46	74.00	-18.54	Pk	Vertical
7386.137	26.42	12.68	39.10	54.00	-14.90	Av	Vertical
4924.218	49.39	10.39	59.78	74.00	-14.22	Pk	Horizontal
4924.218	31.51	10.39	41.90	54.00	-12.10	Av	Horizontal
7386.156	41.79	12.68	54.47	74.00	-19.53	Pk	Horizontal
7386.156	27.03	12.68	39.71	54.00	-14.29	Av	Horizontal

Note:"802.11b" mode is the worst mode.

4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. 3 kHz ≤ Set the RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



4.1.5 TEST RESULTS

EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX b Mode /CH01, CH06, CH11		

Frequency	Power Density A (dBm)	Power Density B (dBm)	Total Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-7.60	-7.83	-4.70	8	PASS
2437 MHz	-9.963	-9.988	-6.97	8	PASS
2462 MHz	-8.162	-8.197	-5.17	8	PASS

NOTE: A(B) Represent the value of antenna A and B, The worst data is A Antenna, only shown Antenna A Plot.








EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX g Mode /CH01, CH06, CH11		

Frequency	Power Density A (dBm)	Power Density B (dBm)	Total Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-15.07	-15.47	-12.26	8	PASS
2437 MHz	-14.32	-14.69	-11.49	8	PASS
2462 MHz	-11.79	-12.03	-8.90	8	PASS

NOTE: A(B) Represent the value of antenna A and B, The worst data is A Antenna, only shown Antenna A Plot.







EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		

Frequency	Power Density A (dBm)	Power Density B (dBm)	Total Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-16.80	-16.95	-13.86	8	PASS
2437 MHz	-13.91	-14.12	-11.00	8	PASS
2462 MHz	-16.08	-16.24	-13.15	8	PASS


NOTE: A(B) Represent the value of antenna A and B, The worst data is A Antenna, only shown Antenna A Plot.



TX CH06




TX CH11




EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09		

Frequency	Power Density A (dBm)	Power Density B (dBm)	Total Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-14.94	-14.97	-11.94	8	PASS
2437 MHz	-13.87	-13.95	-10.90	8	PASS
2462 MHz	-15.05	-15.14	-12.08	8	PASS


NOTE: A(B) Represent the value of antenna A and B, The worst data is A Antenna, only shown Antenna A Plot.



TX CH06



TX CH09



5. BANDWIDTH TEST


5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP




5.1.2 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


5.1.3 TEST RESULTS

EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX b Mode /CH01, CH06, CH11		


Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	11.187	500	Pass
Middle	2437	11.189	500	Pass
High	2462	11.247	500	Pass



TX CH 06




TX CH 11




EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX g Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	16.471	500	Pass
Middle	2437	16.497	500	Pass
High	2462	16.510	500	Pass


TX CH 01



TX CH 06




TX CH 11




EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	17.319	500	Pass
Middle	2437	17.647	500	Pass
High	2462	17.617	500	Pass



TX CH 06




TX CH 11




EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2422	36.438	500	Pass
Middle	2437	36.349	500	Pass
High	2452	36.456	500	Pass


TX CH 03



TX CH 06



TX CH 09



6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz
Test Mode :	TX b/g/n20/n40 Mode		

Test Channel	Frequency (MHz)	Maximum output power. Antenna port				Total Power		LIMIT
		(PK) (dBm)		(AV) (dBm)		(PK)	(AV)	
		ANT A	ANT B	ANT A	ANT B	dBm	dBm	dBm
TX 802.11b Mode								
CH01	2412	9.95	8.92	9.79	8.72	12.48	12.30	30
CH06	2437	9.89	8.91	9.64	8.63	12.44	12.17	30
CH11	2462	9.83	8.93	9.63	8.66	12.41	12.18	30
TX 802.11g Mode								
CH01	2412	9.85	8.75	9.53	8.66	12.35	12.13	30
CH06	2437	9.83	8.85	9.61	8.47	12.38	12.09	30
CH11	2462	9.92	8.94	9.44	8.66	12.47	12.08	30
TX 802.11n/20M Mode								
CH01	2412	9.56	8.66	8.99	8.09	12.14	11.57	30
CH06	2437	9.72	8.78	9.02	8.11	12.29	11.60	30
CH11	2462	9.53	8.51	9.05	8.06	12.06	11.59	30
TX 802.11n/40M Mode								
CH03	2422	8.43	7.21	8.12	7.03	10.87	10.62	30
CH06	2437	8.41	7.24	8.21	7.02	10.87	10.67	30
CH09	2452	8.36	7.36	8.26	6.98	10.90	10.68	30

7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

7.1 DEVIATION FROM STANDARD

No deviation.

7.2 TEST SETUP



7.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.4 TEST RESULTS

EUT :	Wi-Fi Hi-Fi Speaker	Model Name :	K001
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 18V form Adapter AC 120V/60Hz


Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
802.11b			
Left-band	36.17	20	Pass
Right-band	55.12	20	Pass
802.11g			
Left-band	43.29	20	Pass
Right-band	43.29	20	Pass
802.11n20			
Left-band	31.13	20	Pass
Right-band	42.09	20	Pass
802.11n40			
Left-band	27.88	20	Pass
Right-band	34.85	20	Pass

Radiated band edge:


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
802.11b							
2390	59.73	-13.06	46.67	74	-27.33	peak	Vertical
2390	59.44	-13.06	46.38	74	-27.62	peak	Horizontal
2483.5	60.63	-12.78	47.85	74	-26.15	peak	Vertical
2483.5	60.66	-12.78	47.88	74	-26.12	peak	Horizontal
802.11g							
2390	59.54	-13.06	46.48	74	-27.52	peak	Vertical
2390	58.72	-13.06	45.66	74	-28.34	peak	Horizontal
2483.5	60.43	-12.78	47.65	74	-26.35	peak	Vertical
2483.5	60.65	-12.78	47.87	74	-26.13	peak	Horizontal
802.11n(20)							
2390	61.93	-13.06	48.87	74	-25.13	peak	Vertical
2390	61.71	-13.06	48.65	74	-25.35	peak	Horizontal
2483.5	61.85	-12.78	49.07	74	-24.93	peak	Vertical
2483.5	61.97	-12.78	49.19	74	-24.81	peak	Horizontal
802.11n(40)							
2390	62.68	-13.06	49.62	74	-24.38	peak	Vertical
2390	63.77	-13.06	50.71	74	-23.29	peak	Horizontal
2483.5	62.31	-12.78	49.53	74	-24.47	peak	Vertical
2483.5	62.16	-12.78	49.38	74	-24.62	peak	Horizontal

Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit, average not record.


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side




802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side




802.11n-HT20: Band Edge, Left Side




802.11n-HT20: Band Edge, Right Side



802.11n-HT40: Band Edge, Left Side



802.11n-HT40: Band Edge, Right Side



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is FPCB Antenna. It comply with the standard requirement.

9. EUT TEST PHOTO

Radiated Measurement Photos



Conducted Measurement Photos