

# FCC REPORT

**Applicant:** Worldex International Ltd.  
**Address of Applicant:** 3A-8A, Mont Orchid Riverlet, Gongye 3rd Rd, Nanshan, Shenzhen, China

## Equipment Under Test (EUT)

**Product Name:** Tablet PC  
**Model No.:** neos 2, H5002, H5003  
**Trade mark:** neos  
**FCC ID:** 2ACZ2-NEOS2  
**Applicable standards:** FCC CFR Title 47 Part 15 Subpart B  
**Date of sample receipt:** 17 Oct., 2014  
**Date of Test:** 17 Oct., to 14 Nov., 2014  
**Date of report issued:** 17 Nov., 2014  
**Test Result:** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	17 Nov., 2014	Original

Prepared by:

*Sera Xiang*

Date:

17 Nov., 2014

Report Clerk

Reviewed by:

*Abomb Yang*

Date:

17 Nov., 2014

Project Engineer

## 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 VERSION .....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>3</b>
<b>4 TEST SUMMARY .....</b>	<b>4</b>
<b>5 GENERAL INFORMATION .....</b>	<b>5</b>
5.1 CLIENT INFORMATION .....	5
5.2 GENERAL DESCRIPTION OF E.U.T. ....	5
5.3 TEST MODE.....	5
5.4 DESCRIPTION OF SUPPORT UNITS .....	6
5.5 LABORATORY FACILITY .....	6
5.6 LABORATORY LOCATION .....	6
5.7 TEST INSTRUMENTS LIST.....	7
<b>6 TEST RESULTS AND MEASUREMENT DATA .....</b>	<b>8</b>
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION .....	11
<b>7 TEST SETUP PHOTO.....</b>	<b>17</b>
<b>8 EUT CONSTRUCTIONAL DETAILS.....</b>	<b>18</b>

#### 4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass

*Pass: The EUT complies with the essential requirements in the standard.*

## 5 General Information

### 5.1 Client Information

Applicant:	Worldex International Ltd.
Address of Applicant:	3A-8A, Mont Orchid Riverlet, Gongye 3rd Rd, Nanshan, Shenzhen, China
Manufacturer :	Hena Digital Technology (Shenzhen) Co., Ltd.
Address of Manufacturer:	13F, Block B, Tairan Building, Futian District, Shenzhen, China

### 5.2 General Description of E.U.T.

Product Name:	Tablet PC
Model No.:	neos 2, H5002, H5003
Power supply:	Rechargeable Li-ion Battery DC3.7V-1500mAh
AC adapter :	Model:ASUC37a-050100 Input: AC 100-240V 50/60Hz 0.3A Output: DC 5.0V, 1.0A
Remark:	Item No.:neos 2, H5002, H5003 were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference being in appearance of colour.

### 5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Recording mode	Keep the EUT in Recording mode
Playing mode	Keep the EUT in Playing mode
FM mode	Keep the EUT in FM mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

## 5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
MERCURY	Wireless router	MW150R	12922104015	FCC ID

## 5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

## 5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road, Bao'an District, Shenzhen, Guangdong, China

Tel: 0755-23118282

Fax: 0755-23116366


## 5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	04-19-2014	04-19-2015
3	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	04-19-2014	04-19-2015
4	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
5	Coaxial Cable	CCIS	N/A	CCIS0016	04-01-2014	03-31-2015
6	Coaxial Cable	CCIS	N/A	CCIS0017	04-01-2014	03-31-2015
7	Coaxial cable	CCIS	N/A	CCIS0018	04-01-2014	03-31-2015
8	Coaxial Cable	CCIS	N/A	CCIS0019	04-01-2014	03-31-2015
9	Coaxial Cable	CCIS	N/A	CCIS0087	04-01-2014	03-31-2015
10	Amplifier(10kHz-1.3GHz)	HP	8447D	CCIS0003	04-01-2014	03-31-2015
11	Amplifier(1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	06-09-2014	06-08-2015
12	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	04-01-2014	03-31-2015
13	Horn Antenna	ETS-LINDGREN	3160	GTS217	03-30-2014	03-29-2015
14	Printer	HP	HP LaserJet P1007	N/A	N/A	N/A
15	Positioning Controller	UC	UC3000	CCIS0015	N/A	N/A
16	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP	CCIS0023	04-19-2014	04-19-2015
17	EMI Test Receiver	Rohde & Schwarz	ESPI	CCIS0022	04-01-2014	03-31-2015
18	Loop antenna	Laplace instrument	RF300	EMC0701	04-01-2014	03-31-2015
19	Universal radio communication tester	Rhode & Schwarz	CMU200	CCIS0069	05-29-2014	05-28-2015
20	Signal Analyzer	Rohde & Schwarz	FSIQ3	CCIS0088	04-19-2014	04-19-2015

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	10-10-2012	10-09-2015
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	04-10-2014	04-09-2015
3	LISN	CHASE	MN2050D	CCIS0074	04-10-2014	04-10-2015
4	Coaxial Cable	CCIS	N/A	CCIS0086	04-01-2014	03-31-2015

## 6 Test results and Measurement Data


## 6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107						
Test Method:	ANSI C63.4:2003						
Test Frequency Range:	150kHz to 30MHz						
Class / Severity:	Class B						
Receiver setup:	RBW=9kHz, VBW=30kHz						
Limit:	Frequency range (MHz)		Limit (dBμV)				
			Quasi-peak	Average			
	0.15-0.5	66 to 56*		56 to 46*			
	0.5-5	56		46			
	0.5-30	60		50			
Test setup:	 <p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>						
	Test procedure						
Test environment:		Temp.:	23 °C	Humid.:	56%	Press.:	1 01kPa
Measurement Record:		Uncertainty: 3.28dB					
Test Instruments:		Refer to section 5.7 for details					
Test mode:		Refer to section 5.3 for details					
Test results:		Passed					



## Measurement data:

Line:




### Trace: 3

Site : CCIS Shielding Room  
 Condition : FCC PART15 B QP LISN LINE  
 Job No. : 859RF  
 EUT : Tablet PC  
 Model : H-5002  
 Test Mode : PC mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa  
 Test Engineer: Wendell  
 Remark :

	Read	LISN	Cable		Limit	Over	
Freq	Level	Factor	Loss	Level	Line	Limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.381	25.12	0.28	10.72	36.12	48.25	-12.13 Average
2	0.393	32.66	0.28	10.72	43.66	57.99	-14.33 QP
3	0.579	26.88	0.26	10.77	37.91	46.00	-8.09 Average
4	0.641	31.71	0.24	10.77	42.72	56.00	-13.28 QP
5	1.060	30.60	0.25	10.88	41.73	56.00	-14.27 QP
6	1.065	25.18	0.25	10.88	36.31	46.00	-9.69 Average
7	1.403	24.33	0.25	10.91	35.49	46.00	-10.51 Average
8	1.456	31.48	0.26	10.92	42.66	56.00	-13.34 QP
9	1.918	23.92	0.26	10.95	35.13	46.00	-10.87 Average
10	2.285	24.21	0.26	10.95	35.42	46.00	-10.58 Average
11	2.309	31.99	0.26	10.95	43.20	56.00	-12.80 QP
12	2.736	31.27	0.27	10.93	42.47	56.00	-13.53 QP

Neutral:



Trace: 1



Site : CCIS Shielding Room  
 Condition : FCC PART15 B QP LISN NEUTRAL  
 Job No. : 859RF  
 EUT : Tablet PC  
 Model : H-5002  
 Test Mode : PC mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa  
 Test Engineer: Wendell  
 Remark :

	Read	LISN	Cable	Limit	Over	
Freq	Level	Factor	Loss	Level	Line	Limit Remark
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dB	dBuV	dBuV	dB
1	0.174	38.16	0.25	10.77	49.18	64.77 -15.59 QP
2	0.350	32.38	0.25	10.73	43.36	58.96 -15.60 QP
3	0.377	20.21	0.25	10.72	31.18	48.34 -17.16 Average
4	0.589	30.12	0.24	10.77	41.13	56.00 -14.87 QP
5	0.601	21.45	0.23	10.77	32.45	46.00 -13.55 Average
6	1.411	28.88	0.25	10.91	40.04	56.00 -15.96 QP
7	1.433	17.88	0.26	10.92	29.06	46.00 -16.94 Average
8	1.800	19.11	0.28	10.95	30.34	46.00 -15.66 Average
9	1.810	30.38	0.28	10.95	41.61	56.00 -14.39 QP
10	2.664	19.63	0.29	10.93	30.85	46.00 -15.15 Average
11	3.107	33.32	0.29	10.92	44.53	56.00 -11.47 QP
12	3.107	20.60	0.29	10.92	31.81	46.00 -14.19 Average

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

## 6.2 Radiated Emission


Test Requirement:	FCC Part 15 B Section 15.109				
Test Method:	ANSI C63.4:2003				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Limit:	Frequency	Peak	Limit (dBuV/m @ 3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
			74.0		Peak Value
Test setup:	Below 1GHz				
					
	Above 1GHz				
					

Test Procedure:	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>
Test environment:	Temp.: 25 °C Humid.: 55% Press.: 1 01kPa
Measurement Record:	Uncertainty: 4.88dB
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

## Measurement Data

Below 1GHz

Horizontal:




Site : 3m chamber  
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) HORIZONTAL  
 Job No. : 859RF  
 EUT : Tablet PC

Model : H-5002  
 Test mode : PC mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Ffy  
 Remark :

	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	91.816	40.60	12.24	0.92	29.56	24.20	43.50	-19.30	QP
2	150.011	38.46	8.26	1.32	29.22	18.82	43.50	-24.68	QP
3	195.137	44.68	10.57	1.37	28.86	27.76	43.50	-15.74	QP
4	250.301	37.40	12.07	1.62	28.54	22.55	46.00	-23.45	QP
5	285.978	38.69	12.78	1.73	28.47	24.73	46.00	-21.27	QP
6	350.477	36.73	14.27	1.94	28.56	24.38	46.00	-21.62	QP



Vertical:




Site : 3m chamber  
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL  
 Job No. : 859RF  
 EUT : Tablet PC

Model : H-5002  
 Test mode : PC mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Ffy  
 Remark :

Remark	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	38.212	37.26	13.15	0.51	29.92	21.00	40.00	-19.00	QP
2	93.113	38.62	12.50	0.92	29.56	22.48	43.50	-21.02	QP
3	120.277	40.38	10.38	1.12	29.39	22.49	43.50	-21.01	QP
4	194.453	41.55	10.56	1.37	28.87	24.61	43.50	-18.89	QP
5	281.995	36.59	12.70	1.72	28.48	22.53	46.00	-23.47	QP
6	392.095	40.13	14.87	2.09	28.75	28.34	46.00	-17.66	QP

Above 1GHz

Horizontal:




Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL  
 Job No. : 859RF  
 EUT : Tablet PC

Model : H-5002  
 Test mode : PC mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Wendell  
 Remark :

	Freq	ReadAntenna	Cable Preamp		Limit	Over	
		Level Factor	Loss Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1	2080.961	45.84	26.71	5.01	40.56	37.00	74.00 -37.00 Peak
2	2080.961	35.63	26.71	5.01	40.56	26.79	54.00 -27.21 Average
3	3467.664	46.99	28.76	6.33	39.34	42.74	74.00 -31.26 Peak
4	3467.664	36.19	28.76	6.33	39.34	31.94	54.00 -22.06 Average
5	4770.324	46.38	31.47	8.86	40.29	46.42	74.00 -27.58 Peak
6	4770.324	36.03	31.47	8.86	40.29	36.07	54.00 -17.93 Average

Vertical:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL  
 Job No. : 859RF  
 EUT : Tablet PC

Model : H-5002  
 Test mode : PC mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Wendell  
 Remark :

	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
		Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2055.023	45.06	26.45	4.94	40.67	35.78	74.00	-38.22 Peak
2	2055.023	35.05	26.45	4.94	40.67	25.77	54.00	-28.23 Average
3	3387.825	45.98	28.40	6.40	39.00	41.78	74.00	-32.22 Peak
4	3387.825	35.16	28.40	6.40	39.00	30.96	54.00	-23.04 Average
5	4997.811	47.13	31.79	9.12	39.98	48.06	74.00	-25.94 Peak
6	4997.811	37.01	31.79	9.12	39.98	37.94	54.00	-16.06 Average