







ISO/IEC17025Accredited Lab.

Report No: FCC 1408087-01 File reference No: 2014-09-03

Applicant: **OBO Electronics Group Limited**

Product: **TABLET PC**

Model No: TouchSmart SDS, OB701, OB702, OB801, OB802, OB901,

> OB902, OB1001, OB1002, OB7801, OB7802, GK8821, GK8831, GK710, GK736, GK738, GK756I, GK810, GK10181,

GK10141

Trademark: **OBO**

Test Standards: FCC Part 15.247

It is herewith confirmed and found to comply with the Test result:

requirements set up by ANSI C63.4, FCC Part 15 Subpart C, 15.247 regulations evaluation Paragraph for the

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: Sep 03, 2014

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

5/F,Block 4, Anhua Industrial Zone., No.8 TaiRan Rd. CheGongMiao, FuTian District, Shenzhen, CHINA.

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timewaytech.com

Report No: FCC1408087-01 Page 2 of 91

Date: 2014-09-03



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAL-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC-Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-02.

Page 3 of 91

Report No: FCC1408087-01

Date: 2014-09-03



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details.	4
1.3	Description of EUT	4
1.4	Submitted Sample.	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	8
3.1	Summary of Test Results.	8
3.2	Test Standards.	8
4.0	EUT Modification.	8
5.0	Power Line Conducted Emission Test.	9
5.1	Schematics of the Test.	9
5.2	Test Method and Test Procedure.	9
5.3	Configuration of the EUT.	9
5.4	EUT Operating Condition.	10
5.5	Conducted Emission Limit.	10
5.6	Test Result.	10
6.0	Radiated Emission test.	13
6.1	Test Method and Test Procedure.	13
6.2	Configuration of the EUT.	13
6.3	EUT Operation Condition.	13
6.4	Radiated Emission Limit.	14
7.0	6dB Bandwidth Measurement.	33
8.0	Maximum Peak Output Power	49
9.0	Power Spectral Density Measurement.	52
10.0	Out of Band Measurement.	67
11.0	Antenna Requirement.	76
12.0	FCC Label.	77
13 0	Photo of Test Setup and EUT View	78

Date: 2014-09-03



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: OBO Electronics Group Limited

Address: Unit 705, GuanEr Yongtai Building, Congyun Road, Baiyun District, Guangzhou, China

Telephone: 020-81429308(Ext: 604)

Fax: 020-36257622

1.3 Description of EUT

Product: TABLET PC

Manufacturer: OBO Electronics Group Limited

Address: Unit 705, GuanEr Yongtai Building, Congyun Road, Baiyun District,

Guangzhou, China

Brand Name: OBO

Model Number: TouchSmart SDS

Additional Model Number: OB701, OB702, OB801, OB802, OB901, OB902, OB1001, OB1002, OB7801,

OB7802, GK8821, GK8831, GK710, GK736, GK738, GK756I, GK810, GK10181, GK10141

Type of Modulation IEEE 802.11b : DSSS (CCK, QPSK, DBPSK)

IEEE 802.11g/n (HT20): OFDM(64QAM, 16QAM, QPSK, BPSK)

Frequency range IEEE 802.11b/g/n (HT20) : 2412-2462MHz

Channel Spacing 5MHz for IEEE 802.11b/g/n(HT20) Air Data Rate IEEE 802.11b : 11, 5.5, 2, 1 Mbps

IEEE 802.11g: 54, 48,36, 24, 18, 12, 9, 6 Mbps

IEEE 802.11n HT20: 150, 135, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6.5 Mbps

Frequency Selection By software

Channel Number IEEE 802.11b/g/n (HT20): 11 Channels

Antenna: Integral Antenna and the maximum Gain of this antenna is 1.0dBi;

Power Adapter Model No.: FY0502000

Input: 100-240AC, 50/60Hz, 0.5A; Output: DC9V, 2A

he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: FCC1408087-01 Page 5 of 91

Date: 2014-09-03



1.4 Submitted Sample: 2 Samples

1.5 Test Duration 2014-08-20 to 2014-09-02

1.6 Test UncertaintyConducted Emissions Uncertainty =3.6dBRadiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

Terry Tang

Page 6 of 91

Report No: FCC1408087-01

Date: 2014-09-03



2.0 Test Equipments					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2014-08-21	2015-08-20
TWO	R&S	EZH3-Z5	100294	2014-08-22	2015-08-21
Line-V-NETW		EZII3-Z3	100294	2014-08-22	2013-08-21
TWO	R&S	EZH3-Z5	100253	2014-08-22	2015-08-21
Line-V-NETW		DEITS ES	100233	2014 00 22	2013 00 21
Ultra Broadband ANT	R&S	HL562	100157	2014-08-23	2015-08-22
AIVI	R&S				
ESDV Test Receiver	Kas	ESDV	100008	2014-08-22	2015-08-21
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2014-08-21	2015-08-20
System Controller	CT	SC100	-		
Printer	EPSON	РНОТО ЕХЗ	CFNH234850		
Computer	IBM	8434	1S8434KCE99BLXLO*	-	-
Loop Antenna	EMCO	6502	00042960	2014-08-22	2015-08-21
ESPI Test Receiver	R&S	ESI26	838786/013	2014-08-22	2015-08-21
3m OATS			N/A	2014-08-21	2015-08-20
Horn Antenna	R&S	BBHA 9170	BBHA9170265	2014-08-23	2015-08-22
Horn Antenna	R&S	BBHA 9120D	9120D-631	2014-08-23	2015-08-22
Power meter	Anritsu	ML2487A	6K00003613	2014-08-22	2015-08-21
Power sensor	Anritsu	MA2491A	32263	2014-08-22	2015-08-21
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2014-08-23	2015-08-22
LISN	AFJ	LS16C	10010947251	2014-08-21	2015-08-20
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2014-08-22	2015-08-21
9*6*6 Anechoic			N/A	2014-08-21	2015-08-20
EMI Test Receiver	RS	ESCS30	100139	2014-08-22	2015-08-21
Universal Radio					
Communication	RS	CMU200	1100.0008.02	2013-11-28	2014-11-27
Tester					
Spectrum Analyzer	Agilent	E4440A	US44300286	2014-03-23	2015-03-22

Date: 2014-09-03



Page 7 of 91

3. DESCRIPTION OF TEST MODES

IEEE 802.11b, 802.11g, 802.11n (HT20) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 11Mbps data rate (worst case) was chosen for full testing. IEEE 802.11g mode: 54Mbps data rate (worst case) was chosen for full testing. IEEE 802.11n (HT20) mode: 6.5Mbps data rate (worst case) were chosen for full testing

The worst-case data rates are determined according to the description above, based on the investigations by measuring the PSD and average power across all the data rates, bandwidths, modulations and spatial stream modes.

Date: 2014-09-03



3.0 Technical Details

3.1 Summary of test results

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107 & 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit: Table 15.209	PASS	Complies

3.2 Test Standards

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

4.0 EUT Modification


No modification by Shenzhen Timeway Technology Consulting Co., Ltd

Date: 2014-09-03



5.0 Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model	FCC ID
TABLET PC	OBO Electronics Group Limited	TouchSmart SDS, OB701, OB702, OB801, OB802, OB901, OB902, OB1001, OB1002, OB7801, OB7802, GK8821, GK8831, GK710, GK736, GK738, GK756I, GK810, GK10181, GK10141	FCC ID: 2ACZ8-OB1001

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: FCC1408087-01 Page 10 of 91

Date: 2014-09-03



C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
LCD Monitor	SAMSUNG	PH2450	DOC	

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107

Frequency	Class A Lim	its (dB µ V)	Class B Lim	nits (dB µ V)
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0
5.00 ~ 30.00	73.0	60.0	60.0	50.0

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Date: 2014-09-03



A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Keep WIFI Transmitting

Equipment Level: Class B

Results: PASS

Please refer to following diagram for individual



No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBu∀	dBuV	dB	Detector	Comment
1	0.4630	30.00	11.33	41.33	56.64	-15.31	QP	
2	0.4630	0.80	11.33	12.13	46.64	-34.51	AVG	
3	0.5293	28.40	11.40	39.80	56.00	-16.20	QP	
4	0.5293	1.20	11.40	12.60	46.00	-33.40	AVG	
5	1.3460	29.10	12.04	41.14	56.00	-14.86	QP	
6	1.3460	-3.10	12.04	8.94	46.00	-37.06	AVG	
7 *	1.7823	31.10	12.21	43.31	56.00	-12.69	QP	
8	1.7823	2.10	12.21	14.31	46.00	-31.69	AVG	
9	3.9544	25.20	13.08	38.28	56.00	-17.72	QP	
10	3.9544	0.40	13.08	13.48	46.00	-32.52	AVG	

he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2014-09-03



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Keep WIFI Transmitting

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1982	41.60	11.05	52.65	63.69	-11.04	QP	
2		0.1982	7.00	11.05	18.05	53.69	-35.64	AVG	
3		0.2627	36.10	11.12	47.22	61.35	-14.13	QP	
4		0.2627	11.00	11.12	22.12	51.35	-29.23	AVG	
5		0.3300	31.70	11.19	42.89	59.45	-16.56	QP	
6		0.3300	4.00	11.19	15.19	49.45	-34.26	AVG	
7		1.7673	31.60	12.21	43.81	56.00	-12.19	QP	
8		1.7673	1.80	12.21	14.01	46.00	-31.99	AVG	
9		2.1326	31.90	12.35	44.25	56.00	-11.75	QP	
10		2.1326	1.20	12.35	13.55	46.00	-32.45	AVG	
11		3.2776	24.70	12.81	37.51	56.00	-18.49	QP	
12		3.2776	-2.40	12.81	10.41	46.00	-35.59	AVG	

he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: FCC1408087-01 Page 13 of 91

Date: 2014-09-03



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization : Vertical polarization and Horizontal polarization.

Block diagram of Test setup Distance = 3m Computer Pre – Amplifier EUT Turn-table Receiver

- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

Report No: FCC1408087-01 Page 14 of 91

Date: 2014-09-03



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109 and RSS-210

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Report No: FCC1408087-01 Page 15 of 91

Date: 2014-09-03



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal/Vertical (30MHz----1000MHz)

EUT set Condition: **Keep Transmitting**

Results: Pass

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
119.960	27.11	Н	43.50
40.960	26.25	Н	40.00
95.880	28.95	Н	43.50
169.000	33.16	Н	43.50
35.480	36.84	V	40.00
38.600	36.47	V	40.00
104.760	34.65	V	43.50
168.000	29.74	V	43.50


Page 16 of 91

Report No: FCC1408087-01

Date: 2014-09-03



Test Figure:



Date: 20.AUG.2014 12:54:19


Page 17 of 91

Report No: FCC1408087-01

Date: 2014-09-03



Test Figure:



Date: 20.AUG.2014 12:44:36

Report No: FCC1408087-01 Page 18 of 91

Date: 2014-09-03



Operation Mode: Transmitting under CH01 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	(dB µ V/m) Antenna Polarity Limit@3m		
4824.00	48.28 (PK)	Н	74(Peak)/ 54(AV)	
4824.00	46.82 (PK)	V	74(Peak)/ 54(AV)	
7236.00	1	H/V	74(Peak)/ 54(AV)	
9648.00	-	H/V	74(Peak)/ 54(AV)	
12060		H/V 74(Pe		
14472		H/V	74(Peak)/ 54(AV)	
16884		H/V		
19296	-	H/V	74(Peak)/ 54(AV)	
21708		H/V	74(Peak)/ 54(AV)	
24120		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 54Mbps

Date: 2014-09-03



Operation Mode: Transmitting under CH06 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB \(\mu \) V/m) Antenna Polarity Limit@3:		Limit@3m (dB µ V/m)	
4874.00	48.47 (PK)	V	74(Peak)/ 54(AV)	
4874.00	48.82 (PK)	Н	74(Peak)/ 54(AV)	
7311.00	1	H/V	74(Peak)/ 54(AV)	
9748.00		H/V	74(Peak)/ 54(AV)	
12185		H/V	74(Peak)/ 54(AV)	
14622		H/V	74(Peak)/ 54(AV)	
17059	H/V 74(Pe		74(Peak)/ 54(AV)	
19496	-	H/V	74(Peak)/ 54(AV)	
21933		H/V	74(Peak)/ 54(AV)	
24370		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 54 Mbps

Operation Mode: Transmitting under CH11 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
4924	48.08 (PK)	Н	74(Peak)/ 54(AV)
4924	47.64 (PK)	V	74(Peak)/ 54(AV)
7368	-	H/V	74(Peak)/ 54(AV)
9848	-	H/V	74(Peak)/ 54(AV)
12310	-	H/V	74(Peak)/ 54(AV)
14772	-	H/V	74(Peak)/ 54(AV)
17234	H/V		74(Peak)/ 54(AV)
19696	-	H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 54 Mbps

Date: 2014-09-03




Please refer to the following test plots for details:

CH01 for 11g at 54Mbps: Horizontal



CH01 for 11g at 54Mbps: Vertical



he report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Date: 2014-09-03



CH06 for 11g at 54Mbps: Vertical



CH06 for 11g at 54Mbps: Horizontal



he report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Date: 2014-09-03



CH11 for 11g at 54Mbps: Vertical



CH11 for 11g at 54Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2014-09-03



Operation Mode: Transmitting under CH01 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	/m) Antenna Polarity Limit@3m (d	
4824.00	48.82 (PK)	Н	74(Peak)/ 54(AV)
4824.00	48.09 (PK)	V	74(Peak)/ 54(AV)
7236.00	1	H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V 74(Peak)/	
19296	296 H/V		74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

Operation Mode: Transmitting under CH06 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03bc V/m)	@3m (dB \u03m V/m) Antenna Polarity Limit@3m (
4874.00	48.62 (PK)	Н	74(Peak)/ 54(AV)	
4874.00	48.08 (PK)	V	74(Peak)/ 54(AV)	
7311.00		H/V	74(Peak)/ 54(AV)	
9748.00		H/V	74(Peak)/ 54(AV)	
12185		H/V	74(Peak)/ 54(AV)	
14622		H/V	74(Peak)/ 54(AV)	
17059	H/V		74(Peak)/ 54(AV)	
19496		H/V	74(Peak)/ 54(AV)	
21933		H/V	74(Peak)/ 54(AV)	
24370		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

Report No: FCC1408087-01 Page 24 of 91

Date: 2014-09-03



Operation Mode: Transmitting under CH11 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)	
4924	48.29 (PK)	Н	74(Peak)/ 54(AV)	
4924	48.63 (PK)	V	74(Peak)/ 54(AV)	
7368		H/V	74(Peak)/ 54(AV)	
9848		H/V	74(Peak)/ 54(AV)	
12310		H/V	74(Peak)/ 54(AV)	
14772		H/V	74(Peak)/ 54(AV)	
17234		H/V	74(Peak)/ 54(AV)	
19696	H/V		74(Peak)/ 54(AV)	
22158		H/V	74(Peak)/ 54(AV)	
24620		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode at 11Mbps

Date: 2014-09-03




Please refer to the following test plots for details:

CH01 for 11b at 11Mbps: Horizontal



CH01 for 11b at 11Mbps: Vertical



he report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Date: 2014-09-03



CH06 for 11b at 11Mbps: Vertical



CH06 for 11b at 11Mbps: Horizontal



he report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Date: 2014-09-03



CH11 for 11b at 11Mbps: Vertical



CH11 for 11b at 11Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Date: 2014-09-03



Operation Mode: Transmitting under CH01 for 11n HT20 at 6.5Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4824.00	48.35 (PK)	Н	74(Peak)/ 54(AV)
4824.00	48.59 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00	-	H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V 74(Peak)/ 5	
16684		H/V	74(Peak)/ 54(AV)
19296	-	H/V	74(Peak)/ 54(AV)
21708	H/V 74(Peak)/		74(Peak)/ 54(AV)
24120	-	H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 6.5Mbps

Operation Mode: Transmitting under CH06 for 11n HT20 at 6.5Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	V/m) Antenna Polarity Limit@3m		
4874.00	48.54 (PK)	Н	74(Peak)/ 54(AV)	
4874.00	47.69 (PK)	V	74(Peak)/ 54(AV)	
7311.00		H/V	74(Peak)/ 54(AV)	
9748.00		H/V	74(Peak)/ 54(AV)	
12185		H/V	74(Peak)/ 54(AV)	
14622		H/V	74(Peak)/ 54(AV)	
17059		H/V	74(Peak)/ 54(AV)	
19496		H/V	74(Peak)/ 54(AV)	
21933	-	H/V	74(Peak)/ 54(AV)	
24370		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 6.5Mbps

Report No: FCC1408087-01 Page 29 of 91

Date: 2014-09-03



Operation Mode: Transmitting under CH11 for 11n HT20 at 6.5Mbps

	0		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4924	46.69 (PK)	Н	74(Peak)/ 54(AV)
4924	48.14 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 6.5Mbps

Date: 2014-09-03




Please refer to the following test plots for details:

CH01 for 11n HT20 at 6.5Mbps: Horizontal



CH01 for 11n HT20 at 6.5Mbps: Vertical




he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Date: 2014-09-03



CH06 for 11n HT20 at 6.5Mbps: Vertical



CH06 for 11n HT20 at 6.5Mbps: Horizontal



he report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Date: 2014-09-03



CH11 for 11n HT20 at 6.5Mbps: Vertical



CH11 for 11n HT20 at 6.5Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Report No: FCC1408087-01 Page 33 of 91

Date: 2014-09-03



7.0 6dB Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW) \geq 3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 Test Result

Report No: FCC1408087-01 Page 34 of 91

Date: 2014-09-03



6dB Occupied Bandwidth

EUT		TABLET PC		Model		TouchSmart SDS		
Mode	Mode 80		302.11b	02.11b Input Volta		tage	AC	120V
Temperat	ure	24	4 deg. C,	Humidity		56% RH		
Channel				Bandwidth Minimum Limit (MHz) P		Pass/ Fail		
1		2412	1	10.02			0.5	Pass
6		2437	1	10	.02		0.5	Pass
11		2462	1	10.02			0.5	Pass
1		2412	11	9.30			0.5	Pass
6		2437	11	9.	30		0.5	Pass
11		2462	11	9.	30		0.5	Pass


Page 35 of 91

Report No: FCC1408087-01

Date: 2014-09-03



1. 802.11b at 1Mbps of CH01



Date: 22.AUG.2014 11:21:32


Page 36 of 91

Report No: FCC1408087-01

Date: 2014-09-03



2. 802.11b at 1Mbps of CH06




Date: 22.AUG.2014 11:37:09

Report No: FCC1408087-01 Page 37 of 91

Date: 2014-09-03



3. 802.11b at 1Mbps of CH11



Date: 22.AUG.2014 11:41:15


Page 38 of 91

Report No: FCC1408087-01

Date: 2014-09-03



4. 802.11b at 11Mbps of CH01



Date: 22.AUG.2014 11:28:47


Page 39 of 91

Report No: FCC1408087-01

Date: 2014-09-03



5. 802.11b at 11Mbps of CH06



Date: 22.AUG.2014 11:31:15


Page 40 of 91

Report No: FCC1408087-01

Date: 2014-09-03



6. 802.11b at 11Mbps of CH11



Date: 22.AUG.2014 11:48:08

Report No: FCC1408087-01 Page 41 of 91

Date: 2014-09-03



6dB Occupied Bandwidth

EUT		TA	BLET PC		Model		TouchSmart SDS	
Mode		8	302.11g		Input Vol	tage	A	C120V
Temperat	ure	24	4 deg. C,		Humidity	,	5	6% RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)		andwidth Hz)		num Limit MHz)	Pass/ Fail
1		2412	54	16	3.38		0.5	Pass
6		2437	54	16	5.38	3 0.5		Pass
11		2462	54	16	5.38		0.5	Pass

Page 42 of 91


Report No: FCC1408087-01

Date: 2014-09-03



Test Plots:

1. 802.11g at 54Mbps of CH01



Date: 22.AUG.2014 11:26:20


Page 43 of 91

Report No: FCC1408087-01

Date: 2014-09-03



2. 802.11g at 54Mbps of CH06




Date: 22.AUG.2014 11:34:04

Report No: FCC1408087-01 Page 44 of 91

Date: 2014-09-03



3. 802.11g at 54Mbps of CH11



Date: 22.AUG.2014 11:44:47

Report No: FCC1408087-01 Page 45 of 91

Date: 2014-09-03



6dB Occupied Bandwidth

EUT		TA	BLET PC		Model		TouchSmart SDS	
Mode		802	.11n HT20		Input Vol	tage	AC	120V
Temperat	ure	24	4 deg. C,		Humidity		56%	% RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)		ındwidth Hz)		mum Limit MHz)	Pass/ Fail
1		2412	6.5M	17	.58		0.5	Pass
6		2437	6.5M	17	.58		0.5	Pass
11		2462	6.5M	17	.58		0.5	Pass

Page 46 of 91


Report No: FCC1408087-01

Date: 2014-09-03



Test Plots:

1. 802.11n at HT20 of CH01




Date: 22.AUG.2014 11:57:15

Report No: FCC1408087-01 Page 47 of 91

Date: 2014-09-03



2. 802.11n at HT20 of CH06



Date: 22.AUG.2014 11:53:59


Page 48 of 91

Report No: FCC1408087-01

Date: 2014-09-03



3. 802.11n at HT20 of CH11



Date: 22.AUG.2014 11:52:03

Date: 2014-09-03



Page 49 of 91

8. Maximum Output Power

8.1 Test Setup



8.2 Limits of Maximum Output Power

The Maximum Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the Average power was measured

Page 50 of 91

Date: 2014-09-03

Report No: FCC1408087-01



8.4Test Results

EUT		TABLET PC		Model		TouchSmart SDS		
Mode		802.11b		Input	Input Voltage		AC120V	
Temperat	ure	24 deg	g. C,	Humidity			56% RH	
Channel	Cha	annel Frequency Max. Power O (MHz) (dBm)		Output	Power Limit (dBm)		Pass/ Fail	
1		2412	12.82		30		Pass	
6		2437	12.32		30		Pass	
11		2462	11.70		30		Pass	

Note: 1. At finial test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT		TABLET PC		Model		TouchSmart SDS	
Mode		802.11g		Input Voltage			AC120V
Temperati	ure	24 deg	24 deg. C, Humidity		56% RH		
Channel	Cha	annel Frequency	Max. Power C	Output Power		Limit	Pass/ Fail
Chamici		(MHz)	(dBm)		(dBm)		
1		2412	11.62		30		Pass
6		2437	11.15		30		Pass
11		2462	10.51		30		Pass

Note: 1. At finial test to get the worst-case emission at 54Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded

Report No: FCC1408087-01 Page 51 of 91

Date: 2014-09-03



EUT		TABLET PC		Model		TouchSmart SDS		
Mode		802.11n (HT20)		Input	Input Voltage		AC120V	
Temperat	ure	24 deg	g. C,	Hur	Humidity		56% RH	
Channel	Cha	annel Frequency	Max. Power C	wer Output		Limit	Pass/ Fail	
Chamilei		(MHz)	(MHz) (dBm)		(dBm)			
1		2412	10.33		30		Pass	
6		2437 9.		30)	Pass	
11		2462	9.24		30		Pass	

Note: 1. At finial test to get the worst-case emission at 6.5Mbps of 11n HT20 for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded


Report No: FCC1408087-01 Page 52 of 91

Date: 2014-09-03



9. Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW \geq 30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = \max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be ≤ 8 dBm.

Report No: FCC1408087-01 Page 53 of 91

Date: 2014-09-03



9.4Test Result

EUT	EUT TABLE		ET PC Mo		odel Tou		uchSmart SDS
Mode	Mode 802.11b 11N		1Mbps Input Vo		Voltage		AC120V
Temperat	ure	24 deg	24 deg. C, Humidity		nidity		56% RH
Channel	Cha	annel Frequency	Final RF Po	wer	Maximu	n Limit	Pass/ Fail
Chamilei		(MHz)	Level (dBm)		(dB	m)	
			11Mbps	S			
1		2412 -7.49			8		Pass
6		2437 -5.41			8		Pass
11		2462	-5.00		8		Pass

EUT	JT TABLE		T PC Mo		odel To		uchSmart SDS
Mode	Mode 802.11b 1Mbp		1 Mbps	Input Voltage		AC120V	
Temperat	ure	24 deg	g. C,	Humidity		56% RH	
Channel	Cha	annel Frequency	Final RF Po	wer	Maximum Limit		Pass/ Fail
Chamie	(MHz)		Level in (dBm)		(dBm)		
			1Mbps				
1		2412 -7		8			Pass
6		2437	-5.99		8		Pass
11		2462	-4.10		8		Pass

Report No: FCC1408087-01 Page 54 of 91

Date: 2014-09-03



EUT	TABLE		ET PC Mo		odel Tou		uchSmart SDS	
Mode	Mode 802.11g 54Mbps Input Vo		Voltage		AC120V			
Temperati	ure	24 deg	g. C,	Hur	Humidity		56% RH	
Channel	Cha	annel Frequency	Final RF Power		Maximum Limit		Pass/ Fail	
Chamici		(MHz)	Level in (dI	Bm) (dBr		m)		
			6Mbps					
1		2412	-16.26		8		Pass	
6		2437 -15.04			8		Pass	
11		2462	-14.10		8		Pass	


EUT	TABLE		ET PC Mo		odel Tou		ichSmart SDS	
Mode	Mode 802.11n HT20 6.5Mbps Input V		Voltage		AC120V			
Temperati	ure	24 deg	g. C,	Hur	umidity		56% RH	
Channel	Channel Frequency		Final RF Power		Maximum Limit		Pass/ Fail	
Chamilei		(MHz)	Level (dB		(dBm)			
			HT20					
1		2412	-13.10		8		Pass	
6		2437	-12.19	-12.19			Pass	
11		2462	-12.14		8		Pass	

Date: 2014-09-03



9.5 Photo of Power Spectral Density Measurement

1.802.11b at 11Mbps of CH01



Date: 22.AUG.2014 18:34:51


Page 56 of 91

Report No: FCC1408087-01

Date: 2014-09-03



2. 802.11b at 11Mbps at CH06



Date: 22.AUG.2014 18:35:25


Page 57 of 91

Report No: FCC1408087-01

Date: 2014-09-03



3. 802.11b at 11Mbps of CH11



Date: 22.AUG.2014 18:36:24


Page 58 of 91

Report No: FCC1408087-01

Date: 2014-09-03



4. 802.11b at 1Mbps of CH1



Date: 22.AUG.2014 18:23:47


Page 59 of 91

Report No: FCC1408087-01

Date: 2014-09-03



5. 802.11b at 1Mbps of CH6



Date: 22.AUG.2014 18:24:32


Page 60 of 91

Report No: FCC1408087-01

Date: 2014-09-03



6. 802.11b at 1Mbps of CH11



Date: 22.AUG.2014 18:25:08


Page 61 of 91

Report No: FCC1408087-01

Date: 2014-09-03



7. 802.11g at 54Mbps of CH1



Date: 22.AUG.2014 18:33:50


Page 62 of 91

Report No: FCC1408087-01

Date: 2014-09-03



8. 802.11g at 54Mbps of CH6



Date: 22.AUG.2014 18:29:32


Page 63 of 91

Report No: FCC1408087-01

Date: 2014-09-03



9. 802.11g at 54Mbps of CH11



Date: 22.AUG.2014 18:26:47


Page 64 of 91

Report No: FCC1408087-01

Date: 2014-09-03



10. 802.11n at HT20 of CH01



Date: 22.AUG.2014 19:05:23


Page 65 of 91

Report No: FCC1408087-01

Date: 2014-09-03



11. 802.11n at HT20 of CH06



Date: 22.AUG.2014 19:03:20


Page 66 of 91

Report No: FCC1408087-01

Date: 2014-09-03



12. 802.11n at HT20 of CH11



Date: 22.AUG.2014 19:00:53

Page 67 of 91


Report No: FCC1408087-01

Date: 2014-09-03



10 Out of Band Measurement

10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test.(Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=100, VBW=300 kHz. A conducted measurement used

10.4 Test Result

Please see next pages

Note: 1. this is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), after pre-test. It was found that the worse radiated emission was get at the lying position. the worse case was recorded

2. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Date: 2014-09-03




For 802.11b mode

CH01 at 11Mbps

10.4 Band-edge and Restricted band Measurement

EUT	TA	TABLET PC		TouchSmart SDS					
Mode	Keeping Transmitting		Input Voltage	AC120V					
Temperature	24 deg. C,		Humidity	56% RH					
Test Result:	Pass		Detector	PK					
2400	PK (dBμV/m)	66.9	T ::4	$74(dB\mu V/m)$					
	AV (dBμV/m)	48.3	Limit	54(dBμV/m)					
2390	PK (dBμV/m)	39.1	Limit	74(dBμV/m)					
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$					

Test Figure:



Date: 22.AUG.2014 18:49:37

Date: 2014-09-03




CH11 at 11Mbps

10.4 Band-edge and Restricted band Measurement

EUT	TA	BLET PC	Model	TouchSmart SDS
Mode	Keeping	g Transmitting	Input Voltage	AC120V
Temperature	24	deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
2483.5	PK (dBµV/m)	47.9	Limit	74(dBμV/m)
	AV (dBμV/m)	AV (dBμV/m)		54(dBμV/m)

Test Figure:



Date: 22.AUG.2014 18:59:46

Date: 2014-09-03




For 802.11b mode

CH01 at 1Mbps

10.4 Band-edge and Restricted band Measurement

EUT	TA	TABLET PC		TouchSmart SDS					
Mode	Keeping Transmitting		Input Voltage	AC120V					
Temperature	24 deg. C,		Humidity	56% RH					
Test Result:	Pass		Detector	PK					
2400	PK (dBμV/m)	67.2	T 10014	$74(dB\mu V/m)$					
	AV (dBμV/m)	45.9	Limit	54(dBμV/m)					
2390	PK (dBμV/m)	41.6	Limit	74(dBμV/m)					
	AV (dBμV/m)		Limit	54(dBμV/m)					

Test Figure:



Date: 22.AUG.2014 18:37:57

Date: 2014-09-03




CH11 at 1Mbps

10.4 Band-edge and Restricted band Measurement

EUT	TABLET PC		Model	TouchSmart SDS
Mode	Keeping Transmitting		Input Voltage	AC120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m)	46.7	T **4	74(dBμV/m)
	AV (dBμV/m)		Limit	54(dBμV/m)

Test Figure:



Date: 22.AUG.2014 18:57:32

Date: 2014-09-03




For 802.11g mode

CH01 at 6Mbps

10.4 Band-edge and Restricted band Measurement

EUT	TABLET PC		Model	TouchSmart SDS
Mode	Keeping Transmitting		Input Voltage	AC120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400	PK (dBμV/m)	64.6	T ::4	$74(dB\mu V/m)$
	AV (dBμV/m)	42.9	Limit	$54(dB\mu V/m)$
2390	PK (dBμV/m)	40.7	Limit	74(dBμV/m)
	AV (dBμV/m)			$54(dB\mu V/m)$

Test Figure:



Date: 22.AUG.2014 18:48:11

Page 73 of 91

Report No: FCC1408087-01

Date: 2014-09-03




CH11 at 6Mbps

10.4 Band-edge and Restricted band Measurement

EUT	TABLET PC		Model		TouchSmart SDS
Mode	Keeping Transmitting		Input Voltage		AC120V
Temperature	24 deg. C,		Humidity		56% RH
Test Result:	Pass		Detector		PK
2483.5	PK (dBµV/m)	46.1	T 1 14	74(dBμV/m)	
	AV (dBμV/m)		Limit		$54(dB\mu V/m)$

Test Figure:



Date: 22.AUG.2014 18:58:52

Note: The Max. FS in Restrict Band are measured in conventional method.

Date: 2014-09-03




For 802.11n (HT20) mode

CH01 at 6.5Mbps

10.4 Band-edge and Restricted band Measurement

EUT	TABLET PC		Model	TouchSmart SDS
Mode	Keeping Transmitting		Input Voltage	AC120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400	PK (dBμV/m)	65.1	T ::4	74(dBμV/m)
	AV (dBμV/m)	43.2	Limit	54(dBμV/m)
2390	PK (dBµV/m)	41.5	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Date: 22.AUG.2014 18:51:56

Note: The Max. FS in Restrict Band are measured in conventional method.

Date: 2014-09-03




CH11 at 6.5Mbps

10.4 Band-edge and Restricted band Measurement

EUT	TABLET PC		Model	TouchSmart SDS
Mode	Keeping Transmitting		Input Voltage	AC120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBµV/m)	46.9	T 10014	74(dBμV/m)
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Date: 22.AUG.2014 18:56:03

Note: The Max. FS in Restrict Band are measured in conventional method.

Date: 2014-09-03



Page 76 of 91

11.0 Antenna Requirement

11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

Integral antenna used. The maximum Gain of the antennas is 1.0dBi.

Report No: FCC1408087-01 Page 77 of 91

Date: 2014-09-03




12.0 FCC ID Label

FCC ID: 2ACZ8-OB1001

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 78 of 91

Report No: FCC1408087-01

Date: 2014-09-03



13.0 Photo of testing

Conducted Emission Test Setup:



Date: 2014-09-03



Radiated Emission Test Setup:





he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2014-09-03



Photographs - EUT

Outside view





he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Date: 2014-09-03



Outside view





he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Date: 2014-09-03



Outside view





he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Report No: FCC1408087-01 Page 83 of 91

Date: 2014-09-03



Outside view



Date: 2014-09-03



Inside view





he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2014-09-03



Inside view





he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Date: 2014-09-03



Inside view





he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2014-09-03



Inside view





he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd vill not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2014-09-03



Inside view





he report refers only to the sample tested and does not apply to the bulk.

ne report reters only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2014-09-03



Inside view





he report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd vill not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2014-09-03



Inside view





he report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to


Page 91 of 91

Report No: FCC1408087-01

Date: 2014-09-03



Inside view



End of the report