

FCC Test Report

Part 15 subpart C

Client Information:

Applicant: Hamee Corp.

Applicant add.: 5F, 2-9-39, Sakae-cho, Odawara, Kanagawa 250-0011, Japan

Product Information:

EUT Name: TSUMTSUM Bluetooth speaker

Brand Name: Hamee

Model No.: 276-883808

Derivative model No.: 276-883815
(All the same except appearance and model name)

FCC ID: 2AD2X8838

Standards: FCC PART 15 Subpart C: 2016 section 15.247

Test procedure used: ANSI C63.10-2013

Prepared By:

ATS Electronic Technology Co., Ltd.

Add. : 3/F, Building A, No. 1 Hedong Three Road, Jinxia Community, Changan Town,
DongGuan City, GuangDong, P.R.China

Date of Receipt: 2017.5.25

Date of Test: 2017.5.26 to 2017.6.08

Date of Issue: 2017.6.09

Test Result: Pass

This device described above has been tested by ATT Product Service Co., Ltd, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

*This test report must not be used by the client to claim product endorsement by any agency of the U.S. government.

Reviewed by:

A handwritten signature in black ink that reads "Rook Huang".

Approved by:

A handwritten signature in black ink that reads "Simon Zeng".

1 Contents

	Page
COVER PAGE	
1 CONTENTS	2
2 TEST SUMMARY	4
2.1 COMPLIANCE WITH FCC PART 15 SUBPART C	4
2.2 TEST LOCATION	5
2.3 MEASUREMENT UNCERTAINTY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT	6
3.2 DESCRIPTION OF TEST CONDITIONS	8
3.3 TEST PERIPHERAL LIST	9
3.4 EUT PERIPHERAL LIST	9
4 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
5 TEST RESULT	11
5.1 ANTENNA REQUIREMENT	11
5.1.1 Standard requirement	11
5.1.2 EUT Antenna	11
5.2 CONDUCTION EMISSIONS MEASUREMENT	12
5.2.1 Applied procedures / Limit	12
5.2.2 Test procedure	12
5.2.3 Test setup	12
5.2.4 Test results	13
5.3 RADIATED EMISSIONS MEASUREMENT	15
5.3.1 Applied procedures / Limit	15
5.3.2 Test setup	15
5.3.3 Test procedure	18
5.3.4 Test Result	19
5.3.5 TEST RESULTS (Restricted Bands Requirements)	30
5.4 BANDWIDTH TEST	31
5.4.1 Applied procedures / Limit	31
5.4.2 Test procedure	31
5.4.3 Deviation from standard	31
5.4.4 Test setup	31
5.4.5 Test results	32
5.5 CARRIER FREQUENCIES SEPARATED	38
5.5.1 Applied procedures / Limit	38
5.5.2 Test procedure	38

5.5.3	Deviation from standard.....	38
5.5.4	Test setup	38
5.5.5	Test results	39
5.6	HOPPING CHANNEL NUMBER.....	45
5.6.1	Applied procedures / Limit	45
5.6.2	Test procedure.....	45
5.6.3	Deviation from standard.....	45
5.6.4	Test setup	45
5.6.5	Test result	46
5.7	DWELL TIME.....	47
5.7.1	Applied procedures / Limit	47
5.7.2	Test procedure.....	47
5.7.3	Deviation from standard.....	47
5.7.4	Test setup	47
5.7.5	Test result	48
5.8	MAXIMUM PEAK OUTPUT POWER.....	66
5.8.1	Applied procedures / Limit	66
5.8.2	Test procedure.....	66
5.8.3	Deviation from standard.....	66
5.8.4	Test setup	66
5.8.5	Test results	67
5.9	BAND EDGE	73
5.9.1	Applied procedures / Limit	73
5.9.2	Test procedure.....	73
5.9.3	Deviation from standard.....	73
5.9.4	Test setup	73
5.9.5	Test results	74
5.10	CONDUCTED SPURIOUS EMISSIONS	80
5.10.1	Applied procedures / Limit	80
5.10.2	Test procedure.....	80
5.10.3	Deviation from standard.....	80
5.10.4	Test setup	80
5.10.5	Test results	81
6	PHOTOGRAPHS.....	90
6.1	RADIATED SPURIOUS EMISSION TEST SETUP	90
6.2	CONDUCTED EMISSION TEST SETUP.....	91
7	APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	92

2 Test Summary

2.1 Compliance with FCC Part 15 subpart C

Test	Test Requirement	Standard Paragraph	Result
Antenna Requirement	FCC Part 15 C:2016	Section 15.247(c)	PASS
Conduction Emissions	FCC Part 15 C:2016	Section 15.207(a)	PASS
Radiated Emissions	FCC Part 15 C:2016	Section 15.247(d)	PASS
Carrier Frequencies Separated	FCC Part 15 C:2016	Section 15.247(a)(1)	PASS
Hopping Channel Number	FCC Part 15 C:2016	Section 15.247(a)(1) (iii)	PASS
Dwell Time	FCC Part 15 C:2016	Section 15.247(a)(1) (iii)	PASS
Maximum Peak Output Power	FCC Part 15 C:2016	Section 15.247(b)	PASS
Band edge	FCC Part 15 C:2016	Section 15.247(d)	PASS
Conducted Spurious Emissions	FCC Part 15 C:2016	Section 15.247(d)	PASS

2.2 Test Location

All tests were performed at:

ATT Product Service Co., Ltd.

No. 3, ChangLianShan Industrial Park, ChangAn Town, DongGuan City, GuangDong, China.

The FCC Registration: 923232

2.3 Measurement Uncertainty

All measurements involve certain levels of uncertainties, The following measurements uncertainty Levels have estimated based on ANSI C63.10:2013, the maximum value of the uncertainty as below

Test Item	Uncertainty
Uncertainty for Conduction emission test	2.44dB
Uncertainty for Radiation Emission test (150KHz-30MHz)	3.21dB
Uncertainty for Radiation Emission test (30MHz-1GHz)	3.52 dB (Polarize: V)
	3.54 dB (Polarize: H)
Uncertainty for Radiation Emission test (1GHz to 25GHz)	5.54dB (Polarize: V)
	3.56dB (Polarize: H)
Uncertainty for radio frequency	1×10 ⁻⁹
Uncertainty for conducted RF Power	0.65dB

3 General Information


3.1 General Description of EUT

Manufacturer:	Zhongshan Baolijin Electronic Co.,Ltd.
Manufacturer Address:	Baolijin Industrial Park,Jinfeng Road,No.6 Industrial Area,Nanlang Town,Zhongshan,Guangdong,P.R.China
EUT Name:	TSUMTSUM Bluetooth speaker
Model No:	276-883808
Derivative model No.:	276-883815 (All the same except appearance and model name)
Brand Name:	Hamee
Operation frequency:	2402 MHz to 2480 MHz
Number of channel:	79
Modulation Technology:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Bluetooth version:	4.2 without BLE
H/W No.:	V 2.1
S/W No.:	V1.1
Antenna Type:	Integral Antenna
Antenna Gain:	Maximum 0.07 dBi
Power Supply Range:	5Vdc from micro-USB or 3.7Vdc from battery
Power Supply:	5Vdc from computer 3.7Vdc from battery
Power Cord:	N/A
Output power (max) :	1Mbps: 4.446dBm
	2Mbps: 4.626dBm
	3Mbps: 5.048dBm
Model description:	
Note:	
1.	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

Description of Channel:					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.2 Description of Test conditions

- (1) EUT was tested in normal configuration (Please See following Block diagram)



- (2) E.U.T. test conditions:

15.31(e): For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

- (3) Test frequencies:

According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and. If required reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

- (4) Frequency range of radiated measurements:

According to the 15.33, the test range will be up to the tenth harmonic of the highest fundamental frequency.

- (5) Pre-test the EUT in GFSK, $\pi/4$ -DQPSK, 8DPSK mode, all transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet and conducted to determine the worst-case mode, only the worst-case results(GFSK:1Mbps/8DPSK :3Mbps) are recorded in this report.
- (6) The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

3.3 Test Peripheral List

No.	Equipment	Manufacturer	FCC approved	Model No.	Serial No.	Power cord	signal cable
1	Lap top	lenovo	DOC	7457	7457A82	N/A	N/A
2	AC adapter	Stos	VOC	QX6.5W7 5100FG	N/A	N/A	N/A

3.4 EUT Peripheral List

No.	Equipment	Manufacturer	EMC Compliance	Model No.	Serial No.	Power cord	signal cable
1	N/A	N/A	N/A	N/A	N/A	N/A	N/A

4 Equipments List for All Test Items

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	Spectrum Analyzer	ADVANTEST	R3182	150900201	2017.06.27	2018.06.26
2	EMI Measuring Receiver	Schaffner	SCR3501	235	2017.06.27	2018.06.26
3	Low Noise Pre Amplifier	Tsj	MLA-10K01-B01-27	1205323	2017.06.27	2018.06.26
4	Low Noise Pre Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2017.06.27	2018.06.26
5	TRILOG Super Broadband test Antenna	SCHWARZBECK	VULB9160	9160-3206	2017.06.27	2018.06.26
6	Broadband Horn Antenna	SCHWARZBECK	BBHA9120D	452	2017.06.27	2018.06.26
7	SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170367	2017.06.27	2018.06.26
8	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2017.06.27	2018.06.26
9	EMI Test Receiver	R&S	ESCI	100124	2017.06.27	2018.06.26
10	LISN	Kyoritsu	KNW-242	8-837-4	2017.06.27	2018.06.26
11	LISN	Kyoritsu	KNW-407	8-1789-3	2017.06.27	2018.06.26
12	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2017.06.27	2018.06.26
13	Loop Antenna	ARA	PLA-1030/B	1029	2017.06.27	2018.06.26
14	EMI Test Receiver	Rohde & Schwarz	ESIB26	100394	2017.06.27	2018.06.26
15	Radiated Cable 1# (30MHz-1GHz)	FUJIKURA	5D-2W	01	2017.01.04	2018.01.03
16	Radiated Cable 2# (1GHz -25GHz)	FUJIKURA	10D2W	02	2017.01.04	2018.01.03
17	Conducted Cable 1#(9KHz-30MHz)	FUJIKURA	1D-2W	01	2017.01.04	2018.01.03
18	SMA Antenna connector (Impedance:50OHM, cable loss:0.5dBm)	Dosin	Dosin-SMA	N/A	N/A	N/A

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test Result

5.1 Antenna Requirement

5.1.1 Standard requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

5.1.2 EUT Antenna

The antenna is Integral Antenna and no consideration of replacement. Antenna gain is Maximum 0.07 dBi from 2.4GHz to 2.5GHz.

5.2 Conduction Emissions Measurement

5.2.1 Applied procedures / Limit


Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

Note: Decreases with the logarithm of the frequency.

5.2.2 Test procedure


EUT was placed upon a wooden test table 0.8m above the horizontal metal reference plane and 0.4m from the vertical ground plane, and it was connected to an AMN. The closest distance between the boundary of the EUT and the surface of the AMN is 0.8m. All peripherals were connected to another AMN, and placed at a distance of 10cm from each other. A spectrum and receiver was connected to the RF output port of the AMN. Both average and quasi-peak value were detected.

5.2.3 Test setup



5.2.4 Test results


EUT:	TSUMTSUM Bluetooth speaker	Model Name. :	276-883808
Temperature:	24 °C	Relative Humidity:	55%
Pressure:	1010hPa	Test Date :	2017-05-31
Test Mode:	TX (1Mbps) CH00 (worst case)	Phase :	Line
Test Voltage :	5Vdc From PC input 120V/60Hz		



Remark: Factor = LISN factor + Cable Loss + Pulse limiter factor.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dB	Over dB	Detector	Comment
1		0.1524	31.15	10.02	41.17	65.86	-24.69	QP	
2		0.1524	14.68	10.02	24.70	55.86	-31.16	AVG	
3		1.5071	13.05	14.97	28.02	56.00	-27.98	QP	
4		1.5071	7.47	14.97	22.44	46.00	-23.56	AVG	
5		5.0633	22.99	17.02	40.01	60.00	-19.99	QP	
6	*	5.0633	21.31	17.02	38.33	50.00	-11.67	AVG	
7		28.1507	21.72	17.24	38.96	60.00	-21.04	QP	
8		28.1507	5.46	17.24	22.70	50.00	-27.30	AVG	

EUT:	TSUMTSUM Bluetooth speaker	Model Name. :	276-883808
Temperature:	24 °C	Relative Humidity:	55%
Pressure:	1010hPa	Test Date :	2017-05-31
Test Mode:	TX (1Mbps) CH00 (worst case)	Phase :	Neutral
Test Voltage :	5Vdc From PC input 120V/60Hz		



Remark: Factor = LISN factor + Cable Loss + Pulse limiter factor.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dB	Over dB	Detector	Comment
1		0.1573	33.31	10.02	43.33	65.60	-22.27	QP	
2		0.1573	13.78	10.02	23.80	55.60	-31.80	AVG	
3		1.5277	13.21	14.97	28.18	56.00	-27.82	QP	
4		1.5277	7.68	14.97	22.65	46.00	-23.35	AVG	
5		5.4294	20.42	17.02	37.44	60.00	-22.56	QP	
6	*	5.4294	20.34	17.02	37.36	50.00	-12.64	AVG	
7		28.1647	22.55	17.24	39.79	60.00	-20.21	QP	
8		28.1647	6.01	17.24	23.25	50.00	-26.75	AVG	

5.3 Radiated Emissions Measurement

5.3.1 Applied procedures / Limit


15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Frequency of Emission (MHz)	Field Strength		Measurement Distance (meters)
	$\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$	
0.009-0.49	2400/F(kHz)	/	300
0.49-1.705	24000/F(kHz)	/	30
1.705-30	30	/	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3


5.3.2 Test setup

Test Configuration:


1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:



3) 1 GHz to 25 GHz emissions:



5.3.3 Test procedure

EUT was placed upon a wooden test table which was placed on the turn table and operating in the mode as mentioned above. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. A receiving antenna was placed 3m away from the EUT. During testing, turn around the turn table and move the antenna from 1m to 4m to find the maximum field-strength reading. All peripherals were placed at a distance of 10cm between each other. Both horizontal and vertical antenna polarities were tested. The worst case emissions were reported.

For measurement at frequency above 1GHz

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

5.3.4 Test Result

Radiated Emissions Test Data Below 30MHz

EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	25 °C	Test Data	2017-05-31
Pressure:	1005 hPa	Relative Humidity:	60%
Test Mode :	TX	Test Voltage :	3.7Vdc from battery
Measurement Distance	3 m	Frequency Range	9KHz to 30MHz
RBW/VBW	9KHz~150KHz/RB 200Hz for QP, 150KHz~30MHz/RB 9KHz for QP		

No emission found between lowest internal used/generated frequencies to 30MHz.

Radiated Emissions Test Data Below 1GHz

EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	25 °C	Test Data	2017-05-31
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX (1Mbps) CH00 (worst case)	Test Voltage :	3.7Vdc from battery
Measurement Distance	3 m	Frequency Range	30MHz to 1GHz
RBW/VBW	100KHz / 300KHz for spectrum, RBW=120KHz for receiver.		

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
44.12	39.56	-16.85	22.71	40.00	-17.29	QP
62.00	36.74	-14.21	22.53	40.00	-17.47	QP
125.01	36.88	-9.69	27.19	43.50	-16.31	QP
272.28	38.32	-3.58	34.74	46.00	-11.26	QP

(b) Antenna polarization: vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
38.35	43.59	-18.65	24.94	40.00	-15.06	QP
56.40	39.12	-14.27	24.85	40.00	-15.15	QP
163.18	38.74	-8.26	30.48	43.50	-13.02	QP
235.82	41.73	-5.67	36.06	46.00	-9.94	QP

Note:

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss–Pre-amplifier

Radiated Emissions Test Data Above 1GHz

EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	25 °C	Test Data	2017-05-31
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	1Mbps	Test Voltage :	3.7Vdc from battery
Measurement Distance	3 m	Frequency Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average.		

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4804.00	51.29	5.06	56.35	74.00	-17.65	peak
4804.00	36.52	5.06	41.58	54.00	-12.42	AVG
7206.00	45.04	7.03	52.07	74.00	-21.93	peak
7206.00	29.29	7.03	36.32	54.00	-17.68	AVG

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4804.00	51.94	5.06	57.00	74.00	-17.00	peak
4804.00	35.15	5.06	40.21	54.00	-13.79	AVG
7206.00	46.29	7.03	53.32	74.00	-20.68	peak
7206.00	29.77	7.03	36.80	54.00	-17.20	AVG

Note:

8~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss–Pre-amplifier

Lowest channel: 2402 MHz

Data rate: 1Mbps

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4882.00	53.09	5.14	58.23	74.00	-15.77	peak
4882.00	36.28	5.14	41.42	54.00	-12.58	AVG
7323.00	44.90	7.54	52.44	74.00	-21.56	peak
7323.00	28.44	7.54	35.98	54.00	-18.02	AVG

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4882.00	51.91	5.14	57.05	74.00	-16.95	peak
4882.00	34.99	5.14	40.13	54.00	-13.87	AVG
7323.00	45.77	7.54	53.31	74.00	-20.69	peak
7323.00	29.51	7.54	37.05	54.00	-16.95	AVG

Note:

8~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss–Pre-amplifier

Middle Channel: 2441 MHz

Data rate: 1Mbps

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4960.00	51.56	5.22	56.78	74.00	-17.22	peak
4960.00	33.88	5.22	39.10	54.00	-14.90	AVG
7440.00	44.69	8.06	52.75	74.00	-21.25	peak
7440.00	29.02	8.06	37.08	54.00	-16.92	AVG

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4960.00	51.65	5.22	56.87	74.00	-17.13	peak
4960.00	33.86	5.22	39.08	54.00	-14.92	AVG
7440.00	44.70	8.06	52.76	74.00	-21.24	peak
7440.00	29.14	8.06	37.20	54.00	-16.80	AVG

Note:

8~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss–Pre-amplifier

Highest Channel: 2480 MHz

Data rate: 1Mbps

EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	25 °C	Test Data	2017-05-31
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	2Mbps	Test Voltage :	3.7Vdc from battery
Measurement Distance	3 m	Frequency Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average.		

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4804.00	52.42	5.06	57.48	74.00	-16.52	peak
4804.00	33.87	5.06	38.93	54.00	-15.07	AVG
7206.00	41.41	7.03	48.44	74.00	-25.56	peak
7206.00	25.59	7.03	32.62	54.00	-21.38	AVG

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4804.00	49.43	5.06	54.49	74.00	-19.51	peak
4804.00	31.90	5.06	36.96	54.00	-17.04	AVG
7206.00	46.43	7.03	53.46	74.00	-20.54	peak
7206.00	27.31	7.03	34.34	54.00	-19.66	AVG

Note:

8~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss–Pre-amplifier

Lowest channel: 2402 MHz

Data rate: 2Mbps

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4882.00	52.49	5.14	57.63	74.00	-16.37	peak
4882.00	38.14	5.14	43.28	54.00	-10.72	AVG
7323.00	42.88	7.54	50.42	74.00	-23.58	peak
7323.00	22.84	7.54	30.38	54.00	-23.62	AVG

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4882.00	47.86	5.14	53.00	74.00	-21.00	peak
4882.00	33.82	5.14	38.96	54.00	-15.04	AVG
7323.00	40.83	7.54	48.37	74.00	-25.63	peak
7323.00	28.45	7.54	35.99	54.00	-18.01	AVG

Note:

8~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss–Pre-amplifier

Middle Channel: 2441 MHz

Data rate: 2Mbps

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4960.00	49.89	5.22	55.11	74.00	-18.89	peak
4960.00	31.17	5.22	36.39	54.00	-17.61	AVG
7440.00	41.83	8.06	49.89	74.00	-24.11	peak
7440.00	22.88	8.06	30.94	54.00	-23.06	AVG

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4960.00	52.17	5.22	57.39	74.00	-16.61	peak
4960.00	33.53	5.22	38.75	54.00	-15.25	AVG
7440.00	40.30	8.06	48.36	74.00	-25.64	peak
7440.00	25.08	8.06	33.14	54.00	-20.86	AVG

Note:

8~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss–Pre-amplifier

Highest Channel: 2480 MHz

Data rate: 2Mbps

EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	25 °C	Test Data	2017-05-31
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	3Mbps	Test Voltage :	3.7Vdc from battery
Measurement Distance	3 m	Frequency Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average.		

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4804.00	51.57	5.06	56.63	74.00	-17.37	peak
4804.00	35.21	5.06	40.27	54.00	-13.73	AVG
7206.00	45.13	7.03	52.16	74.00	-21.84	peak
7206.00	27.77	7.03	34.80	54.00	-19.20	AVG

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4804.00	51.61	5.06	56.67	74.00	-17.33	peak
4804.00	36.16	5.06	41.22	54.00	-12.78	AVG
7206.00	45.61	7.03	52.64	74.00	-21.36	peak
7206.00	27.89	7.03	34.92	54.00	-19.08	AVG

Note:

8~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss–Pre-amplifier

Lowest Channel: 2402 MHz

Data rate: 3Mbps

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4882.00	52.76	5.14	57.90	74.00	-16.10	peak
4882.00	37.29	5.14	42.43	54.00	-11.57	AVG
7323.00	44.22	7.54	51.76	74.00	-22.24	peak
7323.00	26.56	7.54	34.10	54.00	-19.90	AVG

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4882.00	51.58	5.14	56.72	74.00	-17.28	peak
4882.00	36.00	5.14	41.14	54.00	-12.86	AVG
7323.00	45.09	7.54	52.63	74.00	-21.37	peak
7323.00	27.63	7.54	35.17	54.00	-18.83	AVG

Note:

8~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss–Pre-amplifier

Middle Channel: 2441 MHz

Data rate: 3Mbps

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4960.00	51.23	5.22	56.45	74.00	-17.55	peak
4960.00	34.89	5.22	40.11	54.00	-13.89	AVG
7440.00	44.01	8.06	52.07	74.00	-21.93	peak
7440.00	27.14	8.06	35.20	54.00	-18.80	AVG

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector Type
4960.00	51.32	5.22	56.54	74.00	-17.46	peak
4960.00	34.87	5.22	40.09	54.00	-13.91	AVG
7440.00	44.02	8.06	52.08	74.00	-21.92	peak
7440.00	27.26	8.06	35.32	54.00	-18.68	AVG

Note:

8~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss–Pre-amplifier

Highest channel: 2480 MHz

Data rate: 3Mbps

5.3.5 TEST RESULTS (Restricted Bands Requirements)

EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	25 °C	Test Data	2017-05-31
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX 1Mbps/ 2Mbps/ 3Mbps	Test Voltage :	3.7Vdc from battery
RBW/VBW	1MHz/3MHz for Peak, 1MHz/10Hz for Average.		
Note:	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz. 3. The data of 2390MHz and 2483.5MHz was the worst.		

Test Mode	Ant.Pol. H/V	Freq. (MHz)	Reading		Ant/CF CF(dB)	Act		Limit	
			Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)
Data rate 1Mbps	V	2390.0	60.70	48.98	-5.79	54.91	43.19	74.00	54.00
	H	2390.0	60.95	50.06	-5.79	55.16	44.27	74.00	54.00
	V	2483.5	63.69	52.61	-4.98	58.71	47.63	74.00	54.00
	H	2483.5	60.79	47.86	-4.98	55.81	42.88	74.00	54.00
Data rate 2Mbps	V	2390.0	59.85	48.13	-5.79	54.06	42.34	74.00	54.00
	H	2390.0	59.61	48.72	-5.79	53.82	42.93	74.00	54.00
	V	2483.5	59.97	48.89	-4.98	54.99	43.91	74.00	54.00
	H	2483.5	58.61	45.68	-4.98	53.63	40.70	74.00	54.00
Data rate 3Mbps	V	2390.0	59.85	48.13	-5.79	54.06	42.34	74.00	54.00
	H	2390.0	59.61	48.72	-5.79	53.82	42.93	74.00	54.00
	V	2483.5	59.97	48.89	-4.98	54.99	43.91	74.00	54.00
	H	2483.5	58.61	45.68	-4.98	53.63	40.70	74.00	54.00

(1)	Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode.
(2)	During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
(3)	Corr.Factor = Antenna Factor + Cable Loss – Pre-amplifier.

5.4 BANDWIDTH TEST

5.4.1 Applied procedures / Limit

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.


5.4.2 Test procedure

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW, Sweep = auto, Detector function = peak
Trace = max hold

5.4.3 Deviation from standard

No deviation.

5.4.4 Test setup




5.4.5 Test results


EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	26 °C	Relative Humidity:	53%
Pressure:	1010 hPa	Test Power :	3.7Vdc from battery
Test Mode :	TX 1Mbps/ 2Mbps/ 3Mbps		

Channel		Channel frequency (MHz)	20dB bandwidth (KHz)	Limit (KHz)	Conclusion
1Mbps	Low	2402	1042	N/A	Pass
	Middle	2441	1041	N/A	Pass
	High	2480	1041	N/A	Pass
2Mbps	Low	2402	1356	N/A	Pass
	Middle	2441	1356	N/A	Pass
	High	2480	1356	N/A	Pass
3Mbps	Low	2402	1368	N/A	Pass
	Middle	2441	1368	N/A	Pass
	High	2480	1369	N/A	Pass

CH00-1Mbps




CH 39-1Mbps







CH 78-1Mbps




CH 00-2Mbps




CH 39-2Mbps




CH 78-2Mbps




CH 00-3Mbps



CH 39-3Mbps



CH 78-3Mbps



5.5 Carrier Frequencies Separated

5.5.1 Applied procedures / Limit

15.247(a) (1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.5.2 Test procedure

- (1) Connected the antenna port to the Spectrum Analyzer, set the Spectrum Analyzer as
Span = wide enough to capture the peaks of two adjacent channels, Resolution (or IF)
Bandwidth (RBW) \geq 1% of the span, Video (or Average) Bandwidth (VBW) \geq RBW
Sweep = auto, Detector function = peak, Trace = max hold
- (2) The EUT should be transmitting at its maximum data rate. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.
- (3) The above procedure shall be repeated at the lowest, the middle, and the highest frequency of the stated frequency range with modulated mode. also shall be performed at different modes of operation.

5.5.3 Deviation from standard

No deviation.

5.5.4 Test setup




5.5.5 Test results

EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	26 °C	Relative Humidity:	53%
Pressure:	1010 hPa	Test Power :	3.7Vdc from battery
Test Mode :	TX 1Mbps/ 2Mbps/ 3Mbps		

Channel		Channel frequency (MHz)	Channel Separation (KHz)	Conclusion
1Mbps	Low	2402	0.993	Pass
	Middle	2441	1.011	Pass
	Highest	2480	0.996	Pass
2Mbps	Low	2402	1.002	Pass
	Middle	2441	0.996	Pass
	Highest	2480	1.008	Pass
3Mbps	Low	2402	1.005	Pass
	Middle	2441	0.984	Pass
	Highest	2480	0.996	Pass

Ch. Separation >2/3(20dB bandwidth)

CH 00-1Mbps




CH 39-1Mbps





CH 78-1Mbps




CH 00-2Mbps




CH 39-2Mbps**CH 78-2Mbps**

CH 00-3Mbps



CH 39-3Mbps



CH 78-3Mbps



5.6 Hopping Channel Number

5.6.1 Applied procedures / Limit

15.247(a) (1) (iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.6.2 Test procedure

- (1) Connected the antenna port to the Spectrum Analyzer , set the Spectrum Analyzer as
Span = the frequency band of operation, $RBW \geq 1\%$ of the span, $VBW \geq RBW$ Sweep = auto
Detector function = peak, Trace = max hold
- (2) The EUT should be have its hopping function enabled. Maxhold and record hopping channels It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

5.6.3 Deviation from standard


No deviation.

5.6.4 Test setup



5.6.5 Test result

Hopping Channel Number result		
Operating Mode: Hopping Mode		Test date:2017-06-02
Result	Limit	Conclusion
79	15	Pass



5.7 Dwell time

5.7.1 Applied procedures / Limit

15.247(a) (1) (iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.7.2 Test procedure

- (1) Place the EUT on the table in the chamber or connect the antenna port of the EUT to spectrum analyzer and set it in transmitting mode.
- (2) Set RBW of spectrum analyzer to 1MHz, VBW \geq RBW
- (3) Use a video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for DH5, DH3 and DH1 packet transmitting.
- (8) Measure the maximum time duration of one single pulse.
- (9) A Period Time = $79 \times 0.4 = 31.6$ S
DH1 Time Slot: Reading * $(1600/2) \times 31.6/79$
DH3 Time Slot: Reading * $(1600/4) \times 31.6/79$
DH5 Time Slot: Reading * $(1600/6) \times 31.6/79$

5.7.3 Deviation from standard

No deviation.

5.7.4 Test setup




5.7.5 Test result


EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	26 °C	Relative Humidity:	53%
Pressure:	1010 hPa	Test Power :	3.7Vdc from battery
Test Mode :	CH00-DH1/DH3/DH5 (1Mbps Mode)		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2402 MHz	0.415	0.133	0.4000
DH3	2402 MHz	1.68	0.269	0.4000
DH5	2402 MHz	2.92	0.311	0.4000


CH 00- DH1



CH 00- DH3




CH 00- DH5




EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	26 °C	Relative Humidity:	53%
Pressure:	1010 hPa	Test Power :	3.7Vdc from battery
Test Mode :	CH00-2DH1/2DH3/2DH5 (2Mbps Mode)		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
2DH1	2402 MHz	0.384	0.123	0.4000
2DH3	2402 MHz	1.640	0.262	0.4000
2DH5	2402 MHz	2.900	0.309	0.4000


CH 00- 2DH1



CH 00- 2DH3




CH 00- 2DH5




EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	26 °C	Relative Humidity:	53%
Pressure:	1010 hPa	Test Power :	3.7Vdc from battery
Test Mode :	CH00-3DH1/3DH3/3DH5 (3Mbps Mode)		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
3DH1	2402 MHz	0.430	0.138	0.4000
3DH3	2402 MHz	1.700	0.272	0.4000
3DH5	2402 MHz	2.960	0.316	0.4000


CH 00- 3DH1



CH 00- 3DH3




CH 00- 3DH5




EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	26 °C	Relative Humidity:	53%
Pressure:	1010 hPa	Test Power :	3.7Vdc from battery
Test Mode :	CH39-DH1/DH3/DH5 (1Mbps Mode)		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2441 MHz	0.410	0.131	0.4000
DH3	2441 MHz	1.660	0.266	0.4000
DH5	2441 MHz	2.920	0.311	0.4000

CH 39- DH1



CH 39- DH3




CH 39- DH5




EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	26 °C	Relative Humidity:	53%
Pressure:	1010 hPa	Test Power :	3.7Vdc from battery
Test Mode :	CH39-2DH1/2DH3/2DH5 (2Mbps Mode)		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
2DH1	2441 MHz	0.382	0.122	0.4000
2DH3	2441 MHz	1.630	0.261	0.4000
2DH5	2441 MHz	2.900	0.309	0.4000


CH 39- 2DH1



CH 39- 2DH3



CH 39- 2DH5



Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
3DH1	2441 MHz	0.420	0.134	0.4000
3DH3	2441 MHz	1.660	0.266	0.4000
3DH5	2441 MHz	2.920	0.311	0.4000

Keysight Spectrum Analyzer - Swept SA

07:10:41 PM May 31, 2017

Marker 1 Δ 420.000 μ s

PNO: Fast $\rightarrow \rightarrow$ Trig: Free Run
IFGain: Low Atten: 20 dB

Avg Type: Log-Pwr

Ref Offset 1 dB
Ref 10.00 dBm

10 dB/div
Log

Δ Mkr1 420.0 μ s
-3.07 dB


Center 2.441000000 GHz
Res BW 1.0 MHz
#VBW 3.0 MHz

Span 0 Hz
Sweep 5.000 ms (1001 pts)


MSG Query INTERRUPTED

STATUS

CH 39- 3DH3




CH 39- 3DH5




EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	26 °C	Relative Humidity:	53%
Pressure:	1010 hPa	Test Power :	3.7Vdc from battery
Test Mode :	CH78-DH1/DH3/DH5 (1Mbps Mode)		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2480 MHz	0.410	0.131	0.4000
DH3	2480 MHz	1.680	0.269	0.4000
DH5	2480 MHz	3.000	0.320	0.4000


CH 78- DH1



CH 78- DH3




CH 78- DH5




EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	26 °C	Relative Humidity:	53%
Pressure:	1010 hPa	Test Power :	3.7Vdc from battery
Test Mode :	CH78-2DH1/2DH3/2DH5 (2Mbps Mode)		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
2DH1	2480 MHz	0.388	0.124	0.4000
2DH3	2480 MHz	1.630	0.261	0.4000
2DH5	2480 MHz	2.900	0.309	0.4000


CH 78- 2DH1



CH 78- 2DH3




CH 78- 2DH5




EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	26 °C	Relative Humidity:	53%
Pressure:	1010 hPa	Test Power :	3.7Vdc from battery
Test Mode :	CH78-3DH1/3DH3/3DH5 (3Mbps Mode)		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
3DH1	2480 MHz	0.400	0.128	0.4000
3DH3	2480 MHz	1.650	0.264	0.4000
3DH5	2480 MHz	2.900	0.309	0.4000


CH 78- 3DH1



CH 78- 3DH3



CH 78- 3DH5



5.8 Maximum Peak Output Power

5.8.1 Applied procedures / Limit

15.247(a) (1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

15.247(b) (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.


5.8.2 Test procedure

- (1) Connected the antenna port to the Spectrum Analyzer, set the Spectrum Analyzer as
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
RBW > the 20 dB bandwidth of the emission being measured, VBW \geq RBW, Sweep = auto
Detector function = peak, Trace = max hold
- (2) The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.
- (3) The above procedure shall be repeated at the lowest, the middle, and the highest frequency of the stated frequency range with modulated mode. Also shall be performed at different modes of operation.

5.8.3 Deviation from standard

No deviation.

5.8.4 Test setup




5.8.5 Test results


EUT:	TSUMTSUM Bluetooth speaker	Model Name :	276-883808
Temperature:	26 °C	Relative Humidity:	60%
Pressure:	1010 hPa	Test Voltage :	3.7Vdc from battery
Test Mode :	TX		
Note: All the data rates have be tested and the worst-case as the table below.			

Test Mode	Frequency	Peak Output Power (dBm)	Limit (dBm)	Result
Data rate 1Mbps	2402 MHz	1.429	21	Pass
	2441 MHz	3.266	21	Pass
	2480 MHz	4.446	21	Pass
Data rate 2Mbps	2402 MHz	3.917	21	Pass
	2441 MHz	3.754	21	Pass
	2480 MHz	4.626	21	Pass
Data rate 3Mbps	2402 MHz	4.039	21	Pass
	2441 MHz	4.414	21	Pass
	2480 MHz	5.048	21	Pass


CH 00-1Mbps




CH 39-1Mbps




CH 78-1Mbps




CH 00-2Mbps




CH 39-2Mbps




CH 78-2Mbps




CH 00-3Mbps



CH 39-3Mbps



CH 78-3Mbps



5.9 Band edge

5.9.1 Applied procedures / Limit

15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.9.2 Test procedure

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation, $RBW \geq 1\%$ of the span, $VBW \geq RBW$, Sweep = auto, Detector function = peak, Trace = max hold

5.9.3 Deviation from standard


No deviation.

5.9.4 Test setup




5.9.5 Test results


CH00 (Lower) Data rate 1Mbps




CH 78 (Upper) Data rate 1Mbps




CH00 (Lower) Data rate 2Mbps




CH 78 (Upper) Data rate 2Mbps







CH00 (Lower) Data rate 3Mbps





CH 78 (Upper) Data rate 3Mbps



CH00 (Lower) Data rate 1Mbps**CH 78 (Upper) Data rate 1Mbps**

CH00 (Lower) Data rate 2Mbps**CH 78 (Upper) Data rate 2Mbps**

CH00 (Lower) Data rate 3Mbps**CH 78 (Upper) Data rate 3Mbps**

5.10 Conducted Spurious Emissions

5.10.1 Applied procedures / Limit

15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.10.2 Test procedure

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span. RBW = 100 kHz
VBW \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold
sweep points \geq investigated frequency range/RBW.

5.10.3 Deviation from standard


No deviation.

5.10.4 Test setup




5.10.5 Test results


CH00 Data rate 1Mbps




CH00 Data rate 1Mbps




CH00 Data rate 1Mbps




CH39 Data rate 1Mbps




CH39 Data rate 1Mbps




CH39 Data rate 1Mbps





CH78 Data rate 1Mbps




CH78 Data rate 1Mbps




CH78 Data rate 1Mbps**CH00 Data rate 3Mbps**


CH00 Data rate 3Mbps




CH00 Data rate 3Mbps




CH39 Data rate 3Mbps




CH39 Data rate 3Mbps




CH39 Data rate 3Mbps




CH78 Data rate 3Mbps



CH78 Data rate 3Mbps




CH78 Data rate 3Mbps




6 Photographs

6.1 Radiated Spurious Emission Test Setup

Below 1GHz:




Above 1GHz:





6.2 Conducted Emission Test Setup






7 APPENDIX-Photographs of EUT Constructional Details







BT Antenna







END OF REPORT