

APPLICATION CERTIFICATION  
On Behalf of  
CLEVER BRIGHT INTERNATIONAL (H.K.) LTD

BLUETOOTH EXECUTIVE HEADSET  
Model No.: BTEH-24/6359, CB-BE014, SL Headset

FCC ID: 2AD42BTEH-24

Prepared for : CLEVER BRIGHT INTERNATIONAL (H.K.) LTD  
Address : Rm 1701, Zhuoyue Building, Fuhua Yi Rd., Futian  
Central Zone, Shenzhen, P.R. China.  
Prepared by : ACCURATE TECHNOLOGY CO. LTD  
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.  
Science & Industry Park, Nanshan, Shenzhen, Guangdong  
P.R. China

Tel: (0755) 26503290

Fax: (0755) 26503396

Report Number : ATE20150150  
Date of Test : Jan 19-27,2015  
Date of Report : Jan 28,2015

## TABLE OF CONTENTS

Description	Page
Test Report Certification	
<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1. Description of Device (EUT).....	5
1.2. Description of Test Facility .....	6
1.3. Measurement Uncertainty .....	6
<b>2. MEASURING DEVICE AND TEST EQUIPMENT .....</b>	<b>7</b>
<b>3. OPERATION OF EUT DURING TESTING .....</b>	<b>8</b>
3.1. Operating Mode .....	8
3.2. Configuration and peripherals .....	8
<b>4. TEST PROCEDURES AND RESULTS .....</b>	<b>9</b>
<b>5. 20DB BANDWIDTH TEST.....</b>	<b>10</b>
5.1. Block Diagram of Test Setup.....	10
5.2. The Requirement For Section 15.247(a)(1).....	10
5.3. EUT Configuration on Measurement .....	10
5.4. Operating Condition of EUT .....	10
5.5. Test Procedure .....	11
5.6. Test Result .....	11
<b>6. CARRIER FREQUENCY SEPARATION TEST.....</b>	<b>13</b>
6.1. Block Diagram of Test Setup.....	13
6.2. The Requirement For Section 15.247(a)(1).....	13
6.3. EUT Configuration on Measurement .....	13
6.4. Operating Condition of EUT .....	13
6.5. Test Procedure .....	14
6.6. Test Result .....	14
<b>7. NUMBER OF HOPPING FREQUENCY TEST .....</b>	<b>17</b>
7.1. Block Diagram of Test Setup.....	17
7.2. The Requirement For Section 15.247(a)(1)(iii).....	17
7.3. EUT Configuration on Measurement .....	17
7.4. Operating Condition of EUT .....	17
7.5. Test Procedure .....	18
7.6. Test Result .....	18
<b>8. DWELL TIME TEST .....</b>	<b>19</b>
8.1. Block Diagram of Test Setup.....	19
8.2. The Requirement For Section 15.247(a)(1)(iii).....	19
8.3. EUT Configuration on Measurement .....	19
8.4. Operating Condition of EUT .....	19
8.5. Test Procedure .....	20
8.6. Test Result .....	20
<b>9. MAXIMUM PEAK OUTPUT POWER TEST .....</b>	<b>26</b>
9.1. Block Diagram of Test Setup.....	26
9.2. The Requirement For Section 15.247(b)(1).....	26
9.3. EUT Configuration on Measurement .....	26

9.4.	Operating Condition of EUT .....	26
9.5.	Test Procedure .....	27
9.6.	Test Result .....	27
<b>10.</b>	<b>RADIATED EMISSION TEST .....</b>	<b>29</b>
10.1.	Block Diagram of Test Setup.....	29
10.2.	The Limit For Section 15.247(d) .....	29
10.3.	Restricted bands of operation .....	30
10.4.	Configuration of EUT on Measurement .....	30
10.5.	Test Procedure .....	31
10.6.	The Field Strength of Radiation Emission Measurement Results .....	32
<b>11.</b>	<b>BAND EDGE COMPLIANCE TEST .....</b>	<b>44</b>
11.1.	Block Diagram of Test Setup.....	44
11.2.	The Requirement For Section 15.247(d) .....	44
11.3.	EUT Configuration on Measurement .....	44
11.4.	Operating Condition of EUT .....	44
11.5.	Test Procedure .....	45
11.6.	Test Result .....	45
<b>12.</b>	<b>AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A) ..</b>	<b>53</b>
12.1.	Block Diagram of Test Setup.....	53
12.2.	The Emission Limit .....	53
12.3.	Configuration of EUT on Measurement .....	54
12.4.	Operating Condition of EUT .....	54
12.5.	Test Procedure .....	54
12.6.	Power Line Conducted Emission Measurement Results .....	54
<b>13.</b>	<b>ANTENNA REQUIREMENT.....</b>	<b>57</b>
13.1.	The Requirement .....	57
13.2.	Antenna Construction .....	57

## Test Report Certification

Applicant : CLEVER BRIGHT INTERNATIONAL (H.K.) LTD  
Manufacturer : CLEVER BRIGHT INTERNATIONAL (H.K.) LTD  
EUT Description : BLUETOOTH EXECUTIVE HEADSET  
(A) MODEL NO.: BTEH-24/6359, CB-BE014, SL Headset  
(B) POWER SUPPLY: DC 3.7V (Battery) or DC5V(USB)

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247  
ANSI C63.4- 2009


The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : Jan 19-27,2015

Date of Report : Jan 28,2015

Prepared by :

  
(Eric Zhang, Engineer)

Approved & Authorized Signer :

  
(Sean Liu, Manager)

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

EUT	:	BLUETOOTH EXECUTIVE HEADSET
Model Number	:	BTEH-24/6359, CB-BE014, SL Headset
		Note: These samples are same except for the model number and colors are difference. So we prepare the BTEH-24/6359 for test
Frequency Band	:	2402MHz-2480MHz
Number of Channels	:	79
Modulation type	:	GFSK
Antenna Gain	:	2.3dBi
Antenna type	:	PCB Antenna
Power Supply	:	DC 3.7V (Battery) or DC 5V(USB)
Applicant	:	CLEVER BRIGHT INTERNATIONAL (H.K.) LTD
Address	:	Rm 1701, Zhuoyue Building, Fuhua Yi Rd., Futian Central Zone, Shenzhen, P.R. China.
Manufacturer	:	CLEVER BRIGHT INTERNATIONAL (H.K.) LTD
Address	:	Rm 1701, Zhuoyue Building, Fuhua Yi Rd., Futian Central Zone, Shenzhen, P.R. China.
Date of sample received	:	Jan 19, 2015
Date of Test	:	Jan 19-27,2015

## 1.2. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC

The Registration Number is 752051

Listed by Industry Canada

The Registration Number is 5077A-2

Accredited by China National Accreditation Committee  
for Laboratories

The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO. LTD

Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.  
Science & Industry Park, Nanshan, Shenzhen, Guangdong  
P.R. China

## 1.3. Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2  
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2  
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2  
(Above 1GHz)

## 2. MEASURING DEVICE AND TEST EQUIPMENT

**Table 1: List of Test and Measurement Equipment**

Kind of equipment	Manufacturer	Type	S/N	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan.10, 2015	1 Year
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan.10, 2015	1 Year
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan.10, 2015	1 Year
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan.10, 2015	1 Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan.15, 2015	1 Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan.15, 2015	1 Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan.15, 2015	1 Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan.15, 2015	1 Year
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan.10, 2015	1 Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan.10, 2015	1 Year

### 3. OPERATION OF EUT DURING TESTING

#### 3.1.Operating Mode

The mode is used: Transmitting mode

Low Channel: 2402MHz

Middle Channel: 2441MHz

High Channel: 2480MHz

Hopping

#### 3.2.Configuration and peripherals

EUT

(EUT: BLUETOOTH EXECUTIVE HEADSET)




#### 4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission Test	Compliant
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d) Section 15.209	Radiated Emission Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.203	Antenna Requirement	Compliant

## **5. 20DB BANDWIDTH TEST**

### **5.1. Block Diagram of Test Setup**



(EUT: BLUETOOTH EXECUTIVE HEADSET)

### **5.2. The Requirement For Section 15.247(a)(1)**

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

### **5.3. EUT Configuration on Measurement**

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### **5.4. Operating Condition of EUT**

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

## 5.5. Test Procedure

5.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.


5.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz.

5.5.3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


## 5.6. Test Result

Channel	Frequency (MHz)	GFSK 20dB Bandwidth (MHz)	Result
Low	2402	0.808	Pass
Middle	2441	0.808	Pass
High	2480	0.844	Pass


The spectrum analyzer plots are attached as below.



## Middle channel




## High channel



## 6. CARRIER FREQUENCY SEPARATION TEST

### 6.1. Block Diagram of Test Setup



(EUT: BLUETOOTH EXECUTIVE HEADSET)

### 6.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### 6.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

## 6.5. Test Procedure

6.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz. Adjust Span to 3 MHz.

6.5.3. Set the adjacent channel of the EUT maxhold another trace.


6.5.4. Measurement the channel separation

## 6.6. Test Result


Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.000	25KHz or 20dB bandwidth	PASS
	2403			
Middle	2440	1.000	25KHz or 20dB bandwidth	PASS
	2441			
High	2479	1.000	25KHz or 20dB bandwidth	PASS
	2480			

The spectrum analyzer plots are attached as below.


## Low channel



## Middle channel




High channel





## **7. NUMBER OF HOPPING FREQUENCY TEST**

### **7.1. Block Diagram of Test Setup**



(EUT: BLUETOOTH EXECUTIVE HEADSET)

### **7.2. The Requirement For Section 15.247(a)(1)(iii)**

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### **7.3. EUT Configuration on Measurement**

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### **7.4. Operating Condition of EUT**

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX (Hopping on) modes measure it.

## 7.5. Test Procedure


- 7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.
- 7.5.2. Set the spectrum analyzer as Span=83.5MHz, RBW=100 kHz, VBW=300 kHz.
- 7.5.3. Max hold, view and count how many channel in the band.

## 7.6. Test Result

Total number of hopping channel	Measurement result(CH)	Limit(CH)
	79	$\geq 15$


The spectrum analyzer plots are attached as below.

Number of hopping channels



## 8. DWELL TIME TEST

### 8.1. Block Diagram of Test Setup



(EUT: BLUETOOTH EXECUTIVE HEADSET)

### 8.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 8.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

## 8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Set center frequency of spectrum analyzer = operating frequency.

8.5.3. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz.


8.5.4. Repeat above procedures until all frequency measured were complete.

## 8.6. Test Result


Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.460	147.20	400
	2441	0.460	147.20	400
	2480	0.460	147.20	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2 \times 79)) \times 31.6$				
DH3	2402	1.740	278.40	400
	2441	1.740	278.40	400
	2480	1.740	278.40	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4 \times 79)) \times 31.6$				
DH5	2402	3.000	320.00	400
	2441	3.000	320.00	400
	2480	3.000	320.00	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6 \times 79)) \times 31.6$				

The spectrum analyzer plots are attached as below.


## DH1 Low channel




## DH1 Middle channel




## DH1 High channel




## DH3 Low channel




## DH3 Middle channel




## DH3 High channel



## DH5 Low channel




## DH5 Middle channel






### DH5 High channel



## 9. MAXIMUM PEAK OUTPUT POWER TEST

### 9.1. Block Diagram of Test Setup



(EUT: BLUETOOTH EXECUTIVE HEADSET)

### 9.2. The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 9.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

## 9.5. Test Procedure

9.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz for GFSK mode


9.5.3. Set RBW of spectrum analyzer to 3MHz and VBW to 3MHz for other mode

9.5.4. Measurement the maximum peak output power.


## 9.6. Test Result

Channel	Frequency (MHz)	Peak Output Power(dBm)	Peak Output Power(mW)	Limits dBm / W
Low	2402	-2.24	0.60	30/1.0
Middle	2441	-1.59	0.69	30/1.0
High	2480	-1.66	0.68	30/1.0


The spectrum analyzer plots are attached as below.



### Middle channel



### High channel



## 10. RADIATED EMISSION TEST


### 10.1. Block Diagram of Test Setup

#### 10.1.1. Block diagram of connection between the EUT and simulators



(EUT: BLUETOOTH EXECUTIVE HEADSET)

#### 10.1.2. Anechoic Chamber Test Setup Diagram



(EUT: BLUETOOTH EXECUTIVE HEADSET)

### 10.2. The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also

comply with the radiated emission limits specified in Section 15.209(a).

### 10.3.Restricted bands of operation

#### 10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

<sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510

<sup>2</sup>Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

### 10.4.Configuration of EUT on Measurement

The equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 10.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4- 2009 on radiated emission measurement.

The final measurement in band 9-90 kHz, 110-490 kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

RBW (120 kHz), VBW (300 kHz) for QP detector below 1GHz

Peak detector above 1GHz

RBW (1 MHz), VBW (3MHz) for Peak measurement

RBW (1 MHz), VBW (10Hz) for AV measurement

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

## 10.6.The Field Strength of Radiation Emission Measurement Results

- Note: 1.** The fundamental radiated emissions were reduced by 2.4G Band Reject Filter in the attached plots.  
**2.** The 18-25GHz emissions are not reported, because the levels are too low against the limit.



### ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star2015 #102

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2402MHz

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/23/

Time: 8/54/18

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	322.5896	47.59	-17.28	30.31	46.00	-15.69	QP			
2	384.5446	45.60	-15.77	29.83	46.00	-16.17	QP			
3	787.4749	44.35	-7.97	36.38	46.00	-9.62	QP			



Job No.: star2015 #103

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2402MHz

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/23/

Time: 8/58/17

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	322.5896	46.12	-17.28	28.84	46.00	-17.16	QP			
2	392.7376	46.70	-15.69	31.01	46.00	-14.99	QP			
3	847.7763	39.65	-7.00	32.65	46.00	-13.35	QP			



## ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star2015 #104

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2441MHz

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/23/

Time: 9/02/42

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	327.1553	48.60	-17.11	31.49	46.00	-14.51	QP			
2	394.1198	47.64	-15.69	31.95	46.00	-14.05	QP			
3	850.7603	40.11	-6.95	33.16	46.00	-12.84	QP			

Job No.: star2015 #105

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2441MHz

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/23/

Time: 9/06/21

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	321.4581	47.64	-17.33	30.31	46.00	-15.69	QP			
2	384.5447	43.31	-15.77	27.54	46.00	-18.46	QP			
3	787.4749	40.22	-7.97	32.25	46.00	-13.75	QP			

Job No.: star2015 #106

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2480MHz

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/23/

Time: 9/10/13

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	321.4581	45.81	-17.33	28.48	46.00	-17.52	QP			
2	392.7376	47.63	-15.69	31.94	46.00	-14.06	QP			
3	784.7129	40.29	-8.02	32.27	46.00	-13.73	QP			

Job No.: star2015 #107

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2480MHz

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/23/

Time: 9/14/06

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	335.3016	43.82	-16.73	27.09	46.00	-18.91	QP			
2	392.7376	42.64	-15.69	26.95	46.00	-19.05	QP			
3	827.1795	39.70	-7.33	32.37	46.00	-13.63	QP			

Job No.: star2014 #406

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2402MHz

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/23/

Time: 14/14/53

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	9613.430	40.92	4.92	45.84	54.00	-8.16	peak			
2	9613.430	34.77	4.92	39.69	54.00	-14.31	AVG			





## ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber  
Tel:+86-0755-26503290  
Fax:+86-0755-26503396

Job No.: star2014 #407  
Standard: FCC Class B 3M Radiated  
Test item: Radiation Test  
Temp.( C)/Hum.(%) 25 C / 55 %  
EUT: BLUETOOTH EXECUTIVE HEADSET  
Mode: TX 2402MHz  
Model: BTEH-24/6359  
Manufacturer: CLEVER BRIGHT

Polarization: Vertical  
Power Source: DC 5V  
Date: 15/01/23/  
Time: 14/18/25  
Engineer Signature: STAR  
Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	9923.991	41.23	5.24	46.47	54.00	-7.53	peak			
2	9923.991	36.39	5.24	41.63	54.00	-12.37	AVG			

Job No.: star2014 #408

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2441MHz

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/23/

Time: 14/22/22

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	11204.896	40.91	5.72	46.63	54.00	-7.37	peak			
2	11204.896	35.73	5.72	41.45	54.00	-12.55	AVG			



Job No.: star2014 #409

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2441MHz

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/23/

Time: 14/26/30

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	14450.131	34.56	12.73	47.29	54.00	-6.71	peak			
2	14450.131	29.43	12.73	42.16	54.00	-11.84	AVG			

Job No.: star2014 #410

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2480MHz

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/23/

Time: 14/30/19

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	10545.012	40.83	5.22	46.05	54.00	-7.95	peak			
2	10545.012	34.82	5.22	40.04	54.00	-13.96	AVG			

Job No.: star2014 #411

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2480MHz

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/23/

Time: 14/34/18

Engineer Signature: STAR

Distance: 3m


Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	10363.715	41.59	5.24	46.83	54.00	-7.17	peak			
2	10363.715	35.10	5.24	40.34	54.00	-13.66	AVG			

## 11.BAND EDGE COMPLIANCE TEST

### 11.1.Block Diagram of Test Setup



(EUT: BLUETOOTH EXECUTIVE HEADSET)

### 11.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

### 11.3.EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 11.4.Operating Condition of EUT

11.4.1.Setup the EUT and simulator as shown as Section 11.1.

11.4.2.Turn on the power of all equipment.

11.4.3.Let the EUT work in TX (Hopping off, Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

### 11.5. Test Procedure

11.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.


11.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz with convenient frequency span including 100 kHz bandwidth from band edge.

11.5.3. The band edges were measured and recorded.


### 11.6. Test Result

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
GFSK		
2400	54.53	> 20dBc
2483.5	56.07	> 20dBc

## Low channel



## High channel





## Radiated Band Edge Result

- Note:1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
- $$\text{Result} = \text{Reading} + \text{Corrected Factor}$$
3. Display the measurement of peak values.

### Non-hopping mode



## ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR #3971

Standard: FCC PK

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2402MHz(GFSK)

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/24/

Time: 9/22/49

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	42.59	-6.78	35.81	74.00	-38.19	peak			
2	2390.000	33.56	-6.78	26.78	54.00	-27.22	AVG			
3	2400.000	58.30	-6.76	51.54	74.00	-22.46	peak			
4	2400.000	49.78	-6.76	43.02	54.00	-10.98	AVG			

Job No.: STAR #3970

Standard: FCC PK

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2402MHz(GFSK)

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/24/

Time: 9/18/16

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	46.87	-6.78	40.09	74.00	-33.91	peak			
2	2390.000	36.79	-6.78	30.01	54.00	-23.99	AVG			
3	2400.000	65.28	-6.76	58.52	74.00	-15.48	peak			
4	2400.000	55.17	-6.76	48.41	54.00	-5.59	AVG			



Job No.: STAR #3964

Standard: FCC PK

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2480MHz(GFSK)

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/24/

Time: 8/55/04

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	55.79	-6.54	49.25	74.00	-24.75	peak			
2	2483.500	46.15	-6.54	39.61	54.00	-14.39	AVG			
3	2500.000	42.79	-6.50	36.29	74.00	-37.71	peak			
4	2500.000	33.56	-6.50	27.06	54.00	-26.94	AVG			

Job No.: STAR #3965

Standard: FCC PK

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: TX 2480MHz(GFSK)

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/24/

Time: 8/58/34

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	55.52	-6.54	48.98	74.00	-25.02	peak			
2	2483.500	46.78	-6.54	40.24	54.00	-13.76	AVG			
3	2500.000	43.12	-6.50	36.62	74.00	-37.38	peak			
4	2500.000	34.83	-6.50	28.33	54.00	-25.67	AVG			

## Hopping mode



### ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR #3977

Standard: FCC PK

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: BLUETOOTH EXECUTIVE HEADSET

Mode: HOPPING (GFSK)

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/24/

Time: 9/42/41

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	47.25	-6.78	40.47	74.00	-33.53	peak			
2	2390.000	41.92	-6.78	35.14	54.00	-18.86	AVG			
3	2400.000	62.93	-6.76	56.17	74.00	-17.83	peak			
4	2400.000	53.26	-6.76	46.50	54.00	-7.50	AVG			
5	2483.500	62.88	-6.54	56.34	74.00	-17.66	peak			
6	2483.500	54.71	-6.54	48.17	54.00	-5.83	AVG			
7	2500.000	50.35	-6.50	43.85	74.00	-30.15	peak			
8	2500.000	40.21	-6.50	33.71	54.00	-20.29	AVG			

Job No.: STAR #3978

Standard: FCC PK

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 55 %

EUT: Mono Bluetooth Headset

Mode: HOPPING (QPSK)

Model: BTEH-24/6359

Manufacturer: CLEVER BRIGHT

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/24/

Time: 9/46/40

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	48.39	-6.78	41.61	74.00	-32.39	peak			
2	2390.000	39.99	-6.78	33.21	54.00	-20.79	AVG			
3	2400.000	62.85	-6.76	56.09	74.00	-17.91	peak			
4	2400.000	53.60	-6.76	46.84	54.00	-7.16	AVG			
5	2483.500	64.73	-6.54	58.19	74.00	-15.81	peak			
6	2483.500	54.91	-6.54	48.37	54.00	-5.63	AVG			
7	2500.000	50.12	-6.50	43.62	74.00	-30.38	peak			
8	2500.000	42.11	-6.50	35.61	54.00	-18.39	AVG			


## 12.AC POWER LINE CONDUCTED EMISSION FOR FCC PART

### 15 SECTION 15.207(A)

#### 12.1.Block Diagram of Test Setup

12.1.1.Block diagram of connection between the EUT and simulators

12.1.2.Shielding Room Test Setup Diagram



(EUT: BLUETOOTH EXECUTIVE HEADSET)

#### 12.2.The Emission Limit

12.2.1.Conducted Emission Measurement Limits According to Section 15.207(a)

Frequency (MHz)	Limit dB( $\mu$ V)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0

\* Decreases with the logarithm of the frequency.

### 12.3.Configuration of EUT on Measurement

The equipment are installed on the Conducted Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 12.4.Operating Condition of EUT

12.4.1.Setup the EUT and simulator as shown as Section 11.1.

12.4.2.Turn on the power of all equipment.

12.4.3.Let the EUT work in TX (Operation) mode measure it.

### 12.5.Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4- 2009 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9 kHz.

The frequency range from 150 kHz to 30MHz is checked.

### 12.6.Power Line Conducted Emission Measurement Results

ACCURATE TECHNOLOGY CO., LTD


## CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: BLUETOOTH EXECUTIVE HEADSET M/N:BTEH-24/6359  
 Manufacturer: CLEVER BRIGHT  
 Operating Condition: ON  
 Test Site: 2#Shielding Room  
 Operator: star  
 Test Specification: L 120V/60Hz  
 Comment: Report No.:ATE20150150  
 Start of Test: 2015-1-23 / 10:26:17

### SCAN TABLE: "V 150K-30MHz fin"

Short Description: \_SUB\_STD\_VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	30.0 MHz	4.5 kHz	QuasiPeak	1.0 s	9 kHz	LISN(ESH3-Z5)
Average						



### MEASUREMENT RESULT: "023013\_fin"

2015-1-23 10:26

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.152000	55.80	10.4	66	10.1	QP	L1	GND
0.204000	50.00	10.6	63	13.4	QP	L1	GND
2.868500	39.50	11.7	56	16.5	QP	L1	GND

### MEASUREMENT RESULT: "023013\_fin2"

2015-1-23 10:26

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.154000	42.30	10.4	56	13.5	AV	L1	GND
0.204000	36.20	10.6	53	17.2	AV	L1	GND
2.877500	31.60	11.7	46	14.4	AV	L1	GND




## ACCURATE TECHNOLOGY CO.,LTD

### CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: BLUETOOTH EXECUTIVE HEADSET M/N:BTEH-24/6359  
 Manufacturer: CLEVER BRIGHT  
 Operating Condition: ON  
 Test Site: 2#Shielding Room  
 Operator: star  
 Test Specification: N 120V/60Hz  
 Comment: Report No.:ATE20150150  
 Start of Test: 2015-1-23 / 10:27:26

#### SCAN TABLE: "V 150K-30MHZ fin"

Short Description: \_SUB\_STD\_VTERM2 1.70  
 Start Stop Step Detector Meas. IF Transducer  
 Frequency Frequency Width Time Bandw.  
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz LISN(ESH3-Z5)  
 Average



#### MEASUREMENT RESULT: "023014\_fin"

2015-1-23 10:29

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.158000	55.90	10.4	66	9.7	QP	N	GND
0.210000	49.60	10.7	63	13.6	QP	N	GND
2.976500	40.70	11.7	56	15.3	QP	N	GND

#### MEASUREMENT RESULT: "023014\_fin2"

2015-1-23 10:29

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.162000	42.70	10.4	55	12.7	AV	N	GND
0.210000	38.50	10.7	53	14.7	AV	N	GND
3.012500	32.00	11.7	46	14.0	AV	N	GND




## 13.ANTENNA REQUIREMENT

### 13.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 13.2.Antenna Construction

The antenna is a permanent attached antenna, no consideration of replacement. The gain is 2.3dBi. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna